

## Other decompositions of $\mathbf{X}$

### Eigen decomposition of covariance matrix of $\mathbf{X}$

There is another matrix factorization method known as Eigen Decomposition.

Eigen decomposition, unlike SVD, only works on symmetric matrices  $M$ :

$$M = W\Lambda W^T$$

where  $WW^T = I$

We can obtain the PCA from the Eigen Decomposition of  $\mathbf{X}\mathbf{X}^T$

- the covariance matrix of  $\mathbf{X}$  (i.e., original feature covariance)
- the covariance matrix is symmetric, as required

We can relate the SVD of  $\mathbf{X}$  to the Eigen decomposition of  $\mathbf{X}\mathbf{X}^T$  as follows:

$$\begin{aligned}\mathbf{X}^T \mathbf{X} &= \mathbf{V} \Sigma \mathbf{U}^T \mathbf{U} \Sigma \mathbf{V}^T && \text{from SVD } \mathbf{X} = \mathbf{U} \Sigma \mathbf{V}^T \\ \mathbf{X}^T \mathbf{X} &= \mathbf{V} \Sigma \Sigma^T \mathbf{V}^T && \text{since } \mathbf{U}^T \mathbf{U} = \mathbf{I}\end{aligned}$$

Similarly, we can show

$$\mathbf{X}\mathbf{X}^T = \mathbf{U} \Sigma \Sigma^T \mathbf{U}^T \text{ since } \mathbf{V} \mathbf{V}^T = \mathbf{I}$$

Setting

- $\Lambda = \Sigma \Sigma^T$
- $\mathbf{W} = \mathbf{U} = \mathbf{V}$  we get  $\mathbf{X} = \mathbf{W} \Lambda \mathbf{W}^T$ , the Eigen Decomposition of  $\mathbf{X}\mathbf{X}^T$ .

The  $V$  that transforms  $\mathbf{X}$  (original features) to  $\tilde{\mathbf{X}} = \mathbf{X}V$  (synthetic features)

- Can be computed directly from SVD
- Or by creating covariance matrix  $\mathbf{X}\mathbf{X}^T$  and using Eigen decomposition.

SVD is more commonly used

- There are many fast implementations of SVD
- There is no need to compute the big covariance matrix  $\mathbf{X}\mathbf{X}^T$

## Other factorization methods

- CUR method

$$\text{CUR}(\mathbf{X}) = \mathbf{C} \cdot \mathbf{U} \cdot \mathbf{R}$$

- $\mathbf{C}$  chosen from Columns of  $\mathbf{X}$
- $\mathbf{R}$  chosen from Rows of  $\mathbf{X}$

In [4]: `print("Done")`

Done