

Quiz Submissions - Data Abstraction Homework Quiz

Chork Hieng (username: gt9182iu)

Attempt 1

Written: Feb 12, 2022 2:26 PM - Feb 12, 2022 2:40 PM


[Submission View](#)

Your quiz has been submitted successfully.

Question 1

0 / 1 point

What are the instance variables in the **TimeOfDay** class? List them in the order in which they appear in the class, separated by spaces.

Answer: hour munite second  (**hour minute second**)

Question 2

1 / 1 point

What are the instance variables in the **StudentScores** class? List them in the order in which they appear in the class, separated by spaces. Remember that Java is case sensitive!

Answer: firstName lastName quizScores

Question 3

1 / 1 point

What is the name of the only private function in **TimeOfDay**?

Answer: fix

Question 4

0 / 1 point

How many constructors does **TimeOfDay** have?

Answer: 2  (**4**)

Question 5

0 / 1 point


How many constructors does **StudentScores** have?

Answer: 2  (**1**)

Question 6

0 / 1 point

The **Point2d** class has a **main()** that serves as a test client. When **Point2d** is run as a program, what is the output?

 ☐ 100 (42.00,1.00)

☐ 100 (1.00,1.00)

➡ ☐ 1 (42.00,1.00)

☐ 1 (1.00,1.00)

Question 7

1 / 1 point

What do we call the first constructor in the **Point2d** class?

- ☐ The default constructor.
- ☐ The empty constructor.
- ☐ The normal constructor.

Question 8

1 / 1 point

Which of these is an example of encapsulation?

- ☐ The instance data in a Java class is marked as private.
- ☐ If not constructor is provided by the class, Java will provide a default constructor that initializes all the instance variables to a known value.
- ☐ A Java class combines data with the methods that operate on it.

Question 9

1 / 1 point

Which of these is an example of data hiding?

- ☐ A Java class combines data with the methods that operate on it.
- ☐ The instance data in a Java class is marked as private.
- ☐ If not constructor is provided by the class, Java will provide a default constructor that initializes all the instance variables to a known value.

Question 10

6 / 7 points

For each statement, select whether it is true of reference types or primitive types.

✗ 1 (2) Represents a type that is directly supported by most CPUs. 1. reference types

2. primitive types

- 1 **String** is an example.
- 1 Can be a user-defined type.
- 2 **int** is an example.
- 1 Requires the use of **.equals()** for comparisons.
- 2 Can be meaningfully compared using the **==** operator.
- 1 Must be allocated using the **new** keyword.

Question 11

1 / 1 point


TimeOfDay, **StudentScores**, and **Point2d** are all ADTs.

- ☐ True
- ☐ False

Question 12

0 / 1 point

The **fix()** method is part of the API for **TimeOfDay**.

-  ☐ True
-  ☐ False

Question 13

1 / 1 point


The **getQuizAverage()** method is part of the API for **StudentScores**.


- ☐ True
- ☐ False

Question 14

0 / 1 point

StudentScores has a constructor with a parameter called **numQuizScores**. Why is that not stored as an instance variable?

-  ☐ It is the same as **quizScores.length**.
- ☐ It is never used in the constructor.

 ☐ It is an **int**, and instance variables cannot be **ints**.