

6

Displaying Data from Multiple Tables

ORACLE

Copyright © 2007, Oracle. All rights reserved.

Objectives

After completing this lesson, you should be able to do the following:

- Write `SELECT` statements to access data from more than one table using equijoins and nonequijoins
- Join a table to itself by using a self-join
- View data that generally does not meet a join condition by using outer joins
- Generate a Cartesian product of all rows from two or more tables

ORACLE

6 - 2

Copyright © 2007, Oracle. All rights reserved.

Objectives

This lesson explains how to obtain data from more than one table. A *join* is used to view information from multiple tables. Therefore, you can *join* tables together to view information from more than one table.

Note: Information on joins is found in the section on *SQL Queries and Subqueries: Joins* in *Oracle Database SQL Language Reference 11g, Release 1 (11.1)*.

Lesson Agenda

- **Types of JOINS and its syntax**
- **Natural join:**
 - USING clause
 - ON clause
- **Self-join**
- **Nonequijoins**
- **OUTER join:**
 - LEFT OUTER join
 - RIGHT OUTER join
 - FULL OUTER join
- **Cartesian product**
 - Cross join

ORACLE

Obtaining Data from Multiple Tables

EMPLOYEES

	EMPLOYEE_ID	LAST_NAME	DEPARTMENT_ID
1	100	King	90
2	101	Kochhar	90
3	102	De Haan	90
...			
18	202	Fay	20
19	205	Higgins	110
20	206	Gietz	110

DEPARTMENTS

	DEPARTMENT_ID	DEPARTMENT_NAME	LOCATION_ID
1	10	Administration	1700
2	20	Marketing	1800
3	50	Shipping	1500
4	60	IT	1400
5	80	Sales	2500
6	90	Executive	1700
7	110	Accounting	1700
8	190	Contracting	1700

	EMPLOYEE_ID	DEPARTMENT_ID	DEPARTMENT_NAME
1	200	10	Administration
2	201	20	Marketing
3	202	20	Marketing
4	124	50	Shipping
5	144	50	Shipping
...			
18	205	110	Accounting
19	206	110	Accounting

ORACLE

Obtaining Data from Multiple Tables

Sometimes you need to use data from more than one table. In the example in the slide, the report displays data from two separate tables:

- Employee IDs exist in the EMPLOYEES table.
- Department IDs exist in both the EMPLOYEES and DEPARTMENTS tables.
- Department names exist in the DEPARTMENTS table.

To produce the report, you need to link the EMPLOYEES and DEPARTMENTS tables, and access data from both of them.

Types of Joins

Joins that are compliant with the SQL:1999 standard include the following:

- Natural joins:
 - NATURAL JOIN clause
 - USING clause
 - ON clause
- Outer joins:
 - LEFT OUTER JOIN
 - RIGHT OUTER JOIN
 - FULL OUTER JOIN
- Cross joins

ORACLE

6 - 5

Copyright © 2007, Oracle. All rights reserved.

Types of Joins

To join tables, you can use a join syntax that is compliant with the SQL:1999 standard.

Note: Before the Oracle9i release, the join syntax was different from the American National Standards Institute (ANSI) standards. The SQL:1999-compliant join syntax does not offer any performance benefits over the Oracle-proprietary join syntax that existed in the prior releases. For detailed information about the proprietary join syntax, see Appendix C: Oracle Join Syntax.

Note: The following slide discusses the SQL:1999 join syntax.

Joining Tables Using SQL:1999 Syntax

Use a join to query data from more than one table:

```
SELECT  table1.column, table2.column
FROM    table1
[NATURAL JOIN table2] |
[JOIN table2 USING (column_name)] |
[JOIN table2
  ON (table1.column_name = table2.column_name)] |
[LEFT|RIGHT|FULL OUTER JOIN table2
  ON (table1.column_name = table2.column_name)] |
[CROSS JOIN table2];
```

Joining Tables Using SQL:1999 Syntax

In the syntax:

table1.column denotes the table and the column from which data is retrieved

NATURAL JOIN joins two tables based on the same column name

JOIN *table2* USING *column_name* performs an equijoin based on the column name

JOIN *table2* ON *table1.column_name* = *table2.column_name* performs an equijoin based on the condition in the ON clause

LEFT/RIGHT/FULL OUTER is used to perform outer joins

CROSS JOIN returns a Cartesian product from the two tables

For more information, see the section titled *SELECT* in *Oracle Database SQL Language Reference 11g, Release 1 (11.1)*.

Qualifying Ambiguous Column Names

- Use table prefixes to qualify column names that are in multiple tables.
- Use table prefixes to improve performance.
- Instead of full table name prefixes, use table aliases.
- Table alias gives a table a shorter name:
 - Keeps SQL code smaller, uses less memory
- Use column aliases to distinguish columns that have identical names, but reside in different tables.

ORACLE

6 - 7

Copyright © 2007, Oracle. All rights reserved.

Qualifying Ambiguous Column Names

When joining two or more tables, you need to qualify the names of the columns with the table name to avoid ambiguity. Without the table prefixes, the `DEPARTMENT_ID` column in the `SELECT` list could be from either the `DEPARTMENTS` table or the `EMPLOYEES` table. It is necessary to add the table prefix to execute your query. If there are no common column names between the two tables, there is no need to qualify the columns. However, using the table prefix improves performance, because you tell the Oracle server exactly where to find the columns.

However, qualifying column names with table names can be time consuming, particularly if the table names are lengthy. Instead, you can use *table aliases*. Just as a column alias gives a column another name, a table alias gives a table another name. Table aliases help to keep SQL code smaller, therefore using less memory.

The table name is specified in full, followed by a space and then the table alias. For example, the `EMPLOYEES` table can be given an alias of `e`, and the `DEPARTMENTS` table an alias of `d`.

Guidelines

- Table aliases can be up to 30 characters in length, but shorter aliases are better than longer ones.
- If a table alias is used for a particular table name in the `FROM` clause, then that table alias must be substituted for the table name throughout the `SELECT` statement.
- Table aliases should be meaningful.
- The table alias is valid for only the current `SELECT` statement.

Lesson Agenda

- Types of JOINS and its syntax
- Natural join:
 - USING clause
 - ON clause
- Self-join
- Nonequijoins
- OUTER join:
 - LEFT OUTER join
 - RIGHT OUTER join
 - FULL OUTER join
- Cartesian product
 - Cross join

ORACLE

Creating Natural Joins

- The `NATURAL JOIN` clause is based on all columns in the two tables that have the same name.
- It selects rows from the two tables that have equal values in all matched columns.
- If the columns having the same names have different data types, an error is returned.

ORACLE

6 - 9

Copyright © 2007, Oracle. All rights reserved.

Creating Natural Joins

You can join tables automatically based on the columns in the two tables that have matching data types and names. You do this by using the `NATURAL JOIN` keywords.

Note: The join can happen on only those columns that have the same names and data types in both tables. If the columns have the same name but different data types, then the `NATURAL JOIN` syntax causes an error.

Retrieving Records with Natural Joins

```
SELECT department_id, department_name,  
       location_id, city  
FROM   departments  
NATURAL JOIN locations ;
```

	DEPARTMENT_ID	DEPARTMENT_NAME	LOCATION_ID	CITY
1	60	IT	1400	Southlake
2	50	Shipping	1500	South San Francisco
3	10	Administration	1700	Seattle
4	90	Executive	1700	Seattle
5	110	Accounting	1700	Seattle
6	190	Contracting	1700	Seattle
7	20	Marketing	1800	Toronto
8	80	Sales	2500	Oxford

ORACLE

6 - 10

Copyright © 2007, Oracle. All rights reserved.

Retrieving Records with Natural Joins

In the example in the slide, the `LOCATIONS` table is joined to the `DEPARTMENT` table by the `LOCATION_ID` column, which is the only column of the same name in both tables. If other common columns were present, the join would have used them all.

Natural Joins with a `WHERE` Clause

Additional restrictions on a natural join are implemented by using a `WHERE` clause. The following example limits the rows of output to those with a department ID equal to 20 or 50:

```
SELECT department_id, department_name,  
       location_id, city  
FROM   departments  
NATURAL JOIN locations  
WHERE  department_id IN (20, 50);
```

Creating Joins with the USING Clause

- If several columns have the same names but the data types do not match, natural join can be applied using the `USING` clause to specify the columns that should be used for an equijoin.
- Use the `USING` clause to match only one column when more than one column matches.
- The `NATURAL JOIN` and `USING` clauses are mutually exclusive.

ORACLE

Creating Joins with the USING Clause

Natural joins use all columns with matching names and data types to join the tables. The `USING` clause can be used to specify only those columns that should be used for an equijoin.

Joining Column Names

EMPLOYEES

EMPLOYEE_ID	DEPARTMENT_ID
100	90
101	90
102	90
103	60
104	60
107	60
124	50
141	50
142	50
143	50
144	50
149	80
174	80
176	80

...

DEPARTMENTS

DEPARTMENT_ID	DEPARTMENT_NAME
1	10 Administration
2	20 Marketing
3	50 Shipping
4	60 IT
5	80 Sales
6	90 Executive
7	110 Accounting
8	190 Contracting

Primary key

Foreign key

Joining Column Names

To determine an employee's department name, you compare the value in the `DEPARTMENT_ID` column in the `EMPLOYEES` table with the `DEPARTMENT_ID` values in the `DEPARTMENTS` table. The relationship between the `EMPLOYEES` and `DEPARTMENTS` tables is an *equijoin*; that is, values in the `DEPARTMENT_ID` column in both the tables must be equal. Frequently, this type of join involves primary and foreign key complements.

Note: Equijoins are also called *simple joins* or *inner joins*.

Retrieving Records with the USING Clause

```
SELECT employee_id, last_name,  
       location_id, department_id  
FROM   employees JOIN departments  
       USING (department_id) ;
```

	EMPLOYEE_ID	LAST_NAME	LOCATION_ID	DEPARTMENT_ID
1	200	Whalen	1700	10
2	201	Hartstein	1800	20
3	202	Fay	1800	20
4	124	Mourgos	1500	50
5	144	Vargas	1500	50
6	143	Matos	1500	50
7	142	Davies	1500	50
8	141	Rajs	1500	50
9	107	Lorentz	1400	60
10	104	Ernst	1400	60
...				
19	205	Higgins	1700	110

ORACLE


Retrieving Records with the USING Clause

In the example in the slide, the DEPARTMENT_ID columns in the EMPLOYEES and DEPARTMENTS tables are joined and thus the LOCATION_ID of the department where an employee works is shown.

Using Table Aliases with the USING Clause

- Do not qualify a column that is used in the USING clause.
- If the same column is used elsewhere in the SQL statement, do not alias it.

```
SELECT l.city, d.department_name
FROM   locations l JOIN departments d
USING (location_id)
WHERE  d.location_id = 1400;
```



ORACLE

6 - 14

Copyright © 2007, Oracle. All rights reserved.

Using Table Aliases with the USING clause

When joining with the USING clause, you cannot qualify a column that is used in the USING clause itself. Furthermore, if that column is used anywhere in the SQL statement, you cannot alias it. For example, in the query mentioned in the slide, you should not alias the `location_id` column in the WHERE clause because the column is used in the USING clause.

The columns that are referenced in the USING clause should not have a qualifier (table name or alias) anywhere in the SQL statement. For example, the following statement is valid:

```
SELECT l.city, d.department_name
FROM   locations l JOIN departments d USING (location_id)
WHERE  location_id = 1400;
```

Because, other columns that are common in both the tables, but not used in the USING clause, must be prefixed with a table alias otherwise you get the “column ambiguously defined” error.

In the following statement, `manager_id` is present in both the `employees` and `departments` table and if `manager_id` is not prefixed with a table alias, it gives a “column ambiguously defined” error.

The following statement is valid:

```
SELECT first_name, d.department_name, d.manager_id
FROM   employees e JOIN departments d USING (department_id)
WHERE  department_id = 50;
```

Creating Joins with the ON Clause

- The join condition for the natural join is basically an equijoin of all columns with the same name.
- Use the `ON` clause to specify arbitrary conditions or specify columns to join.
- The join condition is separated from other search conditions.
- The `ON` clause makes code easy to understand.

ORACLE

6 - 15

Copyright © 2007, Oracle. All rights reserved.

Creating Joins with the ON Clause

Use the `ON` clause to specify a join condition. With this, you can specify join conditions separate from any search or filter conditions in the `WHERE` clause.

Retrieving Records with the ON Clause

```
SELECT e.employee_id, e.last_name, e.department_id,  
       d.department_id, d.location_id  
FROM   employees e JOIN departments d  
ON     (e.department_id = d.department_id);
```

	EMPLOYEE_ID	LAST_NAME	DEPARTMENT_ID	DEPARTMENT_ID_1	LOCATION_ID
1	200	Whalen	10	10	1700
2	201	Hartstein	20	20	1800
3	202	Fay	20	20	1800
4	124	Mourgos	50	50	1500
5	144	Vargas	50	50	1500
6	143	Matos	50	50	1500
7	142	Davies	50	50	1500
8	141	Rajs	50	50	1500
9	107	Lorentz	60	60	1400
10	104	Ernst	60	60	1400

...

ORACLE

Retrieving Records with the ON Clause

In this example, the DEPARTMENT_ID columns in the EMPLOYEES and DEPARTMENTS table are joined using the ON clause. Wherever a department ID in the EMPLOYEES table equals a department ID in the DEPARTMENTS table, the row is returned. The table alias is necessary to qualify the matching column_names.

You can also use the ON clause to join columns that have different names. The parenthesis around the joined columns as in the slide example, (e.department_id = d.department_id) is optional. So, even ON e.department_id = d.department_id will work.

Note: SQL Developer suffixes a '_1' to differentiate between the two department_ids.

Creating Three-Way Joins with the ON Clause

```
SELECT employee_id, city, department_name
FROM   employees e
JOIN   departments d
ON     d.department_id = e.department_id
JOIN   locations l
ON     d.location_id = l.location_id;
```

	EMPLOYEE_ID	CITY	DEPARTMENT_NAME
1	100	Seattle	Executive
2	101	Seattle	Executive
3	102	Seattle	Executive
4	103	Southlake	IT
5	104	Southlake	IT
6	107	Southlake	IT
7	124	South San Francisco	Shipping
8	141	South San Francisco	Shipping

...

ORACLE

6 - 17

Copyright © 2007, Oracle. All rights reserved.

Creating Three-Way Joins with the ON Clause

A three-way join is a join of three tables. In SQL:1999-compliant syntax, joins are performed from left to right. So, the first join to be performed is `EMPLOYEES JOIN DEPARTMENTS`. The first join condition can reference columns in `EMPLOYEES` and `DEPARTMENTS` but cannot reference columns in `LOCATIONS`. The second join condition can reference columns from all three tables.

Note: The code example in the slide can also be accomplished with the `USING` clause:

```
SELECT e.employee_id, l.city, d.department_name
FROM   employees e
JOIN   departments d
      USING (department_id)
JOIN   locations l
      USING (location_id)
```

Applying Additional Conditions to a Join

Use the `AND` clause or the `WHERE` clause to apply additional conditions:

```
SELECT e.employee_id, e.last_name, e.department_id,  
       d.department_id, d.location_id  
FROM   employees e JOIN departments d  
ON      (e.department_id = d.department_id)  
AND     e.manager_id = 149 ;
```

Or

```
SELECT e.employee_id, e.last_name, e.department_id,  
       d.department_id, d.location_id  
FROM   employees e JOIN departments d  
ON      (e.department_id = d.department_id)  
WHERE   e.manager_id = 149 ;
```

ORACLE

6 - 18

Copyright © 2007, Oracle. All rights reserved.

Applying Additional Conditions to a Join

You can apply additional conditions to the join.

The example shown performs a join on the `EMPLOYEES` and `DEPARTMENTS` tables and, in addition, displays only employees who have a manager ID of 149. To add additional conditions to the `ON` clause, you can add `AND` clauses. Alternatively, you can use a `WHERE` clause to apply additional conditions.

	EMPLOYEE_ID	LAST_NAME	DEPARTMENT_ID	DEPARTMENT_ID_1	LOCATION_ID
1	174	Abel	80	80	2500
2	176	Taylor	80	80	2500

Lesson Agenda

- Types of JOINS and its syntax
- Natural join:
 - USING clause
 - ON clause
- Self-join
- Nonequijoins
- OUTER join:
 - LEFT OUTER join
 - RIGHT OUTER join
 - FULL OUTER join
- Cartesian product
 - Cross join

ORACLE

Joining a Table to Itself

EMPLOYEES (WORKER)

	EMPLOYEE_ID	LAST_NAME	MANAGER_ID
1	100	King	(null)
2	101	Kochhar	100
3	102	De Haan	100
4	103	Hunold	102
5	104	Ernst	103
6	107	Lorentz	103
7	124	Mourgos	100
8	141	Rajs	124
9	142	Davies	124
10	143	Matos	124

...

EMPLOYEES (MANAGER)

EMPLOYEE_ID	LAST_NAME
100	King
101	Kochhar
102	De Haan
103	Hunold
104	Ernst
107	Lorentz
124	Mourgos
141	Rajs
142	Davies
143	Matos

...

**MANAGER_ID in the WORKER table is equal to
EMPLOYEE_ID in the MANAGER table.**

ORACLE

Joining a Table to Itself

Sometimes you need to join a table to itself. To find the name of each employee's manager, you need to join the EMPLOYEES table to itself, or perform a self-join. For example, to find the name of Lorentz's manager, you need to:

- Find Lorentz in the EMPLOYEES table by looking at the LAST_NAME column
- Find the manager number for Lorentz by looking at the MANAGER_ID column. Lorentz's manager number is 103.
- Find the name of the manager with EMPLOYEE_ID 103 by looking at the LAST_NAME column. Hunold's employee number is 103, so Hunold is Lorentz's manager.

In this process, you look in the table twice. The first time you look in the table to find Lorentz in the LAST_NAME column and the MANAGER_ID value of 103. The second time you look in the EMPLOYEE_ID column to find 103 and the LAST_NAME column to find Hunold.

Self-Joins Using the ON Clause

```
SELECT worker.last_name emp, manager.last_name mgr
FROM   employees worker JOIN employees manager
ON     (worker.manager_id = manager.employee_id);
```

EMP	MGR
1 Hunold	De Haan
2 Fay	Hartstein
3 Gietz	Higgins
4 Lorentz	Hunold
5 Ernst	Hunold
6 Zlotkey	King
7 Mourgos	King
8 Kochhar	King
9 Hartstein	King
10 De Haan	King

...

ORACLE

6 - 21

Copyright © 2007, Oracle. All rights reserved.

Self-Joins Using the ON Clause

The ON clause can also be used to join columns that have different names, within the same table or in a different table.

The example shown is a self-join of the EMPLOYEES table, based on the EMPLOYEE_ID and MANAGER_ID columns.

Note: The parenthesis around the joined columns as in the slide example, (e.manager_id = m.employee_id) is **optional**. So, even ON e.manager_id = m.employee_id will work.

Lesson Agenda

- Types of JOINS and its syntax
- Natural join:
 - USING clause
 - ON clause
- Self-join
- **Nonequijoins**
- OUTER join:
 - LEFT OUTER join
 - RIGHT OUTER join
 - FULL OUTER join
- Cartesian product
 - Cross join

ORACLE

Nonequijoins

EMPLOYEES

	LAST_NAME	SALARY
1	King	24000
2	Kochhar	17000
3	De Haan	17000
4	Hunold	9000
5	Ernst	6000
6	Lorentz	4200
7	Mourgos	5800
8	Rajs	3500
9	Davies	3100
10	Matos	2600
...		
19	Higgins	12000
20	Gietz	8300

JOB_GRADES

	GRADE_LEVEL	LOWEST_SAL	HIGHEST_SAL
1	A	1000	2999
2	B	3000	5999
3	C	6000	9999
4	D	10000	14999
5	E	15000	24999
6	F	25000	40000

JOB_GRADES table defines the **LOWEST_SAL** and **HIGHEST_SAL** range of values for each **GRADE_LEVEL**. Hence, the **GRADE_LEVEL** column can be used to assign grades to each employee.

ORACLE

Nonequijoins

A nonequijoin is a join condition containing something other than an equality operator.

The relationship between the **EMPLOYEES** table and the **JOB_GRADES** table is an example of a nonequijoin. The **SALARY** column in the **EMPLOYEES** table ranges between the values in the **LOWEST_SAL** and **HIGHEST_SAL** columns of the **JOB_GRADES** table. Hence, each employee can be graded based on their salary. The relationship is obtained using an operator other than the equality (=) operator.

Retrieving Records with Nonequijoins

```
SELECT e.last_name, e.salary, j.grade_level
FROM   employees e JOIN job_grades j
ON     e.salary
      BETWEEN j.lowest_sal AND j.highest_sal;
```

	LAST_NAME	SALARY	GRADE_LEVEL
1	Vargas	2500	A
2	Matos	2600	A
3	Davies	3100	B
4	Rajs	3500	B
5	Lorentz	4200	B
6	Whalen	4400	B
7	Mourgos	5800	B
8	Ernst	6000	C
9	Fay	6000	C
10	Grant	7000	C

...

ORACLE

6 - 24

Copyright © 2007, Oracle. All rights reserved.

Retrieving Records with Nonequijoins

The slide example creates a nonequijoin to evaluate an employee's salary grade. The salary must be *between* any pair of the low and high salary ranges.

It is important to note that all employees appear exactly once when this query is executed. No employee is repeated in the list. There are two reasons for this:

- None of the rows in the JOB_GRADES table contain grades that overlap. That is, the salary value for an employee can lie only between the low salary and high salary values of one of the rows in the salary grade table.
- All of the employees' salaries lie within the limits provided by the job grade table. That is, no employee earns less than the lowest value contained in the LOWEST_SAL column or more than the highest value contained in the HIGHEST_SAL column.

Note: Other conditions (such as <= and >=) can be used, but BETWEEN is the simplest.

Remember to specify the low value first and the high value last when using the BETWEEN condition. The Oracle server translates the BETWEEN condition to a pair of AND conditions. Therefore, using BETWEEN has no performance benefits, but should be used only for logical simplicity.

Table aliases have been specified in the slide example for performance reasons, not because of possible ambiguity.

Lesson Agenda

- Types of JOINS and its syntax
- Natural join:
 - USING clause
 - ON clause
- Self-join
- Nonequijoins
- OUTER join:
 - LEFT OUTER join
 - RIGHT OUTER join
 - FULL OUTER join
- Cartesian product
 - Cross join

ORACLE

Returning Records with No Direct Match with Outer Joins

DEPARTMENTS

DEPARTMENT_NAME	DEPARTMENT_ID
Administration	10
Marketing	20
Shipping	50
IT	60
Sales	80
Executive	90
Accounting	110
Contracting	190

EMPLOYEES

	DEPARTMENT_ID	LAST_NAME
1	90	King
2	90	Kochhar
3	90	De Haan
4	60	Hunold
5	60	Ernst
6	60	Lorentz
7	50	Mourgos
8	50	Rajs
9	50	Davies
10	50	Matos
...		
19	110	Higgins
20	110	Gietz

There are no employees in department 190.

Returning Records with No Direct Match with Outer Joins

If a row does not satisfy a join condition, the row does not appear in the query result. For example, in the equijoin condition of EMPLOYEES and DEPARTMENTS tables, department ID 190 does not appear because there are no employees with that department ID recorded in the EMPLOYEES table. Therefore, instead of seeing 20 employees in the result set, you see 19 records.

To return the department record that does not have any employees, you can use an outer join.

INNER Versus OUTER Joins

- In SQL:1999, the join of two tables returning only matched rows is called an inner join.
- A join between two tables that returns the results of the inner join as well as the unmatched rows from the left (or right) table is called a left (or right) outer join.
- A join between two tables that returns the results of an inner join as well as the results of a left and right join is a full outer join.

ORACLE

6 - 27

Copyright © 2007, Oracle. All rights reserved.

INNER Versus OUTER Joins

Joining tables with the `NATURAL JOIN`, `USING`, or `ON` clauses results in an inner join. Any unmatched rows are not displayed in the output. To return the unmatched rows, you can use an outer join. An outer join returns all rows that satisfy the join condition and also returns some or all of those rows from one table for which no rows from the other table satisfy the join condition.

There are three types of outer joins:

- `LEFT OUTER`
- `RIGHT OUTER`
- `FULL OUTER`

LEFT OUTER JOIN

```
SELECT e.last_name, e.department_id, d.department_name
FROM   employees e LEFT OUTER JOIN departments d
ON     (e.department_id = d.department_id) ;
```

	LAST_NAME	DEPARTMENT_ID	DEPARTMENT_NAME
1	Whalen	10	Administration
2	Fay	20	Marketing
3	Hartstein	20	Marketing
4	Vargas	50	Shipping
5	Matos	50	Shipping

...

17	King	90	Executive
18	Gietz	110	Accounting
19	Higgins	110	Accounting
20	Grant	(null)	(null)

ORACLE

LEFT OUTER JOIN

This query retrieves all rows in the EMPLOYEES table, which is the left table, even if there is no match in the DEPARTMENTS table.

RIGHT OUTER JOIN

```
SELECT e.last_name, e.department_id, d.department_name
FROM   employees e RIGHT OUTER JOIN departments d
ON     (e.department_id = d.department_id) ;
```

R2	LAST_NAME	R2	DEPARTMENT_ID	R2	DEPARTMENT_NAME
1	Whalen		10		Administration
2	Hartstein		20		Marketing
3	Fay		20		Marketing
4	Higgins		110		Accounting

...

19	Taylor		80		Sales
20	Grant		(null)	(null)	
21	(null)		190		Contracting

ORACLE

RIGHT OUTER JOIN

This query retrieves all rows in the DEPARTMENTS table, which is the right table, even if there is no match in the EMPLOYEES table.

FULL OUTER JOIN

```
SELECT e.last_name, d.department_id, d.department_name
FROM   employees e FULL OUTER JOIN departments d
ON     (e.department_id = d.department_id) ;
```

#	LAST_NAME	#	DEPARTMENT_ID	#	DEPARTMENT_NAME
1	Whalen		10		Administration
2	Hartstein		20		Marketing
3	Fay		20		Marketing
4	Higgins		110		Accounting
...					
19	Taylor		80		Sales
20	Grant		(null)		(null)
21	(null)		190		Contracting

ORACLE

FULL OUTER JOIN

This query retrieves all rows in the EMPLOYEES table, even if there is no match in the DEPARTMENTS table. It also retrieves all rows in the DEPARTMENTS table, even if there is no match in the EMPLOYEES table.

Lesson Agenda

- Types of JOINS and its syntax
- Natural join:
 - USING clause
 - ON clause
- Self-join
- Nonequijoin
- OUTER join:
 - LEFT OUTER join
 - RIGHT OUTER join
 - FULL OUTER join
- Cartesian product
 - Cross join

ORACLE

Cartesian Products

- A Cartesian product is formed when:
 - A join condition is omitted
 - A join condition is invalid
 - All rows in the first table are joined to all rows in the second table
- To avoid a Cartesian product, always include a valid join condition.

ORACLE

6 - 32

Copyright © 2007, Oracle. All rights reserved.

Cartesian Products

When a join condition is invalid or omitted completely, the result is a *Cartesian product*, in which all combinations of rows are displayed. All rows in the first table are joined to all rows in the second table.

A Cartesian product tends to generate a large number of rows and the result is rarely useful. You should, therefore, always include a valid join condition unless you have a specific need to combine all rows from all tables.

However, Cartesian products are useful for some tests when you need to generate a large number of rows to simulate a reasonable amount of data.

Generating a Cartesian Product

EMPLOYEES (20 rows)

	EMPLOYEE_ID	LAST_NAME	DEPARTMENT_ID
1	100	King	90
2	101	Kochhar	90
3	102	De Haan	90
4	103	Hunold	60
...			
19	205	Higgins	110
20	206	Gietz	110

DEPARTMENTS (8 rows)

	DEPARTMENT_ID	DEPARTMENT_NAME	LOCATION_ID
1	10	Administration	1700
2	20	Marketing	1800
3	50	Shipping	1500
4	60	IT	1400
5	80	Sales	2500
6	90	Executive	1700
7	110	Accounting	1700
8	190	Contracting	1700

Cartesian product:
20 x 8 = 160 rows

	EMPLOYEE_ID	DEPARTMENT_ID	LOCATION_ID
1	100	90	1700
2	101	90	1700
3	102	90	1700
4	103	60	1700
...			
159	205	110	1700
160	206	110	1700

ORACLE

Generating a Cartesian Product

A Cartesian product is generated if a join condition is omitted. The example in the slide displays the employee last name and the department name from the EMPLOYEES and DEPARTMENTS tables. Because no join condition was specified, all rows (20 rows) from the EMPLOYEES table are joined with all rows (8 rows) in the DEPARTMENTS table, thereby generating 160 rows in the output.

Creating Cross Joins

- The `CROSS JOIN` clause produces the cross-product of two tables.
- This is also called a Cartesian product between the two tables.

```
SELECT last_name, department_name  
FROM employees  
CROSS JOIN departments ;
```

1	LAST_NAME	2	DEPARTMENT_NAME
1	Abel		Administration
2	Davies		Administration
3	De Haan		Administration
4	Ernst		Administration
5	Fay		Administration
...			
159	Whalen		Contracting
160	Zlotkey		Contracting

ORACLE

Creating Cross Joins

The example in the slide produces a Cartesian product of the `EMPLOYEES` and `DEPARTMENTS` tables.

Summary

In this lesson, you should have learned how to use joins to display data from multiple tables by using:

- Equijoins
- Nonequijoins
- Outer joins
- Self-joins
- Cross joins
- Natural joins
- Full (or two-sided) outer joins

ORACLE

6 - 35

Copyright © 2007, Oracle. All rights reserved.

Summary

There are multiple ways to join tables.

Types of Joins

- Equijoins
- Nonequijoins
- Outer joins
- Self-joins
- Cross joins
- Natural joins
- Full (or two-sided) outer joins

Cartesian Products

A Cartesian product results in the display of all combinations of rows. This is done by either omitting the WHERE clause or by specifying the CROSS JOIN clause.

Table Aliases

- Table aliases speed up database access.
- Table aliases can help to keep SQL code smaller by conserving memory.
- Table aliases are sometimes mandatory to avoid column ambiguity.

Practice 6: Overview

This practice covers the following topics:

- Joining tables using an equijoin
- Performing outer and self-joins
- Adding conditions

ORACLE

6 - 36

Copyright © 2007, Oracle. All rights reserved.

Practice 6: Overview

This practice is intended to give you experience in extracting data from more than one table using the SQL:1999-compliant joins.

Practice 6

1. Write a query for the HR department to produce the addresses of all the departments. Use the `LOCATIONS` and `COUNTRIES` tables. Show the location ID, street address, city, state or province, and country in the output. Use a `NATURAL JOIN` to produce the results.

	LOCATION_ID	STREET_ADDRESS	CITY	STATE_PROVINCE	COUNTRY_NAME
1	1400	2014 Jabberwocky Rd	Southlake	Texas	United States of America
2	1500	2011 Interiors Blvd	South San Francisco	California	United States of America
3	1700	2004 Charade Rd	Seattle	Washington	United States of America
4	1800	460 Bloor St. W.	Toronto	Ontario	Canada
5	2500	Magdalen Centre, The ...	Oxford	Oxford	United Kingdom

2. The HR department needs a report of all employees. Write a query to display the last name, department number, and department name for all the employees.





	LAST_NAME	DEPARTMENT_ID	DEPARTMENT_NAME
1	Whalen	10	Administration
2	Hartstein	20	Marketing
3	Fay	20	Marketing
4	Davies	50	Shipping
5	Vargas	50	Shipping
6	Rajs	50	Shipping
7	Mourgos	50	Shipping
8	Matos	50	Shipping
9	Hunold	60	IT
10	Ernst	60	IT

...





18	Higgins	110	Accounting
19	Gietz	110	Accounting

Practice 6 (continued)

- The HR department needs a report of employees in Toronto. Display the last name, job, department number, and the department name for all employees who work in Toronto.

	 LAST_NAME	 JOB_ID	 DEPARTMENT_ID	 DEPARTMENT_NAME
1	Hartstein	MK_MAN	20	Marketing
2	Fay	MK_REP	20	Marketing

- Create a report to display employees' last name and employee number along with their manager's last name and manager number. Label the columns Employee, Emp#, Manager, and Mgr#, respectively. Save your SQL statement as lab_06_04.sql. Run the query.

	 Employee	 EMP#	 Manager	 Mgr#
1	Kochhar	101	King	100
2	De Haan	102	King	100
3	Hunold	103	De Haan	102
4	Ernst	104	Hunold	103
5	Lorentz	107	Hunold	103
6	Mourgos	124	King	100
7	Rajs	141	Mourgos	124
8	Davies	142	Mourgos	124
9	Matos	143	Mourgos	124
10	Vargas	144	Mourgos	124

■ ■ ■

15	Whalen	200	Kochhar	101
16	Hartstein	201	King	100
17	Fay	202	Hartstein	201
18	Higgins	205	Kochhar	101
19	Gietz	206	Higgins	205

Practice 6 (continued)

- Modify `lab_06_04.sql` to display all employees including King, who has no manager. Order the results by the employee number. Save your SQL statement as `lab_06_05.sql`. Run the query in `lab_06_05.sql`.

	Employee	EMP#	Manager	Mgr#
1	King	100	(null)	(null)
2	Kochhar	101	King	100
3	De Haan	102	King	100
4	Hunold	103	De Haan	102
5	Ernst	104	Hunold	103
6	Lorentz	107	Hunold	103
7	Mourgos	124	King	100
8	Rajs	141	Mourgos	124
9	Davies	142	Mourgos	124
10	Matos	143	Mourgos	124

■ ■ ■

18	Fay	202	Hartstein	201
19	Higgins	205	Kochhar	101
20	Gietz	206	Higgins	205

- Display employee last names, department numbers, and all the employees who work in the same department as a given employee. Give each column an appropriate label. Save the script to a file named `lab_06_06.sql`.

	DEPARTMENT	EMPLOYEE	COLLEAGUE
1	20	Fay	Hartstein
2	20	Hartstein	Fay
3	50	Davies	Matos
4	50	Davies	Mourgos
5	50	Davies	Rajs
6	50	Davies	Vargas
7	50	Matos	Davies
8	50	Matos	Mourgos
9	50	Matos	Rajs
10	50	Matos	Vargas

■ ■ ■

42	110	Higgins	Gietz
----	-----	---------	-------

Practice 6 (continued)

7. The HR department needs a report on job grades and salaries. To familiarize yourself with the JOB_GRADES table, first show the structure of the JOB_GRADES table. Then create a query that displays the name, job, department name, salary, and grade for all employees.

DESC JOB_GRADES		
Name	Null	Type

GRADE_LEVEL		VARCHAR2(3)
LOWEST_SAL		NUMBER
HIGHEST_SAL		NUMBER
3 rows selected		

	LAST_NAME	JOB_ID	DEPARTMENT_NAME	SALARY	GRADE_LEVEL
1	Vargas	ST_CLERK	Shipping	2500	A
2	Matos	ST_CLERK	Shipping	2600	A
3	Davies	ST_CLERK	Shipping	3100	B
4	Rajs	ST_CLERK	Shipping	3500	B
5	Lorentz	IT_PROG	IT	4200	B
6	Whalen	AD_ASST	Administration	4400	B
7	Mourgos	ST_MAN	Shipping	5800	B
8	Ernst	IT_PROG	IT	6000	C
9	Fay	MK_REP	Marketing	6000	C
10	Gietz	AC_ACCOUNT	Accounting	8300	C

■ ■ ■

18	De Haan	AD_VP	Executive	17000	E
19	King	AD_PRES	Executive	24000	E



Practice 6 (continued)

If you want an extra challenge, complete the following exercises:

8. The HR department wants to determine the names of all the employees who were hired after Davies. Create a query to display the name and hire date of any employee hired after employee Davies.

	 LAST_NAME	HIRE_DATE
1	Lorentz	07-FEB-99
2	Mourgos	16-NOV-99
3	Matos	15-MAR-98
4	Vargas	09-JUL-98
5	Zlotkey	29-JAN-00
6	Taylor	24-MAR-98
7	Grant	24-MAY-99
8	Fay	17-AUG-97

9. The HR department needs to find the names and hire dates of all the employees who were hired before their managers, along with their managers' names and hire dates. Save the script to a file named lab_06_09.sql.

	 LAST_NAME	HIRE_DATE	 LAST_NAME_1	HIRE_DATE_1
1	Whalen	17-SEP-87	Kochhar	21-SEP-89
2	Hunold	03-JAN-90	De Haan	13-JAN-93
3	Vargas	09-JUL-98	Mourgos	16-NOV-99
4	Matos	15-MAR-98	Mourgos	16-NOV-99
5	Davies	29-JAN-97	Mourgos	16-NOV-99
6	Rajs	17-OCT-95	Mourgos	16-NOV-99
7	Grant	24-MAY-99	Zlotkey	29-JAN-00
8	Taylor	24-MAR-98	Zlotkey	29-JAN-00
9	Abel	11-MAY-96	Zlotkey	29-JAN-00

