

```

GNU nano 8.7.1 signals.c
#include <stdio.h>
#include <signal.h>
#include <unistd.h>

void handler(int sig)
{
    if (sig == SIGINT)
        printf("\nSIGINT received\n");

    else if (sig == SIGTERM)
        printf("SIGTERM received\n");

    else if (sig == SIGUSR1)
        printf("SIGUSR1 received\n");
}

int main()
{
    signal(SIGINT, handler);
    signal(SIGTERM, handler);
    signal(SIGUSR1, handler);

    printf("Process ID: %d\n", getpid());
    printf("Waiting for signals...\n");

    while (1)
    {
        sleep(1);
    }

    return 0;
}

```

```

varshith@VarhithReddy:~$ nano signals.c
varshith@VarhithReddy:~$ gcc signals.c -o signals
varshith@VarhithReddy:~$ ./signals
Process ID: 899
Waiting for signals...
^C
SIGINT received
^C

```

```
varshith@VarhithReddy: ~  
GNU nano 8.7.1 server.c  
#include <stdio.h>  
#include <fcntl.h>  
#include <unistd.h>  
#include <sys/stat.h>  
#include <string.h>  
  
int main()  
{  
    char buffer[100];  
  
    mkfifo("myfifo", 0666);  
  
    int fd = open("myfifo", O_RDONLY);  
    read(fd, buffer, sizeof(buffer));  
    printf("Server received: %s\n", buffer);  
  
    close(fd);  
    unlink("myfifo");  
  
    return 0;  
}
```

```
varshith@VarhithReddy: ~  
varshith@VarhithReddy:~$ ./client  
Enter message: Hello Server  
Message sent  
varshith@VarhithReddy:~$ |
```

```
GNU nano 8.7.1 client.c
#include <stdio.h>
#include <fcntl.h>
#include <unistd.h>
#include <string.h>

int main()
{
    char msg[100];

    printf("Enter message: ");
    fgets(msg, sizeof(msg), stdin);

    int fd = open("myfifo", O_WRONLY);

    write(fd, msg, strlen(msg) + 1);

    close(fd);

    printf("Message sent\n");

    return 0;
}
```

```
varshith@VarhithReddy:~$ nano client.c
varshith@VarhithReddy:~$ gcc client.c -o client
varshith@VarhithReddy:~$ ./server
Server received: Hello Server

varshith@VarhithReddy:~$ |
```