

```

1 #include <stdio.h>
2 #include <unistd.h>
3 #include <fcntl.h>
4 #include <sys/stat.h>
5
6 int main()
7 {
8     char buffer[100];
9
10    mkfifo("myfifo", 0666);
11
12    int fd = open("myfifo", O_RDONLY);
13
14    while (1)
15    {
16        read(fd, buffer, sizeof(buffer));
17
18        printf("Server received: %s\n", buffer);
19    }
20
21    close(fd);
22
23    return 0;
24 }

```

```

1 #include <stdio.h>
2 #include <unistd.h>
3 #include <fcntl.h>
4 #include <string.h>
5
6 int main()
7 {
8     char message[100];
9
10    int fd = open("myfifo", O_WRONLY);
11
12    printf("Enter message: ");
13    fgets(message, sizeof(message), stdin);
14
15    write(fd, message, strlen(message) + 1);
16
17    close(fd);
18
19    return 0;
20 }

```

```

yeshwanth@LAPTOP-N3S9K224:~$ gcc q6a1.c
yeshwanth@LAPTOP-N3S9K224:~$ ./a.out
Enter message: Hello Server
yeshwanth@LAPTOP-N3S9K224:~$ gcc q6a1.c
yeshwanth@LAPTOP-N3S9K224:~$ ./a.out
Enter message: Hello Server
yeshwanth@LAPTOP-N3S9K224:~$ |

```

Server received: Hello Server

Server received: Hello Server

Server received: Hello Server

Server received: Hello Server

Server received: Hello Server

Server received: Hello Server

Server received: Hello Server

Server received: Hello Server

Server received: Hello Server

Server received: Hello Server

Server received: Hello Server

Server received: Hello Server

Server received: Hello Server

Server received: Hello Server

Server received: Hello Server

Server received: Hello Server

Server received: Hello Server

Server received: Hello Server

Server received: Hello Server

Server received: Hello Server

Server received: Hello Server

Server received: Hello Server

Server received: 2nd message

Server received: 2nd message

Server received: 2nd message

Server received: 2nd message

Server received: 2nd message

Server received: 2nd message

Server received: 2nd message

Server received: 2nd message

Server received: 2nd message

Server received: 2nd message

Server received: 2nd message

Server received: 2nd message

Server received: 2nd message

Server received: 2nd message

Server received: 2nd message

Server received: 2nd message

Server received: 2nd message

Server received: 2nd message

Server received: 2nd message

Server received: 2nd message

Server received: 2nd message

```

1 #include <stdio.h>
2 #include <signal.h>
3 #include <unistd.h>
4
5 void handler(int sig)
6 {
7     if (sig == SIGINT)
8         printf("\nSIGINT received\n");
9
10    if (sig == SIGTERM)
11        printf("SIGTERM received\n");
12
13    if (sig == SIGUSR1)
14        printf("SIGUSR1 received\n");
15 }
16
17 int main()
18 {
19     signal(SIGINT, handler);
20     signal(SIGTERM, handler);
21     signal(SIGUSR1, handler);
22
23     printf("Process ID: %d\n", getpid());
24     printf("Waiting for signals...\n");
25
26     while (1)
27     {
28         sleep(1);
29     }
30
31     return 0;
32 }

```

```
yeshwanth@LAPTOP-N3S9K224:~$ gedit q6b.c
```

```
** (gedit:9630): WARNING **: 05:55:01.438: Could not load module 'libgail-3.0.so.0' for widget 'GtkLabel'.
```

```
** (gedit:9630): WARNING **: 05:55:01.438: Could not load module 'libgail-3.0.so.0' for widget 'GtkLabel'.
```

```
yeshwanth@LAPTOP-N3S9K224:~$ gcc q6b.c
```

```
yeshwanth@LAPTOP-N3S9K224:~$ ./a.out
```

```
Process ID: 10750
```

```
Waiting for signals...
```

```
SIGUSR1 received
```

```
SIGTERM received
```

```
SIGINT received
```

```
Killed ./a.out
```

```
yeshwanth@LAPTOP-N3S9K224:~$ |
```

```
yeshwanth@LAPTOP-N3S9K224:~$ kill -SIGUSR1 10750
yeshwanth@LAPTOP-N3S9K224:~$ kill -SIGTERM 10750
yeshwanth@LAPTOP-N3S9K224:~$ kill -SIGINT 10750
yeshwanth@LAPTOP-N3S9K224:~$ kill -9 10750
yeshwanth@LAPTOP-N3S9K224:~$ |
```