



Apriori Algorithm



Mohityadav

Read

Discuss

Prerequisite – [Frequent Item set in Data set \(Association Rule Mining\)](#).

Apriori algorithm is given by R. Agrawal and R. Srikant in 1994 for finding frequent itemsets in a dataset for boolean association rule. Name of the algorithm is Apriori because it uses prior knowledge of frequent itemset properties. We apply an iterative approach or level-wise search where k-frequent itemsets are used to find k+1 itemsets.

To improve the efficiency of level-wise generation of frequent itemsets, an important property is used called *Apriori property* which helps by reducing the search space.

Apriori Property –

All non-empty subset of frequent itemset must be frequent. The key concept of Apriori algorithm is its anti-monotonicity of support measure. Apriori assumes that

All subsets of a frequent itemset must be frequent(Apriori property).

If an itemset is infrequent, all its supersets will be infrequent.

AD

Before we start understanding the algorithm, go through some definitions which are explained in my previous post.

Consider the following dataset and we will find frequent itemsets and generate association rules for them.

T1	I1, I2, I5
T2	I2, I4
T3	I2, I3
T4	I1, I2, I4
T5	I1, I3
T6	I2, I3
T7	I1, I3
T8	I1, I2, I3, I5
T9	I1, I2, I3

minimum support count is 2

minimum confidence is 60%

Step-1: K=1

(I) Create a table containing support count of each item present in dataset – Called **C1(candidate set)**

Itemset	sup_count
I1	6
I2	7
I3	6
I4	2
I5	2

(II) compare candidate set item's support count with minimum support count(here min_support=2 if support_count of candidate set items is less than min_support then remove those items). This gives us itemset L1.

Itemset	sup_count
I1	6
I2	7
I3	6
I4	2
I5	2

Step-2: K=2

- Generate candidate set C2 using L1 (this is called join step). Condition of joining L_{k-1} and L_{k-1} is that it should have (K-2) elements in common.
- Check all subsets of an itemset are frequent or not and if not frequent remove that itemset. (Example subset of {I1, I2} are {I1}, {I2} they are frequent. Check for each itemset)
- Now find support count of these itemsets by searching in dataset.

Itemset	sup_count
I1,I2	4
I1,I3	4
I1,I4	1
I1,I5	2
I2,I3	4
I2,I4	2
I2,I5	2
I3,I4	0
I3,I5	1
I4,I5	0

(II) compare candidate (C2) support count with minimum support count (here min_support=2 if support_count of candidate set item is less than min_support then remove those items) this gives us itemset L2.

Itemset	sup_count
I1,I2	4
I1,I3	4
I1,I5	2
I2,I3	4
I2,I4	2
I2,I5	2
I2,I5	2

Step-3:

- Generate candidate set C3 using L2 (join step). Condition of joining L_{k-1} and L_{k-1} is that it should have (K-2) elements in common. So here, for L2, first element should match. So itemset generated by joining L2 is {I1, I2, I3}{I1, I2, I5}{I1, I3, I5}{I2, I3, I4}{I2, I4, I5}{I2, I3, I5}
- Check if all subsets of these itemsets are frequent or not and if not, then remove that itemset. (Here subset of {I1, I2, I3} are {I1, I2}, {I2, I3}, {I1, I3} which are frequent. For {I2, I3, I4}, subset {I3, I4} is not frequent so remove it. Similarly check for every itemset)

Itemset	sup_count
I1,I2,I3	2
I1,I2,I5	2

(II) Compare candidate (C3) support count with minimum support count(here min_support=2 if support_count of candidate set item is less than min_support then remove those items) this gives us itemset L3.

Itemset	sup_count
I1,I2,I3	2
I1,I2,I5	2

Step-4:

- Generate candidate set C4 using L3 (join step). Condition of joining L_{k-1} and L_{k-1} ($K=4$) is that, they should have $(K-2)$ elements in common. So here, for L3, first 2 elements (items) should match.
- Check all subsets of these itemsets are frequent or not (Here itemset formed by joining L3 is {I1, I2, I3, I5} so its subset contains {I1, I3, I5}, which is not frequent). So no itemset in C4
- We stop here because no frequent itemsets are found further

Thus, we have discovered all the frequent item-sets. Now generation of strong association rule comes into picture. For that we need to calculate confidence of each rule.

Confidence –

A confidence of 60% means that 60% of the customers, who purchased milk and bread also bought butter

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

So here, by taking an example of any frequent itemset, we will show the rule generation.

Itemset {I1, I2, I3} //from L3

SO rules can be

$[I1 \wedge I2] \Rightarrow [I3]$ //confidence = $\frac{\text{sup}(I1 \wedge I2 \wedge I3)}{\text{sup}(I1 \wedge I2)} = \frac{2}{4} * 100 = 50\%$

$[I1 \wedge I3] \Rightarrow [I2]$ //confidence = $\frac{\text{sup}(I1 \wedge I2 \wedge I3)}{\text{sup}(I1 \wedge I3)} = \frac{2}{4} * 100 = 50\%$

$[I2 \wedge I3] \Rightarrow [I1]$ //confidence = $\frac{\text{sup}(I1 \wedge I2 \wedge I3)}{\text{sup}(I2 \wedge I3)} = \frac{2}{4} * 100 = 50\%$

$[I1] \Rightarrow [I2 \wedge I3]$ //confidence = $\frac{\text{sup}(I1 \wedge I2 \wedge I3)}{\text{sup}(I1)} = \frac{2}{6} * 100 = 33\%$

$[I2] \Rightarrow [I1 \wedge I3]$ //confidence = $\frac{\text{sup}(I1 \wedge I2 \wedge I3)}{\text{sup}(I2)} = \frac{2}{7} * 100 = 28\%$

$[I3] \Rightarrow [I1 \wedge I2]$ //confidence = $\frac{\text{sup}(I1 \wedge I2 \wedge I3)}{\text{sup}(I3)} = \frac{2}{6} * 100 = 33\%$

So if minimum confidence is 50%, then first 3 rules can be considered as strong association rules.

Limitations of Apriori Algorithm

Apriori Algorithm can be slow. The main limitation is time required to hold a vast number of candidate sets with much frequent itemsets, low minimum support or large itemsets i.e. it is not an efficient approach for large number of datasets. For example, if there are 10^4 frequent 1- itemsets, it need to generate more than 10^7 candidates into 2-length which in turn they will be tested and accumulate. Furthermore, to detect frequent pattern in size 100 i.e. $v_1, v_2 \dots v_{100}$, it have to generate 2^{100} candidate itemsets that yield on costly and wasting of time of candidate generation. So, it will check for many sets from candidate itemsets, also it will scan database many times repeatedly for finding candidate itemsets. Apriori will be very low and inefficiency when memory capacity is limited with large number of transactions.

[Source : <https://arxiv.org/pdf/1403.3948.pdf>]

Last Updated : 13 Jan, 2022

114

Similar Reads

1. K-Nearest Neighbor(KNN) Algorithm
2. Jump Pointer Algorithm
3. Different Types of Clustering Algorithm
4. Raft Consensus Algorithm
5. Weiler Atherton - Polygon Clipping Algorithm
6. Welsh Powell Graph colouring Algorithm
7. Slow Start Backoff Algorithm for Ad-Hoc

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

8. Shamir's Secret Sharing Algorithm | Cryptography
9. Basic Understanding of CURE Algorithm
10. ANN - Bidirectional Associative Memory (BAM) Learning Algorithm

[Previous](#)[Next](#)

Article Contributed By :

**Mohityadav**

Mohityadav

Vote for difficulty

Current difficulty : [Medium](#)

Easy

Normal

Medium

Hard

Expert

Improved By : [JayeshShelar](#), [Avik_Dutta](#), [varshagumber28](#)**Article Tags :** [data mining](#), [Computer Subject](#)**Practice Tags :** [Data Mining](#)[Improve Article](#)[Report Issue](#)**GeeksforGeeks**

A-143, 9th Floor, Sovereign Corporate Tower, Sector-136, Noida, Uttar Pradesh - 201305

feedback@geeksforgeeks.org[Company](#)[Explore](#)

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

[Careers](#)[In Media](#)[Contact Us](#)[Advertise with us](#)[Python Backend LIVE](#)[Android App Development](#)[DevOps LIVE](#)[DSA in JavaScript](#)

Languages

[Python](#)[Java](#)[C++](#)[PHP](#)[GoLang](#)[SQL](#)[R Language](#)[Android Tutorial](#)

Data Structures

[Array](#)[String](#)[Linked List](#)[Stack](#)[Queue](#)[Tree](#)[Graph](#)

Algorithms

[Sorting](#)[Searching](#)[Greedy](#)[Dynamic Programming](#)[Pattern Searching](#)[Recursion](#)[Backtracking](#)

Web Development

[HTML](#)[CSS](#)[JavaScript](#)[Bootstrap](#)[ReactJS](#)[AngularJS](#)[NodeJS](#)

Computer Science

[GATE CS Notes](#)[Operating Systems](#)[Computer Network](#)[Database Management System](#)[Software Engineering](#)[Digital Logic Design](#)[Engineering Maths](#)

Python

[Python Programming Examples](#)[Django Tutorial](#)[Python Projects](#)[Python Tkinter](#)[OpenCV Python Tutorial](#)[Python Interview Question](#)

Data Science & ML

[Data Science With Python](#)[Data Science For Beginner](#)[Machine Learning Tutorial](#)[Maths For Machine Learning](#)

DevOps

[Git](#)[AWS](#)[Docker](#)[Kubernetes](#)

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

[NumPy Tutorial](#)[GCP](#)[NLP Tutorial](#)[Deep Learning Tutorial](#)

Competitive Programming

[Top DSA for CP](#)[Top 50 Tree Problems](#)[Top 50 Graph Problems](#)[Top 50 Array Problems](#)[Top 50 String Problems](#)[Top 50 DP Problems](#)[Top 15 Websites for CP](#)

Interview Corner

[Company Wise Preparation](#)[Preparation for SDE](#)[Experienced Interviews](#)[Internship Interviews](#)[Competitive Programming](#)[Aptitude Preparation](#)

Commerce

[Accountancy](#)[Business Studies](#)[Economics](#)[Management](#)[Income Tax](#)[Finance](#)

SSC/ BANKING

[SSC CGL Syllabus](#)[SBI PO Syllabus](#)[SBI Clerk Syllabus](#)[IBPS PO Syllabus](#)[IBPS Clerk Syllabus](#)[Aptitude Questions](#)[SSC CGL Practice Papers](#)

System Design

[What is System Design](#)[Monolithic and Distributed SD](#)[Scalability in SD](#)[Databases in SD](#)[High Level Design or HLD](#)[Low Level Design or LLD](#)[Top SD Interview Questions](#)

GfG School

[CBSE Notes for Class 8](#)[CBSE Notes for Class 9](#)[CBSE Notes for Class 10](#)[CBSE Notes for Class 11](#)[CBSE Notes for Class 12](#)[English Grammar](#)

UPSC

[Polity Notes](#)[Geography Notes](#)[History Notes](#)[Science and Technology Notes](#)[Economics Notes](#)[Important Topics in Ethics](#)[UPSC Previous Year Papers](#)

Write & Earn

[Write an Article](#)[Improve an Article](#)[Pick Topics to Write](#)[Write Interview Experience](#)[Internships](#)[Video Internship](#)

