



# Livorno

## ARCUS PROFESSIONAL / ONE-PAGE TERRITORY BRIEFING

The selected province requires preliminary screening for Bridge interventions. The value is not the case list: it is understanding whether Livorno has already shown concentrated vulnerability under extreme conditions or risk distributed over time.

|                                                                        |                                                                  |                                                            |                                                       |
|------------------------------------------------------------------------|------------------------------------------------------------------|------------------------------------------------------------|-------------------------------------------------------|
| <b>PRIORITY INDEX</b><br><br><b>38/100</b><br><br>territorial exposure | <b>COLLAPSE RATE</b><br><br><b>1.15x</b><br><br>national rank 35 | <b>EVENTS</b><br><br><b>3</b><br><br>ARCUS cases in sample | <b>EVIDENCE</b><br><br><b>7</b><br><br>linked sources |
|------------------------------------------------------------------------|------------------------------------------------------------------|------------------------------------------------------------|-------------------------------------------------------|



**DECISION MESSAGE**

**Distributed chronic risk**

historical risk distributed across multiple events and dates (33% on the most recurrent date). The 1.15x rate versus the national average places Livorno among the provinces with documented historical vulnerability above the ARCUS/AINOP benchmark. Livorno is national rank 35 by documented ARCUS/AINOP collapse rate.

### 01 NEXT ACTIONS

- Use the territorial exposure indicators to identify the dominant Hydraulic signal.
- Read the documented distributed historical pattern and use individual cases as map/appendix references.
- Request TR100/TR200 hydraulic model, preliminary scour estimate, riverbed/bathymetry evidence and debris-transport indicators where relevant.
- Differentiate checks by geomorphology: torrential/confined channels require scour/debris checks; lowland crossings require flood level and duration checks.

**DATA REQUEST PACKAGE**

TR100/TR200 hydraulic model; preliminary scour depth; riverbed/bathymetry evidence; debris transport indicators where relevant.

**CONFIDENCE NOTE**

Collapse Rate confidence: high. The AINOP denominator should be read as available bridge-census coverage, not as a perfect inventory of the bridge stock.