

Dateiauswertung

GLEICH

.git/hooks/push-to-checkout.sample

Branch 1	main
Branch 2	current
Datei	.git/hooks/push-to-checkout.sample
Typ	Datei

Bewertung

SHA-256 identisch.

Dateiinhalt / Vergleich

1	#!/bin/sh
2	
3	# An example hook script to update a checked-out tree on a git push.
4	#
5	# This hook is invoked by git-receive-pack(1) when it reacts to git
6	# push and updates reference(s) in its repository, and when the push
7	# tries to update the branch that is currently checked out and the
8	# receive.denyCurrentBranch configuration variable is set to
9	# updateInstead.
10	#
11	# By default, such a push is refused if the working tree and the index
12	# of the remote repository has any difference from the currently
13	# checked out commit; when both the working tree and the index match
14	# the current commit, they are updated to match the newly pushed tip
15	# of the branch. This hook is to be used to override the default
16	# behaviour; however the code below reimplements the default behaviour
17	# as a starting point for convenient modification.
18	#
19	# The hook receives the commit with which the tip of the current
20	# branch is going to be updated:
21	commit=\$1
22	
23	# It can exit with a non-zero status to refuse the push (when it does
24	# so, it must not modify the index or the working tree).
25	die () {
26	echo >&2 "\$*"
27	exit 1
28	}
29	
30	# Or it can make any necessary changes to the working tree and to the

31	# index to bring them to the desired state when the tip of the current
32	# branch is updated to the new commit, and exit with a zero status.
33	#
34	# For example, the hook can simply run git read-tree -u -m HEAD "\$1"
35	# in order to emulate git fetch that is run in the reverse direction
36	# with git push, as the two-tree form of git read-tree -u -m is
37	# essentially the same as git switch or git checkout that switches
38	# branches while keeping the local changes in the working tree that do
39	# not interfere with the difference between the branches.
40	
41	# The below is a more-or-less exact translation to shell of the C code
42	# for the default behaviour for git's push-to-checkout hook defined in
43	# the push_to_deploy() function in builtin/receive-pack.c.
44	#
45	# Note that the hook will be executed from the repository directory,
46	# not from the working tree, so if you want to perform operations on
47	# the working tree, you will have to adapt your code accordingly, e.g.
48	# by adding "cd .." or using relative paths.
49	
50	if ! git update-index -q --ignore-submodules --refresh
51	then
52	die "Up-to-date check failed"
53	fi
54	
55	if ! git diff-files --quiet --ignore-submodules --
56	then
57	die "Working directory has unstaged changes"
58	fi
59	
60	# This is a rough translation of:
61	#
62	# head_has_history() ? "HEAD" : EMPTY_TREE_SHA1_HEX
63	if git cat-file -e HEAD 2>/dev/null
64	then
65	head=HEAD
66	else
67	head=\$(git hash-object -t tree --stdin </dev/null)
68	fi
69	
70	if ! git diff-index --quiet --cached --ignore-submodules \$head --
71	then
72	die "Working directory has staged changes"
73	fi
74	
75	if ! git read-tree -u -m "\$commit"
76	then
77	die "Could not update working tree to new HEAD"
78	fi