

Dateiauswertung

GLEICH

.git/hooks/pre-push.sample

Branch 1	main
Branch 2	current
Datei	.git/hooks/pre-push.sample
Typ	Datei

Bewertung

SHA-256 identisch.

Dateiinhalt / Vergleich

1	#!/bin/sh
2	
3	# An example hook script to verify what is about to be pushed. Called by "git
4	# push" after it has checked the remote status, but before anything has been
5	# pushed. If this script exits with a non-zero status nothing will be pushed.
6	#
7	# This hook is called with the following parameters:
8	#
9	# \$1 -- Name of the remote to which the push is being done
10	# \$2 -- URL to which the push is being done
11	#
12	# If pushing without using a named remote those arguments will be equal.
13	#
14	# Information about the commits which are being pushed is supplied as lines to
15	# the standard input in the form:
16	#
17	# <local ref> <local oid> <remote ref> <remote oid>
18	#
19	# This sample shows how to prevent push of commits where the log message starts
20	# with "WIP" (work in progress).
21	
22	remote="\$1"
23	url="\$2"
24	
25	zero=\$(git hash-object --stdin </dev/null tr '[0-9a-f]' '0')
26	
27	while read local_ref local_oid remote_ref remote_oid
28	do
29	if test "\$local_oid" = "\$zero"
30	then

31	# Handle delete
32	:
33	else
34	if test "\$remote_oid" = "\$zero"
35	then
36	# New branch, examine all commits
37	range="\$local_oid"
38	else
39	# Update to existing branch, examine new commits
40	range="\$remote_oid..\$local_oid"
41	fi
42	
43	# Check for WIP commit
44	commit=\$(git rev-list -n 1 --grep '^WIP' "\$range")
45	if test -n "\$commit"
46	then
47	echo >&2 "Found WIP commit in \$local_ref, not pushing"
48	exit 1
49	fi
50	fi
51	done
52	
53	exit 0