

Dateiauswertung

GLEICH

.git/hooks/pre-commit.sample

Branch 1	main
Branch 2	current
Datei	.git/hooks/pre-commit.sample
Typ	Datei

Bewertung

SHA-256 identisch.

Dateiinhalt / Vergleich

1	#!/bin/sh
2	#
3	# An example hook script to verify what is about to be committed.
4	# Called by "git commit" with no arguments. The hook should
5	# exit with non-zero status after issuing an appropriate message if
6	# it wants to stop the commit.
7	#
8	# To enable this hook, rename this file to "pre-commit".
9	
10	if git rev-parse --verify HEAD >/dev/null 2>&1
11	then
12	against=HEAD
13	else
14	# Initial commit: diff against an empty tree object
15	against=\$(git hash-object -t tree /dev/null)
16	fi
17	
18	# If you want to allow non-ASCII filenames set this variable to true.
19	allownonascii=\$(git config --type=bool hooks.allownonascii)
20	
21	# Redirect output to stderr.
22	exec 1>&2
23	
24	# Cross platform projects tend to avoid non-ASCII filenames; prevent
25	# them from being added to the repository. We exploit the fact that the
26	# printable range starts at the space character and ends with tilde.
27	if ["\$allownonascii" != "true"] &&
28	# Note that the use of brackets around a tr range is ok here, (it's
29	# even required, for portability to Solaris 10's /usr/bin/tr), since
30	# the square bracket bytes happen to fall in the designated range.

31	test \$(git diff-index --cached --name-only --diff-filter=A -z \$against
32	LC_ALL=C tr -d '[--]\0' wc -c) != 0
33	then
34	cat <<\EOF
35	Error: Attempt to add a non-ASCII file name.
36	
37	This can cause problems if you want to work with people on other platforms.
38	
39	To be portable it is advisable to rename the file.
40	
41	If you know what you are doing you can disable this check using:
42	
43	git config hooks.allownonascii true
44	EOF
45	exit 1
46	fi
47	
48	# If there are whitespace errors, print the offending file names and fail.
49	exec git diff-index --check --cached \$against --