

Dateiauswertung

GLEICH

.git/hooks/prepare-commit-msg.sample

Branch 1	main
Branch 2	current
Datei	.git/hooks/prepare-commit-msg.sample
Typ	Datei

Bewertung

SHA-256 identisch.

Dateiinhalt / Vergleich

1	#!/bin/sh
2	#
3	# An example hook script to prepare the commit log message.
4	# Called by "git commit" with the name of the file that has the
5	# commit message, followed by the description of the commit
6	# message's source. The hook's purpose is to edit the commit
7	# message file. If the hook fails with a non-zero status,
8	# the commit is aborted.
9	#
10	# To enable this hook, rename this file to "prepare-commit-msg".
11	
12	# This hook includes three examples. The first one removes the
13	# "# Please enter the commit message..." help message.
14	#
15	# The second includes the output of "git diff --name-status -r"
16	# into the message, just before the "git status" output. It is
17	# commented because it doesn't cope with --amend or with squashed
18	# commits.
19	#
20	# The third example adds a Signed-off-by line to the message, that can
21	# still be edited. This is rarely a good idea.
22	
23	COMMIT_MSG_FILE=\$1
24	COMMIT_SOURCE=\$2
25	SHA1=\$3
26	
27	/usr/bin/perl -i.bak -ne 'print unless(m/^\. Please enter the commit message/..m/^\\$)/' "\$COMMIT_MSG_FILE"
28	
29	# case "\$COMMIT_SOURCE,\$SHA1" in
30	# , template,)

31	# /usr/bin/perl -i.bak -pe '
32	# print "\n" . `git diff --cached --name-status -r`
33	# if /^#/ && \$first++ == 0' "\$COMMIT_MSG_FILE" ;;
34	# *) ;;
35	# esac
36	
37	# SOB=\$(git var GIT_COMMITTER_IDENT sed -n 's/^\(.*>\).*\$/Signed-off-by: \1/p')
38	# git interpret-trailers --in-place --trailer "\$SOB" "\$COMMIT_MSG_FILE"
39	# if test -z "\$COMMIT_SOURCE"
40	# then
41	# /usr/bin/perl -i.bak -pe 'print "\n" if !\$first_line++' "\$COMMIT_MSG_FILE"
42	# fi