

sim2diss {smacof}

R Documentation

Converts similarities to dissimilarities

Description

Utility function for converting similarities into dissimilarities. Different methods are provided.

Usage

```
sim2diss(s, method = "corr", to.dist = FALSE)
```

Arguments

s

Similarity matrix (not necessarily symmetric, nor square)

method

Various methods for converting similarities into dissimilarities: "corr", "reverse", "reciprocal", "ranks", "exp", "Gaussian", "cooccurrence", "gravity", "confusion", "transition", "membership", "probability", or an integer value from which the similarity is subtracted

to.dist

If TRUE, object of class dist is produced

Details

The conversion formulas for the various methods can be found in the package vignette.

Value

Returns dissimilarities either as matrix or as dist object.

Examples

```
## Convert crimes data (correlations)
```

```
data(crimes)
```

```
crimeD <- sim2diss(crimes, method = "corr", to.dist = TRUE)
```

```
## Convert Wish data (similarities) by subtracting from 7
```

```
data(wish)
```

```
wishD <- sim2diss(wish, method = 7, to.dist = TRUE)
```

```
## Convert Ekman data (similarities) into dissimilarities
```

```
data(ekman)
```

```
ekmanD <- sim2diss(ekman, method = "confusion", to.dist = TRUE)
```

```
## Convert album ratings (rectangular similarities) by reversing the ratings
```

```
data(RockHard)
```

```
rockD1 <- sim2diss(RockHard[,5:18], method = "reverse")
```

[Package smacof version 1.10-8 Index]