



79.95 EUR

incl. 19% VAT, plus shipping

- USB Interface !
- 4-wire resistive!
- EETI / EGALAX !
- Single Touch!

4-wire resistive touchscreen controller (EETI/EGALAX driver compatible)

## Hardware

- Power Requirements: +5VDC (max. 100mA, typical 70mA, 50mV peak to peak max ripple)
- Protocol USB: Max. 160 points/sec
- Report Rate USB: Max. 160 points/sec
- Response Time Max. 20 ms
- Max. resolution: 4096x4096
- Regulatory Approvals FCC-B, CE
- Pin Out Definition X, Y, X, Y
- Panel Resistance 200 ~ 900 ohm (pin to pin on the same layer)
- O/S support Windows, DOS, MAC, QNX, Android, Linux

## **Software Features**

- Calibration Fast Full oriental 4 points position
- Compensation 1. Accuracy 25 points linearity position, 2. Edge compensation
- Draw Test Position and linearity verification
- Controller Setting 1. Support multiple controllers, 2. Dynamical add/ remove controllers, 3. Change controller interface without reboot
- Languages Support 10 languages for Windows
- Mouse Emulator 1. Right/ left button emulation, 2. Click/ drawing mode
- Sound Notification 1. No sound,2. Touch down,3. Touch up
- Double Click 1. Configurable double click speed, 2. Configurable double click area
- COM Port Support 1. Support COM1~COM256 for Windows and Linux, 2. Support COM1~COM8 for DOS
- Display Support 1. Support monitor/ display rotation, 2. Support multiple monitors, 3. Support split monitor

Touchscreen drivers