

Exercise 02 - Decomposing the ProductSrv

Required Services

The following services are involved and have to be started before the final exercise validation:

- CustomerSrv (<http://localhost:8000>)
- NotificationSrv (<http://localhost:8010>)
- OrderProcessSrv (<http://localhost:8020>)
- OrderSrv (<http://localhost:8030>)
- ProductSrvFacade (<http://localhost:8040>)
- ProductSrv (<http://localhost:8050>)
- CategorySrv (<http://localhost:8060>)
- WarehouseSrv (<http://localhost:8070>)
- WebUI (<http://localhost:5000>)
- Apache Zookeeper (<localhost:2181>)
- Apache Kafka (<localhost:9092>)

Description

The **ProductSrv** has grown over time and is now fairly large compared to the other services. It is responsible for several different entities, namely products, product categories, and the available amount of product copies in the warehouse. The following resources are currently provided:

```
GET      /categories (experiment.webshop.products.resources.ProductResource)
POST     /categories (experiment.webshop.products.resources.ProductResource)
DELETE   /categories/{id} (experiment.webshop.products.resources.ProductResource)
GET      /categories/{id} (experiment.webshop.products.resources.ProductResource)
PUT      /categories/{id} (experiment.webshop.products.resources.ProductResource)

GET      /products (experiment.webshop.products.resources.ProductResource)
POST     /products (experiment.webshop.products.resources.ProductResource)
DELETE   /products/{id} (experiment.webshop.products.resources.ProductResource)
GET      /products/{id} (experiment.webshop.products.resources.ProductResource)
PUT      /products/{id} (experiment.webshop.products.resources.ProductResource)

GET      /products/{id}/availability
(experiment.webshop.products.resources.ProductResource)
PUT      /products/{id}/availability
(experiment.webshop.products.resources.ProductResource)
```

The lead developer has decided to split up the **ProductSrv** to increase maintainability and scaling efficiency. Two new services will be created: A **CategorySrv** handling product categories and a **WarehouseSrv** responsible for product availability. The CRUD operations related to products will remain in the **ProductSrv**. Runnable skeleton projects for the new services have already been created, they just provide no resources yet.

Since this change has been expected some months ago, precautions have been taken. First, the different capabilities of the `ProductSrv` have already been decomposed in separate classes (one `Resource` and one `Repository` class per capability). And second, the `ProductSrvFacade` shields the `ProductSrv` from all consumers so that it will be the only component that has to be adjusted with the new URLs.

Tasks

1. **Move the product category related functionality.** Move all functionality related to product categories from the `ProductSrv` to the new `CategorySrv`. It already has a resource class (`experiment.webshop.categories.resources.CategoryResource`) and a repository class (`experiment.webshop.categories.db.CategoryRepository`) that can be replaced (beware of the new package name though). Make sure to also copy all necessary model classes to the `experiment.webshop.categories.api` package that is currently empty. In the end, the following resources should be provided by the new `CategorySrv` instead:

```
GET      /categories (experiment.webshop.categories.resources.CategoryResource)
POST     /categories (experiment.webshop.categories.resources.CategoryResource)
DELETE   /categories/{id} (experiment.webshop.categories.resources.CategoryResource)
GET      /categories/{id} (experiment.webshop.categories.resources.CategoryResource)
PUT      /categories/{id} (experiment.webshop.categories.resources.CategoryResource)
```

2. **Move the product availability related functionality.** Move all functionality related to product availability from the `ProductSrv` to the new `WarehouseSrv`. It already has a resource class (`experiment.webshop.warehouse.resources.WarehouseResource`) and a repository class (`experiment.webshop.warehouse.db.WarehouseRepository`) that can be replaced (beware of the new package name though). Make sure to also copy all necessary model classes to the `experiment.webshop.warehouse.api` package that is currently empty. In the end, the following resources should be provided by the new `WarehouseSrv` instead:

```
GET      /products/{id}/availability
(experiment.webshop.warehouse.resources.WarehouseResource)
PUT      /products/{id}/availability
(experiment.webshop.warehouse.resources.WarehouseResource)
```

3. **Fix the `ProductSrvFacade`.** Since we moved functionality to new endpoints, we need to adapt the invocation URLs for service consumers. This can be done centrally at the `ProductSrvFacade` in the `experiment.webshop.products.resources.ProductFacadeResource`. A `PRODUCT_SRV_ENDPOINT` already exists. The usage of this endpoint stays the same for product related operations, but for category and warehouse operations, new endpoint variables have to be configured.

Validation

When you are finished with all tasks, make sure all required services (see [Required Services](#)) and the exercise validation UI is up and running (if not, execute `exercise-validation/build-and-run-validation-ui.bat`) and then navigate to `http://localhost:5001` (it is important to start from this page, because it will

determine which version you are working on). Click on [Exercise 02](#) and then on [Start Validation](#). If every check is successful (`status: true`), pause your stopwatch and notify an experiment admin for the manual validation part and to write down your time.