Networking Academy

Christian Dunn 06/19/2023 CST 329 03A Code: 773777

Packet Tracer - Basic Device Configuration

Topology

You will receive one of three possible topologies.

Addressing Table

Device	Interface	IP Address	Default Gateway
Floor - 14	G0/0	172.14.5.1/24	N/A
		2001:DB8:CAFE:1::1/64	
		FE80::1	
	G0/1	172.14.10.1/24	N/A
		2001:DB8:CAFE:2::/64	
Room - 145	VLAN 1		172.14.5.1
Room - 146	VLAN 1	172.14.10.254	172.14.10.1
Manager - A	NIC	172.14.5.50/24	172.14.5.1
		2001:DB8:CAFE:1::2/64	FE80::1
Reception - A	NIC	172.14.5.60/24	172.14.5.1
		2001:DB8:CAFE:1::3/64	FE80::1
Manager - B	NIC	172.14.10.50/24	172.14.10.1
		2001:DB8:CAFE:2::2/64	FE80::1
Reception - B	NIC	172.14.10.60/24	172.14.10.1
		2001:DB8:CAFE:2::3/64	FE80::1

Objectives

- Complete the network documentation.
- Perform basic device configurations on a router and a switch.
- Verify connectivity and troubleshoot any issues.

Scenario

Your network manager is impressed with your performance in your job as a LAN technician. She would like you to demonstrate your ability to configure a router that connects two LANs. Your tasks include configuring

© 2013 - 2025 Cisco and/or its affiliates. All rights reserved. Cisco Public

basic settings on a router and a switch using the Cisco IOS. You will also configure IPv6 addresses on network devices and hosts. You will then verify the configurations by testing end-to-end connectivity. You goal is to establish connectivity between all devices.

Note: The VLAN1 interface on will not be reachable over IPv6.

In this activity you will configure the router, switch, and the **PC hosts**.

Note: Packet Tracer will not score some configured values, however these values are required to accomplish full connectivity in the network.

Requirements

- Provide the missing information in the Addressing Table.







© 2013 - 2025 Cisco and/or its affiliates. All rights reserved. Cisco Public





- Name the router and the second switch . You will not be able to access the switch.

© 2013 - 2025 Cisco and/or its affiliates. All rights reserved. Cisco Public



© 2013 - 2025 Cisco and/or its affiliates. All rights reserved. Cisco Public



- Use **cisco** as the user EXEC password for all lines.

© 2013 - 2025 Cisco and/or its affiliates. All rights reserved. Cisco Public

© 2013 - 2025 Cisco and/or its affiliates. All rights reserved. Cisco Public

© 2013 - 2025 Cisco and/or its affiliates. All rights reserved. Cisco Public



© 2013 - 2025 Cisco and/or its affiliates. All rights reserved. Cisco Public

- Use **class** as the encrypted privileged EXEC password.

© 2013 - 2025 Cisco and/or its affiliates. All rights reserved. Cisco Public

© 2013 - 2025 Cisco and/or its affiliates. All rights reserved. Cisco Public

- Encrypt all plaintext passwords.

© 2013 - 2025 Cisco and/or its affiliates. All rights reserved. Cisco Public

© 2013 - 2025 Cisco and/or its affiliates. All rights reserved. Cisco Public



- Configure an appropriate banner.

© 2013 - 2025 Cisco and/or its affiliates. All rights reserved. Cisco Public

© 2013 - 2025 Cisco and/or its affiliates. All rights reserved. Cisco Public



- Configure IPv4 and IPv6 addressing for the switch according to the Addressing Table.

© 2013 - 2025 Cisco and/or its affiliates. All rights reserved. Cisco Public





- Configure IPv4 and IPv6 addressing for the switch according to the Addressing Table.

© 2013 - 2025 Cisco and/or its affiliates. All rights reserved. Cisco Public

- The hosts are partially configured. Complete the IPv4 addressing, and fully configure the IPv6 addresses according to the Addressing Table.



© 2013 - 2025 Cisco and/or its affiliates. All rights reserved. Cisco Public



© 2013 - 2025 Cisco and/or its affiliates. All rights reserved. Cisco Public



© 2013 - 2025 Cisco and/or its affiliates. All rights reserved. Cisco Public



- Document interfaces with descriptions, including the VLAN 1 interface.

© 2013 - 2025 Cisco and/or its affiliates. All rights reserved. Cisco Public



- Save your configurations.

© 2013 - 2025 Cisco and/or its affiliates. All rights reserved. Cisco Public

© 2013 - 2025 Cisco and/or its affiliates. All rights reserved. Cisco Public

- Verify connectivity between all devices. All devices should be able to ping all other devices with IPv4 and IPv6.

© 2013 - 2025 Cisco and/or its affiliates. All rights reserved. Cisco Public



Somehow the Switch was disconnected from the Router, but they were initially connected and I don't know the solution. It says the disconnection is locked.

- Troubleshoot and document any issues.

© 2013 - 2025 Cisco and/or its affiliates. All rights reserved. Cisco Public

- Implement the solutions necessary to enable and verify full end-to-end connectivity.

Note: Click **Check Results** button to see your progress. Click the **Reset Activity** button to generate a new set of requirements.

© 2013 - 2025 Cisco and/or its affiliates. All rights reserved. Cisco Public