

CddInterface

Gap interface to Cdd package

0.1

18/11/2015

Kamal Saleh

Kamal Saleh

Email: kamal.saleh@rwth-aachen.de

Homepage: Kamal.saleh@rwth-aachen.de

Address: Templergraben

Contents

1	Introduction	3
1.1	Why CddInterface	3
1.2	H-representation and V-representation of polyhedra	3
2	Creating polyhedra and their Operations	5
2.1	Creating a polyhedron	5
2.2	Some operations on polyhedra	6
3	Linear Programs	10
3.1	Creating and solving linear programs	10
4	Attributes and properties	12
4.1	Attributes and properties of polyhedron	12
	Index	16

Chapter 1

Introduction

1.1 Why CddInterface

We know that every convex polyhedron has two representations, one as the intersection of finite half-spaces and the other as Minkowski sum of the convex hull of finite points and the nonnegative hull of finite directions. These are called H-representation and V-representation, respectively.

CddInterface is basically written to translate between these two representations.

1.2 H-representation and V-representation of polyhedra

Let us start by introducing the H-representation. Let A be $m \times d$ matrix and let b be a column m -vector. The H-representation of the polyhedron defined by the system $b + Ax \geq 0$ of m inequalities and d variables $x = (x_1, \dots, x_d)$ is as follows:

H-representation

linearity $t, [i_1, i_2, \dots, i_t]$

begin

$m \times (d + 1)$ numbertype

$b \quad A$

end

The linearity line is added when we want to specify that some rows of the system $b + Ax$ are equalities. That is, $k \in \{i_1, i_2, \dots, i_t\}$ means that the row k of the system $b + Ax$ is specified to be equality. For example, the H-representation of the polyhedron defined by the following system:

$$4 - 3x_1 + 6x_2 - 5x_4 = 0$$

$$1 + 2x_1 - 2x_2 - 7x_3 \geq 0$$

$$-3x_2 + 5x_4 = 0$$

is as follows:

H-representation

linearity 2, [1, 3]

begin

3×5 rational

4 -3 6 0 -5

1 2 -2 -7 0

0 0 -3 0 5

end

Next we define Polyhedra V-format. Let P be represented by n generating points and s generating directions (rays) as

$$P = \text{conv}(v_1, \dots, v_n) + \text{nonneg}(r_{n+1}, \dots, r_{n+s}).$$

Then the Polyhedra V-format is for P is:

V-representation

linearity t , $[i_1, i_2, \dots, i_t]$

begin

$(n+s) \times (d+1)$ numbertype

1 v_1

\vdots \vdots

1 v_n

0 r_{n+1}

\vdots \vdots

0 r_{n+s}

end

In the above format the generating points and generating rays may appear mixed in arbitrary order. Linearity for V-representation specifies a subset of generators whose coefficients are relaxed to be free. That is, $k \in \{i_1, i_2, \dots, i_t\}$ specifies that the k -th generator is specified to be free. This means for each such a ray r_k , the line generated by r_k is in the polyhedron, and for each such a vertex v_k , its coefficient is no longer nonnegative but still the coefficients for all v_i 's must sum up to one.

For example the V-representation of the polyhedron defined as

$$P := \text{conv}((2,3), (-2,-3), (3,5)) + \text{nonneg}((1,2), (-1,-2), (2,11))$$

V-representation

linearity 2, $[1,3]$

begin

4×3 numbertype

1 2 3

1 3 5

0 1 2

0 2 11

end

Chapter 2

Creating polyhedra and their Operations

2.1 Creating a polyhedron

2.1.1 Cdd_PolyhedronByInequalities

▷ Cdd_PolyhedronByInequalities(arg) (function)

Returns: a CddPolyhedron Object

The function takes a list in which every entry represents an inequality(or equality). In case we want some entries to represent equalities we should refer in a second list to their indices.

Example

```
gap> A:= Cdd_PolyhedronByInequalities( [ [ 0, 1, 0 ], [ 0, 1, -1 ] ] );
< Polyhedron given by its H-representation >
gap> Display( A );
H-representation
begin
  2 X 3  rational

    0   1   0
    0   1  -1
end
gap> B:= Cdd_PolyhedronByInequalities( [ [ 0, 1, 0 ], [ 0, 1, -1 ] ], [ 2 ] );
< Polyhedron given by its H-representation >
gap> Display( B );
H-representation
Linearity 1, [ 2 ]
begin
  2 X 3  rational

    0   1   0
    0   1  -1
end
```

2.1.2 Cdd_PolyhedronByGenerators

▷ Cdd_PolyhedronByGenerators(arg) (function)

Returns: a CddPolyhedron Object

The function takes a list in which every entry represents a vertex in the ambient vector space. In case we want some vertices to be free(the vertex and its negative belong to the polyhedron) we should refer in a second list to their indices .

Example

```
gap> A:= Cdd_PolyhedronByGenerators( [ [ 0, 1, 3 ], [ 1, 4, 5 ] ] );
< Polyhedron given by its V-representation >
gap> Display( A );
V-representation
begin
  2 X 3  rational

    0  1  3
    1  4  5
end
gap> B:= Cdd_PolyhedronByGenerators( [ [ 0, 1, 3 ] ], [ 1 ] );
< Polyhedron given by its V-representation >
gap> Display( B );
V-representation
Linearity 1, [ 1 ]
begin
  1 X 3  rational

    0  1  3
end
```

2.2 Some operations on polyhedra

2.2.1 Cdd_Canonicalize (for IsCddPolyhedron)

▷ Cdd_Canonicalize(poly) (operation)

Returns: a CddPolyhedron Object

The function takes a polyhedron and reduces its defining inequalities (generators set) by deleting all redundant inequalities (generators).

Example

```
gap> A:= Cdd_PolyhedronByInequalities( [ [ 0, 2, 6 ], [ 0, 1, 3 ], [1, 4, 10 ] ] );
< Polyhedron given by its H-representation >
gap> B:= Cdd_Canonicalize( A );
< Polyhedron given by its H-representation >
gap> Display( B );
H-representation
begin
  2 X 3  rational

    0  1  3
    1  4  10
end
```

2.2.2 Cdd_V_Rep (for IsCddPolyhedron)

▷ Cdd_V_Rep(poly) (operation)

Returns: a CddPolyhedron Object

The function takes a polyhedron and returns its reduced V-representation.

2.2.3 Cdd_H_Rep (for IsCddPolyhedron)

▷ Cdd_H_Rep(poly)

(operation)

Returns: a CddPolyhedron Object

The function takes a polyhedron and returns its reduced H-representation.

Example

```
gap> A:= Cdd_PolyhedronByInequalities( [ [ 0, 1, 1 ], [0, 5, 5 ] ] );
Polyhedron given by its H-representation >
gap> B:= Cdd_V_Rep( A );
< Polyhedron given by its V-representation >
gap> Display( B );
V-representation
Linearity 1, [ 2 ]
begin
  2 X 3  rational

    0   1   0
    0  -1   1
end
gap> C:= Cdd_H_Rep( B );
< Polyhedron given by its H-representation >
gap> Display( C );
H-representation
begin
  1 X 3  rational

    0   1   1
end
gap> D:= Cdd_PolyhedronByInequalities( [ [ 0, 1, 1, 34, 22, 43 ],
> [ 11, 2, 2, 54, 53, 221 ], [33, 23, 45, 2, 40, 11 ] ] );
< Polyhedron given by its H-representation >
gap> Cdd_V_Rep( D );
< Polyhedron given by its V-representation >
gap> Display( last );
V-representation
Linearity 2, [ 5, 6 ]
begin
  6 X 6  rational

    1  -743/14  369/14  11/14    0    0
    0   -1213   619    22     0    0
    0     -1     1     0     0    0
    0    764   -390   -11     0    0
    0  -13526  6772    99    154   0
    0 -116608  59496  1485     0   154
end
```

2.2.4 Cdd_FourierProjection (for IsCddPolyhedron, IsInt)

▷ `Cdd_FourierProjection(poly, i)` (operation)

Returns: a CddPolyhedron Object

The function returns the Fourier projection of the polyhedron in the subspace $(O, x_1, \dots, x_{i-1}, x_{i+1}, \dots, x_n)$ after applying the Fourier elimination algorithm to get rid of the variable x_i .

To illustrate this projection, Let $P = \text{Conv}((1,2), (4,5))$ in \mathbb{Q}^2 .

To find its projection on the subspace (O, x_1) , we apply the Fourier elimination to get rid of x_2

Example

```
gap> P:= Cdd_PolyhedronByGenerators( [ [ 1, 1, 2 ], [ 1, 4, 5 ] ] );
< Polyhedron given by its H-representation >
gap> H:= Cdd_H_Rep( P );
< Polyhedron given by its H-representation >
gap> Display( H );
H-representation
Linearity 1, [ 1 ]
begin
  3 X 3  rational

  -1  -1  1
  4   -1  0
  -1   1  0
end
gap> P_x1:= Cdd_FourierProjection( H, 2);
< Polyhedron given by its H-representation >
gap> Display( P_x1 );
H-representation
Linearity 1, [ 3 ]
begin
  3 X 3  rational

  4  -1  0
  -1  1  0
  0  0  1
end
gap> Display( Cdd_V_Rep( P_x1 ) );
V-representation
begin
  2 X 3  rational

  1  1  0
  1  4  0
end
```

Let again $Q = \text{Conv}((2,3,4), (2,4,5)) + \text{nonneg}((1,1,1))$, and let us compute its projection on (O, x_2, x_3)

Example

```
gap> Q:= Cdd_PolyhedronByGenerators( [ [1,2,3,4], [1,2,4,5], [0,1,1,1] ] );
< Polyhedron given by its V-representation >
gap> R:= Cdd_H_Rep( Q );
< Polyhedron given by its H-representation >
```



```

gap> Display( R );
H-representation
Linearity 1, [ 1 ]
begin
  4 X 4  rational

  -1  0  -1  1
   2  1  -1  0
  -2  1   0  0
  -1 -1   1  0
end
gap> P_x2_x3:= Cdd_FourierProjection( R, 1);
< Polyhedron given by its H-representation >
gap> Display( P_x2_x3 );
H-representation
Linearity 2, [ 1, 3 ]
begin
  3 X 4  rational

  -1  0  -1  1
  -3  0   1  0
   0  1   0  0
end
gap> Display( Cdd_V_Rep( last ) ) ;
V-representation
begin
  2 X 4  rational

   0  0  1  1
   1  0  3  4
end

```

Chapter 3

Linear Programs

3.1 Creating and solving linear programs

3.1.1 Cdd_LinearProgram (for IsCddPolyhedron, IsString, IsList)

▷ `Cdd_LinearProgram(poly, str, obj)` (operation)

Returns: a `CddLinearProgram` Object

The function takes three variables. The first is a polyhedron `poly`, the second `str` should be `max` or `min` and the third `obj` is the objective.

3.1.2 Cdd_SolveLinearProgram (for IsCddLinearProgram)

▷ `Cdd_SolveLinearProgram(lp)` (operation)

Returns: a list if the program is optimal, otherwise returns the value 0

The function takes a linear program. If the program is optimal, the function returns a list of two entries: the solution vector and the optimal value of the objective, otherwise it returns the value 0.

To illustrate the using of these functions, let us solve the linear program given by:

Maximize $P(x,y) = 1 - 2x + 5y$, with

$$100 \leq x \leq 200$$

$$80 \leq y \leq 170$$

$$y \geq -x + 200$$

We bring the inequalities to the form $b + AX \geq 0$, we get:

$$-100 + x \geq 0$$

$$200 - x \geq 0$$

$$-80 + y \geq 0$$

$$170 - y \geq 0$$

$$-200 + x + y \geq 0$$

Example

```
gap> A:= Cdd_PolyhedronByInequalities( [ [ -100, 1, 0 ], [ 200, -1, 0 ],  
> [ -80, 0, 1 ], [ 170, 0, -1 ], [ -200, 1, 1 ] ] );  
< Polyhedron given by its H-representation >  
gap> Lp:= Cdd_LinearProgram( A, "max", [1, -2, 5] );  
< Linear program >
```

```

gap> S:= Cdd_SolveLinearProgram( Lp );
[ [ 100, 170 ], 651 ]
gap> B:= Cdd_V_Rep( A );
< Polyhedron given by its V-representation >
gap> Display( Lp );
Linear program given by:
H-representation
begin
  5 X 3  rational

  -100    1    0
  200   -1    0
  -80     0    1
  170     0   -1
  -200    1    1
end
max  [ 1, -2, 5 ]
gap> Display( B );
V-representation
begin
  5 X 3  rational

  1  100  170
  1  100  100
  1  120   80
  1  200   80
  1  200  170
end

```

So the optimal solution is $(x = 100, y = 170)$ with optimal value $p = 1 - 2(100) + 5(170) = 651$.

Chapter 4

Attributes and properties

4.1 Attributes and properties of polyhedron

4.1.1 Cdd_Dimension (for IsCddPolyhedron)

▷ `Cdd_Dimension(poly)` (attribute)
Returns: The dimension of the polyhedron

4.1.2 Cdd_AmbientSpaceDimension (for IsCddPolyhedron)

▷ `Cdd_AmbientSpaceDimension(poly)` (attribute)
Returns: The dimension of the ambient space of the polyhedron

4.1.3 Cdd_GeneratingVertices (for IsCddPolyhedron)

▷ `Cdd_GeneratingVertices(poly)` (attribute)
Returns: The reduced generating vertices of the polyhedron

4.1.4 Cdd_GeneratingRays (for IsCddPolyhedron)

▷ `Cdd_GeneratingRays(poly)` (attribute)
Returns: The reduced generating rays of the polyhedron

4.1.5 Cdd_Equalities (for IsCddPolyhedron)

▷ `Cdd_Equalities(poly)` (attribute)
Returns: The reduced defining equalities of the polyhedron

4.1.6 Cdd_Inequalities (for IsCddPolyhedron)

▷ `Cdd_Inequalities(poly)` (attribute)
Returns: The reduced defining inequalities of the polyhedron

4.1.7 Cdd_InteriorPoint (for IsCddPolyhedron)

▷ `Cdd_InteriorPoint(poly)` (attribute)
Returns: An interior point of the polyhedron

4.1.8 Cdd_Faces (for IsCddPolyhedron)

▷ Cdd_Faces(*poly*) (attribute)

Returns: All faces with their dimensions

This function takes a H-represented polyhedron *poly* and returns a list. Every entry in this list is a again a list, contains the dimension and linearity of the face defined as a polyhedron over the same system of inequalities.

4.1.9 Cdd_FacesWithInteriorPoints (for IsCddPolyhedron)

▷ Cdd_FacesWithInteriorPoints(*poly*) (attribute)

Returns: All faces with their dimensions and an interior point in each face

This function takes a H-represented polyhedron *poly* and returns a list. Every entry in this list is a again a list, contains the dimension, linearity of the face defined as a polyhedron over the same system of inequalities and an interior point in the face.

4.1.10 Cdd_Facets (for IsCddPolyhedron)

▷ Cdd_Facets(*poly*) (attribute)

Returns: All facets with their dimensions

This function takes a H-represented polyhedron *poly* and returns a list. Every entry in this list is a again a list, contains the dimension, linearity of the facet defined as a polyhedron over the same system of inequalities.

4.1.11 Cdd_Lines (for IsCddPolyhedron)

▷ Cdd_Lines(*poly*) (attribute)

Returns: All lines in the polyhedron

This function takes a H-represented polyhedron *poly* and returns a list. Every entry in this list is the linearity of a line defined as a polyhedron over the same system of inequalities.

4.1.12 Cdd_Vertices (for IsCddPolyhedron)

▷ Cdd_Vertices(*poly*) (attribute)

Returns: All Vertices

This function takes a H-represented polyhedron *poly* and returns a list. Every entry in this list is the linearity of a vertex defined as a polyhedron over the same system of inequalities.

4.1.13 Cdd_IsEmpty (for IsCddPolyhedron)

▷ Cdd_IsEmpty(*poly*) (property)

Returns: true if the polyhedron is empty and false otherwise

4.1.14 Cdd_IsCone (for IsCddPolyhedron)

▷ Cdd_IsCone(*poly*) (property)

Returns: true if the polyhedron is cone and false otherwise

4.1.15 Cdd_IsPointed (for IsCddPolyhedron)

▷ Cdd_IsPointed(poly)

(property)

Returns: true if the polyhedron is pointed and false otherwise

Example

```
gap> poly:= Cdd_PolyhedronByInequalities( [ [ 1, 3, 4, 5, 7 ], [ 1, 3, 5, 12, 34 ],
> [ 9, 3, 0, 2, 13 ] ], [ 1 ] );
< Polyhedron given by its H-representation >
gap> Cdd_InteriorPoint( poly );
[ -194/75, 46/25, -3/25, 0 ]
gap> Cdd_FacesWithInteriorPoints( poly );
[ [ 3, [ 1 ] ], [ -194/75, 46/25, -3/25, 0 ] ], [ 2, [ 1, 2 ],
[ -62/25, 49/25, -7/25, 0 ] ], [ 1, [ 1, 2, 3 ],
[ -209/75, 56/25, -8/25, 0 ] ], [ 2, [ 1, 3 ], [ -217/75, 53/25, -4/25, 0 ] ] ]
gap> Cdd_Dimension( poly );
3
gap> Cdd_IsPointed( poly );
false
gap> Cdd_IsEmpty( poly );
false
gap> Cdd_Faces( poly );
[ 3, [ 1 ] ], [ 2, [ 1, 2 ] ], [ 1, [ 1, 2, 3 ] ], [ 2, [ 1, 3 ] ] ]
gap> poly2:= Cdd_ExtendLinearity( poly, [1,2,3] );
< Polyhedron given by its H-representation >
gap> Display( poly2 );
H-representation
Linearity 3, [ 1, 2, 3 ]
begin
  3 X 5  rational

      1   3   4   5   7
      1   3   5  12  34
      9   3   0   2  13
end
Cdd_Dimension( poly1 );
Error, Variable: 'poly1' must have a value
not in any function at line 13 of *stdin*
Cdd_Dimension( poly2 );
1
gap> Cdd_Facets( poly );
[ [ 2, [ 1, 2 ] ], [ 2, [ 1, 3 ] ] ]
Cdd_GeneratingVertices( poly );
[ [ -209/75, 56/25, -8/25, 0 ] ]
gap> Cdd_GeneratingRays( poly );
[ [ -97, 369, -342, 75 ], [ 97, -369, 342, -75 ],
[ -8, -9, 12, 0 ], [ 23, -21, 3, 0 ] ]
gap> Cdd_Inequalities( poly );
[ [ 1, 3, 5, 12, 34 ], [ 9, 3, 0, 2, 13 ] ]
gap> Cdd_Equalities( poly );
[ [ 1, 3, 4, 5, 7 ] ]
gap> Cdd_FourierProjection( poly, 2);
< Polyhedron given by its H-representation >
gap> Display( last );
```

```
H-representation
Linearity 1, [ 3 ]
begin
  3 X 5  rational

    9    3    0    2   13
   -1   -3    0   23  101
    0    0    1    0    0
end
```

Index

CddInterface, [3](#)

Cdd_AmbientSpaceDimension
for IsCddPolyhedron, [12](#)

Cdd_Canonicalize
for IsCddPolyhedron, [6](#)

Cdd_Dimension
for IsCddPolyhedron, [12](#)

Cdd_Equalities
for IsCddPolyhedron, [12](#)

Cdd_Faces
for IsCddPolyhedron, [13](#)

Cdd_FacesWithInteriorPoints
for IsCddPolyhedron, [13](#)

Cdd_Facets
for IsCddPolyhedron, [13](#)

Cdd_FourierProjection
for IsCddPolyhedron, IsInt, [8](#)

Cdd_GeneratingRays
for IsCddPolyhedron, [12](#)

Cdd_GeneratingVertices
for IsCddPolyhedron, [12](#)

Cdd_H_Rep
for IsCddPolyhedron, [7](#)

Cdd_Inequalities
for IsCddPolyhedron, [12](#)

Cdd_InteriorPoint
for IsCddPolyhedron, [12](#)

Cdd_IsCone
for IsCddPolyhedron, [13](#)

Cdd_IsEmpty
for IsCddPolyhedron, [13](#)

Cdd_IsPointed
for IsCddPolyhedron, [14](#)

Cdd_LinearProgram
for IsCddPolyhedron, IsString, IsList, [10](#)

Cdd_Lines
for IsCddPolyhedron, [13](#)

Cdd_PolyhedronByGenerators, [5](#)

Cdd_PolyhedronByInequalities, [5](#)

Cdd_SolveLinearProgram
for IsCddLinearProgram, [10](#)

Cdd_Vertices
for IsCddPolyhedron, [13](#)

Cdd_V_Rep
for IsCddPolyhedron, [6](#)