

Database Labs Case Study

This document contains the details of the database that you will set up to do your lab work.
It contains four sections:


1. Data model of the lab database
2. The data contained in each of the tables
3. A set of SQL queries that allow you to investigate SQL through examples
4. A set of questions that ask you to write your own SQL queries

There are around **16 SQL** queries for you to complete each week.

Before you can run these queries in this document you must download from LMS and run in MySQL Workbench the script to create the tables and populate them with data.

Answers for the SQL writing questions will be provided around week 8.

Section 1: Physical data model



This database is the core of an information system used to manage a large city department store.

The store has several departments, both retail and administrative, located on different floors of a building. Each department has several employees working for it, and one boss who manages it: details of employees and bosses are stored in the same table.

The retail departments make sales. The items they sell are delivered by suppliers.
Details of sales, suppliers and deliveries are recorded in the database.

Section 2: Data in the tables

Delivery

DeliveryID	DeliveryQTY	ItemID	DepartmentID	SupplierID
51	50	14	6	105
52	10	14	8	105
53	10	14	3	105
54	10	14	4	105
55	10	14	5	105
56	10	14	7	105
57	50	18	6	101
58	10	9	6	101
59	10	11	6	101
60	25	10	6	101
61	2	17	6	101
62	1	17	4	105
63	20	18	4	103
64	1	9	8	103
65	15	11	6	103
66	1	17	8	103
67	5	17	7	102
68	3	17	6	104
69	5	1	3	105
70	15	8	3	105
71	1	8	3	101
72	1	8	3	102
73	1	8	3	103
74	1	8	3	104
75	5	8	6	105
NULL	NULL	NULL	NULL	NULL

DeliveryID	DeliveryQTY	ItemID	DepartmentID	SupplierID
76	5	8	8	105
77	5	8	4	105
78	5	8	5	105
79	5	8	7	105
80	10	14	6	102
81	1	18	6	102
82	1	9	6	102
83	10	11	6	102
84	5	10	6	102
85	5	18	8	102
86	5	13	7	102
87	5	19	7	102
88	2	20	7	102
89	5	15	6	102
90	5	12	6	102
91	10	15	8	102
92	10	12	8	102
93	2	15	7	102
94	2	12	7	102
95	5	18	4	105
96	2	1	4	105
97	20	8	4	106
98	20	14	4	106
99	1	17	4	106
100	3	6	3	105
101	3	3	3	105
NULL	NULL	NULL	NULL	NULL

Department

DepartmentID	DepartmentName	DepartmentFloor	DepartmentPhone	ManagerID
1	Management	5	34	1
2	Accounting	5	35	5
3	Clothes	2	24	4
4	Equipment	3	57	3
5	Furniture	4	14	3
6	Navigation	1	41	3
7	Recreation	2	29	4
8	Books	1	81	4
9	Purchasing	5	36	7
10	Personnel	5	37	9
11	Marketing	5	38	2
NULL	NULL	NULL	NULL	NULL

Employee

EmployeeID	EmployeeName	EmployeeSalary	DepartmentID	BossID
1	Alice	75000.00	1	0
2	Ned	45000.00	11	1
3	Andrew	25000.00	11	2
4	Clare	22000.00	11	2
5	Todd	38000.00	2	1
6	Nancy	22000.00	2	5
7	Brier	43000.00	9	1
8	Sarah	56000.00	9	7
9	Sophie	35000.00	10	1
10	Sanjay	15000.00	6	3
11	Rita	15000.00	8	4
12	Gigi	16000.00	3	4
13	Maggie	16000.00	3	4
14	Paul	11000.00	4	3
15	James	15000.00	4	3
16	Pat	15000.00	5	3
17	Mark	15000.00	7	3
NULL	NULL	NULL	NULL	NULL

Item

ItemID	ItemName	ItemType	ItemColour
1	Boots - snakeproof	C	Green
2	Elephant polo stick	R	Bamboo
3	Stetson	C	Black
4	Camel saddle	R	Brown
5	Safari chair	F	Khaki
6	Hat - polar explorer	C	White
7	Hammock	F	Khaki
8	Pith helmet	C	Khaki
9	Geo positioning system	N	-
10	Map case	E	Brown
11	Map measure	N	-
12	How to Win Foreign ...	B	-
13	Pocket knife - Avon	E	Brown
14	Pocket knife - Nile	E	Brown
15	Exploring in 10 Easy ...	B	-
16	Safari cooking kit	F	-
17	Sextant	N	-
18	Compass	N	-
19	Tent - 2 person	F	Khaki
20	Tent - 8 person	F	Khaki
NULL	NULL	NULL	NULL

Sale

SaleID	SaleQTY	ItemID	DepartmentID
1001	2	1	3
1002	1	8	3
1003	1	17	6
1004	3	6	3
1005	5	8	4
1006	1	14	3
1007	1	14	7
1008	1	18	6
1009	1	9	6
1010	5	11	6
1011	1	9	8
1012	1	17	8
1013	3	14	8
1014	1	14	6
1015	1	14	4
1016	1	17	3
1017	1	17	4
1018	1	17	7
1019	1	17	5
1020	1	14	5
1021	1	15	8
1022	1	12	8
1023	1	18	8
1024	1	8	8
1025	1	2	7
1026	1	4	7
NULL	NULL	NULL	NULL

Supplier

SupplierID	SupplierName	SupplierPhone
101	Global Books & Maps	55244552
102	Nepalese Corp.	55244552
103	All Sports Manufacturing	55478252
104	Sweatshops Unlimited	55245552
105	All Points_ Inc.	54585252
106	Sao Paulo Manufacturing	54572752
NULL	NULL	NULL

Section 3: Example SQL queries

In this section there are about 60 queries that you can analyse and run yourself. Each includes:

- The task
 - these vary in difficulty and are colour coded
 - green – easy
 - blue - moderate
 - red – hard
- Comments
- A sample SQL query that answers the question
- The result of the query

Often there are several possible solutions, which is why we show the result so you can check your query if you do it differently. If a question is challenging, break it down into components.

Week 3

1. Find the names of all employees

This is the most simple query we can do

```
SELECT EmployeeName FROM Employee;
```

EmployeeName
Alice
Ned
Andrew
Clare
Todd
Nancy
Brier
Sarah
Sophie
Sanjay
Rita
Gigi
Maggie
Paul
James
Pat
Mark

1.1. Find the names of all employees in department number 1

Now add a condition to limit how many rows are returned, and to restrict our result to one column.

```
SELECT EmployeeName FROM Employee
WHERE DepartmentID = 1;
```

EmployeeName
Alice

2. Find the items sold on floors other than the second floor

First look at the slightly simpler query: Which items are sold on the second floor?

```
SELECT DISTINCT ItemID
FROM Sale INNER JOIN Department
ON Sale.DepartmentID = Department.DepartmentID
WHERE DepartmentFloor = 2;
```

It's simple now to change this to: Which items are sold on OTHER floors?

```
SELECT DISTINCT ItemID FROM Sale INNER JOIN Department
ON Sale.DepartmentID = Department.DepartmentID
WHERE DepartmentFloor <> 2;
```

ItemID
8
14
17
18
9
11
15
12

The Natural Join syntax is simpler:

```
SELECT DISTINCT ItemID
FROM Sale NATURAL JOIN Department
WHERE DepartmentFloor <> 2;
```

Variation: find the items sold by at least two departments on the second floor

```
SELECT ItemID FROM Sale NATURAL JOIN Department
WHERE DepartmentFloor = 2
GROUP BY ItemID
HAVING COUNT(DISTINCT Department.DepartmentID) > 1;
```

ItemID
14
17

3. Find the suppliers that deliver compasses

Join the tables, look for compasses and tell us who the suppliers are.

```
SELECT DISTINCT Supplier.SupplierID, SupplierName
FROM Supplier INNER JOIN Delivery INNER JOIN Item
ON Supplier.SupplierID = Delivery.SupplierID
AND Item.ItemID = Delivery.ItemID
WHERE ItemName = 'Compass';
```

SupplierID	SupplierName
101	Global Books & Maps
102	Nepalese Corp.
103	All Sports Manufacturing
105	All Points_ Inc.

4. For each item, give its type, the departments that sell the item, and the floor location of these departments

A simple three way join

```
SELECT Item.ItemName, ItemType,
       Department.DepartmentID, DepartmentFloor
FROM Item INNER JOIN Sale INNER JOIN Department
ON Sale.ItemID = Item.ItemID
AND Sale.DepartmentID =
    Department.DepartmentID;
```

ItemName	ItemType	DepartmentID	DepartmentFloor
Boots - snakeproof	C	3	2
Elephant polo stick	R	7	2
Camel saddle	R	7	2
Hat - polar explorer	C	3	2
Pith helmet	C	3	2
Pith helmet	C	4	3
Pith helmet	C	8	1
Geo positioning system	N	6	1
Geo positioning system	N	8	1
Map measure	N	6	1
How to Win Foreign Friends	B	8	1
Pocket knife - Nile	E	3	2
Pocket knife - Nile	E	7	2
Pocket knife - Nile	E	8	1
Pocket knife - Nile	E	6	1
Pocket knife - Nile	E	4	3
Pocket knife - Nile	E	5	4
Exploring in 10 Easy Lessons	B	8	1
Sextant	N	6	1
Sextant	N	8	1
Sextant	N	3	2
Sextant	N	4	3
Sextant	N	7	2
Sextant	N	5	4
Compass	N	6	1
Compass	N	8	1

5. List suppliers that deliver a total quantity of items of types C and N that is altogether greater than 40

A simple query again – but with a compound condition for items C and N

```
SELECT Delivery.SupplierID, SupplierName FROM Supplier
INNER JOIN Delivery INNER JOIN Item
ON Supplier.SupplierID = Delivery.SupplierID
AND Item.ItemID = Delivery.ItemID
WHERE (ItemType = 'C' OR ItemType = 'N')
GROUP BY Delivery.SupplierID, SupplierName
HAVING SUM(Delivery.QTY) > 40;
```

SupplierID	SupplierName
101	Global Books & Maps
105	All Points_ Inc.

6. Find numbers and names of those employees who make more than their manager

Make two copies of the same table (here called *emp* and *boss*) and join them (just like any other join)

```
SELECT emp.EmployeeID, emp.EmployeeName
FROM Employee emp INNER JOIN Employee boss
ON emp.BossID = boss.EmployeeID
WHERE boss.EmployeeSalary < emp.EmployeeSalary;
```

EmployeeID	EmployeeName
8	Sarah

7. Find the names of employees who are in the same department as their manager (as an employee). Report the name of the employee, the department, and the boss's name

Another join, but on more than one column.

```
SELECT wrk.EmployeeName, wrk.DepartmentID,
boss.EmployeeName
FROM Employee wrk INNER JOIN Employee boss
ON wrk.BossID = boss.EmployeeID
WHERE wrk.DepartmentID = boss.DepartmentID;
```

EmployeeName	DepartmentID	EmployeeName
Andrew	11	Ned
Clare	11	Ned
Nancy	8	Todd
Sarah	9	Brier

8. List the name, salary, and manager of the employees of department 11 who have a salary over \$25,000

This is a self join – Join the bosses and workers into a table, and then restrict which rows are returned.

Look at the output of **SELECT * FROM Employee wrk, Employee boss WHERE wrk.BossID = boss.EmployeeID** to see the single table before we remove rows.

```
SELECT wrk.EmployeeName, wrk.EmployeeSalary,
boss.EmployeeName
FROM Employee wrk INNER JOIN Employee boss
ON wrk.BossID = boss.EmployeeID
WHERE wrk.DepartmentID = 11
AND wrk.EmployeeSalary > 25000;
```

EmployeeName	EmployeeSalary	EmployeeName
Ned	45000.00	Alice

Week 4

9. List the names of the employees who earn more than any employee in the marketing department

Split the problem up into 2 components – calculate max salary of people in marketing (inner query), and then find who earns more than that (outer query).

```
SELECT EmployeeName, EmployeeSalary FROM Employee
WHERE EmployeeSalary >
  (SELECT MAX(EmployeeSalary)
   FROM Employee NATURAL JOIN Department
   WHERE DepartmentName = "Marketing ");
```

EmployeeName	EmployeeSalary
Alice	75000.00
Sarah	56000.00

10. List the name and salary of the managers with more than two employees

First write code for to find managers with > 2 employees (the sub query). Then wrap the extra code around it to get the details of the managers

```
SELECT EmployeeName, EmployeeSalary FROM Employee
WHERE EmployeeID IN
  (SELECT BossID FROM Employee
   GROUP BY BossID
   HAVING COUNT(*) > 2);
```

EmployeeName	EmployeeSalary
Alice	75000.00
Andrew	25000.00
Clare	22000.00

11. Find the suppliers that do not deliver compasses

Work out which suppliers supply compasses (the inner query) and then list the suppliers not in that list (outer query).

```
SELECT SupplierID, SupplierName FROM Supplier
WHERE SupplierID NOT IN
  (SELECT SupplierID FROM Delivery
   NATURAL JOIN Item
   WHERE ItemName = 'Compass');
```

SupplierID	SupplierName
104	Sweatshops Unlimited
106	Sao Paulo Manufacturing

12. List the suppliers that deliver at least two items of type N to departments

Use this one for any query that asks for at least some number...Use DISTINCT to handle multiple deliveries of the same item.

```
SELECT Supplier.SupplierID, SupplierName FROM Delivery
      NATURAL JOIN Supplier NATURAL JOIN Item
WHERE ItemType = 'N'
GROUP BY Supplier.SupplierID, SupplierName
HAVING COUNT(DISTINCT Delivery.ItemID) > 1;
```

SupplierID	SupplierName
101	Global Books & Maps
102	Nepalese Corp.
103	All Sports Manufacturing
105	All Points_ Inc.

or, including the number we are interested in:

```
SELECT Supplier.SupplierID, SupplierName, count(Distinct delivery.itemid) as NumItems
FROM Delivery NATURAL JOIN Supplier NATURAL JOIN Item
WHERE ItemType = 'N'
GROUP BY Supplier.SupplierID, SupplierName
HAVING NumItems > 1;
```

13. List the items delivered by exactly one supplier (i.e. items that are always delivered by the same supplier)

Use Group By with an exact count.

```
SELECT ItemName FROM Delivery NATURAL JOIN Item
GROUP BY ItemName
HAVING COUNT(DISTINCT SupplierID) = 1;
```

ItemName
Boots - snakeproof
Exploring in 10 Easy Lessons
Hat - polar explorer
How to Win Foreign Friends
Pocket knife - Avon
Stetson
Tent - 2 person
Tent - 8 person

Can you include the supplier in the output?

14. List the suppliers that deliver at least 10 items

Group By with count condition again

```
SELECT Supplier.SupplierID, SupplierName
FROM Delivery NATURAL JOIN Supplier
GROUP BY Supplier.SupplierID, SupplierName
HAVING COUNT(DISTINCT Delivery.ItemID) >= 10;
```

SupplierID	SupplierName
102	Nepalese Corp.

Can you include in the output the number of items they supply?

15. List items that are delivered by Nepalese Corp and sold in the Navigation department

Use AND to combine two simple queries together

```
SELECT DISTINCT ItemName FROM Item
WHERE ItemID IN
  (SELECT ItemID FROM Delivery NATURAL JOIN Supplier
   WHERE SupplierName = 'Nepalese corp.')
AND ItemID IN
  (SELECT ItemID FROM Sale NATURAL JOIN Department
   WHERE DepartmentName = 'Navigation');
```

ItemName
Sextant
Pocket knife - Nile
Compass
Geo positioning system
Map measure

16. List items that are delivered by Nepalese Corp or sold in the Navigation department

Similar to question 15, but the condition is OR

```
SELECT DISTINCT ItemName FROM Item
WHERE ItemID IN
  (SELECT ItemID FROM Delivery NATURAL JOIN Supplier
   WHERE SupplierName = 'Nepalese Corp.')
OR ItemID IN
  (SELECT ItemID FROM Sale NATURAL JOIN Department
   WHERE DepartmentName = 'Navigation');
```

ItemName
Pith helmet
Geo positioning system
Map case
Map measure
How to Win Foreign Friends
Pocket knife - Avon
Pocket knife - Nile
Exploring in 10 Easy Lessons
Sextant
Compass
Tent - 2 person
Tent - 8 person

17. Find the average salary of the employees in the Clothes department

A simple join with an Average (and an Alias)

```
SELECT FORMAT(AVG(EmployeeSalary),2) AS AverageSalary
FROM Employee INNER JOIN Department
ON Department.DepartmentID = Employee.DepartmentID
WHERE DepartmentName = 'Clothes';
```

AverageSalary
16,000.00

18. Find, for each department, the average salary of employees

same as 17, except use Group instead of Where

```
SELECT DepartmentName, FORMAT(AVG(EmployeeSalary),2) AS AverageSalary
FROM Employee INNER JOIN Department
ON Department.DepartmentID = Employee.DepartmentID
GROUP BY DepartmentName;
```

DepartmentName	AverageSalary
Accounting	30,000.00
Books	15,000.00
Clothes	16,000.00
Equipment	13,000.00
Furniture	15,000.00
Management	75,000.00
Marketing	30,666.67
Navigation	15,000.00
Personnel	35,000.00
Purchasing	49,500.00
Recreation	15,000.00

19. Find, for each department on the second floor, the average salary of the employees

A slightly more complex join and average

```
SELECT Department.DepartmentName,
       FORMAT(AVG(EmployeeSalary),2) AS AverageSalary
FROM Employee NATURAL JOIN Department
WHERE DepartmentFloor = 2
GROUP BY Department.DepartmentName;
```

DepartmentName	AverageSalary
Clothes	16,000.00
Recreation	15,000.00

20. Find, for each department that sells items of type E, the average salary of the employees

Not a hard query, just lots of stuff in it – joins, conditions and grouping

```
SELECT Department.DepartmentName,
       FORMAT(AVG(EmployeeSalary),2) AS AverageSalary
FROM Employee INNER JOIN Department INNER JOIN Sale INNER JOIN Item
ON Employee.DepartmentID = Department.DepartmentID
AND Department.DepartmentID = Sale.DepartmentID
AND Sale.ItemID = Item.ItemID
WHERE ItemType = 'E'
GROUP BY Department.DepartmentName;
```

DepartmentName	AverageSalary
Books	15,000.00
Clothes	16,000.00
Equipment	13,000.00
Furniture	15,000.00
Navigation	15,000.00
Recreation	15,000.00

21.

(removed due to poorly structured question)

Week 5

22. Find the total number of items of type E sold by the departments on the second floor

Similar to query 20 but a sum

```
SELECT SUM(SaleQTY) FROM Item INNER JOIN Sale INNER JOIN Department
  ON Item.ItemID = Sale.ItemID
 AND Department.DepartmentID = Sale.DepartmentID
 WHERE ItemType = 'E'
 AND DepartmentFloor = 2;
```

SUM(SaleQTY)
2

23. Find, for each item, the total quantity sold by the departments on the second floor

Similar to query 20 again...

```
SELECT Item.ItemName, SUM(SaleQTY) FROM Item
  INNER JOIN Sale INNER JOIN Department
  ON Item.ItemID = Sale.ItemID
 AND Department.DepartmentID = Sale.DepartmentID
 WHERE DepartmentFloor = 2
 GROUP BY Item.ItemName;
```

ItemName	SUM(SaleQTY)
Boots - snakeproof	2
Camel saddle	1
Elephant polo stick	1
Hat - polar explorer	3
Pith helmet	1
Pocket knife - Nile	2
Sextant	2

24. List the departments having an average salary over \$25,000

```
SELECT DepartmentID, AVG(EmployeeSalary)
 FROM Employee GROUP BY DepartmentID
  HAVING AVG(EmployeeSalary) > 25000;
```

This output looks poor... We can fix this using the Format function...

```
SELECT DepartmentID,
  FORMAT(AVG(EmployeeSalary),2) AS AverageSalary
 FROM Employee
 GROUP BY DepartmentID
  HAVING AVG(EmployeeSalary) > 25000;
```

DepartmentID	AVG(EmployeeSalary)
1	75000.000000
8	30000.000000
9	49500.000000
10	35000.000000
11	30666.666667

DepartmentID	AverageSalary
1	75,000.00
8	30,000.00
9	49,500.00
10	35,000.00
11	30,666.67

Other useful formatting functions include UPPER, LOWER, LEFT, RIGHT

25. List the employees in the Accounting department and the difference between their salaries and the average salary of the department

Need to get the average salary for Accounting employees in the same row as the department salary data.

Often due to the complexity of the queries it is often a good idea to create a View, to simplify the query. This has the advantage that parts of the query can be re-used.

First, determine the average salary of the employees in all departments and save this as a view. Then, join this view to the Employee table matching the Accounting department's name.

```
CREATE VIEW vAvgSalaryDept (DepartmentID, dpavgsal) AS
SELECT DepartmentID, AVG(EmployeeSalary) FROM Employee
GROUP BY DepartmentID;

SELECT EmployeeName, FORMAT((EmployeeSalary - dpavgsal),2) AS Salary_DeptAvgSalary
FROM vAvgSalaryDept NATURAL JOIN Employee NATURAL JOIN Department
WHERE Department.DepartmentName = 'Accounting';
```

EmployeeName	Salary_DeptAvgSalary
Todd	8,000.00
Nancy	-8,000.00

26. List each employee's salary, the average salary within that person's department, and the difference between the employees' salaries and the average salary of the department

We already have the average salaries of departments in a View (see q 25). So we just need to use this and join it to department to get our answer.

```
SELECT EmployeeName, EmployeeSalary, FORMAT(dpavgsal,2) AS DeptAvSal,
FORMAT(EmployeeSalary - dpavgsal,2) AS DiffEAvgDSal
FROM vAvgSalaryDept NATURAL JOIN Employee
WHERE vAvgSalaryDept.DepartmentID =
Employee.DepartmentID;
```

EmployeeName	EmployeeSalary	DeptAvSal	DiffEAvgDSal
Alice	75000.00	75,000.00	0.00
Ned	45000.00	30,666.67	14,333.33
Andrew	25000.00	30,666.67	-5,666.67
Clare	22000.00	30,666.67	-8,666.67
Todd	38000.00	30,000.00	8,000.00
Nancy	22000.00	30,000.00	-8,000.00
Brier	43000.00	49,500.00	-6,500.00
Sarah	56000.00	49,500.00	6,500.00
Sophie	35000.00	35,000.00	0.00
Sanjay	15000.00	15,000.00	0.00
Rita	15000.00	15,000.00	0.00
Gigi	16000.00	16,000.00	0.00
Maggie	16000.00	16,000.00	0.00
Paul	11000.00	13,000.00	-2,000.00
James	15000.00	13,000.00	2,000.00
Pat	15000.00	15,000.00	0.00
Mark	15000.00	15,000.00	0.00

27. List the suppliers that deliver all the items of type B to departments on the second floor who sell all the items of type R

In this case we'll create a View showing departments on the 2nd floor who sell all items of type R.

Then we'll use the view to report on the suppliers that deliver all the items of type B to the departments identified in the view.

27.1. first, how would we do this *without* using a View...

```
SELECT SupplierName FROM Supplier WHERE NOT EXISTS
  (SELECT * FROM Item
   WHERE ItemType = 'B' AND NOT EXISTS
    (SELECT * FROM Delivery
     WHERE Delivery.ItemID = Item.ItemID
      AND Delivery.SupplierID = Supplier.SupplierID
      AND DepartmentID IN
       (SELECT DepartmentID FROM Department
        WHERE DepartmentFloor = 2 AND NOT EXISTS
         (SELECT * FROM Item
          WHERE ItemType = 'R' AND NOT EXISTS
           (SELECT * FROM Sale
            WHERE Sale.ItemID = Item.ItemID
             AND Sale.DepartmentID = Department.DepartmentID))))));
```

SupplierName
Nepalese Corp.

27.2. now, using A View...

```
CREATE VIEW vDeptFloor2ItemB AS
  (SELECT DepartmentID FROM Department
   WHERE DepartmentFloor = 2 AND NOT EXISTS
    (SELECT * FROM Item WHERE ItemType = 'R' AND NOT EXISTS
     (SELECT * FROM Sale WHERE Sale.ItemID = Item.ItemID
      AND Sale.DepartmentID = Department.DepartmentID)));
```

```
SELECT SupplierName FROM Supplier WHERE NOT EXISTS
  (SELECT * FROM Item WHERE ItemType = 'B' AND NOT EXISTS
   (SELECT * FROM Delivery WHERE Delivery.ItemID = Item.ItemID
    AND Delivery.SupplierID = Supplier.SupplierID
    AND DepartmentID IN
     (SELECT DepartmentID FROM vDeptFloor2ItemB)));
```

SupplierName
Nepalese Corp.

28. List the suppliers that deliver all the items of type B to the departments that also sell all the items of type N

Split the problem into 3 parts:

Identify the departments that sell all items of type N – that's the 1st view.

Then select the departments to which all items of type B are delivered – that's the 2nd view.

Finally find the suppliers that supply all items of type B to the departments that appear in both views.

CREATE VIEW v33a AS

```
(SELECT DepartmentID FROM Department WHERE NOT EXISTS
  (SELECT * FROM Item
    WHERE ItemType = 'N' AND NOT EXISTS
      (SELECT * FROM Sale
        WHERE Sale.DepartmentID = Department.DepartmentID
        AND Sale.ItemID = Item.ItemID)));
```

CREATE VIEW v33b AS

```
(SELECT DepartmentID FROM Department WHERE NOT EXISTS
  (SELECT * FROM Item
    WHERE ItemType = 'B' AND NOT EXISTS
      (SELECT * FROM Delivery
        WHERE Delivery.DepartmentID = Department.DepartmentID
        AND Delivery.ItemID = Item.ItemID)));
```

SupplierName
Nepalese Corp.

SELECT SupplierName FROM Supplier WHERE NOT EXISTS

```
(SELECT * FROM Item
  WHERE ItemType = 'B' AND NOT EXISTS
    (SELECT * FROM Delivery
      WHERE Delivery.SupplierID = Supplier.SupplierID
      AND Delivery.ItemID = Item.ItemID
      AND EXISTS
        (SELECT * FROM v33a
          WHERE Delivery.DepartmentID = v33a.DepartmentID)
      AND EXISTS
        (SELECT * FROM v33b
          WHERE Delivery.DepartmentID = v33b.DepartmentID)));
```

29. List the employees in the Accounting department and the difference between their salaries and the average salary of all of the departments

You can answer this with a View or a Subquery.
We'll demonstrate the View here and let you try the Subquery.

Using similar logic to query 25...

```
CREATE VIEW vAvgSalary(allavgsal) AS
  SELECT AVG(EmployeeSalary) FROM Employee;
```

```
SELECT EmployeeName, (EmployeeSalary - allavgsal)
FROM vAvgSalary NATURAL JOIN Employee
WHERE DepartmentID IN
  (SELECT DepartmentID FROM Department
   WHERE DepartmentName = 'Accounting');
```

EmployeeName	(EmployeeSalary - allavgsal)
Todd	9823.529412
Nancy	-6176.470588

30. What is the number of supplier-department pairs in which the supplier delivers at least one item of type E to the department?

Again you can answer this with a View or a Subquery.

First, the view:

Set up a view that lists all the supplier-department pairs. Remove duplicates using Distinct.
Then use a count to get the answer.

```
CREATE VIEW v60 AS
  (SELECT DISTINCT SupplierID, DepartmentID FROM Delivery NATURAL JOIN Item
   WHERE ItemType = 'E');
```

```
SELECT COUNT(*) FROM v60;
```

COUNT(*)
10

Now, using a subquery:

```
SELECT count(*) FROM
  (SELECT DISTINCT SupplierID, DepartmentID FROM Delivery NATURAL JOIN Item
   WHERE ItemType = 'E' ) AS tempname;
```

Week 6

31. Give the overall average of the salaries in all departments

A really simple Average query

```
SELECT AVG(EmployeeSalary) FROM Employee;
```

AVG(EmployeeSalary)
28176.470588

We could use the view we created of average salaries per department, but this gives a different answer due to rounding errors

```
SELECT AVG(dpavgsal) FROM vAvgSalaryDept;
```

32. What is the average delivery quantity of items of type N delivered by each company who delivers them

(similar to Query 45)

```
SELECT Delivery.SupplierID, SupplierName, Item.ItemName,  
       FORMAT(AVG(DeliveryQTY),2) AS AvgDelQty  
FROM Delivery INNER JOIN Supplier INNER JOIN Item  
   ON Delivery.SupplierID = Supplier.SupplierID  
   AND Delivery.ItemID = Item.ItemID  
WHERE ItemType = 'N'  
GROUP BY Delivery.SupplierID, SupplierName, Item.ItemName;
```

SupplierID	SupplierName	ItemName	AvgDelQty
101	Global Books & Maps	Compass	50.00
101	Global Books & Maps	Geo positioning system	10.00
101	Global Books & Maps	Map measure	10.00
101	Global Books & Maps	Sextant	2.00
102	Nepalese Corp.	Compass	3.00
102	Nepalese Corp.	Geo positioning system	1.00
102	Nepalese Corp.	Map measure	10.00
102	Nepalese Corp.	Sextant	5.00
103	All Sports Manufacturing	Compass	20.00
103	All Sports Manufacturing	Geo positioning system	1.00
103	All Sports Manufacturing	Map measure	15.00
103	All Sports Manufacturing	Sextant	1.00
104	Sweatshops Unlimited	Sextant	3.00
105	All Points_ Inc.	Compass	5.00
105	All Points_ Inc.	Sextant	1.00
106	Sao Paulo Manufacturing	Sextant	1.00

33. What is the average delivery quantity of items of type N delivered by each supplier to each department (for suppliers that deliver items of type N to the department)

Similar again to query 32, except we average on 3 levels (ie Group By)

```
SELECT Delivery.SupplierID, SupplierName, DepartmentID,  
       Item.ItemName,  
       FORMAT(AVG(DeliveryQTY),2) AS DelQTY  
FROM Delivery INNER JOIN Supplier INNER JOIN Item  
   ON Delivery.SupplierID = Supplier.SupplierID  
   AND Delivery.ItemID = Item.ItemID  
WHERE ItemType = 'N'  
GROUP BY Delivery.SupplierID, SupplierName,  
          DepartmentID, Item.ItemName;
```

SupplierID	SupplierName	DepartmentID	ItemName	DelQTY
101	Global Books & Maps	6	Compass	50.00
101	Global Books & Maps	6	Geo positioning system	10.00
101	Global Books & Maps	6	Map measure	10.00
101	Global Books & Maps	6	Sextant	2.00
102	Nepalese Corp.	2	Compass	5.00
102	Nepalese Corp.	6	Compass	1.00
102	Nepalese Corp.	6	Geo positioning system	1.00
102	Nepalese Corp.	6	Map measure	10.00
102	Nepalese Corp.	7	Sextant	5.00
103	All Sports Manufacturing	2	Geo positioning system	1.00
103	All Sports Manufacturing	2	Sextant	1.00
103	All Sports Manufacturing	4	Compass	20.00
103	All Sports Manufacturing	6	Map measure	15.00
104	Sweatshops Unlimited	6	Sextant	3.00
105	All Points_ Inc.	4	Compass	5.00
105	All Points_ Inc.	4	Sextant	1.00
106	Sao Paulo Manufacturing	4	Sextant	1.00

34. Find the items sold by the departments on the second floor. (only show ItemID)

Note that in a real example we would want to also join to the item table and show the item name, as it is better understood by the users

34.1.Attempt 1

```
SELECT DISTINCT ItemID FROM Sale INNER JOIN Department
ON Department.DepartmentID = Sale.DepartmentID
WHERE DepartmentFloor = 2;
```

34.2.Attempt 2

```
SELECT DISTINCT ItemID FROM Sale
WHERE DepartmentID IN
(SELECT DepartmentID FROM Department
WHERE DepartmentFloor = 2);
```

ItemID
1
8
6
14
17
2
4

34.3.Attempt 3

```
SELECT DISTINCT ItemID FROM Sale
WHERE DepartmentID IN
(SELECT DepartmentID FROM Department
WHERE Department.DepartmentID = Sale.DepartmentID
AND DepartmentFloor = 2);
```

34.4.Attempt 4

```
SELECT DISTINCT ItemID FROM Sale
WHERE EXISTS
(SELECT * FROM Department
WHERE Sale.DepartmentID = Department.DepartmentID
AND DepartmentFloor = 2);
```

35. Find the items sold by no department on the second floor

Compare this with query 2, which asked:

“Which items are sold on the floors other than 2?”

(a slight but significant difference).

```
SELECT DISTINCT ItemID FROM Sale
WHERE ItemID NOT IN
(SELECT DISTINCT ItemID FROM Sale NATURAL JOIN Department
WHERE DepartmentFloor = 2);
```

ItemID
9
11
12
15
18

36. Find the items sold by ALL departments on the second floor

The query is asking you to select the items from sales such that there does not exist a department on the 2nd floor that does not sell the item.

```
SELECT Sale.ItemID FROM Sale NATURAL JOIN Department
WHERE Department.DepartmentFloor = 2
GROUP BY Sale.ItemID
HAVING count(DISTINCT Department.DepartmentID) =
(SELECT count(DISTINCT DepartmentID) FROM Department
WHERE DepartmentFloor = 2);
```

ItemID
14
17

37. Among all the departments with total salary greater than \$25,000, find the departments that sell Item Number 17

Similar to query 9, we find the departments first, then do the selection from that list looking for Item 17

```
SELECT DISTINCT DepartmentName FROM Sale
NATURAL JOIN Department D
WHERE ItemID = 17
AND D.DepartmentID IN
(SELECT DepartmentID FROM Employee
GROUP BY DepartmentID
HAVING SUM(EmployeeSalary) > 25000)
```

DepartmentName
Clothes
Equipment

38. Find the salary of Clare's manager

The inner (sub) query gets the manager, and the outer query gets the manager's details

```
SELECT EmployeeName, EmployeeSalary FROM Employee
WHERE EmployeeID IN
(SELECT BossID FROM Employee
WHERE EmployeeName = 'Clare');
```

EmployeeName	EmployeeSalary
Ned	45000.00

39. Count the number of direct employees of each manager

Do a self join on the Employee table, group and count.

```
SELECT boss.EmployeeID, boss.EmployeeName, COUNT(*)  
  FROM Employee wrk INNER JOIN Employee boss  
    ON wrk.BossID = boss.EmployeeID  
  GROUP BY boss.EmployeeID, boss.EmployeeName;
```

EmployeeID	EmployeeName	COUNT(*)
1	Alice	4
2	Ned	2
3	Andrew	5
4	Clare	3
5	Todd	1
7	Brier	1

40. Find the departments where all the employees earn less than their manager

Compare this to query 6, which asked:

“Which employees make more than their manager?”

```
SELECT DISTINCT DepartmentID FROM Employee  
  WHERE DepartmentID <> 1  
  AND DepartmentID NOT IN  
    (SELECT wrk.DepartmentID FROM Employee wrk INNER JOIN Employee boss  
      ON wrk.BossID = boss.EmployeeID  
      WHERE wrk.EmployeeSalary >= boss.EmployeeSalary);
```

DepartmentID
2
3
4
5
6
7
8
10
11

41. List the departments selling items of type E that are delivered by Nepalese Corp. and/or which are sold by the Navigation department

This is similar to queries 15 and 16. We use one outer query to get the department name and two inner queries (separated by an OR) filter the departments.

```
SELECT DISTINCT DepartmentName FROM Sale NATURAL JOIN Department
WHERE ItemID IN
  (SELECT Item.ItemID FROM Item INNER JOIN Delivery
    INNER JOIN Supplier
    ON Item.ItemID = Delivery.ItemID
    AND Delivery.SupplierID = Supplier.SupplierID
    WHERE SupplierName = 'Nepalese Corp.'
    AND ItemType = 'E')
OR ItemID IN
  (SELECT ItemID FROM Sale NATURAL JOIN Department
    WHERE DepartmentName = 'Navigation');
```

DepartmentName
Clothes
Equipment
Furniture
Navigation
Recreation
Books

42. Is it true that all the departments that sell items of type C are located on the third floor? (you should return either 1 for True or 0 for False)

There is no Boolean functionality in SQL. Instead we can do a count, and test it with "> 0", to give a 0 or 1 as an answer.

```
SELECT COUNT(*) > 0 FROM Department
WHERE DepartmentFloor <> 3
AND EXISTS
  (SELECT * FROM Sale NATURAL JOIN Item
    WHERE Sale.DepartmentID = Department.DepartmentID
    AND ItemType = 'C');
```

COUNT(*)>0
1

43. List pairs of Supplier and Item where the supplier is the only deliverer of the item

For each of the items delivered, check to see that the supplier is the only deliverer of it.

```
SELECT DISTINCT Supplier.SupplierID, SupplierName, ItemID
FROM Supplier NATURAL JOIN Delivery del1
WHERE ItemID NOT IN
  (SELECT ItemID FROM Delivery
    WHERE Delivery.SupplierID <> del1.SupplierID);
```

SupplierID	SupplierName	ItemID
102	Nepalese Corp.	13
102	Nepalese Corp.	19
102	Nepalese Corp.	20
102	Nepalese Corp.	15
102	Nepalese Corp.	12
105	All Points_ Inc.	1
105	All Points_ Inc.	6
105	All Points_ Inc.	3

44. List each item delivered to at least two departments by each supplier that delivers it

Inner query works out which item/supplier pairs only match 1 department

Hint – first try: `select ItemID, SupplierID, DepartmentID from delivery order by ItemID, SupplierID;`

```
SELECT DISTINCT ItemName
FROM Delivery NATURAL JOIN Item
WHERE ItemID NOT IN
  (SELECT ItemID FROM Delivery
   GROUP BY ItemID, SupplierID
   HAVING COUNT(DISTINCT DepartmentID) < 2);
```

ItemName
Boots - snakeproof
How to Win Foreign Friends
Exploring in 10 Easy Lessons

45. What is, for each supplier, the average number of items that they deliver to each department?

Join tables using Group By to structure the result
(similar to query 32)

```
SELECT Delivery.SupplierID, SupplierName, DepartmentName,
       FORMAT(AVG(DeliveryQTY),2) AS AverageDeliveryQTY
FROM Supplier NATURAL JOIN Delivery
NATURAL JOIN Department
GROUP BY Delivery.SupplierID, SupplierName,
         DepartmentName;
```

SupplierID	SupplierName	DepartmentName	AverageDeliveryQTY
101	Global Books & Maps	Clothes	1.00
101	Global Books & Maps	Navigation	19.40
102	Nepalese Corp.	Books	8.33
102	Nepalese Corp.	Clothes	1.00
102	Nepalese Corp.	Navigation	5.29
102	Nepalese Corp.	Recreation	3.50
103	All Sports Manufacturing	Books	1.00
103	All Sports Manufacturing	Clothes	1.00
103	All Sports Manufacturing	Equipment	20.00
103	All Sports Manufacturing	Navigation	15.00
104	Sweatshops Unlimited	Clothes	1.00
104	Sweatshops Unlimited	Navigation	3.00
105	All Points_ Inc.	Books	7.50
105	All Points_ Inc.	Clothes	7.20
105	All Points_ Inc.	Equipment	4.60
105	All Points_ Inc.	Furniture	7.50
105	All Points_ Inc.	Navigation	27.50
105	All Points_ Inc.	Recreation	7.50
106	Sao Paulo Manufacturing	Equipment	13.67

46. For each department, find the average salary of the employees who earn more than the average salary of the department

The inner query averages the salaries of each department (see how it matches the departments).

```
SELECT DepartmentName, FORMAT(AVG(EmployeeSalary),2) AS AverageSalary
FROM Employee Outt NATURAL JOIN Department
WHERE EmployeeSalary >
  (SELECT AVG(EmployeeSalary) FROM Employee Inn
   WHERE Outt.DepartmentID = Inn.DepartmentID)
GROUP BY DepartmentName;
```

DepartmentName	AverageSalary
Accounting	38,000.00
Equipment	15,000.00
Marketing	45,000.00
Purchasing	56,000.00

47. List the departments where the average salary of the employees of each manager is more than \$25,000

Getting harder now. We have to exclude manager's salaries from the calculation (this is accomplished by the inner query). We use Group By to get the data by department.

```
SELECT wrk.DepartmentID, FORMAT(AVG(wrk.EmployeeSalary),2) AS AvgSalary
FROM Employee wrk
WHERE wrk.EmployeeID NOT IN
  (SELECT Department.ManagerID FROM Department
   WHERE wrk.EmployeeID = Department.ManagerID
   AND wrk.DepartmentID = Department.DepartmentID)
GROUP BY wrk.DepartmentID
HAVING AVG(wrk.EmployeeSalary) > 25000;
```

DepartmentID	AvgSalary
9	56,000.00

48. Find the suppliers that deliver both compasses and an item other than compasses

Attempt 1 uses the approach of finding those suppliers that supply things other than compasses, and also supply compasses (sub query)

Attempt 2 uses a more generalizable approach: Find suppliers that have delivered compasses and at least two items...(we use DISTINCT to handle multiple deliveries of compasses for the same supplier.

The generalizable approach is better as it allows queries such as "Find suppliers that deliver two items other than compasses" – change the >1 to >2 in the HAVING clause in Attempt 2 to do this.

48.1.Attempt 1

```
SELECT DISTINCT Delivery.SupplierID, SupplierName
FROM Supplier NATURAL JOIN Delivery NATURAL JOIN Item
WHERE ItemName <> 'Compass'
AND Delivery.SupplierID IN
  (SELECT SupplierID FROM Delivery
   NATURAL JOIN Item
   WHERE ItemName = 'Compass');
```

SupplierID	SupplierName
105	All Points_ Inc.
101	Global Books & Maps
103	All Sports Manufacturing
102	Nepalese Corp.

48.2.Attempt 2

```
SELECT DISTINCT Delivery.SupplierID, SupplierName
FROM Supplier NATURAL JOIN Delivery NATURAL JOIN Item
WHERE Delivery.SupplierID IN
  (SELECT SupplierID FROM Delivery
   NATURAL JOIN Item
   WHERE ItemName = 'Compass')
GROUP BY Delivery.SupplierID, SupplierName
HAVING COUNT(DISTINCT ItemName) > 1;
```

Check your answer using:

```
select supplierid, itemid, itemname from Delivery natural join Item order by supplierid, itemid;
```

49. Who are the suppliers that deliver all the items of type N

This kind of query is called a Relational Divide. You use this when you need to find all of the rows of one table that are related to ALL of some other group of rows.

Here, we want to find any suppliers who deliver ALL of a particular subset of the Item table.

The usual way to do a relational divide in SQL is to use a subquery inside a subquery, each with a NOT EXISTS.

```
SELECT SupplierID, SupplierName FROM Supplier
WHERE NOT EXISTS
  (SELECT * FROM Item WHERE ItemType = 'N'
   AND NOT EXISTS
     (SELECT * FROM Delivery
      WHERE Delivery.SupplierID = Supplier.SupplierID
      AND Delivery.ItemID = Item.ItemID));
```

SupplierID	SupplierName
101	Global Books & Maps
102	Nepalese Corp.
103	All Sports Manufacturing

This is like saying: “Show each supplier for whom there is no item of type N for which there are no deliveries by that supplier of that item”.

Check your answer using: **SELECT * FROM Item WHERE ItemType = 'N';**
and **SELECT SupplierId, ItemId FROM Delivery order by SupplierId, ItemId;**

50. List the departments that have not recorded a sale for all the items of type N

First, use a Relational Divide to find the departments that have sold all items of type N. Then use NOT IN to get those that *haven't* sold all items of type N.

```
SELECT DepartmentName FROM Department
WHERE DepartmentID NOT IN
  (SELECT DepartmentID FROM Department
   WHERE NOT EXISTS
     (SELECT * FROM Item
      WHERE ItemType = 'N'
      AND NOT EXISTS
        (SELECT * FROM Sale
         WHERE Sale.DepartmentID = Department.DepartmentID
         AND Sale.ItemID = Item.ItemID)));
```

DepartmentName
Management
Accounting
Clothes
Equipment
Furniture
Recreation
Books
Purchasing
Personnel
Marketing

Week 8 - CHALLENGE WEEK

51. List the departments that have at least one sale of all the items delivered to them

Another relational divide, or a variation on one, using 3 tables (in this case Sale and 2 copies of Delivery). The second version uses NOT IN as a replacement for NOT EXISTS.

51.1.Attempt 1

```
SELECT DISTINCT DepartmentID FROM Delivery del1
WHERE NOT EXISTS
  (SELECT * FROM Delivery del2
   WHERE del2.DepartmentID = del1.DepartmentID
   AND NOT EXISTS
     (SELECT * FROM Sale
      WHERE del2.ItemID = Sale.ItemID
      AND del1.DepartmentID = Sale.DepartmentID));
```

DepartmentID
8

51.2.Attempt 2

```
SELECT DISTINCT DepartmentID FROM Delivery del1
WHERE NOT EXISTS
  (SELECT * FROM Delivery del2
   WHERE del2.DepartmentID = del1.DepartmentID
   AND ItemID NOT IN
     (SELECT ItemID FROM Sale
      WHERE DepartmentID = del1.DepartmentID));
```

52. List the suppliers that deliver only the items sold by the Books department

Select suppliers for which there does not exist a delivery that does not include the items sold by the Books department.

```
SELECT SupplierName FROM Supplier
WHERE SupplierID IN
  (SELECT SupplierID FROM Delivery
   AND NOT EXISTS
     (SELECT * FROM Delivery
      WHERE Delivery.SupplierID = Supplier.SupplierID
      AND ItemID NOT IN
        (SELECT ItemID FROM Sale NATURAL JOIN Department
         WHERE DepartmentName = 'Books')));
```

SupplierName
Sweatshops Unlimited
Sao Paulo Manufacturing

53.

Removed due to poorly structured question

54. List the departments for which each item delivered to the department is delivered to some other department as well

Find departments where there is not a delivery where a supplier does not deliver the item to some other department.

```
SELECT DISTINCT DepartmentName
FROM Delivery del1 NATURAL JOIN Department
WHERE NOT EXISTS
  (SELECT * FROM Delivery del2
   WHERE del2.DepartmentID = del1.DepartmentID
   AND ItemID NOT IN
    (SELECT ItemID FROM Delivery del3
     WHERE del3.DepartmentID <> del1.DepartmentID));
```

DepartmentName
Equipment
Furniture
Books

55. List the supplier-department pairs where the department sells all items delivered to it by the supplier

This is complex because you have to match the department name and the name of sales and deliveries.

```
SELECT SupplierName, DepartmentID
FROM Delivery del1 NATURAL JOIN Supplier
WHERE NOT EXISTS
  (SELECT * FROM Delivery
   WHERE Delivery.DepartmentID = del1.DepartmentID
   AND Delivery.SupplierID = del1.SupplierID
   AND ItemID NOT IN
    (SELECT ItemID FROM Sale
     WHERE Sale.DepartmentID = del1.DepartmentID));
```

SupplierName	DepartmentID
Global Books & Maps	3
Nepalese Corp.	3
Nepalese Corp.	8
Nepalese Corp.	8
Nepalese Corp.	8
All Sports Manufacturing	8
All Sports Manufacturing	6
All Sports Manufacturing	8
All Sports Manufacturing	3
Sweatshops Unlimited	6
Sweatshops Unlimited	3
All Points_ Inc.	8
All Points_ Inc.	8
Sao Paulo Manufacturing	4
Sao Paulo Manufacturing	4
Sao Paulo Manufacturing	4

56. List the items delivered to all departments by all suppliers

This is a three part query: find the items delivered by all suppliers, find the items delivered to all departments and which items satisfy both conditions – joining the 1st two divides together. We exclude the non-sales departments in the 2nd divide (NOT IN ('Management...'))

```
SELECT ItemName FROM Item
WHERE NOT EXISTS
  (SELECT * FROM Supplier
   WHERE NOT EXISTS
     (SELECT * FROM Delivery
      WHERE Delivery.ItemID = Item.ItemID
      AND Delivery.SupplierID = Supplier.SupplierID))
AND NOT EXISTS
  (SELECT * FROM Department
   WHERE DepartmentName
   NOT IN ('Management', 'Marketing', 'Personnel', 'Accounting', 'Purchasing')
   AND NOT EXISTS
     (SELECT * FROM Delivery
      WHERE Delivery.ItemID = Item.ItemID
      AND Delivery.DepartmentID = Department.DepartmentID));
```

ItemName
Pith helmet

57. List the suppliers that deliver every item of type C to the same department on the second floor

Another divide... the inner query has three Where conditions to handle the “same department” requirement

```
SELECT SupplierName FROM Supplier
WHERE EXISTS
  (SELECT * FROM Department WHERE DepartmentFloor = 2
   AND NOT EXISTS
     (SELECT * FROM Item WHERE ItemType = 'C'
      AND NOT EXISTS
        (SELECT * FROM Delivery
         WHERE Delivery.SupplierID = Supplier.SupplierID
         AND Delivery.ItemID = Item.ItemID
         AND Delivery.DepartmentID = Department.DepartmentID)));
```

SupplierName
All Points_ Inc.

58. List the items that are delivered only by the suppliers that deliver something to all the departments

This one's a bit tricky as only some department have deliveries so we have to get rid of the management departments in the query.

```
SELECT DISTINCT ItemName
FROM Delivery del1 NATURAL JOIN Item
WHERE NOT EXISTS
  (SELECT * FROM Delivery del2
   WHERE del2.ItemID = del1.ItemID
   AND SupplierID NOT IN
     (SELECT SupplierID FROM Delivery
      GROUP BY SupplierID
      HAVING COUNT(DISTINCT DepartmentID) =
        (SELECT COUNT(*) FROM Department
         WHERE DepartmentName NOT IN ('Management',
                                       'Marketing', 'Personnel', 'Accounting', 'Purchasing'))));
```

ItemName
Boots - snakeproof
Stetson
Hat - polar explorer

59. List the items delivered by every supplier that delivers all items of type N

This is a *double* divide...The inner query (shown inside the purple box) determines the suppliers that deliver all items of type N. The outer query determines which of the suppliers (returned by the inner divide) provide all these items.

```
SELECT DISTINCT ItemName FROM Delivery Del
NATURAL JOIN Item
WHERE NOT EXISTS
  (SELECT * FROM Supplier
   WHERE NOT EXISTS
     (SELECT * FROM Item
      WHERE ItemType = 'N'
      AND NOT EXISTS
        (SELECT * FROM Delivery
         WHERE Delivery.ItemID = Item.ItemID
         AND Delivery.SupplierID = Supplier.SupplierID))
   AND NOT EXISTS
     (SELECT * FROM Delivery
      WHERE Delivery.ItemID = Del.ItemID
      AND Delivery.SupplierID = Supplier.SupplierID));
```

ItemName
Pith helmet
Geo positioning system
Map measure
Sextant
Compass

60. List the items sold only by departments that sell all the items delivered to them

Identify which items sold by departments that sell all items delivered to them
Then make sure no other department sells that item

```
SELECT DISTINCT ItemName FROM Sale sal NATURAL JOIN Item
WHERE DepartmentID IN
  (SELECT DepartmentID FROM Department dept1
   WHERE NOT EXISTS
    (SELECT * FROM Delivery
     WHERE Delivery.DepartmentID = dept1.DepartmentID
     AND ItemID NOT IN
      (SELECT ItemID FROM Sale
       WHERE Sale.DepartmentID = dept1.DepartmentID)))
AND NOT EXISTS
  (SELECT * FROM Sale
   WHERE ItemID = sal.ItemID
   AND DepartmentID NOT IN
    (SELECT DepartmentID FROM Department dept2
     WHERE NOT EXISTS
      (SELECT * FROM Delivery
       WHERE Delivery.DepartmentID = dept2.DepartmentID
       AND ItemID NOT IN
        (SELECT ItemID FROM Sale
         WHERE Sale.DepartmentID = dept2.DepartmentID))));
```

ItemName
How to Win Foreign Friends
Exploring in 10 Easy Lessons

This is probably the longest query you will write.

SQL Divide - How it works

“Find the items that have appeared in all sales”

This query could be phrased as: "Select item names where *forall* sales, there *exists* a lineitem row recording that this item was sold." A quick inspection of Table 1 shows that one item satisfies this condition (itemno = 2). While SQL does not directly support *forall*, it can be expressed using *exists*. The query becomes "Find items such that there does not exist a sale in which this item does not appear." The equivalent SQL expression is (this is called an SQL Divide):

```
SELECT itemno, itemname FROM item
WHERE NOT EXISTS
  (SELECT * FROM sale
   WHERE NOT EXISTS
     (SELECT * FROM lineitem
      WHERE lineitem.itemno = item.itemno
      AND lineitem.saleno = sale.saleno))
```

itemno	itemname
2	Pocket knife--Avon

You may be convinced that this query is correct by walking through it step by step using the data in Table 1 and examining the outcome of each step of the query (see Table 2).

Step 1. The first row of item has itemno=1, and the first row of sale has saleno = 1. The innermost query becomes

```
SELECT * FROM lineitem
WHERE lineitem.itemno = 1
AND lineitem.saleno = 1
```

Examination of the lineitem table shows this query returns *false*, which is negated by the NOT before the innermost EXISTS to give *true*.

Step 2. We now advance to the second row of sale with saleno = 2, and execute the innermost query again. This query will also return false which will be negated to true.

Steps 3-5. The results of these and other steps are summarized in Table 2.

Step 6. The subquery

```
SELECT * FROM sale
WHERE NOT EXISTS (...
```

has now been executed for each value of saleno for the first value of itemno and returned *true* for each row. Thus this query returns *true*, and the NOT before the EXISTS of this query changes the *true* to *false*. Since the value returned is *false*, the current value of itemno is not reported.

sale	lineitem	item
saleno	lineno saleno itemno	itemno
1	1 1 2	1
2	1 2 6	2
3	2 2 16	3
4	3 2 19	...
5	4 2 2	
	1 3 4	
	2 3 2	
	1 4 4	
	2 4 9	
	3 4 13	
	4 4 14	
	5 4 3	
	6 4 2	
	1 5 10	
	2 5 11	
	3 5 12	
	4 5 13	
	5 5 2	

Table 1: Condensed versions of sale, lineitem, and item

Steps 7-11. The results of these steps are shown in Table 2.

Step 12. The subquery

```
SELECT * FROM sale
WHERE NOT EXISTS (...
```

has now been executed for each value of saleno for the second value of itemno and returned *false* for each row. Although this query returns *false*, the NOT before the EXISTS changes the *false* to *true*. Since the value returned is *true*, the current value of itemno is reported. Item 2 appears in all sales.

It will take you some time to step through this example to understand how the double **NOT EXISTS** works. Once you do, you will be convinced that the query does work.

Step	itemno	saleno	SELECT * FROM lineitem WHERE lineitem.itemno = item.itemno AND lineitem.saleno = sale.saleno	NOT EXISTS	SELECT * FROM sale WHERE NOT EXISTS (SELECT * FROM lineitem WHERE lineitem.itemno = item.itemno AND lineitem.saleno = sale.saleno)	NOT EXISTS
1	1	1	false	true		
2	1	2	false	true		
3	1	3	false	true		
4	1	4	false	true		
5	1	5	false	true		
6					true	false
7	2	1	true	false		
8	2	2	true	false		
9	2	3	true	false		
10	2	4	true	false		
11	2	5	true	false		
12					false	true
13	3	1	false	true		
14	3	2	false	true		
15	3	3	false	true		
16	3	4	true	false		
17	3	5	false	true		
18					true	false

Table 2: Results of the first 18 steps of the divide statement.

Section 4: Write your own SQL queries

Write your own queries to answer these questions. Answers will be made available to you around week 8. These questions use the same colour code:

- green –easy
- blue - moderate
- red - hard

Week 3

1. List the green items of type C.
2. Find the departments that sell at least 4 items
3. Find the departments that sell at least 4 items and list how many items each department sells
4. Find the employees who are in the same department as their manager.
5. Find the names of brown items sold by the Recreation department.
6. Find the employees whose salary is less than half that of their managers.

Week 4

7. Find the departments that have never sold a geo positioning system
8. Find the items sold by at least two departments.
9. Find the name of the highest-paid employee in the Marketing department.
10. Find the names of employees who make 40 per cent less than the average salary.
11. Find the number of employees with a salary under \$15,000.
12. Find the number of units sold of each item.
13. Find the supplier that delivers no more than two items

Week 5

14. Find the suppliers that have never delivered a compass.
15. Find, for each department, its floor and the average salary in the department.
16. List the departments on the second floor.

17. List the names of items delivered by each supplier. Arrange the report by supplier name, and within supplier name, list the items in alphabetical order.
18. List the number of employees in each department.
19. Whom does Todd manage?
20. Find the first name of Sophie's boss.

Week 6

21. List the names of each manager and their employees arranged by manager's name and employee's name within manager.
22. Who earns the lowest salary?
23. Of those items delivered, find the items not delivered to the Books department.
24. Find the departments that have sold compasses and at least six other items.
25. Find the brown items sold by no department on the second floor.
26. Find the items delivered by all suppliers
27. Find the items not delivered by Nepalese Corp

Week 7

28. Find the items delivered for which there have been no sales.
29. Find the names of employees with a salary greater than the minimum salary paid to a manager.
30. Find the names of suppliers that do not supply compasses or geo positioning systems.
31. Find the number of items of type C sold by the departments on the third floor.
32. If Nancy's boss has a boss, who is it?
33. List each employee and the difference between his or her salary and the average salary of his or her department.
34. List the departments on the second floor that contain more than one employee.

Week 8

35. List the names of employees who earn more than the average salary of employees in the Accounting department.
36. List the names of managers who supervise only one person.
37. List the names of employees who earn less than the minimum salary of the Marketing department.
38. List the department and the item where the department is the only seller of that item.
39. Which department has the highest average salary?
40. Find the khaki items delivered by all suppliers.
41. Find the suppliers that deliver to all departments. Don't forget to exclude the administrative departments, which don't sell items.
42. Find the items delivered to all departments except Administration departments (Management, Marketing, Personnel, Accounting, Purchasing).