

ICPC Notebook

ContentsSultan Halim - National University of Singapore

1 Data Structure and Basics	1
1.1 Bitmask	1
1.2 Sam fenwick tree	1
1.3 Range fenwick tree	2
1.4 UFDS	2
1.5 Segment tree	2
1.6 Backtracking	2
1.7 Sparse Table	3
1.8 LCA	3
2 String	3
2.1 KMP	3
2.2 Aho-Corasick	3
2.3 Hash	3
2.4 SuffixArray	4
3 Graph Basic	4
3.1 Dijkstra	4
3.2 Bellman Ford	5
3.3 MCBM	5
4 Graph	5
4.1 2-SAT	5
4.2 Biconnected Component	6
4.3 Bridge Articulation	6
4.4 Dinic Max Flow	6
4.5 Directed MST	7
4.6 Eulerian Cycle	7
4.7 Edmonds Blossom	8
4.8 Hungarian Assignment	8
4.9 Min Cost Max Flow	9
4.10 Strongly Connected Component	9
4.11 LRFlow	10
4.12 Hopcroft Karp	10
4.13 Heavy Light Decomposition	10
4.14 Gomory-Hu	11
4.15 Online-Bridge	11
5 Math Basic	11
5.1 Big Integer	11
5.2 Prime	12
5.3 Pollard Rho	12
6 Math	13
6.1 Number theory	13
6.2 Chinese Remainder Theorem	14
6.3 Fast Fourier Transform	14
6.4 Sqrt Mod	14
6.5 Brent, Miller Rabin	14
7 Geometry	15
7.1 Rectangle in Rectangle	15
7.2 Geometry Basic	16
7.3 Geometry Circle	16
7.4 Geometry Polygon	17
7.5 Smallest Enclosing Circle	18
7.6 Geometry Complex	18
7.7 Latitude Longitude	18
7.8 Delaunay	19
7.9 Convex hull	19
8 Miscellaneous	19

8.1 Calendar Java	19
8.2 Dynamic Convex Hull DP (Max)	19
8.3 Floyd Cycle Finding	20
8.4 Josephus	20
8.5 Knight Shortest Path	20
8.6 DP Knuth	20
8.7 C++ Template	20
8.8 Java Template	20
8.9 pika	21

9 SHK	21
9.1 SHK C++	21
9.2 SHK Python	21
9.3 SHK Shortcuts	21

1 Data Structure and Basics

1.1 Bitmask

```

#define isOn(S, j) (S & (1 << j))
#define setBit(S, j) (S |= (1 << j))
#define clearBit(S, j) (S &= ~(1 << j))
#define toggleBit(S, j) (S ^= (1 << j))
#define lowBit(S) (S & (-S))
#define setAll(S, n) (S = (1 << n) - 1)

#define modulo(S, N) ((S) & (N - 1)) // returns S % N, where N is a power of 2
#define isPowerOfTwo(S) (!(S & (S - 1)))
#define nearestPowerOfTwo(S) ((int)pow(2.0, (int)(log((double)S) / log(2.0)) + 0.5))
#define turnOffLastBit(S) ((S) & (S - 1))
#define turnOnLastZero(S) ((S) | (S + 1))
#define turnOffLastConsecutiveBits(S) ((S) & (S + 1))
#define turnOnLastConsecutiveZeroes(S) ((S) | (S - 1))

#define LSONe(S) (S & (-S))

```

1.2 Sam fenwick tree

```

class FenwickTree { private:
    vector<long long int> ft;
    int n;

public:
    FenwickTree(int _n) : n(_n) {
        ft.assign(n+1, 0);
    }

    FenwickTree(const vector<int>& f) : n(f.size() - 1) {
        ft.assign(n+1, 0);
        for(int i = 1; i <= n; ++i) {
            ft[i] += f[i];
            if(i + LSONe(i) <= n) {
                ft[i + LSONe(i)] += ft[i];
            }
        }
    }

    long long int rsq(int b) {
        long long int sum = 0;
        for(; b >= LSONe(b);) {
            sum += ft[b];
        }
        return sum;
    }

    long long int rsq(int a, int b) {
        return rsq(b) - rsq(a);
    }

    void adjust(int k, long long int v) {
        for(; k <= n; k += LSONe(k)) {
            ft[k] += v;
        }
    }
};

```

1.3 Range fenwick tree

```
class FenwickTree {
private: vi ft1, ft2;
    int query(vi &ft, int b) {
        int sum = 0; for (; b; b -= LOne(b)) sum += ft[b];
        return sum; }
    void adjust(vi &ft, int k, int v) {
        for (; k < (int)ft.size(); k += LOne(k)) ft[k] += v; }
public:
    FenwickTree() {}
    FenwickTree(int n) { ft1.assign(n + 1, 0); ft2.assign(n+1, 0); }
    int query(int a) { return a + query(ft1, a) - query(ft2, a); }
    int query(int a, int b) { return query(b) - (a == 1 ? 0 : query(a-1)); }
    void adjust(int a, int b, int value){
        adjust(ft1, a, value);
        adjust(ft1, b+1, -value);
        adjust(ft2, a, value * (a-1));
        adjust(ft2, b+1, -1 * value * b);
    }
    int get(int n) {
        return query(n) - query(n-1); }
};
```

1.4 UFDS

```
class UnionFind {
public:
    vector<int> p, rank, setSize;
    int numSets;

public:
    UnionFind(int N) {
        numSets = N;
        setSize.assign(N, 1);
        rank.assign(N, 0);
        p.assign(N, 0);
        for(int i = 0; i < N; ++i) {
            p[i] = i;
        }

        int findSet(int i) {
            return (p[i] == i) ? i : (p[i] = findSet(p[i]));
        }

        bool isSameSet(int i, int j) {
            bool x = findSet(i) == findSet(j);
            return x;
        }

        void unionSet(int i, int j) {
            if(!isSameSet(i, j)) {
                numSets--;
                int x = findSet(i);
                int y = findSet(j);

                if(rank[x] > rank[y]) {
                    p[y] = x; setSize[x] += setSize[y];
                } else {
                    p[x] = y; setSize[y] += setSize[x];
                    if(rank[x] == rank[y]) {
                        rank[y]++;
                    }
                }
            }
        }

        int numDisjoinSets() {
            return numSets;
        }

        int sizeOfSet(int i) {
            return setSize[findSet(i)];
        }
};
```

1.5 Segment tree

```
class SegmentTree {
private: vi st, A;
    int n;
    int left(int p) { return p << 1; } // same as binary heap operations
    int right(int p) { return (p << 1) + 1; }

    void build(int p, int L, int R) { // O(n log n)
        if (L == R) // as L == R, either one is fine
            st[p] = L; // store the index
        else // recursively compute the values
            build(left(p), L, (L + R) / 2), build(right(p), (L + R) / 2 + 1, R);
            int p1 = st[left(p)], p2 = st[right(p)];
            st[p] = (A[p1] <= A[p2]) ? p1 : p2;
    }

    int rmq(int p, int L, int R, int i, int j) { // O(log n)
        if (i > R || j < L) return -1; // current segment outside query range
        if (L >= i && R <= j) return st[p]; // inside query range

        // compute the min position in the left and right part of the interval
        int p1 = rmq(left(p), L, (L+R) / 2, i, j);
        int p2 = rmq(right(p), (L+R) / 2 + 1, R, i, j);

        if (p1 == -1) return p2; // if we try to access segment outside query
        if (p2 == -1) return p1; // same as above
        return (A[p1] <= A[p2]) ? p1 : p2; // as as in build routine

    int update_point(int p, int L, int R, int idx, int new_value) {
        // this update code is still preliminary, i == j
        // must be able to update range in the future!
        int i = idx, j = idx;

        // if the current interval does not intersect
        // the update interval, return this st node value!
        if (i > R || j < L)
            return st[p];

        // if the current interval is included in the update range,
        // update that st[node]
        if (L == i && R == j) {
            A[i] = new_value; // update the underlying array
            return st[p] = L; // this index
        }

        // compute the minimum pition in the
        // left and right part of the interval
        int p1, p2;
        p1 = update_point(left(p), L, (L + R) / 2, idx, new_value);
        p2 = update_point(right(p), (L + R) / 2 + 1, R, idx, new_value);

        // return the pition where the overall minimum is
        return st[p] = (A[p1] <= A[p2]) ? p1 : p2;
    }

public:
    SegmentTree(const vi &A) {
        A = _A; n = (int)A.size(); // copy content for local usage
        st.assign(4 * n, 0); // create large enough vector of zeroes
        build(1, 0, n - 1); // recursive build

        int rmq(int i, int j) { return rmq(1, 0, n - 1, i, j); } // overloading

        int update_point(int idx, int new_value) {
            return update_point(1, 0, n - 1, idx, new_value);
        }
};
```

1.6 Backtracking

```
/* 8 Queens Chess Problem */
#include <cstdlib> // we use the int version of 'abs'
#include <cstdio>
#include <cstring>
using namespace std;

int row[8], TC, a, b, lineCounter; // ok to use global variables

bool place(int r, int c) {
    for (int prev = 0; prev < c; prev++) // check previously placed queens
        if (row[prev] == r || (abs(row[prev] - r) == abs(prev - c)))
            return false; // share same row or same diagonal -> infeasible
    return true;
}

void backtrack(int c) {
    if (c == 8 && row[b] == a) {
        // candidate sol, (a, b) has 1 queen
```

```

    printf("%2d %d", ++lineCounter, row[0] + 1);
    for (int j = 1; j < 8; j++) printf(" %d", row[j] + 1);
    printf("\n"); }
for (int r = 0; r < 8; r++) // try all possible row
    if (place(r, c)) { // if can place a queen at this col and row
        row[c] = r; backtrack(c + 1);
        // put this queen here and recurse
    } }

int main() {
    scanf("%d", &TC);
    while (TC--) {
        scanf("%d %d", &a, &b); a--; b--; // switch to 0-based indexing
        memset(row, 0, sizeof row); lineCounter = 0;
        printf("SOLN      C O L U M N\n");
        printf(" #          1  2  3  4  5  6  7  8\n\n");
        backtrack(0); // generate all possible 8! candidate solutions
        if (TC) printf("\n");
    } } // return 0;

```

1.7 Sparse Table

```

#define MAX_N 1000
#define LOG_TWO_N 10

class RMQ {
private:
    int _A[MAX_N], SpT[MAX_N][LOG_TWO_N];
public:
    RMQ(int n, int A[]) {
        for (int i = 0; i < n; i++) {
            _A[i] = A[i];
            SpT[i][0] = i;
        }
        for (int j = 1; (1 <= j) <= n; j++)
            for (int i = 0; i + (1 <= j) - 1 < n; i++)
                if (_A[SpT[i][j-1]] < _A[SpT[i+(1<=j-1)][j-1]])
                    SpT[i][j] = SpT[i][j-1];
                else
                    SpT[i][j] = SpT[i+(1 <= (j-1))][j-1];

        int query(int i, int j) {
            int k = (int) floor(log((double)j-i+1) / log(2.0));
            if (_A[SpT[i][k]] <= _A[SpT[j-(1<=k)+1][k]]) return SpT[i][k];
            else return SpT[j-(1<=k)+1][k];
        }
    };

```

1.8 LCA

```

inline void makeP() {
    int logg = lg[n];
    for (int j = 1; j <= logg; j++) {
        for (int i = 1; i <= n; i++) {
            if (P[i][j-1] != -1) {
                P[i][j] = P[P[i][j-1]][j-1];
            }
        }
    }
}

inline int LCA(int p, int q) {
    if (L[p] < L[q]) swap(p, q);
    int logg = lg[L[p]];
    for (int i = logg; i >= 0; i--) {
        if (L[p] - (1 <= i) >= L[q]) {
            p = P[p][i];
        }
    }
    if (p == q) return p;
    for (int i = logg; i >= 0; i--) {
        if (P[p][i] != -1 && P[p][i] != P[q][i]) {
            p = P[p][i];
            q = P[q][i];
        }
    }
    return P[p][0];
}

```

2 String

2.1 KMP

```

/*
Searches for the string w in the string s (of length k). Returns the
0-based index of the first match (k if no match is found). Algorithm
runs in O(k) time.
*/

#include <iostream>
#include <string>
#include <vector>

using namespace std;

typedef vector<int> VI;

void buildTable(string& w, VI& t)
{
    t = VI(w.length());
    int i = 2, j = 0;
    t[0] = -1; t[1] = 0;

    while (i < w.length())
    {
        if (w[i-1] == w[j]) { t[i] = j+1; i++; j++; }
        else if (j > 0) j = t[j];
        else { t[i] = 0; i++; }
    }
}

int KMP(string& s, string& w)
{
    int m = 0, i = 0;
    VI t;

    buildTable(w, t);
    while (m+i < s.length())
    {
        if (w[i] == s[m+i])
        {
            i++;
            if (i == w.length()) return m;
        }
        else
        {
            m += i-t[i];
            if (i > 0) i = t[i];
        }
    }
    return s.length();
}

```

2.2 Aho-Corasick

```

#include <bits/stdc++.h>
using namespace std;

// {{{ Aho Corasick
namespace AhoCorasick {
    struct Node {
        int next[26];
        int parent;
        int fromParent;
        int fail;
        int wordCount;
    };

    int last;
    Node node[MAXNODE];

    void init() {
        last = 0;
        for (int i = 0; i < MAXNODE; i++) {
            for (int j = 0; j < 26; j++) {
                node[i].next[j] = -1;
            }
            node[i].parent = node[i].fail = -1;
            node[i].wordCount = 0;
        }
    }
}

```

```

    node[0].fail = 0;
}

int addString(char *s, int offset = 'a') {
    int len = strlen(s);
    int cur = 0;
    for (int i = 0; i < len; i++) { //no C++11? BibleThump
        if (node[cur].next[s[i] - offset] == -1) {
            node[cur].next[s[i] - offset] = ++last;
            node[last].parent = cur;
            node[last].fromParent = s[i] - offset;
        }
        cur = node[cur].next[s[i] - offset];
    }
    node[cur].wordCount++;
    return cur;
}

void constructFail() {
    queue<int> q;
    q.push(0);
    while (!q.empty()) {
        int u = q.front();
        q.pop();
        for (int i = 0; i < 26; i++) {
            if (node[u].next[i] != -1) {
                q.push(node[u].next[i]);
            }
        }
        if (u == 0) {
            continue;
        }
        int v = node[node[u].parent].fail;
        int c = node[u].fromParent;
        while (v != 0 && node[v].next[c] == -1) {
            v = node[v].fail;
        }
        node[u].fail = node[v].next[c] != -1 && node[v].next[c] != u ? node[v].next[c] : 0;
    }
}

int search(char *s, int offset) {
    int len = strlen(s);
    int cur = 0;
    int match = 0;
    for (int i = 0; i < len; i++) {
        while (cur != 0 && node[cur].next[s[i] - offset] == -1) {
            assert(node[cur].fail != -1);
            cur = node[cur].fail;
        }
        if (node[cur].next[s[i] - offset] != -1) {
            cur = node[cur].next[s[i] - offset];
        }
        assert(cur != -1);
        match += node[cur].wordCount;
    }
    return match;
}
// }}}

```

2.3 Hash

```

// {{{ Hash
template<int pr, int MOD> class Hash {
    int n;
    vector<int> p, v;
    void init() {
        p.resize(n);
        p[0] = 1;
        for (int i = 1; i < n; i++) {
            p[i] = (int)(1LL * p[i-1] * pr % MOD);
            v[i] = (int)(1LL * v[i-1] * pr % MOD) + v[i];
            if (v[i] >= MOD) v[i] -= MOD;
        }
    }
public:
    Hash() {}
    Hash(string s) {
        n = (int)s.length();
        v.resize(n);
        for (int i = 0; i < n; i++) {
            v[i] = s;
        }
        init();
    }
    Hash(const vector<int> &v) {
        this->v = v;
    }
}

```

```

n = (int)v.size();
for (auto &x : this->v) {
    x %= MOD;
    if (x < 0) x += MOD;
}
init();
int get(int l, int r) {
    int res = v[r] - (l > 0 ? (int)(1LL * v[l-1] * p[r-l+1] % MOD) : 0);
    if (res >= MOD) res -= MOD;
    if (res < 0) res += MOD;
    return res;
}
};
// }}}

```

2.4 SuffixArray

```

// Source: http://codeforces.com/contest/452/submission/7269543
// Efficient Suffix Array O(N*logN)

// String index from 0
// Usage:
// string s;
// SuffixArray sa(s);
// Now we can use sa.SA and sa.LCP
struct SuffixArray {
    string a;
    int N, m;
    vector<int> SA, LCP, x, y, w, c;

    SuffixArray(string _a, int m) : a(" " + _a), N(a.length()), m(m),
        SA(N), LCP(N), x(N), y(N), w(max(m, N)), c(N) {
        a[0] = 0;
        DA();
        kasailCP();
        #define REF(X) { rotate(X.begin(), X.begin()+1, X.end()); X.pop_back(); }
        REF(SA); REF(LCP);
        a = a.substr(1, a.size());
        for (int i = 0; i < SA.size(); ++i) --SA[i];
        #undef REF
    }

    inline bool cmp (const int a, const int b, const int l) { return (y[a] == y[b] && y[a+1] == y[b+1]); }

    void Sort() {
        for (int i = 0; i < m; ++i) w[i] = 0;
        for (int i = 0; i < N; ++i) ++w[x[y[i]]];
        for (int i = 0; i < m-1; ++i) w[i+1] += w[i];
        for (int i = N-1; i >= 0; --i) SA[--w[x[y[i]]]] = y[i];
    }

    void DA() {
        for (int i = 0; i < N; ++i) x[i] = a[i], y[i] = i;
        Sort();
        for (int i, j = 1, p = 1; p < N; j <= 1, m = p) {
            for (p = 0, i = N-j; i < N; i++) y[p++] = i;
            for (int k = 0; k < N; ++k) if (SA[k] >= j) y[p++] = SA[k] - j;
            Sort();
            for (swap(x, y), p = 1, x[SA[0]] = 0, i = 1; i < N; ++i)
                x[SA[i]] = cmp(SA[i-1], SA[i], j) ? p-1 : p++;
        }
    }

    void kasailCP() {
        for (int i = 0; i < N; ++i) c[SA[i]] = i;
        for (int i = 0, j, k = 0; i < N; LCP[c[i++]] = k)
            if (c[i] > 0) for (k ? k-- : 0, j = SA[c[i]-1]; a[i+k] == a[j+k]; k++);
            else k = 0;
    }
};

```

3 Graph Basic

3.1 Dijkstra

```

int main() {
    int V, E, s, u, v, w;
    vector<vii> AdjList;
}

```

```

AdjList.assign(V, vii()); // assign blank vectors of pair<int, int>s to AdjList
for (int i = 0; i < E; i++) {
    scanf("%d %d %d", &u, &v, &w);
    AdjList[u].push_back(ii(v, w));
    // directed graph
}

// Dijkstra routine
vi dist(V, INF); dist[s] = 0; // INF = 1B to avoid overflow
priority_queue<ii, vector<ii>, greater<ii> > pq; pq.push(ii(0, s)); // to sort the pairs by increasing distance

from s
while (!pq.empty()) { // main

    loop
    ii front = pq.top(); pq.pop(); // greedy: pick shortest unvisited vertex
    int d = front.first, u = front.second;
    if (d > dist[u]) continue; // this check is important, see the explanation
    for (int j = 0; j < (int)AdjList[u].size(); j++) {
        ii v = AdjList[u][j]; // all outgoing edges
        from u
        if (dist[u] + v.second < dist[v.first]) {
            dist[v.first] = dist[u] + v.second; // relax operation
            pq.push(ii(dist[v.first], v.first));
        } } // note: this variant can cause duplicate items in the priority queue

for (int i = 0; i < V; i++) // index + 1 for final answer
    printf("SSSP(%d, %d) = %d\n", s, i, dist[i]);

return 0;
}

```

3.2 Bellman Ford

```

int main() {
    int V, E, s, a, b, w;
    vector<vi> AdjList;

    AdjList.assign(V, vii()); // assign blank vectors of pair<int, int>s to AdjList
    for (int i = 0; i < E; i++) {
        scanf("%d %d %d", &a, &b, &w);
        AdjList[a].push_back(ii(b, w));
    }

    // Bellman Ford routine
    vi dist(V, INF); dist[s] = 0;
    for (int i = 0; i < V - 1; i++) // relax all E edges V-1 times, overall O(VE)
        for (int u = 0; u < V; u++) // these two loops = O(E)
            for (int j = 0; j < (int)AdjList[u].size(); j++) {
                ii v = AdjList[u][j]; // we can record SP spanning here if needed
                dist[v.first] = min(dist[v.first], dist[u] + v.second); // relax
            }

    bool hasNegativeCycle = false;
    for (int u = 0; u < V; u++) // one more pass to check
        for (int j = 0; j < (int)AdjList[u].size(); j++) {
            ii v = AdjList[u][j];
            if (dist[v.first] > dist[u] + v.second) // should be false
                hasNegativeCycle = true; // but if true, then negative cycle exists!
        }

    printf("Negative Cycle Exist? %s\n", hasNegativeCycle ? "Yes" : "No");

    if (!hasNegativeCycle)
        for (int i = 0; i < V; i++)
            printf("SSSP(%d, %d) = %d\n", s, i, dist[i]);

    return 0;
}

```

3.3 MCBM

```

vector<vi> AdjList;
vi match, vis; // global variables

int Aug(int l) { // return 1 if an augmenting path is found
    if (vis[l]) return 0; // return 0
    vis[l] = 1;
}

```

```

for (int j = 0; j < (int)AdjList[l].size(); j++) {
    int r = AdjList[l][j];
    if (match[r] == -1 || Aug(match[r])) {
        match[r] = l; return 1; // found 1
    }
}
return 0; // no matching

int main() {
    int V = 5, Vleft = 3; // we ignore vertex 0
    AdjList.assign(V, vii());
    AdjList[1].push_back(3); AdjList[1].push_back(4);
    AdjList[2].push_back(3);

    int MCBM = 0;
    match.assign(V, -1); // V is the number of vertices in bipartite graph
    for (int l = 0; l < Vleft; l++) { // Vleft = size of the left set
        vis.assign(Vleft, 0); // reset before each recursion
        MCBM += Aug(l);
    }

    printf("Found %d matchings\n", MCBM); // the answer is 2 for Figure 4.42

    return 0;
}

```

4 Graph

4.1 2-SAT

```

// VAR(x), NOT(x)
// TwoSat(int varCount)
// bool TwoSat.solve() -> vector<int> TwoSat.value
// {{{ 2-SAT
using graph = vector<vi>;
inline int VAR(int x) { return 2 * x; }
inline int NOT(int x) { return x ^ 1; }

struct TwoSat {
    int n;
    vi value;
    graph g, grev;
    TwoSat(int n) : n(2 * n), g(2 * n) {}

    void addImplication(int x, int y) {
        g[x].emplace_back(y);
        g[NOT(y)].emplace_back(NOT(x));
    }

    void addOr(int x, int y) {
        g[NOT(x)].emplace_back(y);
        g[NOT(y)].emplace_back(x);
    }

    void dfs(int u, graph &g, vi &visit, vi &order) {
        visit[u] = 1;
        for (int v : g[u]) {
            if (!visit[v]) {
                dfs(v, g, visit, order);
            }
        }
        order.push_back(u);
    }

    bool solve() {
        grev.assign(n, vi());
        for (int i = 0; i < n; i++) {
            for (int j : g[i]) {
                grev[j].push_back(i);
            }
        }
        vi visited(n, false);
        vi order;
        for (int i = 0; i < n; i++) {
            if (!visited[i]) {
                dfs(i, g, visited, order);
            }
        }
        reverse(ALL(order));
        vi repr(n);
        fill(ALL(visited), false);
        value.assign(n, -1);
    }
}

```

```

for (int u : order) {
    if (!visited[u]) {
        vi tmp;
        dfs(u, grev, visited, tmp);
        for (int v : tmp) {
            repr[v] = tmp[0];
            if (value[v] == -1) {
                value[v] = 1;
                value[NOT(v)] = 0;
            }
        }
    }
}
for (int i = 0; i < n; i++) {
    if (repr[i] == repr[NOT(i)]) {
        return false;
    }
}
return true;
};
// }}}

```

4.2 Biconnected Component

```

// Input graph: vector< vector<int> > a, int n
// Note: 0-indexed
// Usage: BiconnectedComponent bc; (bc.components is the list of components)

struct BiconnectedComponent {
    vector<int> low, num, s;
    vector< vector<int> > components;
    int counter;

    BiconnectedComponent() : num(n, -1), low(n, -1), counter(0) {
        for (int i = 0; i < n; i++)
            if (num[i] < 0)
                dfs(i, 1);
    }

    void dfs(int x, int isRoot) {
        low[x] = num[x] = ++counter;
        if (a[x].empty()) {
            components.push_back(vector<int>(1, x));
            return;
        }
        s.push_back(x);

        for (int i = 0; i < a[x].size(); i++) {
            int y = a[x][i];
            if (num[y] > -1) low[x] = min(low[x], num[y]);
            else {
                dfs(y, 0);
                low[x] = min(low[x], low[y]);

                if (isRoot || low[y] >= num[x]) {
                    components.push_back(vector<int>(1, x));
                    while (1) {
                        int u = s.back();
                        s.pop_back();
                        components.back().push_back(u);
                        if (u == y) break;
                    }
                }
            }
        }
    }
};

```

4.3 Bridge Articulation

```

// Assume already have undirected graph vector< vector<int> > G with V vertices
// Vertex index from 0
// Usage:
// UndirectedDfs tree;
// Then you can use tree.bridges and tree.cuts
struct UndirectedDfs {
    vector<int> low, num, parent;
    vector<bool> articulation;
    int counter, root, children;

    vector< pair<int, int> > bridges;
    vector<int> cuts;
};

```

```

UndirectedDfs() : low(V, 0), num(V, -1), parent(V, 0), articulation(V, false),
    counter(0), children(0) {
    for (int i = 0; i < V; ++i) if (num[i] == -1) {
        root = i; children = 0;
        dfs(i);
        articulation[root] = (children > 1);
    }
    for (int i = 0; i < V; ++i)
        if (articulation[i]) cuts.push_back(i);
}

private:
void dfs(int u) {
    low[u] = num[u] = counter++;
    for (int j = 0; j < G[u].size(); ++j) {
        int v = G[u][j];
        if (num[v] == -1) {
            parent[v] = u;
            if (u == root) children++;
            dfs(v);
            if (low[v] >= num[u])
                articulation[u] = true;
            if (low[v] > num[u]) bridges.push_back(make_pair(u, v));
            low[u] = min(low[u], low[v]);
        } else if (v != parent[u])
            low[u] = min(low[u], num[v]);
    }
}
};

```

4.4 Dinic Max Flow

```

#include <bits/stdc++.h>
using namespace std;

//Add Edge : MaxFlow.addEdge(int from, int to, F capacity)
//Solve : MaxFlow.calcMaxFlow(int source, int sink)
// {{{ Dinic Max Flow<F=int>
template<typename F = int>
struct DinicMaxFlow {
    struct Edge {
        int to, rev;
        F flow, cap;
    };

    const F INF_FLOW = numeric_limits<F>::max() / 2;
    const int INF_DIST = 1e9;

    int source, sink;
    vector<vector<Edge>> graph;
    vector<int> dist, ptr;

    DinicMaxFlow(int N) : graph(N), dist(N), ptr(N) {}

    void addEdge(int from, int to, F cap) {
        if (from == to) {
            return;
        }
        Edge e1 { to, SZ(graph[to]), 0, cap };
        Edge e2 { from, SZ(graph[from]), 0, 0 };
        graph[from].push_back(e1);
        graph[to].push_back(e2);
    }

    bool buildLevelGraph() {
        fill(begin(dist), end(dist), INF_DIST);
        queue<int> q;
        dist[source] = 0;
        q.push(source);
        while (!q.empty()) {
            int u = q.front();
            q.pop();
            for (const auto &e : graph[u]) {
                if (e.flow < e.cap && dist[e.to] > dist[u] + 1) {
                    dist[e.to] = dist[u] + 1;
                    q.push(e.to);
                }
            }
        }
        return dist[sink] != INF_DIST;
    }

    F dfs(int u, F bottleneck) {
        if (u == sink || bottleneck == 0) {
            return bottleneck;
        }
        for (int &i : ptr[u]; i < SZ(graph[u]); i++) {
            auto &e = graph[u][i];

```

```

    auto &b = graph[e.to][e.rev];
    if (dist[e.to] != dist[u] + 1 || e.flow >= e.cap) {
        continue;
    }
    F pushed = dfs(e.to, min(e.cap - e.flow, bottleneck));
    if (pushed > 0) {
        e.flow += pushed;
        b.flow -= pushed;
        return pushed;
    }
}
return 0;
}

F calcMaxFlow(const int source, const int sink) {
    this->source = source;
    this->sink = sink;
    F mf = 0;
    while (buildLevelGraph()) {
        fill(begin(ptr), end(ptr), 0);
        F pushed;
        while ((pushed = dfs(source, INF_FLOW))) {
            mf += pushed;
        }
    }
    return mf;
}
};
// }}}

```

4.5 Directed MST

```

#include "../template.h"

const int maxe = 100111;
const int maxv = 100;

// Index from 0
// Running time O(E*V)
namespace chuliu {
    struct Cost;
    vector<Cost> costlist;

    struct Cost {
        int id, val, used, a, b, pos;
        Cost() { val = -1; used = 0; }
        Cost(int _id, int _val, bool temp) {
            a = b = -1; id = _id; val = _val; used = 0;
            pos = costlist.size(); costlist.push_back(*this);
        }
        Cost(int _a, int _b) {
            a = _a; b = _b; id = -1; val = costlist[a].val - costlist[b].val;
            used = 0; pos = costlist.size(); costlist.push_back(*this);
        }
        void push() {
            if (id == -1) {
                costlist[a].used += used;
                costlist[b].used -= used;
            }
        }
    };

    struct Edge {
        int u, v;
        Cost cost;
        Edge() {}
        Edge(int id, int _u, int _v, int c) {
            u = _u; v = _v; cost = Cost(id, c, 0);
        }
    } edge[maxe];

    int n, m, root, pre[maxv], node[maxv], vis[maxv], best[maxv];

    void init(int _n) {
        n = _n; m = 0;
        costlist.clear();
    }

    void add(int id, int u, int v, int c) {
        edge[m++] = Edge(id, u, v, c);
    }

    int mst(int root) {
        int ret = 0;

        while (true) {
            REP(i, n) best[i] = -1;

```

```

            REP(e, m) {
                int u = edge[e].u, v = edge[e].v;
                if ((best[v] == -1 || edge[e].cost.val < costlist[best[v]].val) && u != v) {
                    pre[v] = u;
                    best[v] = edge[e].cost.pos;
                }
            }

            REP(i, n) if (i != root && best[i] == -1) return -1;

            int cntnode = 0;
            memset(node, -1, sizeof node); memset(vis, -1, sizeof vis);

            REP(i, n) if (i != root) {
                ret += costlist[best[i]].val;
                costlist[best[i]].used++;

                int v = i;
                while (vis[v] != i && node[v] == -1 && v != root) {
                    vis[v] = i;
                    v = pre[v];
                }

                if (v != root && node[v] == -1) {
                    for (int u = pre[v]; u != v; u = pre[u]) node[u] = cntnode;
                    node[v] = cntnode++;
                }
            }

            if (cntnode == 0) break;

            REP(i, n) if (node[i] == -1) node[i] = cntnode++;

            REP(e, m) {
                int v = edge[e].v;
                edge[e].u = node[edge[e].u];
                edge[e].v = node[edge[e].v];
                if (edge[e].u != edge[e].v) edge[e].cost = Cost(edge[e].cost.pos, best[v]);
            }

            n = cntnode;
            root = node[root];
        }

        return ret;
    }

    vector<int> trace() {
        vector<int> ret;
        FORD(i, costlist.size()-1, 0) costlist[i].push();
        REP(i, costlist.size()) {
            Cost cost = costlist[i];
            if (cost.id != -1 && cost.used > 0) ret.push_back(cost.id);
        }
        return ret;
    }
}

int main() {

```

4.6 Eulerian Cycle

```

// directed!
// careful with empty graph!
// {{{ eulerianTour
template<typename T>
bool eulerianTour(const vector<vector<T>> &g, vi &tour) {
    int n = SZ(g);
    int edgeCount = 0;
    vi inDeg(n), outDeg(n);
    for (int i = 0; i < n; i++) {
        outDeg[i] = SZ(g[i]);
        for (auto &it : g[i]) {
            inDeg[it.fi]++;
            edgeCount++;
        }
    }

    int out = -1, in = -1;
    for (int i = 0; i < n; i++) {
        if (inDeg[i] == outDeg[i] + 1) {
            debug printf("finish vertex %d\n", i);
            if (out == -1) {
                out = i;
            } else {
                return false;
            }
        }
    }
}

```

```

    } else if (outDeg[i] == inDeg[i] + 1) {
        debug printf("start vertex %d\n", i);
        if (in == -1) {
            in = i;
        } else {
            return false;
        }
    } else if (outDeg[i] != inDeg[i]) {
        return false;
    }
}
// either zero or both
if ((in != -1) ^ (out != -1)) {
    return false;
}
if (in == -1) {
    for (int i = 0; i < n; i++) {
        if (outDeg[i] != 0) {
            in = out = i;
            break;
        }
    }
}
// empty graph?
if (in == -1) {
    in = out = 0;
}
}
tour.clear();
stack<int> st;
vi visit(n);
vi ptr(n);
st.push(in);
while (!st.empty()) {
    int u = st.top();
    visit[u] = true;
    if (ptr[u] == S2(g[u])) {
        tour.push_back(u);
        st.pop();
    } else {
        st.push(g[u][ptr[u]++].fi);
    }
}
reverse(ALL(tour));
return S2(tour) == edgeCount + 1;
}
// }}}

```

4.7 Edmonds Blossom

```

// General matching on graph

const int maxv = 1000;
const int maxe = 50000;

// Index from 1
// Directed
struct EdmondsLawler {
    int n, E, start, finish, newRoot, qsize, adj[maxe], next[maxe], last[maxv], mat[maxv], que[maxv],
        dad[maxv], root[maxv];
    bool inque[maxv], inpath[maxv], inblossom[maxv];

    void init(int _n) {
        n = _n; E = 0;
        for (int x=1; x<=n; ++x) { last[x] = -1; mat[x] = 0; }
    }

    void add(int u, int v) {
        adj[E] = v; next[E] = last[u]; last[u] = E++;
    }

    int lca(int u, int v) {
        for (int x=1; x<=n; ++x) inpath[x] = false;
        while (true) {
            u = root[u];
            inpath[u] = true;
            if (u == start) break;
            u = dad[mat[u]];
        }
        while (true) {
            v = root[v];
            if (inpath[v]) break;
            v = dad[mat[v]];
        }
        return v;
    }

    void trace(int u) {
        while (root[u] != newRoot) {
            int v = mat[u];
            inblossom[root[u]] = true;

```

```

            inblossom[root[v]] = true;
            u = dad[v];
            if (root[u] != newRoot) dad[u] = v;
        }
    }

    void blossom(int u, int v) {
        for (int x=1; x<=n; ++x) inblossom[x] = false;

        newRoot = lca(u, v);
        trace(u); trace(v);

        if (root[u] != newRoot) dad[u] = v;
        if (root[v] != newRoot) dad[v] = u;

        for (int x=1; x<=n; ++x) if (inblossom[root[x]]) {
            root[x] = newRoot;
            if (!inque[x]) {
                inque[x] = true;
                que[qsize++] = x;
            }
        }
    }

    bool bfs() {
        for (int x=1; x<=n; ++x) {
            inque[x] = false;
            dad[x] = 0;
            root[x] = x;
        }
        qsize = 0;
        que[qsize++] = start;
        inque[start] = true;
        finish = 0;

        for (int i=0; i<qsize; ++i) {
            int u = que[i];
            for (int e = last[u]; e != -1; e = next[e]) {
                int v = adj[e];
                if (root[v] != root[u] && v != mat[u]) {
                    if (v == start || (mat[v] > 0 && dad[mat[v]] > 0)) blossom(u, v);
                    else if (dad[v] == 0) {
                        dad[v] = u;
                        if (mat[v] > 0) que[qsize++] = mat[v];
                        else {
                            finish = v;
                            return true;
                        }
                    }
                }
            }
        }
        return false;
    }

    void enlarge() {
        int u = finish;
        while (u > 0) {
            int v = dad[u], x = mat[v];
            mat[v] = u;
            mat[u] = v;
            u = x;
        }
    }

    int maxmat() {
        for (int x=1; x<=n; ++x) if (mat[x] == 0) {
            start = x;
            if (bfs()) enlarge();
        }

        int ret = 0;
        for (int x=1; x<=n; ++x) if (mat[x] > x) ++ret;
        return ret;
    }
} edmonds;

```

4.8 Hungarian Assignment

```

const int MN = 3210;
const int inf = 1000111000;

// Vertex: 1 --> nx, 1 --> ny
// cost >= 0
// fx[x] + fy[y] <= cost[x][y] for all x, y
// Min cost matching

struct Hungary {
    int nx, ny, cost[MN][MN], fx[MN], fy[MN], matx[MN], which[MN], dist[MN];
    bool used[MN];

```



```

void init(int _nx, int _ny) {
    nx = _nx; ny = _ny;
    memset(fx, 0, sizeof fx);
    memset(fy, 0, sizeof fy);
    memset(used, false, sizeof used);
    memset(matx, 0, sizeof matx);
    for(int i=0; i<=nx; ++i) for(int j=0; j<=ny; ++j) cost[i][j] = inf;
}

void add(int x, int y, int c) { cost[x][y] = min(cost[x][y], c); }

int mincost() {
    for(int x=1; x<=nx; ++x) {
        int y0 = 0; matx[0] = x;
        for(int y=0; y<=ny; ++y) { dist[y] = inf + 1; used[y] = false; }

        do {
            used[y0] = true;
            int x0 = matx[y0], delta = inf + 1, y1;

            for(int y=1; y<=ny; ++y) if (!used[y]) {
                int curdist = cost[x0][y] - fx[x0] - fy[y];
                if (curdist < dist[y]) {
                    dist[y] = curdist;
                    which[y] = y0;
                }
                if (dist[y] < delta) {
                    delta = dist[y];
                    y1 = y;
                }
            }

            for(int y=0; y<=ny; ++y) if (used[y]) {
                fx[matx[y]] += delta;
                fy[y] -= delta;
            } else dist[y] -= delta;

            y0 = y1;
        } while (matx[y0] != 0);

        do {
            int y1 = which[y0];
            matx[y0] = matx[y1];
            y0 = y1;
        } while (y0);
    }

    // return -fy[0]; // n u l u n m b o c b g h p y
    int ret = 0;
    for(int y=1; y<=ny; ++y) {
        int x = matx[y];
        if (cost[x][y] < inf) ret += cost[x][y];
    }
    return ret;
}
} hungary;

```

4.9 Min Cost Max Flow

```

// Min Cost Max Flow - SPFA
// Index from 0
// Lots of double comparison --> likely to fail for double
// Example:
// MinCostFlow mcf(n);
// mcf.addEdge(1, 2, 3, 4);
// cout << mcf.minCostFlow() << endl;

template<class Flow=int, class Cost=int>
struct MinCostFlow {
    const Flow INF_FLOW = 1000111000;
    const Cost INF_COST = 1000111000111000LL;

    int n, t, S, T;
    Flow totalFlow;
    Cost totalCost;
    vector<int> last, visited;
    vector<Cost> dis;
    struct Edge {
        int to;
        Flow cap;
        Cost cost;
        int next;
        Edge(int to, Flow cap, Cost cost, int next) :
            to(to), cap(cap), cost(cost), next(next) {}
    };
    vector<Edge> edges;

```

```

MinCostFlow(int n) : n(n), t(0), totalFlow(0), totalCost(0), last(n, -1), visited(n, 0), dis(n, 0)
{
    edges.clear();
}

int addEdge(int from, int to, Flow cap, Cost cost) {
    edges.push_back(Edge(to, cap, cost, last[from]));
    last[from] = t++;
    edges.push_back(Edge(from, 0, -cost, last[to]));
    last[to] = t++;
    return t - 2;
}

pair<Flow, Cost> minCostFlow(int _S, int _T) {
    S = _S; T = _T;
    SPFA();
    while (1) {
        while (1) {
            REP(i, n) visited[i] = 0;
            if (!findFlow(S, INF_FLOW)) break;
        }
        if (!modifyLabel()) break;
    }
    return make_pair(totalFlow, totalCost);
}

private:
void SPFA() {
    REP(i, n) dis[i] = INF_COST;
    priority_queue< pair<Cost, int> > Q;
    Q.push(make_pair(dis[S]=0, S));
    while (!Q.empty()) {
        int x = Q.top().second;
        Cost d = -Q.top().first;
        Q.pop();
        // For double: dis[x] > d + EPS
        if (dis[x] != d) continue;
        for(int it = last[x]; it >= 0; it = edges[it].next)
            if (edges[it].cap > 0 && dis[edges[it].to] > d + edges[it].cost)
                Q.push(make_pair(-(dis[edges[it].to] = d + edges[it].cost), edges[it].to));
    }
    REP(i, n) dis[i] = dis[T] - dis[i];
}

Flow findFlow(int x, Flow flow) {
    if (x == T) {
        totalCost += dis[S] * flow;
        totalFlow += flow;
        return flow;
    }
    visited[x] = 1;
    Flow now = flow;
    for(int it = last[x]; it >= 0; it = edges[it].next)
        // For double: fabs(dis[edges[it].to] + edges[it].cost - dis[x]) < EPS
        if (edges[it].cap && !visited[edges[it].to] && dis[edges[it].to] + edges[it].cost == dis[x]) {
            Flow tmp = findFlow(edges[it].to, min(now, edges[it].cap));
            edges[it].cap -= tmp;
            edges[it ^ 1].cap += tmp;
            now -= tmp;
            if (!now) break;
        }
    return flow - now;
}

bool modifyLabel() {
    Cost d = INF_COST;
    REP(i, n) if (visited[i])
        for(int it = last[i]; it >= 0; it = edges[it].next)
            if (edges[it].cap && !visited[edges[it].to])
                d = min(d, dis[edges[it].to] + edges[it].cost - dis[i]);

    // For double: if (d > INF_COST / 10) INF_COST = 1e20
    if (d == INF_COST) return false;
    REP(i, n) if (visited[i])
        dis[i] += d;
    return true;
}
}

```

4.10 Strongly Connected Component

```

// Assume that already have directed graph vector< vector<int> > G with V vertices
// Index from 0
// Usage:
// DirectedDfs tree;
// Now you can use tree.scc

```

```

struct DirectedDfs {
    vector<int> num, low, current, S;
    int counter;
    vector< vector<int> > scc;

    DirectedDfs() : num(V, -1), low(V, 0), current(V, 0), counter(0) {
        REP(i, V) if (num[i] == -1) dfs(i);
    }

    void dfs(int u) {
        low[u] = num[u] = counter++;
        S.push_back(u);
        current[u] = 1;
        REP(j, G[u].size()) {
            int v = G[u][j];
            if (num[v] == -1) dfs(v);
            if (current[v]) low[u] = min(low[u], low[v]);
        }
        if (low[u] == num[u]) {
            scc.push_back(vector<int>());
            while (1) {
                int v = S.back(); S.pop_back(); current[v] = 0;
                scc.back().push_back(v);
                if (u == v) break;
            }
        }
    }
};

```

4.11 LRFlow

```

#include "Dinic.cpp"

//Construct : LRFlow(int N, int originalSource, int originalSink)
//Add Edge : LRFlow.addEdge(int from, int to, F lowerBound, F upperBound) []
//Solve: LRFlow.calcLRFlow()
// {{{ LR FLOW<F=int, MF=DinicMaxFlow<F>>
template<typename F = int, typename MF = DinicMaxFlow<F>>
struct LRFlow {
    MF mf;
    F lowerBoundSum = 0;
    int n, realSource, realSink;

    LRFlow(int n, int src, int snk) : mf(n + 2), n(n + 2) {
        realSource = this->n - 2;
        realSink = this->n - 1;
        mf.addEdge(snk, src, mf.INF_FLOW);
    }

    void addEdge(int from, int to, F lowerBound, F upperBound) {
        assert(lowerBound <= upperBound);
        lowerBoundSum += lowerBound;
        mf.addEdge(from, to, upperBound - lowerBound);
        mf.addEdge(realSource, to, lowerBound);
        mf.addEdge(from, realSink, lowerBound);
    }

    pair<F, bool> calcLRFlow() {
        F maxFlow = mf.calcMaxFlow(realSource, realSink);
        return make_pair(maxFlow, maxFlow == lowerBoundSum);
    }
};
// }}}

```

4.12 Hopcroft Karp

```

#include <algorithm>
#include <iostream>

using namespace std;

const int MAXN1 = 50000;
const int MAXN2 = 50000;
const int MAXM = 150000;

int n1, n2, edges, last[MAXN1], prev[MAXM], head[MAXM];
int matching[MAXN2], dist[MAXN1], Q[MAXN1];
bool used[MAXN1], vis[MAXN1];

void init(int _n1, int _n2) {
    n1 = _n1;
    n2 = _n2;
    edges = 0;
}

```

```

        fill(last, last + n1, -1);
    }

    void addEdge(int u, int v) {
        head[edges] = v;
        prev[edges] = last[u];
        last[u] = edges++;
    }

    void bfs() {
        fill(dist, dist + n1, -1);
        int sizeQ = 0;
        for (int u = 0; u < n1; ++u) {
            if (!used[u]) {
                Q[sizeQ++] = u;
                dist[u] = 0;
            }
        }
        for (int i = 0; i < sizeQ; i++) {
            int u1 = Q[i];
            for (int e = last[u1]; e >= 0; e = prev[e]) {
                int u2 = matching[head[e]];
                if (u2 >= 0 && dist[u2] < 0) {
                    dist[u2] = dist[u1] + 1;
                    Q[sizeQ++] = u2;
                }
            }
        }
    }

    bool dfs(int u1) {
        vis[u1] = true;
        for (int e = last[u1]; e >= 0; e = prev[e]) {
            int v = head[e];
            int u2 = matching[v];
            if (u2 < 0 || !vis[u2] && dist[u2] == dist[u1] + 1 && dfs(u2)) {
                matching[v] = u1;
                used[u1] = true;
                return true;
            }
        }
        return false;
    }

    int maxMatching() {
        fill(used, used + n1, false);
        fill(matching, matching + n2, -1);
        for (int res = 0;;) {
            bfs();
            fill(vis, vis + n1, false);
            int f = 0;
            for (int u = 0; u < n1; ++u)
                if (!used[u] && dfs(u))
                    ++f;
            if (!f)
                return res;
            res += f;
        }
    }

    int main() {
        init(2, 2);

        addEdge(0, 0);
        addEdge(0, 1);
        addEdge(1, 1);

        cout << (2 == maxMatching()) << endl;
    }
}

```

4.13 Heavy Light Decomposition

```

template <class T, int V>
class HeavyLight {
    int parent[V], heavy[V], depth[V];
    int root[V], treePos[V];
    SegmentTree<T> tree;

    template <class G>
    int dfs(const G& graph, int v) {
        int size = 1, maxSubtree = 0;
        for (int u : graph[v]) if (u != parent[v]) {
            parent[u] = v;
            depth[u] = depth[v] + 1;
            int subtree = dfs(graph, u);
            if (subtree > maxSubtree) heavy[v] = u, maxSubtree = subtree;
            size += subtree;
        }
    }
}

```

```

    }
    return size;
}

template <class BinaryOperation>
void processPath(int u, int v, BinaryOperation op) {
    for (; root[u] != root[v]; v = parent[root[v]]) {
        if (depth[root[u]] > depth[root[v]]) swap(u, v);
        op(treePos[root[v]], treePos[v] + 1);
    }
    if (depth[u] > depth[v]) swap(u, v);
    op(treePos[u], treePos[v] + 1);
}

public:
    template <class G>
    void init(const G& graph) {
        int n = graph.size();
        fill_n(heavy, n, -1);
        parent[0] = -1;
        depth[0] = 0;
        dfs(graph, 0);
        for (int i = 0, currentPos = 0; i < n; ++i)
            if (parent[i] == -1 || heavy[parent[i]] != i)
                for (int j = i; j != -1; j = heavy[j]) {
                    root[j] = i;
                    treePos[j] = currentPos++;
                }
        tree.init(n);
    }

    void set(int v, const T& value) {
        tree.set(treePos[v], value);
    }

    void modifyPath(int u, int v, const T& value) {
        processPath(u, v, [this, &value](int l, int r) { tree.modify(l, r, value); });
    }

    T queryPath(int u, int v) {
        T res = T();
        processPath(u, v, [this, &res](int l, int r) { res.add(tree.query(l, r)); });
        return res;
    }
};

```

4.14 Gomory-Hu

```

// tree which represents all-pair min-cut
// min-cut of u-v = minimum edge in path from u to v in tree
// combine the following function with usual max flow routine
// also because we need to reset the flow graph during each max flow, // don't forget to add variable
// in struct to record initial capacity
void buildGomoryHu() {
    for(int i = 2; i <= n; i++)
        parent[i] = 1;
    for(int i = 2; i <= n; i++) {
        int minCut = maxFlow(i, parent[i]);
        tree[parent[i]].pb((i, minCut));
        // the one below is not necessary if we want to make a rooted tree tree[i].pb((parent[i], minCut));
        for(int j = i + 1; j <= n; j++) {
            if(dist[j] != -1 && parent[j] == parent[i]) {
                parent[j] = i;
            }
        }
    }
}

```

4.15 Online-Bridge

```

// O(N + M)
int psetBridge[N], psetComp[N]; // UF super vertice, UF tree int par[N];
bool seen[N];
int size[N];
int bridge;
int n;
void reset() {
    for(int i = 0; i <= n; i++) {
        psetBridge[i] = psetComp[i] = i;
        par[i] = -1;
        seen[i] = 0;
        size[i] = 1;
    }
}

```

```

    bridge = 0;
}

int findsB(int x) {
    if(x == -1) return -1;
    return x == psetBridge[x] ? x : psetBridge[x] = findsB(psetBridge[x]);
}

int findsC(int x) {
    x = findsB(x);
    return x == psetComp[x] ? x : psetComp[x] = findsC(psetComp[x]);
}

void makeRoot(int x) { // make super vertice which contains x root of its tree
    x = findsB(x);
    int root = x;
    int chld = -1;
    while(x != -1) {
        int papa = findsB(par[x]);
        par[x] = chld;
        psetComp[x] = root;
        chld = x;
        x = papa;
    }
    size[root] = size[chld];
}

void mergePath(int u, int v) { // remove bridge between u and v in tree vector<int> vu, vv;
    int lca = -1;
    while(1) {
        if(u != -1) {
            u = findsB(u);
            vu.push_back(u);
            if(seen[u]) {
                lca = u;
                break;
            }
            seen[u] = 1;
            u = par[u];
        }
        if(v != -1) {
            v = findsB(v);
            vv.push_back(v);
            if(seen[v]) {
                lca = v;
                break;
            }
            seen[v] = 1;
            v = par[v];
        }
    }
    for(int i = 0; i < 2; i++) {
        vector<int> &proc = i ? vv : vu;
        for(int x : proc) {
            psetBridge[x] = lca;
            if(x == lca) {
                break;
            }
            bridge--;
        }
        for(int x : proc)
            seen[x] = 0;
    }

    void addEdge(int u, int v) {
        u = findsB(u);
        v = findsB(v);
        if(u != v) {
            int uu = findsC(u);
            int vv = findsC(v);
            if(uu != vv) {
                bridge++;
                if(size[uu] > size[vv]) {
                    swap(u, v);
                    swap(vv, uu);
                }
                makeRoot(u);
                par[u] = psetComp[u] = v;
                size[vv] += size[u];
            } else
                mergePath(u, v);
        }
    }
}

```

5 Math Basic

5.1 Big Integer

```
import java.io.*;
```

```

import java.util.*;
import java.util.Scanner;
import java.math.BigInteger;

class BigInteger2 {
    public static void main(String[] args) throws Exception {
        BufferedReader br = new BufferedReader(new InputStreamReader(System.in));
        PrintWriter pw = new PrintWriter(new BufferedWriter(new OutputStreamWriter(System.out)));
        while (true) {
            String N = br.readLine();
            if (N == null) break;
            BigInteger BN = new BigInteger(N);
            BigInteger BRN = new BigInteger(
                new String(BN.toString().reverse().toString());
            pw.printf("%s is ", N);
            if (!BN.isProbablePrime(10)) // 10 is enough
                pw.printf("not prime.\n");
            else if (!BN.equals(BRN) && BRN.isProbablePrime(10))
                pw.printf("emirp.\n");
            else
                pw.printf("prime.\n");
            pw.close();
        }
    }

import java.util.Scanner; // Scanner class is inside package java.util
import java.math.BigInteger; // BigInteger class is inside package java.math

class Main { /* UVA 10925 - Krakovia, 0.732s in Java */
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int caseNo = 1;
        while (true) {
            int N = sc.nextInt(), F = sc.nextInt(); // N bills, F friends
            if (N == 0 && F == 0) break;
            BigInteger sum = BigInteger.ZERO; // BigInteger has this constant ZERO
            for (int i = 0; i < N; i++) { // sum the N large bills
                BigInteger V = sc.nextBigInteger(); // for reading next BigInteger!
                sum = sum.add(V); // this is BigInteger addition
            }
            System.out.println("Bill #" + (caseNo++) + " costs " +
                sum + ": each friend should pay " + sum.divide(BigInteger.valueOf(F)));
            System.out.println(); // the line above is BigInteger division
        } } // divide the large sum to F friends
    }
}

```

5.2 Prime

```

ll _sieve_size;
bitset<10000010> bs; // 10^7 should be enough for most cases
vi primes; // compact list of primes in form of vector<int>

// first part

void sieve(ll upperbound) { // create list of primes in [0..upperbound]
    _sieve_size = upperbound + 1; // add 1 to include upperbound
    bs.set();

    // set all bits to 1
    bs[0] = bs[1] = 0; //
    for (int i = 2; i <= _sieve_size; i++) if (bs[i]) {
        // cross out multiples of i starting from i * i!
        for (ll j = i * i; j <= _sieve_size; j += i) bs[j] = 0;
        primes.push_back(i); // also add this vector containing list of primes
    } // call this

    // method in main method

bool isPrime(ll N) { // a good enough deterministic prime tester
    if (N < _sieve_size) return bs[N]; // O(1) for small primes
    for (int i = 0; i < (int)primes.size(); i++)
        if (N % primes[i] == 0) return false;
    return true; // it takes longer time if N is a large prime!
} // note: only work for N <= (last prime in vi "primes")^2

// second part

vi primeFactors(ll N) { // remember: vi is vector of integers, ll is long long
    vi factors; // vi 'primes' (generated by sieve) is optional
    ll PF_idx = 0, PF = primes[PF_idx]; // using PF = 2, 3, 4, ..., is also ok
    while (N != 1 && (PF * PF <= N)) { // stop at sqrt(N), but N can get smaller
        while (N % PF == 0) { N /= PF; factors.push_back(PF); } // remove this PF
        PF = primes[++PF_idx]; // only consider primes!
    }
    if (N != 1) factors.push_back(N); // special case if N is actually a prime
    return factors; // if pf exceeds 32-bit integer, you have to change vi
}

```

```

// third part

ll numPF(ll N) {
    ll PF_idx = 0, PF = primes[PF_idx], ans = 0;
    while (N != 1 && (PF * PF <= N)) {
        while (N % PF == 0) { N /= PF; ans++; }
        PF = primes[++PF_idx];
    }
    if (N != 1) ans++;
    return ans;
}

ll numDiffPF(ll N) {
    ll PF_idx = 0, PF = primes[PF_idx], ans = 0;
    while (N != 1 && (PF * PF <= N)) {
        if (N % PF == 0) ans++; // count this pf
        only once
        while (N % PF == 0) N /= PF;
        PF = primes[++PF_idx];
    }
    if (N != 1) ans++;
    return ans;
}

ll sumPF(ll N) {
    ll PF_idx = 0, PF = primes[PF_idx], ans = 0;
    while (N != 1 && (PF * PF <= N)) {
        while (N % PF == 0) { N /= PF; ans += PF; }
        PF = primes[++PF_idx];
    }
    if (N != 1) ans += N;
    return ans;
}

ll numDiv(ll N) {
    ll PF_idx = 0, PF = primes[PF_idx], ans = 1; // start from ans = 1
    while (N != 1 && (PF * PF <= N)) {
        ll power = 0; //
        count the power
        while (N % PF == 0) { N /= PF; power++; }
        ans *= (power + 1); // according to
        the formula
        PF = primes[++PF_idx];
    }
    if (N != 1) ans *= 2; // (last factor has pow = 1, we add 1 to it)
    return ans;
}

ll sumDiv(ll N) {
    ll PF_idx = 0, PF = primes[PF_idx], ans = 1; // start from ans = 1
    while (N != 1 && (PF * PF <= N)) {
        ll power = 0;
        while (N % PF == 0) { N /= PF; power++; }
        ans *= ((ll)pow((double)PF, power + 1.0) - 1) / (PF - 1); // formula
        PF = primes[++PF_idx];
    }
    if (N != 1) ans *= ((ll)pow((double)N, 2.0) - 1) / (N - 1); // last one
    return ans;
}

ll EulerPhi(ll N) {
    ll PF_idx = 0, PF = primes[PF_idx], ans = N; // start from ans = N
    while (N != 1 && (PF * PF <= N)) {
        if (N % PF == 0) ans -= ans / PF; // only count unique factor
        while (N % PF == 0) N /= PF;
        PF = primes[++PF_idx];
    }
    if (N != 1) ans -= ans / N; // last factor
    return ans;
}

```

5.3 Pollard Rho

```

#include <cstdio>
using namespace std;

#define abs_val(a) ((a)>=0)?(a):-(a)
typedef long long ll;

ll mulmod(ll a, ll b, ll c) { // returns (a * b) % c, and minimize overflow
    ll x = 0, y = a % c;
    while (b > 0) {
        if (b % 2 == 1) x = (x + y) % c;
        y = (y * 2) % c;
        b /= 2;
    }
}

```

```

    }
    return x % c;
}

ll gcd(ll a, ll b) { return !b ? a : gcd(b, a % b); } // standard gcd

ll pollard_rho(ll n) {
    int i = 0, k = 2;
    ll x = 3, y = 3; // random seed = 3, other values possible
    while (1) {
        i++;
        x = (mulmod(x, x, n) + n - 1) % n; // generating function
        ll d = gcd(abs_val(y - x), n); // the key insight
        if (d != 1 && d != n) return d; // found one non-trivial factor
        if (i == k) y = x, k *= 2;
    }
}

int main() {
    ll n = 2063512844981574047LL; // we assume that n is not a large prime
    ll ans = pollard_rho(n); // break n into two non trivial factors
    if (ans > n / ans) ans = n / ans; // make ans the smaller factor
    printf("%lld %lld\n", ans, n / ans); // should be: 1112041493 1855607779
} // return 0;

```

6 Math

6.1 Number theory

```

// This is a collection of useful code for solving problems that
// involve modular linear equations. Note that all of the
// algorithms described here work on nonnegative integers.

```

```

#include <iostream>
#include <vector>
#include <algorithm>

using namespace std;

typedef vector<int> VI;
typedef pair<int, int> PII;

// return a % b (positive value)
int mod(int a, int b) {
    return ((a%b) + b) % b;
}

// computes gcd(a,b)
int gcd(int a, int b) {
    while (b) { int t = a%b; a = b; b = t; }
    return a;
}

// computes lcm(a,b)
int lcm(int a, int b) {
    return a / gcd(a, b)*b;
}

// (a^b) mod m via successive squaring
int powermod(int a, int b, int m)
{
    int ret = 1;
    while (b)
    {
        if (b & 1) ret = mod(ret*a, m);
        a = mod(a*a, m);
        b >>= 1;
    }
    return ret;
}

// returns g = gcd(a, b); finds x, y such that d = ax + by
int extended_euclid(int a, int b, int &x, int &y) {
    int xx = y = 0;
    int yy = x = 1;
    while (b) {
        int q = a / b;
        int t = b; b = a%b; a = t;
        t = xx; xx = x - q*xx; x = t;
        t = yy; yy = y - q*yy; y = t;
    }
    return a;
}

// finds all solutions to ax = b (mod n)
VI modular_linear_equation_solver(int a, int b, int n) {

```

```

    int x, y;
    VI ret;
    int g = extended_euclid(a, n, x, y);
    if (!(b%g)) {
        x = mod(x*(b / g), n);
        for (int i = 0; i < g; i++)
            ret.push_back(mod(x + i*(n / g), n));
    }
    return ret;
}

// computes b such that ab = 1 (mod n), returns -1 on failure
int mod_inverse(int a, int n) {
    int x, y;
    int g = extended_euclid(a, n, x, y);
    if (g > 1) return -1;
    return mod(x, n);
}

// Chinese remainder theorem (special case): find z such that
// z % m1 = r1, z % m2 = r2. Here, z is unique modulo M = lcm(m1, m2).
// Return (z, M). On failure, M = -1.
PII chinese_remainder_theorem(int m1, int r1, int m2, int r2) {
    int s, t;
    int g = extended_euclid(m1, m2, s, t);
    if (r1%g != r2%g) return make_pair(0, -1);
    return make_pair(mod(s*r2*m1 + t*r1*m2, m1*m2 / g), m1*m2 / g);
}

// Chinese remainder theorem: find z such that
// z % m[i] = r[i] for all i. Note that the solution is
// unique modulo M = lcm_i (m[i]). Return (z, M). On
// failure, M = -1. Note that we do not require the a[i]'s
// to be relatively prime.
PII chinese_remainder_theorem(const VI &m, const VI &r) {
    PII ret = make_pair(r[0], m[0]);
    for (int i = 1; i < m.size(); i++) {
        ret = chinese_remainder_theorem(ret.second, ret.first, m[i], r[i]);
        if (ret.second == -1) break;
    }
    return ret;
}

// computes x and y such that ax + by = c
// returns whether the solution exists
bool linear_diophantine(int a, int b, int c, int &x, int &y) {
    if (!(a && b))
    {
        if (c) return false;
        x = 0; y = 0;
        return true;
    }
    if (!a)
    {
        if (c % b) return false;
        x = 0; y = c / b;
        return true;
    }
    if (!b)
    {
        if (c % a) return false;
        x = c / a; y = 0;
        return true;
    }
    int g = gcd(a, b);
    if (c % g) return false;
    x = c / g + mod_inverse(a / g, b / g);
    y = (c - a*x) / b;
    return true;
}

int main() {
    // expected: 2
    cout << gcd(14, 30) << endl;

    // expected: 2 -2 1
    int x, y;
    int g = extended_euclid(14, 30, x, y);
    cout << g << " " << x << " " << y << endl;

    // expected: 95 451
    VI sols = modular_linear_equation_solver(14, 30, 100);
    for (int i = 0; i < sols.size(); i++) cout << sols[i] << " ";
    cout << endl;

    // expected: 8
    cout << mod_inverse(8, 9) << endl;

    // expected: 23 105
    //
    PII ret = chinese_remainder_theorem(VI({ 3, 5, 7 }), VI({ 2, 3, 2 }));
    cout << ret.first << " " << ret.second << endl;
}

```

```

ret = chinese_remainder_theorem(VI({ 4, 6 } ), VI({ 3, 5 } ));
cout << ret.first << " " << ret.second << endl;

// expected: 5 -15
if (!linear_diophantine(7, 2, 5, x, y)) cout << "ERROR" << endl;
cout << x << " " << y << endl;
return 0;
}

```

6.2 Chinese Remainder Theorem

```

bool linearCongruences(const vector<int> &a, const vector<int> &b,
    const vector<int> &m, int &x, int &M) {
    int n = a.size();
    x = 0; M = 1;
    REP(i, n) {
        int a_ = a[i] % M, b_ = b[i] - a[i] * x, m_ = m[i];
        int y, t, g = extgcd(a_, m_, y, t);
        if (b_ % g) return false;
        b_ /= g; m_ /= g;
        x += M * (y * b_ % m_);
        M *= m_;
    }
    x = (x + M) % M;
    return true;
}

```

6.3 Fast Fourier Transform

```

// {{{ FFT Generic
template<typename T>
struct FFTTrait {
    static T getRoot(int, bool) { assert(false); }
};

template<>
struct FFTTrait<complex<double>> {
    static complex<double> getRoot(int len, bool rev) {
        double ang = 2 * M_PI / len;
        return rev ? complex<double>{cos(ang), sin(ang)} : complex<double>{cos(-ang), sin(-ang)};
    }
};

template<typename T = complex<double>, typename Trait = FFTTrait<T>>
struct FFT {
    const static int MAXLEN = 1 << 20;
    static void reorder(vector<T> &data) {
        int n = SZ(data);
        assert(n > 0 && (n & (n - 1)) == 0);
        int bitCount = __builtin_ctz(n);
        for (int i = 0; i < n; i++) {
            int j = 0;
            for (int b = 0; b < bitCount; b++) {
                if (i & (1 << b)) {
                    j |= 1 << (bitCount - 1 - b);
                }
            }
            if (i < j) {
                swap(data[i], data[j]);
            }
        }
    }

    static void fix(vector<T> &data) {
        int n = 1;
        while (n < SZ(data)) n *= 2;
        n *= 2;
        data.resize(n);
    }

    static void fft(vector<T> &data, bool rev) {
        reorder(data);
        int n = SZ(data);
        for (int len = 2; len <= n; len <<= 1) {
            static T roots[MAXLEN];
            int len2 = len >> 1;
            T w = Trait::getRoot(len, rev);
            roots[0] = T(1);
            for (int i = 1; i < len2; i++) {
                roots[i] = roots[i - 1] * w; // binary? can be precomputed
            }
            for (int i = 0; i < n; i += len) {
                for (int j = 0; j < len2; j++) {
                    T p = data[i + j];
                    T q = roots[j] * data[i + j + len2];

```

```

        data[i + j] = p + q;
        data[i + j + len2] = p - q;
    }
}

if (rev) {
    for (int i = 0; i < n; i++) {
        data[i] /= n;
    }
}
};
// }}}

```

6.4 Sqrt Mod

```

// Jacobi Symbol (m/n), m, n 0 and n is odd
// (m/n)==1 x^2 == m (mod n) solvable, -1 unsolvable
#define NEGPOW(e) ((e) % 2 ? -1 : 1)
int jacobi(int a, int m) {
    if (a == 0) return m == 1 ? 1 : 0;
    if (a % 2) return NEGPOW((a-1)*(m-1)/4)*jacobi(m%a, a);
    else return NEGPOW((m-m-1)/8)*jacobi(a/2, m);
}

int invMod(int a, int m) {
    int x, y;
    if (extgcd(a, m, x, y) == 1) return (x + m) % m;
    else return 0; // unsolvable
}

// No solution when: n(p-1)/2 = -1 mod p
int sqrtMod(int n, int p) { //find x: x^2 = n (mod p) p is prime
    int S, Q, W, i, m = invMod(n, p);
    for (Q = p - 1, S = 0; Q % 2 == 0; Q /= 2, ++S);
    do { W = rand() % p; } while (W == 0 || jacobi(W, p) != -1);
    for (int R = powMod(n, (Q+1)/2, p), V = powMod(W, Q, p); ;) {
        int z = R * R * m % p;
        for (i = 0; i < S && z % p != 1; z *= V, ++i);
        if (i == 0) return R;
        R = (R + powMod(V, 1 << (S-i-1), p)) % p;
    }
}

int powMod (int a, int b, int p) {
    int res = 1;
    while (b)
        if (b & 1)
            res = int (res * 1ll * a % p), --b;
        else
            a = int (a * 1ll * a % p), b >>= 1;
    return res;
}

```

6.5 Brent, Miller Rabin

```

#include "../Prime/RabinMiller.h"

long long mul(long long a, long long b, long long mod) {
    if (b == 0) return 0;
    if (b == 1) return a % mod;
    long long mid = mul(a, b >> 1, mod);
    mid = (mid + mid) % mod;
    if (b & 1) return (mid + a) % mod;
    else return mid;
}

long long brent(long long n) {
    if (n == 1) return 1;
    if (!(n & 1)) return 2;
    if (!(n % 3)) return 3;

    const int p[3] = {1, 3, 5};
    long long y, q, x, ys, g, my = 3;
    int i, j, k, m, r, c;

    for (i = 0; i < my; ++i) {
        y = 1; r = 1; q = 1; m = 111; c = p[i];

        do {
            x = y; k = 0;
            for (j = 1; j <= r; ++j) y = (mul(y, y, n) + c) % n;
            do {
                ys = y;
                for (j = 1; j <= min(m, r-k); ++j) {
                    y = (mul(y, y, n) + c) % n;

```

```

        q = mul(q, abs(x - y), n);
    }
    g = __gcd(q, n); k += m;
} while (k < r && g < 2);
r <= 1;
} while (g < 2);

if (g == n)
do {
    ys = (mul(ys, ys, n) + c) % n;
    g = __gcd(abs(x - ys), n);
} while (g < 2);

if (g != n) return g;
}
return n;
}

```

7 Geometry

7.1 Rectangle in Rectangle

```

// Checks if rectangle of sides x,y fits inside one of sides X,Y
// Not tested with doubles but should work fine :)
// Code as written rejects rectangles that just touch.
bool rect_in_rect(int X, int Y, int x, int y) {
    if (Y > X) swap(Y, X);
    if (y > x) swap(y, x);
    double diagonal = sqrt(double(X)*X + double(Y)*Y);
    if (x < X && y < Y) return true;
    else if (y >= Y || x >= diagonal) return false;
    else {
        double w, theta, tMin = PI/4, tMax = PI/2;
        while (tMax - tMin > EPS) {
            theta = (tMax + tMin)/2.0;
            w = (Y-x*cos(theta))/sin(theta);
            if (w < 0 || x * sin(theta) + w * cos(theta) < X) tMin = theta;
            else tMax = theta;
        }
        return (w > y);
    }
}

```

7.2 Geometry Basic

```

#define EPS 1e-6

double DEG_to_RAD(double d) { return d * M_PI / 180.0; }
double RAD_to_DEG(double r) { return r * 180.0 / M_PI; }

inline int cmp(double a, double b) {
    return (a < b - EPS) ? -1 : ((a > b + EPS) ? 1 : 0);
}

struct Point {
    double x, y;
    Point(double x = 0.0, double y = 0.0) : x(x), y(y) {}

    Point operator + (Point a) { return Point(x+a.x, y+a.y); }
    Point operator - (Point a) { return Point(x-a.x, y-a.y); }
    Point operator * (double k) { return Point(x*k, y*k); }
    Point operator / (double k) { return Point(x/k, y/k); }

    double operator * (Point a) { return x*a.x + y*a.y; } // dot product
    double operator % (Point a) { return x*a.y - y*a.x; } // cross product

    int cmp(Point q) const { if (int t = ::cmp(x,q.x)) return t; return ::cmp(y,q.y); }

    #define Comp(x) bool operator x (Point q) const { return cmp(q) x 0; }
    Comp(>) Comp(<) Comp(==) Comp(>=) Comp(<=) Comp(!=)
    #undef Comp

    Point conj() { return Point(x, -y); }
    double norm() { return x*x + y*y; }

    // Note: There are 2 ways for implementing len():
    // 1. sqrt(norm()) --> fast, but inaccurate (produce some values that are of order X^2)
    // 2. hypot(x, y) --> slow, but much more accurate
    double len() { return sqrt(norm()); }
}

```

```

Point rotate(double alpha) {
    double cosa = cos(alpha), sina = sin(alpha);
    return Point(x * cosa - y * sina, x * sina + y * cosa);
}

int ccw(Point a, Point b, Point c) {
    return cmp((b-a)%(c-a), 0);
}

double angle(Point a, Point o, Point b) { // angle AOB
    a = a - o; b = b - o;
    return acos((a * b) / sqrt(a.norm() * b.norm()));
}

// Distance from p to Line ab (closest Point --> c)
double distToLine(Point p, Point a, Point b, Point &c) {
    Point ap = p - a, ab = b - a;
    double u = (ap * ab) / ab.norm();
    c = a + (ab * u);
    return (p-c).len();
}

// Distance from p to segment ab (closest Point --> c)
double distToLineSegment(Point p, Point a, Point b, Point &c) {
    Point ap = p - a, ab = b - a;
    double u = (ap * ab) / ab.norm();
    if (u < 0.0) {
        c = Point(a.x, a.y);
        return (p - a).len();
    }
    if (u > 1.0) {
        c = Point(b.x, b.y);
        return (p - b).len();
    }
    return distToLine(p, a, b, c);
}

struct Line {
    double a, b, c;
    Point A, B; // Added for polygon intersect line. Do not rely on assumption that these are valid

    Line(double a, double b, double c) : a(a), b(b), c(c) {}

    Line(Point A, Point B) : A(A), B(B) {
        a = B.y - A.y;
        b = A.x - B.x;
        c = -(a * A.x + b * A.y);
    }

    Line(Point P, double m) {
        a = -m; b = 1;
        c = -((a * P.x) + (b * P.y));
    }

    double f(Point A) {
        return a*A.x + b*A.y + c;
    }
};

bool areParallel(Line l1, Line l2) {
    return cmp(l1.a*l2.b, l1.b*l2.a) == 0;
}

bool areSame(Line l1, Line l2) {
    return areParallel(l1, l2) && cmp(l1.c*l2.a, l2.c*l1.a) == 0;
}

bool areIntersect(Line l1, Line l2, Point &p) {
    if (areParallel(l1, l2)) return false;
    double dx = l1.b*l2.c - l2.b*l1.c;
    double dy = l1.c*l2.a - l2.c*l1.a;
    double d = l1.a*l2.b - l2.a*l1.b;
    p = Point(dx/d, dy/d);
    return true;
}

void closestPoint(Line l, Point p, Point &ans) {
    if (fabs(l.b) < EPS) {
        ans.x = -(l.c) / l.a; ans.y = p.y;
        return;
    }
    if (fabs(l.a) < EPS) {
        ans.x = p.x; ans.y = -(l.c) / l.b;
        return;
    }
    Line perp(l.b, -l.a, -(l.b*p.x - l.a*p.y));
    areIntersect(l, perp, ans);
}

void reflectionPoint(Line l, Point p, Point &ans) {
    Point b;
    closestPoint(l, p, b);
    ans = p + (b - p) * 2;
}

```

7.3 Geometry Circle

```

}

struct Circle : Point {
    double r;
    Circle(double x = 0, double y = 0, double r = 0) : Point(x, y), r(r) {}
    Circle(Point p, double r) : Point(p), r(r) {}

    bool contains(Point p) { return (*this - p).len() <= r + EPS; }
};

// Find common tangents to 2 circles
// Helper method
void tangents(Point c, double r1, double r2, vector<Line> & ans) {
    double r = r2 - r1;
    double z = sqrt(c.x * c.x + c.y * c.y);
    double d = z - sqrt(r);
    if (d < -EPS) return;
    d = sqrt(fabs(d));
    Line l((c.x * r + c.y * d) / z,
          (c.y * r - c.x * d) / z,
          r1);
    ans.push_back(l);
}

// Actual method: returns vector containing all common tangents
vector<Line> tangents(Circle a, Circle b) {
    vector<Line> ans; ans.clear();
    for (int i=-1; i<=1; i+=2)
        for (int j=-1; j<=1; j+=2)
            tangents(b-a, a.r+1, b.r+j, ans);
    for (int i = 0; i < ans.size(); ++i)
        ans[i].c -= ans[i].a * a.x + ans[i].b * a.y;

    vector<Line> ret;
    for (int i = 0; i < (int) ans.size(); ++i) {
        bool ok = true;
        for (int j = 0; j < i; ++j)
            if (areSame(ret[j], ans[i])) {
                ok = false;
                break;
            }
        if (ok) ret.push_back(ans[i]);
    }
    return ret;
}

// Circle & line intersection
vector<Point> intersection(Line l, Circle cir) {
    double r = cir.r, a = l.a, b = l.b, c = l.c + l.a*cir.x + l.b*cir.y;
    vector<Point> res;

    double x0 = -a*c/(a*a+b*b), y0 = -b*c/(a*a+b*b);
    if (c*c > r*r*(a*a+b*b)+EPS) return res;
    else if (fabs(c*c - r*r*(a*a+b*b)) < EPS) {
        res.push_back(Point(x0, y0) + Point(cir.x, cir.y));
        return res;
    }
    else {
        double d = r*r - c*c/(a*a+b*b);
        double mult = sqrt(d / (a*a+b*b));
        double ax, ay, bx, by;
        ax = x0 + b * mult;
        bx = x0 - b * mult;
        ay = y0 + a * mult;
        by = y0 - a * mult;

        res.push_back(Point(ax, ay) + Point(cir.x, cir.y));
        res.push_back(Point(bx, by) + Point(cir.x, cir.y));
        return res;
    }
}

double commonCircleArea(Circle c1, Circle c2) { //return the common area of two circle
    double d = hypot(c1.x-c2.x, c1.y-c2.y), area;
    if (c1.r+c2.r <= d) area = 0;
    else if (c2.r+d <= c1.r) area = (c1.r * c1.r - c2.r * c2.r) * M_PI;
    else if (c1.r+d <= c2.r) area = (c2.r * c2.r - c1.r * c1.r) * M_PI;
    else {
        double p1 = c2.r * c2.r * acos((d*d + c2.r*c2.r - c1.r*c1.r) / (2*d*c2.r));
        double p2 = c1.r * c1.r * acos((d*d + c1.r*c1.r - c2.r*c2.r) / (2*d*c1.r));
        double p3 = 0.5 * sqrt((-d+c2.r+c1.r) * (d+c2.r-c1.r) * (d+c1.r-c2.r) * (d+c1.r+c2.r));
        area = p1 + p2 - p3;
    }
    return area;
}

```

```

// Given 2 circles: (0, 0, r) and (c2.x, c2.y, c2.r)
// Intersections are intersections with line Ax + By + C where
// A = -2 * c2.x
// B = -2 * c2.y
// C = c2.x^2 + c2.y^2 + r^2 - c2.r^2

```

7.4 Geometry Polygon

```

typedef vector< Point > Polygon;

// Convex Hull: returns minimum number of vertices. Should work when N <= 1 and when all points
// are collinear
struct comp_hull {
    Point pivot;
    bool operator() (Point q, Point w) {
        Point Q = q - pivot, W = w - pivot;
        double R = Q % W;
        if (cmp(R, 0)) return R < 0;
        return cmp(Q*Q, W*W) < 0;
    }
};

Polygon convex_hull(Polygon p) { // minimum vertices
    int j = 0, k, n = p.size();
    Polygon r(n);
    if (!n) return r;
    comp_hull comp;
    comp.pivot = *min_element(p.begin(), p.end());
    sort(p.begin(), p.end(), comp);
    for (int i = 0; i < n; ++i) {
        while (j > 1 && ccw(r[j-1], r[j-2], p[i]) <= 0) j--;
        r[j++] = p[i];
    }
    r.resize(j);
    if (r.size() >= 2 && r.back() == r.front()) r.pop_back();
    return r;
}

// Area, perimeter, centroid
double signed_area(Polygon p) {
    double area = 0;
    for (int i = 0; i < p.size(); ++i) {
        int j = (i+1) % p.size();
        area += p[i].x*p[j].y - p[j].x*p[i].y;
    }
    return area / 2.0;
}

double area(const Polygon &p) {
    return fabs(signed_area(p));
}

Point centroid(Polygon p) {
    Point c(0, 0);
    double scale = 6.0 * signed_area(p);
    for (int i = 0; i < p.size(); ++i) {
        int j = (i+1) % p.size();
        c = c + (p[i].x*p[j].y - p[j].x*p[i].y);
    }
    return c / scale;
}

double perimeter(Polygon P) {
    double res = 0;
    for (int i = 0; i < P.size(); ++i) {
        int j = (i+1) % P.size();
        res += (P[i] - P[j]).len();
    }
    return res;
}

// Is convex: checks if polygon is convex. Assume there are no 3 collinear points
bool is_convex(const Polygon &p) {
    int sz = (int) p.size();
    if (sz <= 2) return false;
    int isLeft = ccw(P[0], P[1], P[2]);
    for (int i = 1; i < sz; ++i)
        if (ccw(P[i], P[(i+1) % sz], P[(i+2) % sz]) * isLeft < 0)
            return false;
    return true;
}

// Inside polygon: O(N). Works with any polygon
// Does not work when point is on edge. Should check separately
bool in_polygon(const Polygon &p, Point pt) {
    if ((int)p.size() == 0) return false;
    double sum = 0;
    for (int i = 0; i < (int)p.size(); ++i) {
        Point Pj = P[(i+1) % p.size()];
        if (ccw(pt, P[i], Pj) > 0)
            sum += angle(P[i], pt, Pj);
        else sum -= angle(P[i], pt, Pj);
    }
}

```



```

    }
    return fabs(fabs(sum) - 2*M_PI) < EPS;
}

// Check point in convex polygon, O(logN)
// Source: http://codeforces.com/contest/166/submission/1392387
// On edge --> false
#define Det(a,b,c) ((double)(b.x-a.x)*(double)(c.y-a.y)-(double)(b.y-a.y)*(c.x-a.x))
bool in_convex(vector<Point>& l, Point p) {
    int a = 1, b = l.size()-1, c;
    if (Det(l[0], l[a], l[b]) > 0) swap(a,b);
    // Allow on edge --> if (Det... > 0 || Det... < 0)
    if (Det(l[0], l[a], p) >= 0 || Det(l[0], l[b], p) <= 0) return false;
    while (abs(a-b) > 1) {
        c = (a+b)/2;
        if (Det(l[0], l[c], p) > 0) b = c; else a = c;
    }
    // Allow on edge --> return Det... <= 0
    return Det(l[a], l[b], p) < 0;
}

// Cut a polygon with a line. Returns one half.
// To return the other half, reverse the direction of Line l (by negating l.a, l.b)
// The line must be formed using 2 points
Polygon polygon_cut(Polygon P, Line l) {
    Polygon Q;
    for (int i = 0; i < P.size(); ++i) {
        Point A = P[i], B = (i == P.size()-1) ? P[0] : P[i+1];
        if (ccw(l.A, l.B, A) != -1) Q.push_back(A);
        if (ccw(l.A, l.B, A)*ccw(l.A, l.B, B) < 0) {
            Point p; areIntersect(Line(A, B), l, p);
            Q.push_back(p);
        }
    }
    return Q;
}

// Find intersection of 2 polygons
// Helper method
bool intersect_lpt(Point a, Point b,
    Point c, Point d, Point &r) {
    double D = (b - a) % (d - c);
    if (cmp(D, 0) == 0) return false;
    double t = ((c - a) % (d - c)) / D;
    double s = -((a - c) % (b - a)) / D;
    r = a + (b - a) * t;
    return cmp(t, 0) > 0 && cmp(t, 1) < 0 && cmp(s, 0) > 0 && cmp(s, 1) < 0;
}

Polygon convex_intersect(Polygon P, Polygon Q) {
    const int n = P.size(), m = Q.size();
    int a = 0, b = 0, aa = 0, ba = 0;
    enum { Pin, Qin, Unknown } in = Unknown;
    Polygon R;
    do {
        int a1 = (a+n-1) % n, b1 = (b+m-1) % m;
        double C = (P[a] - P[a1]) % (Q[b] - Q[b1]);
        double A = (P[a] - Q[b]) % (P[a] - Q[b1]);
        double B = (Q[b1] - P[a]) % (Q[b] - P[a]);
        Point r;
        if (intersect_lpt(P[a], P[a1], Q[b1], Q[b], r)) {
            if (in == Unknown) aa = ba = 0;
            R.push_back(r);
            in = B > 0 ? Pin : A > 0 ? Qin : in;
        }
        if (C == 0 && B == 0 && A == 0) {
            if (in == Pin) { b = (b+1) % m; ++ba; }
            else { a = (a+1) % n; ++aa; }
        }
        else if (C > 0) {
            if (A > 0) { if (in == Pin) R.push_back(P[a]); a = (a+1) % n; ++aa; }
            else { if (in == Qin) R.push_back(Q[b]); b = (b+1) % m; ++ba; }
        }
        else {
            if (B > 0) { if (in == Qin) R.push_back(Q[b]); b = (b+1) % m; ++ba; }
            else { if (in == Pin) R.push_back(P[a]); a = (a+1) % n; ++aa; }
        }
    } while ( (aa < n || ba < m) && aa < 2*n && ba < 2*m );
    if (in == Unknown) {
        if (in_convex(Q, P[0])) return P;
        if (in_convex(P, Q[0])) return Q;
    }
    return R;
}

// Find the diameter of polygon.
// Rotating callipers
double convex_diameter(Polygon pt) {
    const int n = pt.size();
    int is = 0, js = 0;
    for (int i = 1; i < n; ++i) {
        if (pt[i].y > pt[is].y) is = i;
        if (pt[i].y < pt[js].y) js = i;
    }
}

```

```

double maxd = (pt[is]-pt[js]).norm();
int i, maxi, j, maxj;
i = maxi = is;
j = maxj = js;
do {
    int jj = j+1; if (jj == n) jj = 0;
    if ((pt[i] - pt[jj]).norm() > (pt[i] - pt[j]).norm()) j = (j+1) % n;
    else i = (i+1) % n;
    if ((pt[i]-pt[j]).norm() > maxd) {
        maxd = (pt[i]-pt[j]).norm();
        maxi = i; maxj = j;
    }
    while (i != is || j != js);
    return maxd; /* farthest pair is (maxi, maxj). */
}

// Closest pair
// Source: e-maxx.ru
#define upd_ans(x, y) {}
#define MAXN 100
double mindist = 1e20; // will be the result
void rec(int l, int r, Point a[]) {
    if (r - l <= 3) {
        for (int i=l; i<=r; ++i)
            for (int j=i+1; j<=r; ++j)
                upd_ans(a[i], a[j]);
        sort(a+l, a+r+1); // compare by y
        return;
    }
    int m = (l + r) >> 1;
    int midx = a[m].x;
    rec(l, m, a), rec(m+1, r, a);
    static Point t[MAXN];
    merge(a+l, a+m+1, a+m+1, a+r+1, t); // compare by y
    copy(t, t+r-l+1, a+l);

    int tsz = 0;
    for (int i=l; i<=r; ++i)
        if (fabs(a[i].x - midx) < mindist) {
            for (int j=tsz-1; j>=0 && a[i].y - t[j].y < mindist; --j)
                upd_ans(a[i], t[j]);
            t[tsz++] = a[i];
        }

    // Pick theorem
    // Given non-intersecting polygon.
    // S = area
    // I = number of integer points strictly Inside
    // B = number of points on sides of polygon
    // S = I + B/2 - 1
}

// Smallest enclosing circle:
// Given N points. Find the smallest circle enclosing these points.
// Amortized complexity: O(N)

struct SmallestEnclosingCircle {
    Circle getCircle(vector<Point> points) {
        assert(!points.empty());

        random_shuffle(points.begin(), points.end());
        Circle c(points[0], 0);
        int n = points.size();

        for (int i = 1; i < n; ++i)
            if ((points[i] - c).len() > c.r + EPS)
            {
                c = Circle(points[i], 0);
                for (int j = 0; j < i; ++j)
                    if ((points[j] - c).len() > c.r + EPS)
                    {
                        c = Circle((points[i] + points[j]) / 2, (points[i] - points[j]).len() / 2);
                        for (int k = 0; k < j; ++k)
                            if ((points[k] - c).len() > c.r + EPS)
                                c = getCircumcircle(points[i], points[j], points[k]);
                    }
            }

        return c;
    }

    Circle getCircumcircle(Point a, Point b, Point c) {
        double d = 2.0 * (a.x * (b.y - c.y) + b.x * (c.y - a.y) + c.x * (a.y - b.y));
        assert(fabs(d) > EPS);
    }
}

```

7.5 Smallest Enclosing Circle

```

double x = (a.norm() * (b.y - c.y) + b.norm() * (c.y - a.y) + c.norm() * (a.y - b.y)) / d;
double y = (a.norm() * (c.x - b.x) + b.norm() * (a.x - c.x) + c.norm() * (b.x - a.x)) / d;
Point p(x, y);
return Circle(p, (p - a).len());
}
};

```

7.6 Geometry Complex

```

// add : a + b
// scalar multi : r * a
// dot product : (conj(a) * b).x
// cross product : (conj(a) * b).y
// squared distance : norm(a - b)
// euclidean distance : abs(a - b)
// angle of elevation : arg(b - a)
// slope of line (a, b) : tan(arg(b - a))
// polar to cartesian : polar(r, theta)
// rotation about the origin : a * polar(1.0, theta)
// rotation about pivot p : (a - p) * polar(1.0, theta) + p
// angle ABC: abs(remainder(arg(a - b) - arg(c - b), 2.0 * M_PI)) distance: [-PI, PI]
// project p onto vector v : v * dot(p, v) / norm(v)
// project p onto line(a, b) : a + (b - a) * dot(p - a, b - a) / norm(b - a)
// reflect p across line (a, b) : a + conj((p - a) / (b - a)) * (b - a)
// relect p across line (a, b) : a + conj((p - a) / (b - a)) * (b - a)
// intersection of line(a, b) and (p, q) :
point intersection(point a, point b, point c) {
    double c1 = cross(p - a, b - a), c2 = cross(q - a, b - a);
    return (c1 * q - c2 * p) / (c1 - c2); //undefined if parallel
}
// read:
template<class T>
istream &operator>>(istream &is, complex<T> &p) {
    T value;
    is >> value;
    p.real(value);
    is >> value;
    p.imag(value);
    return is;
}

```

7.7 Latitude Longitude

```

/*
Converts from rectangular coordinates to latitude/longitude and vice versa. Uses degrees (not radians).
*/

#include <iostream>
#include <cmath>

using namespace std;

struct ll
{
    double r, lat, lon;
};

struct rect
{
    double x, y, z;
};

ll convert(rect& P)
{
    ll Q;
    Q.r = sqrt(P.x*P.x+P.y*P.y+P.z*P.z);
    Q.lat = 180/M_PI*asin(P.z/Q.r);
    Q.lon = 180/M_PI*acos(P.x/sqrt(P.x*P.x+P.y*P.y));

    return Q;
}

rect convert(ll& Q)
{
    rect P;
    P.x = Q.r*cos(Q.lon*M_PI/180)*cos(Q.lat*M_PI/180);
    P.y = Q.r*sin(Q.lon*M_PI/180)*cos(Q.lat*M_PI/180);
    P.z = Q.r*sin(Q.lat*M_PI/180);

    return P;
}

```

```

int main()
{
    rect A;
    ll B;

    A.x = -1.0; A.y = 2.0; A.z = -3.0;

    B = convert(A);
    cout << B.r << " " << B.lat << " " << B.lon << endl;

    A = convert(B);
    cout << A.x << " " << A.y << " " << A.z << endl;
}

```

7.8 Delaunay

```

#include <iostream>
#include <cstdio>
#include <algorithm>
#include <vector>
#include <complex>
#include <list>
#include <array>
#include <set>
using namespace std;

typedef long double ld;
typedef complex<ld> Pnt;
typedef array<int, 2> Edge;
typedef array<int, 3> Tri;
typedef pair<Pnt, ld> Circ;
const ld oo = 1e9;
const ld eps = 1e-6;
int n;

Circ compute_circumcircle(Pnt a, Pnt b, Pnt c) {
    b -= a;
    c -= a;
    auto center = (b*norm(c)-c*norm(b)) / (b*conj(c)-c*conj(b));
    return {center+a, norm(center)};
}

vector<Tri> delaunay(vector<Pnt> pnts) {
    pnts.push_back((-oo, -oo));
    pnts.push_back({oo, -oo});
    pnts.push_back({oo, oo});
    pnts.push_back((-oo, oo));
    list<pair<Tri, Circ>> tcs;
    tcs.push_back({{n, n+1, n+2}, {0, 2*oo*oo}});
    tcs.push_back({{n+2, n+3, n}, {0, 2*oo*oo}});
    for (int i = 0; i < n; i++) {
        set<Edge> edges;
        for (auto it = begin(tcs); it != end(tcs); ) {
            auto tri = it->second;
            ld d = norm(pnts[i] - tri.first) - tri.second;
            if (d < -eps) {
                auto tri = it->first;
                auto j = *prev(end(tri));
                for (int k: tri) {
                    auto ite = edges.find({k, j});
                    if (ite == end(edges)) {
                        edges.insert({j, k});
                    } else {
                        edges.erase(ite);
                    }
                    j = k;
                }
                it = tcs.erase(it);
            } else {
                it++;
            }
        }
        int j0 = (*begin(edges))[0];
        for (int j = j0; ; ) {
            int k = (*edges.lower_bound({j, 0}))[1];
            Circ circ = compute_circumcircle(pnts[i], pnts[j], pnts[k]);
            tcs.push_back({{i, j, k}, circ});
            j = k;
            if (j == j0) break;
        }
    }
    vector<Tri> tris;
    for (auto& tc: tcs) {
        auto& tri = tc.first;
        bool flag = false;
        for (int j: tri) {
            flag = flag || j >= n;
        }
    }
}

```

```

    }
    if (flag) continue;
    tris.push_back(tri);
}
return tris;
}

```

7.9 Convex hull

```

// Compute the 2D convex hull of a set of points using the monotone chain
// algorithm. Eliminate redundant points from the hull if REMOVE_REDUNDANT is
// #defined.
//
// Running time: O(n log n)
//
// INPUT:  a vector of input points, unordered.
// OUTPUT: a vector of points in the convex hull, counterclockwise, starting
//         with bottommost/leftmost point

#include <cstdio>
#include <cassert>
#include <vector>
#include <algorithm>
#include <cmath>
// BEGIN CUT
#include <map>
// END CUT

using namespace std;

#define REMOVE_REDUNDANT

typedef double T;
const T EPS = 1e-7;
struct PT {
    T x, y;
    PT() {}
    PT(T x, T y) : x(x), y(y) {}
    bool operator<(const PT &rhs) const { return make_pair(y,x) < make_pair(rhs.y,rhs.x); }
    bool operator==(const PT &rhs) const { return make_pair(y,x) == make_pair(rhs.y,rhs.x); }
};

T cross(PT p, PT q) { return p.x*q.y-p.y*q.x; }
T area2(PT a, PT b, PT c) { return cross(a,b) + cross(b,c) + cross(c,a); }

#ifdef REMOVE_REDUNDANT
bool between(const PT &a, const PT &b, const PT &c) {
    return (fabs(area2(a,b,c)) < EPS && (a.x-b.x)*(c.x-b.x) <= 0 && (a.y-b.y)*(c.y-b.y) <= 0);
}
#endif

void ConvexHull(vector<PT> &pts) {
    sort(pts.begin(), pts.end());
    pts.erase(unique(pts.begin(), pts.end()), pts.end());
    vector<PT> up, dn;
    for (int i = 0; i < pts.size(); i++) {
        while (up.size() > 1 && area2(up[up.size()-2], up.back(), pts[i]) >= 0) up.pop_back();
        while (dn.size() > 1 && area2(dn[dn.size()-2], dn.back(), pts[i]) <= 0) dn.pop_back();
        up.push_back(pts[i]);
        dn.push_back(pts[i]);
    }
    pts = dn;
    for (int i = (int) up.size() - 2; i >= 1; i--) pts.push_back(up[i]);

#ifdef REMOVE_REDUNDANT
    if (pts.size() <= 2) return;
    dn.clear();
    dn.push_back(pts[0]);
    dn.push_back(pts[1]);
    for (int i = 2; i < pts.size(); i++) {
        if (between(dn[dn.size()-2], dn[dn.size()-1], pts[i])) dn.pop_back();
        dn.push_back(pts[i]);
    }
    if (dn.size() >= 3 && between(dn.back(), dn[0], dn[1])) {
        dn[0] = dn.back();
        dn.pop_back();
    }
    pts = dn;
#endif
}

// BEGIN CUT
// The following code solves SPOJ problem #26: Build the Fence (BSHEEP)

int main() {
    int t;
    scanf("%d", &t);
    for (int caseno = 0; caseno < t; caseno++) {

```

```

int n;
scanf("%d", &n);
vector<PT> v(n);
for (int i = 0; i < n; i++) scanf("%lf%lf", &v[i].x, &v[i].y);
vector<PT> h(v);
map<PT,int> index;
for (int i = n-1; i >= 0; i--) index[v[i]] = i+1;
ConvexHull(h);

double len = 0;
for (int i = 0; i < h.size(); i++) {
    double dx = h[i].x - h[(i+1)%h.size()].x;
    double dy = h[i].y - h[(i+1)%h.size()].y;
    len += sqrt(dx*dx+dy*dy);
}

if (caseno > 0) printf("\n");
printf("%.2f\n", len);
for (int i = 0; i < h.size(); i++) {
    if (i > 0) printf(" ");
    printf("%d", index[h[i]]);
}
printf("\n");
}

// END CUT

```

8 Miscellaneous

8.1 Calendar Java

```

/*
Constructors:
GregorianCalendar()
GregorianCalendar(int year, int month, int dayOfMonth)
GregorianCalendar(int year, int month, int dayOfMonth, int hour, int minute)
Methods:
add(int field, int amount)
get(int field)
set(int field, int value)
Fields:
GregorianCalendar.YEAR
GregorianCalendar.MONTH
GregorianCalendar.WEEK_OF_YEAR
GregorianCalendar.DAY_OF_MONTH
GregorianCalendar.DAY_OF_WEEK
GregorianCalendar.DATE
*/

```

8.2 Dynamic Convex Hull DP (Max)

```

const ll is_query = -(1LL<<62);
struct Line {
    ll m, b;
    mutable function<const Line*> succ;
    bool operator<(const Line& rhs) const {
        if (rhs.b != is_query) return m < rhs.m;
        const Line* s = succ();
        if (!s) return 0;
        ll x = rhs.m;
        return b - s->b < (s->m - m) * x;
    }
};

struct HullDynamic : public multiset<Line> { // will maintain upper hull for maximum
    bool bad(iterator y) {
        auto z = next(y);
        if (y == begin()) {
            if (z == end()) return 0;
            return y->m == z->m && y->b <= z->b;
        }
        auto x = prev(y);
        if (z == end()) return y->m == x->m && y->b <= x->b;
        return (x->b - y->b)*(z->m - y->m) >= (y->b - z->b)*(y->m - x->m);
    }

    void insert_line(ll m, ll b) {
        auto y = insert({ m, b });
        y->succ = [=] { return next(y) == end() ? 0 : &*next(y); };
        if (bad(y)) { erase(y); return; }
        while (next(y) != end() && bad(next(y))) erase(next(y));
    }
};

```

```

    while (y != begin() && bad(prev(y))) erase(prev(y));
}
ll eval(ll x) {
    auto l = *lower_bound((Line) { x, is_query });
    return l.m * x + l.b;
}
};

```

8.3 Floyd Cycle Finding

```

pii floyd(int x0) {
    int tortoise = f(x0), hare = f(f(x0));
    while (tortoise != hare) {
        tortoise = f(tortoise);
        hare = f(f(hare));
    }
    int mu = 0; hare = 0;
    while (tortoise != hare) {
        tortoise = f(tortoise);
        hare = f(hare);
        mu++;
    }
    int lambda = 1;
    hare = f(tortoise);
    while (tortoise != hare) {
        hare = f(hare);
        lambda++;
    }
    return mp(mu, lambda);
}

```

8.4 Josephus

```

/*
case k = 2 -> if n = 2^m + k and 0 <= k < 2^m, then f(n) =
2k+1
general case (0-based) -> f(n, k) = (f(n-1, k) + k) mod n,
f(1, k) = 0
*/

```

8.5 Knight Shortest Path

```

// knight shortest path
int f(int x1, int y1, int x2, int y2)
{
    int dx=abs(x2-x1);
    int dy=abs(y2-y1);
    int lb=(dx+1)/2;
    lb>=(dy+1)/2;
    lb>=(dx+dy+2)/3;
    while ((lb%2) != (dx+dy)%2) lb++;
    if (abs(dx)==1 && dy==0) return 3;
    if (abs(dy)==1 && dx==0) return 3;
    if (abs(dx)==2 && abs(dy)==2) return 4;
    return lb;
}

```

8.6 DP Knuth

```

// http://codeforces.com/blog/entry/8219
// Original Recurrence:
// dp[i][j] = min(dp[i][k] + dp[k][j]) + C[i][j] for k = i+1..j-1
// Necessary & Sufficient Conditions:
// A[i][j-1] <= A[i][j] <= A[i+1][j]
// with A[i][j] = smallest k that gives optimal answer
// Also applicable if the following conditions are met:
// 1. C[a][c] + C[b][d] <= C[a][d] + C[b][c] (quadrangle inequality)
// 2. C[b][c] <= C[a][d] (monotonicity)
// for all a <= b <= c <= d
// To use:
// Calculate dp[i][i] and A[i][i]
//
// FOR(len = 1..n-1)
//   FOR(i = 1..n-len) {

```

```

//   j = i + len
//   FOR(k = A[i][j-1]..A[i+1][j])
//       update(dp[i][j])
//   }

// OPTCUT
#include "../template.h"

const int MN = 2011;
int a[MN], dp[MN][MN], C[MN][MN], A[MN][MN];
int n;

int main() {
    while (cin >> n) {
        FOR(i,1,n) {
            cin >> a[i];
            a[i] += a[i-1];
        }
        FOR(i,1,n) FOR(j,i,n) C[i][j] = a[j] - a[i-1];

        FOR(i,1,n) dp[i][i] = 0, A[i][i] = i;

        FOR(len,1,n-1)
            FOR(i,1,n-len) {
                FOR(j,i,n-len) {
                    int j = i + len;
                    dp[i][j] = 2000111000;
                    FOR(k,A[i][j-1],A[i+1][j]) {
                        int cur = dp[i][k-1] + dp[k][j] + C[i][j];
                        if (cur < dp[i][j]) {
                            dp[i][j] = cur;
                            A[i][j] = k;
                        }
                    }
                }
            }

        cout << dp[1][n] << endl;
    }
}

```

8.7 C++ Template

```

#ifdef __DEBUG
#define debug if (true)
#define _GLIBCXX_DEBUG
#else
#define debug if (false)
#endif

#include <bits/stdc++.h>
using namespace std;

#define mp make_pair
#define pb push_back
#define fi first
#define se second
#define ALL(a) begin(a), end(a)
#define SZ(a) ((int)(a).size())

typedef long long ll;
typedef pair<int, int> pii;
typedef vector<int> vi;

int main() {
    ios::sync_with_stdio(false);
    cin.tie(nullptr);

    return 0;
}

```

8.8 Java Template

```

import java.util.*;
import java.io.*;

class Main {
    FastScanner in;
    PrintWriter out;

    public void solve() throws IOException {
    }

    public void run() {
        try {

```

```

in = new FastScanner(System.in);
out = new PrintWriter(System.out);

solve();

out.close();
} catch (IOException e) {
    e.printStackTrace();
}
}

class FastScanner {
    BufferedReader br;
    StringTokenizer st;

    FastScanner(InputStream is) {
        br = new BufferedReader(new InputStreamReader(is));
    }

    FastScanner(File f) {
        try {
            br = new BufferedReader(new FileReader(f));
        } catch (FileNotFoundException e) {
            e.printStackTrace();
        }
    }

    String next() {
        while (st == null || !st.hasMoreTokens()) {
            try {
                st = new StringTokenizer(br.readLine());
            } catch (IOException e) {
                e.printStackTrace();
            }
        }
        return st.nextToken();
    }

    int nextInt() {
        return Integer.parseInt(next());
    }
}

public static void main(String[] arg) {
    new Main().run();
}
}

```

8.9 pika

```

#!/usr/bin/env bash
set -e
if [ "$2" == "-d" ]; then
    g++ -o "$1" "$1.cpp" -std=c++14 -D_GLIBCXX_DEBUG -D__DEBUG -g
else
    g++ -o "$1" "$1.cpp" -std=c++14 -O2 -Wall
fi
echo "COMPILE OK"
time "./$1" < "$1.in"

```

9 SHK

9.1 SHK C++

```

#include <bits/stdc++.h>

using namespace std;
const double PI = acos(-1);
#define INF 1E9
#define endl '\n'
#define pb push_back
// A lot of typedefs
typedef long long ll;

```

```

// struct
struct mystruct {
    int counter;
};

//custom hashing
struct custom_hash {
    inline std::size_t operator()(const std::pair<int,int> & v) const {
        return v.first*31+v.second*7;
    }
};

// pq/set custom comparator, will get reversed (at least in pq)
class mycomp {
public:
    bool operator() (mystruct a, mystruct b) {
        return a.counter > b.counter;
    }
};

// sort custom comparator
bool customcompare(mystruct a, mystruct b) {
    return a.counter > b.counter;
}

int main ()
{
    ios::sync_with_stdio(false);
    cin.tie(nullptr);
    return 0;
}

```

9.2 SHK Python

```

import sys

class SamInput(object):
    def __init__(self):
        self.inp = []
        for i in sys.stdin:
            i = i.replace("\n", "")
            j = list(i.split())
            self.inp.append(j)

    def readln(self):
        if (len(self.inp) == 0) :
            return False
        else:
            return str.join(" ", self.inp.pop(0))

    def read(self):
        if (len(self.inp) == 0):
            return False
        while (len(self.inp[0]) == 0):
            self.inp.pop(0)
            if (len(self.inp) == 0):
                return False
        return self.inp[0].pop(0)

```

9.3 SHK Shortcuts

Comment highlighted code
 Ctrl + Shift + C
 Uncomment highlighted code
 Ctrl + Shift + X

Indent block.
 Tab
 Dedent block.
 Shift + Tab

Line cut.
 Ctrl + L
 Line copy.
 Ctrl + Shift + T

```

g++ x.cpp -std=c++11 -o x
x.exe < test.txt

```