

Cloud Computing with AWS

By Adam Cordner, Chris Perry & Evie Snuffle

A report submitted as part of a required module
for the degree of BSc. (Hons.) in Computer Science
at the School of Computing and Digital Technology,
Birmingham City University, United Kingdom

May 2022,
CMP6210 Cloud Computing 2021–2022
Module Coordinator: Dr Khaled Mahbub

Student IDs: 18109958, 18103708, 18128599

Contents

1 Glossary	vi
2 Introduction	1
3 Web App	2
3.1 Software Stack	2
3.2 Database Design	2
3.3 Interface Design	5
4 Virtual Private Cloud and Subnets	8
5 Elastic Cloud Compute	9
5.1 AWS Setup	9
5.2 EC2 Login	13
5.3 Package Setup	14
5.4 Web App Setup	15
5.5 systemd Services	17
6 Simple Storage Service (S3)	18
7 CloudFront	19
8 CloudWatch	27
9 CloudTrail	28
10 Relational Database Service	29
11 Availability Zones	30
12 Elastic Load Balancing	31
13 Security Practices	32
14 Cost Breakdown	33
14.1 Estimated Costs	33
14.2 Scaling Up to 10,000 Users	33
14.3 Scaling Up to One Million Users	33
14.4 Scaling Up to Ten Million Users	33

15 Testing	34
15.1 Testing EC2	34
15.2 Testing S3	34
15.3 Testing CloudFront	34
15.4 Testing RDS	34
15.5 Testing CloudWatch	36
15.6 Testing CloudTrail	36
15.7 Testing ELB	36
16 Future Enhancements	37
17 Conclusion	38
A Screenshots	39
Bibliography	39

List of Figures

3.1 Database tables overview.	2
3.2 migrations table.	3
3.3 users table.	3
3.4 stories table.	4
3.5 <i>Digital-Ink</i> home page log in and sign up forms.	5
3.6 <i>Digital-Ink</i> story creation form.	6
3.7 <i>Digital-Ink</i> account page.	7
3.8 <i>Digital-Ink</i> stories page and story view.	7
5.1 Selection of EC2 OS Image.	9
5.2 Selection of EC2 Instance.	10
5.3 Selection of EC2 Keypair.	10
5.4 Selection of EC2 Networking options.	11
5.5 Generated EC2 Keypair in the .pem format.	11
5.6 Selection of EC2 Storage Configuration.	12
5.7 SSH command to log into EC2 instance.	13
5.8 Logging into EC2 instance.	13
5.9 Installing Git.	14
5.10 Installing Docker.	14
5.11 Cloning the web app from Github.	15
5.12 Containers required for the web app being pulled from Docker Hub.	15
5.13 Creation of tables through php artisan migrate command.	16
5.14 Digital Ink shown when accessed through the IPv4 address.	16
5.15 Creation of systemd Service	17
7.1 Applying CloudFront bucket policy.	20
7.2 Applying CloudFront origins to S3 bucket.	20
7.3 Applying CloudFront Distribution Permissions.	21
7.4 Applying CloudFront Cache Keys and Origin Requests.	21
7.5 Function Association.	22
7.6 Applying CloudFront Settings.	23
7.7 Applying CloudFront Settings.	23
7.8 Created CloudFront Distribution.	24
7.9 Image location before CloudFront.	24
7.10 Image location after CloudFront.	25
7.11 Image location after CloudFront.	26

A.1	After Allocating Elastic IP Address	39
A.2	Allocating Elastic IP Address	39
A.3	Cloning the App	40
A.4	CloudWatch Conditions	40
A.5	CloudWatch Specify Metric	41
A.6	Create Instance - Application and OS Images	41
A.7	Create Instance - Configure Storage	42
A.8	Create Instance - Instance Type	42
A.9	Create Instance - Name & Tags	43
A.10	Create Instance - Network Settings	43
A.11	Creating Key Pair	44
A.12	Digital Ink	44
A.13	Docker Compose	45
A.14	Edit Instance - Network Settings	45
A.15	Installing Docker using Package Manager	46
A.16	Installing Docker using Package Manager (In Progress)	46
A.17	Installing Git	47
A.18	Starting Docker systemd Service	47
A.19	Instances	48
A.20	Launching Instance	48
A.21	Log In with Key Pair	49
A.22	Selecting a VPC Configuration	49
A.23	Successfully Initiated Instance	50
A.24	VPC Successfully Created	50
A.25	VPC with Public and Private Subnets, Loading	51
A.26	VPC with Public and Private Subnets	51
A.27	Your VPCs	52

Chapter 1

Glossary

- **ACL** — Access Control List
- **ACM** — AWS Certificate Manager
- **AMI** — Amazon Machine Images
- **App** — Application
- **AWS** — Amazon Web Services
- **AZ** — Availability Zone
- **CA** — Certificate Authority
- **CDS** — Content Delivery Network
- **CPU** — Central Processing Unit
- **DB** — Database
- **DIG** — Domain Information Groper
- **EC2** — Elastic Cloud Compute
- **ELB** — Elastic Load Balancing
- **.env** — Environment File Extension
- **GB** — Gigabyte
- **HTTP** — HyperText Transfer Protocol
- **HTTPS** — HyperText Transfer Protocol Secure
- **IAM** — Identity and Access Management
- **IEEE** — Institute of Electrical and Electronics Engineers
- **IP** — Internet Protocol
- **IPv4** — Internet Protocol Version 4
- **LAMP** — Linux, Apache, MySQL, PHP

- **ML** — Machine Learning
- **nslookup** — Name Server Lookup
- **OS** — Operating System
- **.pem** — Privacy Enhanced Mail File Extension
- **PHP** — PHP: Hypertext Preprocessor
- **RAM** — Random Access Memory
- **S3** — Simple Storage Service
- **RAM** — Random Access Memory
- **RDBMS** — Relational Database Management System
- **RDS** — Relational Database Service
- **SaaS** — Software as a Service
- **SNS** — Simple Notification Service
- **SQL** — Structured Query Language
- **SSH** — Secure Shell
- **VPC** — Virtual Private Cloud
- **VPN** — Virtual Private Network
- **WAF** — Web Application Firewall

Chapter 2

Introduction

This report details the process of designing, developing, and deploying a cloud application onto Amazon Web Services (AWS). The application is called *Digital Ink* and allows users to create, edit, and delete their own short stories. Users can then view their own short stories and other users' short stories. It was first developed locally using a LAMP stack. This consisted of Linux - hosted through Docker - for the operating system, an Apache HTTP Server, MySQL for the relational database management, and PHP as the programming language.

After the application was built locally, it was gradually integrated onto AWS. This involved implementing several AWS cloud features to enhance the application, ensure application security, and increase availability. This was accomplished by using Simple Storage Service (S3), Elastic Compute Cloud (EC2), ELB (Elastic Load Balancing), and more. The process of implementing these cloud features will be discussed throughout the report.

After the application was integrated onto AWS, an evaluation of the process was conducted. This includes a discussion of the security practices used, estimated costs for different user scales, and thorough testing. Lastly, several enhancements which could be made to the application in the future will be discussed.

Chapter 3

Web App

This chapter of the report will detail the local design and development of the *Digital Ink* web application. We will first discuss the software stack used to develop the app, then the design of the database used, and, lastly, the design of the user interface.

3.1 Software Stack

Digital Ink was first developed locally using a LAMP stack. LAMP refers to a generic software stack, where each letter in the acronym stands for one the following open source building blocks: Linux, Apache HTTP Server, MySQL, and PHP ([lee2003open](#)). The web app is hosted within a Docker container ([anderson2015docker](#)) which runs a minified version of the Linux operating system. Apache is an open-source web server software which is used to host the app on the web ([fielding1997apache](#)). MySQL is an open-source relational database management system ([widenius2002mysql](#)) which is used to store all the data used within the app, including user details and story details. PHP is a programming language aimed towards web development, chosen due to its stability and reliability ([lerdorf2002programming](#)). Additionally, all developers involved have prior experience with PHP.

3.2 Database Design

As mentioned before, the web app uses the MySQL relational database management system to store its data. MySQL is a relational database management system (RDBMS) which stores data in the form of tables, where Structured Query Language (SQL) is used to access the database. As shown in Figure 3.1, the database which this web app uses consists of three tables: `users`, `stories`, and `migrations`.




Figure 3.1: Database tables overview.

The `migrations` table (see Figure 3.2) contains records which correspond to the migrations within the Laravel web app. These migrations contain the scripts required to automatically generate the `users` and `stories` tables in SQL. It contains the following three columns:


- `id`: the unique ID for each migration.
- `migration`: points to the scripts used to create tables.
- `batch`: how many times the script has been ran.

<code>id</code>	<code>migration</code>	<code>batch</code>
1	<code>2014_10_12_000000_create_users_table</code>	1
4	<code>2020_03_13_105916_create_stories_table</code>	1

Figure 3.2: `migrations` table.

The `users` table (see Figure 3.3) contains all the information about user accounts, and it contains the following seven columns:

- `id`: the unique ID for each user account.
- `name`: the name associated with user account.
- `email`: the unique email used to log in.
- `password`: the password used to log in, encrypted with 184 bit hashing by **Bcrypt (laravel2022hashing)**.
- `remember_token`: keeps the user logged in if they select "Remember me".
- `created_at`: records what date and time the user account was first created at.
- `updated_at`: records what date and time the user account was last updated at.



The screenshot shows the MySQL Workbench interface with a database named 'TL5v1.2' and a schema named 'digital-ink'. The 'users' table is selected. The table has the following structure:

stories					users		
<code>id</code>	<code>name</code>	<code>email</code>	<code>password</code>	<code>remember_token</code>	<code>created_at</code>	<code>updated_at</code>	
1	Adam	adam.cordner@mail.bcu.ac.uk	\$2y\$10\$ISS.3eqO3o0dRXaK8sMy.eBqUapgD...	mDUIGRilVhyEi6...	2022-05-10 15:50:27	2022-05-10 15:50:27	
2	evie	^~@snugg.ie	\$2y\$10\$vVRMmN/IRSIYTrCUjJEPu44jkVI0r5...	Mu1WdyOz1e8...	2022-05-10 15:51:29	2022-05-10 15:51:29	

Figure 3.3: `users` table.

The `stories` table (see Figure 3.4) contains all the information about user-created stories, and it contains the following 11 columns:

- `id`: the unique ID for each story.
- `author_id`: the unique ID associated with the user who created the story.
- `title`: the title associated with the story.
- `genre`: the genre associated with the story, which can be one of eight different genres.
- `blurb`: a brief description of the story.
- `content`: the full content of the story.
- `cover_image`: a thumbnail image for the story.
- `file_upload`: an optional PDF upload of the story.
- `published`: 1 if the story has been made public, or 0 if it is a draft.
- `created_at`: records what date and time the story was first created at.
- `updated_at`: records what date and time the story was last updated at.

<code>id</code>	<code>author_id</code>	<code>title</code>	<code>genre</code>	<code>blurb</code>	<code>content</code>
		<code>cover_image</code>	<code>file_upload</code>	<code>published</code>	<code>created_at</code>
2	1 → Group 4 Loves AWS	Romance	Meet Group 4 and their love for AWS!	Group 4 loves using AWS' cloud features to host Di...	
3	2 → cheese savoury	Action and Adventure	nice and simple	on malted granary	
		./storage/cover_images/7537329101652200606.j...	NULL	1	2022-05-10 16:36:46 ⏺ 2022-05-10 16:36:46 ⏺
		images/digital-ink-logo.png	NULL	1	2022-05-10 16:38:51 ⏺ 2022-05-10 16:38:51 ⏺

Figure 3.4: `stories` table.

3.3 Interface Design

The design of the web app was created using Blade, a powerful templating engine ([laravel2022blade](#)). When the user initially accesses the web app, they are able to log in or sign up. This can be seen in Figure 3.5. When a user has created an account, a record is written to the `users` table in the database.



The figure shows the Digital Ink home page with two forms: a login form at the top and a sign-up form below it.

Login Form:

- Email: Enter Email
- Password: Enter Password
- Remember me:
- Login button (purple rounded rectangle)
- Text: Don't have an account already? Why not sign up?

Sign Up Form:

- Name: Enter Name
- Email: Enter Email
- Password: Enter Password
- Repeat Password: Repeat Password
- Sign Up button (purple rounded rectangle)

Figure 3.5: *Digital-Ink* home page log in and sign up forms.

Once a user is signed in, they can create a story. Creating a story requires the user to enter a title, a genre, the story itself, a blurb, and, optionally, a thumbnail image. This can be seen in Figure 3.6. Once a story has been created, it is written to the `stories` table.

Create your story!



The figure shows a three-panel interface for creating a story. The top panel is titled 'Create your story!' and contains fields for 'Author Reference Number' (with value '1'), 'Title' (with placeholder 'Every story needs a good title!' and value 'Group 4 Loves AWS'), and 'Genre' (with placeholder 'What type of story are you creating?' and value 'Romance'). The middle panel is titled 'Your Story:' and contains a text area with placeholder text 'Group 4 loves using AWS' cloud features to host Digital Ink.' and a file selection button 'Browse...' showing 'No file selected.'. The bottom panel is titled 'Blurb:' and contains a text area with placeholder text 'Meet Group 4 and their love for AWS!' and a file selection button 'Browse...' showing 'index.jpg'. It also includes a section titled 'Nearly finished! *' with a question 'Do you want to save your story as a draft or publish it onto our site?' and two options: 'Save as a Draft' (unchecked) and 'Upload' (checked). A 'Complete' button is located at the bottom right of the bottom panel.

Author Reference Number: *

1

Title: *

Every story needs a good title!

Group 4 Loves AWS

Genre: *

What type of story are you creating?

Romance

Your Story: *

Add the content of your story below.

Group 4 loves using AWS' cloud features to host Digital Ink.

Browse... No file selected.

Blurb: *

Add a short description of your story!

Meet Group 4 and their love for AWS!

Browse... index.jpg

Nearly finished! *

Do you want to save your story as a draft or publish it onto our site?

Save as a Draft

Upload

Complete

Figure 3.6: *Digital-Ink* story creation form.

After this, the user can see all of their uploaded stories on their account page. This can be seen in Figure 3.7. From here, a story can be edited or deleted, which either updates a record in the `stories` table or removes a record from it.

The screenshot shows a user interface for managing published stories. At the top, a green header bar displays the message "Yay! Your story has been published!". Below this, a title "Hi Adam!" is shown. The main content area is titled "Here are your published stories:" and contains a table with three columns: "TITLE", "GENRE", and "ACTIONS". The table has one row of data: "Group 4 Loves AWS" under "TITLE", "Romance" under "GENRE", and two buttons under "ACTIONS": "Edit" (highlighted with a green oval) and "Delete" (highlighted with a red oval).

TITLE	GENRE	ACTIONS
Group 4 Loves AWS	Romance	Edit Delete

Figure 3.7: *Digital-Ink* account page.

Lastly, on the Stories page, a user can view and search through all uploaded stories across all users. Each story's title, genre, and blurb is shown in a list view. A user can click into one of these stories to see the thumbnail image and read the full story. These pages can be seen in Figure 3.8.

The screenshot shows the "Stories" page and a detailed view of a story. The top navigation bar includes a search bar with placeholder text "Enter a title to search" and a "Search" button. The main content area displays a table with four columns: "AUTHOR ID", "TITLE", "GENRE", and "BLURB". Two stories are listed: "Group 4 Loves AWS" by author ID 1 (Romance, blurb: "Meet Group 4 and their love for AWS!") and "cheese savoury" by author ID 2 (Action and Adventure, blurb: "nice and simple"). Below the table, a specific story is viewed for "Group 4 Loves AWS". It shows a thumbnail image of a person, the title "Group 4 Loves AWS", the author "Written by: 1", the genre "Genre: Romance", and a blurb: "Group 4 loves using AWS' cloud features to host Digital Ink.". A "Back" button is located at the bottom left of the story view.

AUTHOR ID	TITLE	GENRE	BLURB
1	Group 4 Loves AWS	Romance	Meet Group 4 and their love for AWS!
2	cheese savoury	Action and Adventure	nice and simple

Figure 3.8: *Digital-Ink* stories page and story view.

Chapter 4

Virtual Private Cloud and Subnets

Amazon Virtual Private Cloud (VPC) allows for AWS resources to be launched in a virtual network that has been custom defined and configured. This virtual network is similar to a traditional network which operates within your own physical data center, with the added benefits of the scalable AWS infrastructure (**amazon2022what**). A VPC can have multiple assigned subnets, which are a range of IP addresses accessible in the VPC.

Chapter 5

Elastic Cloud Compute

5.1 AWS Setup

After the VPC and subnets were configured, the initial deployment of the web app began with setting up EC2. This AWS service allows for scalable computing capacity through the use of a virtual computing environment hosted in the cloud (**aws2022ec2**). The web app will be stored on an EC2 instance of Amazon Linux, known as Amazon Machine Image (AMI), which will then be launched through a docker container stored on the app.




Figure 5.1: Selection of EC2 OS Image.

Figure 5.1 details the selection of the Operating System (OS) that will be used for the EC2 instance. The *Amazon Linux 2 AMI* was selected, as it is already configured with Linux and does not need any more setup.

Now that an AMI has been chosen, the specific instance type that will be used within this AMI can be selected. It was decided that the instance type of *t2.micro* would be used, as it contains only 1GB of Random Access Memory (RAM), as seen in Figure 5.2.




Figure 5.2: Selection of EC2 Instance.

A key pair will allow for the ability to sign in to the EC2 instance with a unique set of login credentials, heightening the security of the project.

The next stage of the setup process was to set up networking for the EC2 instance, in order for the web app to work with Docker to download relevant containers from Docker-Hub, which will allow a Laravel instance to be initialised, as discussed in Section 3. This process can be seen in Figure 5.3.




Figure 5.3: Selection of EC2 Keypair.

The instance is assigned the VPC created in Section 4, where it is assigned a subnet in the same availability zone of us-east-1.

This setup can be seen in Figure 5.4. An EC2 keypair is then generated in the .pem




Figure 5.4: Selection of EC2 Networking options.

```
chris@Christophers-MacBook-Pro:~/Desktop/Keypair
└─ ssh -i Group4_KeyPair.pem ec2-user@52.45.13.111
```

Figure 5.5: Generated EC2 Keypair in the .pem format.

format.

This is enough to comfortably run the web app without any issues. Storage for the AMI was subsequently chosen. It was decided that 8GB of storage would be used, as this is enough to run the web app and still provide leftover storage for any system-critical tasks.




Figure 5.6: Selection of EC2 Storage Configuration.

The selection of these options can be found in Figure 5.6. In addition to this, the chosen options are eligible for "Free Tier", which means that it will use a limited amount of the \$100 budget allocated for the project.


5.2 EC2 Login

The EC2 instance `group4-ec2` is now live, and the webapp can be loaded onto it. The instance is first logged in to through the use of the `ssh` command, followed by the `-i` argument to specify an identify file, which was generated earlier, and then the public ipv4 address of the instance.

```
ssh -i ~/Desktop/Group4_KeyPair.pem ec2-user@52.45.13.111
```

Figure 5.7: SSH command to log into EC2 instance.

This command can seen being executed in Figure 5.7.



A screenshot of a terminal window titled "ec2-user@ip-172-31-27-208:~". The window shows the command `ssh -i Group4_KeyPair.pem ec2-user@52.45.13.111` being run, followed by the output: "Last login: Thu May 12 13:09:24 2022 from 193.60.143.13". Below this, the Amazon Linux 2 AMI logo is displayed, consisting of a stylized tree or root system icon. The final line of output is `https://aws.amazon.com/amazon-linux-2/ [ec2-user@ip-172-31-27-208 ~]$`.

Figure 5.8: Logging into EC2 instance.

The logged in EC2 instance can be seen in Figure 5.8.

5.3 Package Setup

The web app is stored on GitHub, and the AMI does not come with GitHub by default. Git is subsequently installed via `yum install git`.

```
git-core x86_64 0:2.32.0-1.amzn2.0.1
git-core-doc noarch
perl-Error noarch
perl-Git noarch
perl-TermReadKey x86_64 0:2.32.0-1.amzn2.0.1
2.32.0-1.amzn2.0.1
2.32.0-1.amzn2.0.1
1:0.17020-2.amzn2
2.32.0-1.amzn2.0.1
2.30-20.amzn2.0.2
amzn2-core
amzn2-core
amzn2-core
amzn2-core
amzn2-core
amzn2-core

Transaction Summary
====

Install 1 Package (+0 Dependent packages)

Total download size: 7.8 M
Installed size: 38 M
Is this ok [y/N]: y
Downloading packages:
(1/7): emacs-fsfilesystem-27.2-4.amzn2.0.1.noarch.rpm | 67 kB 00:00:00
(2/7): git-2.32.0-1.amzn2.0.1.x86_64.rpm | 2.7 MB 00:00:00
(3/7): git-core-doc-2.32.0-1.amzn2.0.1.noarch.rpm | 32 kB 00:00:00
(4/7): perl-Error-0.17020-2.amzn2.noarch.rpm | 43 kB 00:00:00
(5/7): perl-Git-2.32.0-1.amzn2.0.1.noarch.rpm | 4.8 MB 00:00:00
(6/7): git-core-2.32.0-1.amzn2.0.1.x86_64.rpm | 31 kB 00:00:00
(7/7): perl-TermReadKey-2.30-20.amzn2.0.2.x86_64.rpm | 29 MB/S | 7.8 MB 00:00:00

Total
Running transaction check
Running transaction test
Transaction test succeeded
Running transaction
  Installing : git-core-2.32.0-1.amzn2.0.1.x86_64
  Installing : git-core-doc-2.32.0-1.amzn2.0.1.noarch
  Installing : perl-Error-0.17020-2.amzn2.noarch
  Installing : 1:emacs-fsfilesystem-27.2-4.amzn2.0.1.noarch
  Installing : perl-TermReadKey-2.30-20.amzn2.0.2.x86_64
  Installing : perl-Git-2.32.0-1.amzn2.0.1.noarch
  Installing : git-2.32.0-1.amzn2.0.1.x86_64
  Verifying : perl-TermReadKey-2.30-20.amzn2.0.2.x86_64
  Verifying : git-core-doc-2.32.0-1.amzn2.0.1.noarch
  Verifying : perl-Git-2.32.0-1.amzn2.0.1.noarch
  Verifying : 1:emacs-fsfilesystem-27.2-4.amzn2.0.1.noarch
  Verifying : git-2.32.0-1.amzn2.0.1.x86_64
  Verifying : git-core-2.32.0-1.amzn2.0.1.x86_64
  Verifying : 1:perl-Error-0.17020-2.amzn2.noarch

Installed:
  git.x86_64 0:2.32.0-1.amzn2.0.1

Dependency Installed:
  emacs-fsfilesystem.noarch 1:27.2-4.amzn2.0.1  git-core.x86_64 0:2.32.0-1.amzn2.0.1  git-core-doc.noarch 0:2.32.0-1.amzn2.0.1  perl-Error.noarch 1:0.17020-2.amzn2  perl-Git.noarch 0:2.32.0-1.amzn2.0.1
  perl-TermReadKey.x86_64 0:2.30-20.amzn2.0.2

Completed!
[ec2-user@ip-172-31-27-208 ~]$ 
```

Figure 5.9: Installing Git.

The web app also requires docker, and `yum install docker` is executed to install Docker as a result.

```
[ec2-user@ip-172-31-27-208 ~]$ sudo yum update
Loaded plugins: extras_suggestions, langpacks, priorities, update-motd
amzn2-core
No packages marked for update
[ec2-user@ip-172-31-27-208 ~]$ sudo yum install docker docker-compose
Loaded plugins: extras_suggestions, langpacks, priorities, update-motd
No package docker-compose available.
Resolving Dependencies
--> Running transaction check
--> Package docker.x86_64 0:20.10.13-2.amzn2 will be installed
--> Processing Dependency: runc >= 1.0.0 for package: docker-20.10.13-2.amzn2.x86_64
--> Processing Dependency: libcgroup >= 0.40.rcl1-5.15 for package: docker-20.10.13-2.amzn2.x86_64
--> Processing Dependency: containerd >= 1.3.2 for package: docker-20.10.13-2.amzn2.x86_64
--> Processing Dependency: libselinux >= 3.0 for package: docker-20.10.13-2.amzn2.x86_64
--> Running transaction check
-->>> Package containerd.x86_64 0:1.4.13-2.amzn2.0.1 will be installed
-->>> Package libcgroup.x86_64 0:0.9.41-21.amzn2 will be installed
-->>> Package pigz.x86_64 0:2.3.4-1.amzn2.0.1 will be installed
-->>> Package runc.x86_64 0:1.0.3-2.amzn2 will be installed
-->>> Finished Dependency Resolution

Dependencies Resolved

---- Package Arch Version Repository Size
Installing:
  docker      x86_64  20.10.13-2.amzn2   amzn2extra-docker  40 M
Installing for dependencies:
  containerd  x86_64  1.4.13-2.amzn2.0.1  amzn2extra-docker  23 M
  libcgroup   x86_64  0.41-21.amzn2       amzn2-core          66 k
  pigz        x86_64  2.3.4-1.amzn2.0.1    amzn2-core          81 k
  runc        x86_64  1.0.3-2.amzn2       amzn2extra-docker  3.0 M

Transaction Summary
=====
Install 1 Package (+4 Dependent packages)

Total download size: 67 M
Installed size: 280 M
Is this ok [y/d/N]:
```

Figure 5.10: Installing Docker.

5.4 Web App Setup

The web app is firstly cloned from its repository via the `git clone` command, and a new `digital-ink` folder is made to store the contents.

```
[ec2-user@ip-172-31-27-208 ~]$ git clone https://github.com/ChrisP99/digital-ink
.git
-bash: git: command not found
[ec2-user@ip-172-31-27-208 ~]$ git clone https://github.com/ChrisP99/digital-ink
.git
Cloning into 'digital-ink'...
remote: Enumerating objects: 959, done.
remote: Counting objects: 100% (959/959), done.
remote: Compressing objects: 100% (324/324), done.
remote: Total 959 (delta 593), reused 959 (delta 593), pack-reused 0
Receiving objects: 100% (959/959), 3.32 MiB | 19.01 MiB/s, done.
Resolving deltas: 100% (593/593), done.
[ec2-user@ip-172-31-27-208 ~]$
```

Figure 5.11: Cloning the web app from Github.

The `cd` command is used to move into the `digital-ink` folder, and the web app is subsequently launched through the `docker-compose up -d` to launch the web app as a detached Docker container. Relevant containers that are required to be downloaded from the `dockerfile` are then pulled.




Figure 5.12: Containers required for the web app being pulled from Docker Hub.

The result of this command launches 3 containers:

1. `digital-ink`: An instance of the web app which uses a custom Laravel container.
2. `mysql`: An instance of a local database made in MySQL.
3. `phpmyadmin`: A way to locally manage the database through a UI.

At the minute, the web app is live through the `digital-ink` container, and is using a local version of MySQL as a database, stored within the `mysqlDocker` container. The database has no tables, but can be populated through the use of Laravel. The container is firstly accessed through docker `exec` app bash, and the database is populated with tables with `php artisan migrate`. This then generates tables to store users and their stories.

```
[ec2-user@ip-172-31-27-208 digital-ink]$ sudo /usr/local/bin/docker-compose exec app bash
root@d0e13abddf12:/srv/app# php artisan migrate
Migration table created successfully.
Migrating: 2014_10_12_000000_create_users_table
Migrated: 2014_10_12_000000_create_users_table (0.08 seconds)
Migrating: 2014_10_12_100000_create_password_resets_table
Migrated: 2014_10_12_100000_create_password_resets_table (0.07 seconds)
Migrating: 2019_08_19_000000_create_failed_jobs_table
Migrated: 2019_08_19_000000_create_failed_jobs_table (0.04 seconds)
Migrating: 2020_03_13_105916_create_stories_table
Migrated: 2020_03_13_105916_create_stories_table (0.16 seconds)
root@d0e13abddf12:/srv/app#
```

Figure 5.13: Creation of tables through `php artisan migrate` command.

The subsequent output of this command can be found in Figure 5.13. When the website is accessed at the public IPv4 address at , Digital Ink will now be shown.




Figure 5.14: Digital Ink shown when accessed through the IPv4 address.

```

ec2-user@ip-172-31-27-208:~-
> ssh -l ~/Downloads/Group4_KeyPair.pem ec2-user@52.45.13.111
Last login: Thu May 12 13:07:11 2022 from 193.68.143.13
[ec2-user@ip-172-31-27-208 ~] $ uptime
13:09:27 up 0 min, 1 user, load average: 4.75, 1.19, 0.40
[ec2-user@ip-172-31-27-208 ~] $ systemctl cat digital-ink
# /etc/systemd/system/digital-ink.service
[Unit]
Description=Starts digital ink EC2
After=network.target

[Service]
Type=simple
ExecStartPre=/usr/bin/sudo systemctl start docker
ExecStart=/usr/local/bin/docker-compose -f docker-compose.yml up
WorkingDirectory=/home/ec2-user/digital-ink

[Install]
WantedBy=multi-user.target
[ec2-user@ip-172-31-27-208 ~] $ systemctl status digital-ink
● ● digital-ink.service - Starts digital ink EC2
   Loaded: loaded (/etc/systemd/system/digital-ink.service; enabled; vendor preset: disabled)
     Active: active (running) since Thu 2022-05-12 13:09:19 UTC; 17s ago
       Process: 2906 ExecStartPre=/usr/bin/sudo systemctl start docker (code=exited, status=0/SUCCESS)
      Main PID: 3552 (docker-compose)
         Tasks: 6
        Memory: 30.8M
       CGroup: /system.slice/digital-ink.service
               └─3552 /usr/local/bin/docker-compose -f docker-compose.yml up

May 12 13:09:21 ip-172-31-27-208.ec2.internal docker-compose[3552]: digital-ink-db-1 | 2022-05-12T13:09:21.894808Z 0 [ERROR] InnoDB: Could not find a valid tablespace file for 'mysql/time.... the issue.
May 12 13:09:21 ip-172-31-27-208.ec2.internal docker-compose[3552]: digital-ink-db-1 | 2022-05-12T13:09:21.894824Z 0 [Warning] InnoDB: Cannot calculate statistics for table 'mysql'.time_z.... the issue.
May 12 13:09:21 ip-172-31-27-208.ec2.internal docker-compose[3552]: digital-ink-db-1 | 2022-05-12T13:09:21.894830Z 0 [Warning] InnoDB: Error: log file mysql-bin.000001 is open and lock 'F' is held by some other process.
May 12 13:09:22 ip-172-31-27-208.ec2.internal docker-compose[3552]: digital-ink-db-1 | 2022-05-12T13:09:22.037710Z 0 [Note] Event Scheduler: Starting 0 events
May 12 13:09:22 ip-172-31-27-208.ec2.internal docker-compose[3552]: digital-ink-db-1 | Version: '5.7.38' socket: '/var/run/mysql/mysqld.sock' port: 3306 MySQL Community Server (GPL)
May 12 13:09:22 ip-172-31-27-208.ec2.internal docker-compose[3552]: digital-ink-app-1 | AN00558: apache2: Could not reliably determine the server's fully qualified domain name, using 172.21...his message
May 12 13:09:22 ip-172-31-27-208.ec2.internal docker-compose[3552]: digital-ink-app-1 | AN00558: apache2: Could not reliably determine the server's fully qualified domain name, using 172.21...his message
May 12 13:09:22 ip-172-31-27-208.ec2.internal docker-compose[3552]: digital-ink-app-1 | [Thu May 12 13:09:22.671766 2022] [mpm_prefork:notice] [pid 1] AH00163: Apache/2.4.25 (Debian) PHP/7.... operations
May 12 13:09:22 ip-172-31-27-208.ec2.internal docker-compose[3552]: digital-ink-app-1 | [Thu May 12 13:09:22.672038 2022] [core:notice] [pid 1] AH00094: Command line: 'apache2 -D FOREGROUND'
Hint: Some lines were ellipsized, use -l to show in full.
[ec2-user@ip-172-31-27-208 ~] $
```

The terminal window shows the creation of a systemd service named 'digital-ink' in the directory '/etc/systemd/system'. The service starts the 'docker' daemon and runs a Docker Compose command to start the 'digital-ink' application. The configuration includes a 'Description' of starting digital ink EC2, a 'Type' of 'simple', and an 'ExecStart' command of '/usr/local/bin/docker-compose -f docker-compose.yml up'. The 'Install' section specifies it should start at the 'network.target'. The 'Status' command shows the service is active and running. Log output indicates MySQL errors related to tablespace files and Apache errors about FQDN resolution.

Figure 5.15: Creation of systemd Service

5.5 systemd Services

systemd is a service manager, which is a program that launches and monitors different services across the system. The digital-ink application is automatically started upon boot by the systemd process, which ensures that the application is started correctly and without errors. If any errors occur, systemd will log them in a tool known as journalctl and then follow a configuration file for instructions on how to handle those errors. This can range from simply restarting a program that has errored, to trying once again, or recording the failure and performing no action.

Chapter 6

Simple Storage Service (S3)

AWS S3 is a form of cloud-based object storage. This is a style of network filesystem that treats each file as a separate object with a unique ID, which allows each object to be served individually over a network with a single URL, which can also be enhanced with a content delivery network.

Each S3 instance is separated into logical containers known as buckets. Each S3 bucket can have its own credentials, its own endpoint and other permissions and configuration. Object storage is particularly useful when creating an application that scales as you are billed per unit of storage that you use, and in theory are able to use infinite storage as your application demands. The only limitation with object storage is how much you are able to pay for. Each object is automatically replicated across many different nodes, providing data redundancy against multiple different availability zones.

S3 is perhaps the most popular AWS service and used by many different SaaS applications across the internet, for instance Instagram, Facebook, Discord and Twitter are all known for using S3 or S3-style storage. The advent of object storage has created an almost de-facto standard, which has led to the creation of many 'S3-compatible' or 'S3-like' competitor solutions, such as those run by Google Cloud and Microsoft Azure.

Chapter 7

CloudFront

CloudFront will allow for the distribution of static and dynamic web images more efficiently. An international network of data centres, referred to as edge locations, are used to deliver content for CloudFront. An edge location which offers the lowest latency or delay in serving these files will be used. This will involve the creation of a CloudFront Distribution.

Firstly, an origin is chosen which is the S3 bucket created in Section 6. It is then given a name of `group4-digital-ink.s3.us-east-1.amazonaws.com`. The "Yes use OAI" option is selected, in order to restrict bucket access to only CloudFront. The "Bucket Policy" option is set to "Yes" to automatically update permissions on the bucket to allow read access for the OAI. These options can be seen configured in Figures 7.1 and 7.2.




Figure 7.1: Applying CloudFront bucket policy.




Figure 7.2: Applying CloudFront origins to S3 bucket.

Permissions are then applied to the CloudFront distribution itself. Objects are set to be compressed automatically to save space, and for viewing images, permissions are set to be in both HTTP and HTTPS, and to only allow GET and HEAD, so images can only be viewed.




Figure 7.3: Applying CloudFront Distribution Permissions.

A cache policy and origin request policy is subsequently applied to the aforementioned permissions. The "CachingOptimized" policy is applied for compression. Origin Request policy is set to "CORS-S3Origin" in order for CORS to be automatically set up for the S3 bucket. Any GET requests are then compatible in the response headers through "SimpleCORS".




Figure 7.4: Applying CloudFront Cache Keys and Origin Requests.

No function associations are set due to the lack of CloudFront functions and Lambdas.

The screenshot shows the 'Function associations - optional' section of the CloudFront Distribution configuration. It includes four dropdown menus for 'Function type': 'Viewer request' (No association), 'Viewer response' (No association), 'Origin request' (No association), and 'Origin response' (No association). Below this is a 'Settings' section with 'Price class' (Info) and 'AWS WAF web ACL - optional'. The 'Price class' dropdown is set to 'Use all edge locations (best performance)'. The 'AWS WAF web ACL' dropdown is set to 'Choose web ACL'. At the bottom, there are links for 'Feedback', 'Looking for language selection? Find it in the new Unified Settings', and 'Cookie preferences'.

Figure 7.5: Function Association.

The settings for the CloudFront Distribution can now be set. In order to ensure high availability, the option "Use all edge locations" is selected, so that images can be distributed to the user from the closest edge location in relation to their IP address. No ACL can be added to the WAF due to permissions issues, and a SSL Certificate cannot be set as the web app is not being served from the internet. For logging purposes "Standard Logging" is set to "On", and logs are saved to the same S3 bucket. Cookie logging is enabled, and IPv6 is set to "On", to allow for more IP addresses to access the CloudFront Distributed content. These settings can be found in Figures ?? and 7.7.




Figure 7.6: Applying CloudFront Settings.





Figure 7.7: Applying CloudFront Settings.


A CloudFront Distribution has now been created, and can be found in Figure 7.8.



The screenshot shows the AWS CloudFront console under the 'Distributions' section. A single distribution is listed with the ID E21BWNC9VESEB5 and the domain name d1bdkf7iuqj4qy.cloudfront.net. The interface includes standard AWS navigation elements like search, enable/disable buttons, and a 'Create distribution' button.

Figure 7.8: Created CloudFront Distribution.

Finally, the images contained within the webserver were changed from their local location to their relevant CloudFront locations. This change can be seen in Figures 7.9 and 7.10.



The screenshot shows a code editor displaying the file 'base.blade.php'. The code is a Blade template with the following line highlighted:

```

```

This line is being modified from a local asset path to a CloudFront URL. The code editor interface includes a sidebar for 'Project', 'Structure', and 'Favorites', and a bottom bar for 'Terminal' and 'Event Log'.

Figure 7.9: Image location before CloudFront.

The screenshot shows a code editor interface with a dark theme. The top navigation bar includes tabs for 'Project', 'resources', 'views', and 'base.blade.php'. The main area displays a PHP file named 'base.blade.php' with line numbers from 36 to 56. The code is a template for a header section, including a container, a row with three columns, and links for 'Stories', 'Create', and 'About'. A specific line, number 51, contains an image tag with a CloudFront URL as its source:

```
51: 
```

The bottom status bar shows various icons and text, including 'Dockerfile detection: You may setup Docker deployment run configuration for the following file(s): blog/vendor/guzzlehttp/guzzle/Dockerfile // .docker/Dockerfile... (4 minutes ago)'. The bottom right corner shows the date and time as 'at 21:59:59'.

Figure 7.10: Image location after CloudFront.




Figure 7.11: Image location after CloudFront.

As seen in Figure 7.11, the Digital Ink logo is now hosted on CloudFront.

Chapter 8

CloudWatch

Amazon CloudWatch is a monitoring and observation tool which can provide developers with insights to monitor applications, react to performance changes, and optimise resource consumption. CloudWatch collects monitoring and operational data about the application as logs and metrics to provide a complete overview of operation health, resource consumption, and the services currently running on AWS. This is useful for any cloud-based application as it allows developers to set alarms, visualise metric logs, troubleshoot errors and, most importantly, identify and correct anomalous behaviour ([amazon2022amazon](#)). An example of CloudWatch usage would be an alarm set to alert developers when a specified resource consumption level is over a certain threshold.

Chapter 9

CloudTrail

Chapter 10

Relational Database Service

Amazon RDS service allows a user to create a fully-featured and highly-available SQL database that is automatically replicated to another availability zone. (TODO: Oops, no multi-az) This means that if the primary database becomes unavailable, there is automatic failover providing redundancy for all the data stored within.

To create an Amazon RDS instance, a suitable name/identifier for the database is required before created as well as a selection for the resource limits for the virtual server. The database requires a username and passphrase, although for additional security there is the option to automatically generate a passphrase.

Afterwards, the type of SQL database required (such as MySQL, PostgreSQL, MariaDB or others) will be selected and then the database should begin provisioning.

Chapter 11

Availability Zones

Chapter 12

Elastic Load Balancing

Elastic Load Balancing is used to automatically scale your EC2 instances to meet any changes in demand from your users. ELB can be used to both scale up or down the instance's resources to ensure that your application is kept performant and available regardless of how many users visit. It is also possible to scale down the resources again, after the spike in usage has passed, to save money when it comes to billing and ensure you aren't paying for any additional resources that are not being used.

Chapter 13

Security Practices

Chapter 14

Cost Breakdown

If this web app was to be deployed to the public, or be expanded to a larger market, it would be important to gather estimated costs for hosting the app in the cloud with all the AWS services being used. The AWS Pricing Calculator can be used to calculate current costs and predict future costs. To calculate these costs, it is required to specify every implemented feature and several projected inputs and outputs, such as amount of data transferred on the app per month ([amazon2022aws](#)). The monthly cost and a yearly cost of deploying the app in its current state was calculated first. Following this, the calculator was used to predict monthly and yearly costs for scaling the deployment up to larger user-bases. These figures were calculated for scaling the app up to 10,000 users, one million users, and ten million users, which would require upgrading some selected AWS features.

14.1 Estimated Costs

14.2 Scaling Up to 10,000 Users

14.3 Scaling Up to One Million Users

14.4 Scaling Up to Ten Million Users

Chapter 15

Testing

This chapter of the report will detail the testing conducted on the configured AWS services. This was done to determine the accuracy and efficiency of the configurations made during the deployment process. The testing was conducted by using Gherkin, a language used to define behaviour and test cases (**dos2018automated**). It is non-technical and is intended to be easily human-readable. Gherkin uses set keywords for structure and meaning: Given, When, and Then. An example of this structure can be seen in Figure ??.

```
Scenario: ...
  Given ...
  When ...
  Then ...
```

EC2, S3, CloudFront, RDS, CloudWatch, and CloudTrail were all tested using this approach. Screenshots are included to illustrate the results of these tests.

15.1 Testing EC2

```
Scenario: Accessing instance through SSH with .pem file private key.
  Given ...
  When ...
  Then ...

Scenario: Accessing web app through EC2 domain name.
  Given ...
  When ...
  Then ...
```

15.2 Testing S3

```
Scenario: Accessing web app image through S3 domain name.
  Given ...
  When ...
  Then ...
```

15.3 Testing CloudFront

15.4 Testing RDS

```
Scenario: Accessing web app image through CloudFront domain name.
  Given ...
  When ...
  Then ...

Scenario: Accessing web app image through CloudFront domain name in another region.
  Given ...
  When ...
  Then ...

Scenario: Accessing web app image through CloudFront domain name in another IP address.
  Given ... (NSLookup test)
  When ...
  Then ...

Scenario: Creating user information through the web app.
  Given ...
  When ...
  Then ...

Scenario: Creating story information through the web app.
  Given ...
  When ...
  Then ...

Scenario: Reading user information from the database into the web app.
  Given ...
  When ...
  Then ...

Scenario: Reading story information from the database into the web app.
  Given ...
  When ...
  Then ...

Scenario: Updating user information in the database through the web app.
  Given ...
  When ...
  Then ...

Scenario: Updating story information in the database through the web app.
  Given ...
  When ...
  Then ...

Scenario: Deleting user information in the database through the web app.
  Given ...
  When ...
  Then ...

Scenario: Deleting story information in the database through the web app.
  Given ...
  When ...
  Then ...
```

15.5 Testing CloudWatch

(One test for each of the metrics we set up.)

Scenario:

```
Given ...
When ...
Then ...
```

15.6 Testing CloudTrail

(One test for each of the metrics we set up.)

Scenario:

```
Given ...
When ...
Then ...
```

15.7 Testing ELB

(Test for turning off instance 1. Test for turning off instance 2.)

Chapter 16

Future Enhancements

An SSL/TLS certificate could be added, as it was not possible to do this from within the lab tutorial due to a lack of permissions from the root AWS account. By adding a certificate we would be able to encrypt the connections to our EC2 instance and increase the security of our application for all users.

We would like to add more roles and users to our IAM, but were limited by the amount that we were able to access.


If we were to do the project again, we would use AWS Elastic Beanstalk as it allows automatic orchestration of all the resources needed for a LAMP stack style application such as ours, it also has support for Docker which is a containerization technology that we had used in our application project.

Chapter 17

Conclusion


Appendix A: Screenshots

I am an appendix, please be kind.




The screenshot shows the AWS VPC Elastic IP addresses page. A green success message at the top states "Elastic IP address allocated successfully. Elastic IP address 52.3.74.136". Below this, the "Elastic IP addresses (1/1)" section displays a table with one row. The table columns are Name, Allocated IPv4 add..., Type, Allocation ID, and Reverse DNS record. The single entry is "52.3.74.136" with Type "Public IP" and Allocation ID "eipalloc-017ccecd4b183730c". At the bottom, there is a "Summary" tab and a "Tags" tab, with the "Summary" tab currently selected. The IP address 52.3.74.136 is also highlighted in the table.

Figure A.1: After Allocating Elastic IP Address



The screenshot shows the "Allocate Elastic IP address" settings page. The "Elastic IP address settings" section includes a "Network Border Group" dropdown set to "us-east-1". Under "Public IPv4 address pool", the "Amazon's pool of IPv4 addresses" option is selected. There is also a note about public IPv4 addresses being disabled because no pools were found. The "Global static IP addresses" section contains a note about AWS Global Accelerator and a "Create accelerator" button.

Figure A.2: Allocating Elastic IP Address



```
ec2-user@ip-172-31-27-208:~$ git clone https://github.com/ChrisP99/digital-ink.git
-bash: git: command not found
[ec2-user@ip-172-31-27-208 ~]$ git clone https://github.com/ChrisP99/digital-ink.git
Cloning into 'digital-ink'...
remote: Enumerating objects: 959, done.
remote: Counting objects: 100% (959/959), done.
remote: Compressing objects: 100% (324/324), done.
remote: Total 959 (delta 593), reused 959 (delta 593), pack-reused 0
Receiving objects: 100% (959/959), 3.32 MiB | 19.01 MiB/s, done.
Resolving deltas: 100% (593/593), done.
[ec2-user@ip-172-31-27-208 ~]$
```

Figure A.3: Cloning the App




Figure A.4: CloudWatch Conditions




Figure A.5: CloudWatch Specify Metric




Figure A.6: Create Instance - Application and OS Images




Figure A.7: Create Instance - Configure Storage




Figure A.8: Create Instance - Instance Type




Figure A.9: Create Instance - Name & Tags




Figure A.10: Create Instance - Network Settings




Figure A.11: Creating Key Pair




Figure A.12: Digital Ink

```
ec2-user@ip-172-31-27-208:~/digital-ink

: phpmyadmin Pulling
: 5eb5b503b376 Extracting      27.53MB/31.37MB          5.9s
: 8b1a0d84cf101 Download complete                         5.7s
: 38c937addeb7 Download complete                         5.7s
: 6a2f1dc96e59 Download complete                         5.7s
: f8c3f82c39d4 Download complete                         5.7s
: 90fc6462b088 Download complete                         5.7s
[+] Running 0/319 Download complete                      5.7s
: phpmyadmin Pulling
: 5eb5b503b376 Extracting      27.53MB/31.37MB          6.0s
: 8b1a0d84cf101 Download complete                         5.8s
: 38c937addeb7 Download complete                         5.8s
: 6a2f1dc96e59 Download complete                         5.8s
: f8c3f82c39d4 Download complete                         5.8s
: 90fc6462b088 Download complete                         5.8s
[+] Running 7/319 Download complete                      5.8s
: phpmyadmin Pulling
: 5eb5b503b376 Pull complete                           7.9s
: 8b1a0d84cf101 Pull complete                           7.9s
: 38c937addeb7 Extracting      [=====] 32.31MB/91.6MB          12.8s
: 6a2f1dc96e59 Download complete                         12.8s
: f8c3f82c39d4 Download complete                         12.8s
: 90fc6462b088 Download complete                         12.8s
: c670d99116c9 Download complete                         12.8s
: 268554d6fe96 Download complete                         12.8s
: 6c29fa0d4492 Download complete                         12.8s
: 73c23c0a259 Download complete                         12.8s
: 81ac13c96fc2 Download complete                         12.8s
: b60a3e6c23949 Download complete                         12.8s
: dac5dd67fd59 Download complete                         12.8s
: fd46866d9c36 Download complete                         12.8s
: 443a80ef4c80 Download complete                         12.8s
: 5e0049224f95 Download complete                         12.8s
: 213e66cdf7f56 Download complete                         12.8s
: 9b9b44731108 Download complete                         12.8s
[+] db Pulling
: 15bb3e15f562 Pull complete                           13.0s
: 96c2ab037a1b Pull complete                           8.5s
: 8aa3ac85066b Pull complete                           9.8s
: ac7e524fc98 Pull complete                           9.4s
: f6a88631064f Pull complete                           9.8s
: 15bb3e3cf1f50 Extracting      [=====] 13.11MB/14.06MB          10.1s
: ae65dc337dc8 Download complete                         12.7s
: ad4c4c43ad5f52 Download complete                         12.7s
: c6cab33e8ff1 Download complete                         12.7s
: 2e1cf2c43f16 Download complete                         12.7s
: 2e5ee322aaf48 Download complete                         12.7s
```

Figure A.13: Docker Compose

The screenshot shows the AWS Launch Wizard interface for creating a new Amazon Linux 2 instance. The 'Network settings' section includes a subnet (vpc-006b19b59ed484041) and security group rules for SSH, HTTP, and HTTPS traffic. The 'Summary' section shows one instance, the AMI (Amazon Linux 2 Kernel 5.10 AMI), and the instance type (t2.micro). The 'Configure storage' section shows a root volume of 8 GiB. At the bottom, there are 'Cancel' and 'Launch instance' buttons.

aws Services Search for services, features, blogs, docs, and more [Option+Shift]

☰ N. Virginia v vclabs/user1803655=Christopher.Perry2@mail.bcu.ac.uk @ 4241...

▼ Network settings

Network
vpc-006b19b59ed484041

Subnet
No preference (Default subnet in any availability zone)

Auto-assign public IP
Enable

Security groups (Firewall) [Info](#)
We'll create a new security group called 'launch-wizard-1' with the following rules:

Allow SSH traffic from Anywhere
Helps you connect to your instance 0.0.0.0/0

Allow HTTPs traffic from the internet
To set up an endpoint, for example when creating a web server

Allow HTTP traffic from the internet
To set up an endpoint, for example when creating a web server

▼ Summary

Number of instances [Info](#)
1

Software Image (AMI)
Amazon Linux 2 Kernel 5.10 AMI...read more
ami-0022f774911c1d690

Virtual server type (instance type)
t2.micro

Firewall (security group)
New security group

Storage (volumes)
1 volume(s) - 8 GiB

[Cancel](#) [Launch instance](#)

▼ Configure storage [Info](#) Advanced

1x 8 GiB gp2 Root volume

Feedback Looking for language selection? Find it in the new [Unified Settings](#)

© 2022, Amazon Web Services, Inc. or its affiliates. Privacy Terms Cookie preferences

Figure A.14: Edit Instance - Network Settings

```
[ec2-user@ip-172-31-27-208 ~]$ sudo yum update
Loaded plugins: extras_suggestions, langpacks, priorities, update-motd
amzn2-core
No packages marked for update
[ec2-user@ip-172-31-27-208 ~]$ sudo yum install docker docker-compose
Loaded plugins: extras_suggestions, langpacks, priorities, update-motd
No package docker-compose available.
Resolving Dependencies
--> Running transaction check
--> Package docker x86_64 0:20.10.13-2.amzn2 will be installed
--> Processing Dependency: runc >= 1.0.0 for package: docker-20.10.13-2.amzn2.x86_64
--> Processing Dependency: libcgroup >= 0.40.rcl5.15 for package: docker-20.10.13-2.amzn2.x86_64
--> Processing Dependency: containerd >= 1.3.2 for package: docker-20.10.13-2.amzn2.x86_64
--> Processing Dependency: pigz for package: docker-20.10.13-2.amzn2.x86_64
--> Running transaction check
--> Package containerd.x86_64 0:1.4.13-2.amzn2.0.1 will be installed
--> Package libcgroup.x86_64 0:0.41-21.amzn2 will be installed
--> Package pigz.x86_64 0:2.3.4-1.amzn2.0.1 will be installed
--> Package runc.x86_64 0:1.0.3-2.amzn2 will be installed
--> Finished Dependency Resolution

Dependencies Resolved

=====
| Package      | Arch | Version       | Repository | Size |
|=====|=====|=====|=====|=====|
| Installing: |       |             |            |        |
| docker       | x86_64 | 20.10.13-2.amzn2 | amzn2extra-docker | 40 M |
| Installing for dependencies: |       |             |            |        |
| containerd  | x86_64 | 1.4.13-2.amzn2.0.1 | amzn2extra-docker | 23 M |
| libcgroup   | x86_64 | 0.41-21.amzn2    | amzn2-core       | 66 k  |
| pigz        | x86_64 | 2.3.4-1.amzn2.0.1 | amzn2-core       | 81 k  |
| runc        | x86_64 | 1.0.3-2.amzn2    | amzn2extra-docker | 3.0 M |
|=====|=====|=====|=====|=====|
Transaction Summary
=====
| Install 1 Package (<4 Dependent packages) |
Total download size: 67 M
Installed size: 280 M
Is this ok [D/y/N]: [ ] | 54% | 5.2 GB | 0 18% | ① 5-04, 1:31 PM | snuffle | ↻ | □ ~ | % ssh + fish + bash + zsh + fish + fish + fish + fish + fish + fish + spacedust |
```

Figure A.15: Installing Docker using Package Manager

```
Resolving Dependencies
--> Running transaction check
--> Package docker.x86_64 0:20.10.13-2.amzn2 will be installed
--> Processing Dependency: runc >= 1.0.0 for package: docker-20.10.13-2.amzn2.x86_64
--> Processing Dependency: libcgroup >= 0.40.rcl5.15 for package: docker-20.10.13-2.amzn2.x86_64
--> Processing Dependency: containerd >= 1.3.2 for package: docker-20.10.13-2.amzn2.x86_64
--> Processing Dependency: pigz for package: docker-20.10.13-2.amzn2.x86_64
--> Running transaction check
--> Package containerd.x86_64 0:1.4.13-2.amzn2.0.1 will be installed
--> Package libcgroup.x86_64 0:0.41-21.amzn2 will be installed
--> Package pigz.x86_64 0:2.3.4-1.amzn2.0.1 will be installed
--> Package runc.x86_64 0:1.0.3-2.amzn2 will be installed
--> Finished Dependency Resolution

Dependencies Resolved

=====
| Package      | Arch | Version       | Repository | Size |
|=====|=====|=====|=====|=====|
| Installing: |       |             |            |        |
| docker       | x86_64 | 20.10.13-2.amzn2 | amzn2extra-docker | 40 M |
| Installing for dependencies: |       |             |            |        |
| containerd  | x86_64 | 1.4.13-2.amzn2.0.1 | amzn2extra-docker | 23 M |
| libcgroup   | x86_64 | 0.41-21.amzn2    | amzn2-core       | 66 k  |
| pigz        | x86_64 | 2.3.4-1.amzn2.0.1 | amzn2-core       | 81 k  |
| runc        | x86_64 | 1.0.3-2.amzn2    | amzn2extra-docker | 3.0 M |
|=====|=====|=====|=====|=====|
Transaction Summary
=====
| Install 1 Package (<4 Dependent packages) |
Total download size: 67 M
Installed size: 280 M
Is this ok [D/y/N]: y
Downloading packages:
(1/5): libcgroup-0.41-21.amzn2.x86_64.rpm | 66 kB 00:00:00
(2/5): pigz-2.3.4-1.amzn2.0.1.x86_64.rpm | 81 kB 00:00:00
(3/5): containerd-1.4.13-2.amzn2.0.1.x86_64.rpm | 23 MB 00:00:00
(4/5): docker-20.10.13-2.amzn2.x86_64.rpm | 40 MB 00:00:00
(5/5): runc-1.0.3-2.amzn2.x86_64.rpm | 3.0 MB 00:00:00
=====
Total
Running transaction check
Running transaction test
Transaction test succeeded
Running transaction
  Installing : runc-1.0.3-2.amzn2.x86_64
  1/5
  Installing : containerd-1.4.13-2.amzn2.0.1.x86_64
  2/5
  Installing : libcgroup-0.41-21.amzn2.x86_64
  3/5
  Installing : pigz-2.3.4-1.amzn2.0.1.x86_64
  4/5
  Installing : docker-20.10.13-2.amzn2.x86_64 [#####
] 5/5
  66 MB/s | 67 MB 00:00:01
| 74% | 5.3 GB | 0 18% | ① 5-04, 1:31 PM | snuffle | ↻ | □ ~ | % ssh + fish + bash + zsh + fish + fish + fish + fish + fish + fish + spacedust |
```

Figure A.16: Installing Docker using Package Manager (In Progress)

```
git-core x86_64 2.32.0-1.amzn2.0.1 amzn2-core 2.7 M
git-core-doc noarch 2.32.0-1.amzn2.0.1 amzn2-core 2.7 M
perl-Error noarch 1:0.17020-2.amzn2 amzn2-core 32 k
perl-Git noarch 2.32.0-1.amzn2.0.1 amzn2-core 43 k
perl-TermReadKey x86_64 2.30-20.amzn2.0.2 amzn2-core 31 k

Transaction Summary
=====

Install 1 Package (+6 Dependent packages)

Total download size: 7.8 M
Installed size: 38 M
Is this ok [y/d/N] y
Downloading packages:
=====
(G/7): emacs-fs/filesystem-27.2-2.x86_64.amzn2.0.1.noarch.rpm | 67 kB 00:00:00
(G/7): git-2.32.0-1.amzn2.0.1.x86_64.rpm | 126 kB 00:00:00
(G/7): git-core-doc-2.32.0-1.amzn2.0.1.noarch.rpm | 2.7 MB 00:00:00
(G/7): perl-Error-0.17020-2.amzn2.noarch.rpm | 32 kB 00:00:00
(G/7): perl-Git-2.32.0-1.amzn2.0.1.noarch.rpm | 43 kB 00:00:00
(G/7): git-core-2.32.0-1.amzn2.0.1.x86_64.rpm | 4.8 MB 00:00:00
(G/7): perl-TermReadKey-2.30-20.amzn2.0.2.x86_64.rpm | 31 kB 00:00:00
=====
29 MB/s | 7.8 MB 00:00:00

Total
Running transaction check
Running transaction test
Transaction test succeeded
Running transaction
=====
Installing : git-core-2.32.0-1.amzn2.0.1.x86_64 1/7
Installing : git-core-doc-2.32.0-1.amzn2.0.1.noarch 2/7
Installing : 1:perl-Error-0.17020-2.amzn2.noarch 3/7
Installing : 1:emacs-fs/filesystem-27.2-2.x86_64.amzn2.0.1.noarch 4/7
Installing : perl-TermReadKey-2.30-20.amzn2.0.2.x86_64 5/7
Installing : perl-Git-2.32.0-1.amzn2.0.1.noarch 6/7
Installing : git-core-2.32.0-1.amzn2.0.1.x86_64 7/7
Verifying : perl-TermReadKey-2.30-20.amzn2.0.2.x86_64 1/7
Verifying : git-core-doc-2.32.0-1.amzn2.0.1.noarch 2/7
Verifying : perl-Git-2.32.0-1.amzn2.0.1.noarch 3/7
Verifying : 1:emacs-fs/filesystem-27.2-2.x86_64.amzn2.0.1.noarch 4/7
Verifying : git-2.32.0-1.amzn2.0.1.x86_64 5/7
Verifying : git-core-2.32.0-1.amzn2.0.1.x86_64 6/7
Verifying : 1:perl-Error-0.17020-2.amzn2.noarch 7/7

Installed:
git.x86_64 0:2.32.0-1.amzn2.0.1

Dependency Installed:
emacs-fs/filesystem.noarch 1:27.2-4.amzn2.0.1 git-core.x86_64 0:2.32.0-1.amzn2.0.1 git-core-doc.noarch 0:2.32.0-1.amzn2.0.1 perl-Error.noarch 1:0.17020-2.amzn2 perl-Git.noarch 0:2.32.0-1.amzn2.0.1 perl-TermReadKey.x86_64 0:2.30-20.amzn2.0.2

Complete!
[ec2-user@ip-172-31-27-208 ~]$ █
& snuffleupug □ ⟲ ls ssh • fish • bash • zsh • fish • fish • fish • fish -fslsh | spacedust |
```

Figure A.17: Installing Git

Figure A.18: Starting Docker systemd Service

The screenshot shows the AWS EC2 Instances page. On the left, there's a sidebar with various navigation options like EC2 Dashboard, EC2 Global View, Events, Tags, Limits, Instances (selected), Instance Types, Launch Templates, Spot Requests, Savings Plans, Reserved Instances, Dedicated Hosts, Scheduled Instances, Capacity Reservations, Images, AMIs, and AMI Catalog. The main content area has a title 'Instances (2) Info' with a search bar and a table. The table has columns for Name, Instance ID, Instance state, Instance type, Status check, Alarm status, Availability Zone, and Public IP. It lists two instances: 'Group4_EC2' (terminated, t2.micro, us-east-1d) and 'Group4_EC2' (running, t2.micro, us-east-1d). Below the table is a modal titled 'Select an instance'.

Figure A.19: Instances

The screenshot shows the 'Launching instance' step in the AWS EC2 instance launch process. At the top, there's a message about opting into the new launch experience with a 'Opt-out to the old experience' link. Below it, the breadcrumb navigation shows 'EC2 > Instances > Launch an instance'. The main content area has a title 'Launching instance' and instructions: 'Please wait while we launch your instance.' and 'Do not close your browser while this is loading.' A progress bar at the bottom indicates 'Launch initiation' is at 80% completion. There's also a 'Details' link.

Figure A.20: Launching Instance

```

ec2-user@ip-172-31-27-208:~/digital-ink
logout
Connection to 3.91.192.250 closed.
> ssh -i ~/Desktop/Group4_KeyPair.pem ec2-user@3.91.192.250
Last login: Wed May  4 13:21:09 2022 from 193.60.143.12
  _\|_ _\|_
 _\| (   /  Amazon Linux 2 AMI
  _\|_\|_|_|
https://aws.amazon.com/amazon-linux-2/
[ec2-user@ip-172-31-27-208 ~]$ cd digital-ink
[ec2-user@ip-172-31-27-208 digital-ink]$ cd ..
[ec2-user@ip-172-31-27-208 ~]$ sudo mv digital-ink digital-ink.old
[ec2-user@ip-172-31-27-208 ~]$ git clone https://github.com/ChrisP99/digital-ink.git
Cloning into 'digital-ink'...
remote: Enumerating objects: 9909, done.
remote: Counting objects: 100% (9909/9909), done.
remote: Compressing objects: 100% (6382/6382), done.
remote: Total 9909 (delta 3080), reused 9863 (delta 3034), pack-reused 0
Receiving objects: 100% (9909/9909), 17.59 MiB | 14.30 MiB/s, done.
Resolving deltas: 100% (3080/3080), done.
Updating files: 100% (8963/8963), done.
[ec2-user@ip-172-31-27-208 ~]$ cd digital-ink
[ec2-user@ip-172-31-27-208 digital-ink]$ sudo /usr/local/bin/docker-compose up -d
[*] Running 3/3
  • Container digital-ink-db-1  Running
  • Container phpmadmin  Running
  • Container digital-ink-app-1 Started
[ec2-user@ip-172-31-27-208 digital-ink]$ sudo /usr/local/bin/docker-compose down
[*] Running 4/4
  • Container phpmadmin  Removed
  • Container digital-ink-app-1 Removed
  • Container digital-ink-db-1 Removed
  • Network digital-ink_default Removed
[ec2-user@ip-172-31-27-208 digital-ink]$ sudo /usr/local/bin/docker-compose up -d
[*] Running 4/4
  • Network digital-ink_default Created
  • Container digital-ink-db-1 Started
  • Container phpmadmin  Started
  • Container digital-ink-app-1 Started
[ec2-user@ip-172-31-27-208 digital-ink]$ sudo /usr/local/bin/docker-compose exec app bash
root@c565ab9c37ff:/srv/app# php artisan migrate
Nothing to migrate.
root@c565ab9c37ff:/srv/app# 

```

Figure A.21: Log In with Key Pair




Figure A.22: Selecting a VPC Configuration




Figure A.23: Successfully Initiated Instance




Figure A.24: VPC Successfully Created




Figure A.25: VPC with Public and Private Subnets, Loading




Figure A.26: VPC with Public and Private Subnets

Your VPCs (2) info

Name	VPC ID	State	IPv4 CIDR	IPv6 CIDR
-	vpc-006b19b59ed484041	Available	172.31.0.0/16	-
Group4_VPC	vpc-0b0472507c8bf18c9	Available	10.0.0.0/16	-

vpc-07657585bc0e3b3b5

Details CIDs Flow logs Tags

Details

VPC ID vpc-07657585bc0e3b3b5	State Available	DNS hostnames Disabled	DNS resolution Enabled
---------------------------------	--------------------	---------------------------	---------------------------

Feedback Looking for language selection? Find it in the new Unified Settings [?](#)

© 2022, Amazon Web Services, Inc. or its affiliates. [Privacy](#) [Terms](#) [Cookie preferences](#)

Figure A.27: Your VPCs