
The model is solved by value function iteration based on the standard calibration of Arellano (2008) considering 21 states for the output level, and 250 grid points in the interval [-0.4:0] for debt. The computed value functions are:



The value functions are plotting by output level from blue [low level of output] to red [high level of output].

The result shows states with high non-linearities. When we split the solution into the value of repayment and the value of default we find:




Figure 2: Value and Policy functions

In panels (a) and (b) I plot the value functions for repayment and default, respectively. Fo the latter, we observe linear function dependent of the state level. In contrast, the value of repayment is concave for low levels of production and passing to be almost linear in the high states. In panel (c) we observed that the policy function for new issued debt is highly non-linear, while the default choices (panel d) exhibits well defined limits between the states in which the government chooses whether defaulting.

After simulated 1 million observations from the model, I find a default probability of 2.58 percent with the following state of default (plotted in panel b): The figure shows two potential





Figure 3: Simulated default states



Panel (b) plots the simulated states of default leaving in white the state combinations that are not observed in the simulation.

problems that an implementation of a PLM could face. First, there is a large portion of the state-space that is not covered by the simulation. It could lead a high out-sample forecast problem given the overweight of non-default states. Second, the difference between the policy

function and the state of default. The policy function reflects the optimal default decision that government makes. However, we only observe that state of default which also considers stay in default after a defaulting. It is showed in panel (b) when although there is not debt the default state is still shaded in yellow.

1 The updating algorithm

To update the policy functions, I follow:

Initialization:
$$v_r^{(0)}, v_d^{(0)}$$

$$v^{(0)} = max\left(v_r^{(0)}, v_d^{(0)}\right)$$
Initial bond price:
$$D^{(0)} = \mathcal{I}\left(max\left(v_r^{(0)}, v_d^{(0)}\right)\right)$$

$$q^{(0)} = \left(\frac{1}{1-r}\right) \cdot * (1 \cdot - \delta^{(0)})$$

Updating expectations:

$$\begin{split} \mathbb{E}[v]^{(1)} &= v^{(0)} \Pi^T \\ \mathbb{E}[v_r]^{(1)} &= v_r^{(0)} \Pi^T \\ \mathbb{E}[v_d]^{(1)} &= v_d^{(0)} \Pi^T \end{split}$$

Finding Policy function and updating value functions (and price):

$$\begin{split} v_r^{(1)} &= \max\{u(b+y-q^{(0)}b') + \beta \mathbb{E}[v]^{(1)}\} \to \text{by choosing } b^{(1)'} \\ v_d^{(1)} &= u(y^{def}) + \beta(\theta \mathbb{E}[v|b'=0]^{(1)} + (1-\theta)\mathbb{E}[v_d]^{(1)}) \\ v^{(1)} &= \max\left(v_r^{(1)}, v_d^{(1)}\right) \\ D^{(1)} &= \mathcal{I}\left(\max\left(v_r^{(1)}, v_d^{(1)}\right)\right) \\ \delta^{(1)} &= D^{(1)}\Pi^T \\ q^{(1)} &= \left(\frac{1}{1-r}\right) . * (1.-\delta^{(1)}) \end{split}$$

 $\frac{q^{(1)} = \left(\frac{1}{1-r}\right) \cdot * (1 \cdot - \delta^{(1)})}{\text{To verify that the implementation is correct I run the algorithm with the value functions}}$ solved in the model and I find no discrepancy in the updated policy functions

2 Selecting initial models

Before to implement the algorithm with simulated data, I will show how some model perform when they use all the information from the model [value functions in the whole grid]. The models to be compare are:

1. OLS:

$$v_r = \beta_0 + \beta_1 b + \beta_2 y + \beta_3 b^2 + \beta_4 y^2 + \beta_5 b * y + \epsilon$$

2. Power series with normalization in range [-1,1]:

If x lies in the interval [a,b], the transformation:

$$\tilde{x} = 2\frac{x-a}{b-a} - 1$$

will lies in the interval [-1,1].

Procedure:

- \bullet Determine an expansion degree d
- I calculate \tilde{b} , \tilde{y} , and \tilde{v}_r
- Estimate by OLS

$$\tilde{v}_r = \sum_{i=0}^d \sum_{j=0}^{d-i} \alpha_{i,j} \tilde{b}^i \tilde{y}^j + \epsilon_{ps}$$

- 3. Chebyshev basis: Procedure
 - \bullet Determine an expansion degree d
 - I calculate \tilde{b} , \tilde{y} , and \tilde{v}_r
 - Estimate by OLS

$$\tilde{v}_r = \sum_{i=0}^d \sum_{j=0}^{d-i} \theta_{i,j} T_i(\tilde{b}) T_j(\tilde{y}^j) + +\epsilon_{cheb}$$

where T(x) is the Chebyshev polynomial of the first kind.

- 4. Neural Networks with one hidden layer, d neurons and the following activation functions
 - (a) softplus: f(x) = log(exp(x) + 1)
 - (b) tanh: $f(x) = \frac{exp(2x)-1}{exp(2x)+1}$
 - (c) elu: $f(x) = \begin{cases} x & \text{if } x > 0 \\ exp(x) 1 & \text{otherwise} \end{cases}$
 - (d) sigmoid: $f(x) = \frac{1}{1 + exp(-x)}$
 - (e) swish: $f(x) = \frac{x}{1 + exp(-x)}$

The estimation is made by using a descent algorithm, and minimizing the MSE. Each sample is composed by 10 times the total observations number randomly sorted to exploit the learning. I consider 10 epochs per model training.


4

Table 2 show the MSE and MAE calculated over the original values of v_r after estimating each model with d=4

Table 1: Fit error by model

	OLS	Power series	Chebyshev	Sotfplus	Tanh	Elu	Sigmoid	Swish
RMSE	0.034	0.009	0.009	0.033	0.015	0.018	0.013	0.014
MAE	0.148	0.029	0.029	0.082	0.069	0.068	0.068	0.068
RMS $100 * \frac{\hat{v}_r - v_r}{v_r}$	0.156	0.04	0.04	0.157	0.067	0.081	0.06	0.066
$MA 100 * \frac{\hat{v}_r - v_r}{v_r}$	0.6	0.124	0.124	0.366	0.28	0.278	0.278	0.277

Figure 4: Estimated residual



Panel (a) plots the value of repayment, while the rest of panel plot the residuals of each proposed model.


In relative terms, there are not big differences between power series functions and neural networks, but after applying the updating algorithm and simulated 100 thousands observations, I find high volatility in terms of percentage of defaults. With exception of the simplest OLS model, the percentage of error in default decisions are lower than 2 percent. However, the OLS model performs better in one-step ahead updating.

Table 2: Fit error by model

	OLS	Power series	Chebyshev	Sotfplus	Tanh	Elu	Sigmoid	Swish
Default %	8.47	1.99	1.94	46.81	40.2	42.87	41.47	24.01
% Default Error	2.7	0.4	0.4	1.1	1.3	1.5	1.2	1.2


One possible explanation of these results appears after observing the error in the policy function for new debt after updating. Figure 6 plots these series.

Figure 5: Estimated residual



Panel (a) plots the policy function for debt, while the rest of panels plot the policy function for new debt of each proposed model.

Figure 6: Error in Policy functions



Panel (a) plots the policy function for debt, while the rest of panels plot the residuals of each proposed model.