

Quantitative Research Methods

Chapter 1: Introduction

Prof. Dr. Christoph Weisser

The course at a glance

Chapter	Topic
Ch. 1	Introduction
Ch. 2	Statistical learning — accuracy, bias–variance, Bayes classifier, KNN
Ch. 3	Linear regression — estimation, inference, diagnostics
Ch. 4	Classification — logistic regression, confusion matrix, ROC
Ch. 5	Resampling — validation, CV, bootstrap
Ch. 6	Model selection and regularisation — ridge, lasso
Ch. 7	Moving beyond linearity — splines, GAMs
Ch. 8	Tree-based methods — trees, forests, boosting
Ch. 10	Deep learning — MLPs, CNNs, training

Nine chapter decks of 180 minutes each, after a taught precourse session; Chapters 2, 3 and 4 run over two sessions apiece. Today's chapter is highlighted. Short exercises every ~ 20 min; extended exercises every ~ 45 min; each chapter has a companion lab notebook.

Support vector machines (Ch. 9), survival analysis (Ch. 11), multiple testing (Ch. 13) and unsupervised learning (Ch. 12) are optional self-study modules in Chapters/Advanced/.

Contents

1 Welcome

2 Definitions

3 Examples

4 Tools

5 Datasets

6 Roadmap

7 Pitfalls

8 Summary

Optional and advanced material is collected in the **appendix** at the end of the deck.

Notation in this chapter

Symbol	Meaning
n	number of observations (sample size)
p	number of variables (predictors)
x_i	predictor value(s) of the i -th observation
y_i	response value of the i -th observation
X	$n \times p$ matrix of all predictor values
y	n -vector stacking the responses $y_1, \dots, y_n$
x_{ij}	value of variable j for observation i
$Y = f(X) + \varepsilon$	general model: systematic part plus noise
f	unknown true function linking X to Y
ε	random error term with mean zero
$\hat{f}$	estimate of f learned from the data
$\hat{Y} = \hat{f}(X)$	prediction of Y at input X

Sources and references

Primary textbook

James, G., Witten, D., Hastie, T., Tibshirani, R., & Taylor, J. (2023). *An Introduction to Statistical Learning, with Applications in Python*. Springer.

About these slides

Each idea is introduced with motivation, intuition, and a worked example. Slide titles are descriptive; key formulas are read symbol-by-symbol.

Learning objectives for this chapter

By the end of this chapter you will be able to:

- **Define** statistical learning and explain why it matters.
- **Distinguish** supervised from unsupervised learning, and regression from classification.
- **Articulate** the difference between prediction and inference, and explain when each goal applies.
- **Read** the standard notation: n , p , design matrix X , response vector y .
- **Recognise** the three motivating data sets (Wage, Smarket, NCI60) and the type of question each illustrates.
- **Set up** the Python tooling we will use throughout.

Where this chapter is used in industry

Sector	Concrete application	Which decision it drives
Banking	Credit scoring at application: probability of default from bureau and application data	Accept or decline this applicant; where to set the cut-off and the credit limit
Retail	Weekly demand forecast per article and store	How many units to order and where to set the reorder point
Telco, SaaS	Churn score per subscriber for the coming quarter	Which subscribers receive a retention offer, and which are left alone

A number is only worth modelling if it moves a lever

All three rows need the same three ingredients: a response somebody actually recorded, predictors that are *available before* the decision is taken, and a lever that moves when the number moves. Without the third, the model is a report, not a tool.

Two business problems we follow all semester

Not twelve unrelated anecdotes: two business problems return chapter after chapter.

A retail bank's credit scorecard

Ch. 00b	the log-odds scale a scorecard is built on
Ch. 04	the scorecard itself: PD, cut-off, reason codes
Ch. 05	independent validation, out-of-time testing
Ch. 06	which bureau attributes make the final card
Ch. 07	why scorecards bin inputs into bands
Ch. 08	the boosted challenger model
Ch. 13	fairness testing across many subgroups

A retailer's pricing and demand question

Ch. 00b	elasticity from a log-log model
Ch. 02	what is irreducible in a demand forecast
Ch. 03	marketing mix modelling and the budget split
Ch. 07	the price-response curve that saturates
Ch. 08	the boosted demand forecast
Ch. 10	one network across thousands of series

One decision — many chapters

Neither list is a tour of techniques. The same decision — accept this applicant, set this price — keeps coming back, and each chapter adds the piece the previous tool could not supply: a validated card, a shorter list of attributes, a curve that saturates. Methods are chosen by what the decision needs, never because they are new.

Outline

- 1 Welcome
- 2 Definitions
- 3 Examples
- 4 Tools
- 5 Datasets
- 6 Roadmap
- 7 Pitfalls
- 8 Summary

Roadmap of this chapter

How this chapter is organised

- 1 Why statistical learning matters today.
- 2 Definitions: supervised vs. unsupervised, regression vs. classification.
- 3 Three motivating examples: Wage, Smarket, NCI60.
- 4 Notation: n , p , design matrix X .
- 5 The Python ecosystem we will use.

Each section ends with a mini-check question to help you self-assess.

Why statistical learning is the most-asked-for skill

Every discipline now collects more data than it can analyse by hand.

The pressure

Storage is essentially free; sensors, transactions, and web interactions generate terabytes per minute. The bottleneck has shifted from collecting data to understanding it.

Hal Varian quote

"I keep saying that the sexy job in the next ten years will be statisticians. And I'm not kidding."

What this course is and is not

What it is

A course on the *statistical foundations* of learning. We focus on *ideas*, interpretability, and honest evaluation.

What it is not

A pure machine-learning engineering course. We will not deploy deep nets at production scale.

The course's promise

Two questions for every model: (1) *What does this model assume about the world?* (2) *What happens when those assumptions fail?*

Prerequisites

Mathematics

Linear algebra (matrices, eigenvectors), introductory calculus (derivatives, gradients), basic probability.

Statistics

Descriptive statistics; simple/multiple linear regression at the level of an introductory econometrics course.

Programming

Some Python experience is helpful but not required — we start from the basics in the lab sessions.

The convergence of statistics and computer science

Statistics emphasises

- models and assumptions
- inference and uncertainty
- interpretability
- rigorous quantification of error

Machine learning emphasises

- algorithms and computation
- predictive accuracy
- flexibility and scale
- large, complex data sets

Statistical learning

The intersection: methods that are computationally feasible *and* statistically principled.

Outline

- 1 Welcome
- 2 Definitions
- 3 Examples
- 4 Tools
- 5 Datasets
- 6 Roadmap
- 7 Pitfalls
- 8 Summary

What is statistical learning?

In one sentence

Statistical learning is the use of **past data** to build a **rule** that turns what we *can* measure into what we *want to know* — together with an honest account of how far that rule can be trusted.

The same sentence with a data set attached

Past data: 3 000 recorded salaries, each with the age, education and year that came with it.

The rule: what to expect a 45-year-old graduate to earn. *How far to trust it:* two people with identical records still earn different salaries, and a useful model says how wide that spread is.

Takeaway

The second half is what makes it *statistical*. Any program can print a number; a statistical model also says how much of that number is noise.

The one equation the whole course rests on

The statistical-learning model

With a response Y and predictors $X = (X_1, \dots, X_p)$, assume a systematic relationship:

$$Y = f(X) + \varepsilon$$

How to read this


f is the *systematic* part — what X genuinely says about Y : fixed, real, never observed. ε is everything else (variables nobody recorded, plain chance), with mean zero. *Learning* means estimating f by an $\hat{f}$ built from n past cases.

Takeaway

Every method in this course is another way of estimating the same f ; they differ only in what they assume about its shape — and none can beat ε .

Which box is my problem in? Two questions decide (native diagram)

Do not start from the method. Start from two questions about the data you already have.



Takeaway

Two answers fix the branch. Which algorithm you then use — and how flexible it is — is a choice *inside* the box, and that is what the rest of the course is about.

Answering the two questions — and the usual traps

Q1 asks what your rows contain — not what you wish they contained

A firm that wants to score churn but never recorded who churned has no supervised problem — it has a labelling project. Outcome written down: credit decisions, weekly demand, churn. Nothing written down: segmentation, anomaly detection.

Q2 asks about the response only — never the predictors

A postcode stored as an integer is a class; a five-star rating stored as text is a number. The test: what would being *wrong* mean? Off by how much $\Rightarrow$ regression; in the wrong bucket $\Rightarrow$ classification.

Why the branch matters at all

It fixes how you keep score: squared error, or misclassification rate — and for unsupervised problems, no “accuracy” at all: nothing to be right about.

The fundamental setup

We observe a sample

$$\{(x_1, y_1), (x_2, y_2), \dots, (x_n, y_n)\}$$

where each $x_i \in \mathbb{R}^p$ is a vector of p *predictors* and y_i is a *response*.

How to read this

Symbol	Meaning
n	Number of observations (sample size)
p	Number of predictors per observation
x_i	Vector of p predictors for observation i
y_i	Response for observation i (number or category)

In the unsupervised case there is no y_i — we only have $x_1, \dots, x_n$.

Two distinct goals: prediction vs. inference

Prediction

Given a new x_0 , what value of Y should we expect?

Inference

How does Y depend on X ? Which features matter? In what direction? By how much?

Two examples


Prediction: given a patient's measurements, will they survive 5 years?

Inference: which marketing channels actually drive sales?

Which goal you have shapes the method

Most real problems involve both. Prediction can tolerate a black-box model; inference demands an interpretable $\hat{f}$ whose structure we can read off.

The supervised-learning workflow



Takeaway

We learn $\hat{f}$ from training data, then reuse it on new inputs — prediction targets $\hat{y}_0$; inference targets the structure of $\hat{f}$.

Exercise 1.1 — Prediction vs. Inference [Concept]

Exercise

For each scenario, decide whether the *primary* goal is **prediction** or **inference**, and justify in one line.

- 1 A bank wants to know *which* applicant characteristics raise default risk, and *by how much*.
- 2 A streaming service auto-fills the rating a user would give a film they have not seen.
- 3 An economist estimates the effect of a minimum-wage rise on employment.
- 4 A hospital flags high-risk patients from lab values; it need not explain the reasoning.
- 5 For a *pure inference* goal, would you prefer a linear model or a deep neural network? Why?

Solution — Exercise 1.1 (1/2)

Solution

How to decide. Ask what the *deliverable* is: an accurate value $\hat{Y}$ for new cases means *prediction*; a statement about *how* Y depends on the X_j (which ones, in which direction, by how much) means *inference*.

- 1 **Inference.** The deliverable is which predictors matter and the direction/magnitude of their effect, not a single forecast. The give-away words are “*which* characteristics” and “*by how much*” — both ask about the structure of f , so the bank needs a model whose coefficients it can read off and defend.
- 2 **Prediction.** Only the accuracy of the filled-in rating matters; *why* the user would rate it that way is irrelevant. The rating is consumed directly by the recommender — nobody inspects the mechanism — so a black-box $\hat{f}$ is perfectly acceptable.
- 3 **Inference.** The goal is a causal effect size (a coefficient with a confidence interval). A forecast of employment alone would not answer the policy question “what happens *if* the minimum wage rises?”.

Solution — Exercise 1.1 (2/2)

Solution

- ④ **Prediction.** Accurate flagging is what counts; interpretability is secondary here. The hospital acts on the flag itself (direct attention to high-risk patients), so the model is judged purely on its held-out accuracy.
- ⑤ **Linear model.** Its coefficients have direct meaning and come with standard errors, confidence intervals and p -values, so we can quantify *how* Y depends on each X_j . A deep network predicts well but is a black box — its weights do not answer an inference question.

Rule of thumb: prediction cares only about $\hat{Y}$; inference cares about the *structure* of f .

Common mistake

Classifying by the *tool* instead of the *question* (“it uses regression, so it must be inference”). Any model can serve either goal — what decides is whether the answer you hand over is $\hat{Y}$ itself or the shape of f .

Outline

- 1 Welcome
- 2 Definitions
- 3 Examples**
- 4 Tools
- 5 Datasets
- 6 Roadmap
- 7 Pitfalls
- 8 Summary

Three motivating examples set the tone

We will study three very different data sets, each illustrating one major flavour of problem.

Takeaway

- **Wage:** regression, mostly inference — the same shape as a pay-equity review, where the coefficient *is* the deliverable.
- **Smarket:** classification, weak signal — the same shape as a trading or forecasting signal with a very low signal-to-noise ratio.
- **NCI60:** unsupervised, structure discovery — the same shape as segmenting customers or products where no label exists.

Example 1: Wage — a regression problem

The data

Survey of 3,000 men working in the central Atlantic region of the U.S. Response wage is continuous, so this is a *regression* problem.


Variables

- Response: wage (annual income in thousands of dollars).
- Predictors: age, year, education, plus marital status, race, region.

Live demo — §1 of the notebook

Switch to `chapter_01_lab.ipynb` §1 and run the loading and plotting cells: `Wage.shape` prints (3000, 11), and the three-panel reproduction of Fig. 1.1 shows the wage–age curvature live.

Wage data: wage vs. age, year, and education



Source: Figure 1.1 — ISLP, James et al. (2023).

What the Wage plots tell us

Reading the three panels left to right:

- **Wage vs. age:** increasing until around 60, then a slight decline — a *nonlinear* relationship.
- **Wage vs. year:** a slow upward trend — wages grow modestly over time.
- **Wage vs. education:** a strong, monotone effect — higher education levels mean higher wages.

Modelling implication

A purely linear regression in age would miss the curvature. We will need polynomial terms or splines (Ch. 7).

Example 2: Smarket — a classification problem

The data

Daily percentage returns of the S&P 500 from 2001–2005. Response Direction (Up/Down) is binary, so this is a *classification* problem.


Variables

- Response: Direction (Up / Down).
- Predictors: Lag1, ..., Lag5 (previous five days' returns) and Volume.

Live demo — §2 of the notebook

Switch to `chapter_01_lab.ipynb` §2 and run the boxplot cell: the Lag1–Lag3 boxes for Up vs. Down days overlap almost completely — the weak signal the next slides discuss, drawn from the raw data.

Smarket: previous-day returns by direction



Source: Figure 1.2 — ISLP, James et al. (2023).

Reading the boxplots

Each panel compares returns from one, two, and three days ago for days where the market went Up vs. Down.


The bad news

The boxplots are *nearly identical*. Past returns barely predict the next day's direction — consistent with the efficient-markets hypothesis.

A cautionary tale

Even when a problem “looks like” a classification problem, it does not follow that we can solve it well. Prediction is only possible if predictors actually carry information about the response.

Smarket: a tiny but real signal



Quadratic discriminant analysis on the same predictors yields about 60 % accuracy on held-out 2005 data — a small but potentially profitable edge.

Source: Figure 1.3 — ISLP, James et al. (2023).

Example 3: NCI60 — an unsupervised problem

The data

NCI60: 64 cancer cell lines, 6,830 gene expression measurements each. *No* response variable — we don't know what to predict.


Takeaway

Goal: discover *groups* of similar cell lines (clustering) and *visualise* the high-dimensional data in 2D (dimension reduction). This is unsupervised learning.

Live demo — §3 of the notebook

Switch to `chapter_01_lab.ipynb` §3 and run the PCA cell (needs the ISLP package; Colab installs it automatically): 6 830 genes collapse to two components, and cell lines of the same cancer type land next to each other.


NCI60: the first two principal components



Cell lines of the same cancer type cluster together. PCA recovered biologically meaningful structure from raw gene expression alone — without ever seeing the labels.

Source: Figure 1.4 — ISLP, James et al. (2023).

The three problems on one map



Takeaway

Where a data set sits decides which chapters apply. Below the diagonal ($n \gg p$) least squares behaves; NCI60 sits at $p/n \approx 107$, where no unique least-squares fit exists — hence Chapter 6, and the unsupervised Advanced module (Ch. 12).

What the three examples illustrate

The course's three flavours

- **Wage**: a quantitative response, mostly an *inference* question → regression.
- **Smarket**: a categorical response, mostly a *prediction* question → classification.
- **NCI60**: no response, structural questions → unsupervised learning.

These three flavours structure the rest of the course.

Live demo — §4 of the notebook

Run the summary-table cell in `chapter_01_lab.ipynb` §4: it prints n , p and p/n for the three data sets side by side — $p/n \approx 0.003$ for Wage against 107 for NCI60.

Mini-check: types of problems

Quick self-assessment

For each of the following, decide: regression, classification, or unsupervised?

- 1 Predicting next year's GDP growth from macro indicators.
- 2 Detecting which customers will cancel their subscription.
- 3 Grouping news articles into topics without prior labels.
- 4 Forecasting house prices from features.
- 5 Identifying the digit shown in a 28×28 pixel image.

Answers

1. regression. 2. classification. 3. unsupervised. 4. regression. 5. classification.

Notation: n , p , and the design matrix

Sample size and dimension

- n : number of observations
- p : number of predictors (features)

Generic notation

Object	Notation
Scalars	lower-case italic, a, b, x, y
Vectors of length n	bold lower-case, $\mathbf{a}$
Vectors of length $\neq n$	lower-case italic, x_i
Matrices	bold upper-case, $\mathbf{A}, \mathbf{X}$

Exercise 1.2 — Regression, Classification, or Unsupervised? [Concept]

Exercise

Classify each task. If it is *supervised*, also say whether it is **regression** or **classification** and name the response Y .

- 1 Predict a used car's selling price from mileage, age, brand.
- 2 Segment 64 cell lines described by 6,830 gene-expression values into similar groups.
- 3 Predict whether an incoming e-mail is spam.
- 4 Forecast tomorrow's electricity demand (MWh) from weather and calendar features.
- 5 Reduce 20 survey questions to a few underlying "factors".
- 6 Recognise which of the digits 0–9 a handwritten image shows.

Solution — Exercise 1.2 (1/2)

Solution

Method. First look for a designated response Y : none $\Rightarrow$ *unsupervised*. If there is one, its *type* decides: quantitative $\Rightarrow$ regression, qualitative $\Rightarrow$ classification.

- ➊ **Supervised regression**; $Y = \text{price}$ (quantitative). Past sales provide labelled pairs (features, price), and the target is a number on a continuous scale — exactly the setting squared-error loss is made for.
- ➋ **Unsupervised** (clustering); there is no response Y . All 6,830 gene-expression values are inputs — none of them is a label — and the goal is to *discover* groups, not to predict anything.
- ➌ **Supervised classification**; $Y = \text{spam / not-spam}$ (binary, qualitative). The training e-mails are already labelled, and the output is a category, not a quantity.

Solution — Exercise 1.2 (2/2)

Solution

- ④ **Supervised regression**; Y = demand in MWh (quantitative). Weather and calendar variables are the predictors; historical demand records supply the labels.
- ⑤ **Unsupervised** (dimension reduction); no response Y . We seek a few latent “factors” that summarise 20 correlated answers — PCA / factor-analysis territory (Ch. 12, an optional Advanced module).
- ⑥ **Supervised classification**; Y = digit $0, \dots, 9$ (10 qualitative classes). The pixel intensities are *numeric predictors*, but numeric inputs do not make it a regression — the output is one of ten categories, and a “7” is not numerically closer to an “8” than to a “1” in any sense that squared error could use.

Decision rule: no $Y \Rightarrow$ unsupervised. With a Y : quantitative $\Rightarrow$ regression, qualitative $\Rightarrow$ classification. The type of the *response* decides — not the predictors.

Common mistake

Letting the predictors vote — e.g. calling digit recognition “regression” because pixels are numbers, or task 1 “classification” because brand is categorical. Only the type of Y matters.

Outline

- 1 Welcome
- 2 Definitions
- 3 Examples
- 4 Tools**
- 5 Datasets
- 6 Roadmap
- 7 Pitfalls
- 8 Summary

Why Python?

Python is the most widely used language in industry data science and machine learning.

The scientific stack

NumPy, pandas, matplotlib, scikit-learn, statsmodels, ISLP. All free, mature, and well-documented.

How to read this

The *first* edition of the textbook used R. The methods are identical — only the syntax changes. We will use Python throughout.

Two libraries, two jobs

Reach for statsmodels where a coefficient has to be defended, and for scikit-learn where a score has to be produced every night.

The core scientific stack

Library	Role
numpy	numerical arrays, linear algebra
pandas	data frames, CSV I/O, group-by
matplotlib	plotting (low-level)
seaborn	plotting (statistical)
scipy	scientific routines (optimisation, stats)
statsmodels	inference-oriented regression / GLM
scikit-learn	general-purpose ML
ISLP	book companion package

Standard imports

```
import numpy as np # arrays/linear algebra: maths layer
import pandas as pd # labelled tables: the data layer
import matplotlib.pyplot as plt # plots: look before you model

# scikit-learn, in the order you use it: model, split, score
from sklearn.linear_model import LinearRegression, LogisticRegression
from sklearn.model_selection import train_test_split, cross_val_score
from sklearn.metrics import mean_squared_error, accuracy_score

from ISLP import load_data # book datasets, loaded by name
```

How to read this

Adopt these as the default first cell of every notebook. Nothing is computed here — the cell only makes tools available, so it prints nothing. The `sklearn` lines supply, in the order you use them, the *model*, the *split* that keeps a score honest, and the *metric*.

30-second tour: NumPy

```
import numpy as np # np is the universal alias
x = np.array([1, 2, 3, 4]) # 1-D array (a vector)
A = np.array([[1, 2], [3, 4]]) # 2-D array (a matrix)

x.shape # (4,) -- one axis of length 4
A.shape # (2, 2) -- 2 rows, 2 columns
A @ A # @ is the matrix product, not elementwise
np.linalg.inv(A) # inverse -- appears in least squares
np.mean(x), np.std(x) # summaries: centre and spread
```

How to read this

Shapes are what you check first: $(4,)$ is a vector of four numbers, $(2, 2)$ is two rows by two columns. Every design matrix in this course is $n \times p$ (rows = observations, columns = predictors), so an unexpected shape means a transposed matrix, not a broken formula.

30-second tour: pandas

```
import pandas as pd # pd is the universal alias
df = pd.read_csv("Wage.csv") # CSV on disk -> a table in memory

df.shape # (3000, 11) -- n = 3000 rows, 11 columns
df.head() # eyeball the first 5 rows before anything
df["wage"].mean() # a column behaves like a vector
df.groupby("education")["wage"].mean() # does wage differ by group?
df.describe() # count/mean/std/quartiles, all columns
```

Live demo — §1 of the notebook

Read `.shape` first: those two numbers are the n and (almost) the p of the problem. These calls run for real in `chapter_01_lab.ipynb` §1: `Wage.describe(include='all')`. It shows which columns are numeric and which categorical — e.g. mean age 42.4, top education level 2. *HS Grad* (971 of 3 000).

30-second tour: scikit-learn

```
from sklearn.linear_model import LinearRegression

X = df[["age", "year"]].values # design matrix X: n rows, p = 2
y = df["wage"].values # response y: one number per row
model = LinearRegression() # pick the model class (not fitted yet)
model.fit(X, y) # estimate f-hat from the data

print(model.coef_, model.intercept_) # the fitted f-hat, in numbers
yhat = model.predict(X) # apply f-hat: y-hat for every row
```

Every scikit-learn model follows the same fit / predict API.

How to read this

fit is the estimation step, and it prints nothing: it *changes the model object*, storing the estimates in `coef_` and `intercept_` — the underscore marks ‘learned from data’. `predict` reuses them on any `X` with the same p columns.

Outline

- 1 Welcome
- 2 Definitions
- 3 Examples
- 4 Tools
- 5 Datasets**
- 6 Roadmap
- 7 Pitfalls
- 8 Summary

Datasets used throughout the book

ISLP comes with a curated collection of datasets that illustrate every major method.

Takeaway

All accessible via the ISLP Python package, also as CSV files. Most are tabular and modest in size — chosen to run on a laptop in seconds. Outside a textbook no such tidy table exists: it has to be joined together *as of the decision date*, and a field recorded only *after* the decision is the classic leakage bug.

Run this live

Exercise 1.3 (next slides) is worked in Python in `chapter_01_lab.ipynb`, under *Lecture exercises — worked Python solutions*: the cell recomputes every number ($n = 5$, $p = 3$, $x_{2,3} = 82$).

Exercise 1.3 — Notation: n , p , and X [Math]

Exercise

For five patients we record age (yrs), BMI, and resting heart rate HR; the response is systolic blood pressure SBP.

Patient	age	BMI	HR	SBP
1	45	24.0	70	128
2	60	29.5	82	145
3	52	26.1	75	138
4	38	22.3	68	120
5	71	31.0	90	158

- 1 State n and p .
- 2 Give the dimensions of the design matrix X and the response vector y .
- 3 Write the predictor vector x_3 and give the value $x_{2,3}$.
- 4 If an intercept column of ones is added, what are the dimensions of the model matrix?
- 5 Is this a regression or a classification problem?

Solution — Exercise 1.3 (1/2)

Solution

- 1 Count the rows and the predictor columns of the table: $n = 5$ observations (one per patient); $p = 3$ predictors (age, BMI, HR). SBP is the response, *not* a predictor — the variable we model is never counted in p .
- 2 Rows = patients, columns = predictors, so $X \in \mathbb{R}^{5 \times 3}$; stacking the five responses gives $y = (128, 145, 138, 120, 158)^\top \in \mathbb{R}^5$ (a 5×1 column).
- 3 Read off *row* 3 of the table: $x_3 = (52, 26.1, 75)^\top$ — all predictors of patient 3. For $x_{2,3}$ the *first* index is the row (observation), the *second* the column (predictor): predictor 3 (HR) of patient 2, i.e. $x_{2,3} = 82$.

Solution — Exercise 1.3 (2/2)

Solution

- ④ Adding a column of ones gives $\tilde{X} \in \mathbb{R}^{5 \times 4}$: the row count stays at $n = 5$, while the column count grows from $p = 3$ to $p + 1 = 4$ — the extra column of ones multiplies the intercept β_0 in a linear model.
- ⑤ **Regression:** SBP is quantitative (blood pressure in mmHg, on a continuous scale), so regression methods and squared-error loss apply.

Note on indexing: x_{ij} is row i (observation), column j (predictor). Row i is one patient across all predictors; column j is one predictor across all patients.

Common mistake

Reading $x_{2,3}$ column-first as “column 2, row 3”, which would give the BMI of patient 3 (26.1) instead of the correct $x_{2,3} = 82$; and counting the response SBP into p , which would wrongly give $p = 4$.

Outline

- 1 Welcome
- 2 Definitions
- 3 Examples
- 4 Tools
- 5 Datasets
- 6 Roadmap**
- 7 Pitfalls
- 8 Summary

The book in one slide

- Ch. 2 Statistical Learning (foundations)
 - Ch. 3 Linear Regression
 - Ch. 4 Classification (logistic, LDA, QDA, naive Bayes)
 - Ch. 5 Resampling Methods (CV, bootstrap)
 - Ch. 6 Linear Model Selection and Regularisation
 - Ch. 7 Moving Beyond Linearity (splines, GAMs)
 - Ch. 8 Tree-Based Methods (CART, RF, boosting, BART)
 - Ch. 9 Support Vector Machines — *Advanced module*
 - Ch. 10 Deep Learning
 - Ch. 11 Survival Analysis and Censored Data — *Advanced module*
 - Ch. 12 Unsupervised Learning (PCA, clustering) — *Advanced module*
 - Ch. 13 Multiple Testing — *Advanced module*
-

The four modules marked *Advanced* are not taught in the nine sessions — they sit in Chapters/Advanced/ as optional self-study decks.

The narrative arc

- Chapters 2–4 establish the *vocabulary* and *baseline* methods (regression and classification).
- Chapter 5 teaches you how to *honestly evaluate* models.
- Chapter 6 takes the linear model beyond OLS (subset selection, ridge, lasso).
- Chapters 7–10 add increasing flexibility: nonlinear, trees, SVMs, deep nets.
- Chapter 11 specialises to time-to-event data.
- Chapter 12 returns to unsupervised problems — an optional Advanced module, and the natural sequel to this chapter's NCI60 example.
- Chapter 13 reasons about many simultaneous tests.

Takeaway

The arc: build *vocabulary* and baseline methods, learn to *evaluate honestly*, then add *flexibility* step by step before specialising.

Extended Exercise 1.1 — Anatomy of a loan-default study [Integrative]

Extended exercise (15 min)

A regional bank has records on **20,000** past personal-loan customers. For each it stored: annual income, current debt, credit-utilisation ratio, `loan_amount` requested, `employment_length` (yrs), number of prior `late_payments`, and `home_ownership` (own/rent/mortgage). For every past customer it also knows whether they eventually defaulted (Yes/No). The bank wants to **(a)** flag which *new* applicants are likely to default, and **(b)** understand *which* factors drive default and *by how much*, to justify decisions to a regulator.

- 1 Identify the response Y and the predictors; state n and p .
- 2 Regression or classification? Supervised or unsupervised? Justify each.
- 3 Which of goals (a) and (b) is *prediction* and which is *inference*?
- 4 Write the model $Y = f(X) + \varepsilon$. What does the irreducible error ε represent *here*? Give two concrete sources.
- 5 Sketch a sensible end-to-end workflow, and say which model family suits goal (b) given the regulator.

Solution — Extended Exercise 1.1 (1/2)

Solution

- 1. Response, predictors, n , p .** The response is $Y = \text{defaulted}$ (Yes/No). The predictors are the seven recorded features (income, debt, utilisation, loan_amount, employment_length, late_payments, home_ownership), so $p = 7$ and $n = 20,000$. Nuance: home_ownership has 3 levels — as *one* predictor $p = 7$, but dummy-encoding turns it into 2 columns, so the model matrix (with an intercept) has $6+2+1 = 9$ columns.
- 2. Problem type / supervision.** Y is qualitative (binary) $\Rightarrow$ a **classification** problem — the type of Y decides, not the predictors. Because every training customer carries a *label* defaulted, this is **supervised** learning.
- 3. Prediction vs. inference.** Goal (a), flagging new applicants, is **prediction**: we only need an accurate $\hat{Y}$. Goal (b), which factors matter and by how much for a regulator, is **inference**: we need the structure of f — signed, quantified effects.

Common mistake

Counting the response defaulted among the predictors (giving $p = 8$) — the response is never a column of X .

Solution — Extended Exercise 1.1 (2/2)

Solution

4. Model and irreducible error. We posit $Y = f(X) + \varepsilon$ with $E[\varepsilon] = 0$: f is the systematic part of default risk explained by the seven features; ε is everything they *cannot* explain. Here ε absorbs (i) *post-application life events* — a later job loss, illness, or divorce that no application-time feature can foresee; and (ii) *unmeasured or random factors* — a local recession, fraud, or plain chance. Even the *true* f cannot beat this noise floor $\text{Var}(\varepsilon)$; for a Yes/No response its analogue is the Bayes error rate (Ch. 2).

5. A sensible workflow.

- 1 Assemble clean labelled data; *avoid leakage* (no post-outcome fields).
- 2 Split into train / test (or cross-validate); lock the test set away.
- 3 Preprocess: dummy-encode `home_ownership`, impute missing values, *standardise* numeric predictors.
- 4 For goal (b) use an **interpretable** model — *logistic regression* gives signed coefficients / odds ratios with confidence intervals a regulator can read; optionally add a flexible model (random forest) to gauge attainable accuracy for goal (a).
- 5 Evaluate on held-out data with a metric fit for *imbalanced* classes (ROC-AUC, precision/recall, or a cost-weighted error), not raw accuracy, and pick by cross-validated performance.

Outline

- 1 Welcome
- 2 Definitions
- 3 Examples
- 4 Tools
- 5 Datasets
- 6 Roadmap
- 7 Pitfalls**
- 8 Summary

Pitfalls to remember from day one

The classic mistakes

- 1 Reporting training error and calling it “performance”.
- 2 Ignoring data quality (selection bias, leakage, label noise).
- 3 Reading univariate associations as causal effects.
- 4 Forgetting to standardise features for distance-based methods.
- 5 Treating p -values as truth instead of evidence (Ch. 13).
- 6 Re-using the test set during model selection.

The two that kill whole projects

Training on a population different from the one you will score, and shipping a score nobody can explain to the person who has to act on it.

Self-check questions

- 1 In your own words, what is the difference between *prediction* and *inference*? Give one example of each. (p. 20)
- 2 Which of the three motivating data sets (Wage, Smarket, NCI60) would benefit most from a flexible method, and why? (p. 38)
- 3 For the Boston housing data ($n = 506$, $p = 12$), what regime are we in: low-dimensional or high-dimensional? Explain. (pp. 36 and 40)
- 4 Write the design matrix X for $n = 4$ observations of $p = 2$ predictors plus an intercept. (pp. 54–55)

Get hands-on: the companion lab notebook

Companion notebook: `chapter_01_lab.ipynb`

These datasets are explored in the companion Jupyter notebook. Open it and run it cell by cell:

- §1 *The Wage data* — reproducing Fig. 1.1;
- §2 *The Stock Market data* — *Smarket* (Fig. 1.2);
- §3 *The NCI60 cancer cell lines*;
- §4 *The three problem types, side by side* — n , p and p/n in one table.

Data loads via the ISLP package or the bundled CSV files; the notebook ends with hands-on exercises.

Outline

- 1 Welcome
- 2 Definitions
- 3 Examples
- 4 Tools
- 5 Datasets
- 6 Roadmap
- 7 Pitfalls
- 8 Summary**

Chapter 1 in one slide

What we accomplished

Established the *vocabulary*, *problem types*, and *tools* of statistical learning.

- Defined supervised vs. unsupervised, regression vs. classification.
- Walked through three motivating examples.
- Set up the standard notation and Python tooling.
- Surveyed the data sets we will see throughout the course.

Key formulas and notation at a glance

Data n observations, p predictors; design matrix $X \in \mathbb{R}^{n \times p}$, response $y \in \mathbb{R}^n$.

Supervised model $Y = f(X) + \varepsilon$, with f unknown and $E[\varepsilon] = 0$.

Two goals *Prediction*: $\hat{Y} = \hat{f}(X)$. *Inference*: understand the shape of f .

Response type *Regression* (Y quantitative) vs. *classification* (Y qualitative).

Error reducible (improve $\hat{f}$) vs. irreducible ($\text{Var}(\varepsilon) = \sigma^2$).

Supervision *supervised* (labels y available) vs. *unsupervised* (no y).

Vocabulary checklist

Term	Meaning
Statistical learning	Tools for understanding data
Supervised / unsupervised	With / without a response Y
Regression / classification	Y quantitative / qualitative
Prediction / inference	Forecast Y / explain how Y depends on X
Predictor / response	X_j / Y
Training / test set	Data used to fit / evaluate

Ten things to remember from Chapter 1

- 1 Statistical learning = tools for understanding data.
- 2 Two families: supervised and unsupervised.
- 3 Two flavours of supervised: regression and classification.
- 4 Two questions: prediction and inference.
- 5 The Wage example: regression, mostly inference.
- 6 The Smarket example: classification, very weak signal.
- 7 The NCI60 example: unsupervised structure discovery.
- 8 Notation: n obs., p predictors, X , y .
- 9 Tools: NumPy, pandas, scikit-learn, ISLP.
- 10 Always validate on data you did not train on.

What's next

Chapter 2: *Statistical Learning — the foundations.*

- Define the unknown function f .
- Distinguish parametric from nonparametric methods.
- Decompose prediction error into bias and variance.
- Meet our first concrete classifier: K -nearest neighbours.


Appendix — what is in here, and why

Nothing in the appendix is needed to follow the chapter: each slide is a formal derivation, a longer worked exercise, or a side topic. Read it when you want the full story, or when a later chapter sends you back here.

Contents of the appendix

- **The two recreated overview figures** — Wage close up and the Smarket lag boxplots, computed from the raw data. The main deck teaches from the ISLP originals; these show the same pictures can be rebuilt in a dozen lines.
- **The design matrix in full** — the anatomy of X and y drawn out entry by entry, and the notation for estimates. The one-slide version in the main deck (“Notation: n , p , and the design matrix”) is all the chapter needs.
- **The dataset catalogue** — the two reference tables of every ISLP data set. Look them up when a lab asks for a data set you have not met.


Wage data up close: age, year, and education



Takeaway

Wage rises then dips with age (nonlinear), drifts gently upward over the years (linear), and climbs steeply with education.

Recreating Figure 1.2 from the raw Smarket data



Takeaway

Median Lag1 from `Smarket.csv`: +0.10 % before Down days vs. -0.05 % before Up days — a 0.15-point gap against boxes spanning ± 0.6 %. Yesterday's return barely separates the classes: market prediction is hard.

The design matrix


Stack the predictor vectors as rows:

$$\mathbf{X} = \begin{pmatrix} x_{11} & x_{12} & \cdots & x_{1p} \\ x_{21} & x_{22} & \cdots & x_{2p} \\ \vdots & \vdots & \ddots & \vdots \\ x_{n1} & x_{n2} & \cdots & x_{np} \end{pmatrix} \in \mathbb{R}^{n \times p}.$$

How to read this

- Row i : vector $\mathbf{x}_i = (x_{i1}, \dots, x_{ip})^\top$ — one observation, all predictors.
- Column j : vector $\mathbf{x}_j$ — all observations, one predictor.
- x_{ij} : value of the j -th predictor for the i -th observation.

Anatomy of the data: the matrix X and the vector y



Takeaway

A **row** is one observation x_i (all predictors); a **column** is one predictor across all observations; x_{ij} sits at row i , column j . Supervised learning pairs each row of X with its response y_i .

The response and estimates

Response vector

$$\mathbf{y} = (y_1, y_2, \dots, y_n)^\top \in \mathbb{R}^n.$$

The hat convention

Estimated quantities wear a hat: $\hat{\beta}, \hat{f}, \hat{y}$. The hat reminds us that these are computed from a sample and therefore have sampling variability.

Common usage

Predicted (fitted) values: $\hat{y}_i$.

Residuals: $e_i = y_i - \hat{y}_i$.

Train vs. test: subscripts tr and te .

Datasets at a glance (1/2)

Name	n	p	Response	Used in
Wage	3000	10	wage (num.)	Ch. 1, 7
Smarket	1250	8	Direction (binary)	Ch. 1, 4
NCI60	64	6830	— (unsup.)	Ch. 1, 12 [†]
Auto	392	8	mpg (num.)	Ch. 3
Boston	506	12	medv (num.)	Ch. 3, 8
Carseats	400	10	Sales (num.)	Ch. 3, 8
Credit	400	10	Balance (num.)	Ch. 3, 6
Default	10000	3	default (binary)	Ch. 4
Heart	303	13	AHD (binary)	Ch. 4, 8

[†] optional Advanced self-study module.

Datasets at a glance (2/2)

Name	n	p	Response	Used in
Caravan	5822	85	Purchase (binary)	Ch. 4
OJ	1070	17	Purchase (binary)	Ch. 8, 9 [†]
Hitters	322	19	Salary (num.)	Ch. 6, 8
College	777	17	Apps (num.)	Ch. 6
BrainCancer	88	8	survival	Ch. 11 [†]
USArrests	50	4	— (unsup.)	Ch. 12 [†]
Bikeshare	8645	14	bikers (num.)	Ch. 4

† optional Advanced self-study module.