

Quantitative Research Methods

Chapter 0b: Precourse Toolkit

Prof. Dr. Christoph Weisser

The course at a glance

Chapter	Topic
Ch. 0 + 0b	Statistics refresher and the toolkit — one taught session
Ch. 1	Introduction
Ch. 2	Statistical learning — accuracy, bias–variance, Bayes classifier, KNN
Ch. 3	Linear regression — estimation, inference, diagnostics
Ch. 4	Classification — logistic regression, confusion matrix, ROC
Ch. 5	Resampling — validation, CV, bootstrap
Ch. 6	Model selection and regularisation — ridge, lasso
Ch. 7	Moving beyond linearity — splines, GAMs
Ch. 8	Tree-based methods — trees, forests, boosting
Ch. 10	Deep learning — MLPs, CNNs, training

The precourse is taught in one 180-minute session drawing on both decks, before Chapter 1; the nine chapter decks follow. It assumes nothing beyond an introductory undergraduate course. Today's session is highlighted.

Support vector machines (Ch. 9), survival analysis (Ch. 11), multiple testing (Ch. 13) and unsupervised learning (Ch. 12) are optional self-study modules in Chapters/Advanced/.

Contents

- 1 Reading mathematical notation
- 2 Logs, exponentials and growth
- 3 Probability, odds and the logit
- 4 Likelihood and maximum likelihood
- 5 The Python you will actually write
- 6 Summary

Optional and advanced material is collected in the **appendix** at the end of the deck.

Why this second session exists

These five topics were counted in the nine chapter decks. Each is used *heavily* and explained *nowhere* — the chapters assume you already read them fluently.

Topic	Where it bites	Uses
log and exp	Ch. 4 (113), Ch. 10 (31), Ch. 6 (16)	176
odds and the logit	Ch. 4 (92), Ch. 10 (12)	108
likelihood and $\prod$	Ch. 4 (35), Ch. 2–3	37
$\sum$, arg max, indicator, set notation	every chapter from Ch. 2	180
counting and 2^P cost	Ch. 6 (subset selection)	13

The claim

None of this is hard. All of it is *unfamiliar notation for familiar ideas* — and unfamiliar notation is what makes a lecture feel impossible to follow.

Notation introduced in this session

Symbol	Meaning
$\sum_{i=1}^n a_i$	add up $a_1, \dots, a_n$
$\prod_{i=1}^n a_i$	multiply $a_1, \dots, a_n$
$\arg \min_{\theta} f(\theta)$	the <i>value of</i> θ that makes f smallest
$I(\text{condition})$	1 if the condition holds, 0 otherwise
$x \in \mathcal{S}, \mathcal{S} $	x is in the set $\mathcal{S}$; the size of $\mathcal{S}$
$\log, \exp$	natural logarithm (base e) and its inverse e^x
$\text{odds} = \frac{p}{1-p}$	how much more likely than not
$\text{logit}(p) = \log \frac{p}{1-p}$	log-odds: a probability on an unbounded scale
$\sigma(z) = \frac{1}{1+e^{-z}}$	the logistic (sigmoid) function; the inverse of the logit
$L(\theta), \ell(\theta)$	likelihood and log-likelihood of the parameter θ
$\hat{\theta}_{\text{MLE}}$	the value of θ that maximises the likelihood
$\binom{p}{k}$	the number of ways of choosing k items from p
2^p	the number of subsets of p predictors: how the cost grows

Learning objectives for this session

By the end you will be able to:

- **Read aloud** any formula in the course: sums, products, arg max, indicators, subscripts and set notation.
- **Manipulate** logs and exponentials, and explain what a coefficient means when the response is logged.
- **Convert** freely between probability, odds and log-odds, and explain why classification models work on the logit scale.
- **Write down** a likelihood, take its log, and explain what maximum likelihood chooses — and why it coincides with least squares under normal errors.
- **Count** models and explain why 2^p makes exhaustive search hopeless.
- **Write** the Python the labs actually use: functions, loops, comprehensions, seeds, and the fit/predict pattern.

Outline

- 1 Reading mathematical notation
- 2 Logs, exponentials and growth
- 3 Probability, odds and the logit
- 4 Likelihood and maximum likelihood
- 5 The Python you will actually write
- 6 Summary

The anatomy of a formula

... and stop at $i = n$

do this to every observation

$$\text{RSS} = \sum_{i=1}^n (y_i - \hat{y}_i)^2$$

start at $i = 1$

square it, so sign does not matter

How to read any formula

Read it as an *instruction*, left to right: “for each observation, take the gap between what happened and what we predicted, square it, and add those up”. A formula is a recipe, not a hieroglyph.

Sums and products

The two operators that appear everywhere

$$\sum_{i=1}^n a_i = a_1 + a_2 + \cdots + a_n, \quad \prod_{i=1}^n a_i = a_1 \times a_2 \times \cdots \times a_n.$$

With numbers

For $a = (2, 5, 3)$: $\sum_i a_i = 10$ and $\prod_i a_i = 30$. In Python: `a.sum()` and `a.prod()`.

Rules worth knowing

$$\sum_i (a_i + b_i) = \sum_i a_i + \sum_i b_i, \quad \sum_i c a_i = c \sum_i a_i, \quad \sum_{i=1}^n c = nc.$$

The one that is *not* a rule

$\sum_i a_i b_i \neq (\sum_i a_i)(\sum_i b_i)$, and $\sum_i a_i^2 \neq (\sum_i a_i)^2$.

arg min, arg max and the indicator

min versus arg min

$\min_{\theta} f(\theta)$ is the smallest *value* of f ; $\arg \min_{\theta} f(\theta)$ is the θ *that achieves it*.

$$f(\theta) = (\theta - 3)^2 + 5 \implies \min_{\theta} f = 5, \quad \arg \min_{\theta} f = 3.$$

Estimation is always an arg min (of a loss) or an arg max (of a likelihood): we want the *parameter*, not the value of the criterion.

The indicator function

$$I(\text{condition}) = \begin{cases} 1 & \text{if the condition is true,} \\ 0 & \text{otherwise.} \end{cases}$$

It turns counting into arithmetic. The classification error rate is

$$\frac{1}{n} \sum_{i=1}^n I(y_i \neq \hat{y}_i) \quad \text{— “the fraction of observations we got wrong”}.$$

Sets, subscripts and the notation of a data set

Sets

$x \in \mathcal{S}$ means “ x belongs to $\mathcal{S}$ ”; $|\mathcal{S}|$ is the number of elements in $\mathcal{S}$. In Chapter 8, R_j is the set of observations falling in region j of a tree, and $\frac{1}{|R_j|} \sum_{i \in R_j} y_i$ is just “the mean response of the points in that box”.

Subscripts and superscripts

x_{ij}	observation i , variable j (row first, then column)
x_i	the whole i -th row (a vector of p numbers)
β_j	the coefficient belonging to variable j
$\hat{y}_i^{(-i)}$	prediction for i from a model fitted <i>without</i> i
α^{*b}	the estimate from bootstrap sample b (a label, not a power)

Read the superscript before you square it

In Chapter 5, $\hat{\alpha}^{*b}$ is “the estimate from resample b ”. A superscript is often an *index*, not an exponent — context decides.

Exercise 0b.1 — Translating notation [Math]

Exercise

Let $y = (3, 1, 4)$ and $\hat{y} = (2, 2, 4)$, so $n = 3$.

- 1 Write $\sum_{i=1}^3 (y_i - \hat{y}_i)^2$ in words, then compute it.
- 2 Compute $\frac{1}{n} \sum_{i=1}^n I(y_i \neq \hat{y}_i)$ and say what it measures.
- 3 For $g(\theta) = (\theta - 4)^2 + 7$, give $\min_{\theta} g$ and $\arg \min_{\theta} g$.
- 4 Let $\mathcal{S} = \{i : y_i > 2\}$. List $\mathcal{S}$, give $|\mathcal{S}|$, and compute $\frac{1}{|\mathcal{S}|} \sum_{i \in \mathcal{S}} y_i$.
- 5 Is $\sum_i (y_i - \hat{y}_i)^2$ the same as $(\sum_i (y_i - \hat{y}_i))^2$? Check with these numbers.

Live demo — §1 of the notebook

After solving by hand, run `chapter_00b_1lab.ipynb` §1: its notation cells compute this exact data — RSS 2.0, error rate 0.667, $|\mathcal{S}| = 2$ with mean 3.5 — each in one line of numpy.

Solution — Exercise 0b.1 (1/2)

Solution

- (1) “For each of the three observations, subtract the prediction from the observation, square the result, and add the three numbers.” Differences: 1, -1 , 0; squares 1, 1, 0; total 2.
- (2) The indicator is 1 for observations 1 and 2 (where $y_i \neq \hat{y}_i$) and 0 for the third, so the average is $2/3 \approx 0.67$: *the fraction of predictions that are wrong* — the misclassification rate of Chapters 2 and 4.

Solution — Exercise 0b.1 (2/2)

Solution

(3) A square is never negative, so g is smallest when $(\theta - 4)^2 = 0$. Hence $\arg \min_{\theta} g = 4$ and $\min_{\theta} g = 7$. Note the two answers are different objects: one is a parameter, the other a loss value.

(4) $\mathcal{S} = \{1, 3\}$ (observations with $y_i > 2$), so $|\mathcal{S}| = 2$ and the mean over the set is $(3 + 4)/2 = 3.5$. This is exactly the calculation a regression tree does inside one leaf.

(5) No. Here $\sum_i (y_i - \hat{y}_i)^2 = 2$ but $(\sum_i (y_i - \hat{y}_i))^2 = (1 - 1 + 0)^2 = 0$. Squaring first keeps the errors from cancelling — which is the whole reason least squares squares.


Common mistake

Writing min when arg min is meant. Every estimator ahead is an arg min: $\hat{\beta}$ is the *coefficient value* that minimises RSS, never the RSS value itself.

Outline

- 1 Reading mathematical notation
- 2 Logs, exponentials and growth**
- 3 Probability, odds and the logit
- 4 Likelihood and maximum likelihood
- 5 The Python you will actually write
- 6 Summary

The two functions Chapter 4 is written in



The rules, all of them

$$\begin{aligned} \log(ab) &= \log a + \log b, & \log(a/b) &= \log a - \log b, & \log(a^k) &= k \log a, \\ \log 1 &= 0, & \log e &= 1, & e^{\log a} &= a, & \log(e^x) &= x, & e^{a+b} &= e^a e^b. \end{aligned}$$

“log” in this course always means the *natural* logarithm, base $e \approx 2.718$ — what `np.log` computes.

Why logs are everywhere in statistics


Three jobs a log does

- 1 **Turns multiplying into adding.** A likelihood is a product over n observations; its log is a sum, which we can differentiate. (Next section.)
- 2 **Turns unbounded ratios into a symmetric scale.** Odds run from 0 to ∞ ; log-odds run from $-\infty$ to ∞ . (Section after that.)
- 3 **Tames skew and turns effects into percentages.** A right tail is compressed, and a coefficient on $\log y$ reads as a *relative* change — in a log-log demand model the slope *is* the price elasticity.

Numerical underflow — the practical reason

A likelihood multiplies n probabilities. With $n = 1000$ and each around 0.5, the product is $\approx 10^{-301}$, close to the smallest number a computer can store; at $n = 2000$ it underflows to zero and every model looks equally good. Its log ≈ -693 is perfectly ordinary.

A log scale can straighten a relationship



Boston: median house value against the share of lower-status population. On the raw scale the cloud curves and $r = -0.74$; after logging the response it is close to straight, and $r = -0.81$.

How to read a logged coefficient

In $\log y = \beta_0 + \beta_1 x$, a one-unit rise in x multiplies y by e^{β_1} . For small β_1 , that is roughly a $100\beta_1\%$ change: $\beta_1 = -0.05$ means “about 5% lower”.

Exercise 0b.2 — Logs in practice [Math]

Exercise

- 1 Simplify $\log(x^3y) - \log(y)$ and $\log(e^{2x})$.
- 2 Solve $e^{0.4t} = 5$ for t .
- 3 A model gives $\log(\text{wage}) = 2.1 + 0.08 \text{educ}$. By what factor does an extra year of education multiply the wage? Express it as a percentage.
- 4 Prices rise 3% a year. Write the price after t years, take logs, and say why the log of the price is a straight line in t .
- 5 Why can you not take the log of a variable that contains zeros, and what do people do instead?

Live demo — §2 of the notebook

Run `chapter_00b_lab.ipynb` §2 alongside: it checks part (2) numerically ($t = \log 5 / 0.4 = 4.024$) and shows logging Boston's `medv` move r from -0.74 to -0.81 .

Solution — Exercise 0b.2 (1/2)

Solution

- (1) $\log(x^3y) - \log y = \log x^3 + \log y - \log y = 3 \log x$. And $\log(e^{2x}) = 2x$, since log and exp undo each other.
- (2) Take logs of both sides: $0.4t = \log 5 = 1.609$, so $t = 1.609/0.4 = 4.02$.
- (3) An extra year adds 0.08 to $\log(\text{wage})$, so it multiplies the wage by $e^{0.08} = 1.083$: about +8.3%. Note the shortcut “0.08 $\rightarrow$ 8%” is an approximation that is good for small coefficients and poor for large ones ($e^{0.5} = 1.65$, not 1.5).

Solution — Exercise 0b.2 (2/2)

Solution

(4) $P_t = P_0(1.03)^t$, so $\log P_t = \log P_0 + t \log(1.03) = \log P_0 + 0.0296 t$. Constant *growth rates* are straight lines on a log scale — which is why growth data are always plotted that way.

(5) $\log 0 = -\infty$ (and logs of negatives are undefined), so a single zero destroys the column. Common fixes: model $\log(y + 1)$; use a square root instead; or — best — use a model built for the data type, such as the Poisson regression of Chapter 4 for counts.

Common mistake

Inventing a rule for sums. $\log(a + b)$ simplifies to nothing — the log rules turn *products* into sums; there is no rule for the log of a sum.

Outline

- 1 Reading mathematical notation
- 2 Logs, exponentials and growth
- 3 Probability, odds and the logit
- 4 Likelihood and maximum likelihood
- 5 The Python you will actually write
- 6 Summary

Three ways to say the same thing

Definitions


$$\text{odds} = \frac{p}{1-p}, \quad \text{logit}(p) = \log \frac{p}{1-p}, \quad p = \sigma(z) = \frac{1}{1+e^{-z}}.$$

probability	odds	log-odds	said aloud
0.10	0.11	-2.20	"1 to 9 against"
0.25	0.33	-1.10	"1 to 3 against"
0.50	1.00	0.00	"evens"
0.75	3.00	+1.10	"3 to 1 on"
0.90	9.00	+2.20	"9 to 1 on"

Why the log-odds scale

Probabilities are squeezed against 0 and 1; log-odds run from $-\infty$ to $+\infty$, symmetrically about zero. Models work on the log-odds scale because it has *room*: whatever number a linear predictor produces is a legal log-odds.

Why Chapter 4 cannot just fit a straight line



Default ($n = 10\,000$, 3.3% default). The dashed line is ordinary least squares on a 0/1 response: it predicts *negative* probabilities for small balances and would exceed 1 eventually. The logistic curve cannot.

The one-line summary of logistic regression

Model the *log-odds* as linear: $\log \frac{p(x)}{1-p(x)} = \beta_0 + \beta_1 x$, then convert back with σ . That is the whole idea; Chapter 4 fills in the details.

Exercise 0b.3 — Odds and odds ratios [Math]

Exercise

In a promotion study, 45% of customers who received a voucher bought something, against 25% of those who did not.

- 1 Compute the odds of buying in each group.
- 2 Compute the **odds ratio** (voucher vs. no voucher) and state in words what it says.
- 3 Compute the log-odds in each group, and check that their difference equals the log of the odds ratio.
- 4 A logistic model reports a coefficient of 0.90 for the voucher dummy. Convert it to an odds ratio.
- 5 If the log-odds of an outcome are -1.4 , what is the probability?

Live demo — §3 of the notebook

Run `chapter_00b_lab.ipynb` §3: `odds()`, `logit()` and `sigmoid()` rebuild the conversion table, and the worked cell under *Lecture exercises* verifies every part of this exercise.

Solution — Exercise 0b.3 (1/2)

Solution

(1) Voucher: $0.45/0.55 = 0.818$. No voucher: $0.25/0.75 = 0.333$.

(2) Odds ratio = $0.818/0.333 = 2.45$: the *odds* of buying are about two and a half times higher with a voucher. Note this is not “2.45 times as likely” — the ratio of *probabilities* is only $0.45/0.25 = 1.8$. Odds ratios and risk ratios are different numbers, and confusing them overstates effects.

Solution — Exercise 0b.3 (2/2)

Solution

(3) $\log 0.818 = -0.201$ and $\log 0.333 = -1.099$; the difference is $0.898 = \log(2.45) \checkmark$.
Differences on the log-odds scale are ratios on the odds scale — which is exactly what a logistic coefficient is.

(4) $e^{0.90} = 2.46$ — the same odds ratio, as it must be: the coefficient of a dummy *is* the log odds ratio.

(5) $p = \sigma(-1.4) = 1/(1 + e^{1.4}) = 1/(1 + 4.055) = 0.198$, about 20%.

Common mistake

Reading odds as probabilities. Odds of 0.818 do not mean “82%” — convert back with $p = \text{odds}/(1 + \text{odds}) = 0.45$.

Outline

- 1 Reading mathematical notation
- 2 Logs, exponentials and growth
- 3 Probability, odds and the logit
- 4 Likelihood and maximum likelihood**
- 5 The Python you will actually write
- 6 Summary

The idea in one sentence

Maximum likelihood

Among all parameter values, choose the one that makes the data you actually observed *most probable*.

The likelihood function


For independent observations $y_1, \dots, y_n$ with parameter θ ,

$$L(\theta) = \prod_{i=1}^n P(y_i \mid \theta), \quad \ell(\theta) = \log L(\theta) = \sum_{i=1}^n \log P(y_i \mid \theta).$$

Read the direction of the conditioning

$P(y_i \mid \theta)$ is a probability *of the data given a parameter*. As a function of θ with the data *fixed*, we call it a likelihood — and it is **not** a probability distribution over θ . That is the commonest misunderstanding here.

A coin, worked end to end



Seven heads in ten tosses. The likelihood $L(\pi) = \binom{10}{7} \pi^7 (1 - \pi)^3$ peaks at $\hat{\pi} = 0.7$; the log-likelihood peaks in the same place, because log is increasing.

Why we always maximise the log

Same answer, easier algebra (sums, not products), and no numerical underflow. Every “log-likelihood” in Chapters 4, 6 and 10 is this.


Maximum likelihood outside the classroom

Least squares is the special case, not the rule. Claim frequency and severity models, probability-of-default models and demand models are nearly all fitted by maximum likelihood instead — because the response is a count, a 0/1 event, or a skewed positive amount, and none of those has normal errors. Durations behave the same way: a retention curve falls away roughly exponentially, so the log of the share still active is close to linear in time, and fitting on that scale returns the expected customer lifetime.

What one principle buys

The same estimation idea covers continuous responses, classes, counts and durations — which is why Chapters 4, 6 and 10 all report a log-likelihood instead of an R^2 .

The price of a probability: $-\log \hat{p}$



Takeaway

Maximising the log-likelihood means paying $-\log \hat{p}$ for the probability you gave what actually happened: hedging at 0.5 costs 0.69, confident-and-wrong costs without bound. This curve is the loss of logistic regression (Ch. 4) and of cross-entropy (Ch. 10).

Exercise 0b.4 — What a likelihood is and is not [Concept]

Exercise

Decide whether each statement is correct, and correct the ones that are not.

- 1 “The likelihood that $\pi = 0.7$ is 0.27, so there is a 27% chance the true value is 0.7.”
- 2 “The maximum-likelihood estimate is the most probable value of the parameter.”
- 3 “Adding an observation always lowers the likelihood.”
- 4 “Maximising the likelihood and maximising the log-likelihood can give different answers.”
- 5 “A model with a higher log-likelihood always predicts new data better.”

Live demo — §4 of the notebook

Run `chapter_00b_lab.ipynb` §4 alongside: the coin cells show L and ℓ peaking at the same $\hat{\pi} = 0.699$ (statement 4 settled by machine), and `scipy` recovers $\hat{\pi} = 0.0333$ on Default.

Solution — Exercise 0b.4

Solution

- (1) **Wrong.** A likelihood is a probability of the *data*, computed *given* a parameter value — not a probability of the parameter. Likelihoods need not sum or integrate to 1 over π , so “27% chance” is meaningless here. (Turning it into a statement about π requires a prior and Bayes’ theorem.)
- (2) **Wrong, in the same way.** It is the value *under which the observed data are most probable*. The distinction matters exactly when someone asks “how sure are you?” — that question is answered by a standard error or an interval, not by the likelihood’s height.
- (3) **Correct for discrete data.** Each extra observation multiplies in another probability ≤ 1 , so L shrinks; for a continuous response the factors are densities and can exceed 1. Only *comparisons at the same data set* are meaningful — which is why you can never compare log-likelihoods across samples of different size.
- (4) **Wrong.** log is strictly increasing, so it preserves the location of the maximum. The maximiser is identical; only the value differs.
- (5) **Wrong.** Likelihood is measured on the *training* data, and a more flexible model can always be made to fit it better — overfitting. That is precisely why Chapter 6 penalises the log-likelihood (AIC, BIC) and Chapter 5 measures performance on held-out data instead.

Common mistake: the root of (1), (2) and (4) is one flipped conditioning: L is the probability of *this data* given π , never of π given the data. Keep that direction straight and the statements sort themselves.

Outline

- 1 Reading mathematical notation
- 2 Logs, exponentials and growth
- 3 Probability, odds and the logit
- 4 Likelihood and maximum likelihood
- 5 The Python you will actually write
- 6 Summary

Functions and loops — used in all fifteen labs

```
def rmse(y, y_hat): # define once, reuse everywhere
    """Root mean squared error.""" # what help(rmse) shows
    return np.sqrt(np.mean((y - y_hat) ** 2)) # the value handed back

scores = [] # accumulate results in a list
for degree in range(1, 6): # range(1, 6) -> 1, 2, 3, 4, 5
    fit = np.polyfit(x_train, y_train, degree) # fit on train data only
    scores.append(rmse(y_test, np.polyval(fit, x_test))) # test error

best = int(np.argmin(scores)) + 1 # argmin: position 0 -> degree 1
print(f"best degree: {best} (RMSE {min(scores):.3f})") # {} filled in
```

The pattern behind every tuning experiment

Define a scoring function; loop over candidate settings; store each score; take the `argmin`. Chapters 5–8 change what happens inside the loop, never the shape of it.

Four idioms worth ten minutes each

```
squares = [d ** 2 for d in range(5)] # a loop that fills a list
mask = df["balance"] > 1000 # True/False for each row
df.loc[mask, "income"].mean() # mean income where True

for name, group in df.groupby("education"): # one loop pass per level
    print(name, group["wage"].median()) # median wage per group

for ax, col in zip(axes.ravel(), columns): # pairs panel with column
    ax.hist(df[col]) # one histogram per panel
```

Two things that will bite you

- ❶ **Indexing starts at 0**, and `range(1, 6)` *excludes* 6. Off-by-one errors are the most common lab bug.
- ❷ **Chained assignment**: `df[df.x > 1]["y"] = 0` silently does nothing. Use `df.loc[df.x > 1, "y"] = 0` — the `.loc` above: rows and column in one bracket.

Randomness, seeds and reproducibility

```
rng = np.random.default_rng(2024) # ONE generator, seeded once
sample = rng.choice(data, size=100) # same 100 draws on every run

from sklearn.model_selection import train_test_split # the split helper
X_tr, X_te, y_tr, y_te = train_test_split(X, y, test_size=0.3,
                                          random_state=42) # same split
```

Every model in this course is scored on data it has never seen



A “random” generator is a deterministic recipe and the seed is where it starts, so the same seed replays the same draws — which is why your numbers match the slides. Change the seed and the third decimal moves: not a bug, but sampling variability, which Chapter 5 is about measuring. `test_size=0.3` sets aside 30% of the rows as the test set.

The scikit-learn contract: fit, predict, score

```
from sklearn.linear_model import LinearRegression # the model class
from sklearn.metrics import mean_squared_error # a scoring rule

model = LinearRegression() # 1. choose a model (empty)
model.fit(X_train, y_train) # 2. learn from TRAINING data only
pred = model.predict(X_test) # 3. predict on unseen data
mean_squared_error(y_test, pred) # 4. score honestly
model.coef_, model.intercept_ # what fit() stored; note the _
```

Learn it once and you know every model in the course

Trees, forests, boosting, SVMs and neural nets use the same three methods: swapping `LinearRegression()` for `RandomForestRegressor()` changes one line.

The cardinal sin

Never call `fit` on the test set — not for the model, and not for a scaler either (Chapter 5).

Exercise 0b.6 — Reading and fixing code [Python]

Exercise — a student writes this to compare polynomial degrees

```
scores = []  
for degree in range(1, 5):  
    fit = np.polyfit(x, y, degree) # (a)  
    scores.append(rmse(y, np.polyval(fit, x))) # (b)  
best = np.argmin(scores) # (c)  
print("best degree:", best)
```

- 1 Which degrees are actually tried?
- 2 Line (c) prints 3. Why is that answer wrong, and what is the correct degree?
- 3 Lines (a) and (b) use the same data. How will scores behave as the degree rises, and why is the comparison meaningless?
- 4 Rewrite the loop so the comparison is honest. Name the one function you need.
- 5 Why should the code set a seed?

Run this live

Worked solution: `chapter_00b_lab.ipynb`, *Lecture exercises — worked Python solutions*, cell *Exercise 0b.6 — Reading and fixing code [Python]*.

Solution — Exercise 0b.6

Solution

- (1) `range(1, 5)` yields 1, 2, 3, 4 — the upper limit is *excluded*. Degree 5 is never tried.
- (2) `np.argmin` returns a *position*, and positions start at 0. Position 3 is the fourth entry, i.e. degree 4. The fix is `best = np.argmin(scores) + 1`, or better, store the degrees alongside the scores.
- (3) The model is scored on the same data it was fitted to, so the RMSE can only fall as the degree rises — a high enough polynomial passes through every point and scores 0. The loop therefore always “discovers” the most complex model. This is overfitting, the central problem of Chapter 2.
- (4) Split first, fit on training data, score on test data:

```
X_tr, X_te, y_tr, y_te = train_test_split(x, y, test_size=.3, random_state=42)
for degree in range(1, 6): # now all five degrees
    fit = np.polyfit(X_tr, y_tr, degree) # learn on the training half
    scores.append(rmse(y_te, np.polyval(fit, X_te))) # score on test
```

The function is `sklearn.model_selection.train_test_split` (Chapter 5 replaces it with cross-validation).

- (5) Without a seed the split differs on every run, so the “best” degree changes between runs and neither you nor a reader can reproduce the number. A seed makes the result checkable — it does not make it correct.

Common mistake: the thread through all five bugs — trusting a printed number without asking what was computed. Off-by-one and leakage errors run *silently*; print intermediate objects and check them.

Extended Exercise 0b.2 — A complete small experiment [Python]

Extended exercise (15 min)

You are given `Auto` and want to know how well `horsepower` predicts `mpg`, and whether a curve beats a line.

- 1 Write, in words or code, the six steps of the experiment from loading the data to reporting a number.
- 2 Which step must come *before* any model is fitted, and why?
- 3 On one 70/30 split you get test RMSEs 4.96, 4.52, 4.54, 4.55, 4.44 for degrees 1 to 5. Which degree do you choose, and which part of that sequence is real?
- 4 Rerunning with 30 different seeds, degree 5 wins 21 times, degree 2 six times and degree 3 three times. What does that tell you about your answer to (3), and what would you do about it?
- 5 Your colleague standardised `horsepower` using the mean and SD of the *whole* data set before splitting. Explain the problem in one sentence.

Run this live

Worked solution: `chapter_00b_lab.ipynb`, *Lecture exercises — worked Python solutions*, cell *Extended Exercise 0b.2 — A complete small experiment [Python]*.

Solution — Extended Exercise 0b.2

Solution

(1) The six steps. Load; *look* (scatter, and check for missing values — Auto stores them as '??'); split with a seed; fit each candidate on train; score each on test; report the chosen model *with* its test error.

(2) Looking, and splitting. Plot before modelling — the curvature is obvious and says a polynomial is worth trying. The split must precede every fitting decision, so nothing learned from the test set can influence the model.

(3) Only the first step is real. The drop from 4.96 to 4.52 is large and reflects genuine curvature: a line is the wrong shape. Beyond that the numbers differ by less than 0.12 — ordinary split-to-split noise. Degree 5 is nominally lowest, but nothing meaningful separates it from degree 2 — so choose **degree 2**, the simplest model that is not beaten.

(4) The winner is unstable, so do not trust it. A single split is a high-variance estimate, and the seed sweep proves it: three different “best” degrees appear. The fix is *k*-fold cross-validation (Chapter 5): here (5-fold, repeated 10×) it gives RMSEs of 4.91, 4.36, 4.37, 4.38, 4.34 with a repeat-to-repeat spread of about ± 0.04 : degree 1 is clearly worse, and *degrees 2 to 5 are statistically indistinguishable*. The defensible sentence is “a quadratic is a real improvement on a line; beyond that this data set cannot tell”.

(5) Leakage. The scaler learned its mean and SD from data that includes the test set, so the test error is no longer an honest estimate of performance on new data. Fit the scaler on the training set alone.

Common mistake: rerunning with new seeds until the ranking looks right — the sweep is a diagnostic, not a menu; a fixed seed buys reproducibility, not correctness.

Outline

- 1 Reading mathematical notation
- 2 Logs, exponentials and growth
- 3 Probability, odds and the logit
- 4 Likelihood and maximum likelihood
- 5 The Python you will actually write
- 6 **Summary**

The session in one slide

- **Notation** is instructions: $\sum$ add, $\prod$ multiply, $\arg \min$ “the value that minimises”, $I(\cdot)$ a 0/1 switch, $|S|$ a count. Read formulas aloud.
- **Logs** turn products into sums, ratios into differences and skew into symmetry; e^β converts a logged coefficient back into a multiplicative effect.
- **Odds** $= p/(1 - p)$; **logit** $= \log$ odds, on $(-\infty, \infty)$; σ brings it back to $(0, 1)$. Logistic regression is a linear model *on the logit scale*.
- **Likelihood** is the probability of the observed data as a function of the parameter; maximise its log. Under normal errors this is least squares; under Bernoulli it gives k/n and, with predictors, logistic regression.
- **Counting** explains Chapter 6: 2^p subsets is hopeless, $p^2/2$ is not.
- **Python**: a function, a loop, a seed, and `fit/predict` on a split — that is every lab.

Key formulas at a glance

Notation

$$\sum_{i=1}^n a_i, \quad \prod_{i=1}^n a_i, \quad \arg \min_{\theta} f(\theta), \quad \frac{1}{n} \sum_{i=1}^n I(y_i \neq \hat{y}_i).$$

Logs, odds and the logistic function

$$\log(ab) = \log a + \log b, \quad \log(a^k) = k \log a, \quad \log \frac{p(x)}{1-p(x)} = \beta_0 + \beta_1 x \implies \text{odds ratio} = e^{\beta_1}.$$

$$\text{odds} = \frac{p}{1-p}, \quad p = \frac{\text{odds}}{1+\text{odds}}, \quad \text{logit}(p) = \log \frac{p}{1-p}, \quad \sigma(z) = \frac{1}{1+e^{-z}}.$$

Likelihood and counting

$$\ell(\theta) = \sum_{i=1}^n \log P(y_i | \theta), \quad \hat{\theta} = \arg \max_{\theta} \ell(\theta), \quad \binom{p}{k}, \quad \sum_{k=0}^p \binom{p}{k} = 2^p.$$

Vocabulary check

Term	One-line meaning
Summation / product notation	compact instructions to add or multiply
Indicator function	a 0/1 switch that turns counting into arithmetic
arg min / arg max	the input that minimises / maximises, not the value
Natural logarithm	the inverse of e^x ; <code>np.log</code>
Odds	$p/(1-p)$: how much more likely than not
Odds ratio	ratio of two odds — what a logistic coefficient exponentiates to
Logit	log-odds; the scale on which classification is linear
Logistic / sigmoid	$\sigma(z) = 1/(1 + e^{-z})$; maps any number into $(0, 1)$
Likelihood	probability of the observed data, as a function of the parameter
Log-likelihood	its log: sums instead of products, no underflow
Maximum likelihood	the parameter that makes the observed data most probable
Cross-entropy	$-\ell$ for a classifier; the loss of Chapter 10
Binomial coefficient	$\binom{p}{k}$: the number of subsets of size k
Data leakage	letting test information reach the training pipeline
Seed	fixes the random draw so results are reproducible

Where each topic reappears in the course

Topic from this session	Comes back in
$\sum$, $\prod$, $\arg \min$, $l(\cdot)$	every chapter; RSS and error rates from Ch. 2
Sets and $ \mathcal{S} $	Ch. 8 (tree regions), Ch. 12 clusters (Advanced)
Logs and exponentials	Ch. 3 (logged responses), Ch. 4, Ch. 10
Odds, logits, the sigmoid	Ch. 4 (logistic regression), Ch. 10 (activations)
Likelihood and log-likelihood	Ch. 4 (fitting), Ch. 6 (AIC, BIC)
Maximum likelihood	Ch. 4, Ch. 6, Ch. 10 (cross-entropy)
2^p and counting	Ch. 6 (subset selection)
Loops, functions, $\arg \min$	every lab; tuning loops in Ch. 5–8
Seeds and splits	Ch. 2 onwards; formalised in Ch. 5
<code>fit</code> / <code>predict</code>	every model in the course
Leakage	Ch. 5 (the rule), Ch. 6 (scaling inside CV)

Common pitfalls to leave behind

Don't

- 1 Confuse min with arg min, or a value with an index.
- 2 Read $\hat{\alpha}^{*b}$ as a power — superscripts are often labels.
- 3 Write $\sum_i a_i^2 = (\sum_i a_i)^2$. It is false, and it is the reason squared errors work.
- 4 Report an odds ratio as if it were a ratio of probabilities.
- 5 Say “the likelihood that the parameter is 0.3”. Likelihood is about the *data*, given the parameter.
- 6 Take logs of a variable containing zeros without saying what you did.
- 7 Score a model on the data it was fitted to.
- 8 Forget the seed — or change it until the answer looks better.

Self-check questions

- 1 Read $\frac{1}{n} \sum_{i=1}^n I(y_i \neq \hat{y}_i)$ aloud, in words. (pp. 9 and 12)
- 2 What is the difference between $\min_{\theta} f$ and $\arg \min_{\theta} f$? (p. 11)
- 3 Simplify $\log(a^2 b) - 2 \log a$. (p. 16)
- 4 A logistic coefficient is -0.7 . What happens to the odds? (p. 22)
- 5 Convert log-odds $+1.6$ into a probability. (p. 22)
- 6 Why is a log-likelihood a sum when a likelihood is a product? (p. 29)
- 7 Under what assumption is least squares equivalent to maximum likelihood? (appendix, p. 52)
- 8 How many models does best-subset selection fit with $p = 20$? (appendix, p. 56)
- 9 What does `np.argmin` return — and what does it not return? (p. 11)
- 10 Name two things that must never be fitted on the test set. (p. 37)

Five things to remember

- 1 **A formula is a recipe.** Read it aloud as an instruction and it stops being intimidating.
- 2 **Logs convert.** Products to sums, ratios to differences, growth to straight lines, coefficients to percentages.
- 3 **Classification lives on the logit scale,** because probabilities do not have room to be linear.
- 4 **Maximum likelihood is one principle** behind least squares, logistic regression, AIC/BIC and cross-entropy.
- 5 **Fit on training data, score on test data, seed everything.** Every lab, every chapter, no exceptions.

What's next

Lecture 1 — *Chapter 1: Introduction* and the start of *Chapter 2: Statistical Learning*.

- $Y = f(X) + \varepsilon$: what statistical learning is trying to do.
- Prediction versus inference; supervised versus unsupervised.
- The course data sets and the notation that goes with them.

Companion notebook: `chapter_00b_lab.ipynb`

The notebook (next to this deck) runs everything here, live: §1 Reading mathematical notation; §2 Logs and exponentials; §3 Probability, odds and the logit; §4 Likelihood and maximum likelihood; §5 Counting: why best-subset selection dies; §6 The Python patterns every lab uses — plus worked solutions to the [Python] exercises.


Appendix — what is in here, and why

Nothing in the appendix is needed to follow the chapter: each slide is a formal derivation, a longer worked exercise, or a side topic. Read it when you want the full story, or when a later chapter sends you back here.

Contents of the appendix


- **The three scales, drawn** — probability, odds and log-odds side by side; the conversion table in the main deck carries the same content numerically.
- **Least squares as maximum likelihood** — the derivation that connects Chapter 3 to Chapter 4, plus Extended Exercise 0b.1 (deriving an estimator from scratch). The two methods are usable without it.
- **Counting and computational cost** — how the 2^P models of Chapter 6 explode, and why “just try everything” fails (with Exercise 0b.5). Chapter 6 re-states the conclusion where it is needed.

The three scales, drawn



Left to right: probabilities become odds (0 to ∞), odds become log-odds ($-\infty$ to ∞), and the logistic function $\sigma(z) = 1/(1 + e^{-z})$ carries them back. Because σ can never leave (0, 1), *any* number a linear model produces becomes a legal probability. Read the picture right to left and you have the standing warning about odds: they are not probabilities, and converting a full set back gives numbers that sum to more than one.

Least squares is maximum likelihood in disguise



With normal errors $P(y_i | \mu) = \frac{1}{\sigma \sqrt{2\pi}} \exp\left(-\frac{(y_i - \mu)^2}{2\sigma^2}\right)$, and the log strips the exponential down to its exponent:
 $\log P(y_i | \mu) = -\frac{(y_i - \mu)^2}{2\sigma^2} + \text{const}$, so

$$\ell(\mu) = -\frac{1}{2\sigma^2} \sum_i (y_i - \mu)^2 + \text{const} \quad \Rightarrow \quad \arg \max_{\mu} \ell(\mu) = \arg \min_{\mu} \sum_i (y_i - \mu)^2.$$

One principle under two names

Maximising the likelihood *is* minimising squared error whenever the errors are normal. Chapter 4 keeps the principle and drops the normal assumption — that is all logistic regression does.

Extended Exercise 0b.1 — Deriving an estimator [Math]

Extended exercise (15 min)

In a sample of n customers, k default. Model each customer as an independent Bernoulli trial with unknown default probability π .

- 1 Write the likelihood $L(\pi)$ as a product, then simplify it to a single expression in π , k and n .
- 2 Take logs to get $\ell(\pi)$.
- 3 Differentiate ℓ with respect to π , set the derivative to zero, and solve. What is $\hat{\pi}_{\text{MLE}}$?
- 4 Evaluate it for the Default data: $n = 10\,000$ with 333 defaults.
- 5 Explain why maximising ℓ gives the same answer as maximising L , and why we bother with the log at all.
- 6 Chapter 4 replaces the single π by $\pi(x_i) = \sigma(\beta_0 + \beta_1 x_i)$. Write the resulting log-likelihood, and say why it can no longer be solved by hand.

Solution — Extended Exercise 0b.1 (1/4)

Solution

(1) The likelihood. Each defaulting customer contributes π and each non-defaulting one $1 - \pi$; independence lets us multiply:

$$L(\pi) = \prod_{i=1}^n \pi^{y_i} (1 - \pi)^{1-y_i} = \pi^k (1 - \pi)^{n-k}, \quad k = \sum_i y_i.$$

The exponent trick is worth noticing: $\pi^{y_i} (1 - \pi)^{1-y_i}$ equals π when $y_i = 1$ and $1 - \pi$ when $y_i = 0$.

(2) The log-likelihood.

$$\ell(\pi) = k \log \pi + (n - k) \log(1 - \pi).$$

The product has become a sum — the only reason this is doable by hand.

Solution — Extended Exercise 0b.1 (2/4)

Solution

(3) Maximise.

$$\frac{d\ell}{d\pi} = \frac{k}{\pi} - \frac{n-k}{1-\pi} = 0 \implies k(1-\pi) = (n-k)\pi \implies \hat{\pi}_{\text{MLE}} = \frac{k}{n}.$$

The sample proportion — exactly what anyone would have guessed. That is the point: maximum likelihood *derives* the obvious estimator, and keeps working when the answer is no longer obvious.

Solution — Extended Exercise 0b.1 (3/4)

Solution

(4) **The numbers.** $\hat{\pi} = 333/10\,000 = 0.0333$, the 3.3% default rate quoted in Chapter 4.

(5) **Why the log is safe — and necessary.** $\log$ is strictly increasing, so it preserves the location of the maximum: if $L(a) > L(b)$ then $\ell(a) > \ell(b)$. We use it because it converts the product into a sum (so the derivative is a sum of simple terms) and because the product itself underflows to zero on a computer for even moderate n .

Solution — Extended Exercise 0b.1 (4/4)

Solution

(6) The regression version. With $\pi_i = \sigma(\beta_0 + \beta_1 x_i)$,

$$\ell(\beta_0, \beta_1) = \sum_{i=1}^n \left[y_i \log \pi_i + (1 - y_i) \log(1 - \pi_i) \right].$$

Setting the derivatives to zero now gives equations in which β appears *inside* σ , so they cannot be rearranged into a closed form as the normal equations were. Software maximises ℓ numerically — by walking uphill, exactly the gradient method of Part (a). Note also that $-\ell$ is the “binary cross-entropy” loss of Chapter 10: the same quantity under a different name.

Common mistake

Treating $\hat{\pi} = k/n$ as exact. With $k = 0$ the MLE announces “defaults are impossible” — an estimate inherits the sample’s noise and needs a standard error, not blind faith.

How many models are there?

Counting rules

$$k! = k(k-1) \cdots 1, \quad \binom{p}{k} = \frac{p!}{k!(p-k)!}, \quad \sum_{k=0}^p \binom{p}{k} = 2^p.$$

$\binom{p}{k}$ counts the subsets of size k ; summing over all k counts *every* subset — each variable is either in or out, hence 2^p .


With numbers

With $p = 4$ predictors there are $\binom{4}{2} = 6$ two-variable models and $2^4 = 16$ models in total (including the empty one). With $p = 10$: 1024. With $p = 40$: over 10^{12} .

Where you meet this

Chapter 6 asks which subset of predictors to keep. The count above is why “try them all” stops being possible around $p = 30$, and why stepwise selection and regularisation exist at all.

The cost of “just try everything”



Forward stepwise selection fits about $p^2/2$ models instead of 2^p : for $p = 40$, roughly 800 instead of 10^{12} . At 0.01 s per fit that is eight seconds against about 350 years — with no guarantee of finding the same answer, which is the trade-off Chapter 6 discusses.

Exercise 0b.5 — Counting [Math]

Exercise

A data set has $p = 6$ candidate predictors.

- 1 How many models contain exactly two predictors?
- 2 How many models are there in total?
- 3 Best-subset selection fits all of them; forward stepwise fits $1 + p(p + 1)/2$. Compute both counts.
- 4 Each fit takes 0.01 seconds. How long does each strategy take for $p = 6$, and for $p = 30$?
- 5 Testing every model against the data and keeping the best R^2 has a statistical cost as well as a computational one. What is it? (One sentence; Chapter 13 gives it a name.)

Live demo — §5 of the notebook

Run `chapter_00b_lab.ipynb` §5 alongside: the counting cells print $\binom{6}{2} = 15$, $2^6 = 64$ and 22 stepwise fits — parts (1)–(3) — plus the table behind part (4)'s 124 days at $p = 30$.

Solution — Exercise 0b.5 (1/2)

Solution

(1) $\binom{6}{2} = \frac{6 \cdot 5}{2} = 15$.

(2) $2^6 = 64$ (the empty model included).

(3) Best subset: 64 fits. Forward stepwise: $1 + 6(7)/2 = 22$ fits. For $p = 30$ the same formulas give $2^{30} \approx 1.07 \times 10^9$ against 466.

(4) At 0.01 s per fit and $p = 6$: 0.64 s versus 0.22 s — no practical difference. At $p = 30$: 1.07×10^7 seconds ≈ 124 days versus 4.7 seconds. This is why Chapter 6 does not simply recommend best-subset selection.

Solution — Exercise 0b.5 (2/2)

Solution

(5) Picking the winner from a huge number of models is *selection on noise*: with enough candidates, some model fits the sample well by luck, so its R^2 is optimistic and it may not generalise. That is **multiple testing** (Chapter 13), and it is also why model choice must be judged on held-out data (Chapter 5).

Common mistake

Assuming the 22 stepwise fits search the same space as the 64. Stepwise follows one *path* through the subsets, so it can miss the best model — the speed is bought with a restricted search.