

[Dismiss](#)

DARK MODE

You've been asking for dark mode for *years*.
The dark mode beta is finally here.

Change your [preferences](#) any time.

NumPy: difference between linalg.eig() and linalg.eigh()

Asked 2 years, 8 months ago Active 2 years, 8 months ago Viewed 9k times



Information Technology Solutions

[View all 2 job openings!](#)

In a Python 3 application I'm using NumPy to calculate eigenvalues and eigenvectors of a symmetric real matrix.

13

Here's my demo code:

```
import numpy as np
a = np.random.rand(3,3) # generate a random array shaped (3,3)

a = (a + a.T)/2 # a becomes a random simmetric matrix

evalues1, evectors1 = np.linalg.eig(a)

evalues2, evectors2 = np.linalg.eigh(a)
```

Except for the signs, I got the same eigenvectors and eigenvalues using `np.linalg.eig` and `np.linalg.eigh`. So, what's the difference between the two methods?

Thanks

EDIT: I've read the docs here

<https://docs.scipy.org/doc/numpy/reference/generated/numpy.linalg.eig.html> and here <https://docs.scipy.org/doc/numpy/reference/generated/numpy.linalg.eigh.html> but still I can not understand why I should use `eigh()` when I have a symmetric array.

`python-3.x` `numpy`

edited Aug 1 '17 at 13:58

asked Aug 1 '17 at 10:10

By using our site, you acknowledge that you have read and understand our [Cookie Policy](#), [Privacy Policy](#), and [our Terms of Service](#).

2 Read the docs? docs.scipy.org/doc/numpy-1.10.1/reference/generated/... – MaxNoe Aug 1 '17 at 10:14

if you look at `evecs1` and `evecs2` - it's not just the sign that got flipped for some elements, the position of some elements have changed too. I would go with the read-the-doc option! (if you on in ipython notebook, just run `??np.linalg.eig` and `??np.linalg.eigh` to see the docs! – Atlas7 Aug 1 '17 at 10:18

Here is a hint: remove/comment line 4 and try again ;) – Feodoran Aug 1 '17 at 10:27

1 Answer

Active	Oldest	Votes
--------	--------	-------



24



`eigh` guarantees you that the eigenvalues are sorted and uses a faster algorithm that takes advantage of the fact that the matrix is symmetric. **If you know that your matrix is symmetric, use this function.**

Attention, `eigh` doesn't check if your matrix is indeed symmetric, it by default just takes the lower triangular part of the matrix and assumes that the upper triangular part is defined by the symmetry of the matrix.

`eig` works for general matrices and therefore uses a slower algorithm, you can check that for example with IPython's magic command `%timeit`. If you test with larger matrices, you will also see that in general the eigenvalues are not sorted here.

answered Aug 1 '17 at 10:37



Michael H.

2,034 1 11 22

1 Excellent answer! – Kaushal28 May 4 '19 at 9:11

Warning: Numpy's documentation of `eig` states that The eigenvalues are not necessarily ordered. – kilojoules Nov 25 '19 at 19:29

