

INFORMATION TECHNOLOGY: PRACTICAL EXAMINATION 2011 (version 1)				
	Candidate:			
	Marker:			
		120	0	0
		Total	Pupil	IDC
1.1	SELECT * FROM tblCountries ORDER BY country;	3		0
1.2	SELECT * FROM tblEvents WHERE category = 'Swimming';	3		
1.3	SELECT athlete FROM tblResults WHERE medal = 'Silver' OR medal = 'Gold'(or any correct condition, -1 to a max of 2 for mistakes);	4		
1.4	SELECT continent, COUNT(*) AS countries FROM tblCountries GROUP BY continent;	4		
1.5	UPDATE tblCountries SET continent = 'Europe' WHERE code = 'RUS';	3		
1.6	INSERT INTO tblResults (eventID, athlete, medal, code)(correct field list, 'record' is optional) VALUES (47, 'Kerron Stewart', 'Silver', 'JAM') (correct values, appropriate for fields, -1 to a max of 2 for mistakes);	4		
1.7	SELECT athlete FROM tblResults INNER JOIN tblEvents ON tblResults.eventID = tblEvents.eventID WHERE description = '100 metres';	5		
1.8	SELECT country, medal(both country and medal must be present), COUNT(*) FROM tblResults INNER JOIN tblCountries ON tblResults.code = tblCountries.code GROUP BY country, medal;	7		
1.9	SELECT SUM(officials) * 500 AS Cost FROM tblEvents WHERE description LIKE '*freestyle*'(accept also '*freestyle' / Could also use RIGHT(description, 9)(both parameters correct) = 'freestyle');	7		
2	Class name, at least one property is: private, correctly typed and correctly named; other instance vars correct, constructor named correctly, 4 parameters, parameter assignments correct; at least one accessor method: correctly typed, correctly named, correct return, all other accessors correct; toString correct, correct fields and format (-1 to a max of -2 for errors)	15		0
3.1	Class name OlympicRecord, extends RaceResult	2		0
3.2	Constructor named correctly, 4 parameters, calls parent constructor with relevant parameters	3		
3.3	Method named isValid, if-statement condition (getPosition() == 1) , return appropriate values	4		
4.1	Class extends OlympicRecord	1		0
4.2	Constructor method is named correctly, uses parent constructor.	2		
4.3	toString method correct header, call parent toString, append "World Record" text.	3		

5.1	Class called RecordManager	1		
5.2	Array of RaceResults declared, 500 elements, int counter.	4		
5.3	Constructor method RecordManager, opens file for reading, loops correctly, parses line for '#' character, determines type of record ('---', 'OLR', 'WRC'), creates appropriate objects with correct parameters for at least one, adds to array, increments counter, reads in next line for parsing.	12		
5.4	toString method added, for-loop through elements, append to temp String using object's toString, add new line character.	5		
5.5	Method called delete (or appropriate name, "remove" etc.) , accepts integer parameter, correct for-loop, shift elements , decrease counter.	5		
5.6	Method given appropriate name (e.g. countOlympicRecords) , for-loop, "instanceof" check, increment counter, return counter. Second method (countWorldRecords) employs same logic.	6		
5.7	Method called validate, iterates through array, checks for "instanceof" OlympicRecord, type-casts correctly, checks isValid method, uses delete method (Q5.5) to remove element from array	6		0
6.1	Determine whether contains "m", extract minutes extract seconds correct calculation (m*60+s), return double value of seconds	5		
6.2	Correct method header, mark for appending getTimeInSeconds method results to toString	2		0
7	Instantiates a RecordManager object, calls toString method, outputs results of both countOR and countWR methods at least once, validates data.	4		0