

# Index

- \$-notation, 31–34
- abstract data type, 3
- abstraction, 3
- accumulated debt, 58, 60
- accumulated savings, 40, 58
- accumulating parameter, 86, 95
- actual cost, 60
- AltBinaryRandomAccessList**  
(structure), 147
- amortization
  - banker's method, *see* banker's method
  - eliminating, *see* scheduling
  - physicist's method, *see* physicist's method
  - problem with persistence, 54–55
  - traditional, 39–41
- anticredits, 81
- assignments, 2
- banker's method
  - justification of, 62–63
  - traditional, 40
  - with lazy evaluation, 61–62, 69
- BankersDeque** (functor), 110
- BankersQueue** (structure), 65
- batched rebuilding, 99–101
- BatchedQueue** (structure), 43
- binary search trees, 99
  - delete, 100
  - red-black, 24–28, 203
  - unbalanced, 11–14, 203
- BinaryRandomAccessList** (structure), 123
- binomial heaps, 20–24, 45–46, 70, 89–93, 198
  - binomial queues, *see* binomial heaps
  - binomial trees, 21, 118, *see also*
    - k*-nomial trees
  - BinomialHeap** (functor), 24
  - Bootstrap** (functor), 161
  - bootstrap loader, 141
  - BootstrappedQueue** (structure), 149
  - bootstrapping, 141, *see also*
    - data-structural bootstrapping
  - bootstrapping a compiler, 141
  - bottom-up mergesort, 74–78, 94–97, 202
  - BottomUpMergeSort** (structure), 77
- c-deques, *see* catenable deques
- caching, 3
- call-by-name, 59, 63
- call-by-need, *see* lazy evaluation
- call-by-value, *see* strict evaluation
- catenable deques, 175–184, 191, 192
  - implicit, 177–184
  - signature, 176, 191
  - simple, 175–178
- catenable lists, 153–158, 169, 191
  - signature, 153, 190
- CATENABLEDEQUE** (signature), 176
- CatenableList** (functor), 156
- CATENABLELIST** (signature), 153
- cheap operations, 40
- chef's knives, 2
- complete binary leaf trees, 118
- complete binary trees, 118, 132
- complete cost, 60
- complete *k*-ary leaf trees, 138
- complete *k*-ary trees, 138
- copying, 7
- coroutines, 101, 102, 106, 113

- credits, 40, 41
- dancing bear, 2
- data structure, meanings of, 3–4
- data-structural bootstrapping, 169
- debit inheritance, 67–68
- debit passing, 174, 183
- dense representations, 116, 117
- DEQUE (signature), 45, 107
- deques, 44, 106, 113
  - banker's, 108–110, 189
  - output-restricted, 107
  - real-time, 111–112, 170
  - signature, 45, 107, 189
- destructive updates, 2
- digital search trees, *see* tries
- dominoes, 85
- double-ended queues, *see* deques
- ephemeral data structures, 2, 4, 58
- execution traces, 57, 62–63
- expensive operations, 40, 59, 62
- ExplicitMin (functor), 23
- FIFO queues, *see* queues
- finite maps
  - over products, 167
  - over sums, 168
  - signature, 163, 204
- FINITEMAP (signature), 16, 163
- flexible arrays, *see* random-access lists
- foldr1, 155
- Ford, Henry, 1
- function (as opposed to operation), 4
- functional programming, theoretical
  - efficiency of, 2
- functors in Standard ML, 4
- future, logical, 57
- garbage collection, 10
- global rebuilding, 98, 101–102, 106, 113
- hash table, 165, 166
- HEAP (signature), 18
- heap-ordered trees, 17
- heaps, 169
  - binomial, 20–24, 45–46, 198
  - binomial, lazy, 70–71, 162
  - binomial, scheduled, 89–93
  - bootstrapped, 158–162, 201
  - delete, 138
  - leftist, 17–20, 52, 197
  - leftist, weight-biased, 19
  - pairing, 52–54, 56, 199
  - pairing, lazy, 79–81, 200
  - signature, 18, 162, 197
  - skew binomial, 134–137, 162, 170, 200
  - splay, 46–52, 56, 198
- HEAPWITHINFO (signature), 162
- higher-order functions, 76
- higher-order functors, 160
- hints to practitioners, 26, 44, 52, 53, 81, 89, 133, 150, 158
- history, logical, 57, 61
- HoodMelvilleQueue (structure), 105
- imperative data structures, 2
- implementation, 3
- implicit recursive slowdown, 171
- ImplicitCatenableDeque (functor), 181, 182
- ImplicitQueue (structure), 174
- incremental computations, 34, 61, 62, 67, 70
- interactive systems, 83
- intrinsic cost, 84
- $k$ -nomial trees, 138
- knives, 2
- layaway plan, 60
- lazy evaluation, 2, 31, 37, 59
  - syntax for, *see* \$-notation
  - time analysis, 60, 82
- lazy numerical representations, 125–127
- lazy rebuilding, 104–106
- LazyBinomialHeap (functor), 71
- LazyPairingHeap (functor), 80
- leaf tree, 118
- left-associative appends, 147
- leftist heaps, 17–20, 52, 197
- LeftistHeap (functor), 20
- life cycle of suspensions, 61
- lists, 7–10
- logical future, 57, 59, 61, 85
- logical history, 57, 61
- memoization, 3, 37, 63
- mergeable heaps, *see* heaps
- mergesort, *see* bottom-up mergesort
- Model T, 1
- monolithic computations, 34, 61, 62, 67, 70

- nested suspensions, 60, 67, 106
- non-uniform recursion, 142–144, *see also* polymorphic recursion
- normal-order reduction, 37
- numerical representations, 115
- object, 3
- operation, meanings of, 4
- operator, 4
- or-patterns, 26
- ORDERED** (signature), 14
- pairing heaps, 52–54, 56, 79–81, 199, 200
- PairingHeap** (functor), 54
- parallel systems, 83
- particle–antiparticle annihilation, 81
- path compression, 81
- path copying, 15
- pattern matching, 36
  - on abstract types, 180
- pebble games, 97
- pennants, 118, 138
- persistence
  - problem with amortization, 54–55
- persistent data structures, 2, 7, 59, 83
- persistent identity, 3
- physicist’s method
  - limitations, 69
  - traditional, 40–41, 82
  - with lazy evaluation, 68–70
- PhysicistsQueue** (structure), 73
- polymorphic recursion, 144, 170
- positional number systems, 116
- potential, 41
- priority queues, *see* heaps
- quaternary numbers, 138
- QUEUE** (signature), 42
- queues, 97
  - banker’s, 64–67, 86, 106, 107, 186
  - batched, 42–44, 101, 186
  - bootstrapped, 146–150, 188
  - Hood–Melville, 102–105, 107, 187
  - implicit, 172–175, 189
  - physicist’s, 72–73, 104, 187
  - real-time, 86–89, 106, 107
  - signature, 42, 186
- random-access lists, 119
  - binary, 119–123, 144–147, 194, 196
  - signature, 120, 194
  - skew binary, 132–134, 195
- RANDOMACCESSLIST** (signature), 120
- real-time systems, 83
- realized costs, 60
- realized debits, 63
- RealTimeDeque** (functor), 112
- RealTimeQueue** (structure), 88
- recursive modules, 160, 161
- recursive slowdown, 130, 170, 171, 184,
  - see also* implicit recursive slowdown
- red-black trees, 24–28, 125, 203
  - delete, 100
- RedBlackSet** (functor), 28
- redundant number system, 116
- reference cell, 4
- ScheduledBinomialHeap** (functor), 93
- ScheduledBottomUpMergeSort** (functor), 96
- scheduling, 84–86, 106
- segmented representations, 127–130
- self-modification, 59
- SET** (signature), 12
- sets
  - signature, 202
- shared cost, 60
- sharing, 7
- signatures in Standard ML, 4
- SimpleCatenableDeque** (functor), 178
- skew binary numbers, 131–132
  - canonical form, 131
- skew binomial trees, 135
- skew  $k$ -ary numbers, 139
- SkewBinaryRandomAccessList** (structure), 134
- SkewBinomialHeap** (functor), 137
- snoc, etymology of, 42
- SORTABLE** (signature), 74
- sortable collections, 74
  - signature, 74, 202
- sparse representations, 116, 117
- splay trees, 46–52, 56, 59, 198
- SplayHeap** (functor), 50
- STACK** (signature), 8
- steques, *see* output-restricted dequeues
- Stream** (structure), 36
- STREAM** (signature), 36
- streams, 34–37
  - signature, 36
- strict evaluation, 2, 59
- structural abstraction, 151–153, 170

- structural decomposition, 142
- structures in Standard ML, 4
- suspensions, 31
  - as nullary functions, 37
  - life cycle of, 61
  - nested, 60, 67, 106
  - trivial, 35
- telescoping series, 41
- terminology, 3–4
- Trie (functor), 165
- TrieOfTrees (functor), 168
- tries, 163–168, 204
- trinary numbers, 138
- trivial suspensions, 35
- UnbalancedSet (functor), 14
- uniform recursion, 142
- unrealized costs, 60
- unshared cost, 60
- values in Standard ML, 4
- version, 3
- version graphs, 58
- views, 180
- weak updates, 100
- worst-case data structures, benefits of, 83
- zeroless representations, 122–125