

S5: Programming with Effects

S5.2: State and Effects

CSci 2041: Advanced Programming Principles

University of Minnesota,
Prof. Van Wyk,
Spring 2018

1

Need for mutable state

- ▶ We saw need for mutable references in implementing laziness in a strict language and for building circular structures (closures).
- ▶ We may need it for some data structures, doubly linked lists or other circular structures.
We can't create these *from the bottom up* like lists or trees.

2

Two points for discussion

- ▶ pointing vs. copying
When can two references point to the same data in memory and when must we duplicate that memory?
- ▶ Denotational semantics
We've seen how to evaluate expressions.
What is the meaning of a statement?

3

Pointing vs Copying

- ▶ Consider following function and lists

```
let cons2 x y lst = x :: y :: lst
let l1 = all_ints_up_to 1000000
let l2 = cons2 1 2 l1
```

- ▶ How much memory is required to store both `l1` and `l2`?
- ▶ Is there some reason that the underlying machine representation of `l2` could have a pointer to `l1`?
Or must be copy all of `l1` to create a duplicate that is used in `l2`?

4

- ▶ In a language in which the value of `l1` never changes, because it might be a pure functional language, then `l2` can have a pointer to `l1`.
- ▶ In a language in which some element of `l1` might be changed by an assignment statement, then we may want to make a copy of `l1`.
- ▶ In mainstream languages the issue is phrased as making a `shallow copy` or a `deep copy`.

5

- ▶ The key issue is whether or not a data structure is `mutable`.

Will it be changed after it is created?

- ▶ There are many libraries for Java and C++ that work over `non-mutable` data.
 - ▶ They don't provide operations to change a value once it has been created.
 - ▶ Thus the library implements only shallow copies and saves memory.

6

Denotational Semantics

- ▶ We've seen how to evaluate expressions to compute a value.
- ▶ How do we execute statements?
- ▶ The paper "The Denotational Semantics of Programming Languages" by R. D. Tennent provides a good introduction to this topic. If you are interested in a historical paper on programming language semantics you should take a look. It is in the [Resources](#) directory of the public class repository.

7

Meaning of expressions

- ▶

```
type value = Int of int | Bool of bool | ...  
type environment = (string * value) list  
eval:  expr -> environment -> value
```
- ▶ Consider some expression

```
let e1 = Add ( Mul (Id "x", ...), ... )
```
- ▶ What is its meaning?
Does `eval` define its meaning?
- ▶ What is the type of `eval e1`?

8

Meaning of expressions

- ▶ What is the type of `eval e1`?
- ▶ It is `env -> value`.
- ▶ So we can think of the meaning of an expression as a function from an environment or state to a value.

9

States and environments

- ▶ states and environments are more or less the same thing
- ▶ they map names to values
- ▶ but we tend to use the term “environment” in evaluating expressions or pure functional languages
and “state” when thinking of imperative programs with statements and side effects

10

Meaning of statements

- ▶ So what about statements?
- ▶ What is a statement? What is the “type” of its meaning?
- ▶ What is the meaning of `x = y + 3; ?`
- ▶ We can think of statements as state transformers.
- ▶ Their meaning has the type `state -> state`.
- ▶ So let's define the type `stmt` and the function
`exec: stmt -> state -> state`.
- ▶ Find this code in `interpreter.ml` in the sample programs directorires on GitHub.

11