

Schema documentation for entity-eca-1.3.xsd

20 october 2013

Table of Contents

Namespace: ""	1
Schemas	1
Main schema entity-eca-1.3.xsd	1
Elements	1
Element eecas	1
Element eeca	1

Namespace: ""


Schemas

Main schema entity-eca-1.3.xsd

Namespace	No namespace
-----------	--------------

Elements


Element eecas

Namespace	No namespace
Diagram	
Instance	<pre><eecas> <eeca entity="" get-entire-entity="false" on-create="false" on-delete="false" on- find-count="false" on-find-iterator="false" on-find-list="false" on-find-one="false" on- update="false" run-before="false" run-on-error="false">{0,unbounded}</eeca> </eecas></pre>

Element eeca

Namespace	No namespace
Annotations	<p>Triggered by entity operations such a create, update, delete, and find. If condition (optional) evaluates to true then the actions are run.</p> <p>Entity ECAs are meant for maintenance of data derived from other entities. Entity ECAs should NOT generally be used for triggering business processes, Service ECA rules are a much better tool for that.</p> <p>For create, update, and delete operations the context coming in will be the current context plus the entity value's fields added to the context for convenience in reading, and a "entityValue" variable for the actual EntityValue object.</p>

Diagram



Used by

Element `eecas`

Instance

```
<eeca entity="" get-entire-entity="false" on-create="false" on-delete="false" on-find-count="false" on-find-iterator="false" on-find-list="false" on-find-one="false" on-update="false" run-before="false" run-on-error="false">
  <condition>{0,1}</condition>
  <actions>{1,1}</actions>
</eeca>
```

Attributes

QName	Type	Fixed	Default	Use
entity	xs:string			required
get-entire-entity	boolean		false	optional
Get the entire entity before running the actions for update and delete operations.				
on-create	boolean		false	optional
on-delete	boolean		false	optional
on-find-count	boolean		false	optional
on-find-iterator	boolean		false	optional
on-find-list	boolean		false	optional
on-find-one	boolean		false	optional
on-update	boolean		false	optional
run-before	boolean		false	optional

	QName	Type	Fixed	Default	Use
		If false (default) runs after the entity operation. If true runs before the operation.			
	run-on-error	boolean		false	optional