


Hardware Optimized OCI Images via MetaHub Registry Proxy

High Performance Container Workshop - ISC19

Image Lifecycle needs Composability and Workflow

- Multiple phases in ML lifecycle
- Modular Assembly of Software Stacks
- **With drivers and growing set of hardware and software, curating these stacks is hard.**



source: <https://thenewstack.io/an-introduction-to-the-machine-learning-platform-as-a-service/>

Current State of Affairs [cont]

Images optimized for different CPU μ -arch are picked by name.

As described in the previous slides.

Type1

broadwell

Type2

skylake

Type3

coffelake

Type4

broadwell

Tesla M60

```
$ docker run -ti --rm qnib/bench:cpu-broadwell  
>> This container is optimized for: cpu:broadwell
```

```
$ docker run -ti --rm qnib/bench:cpu-skylake  
>> This container is optimized for: cpu:skylake
```

```
$ docker run -ti --rm qnib/bench:generic  
>> This container is not optimized for a specific microarchitecture
```

```
$ docker run -ti --rm qnib/bench:cpu_broadwell-nvcap_52  
>> This container is optimized for: cpu:broadwell,nvcap:5.2
```

Dynamic Manifest List FTW!

Manifest List provides choice via OCI

“platform.features”.

Unfortunately this needs to be implemented by each runtime independently.



```
image: qnib/bench
manifests:
  - image: qnib/bench:cpu-broadwell
    platform:
      architecture: amd64
      features: ["cpu:broadwell"]
  - image: qnib/bench:cpu-skylake
    platform:
      architecture: amd64
      features: ["cpu:skylake"]
  - image: qnib/bench:cpu-coffelake
    platform:
      architecture: amd64
      features: ["cpu-coffelake"]
  - image:
      qnib/bench:cpu_broadwell-nvcap_52
    platform:
      architecture: amd64
      features:
        - cpu-broadwell
        - nvcap-5.2
```

MetaHub to proxy normal Registry

To be agnostic in terms of the runtime and supervision engine, MetaHub will dynamically create a Manifest List depending on the token used to authenticate.

Machine Types

SIGN OUT

ADD

Type1

Broadwell

CREDENTIALS

Type2

Skylake

CREDENTIALS


Type3

CREDENTIALS

Type4


Broadwell, Tesla M60

CREDENTIALS



MetaHub to proxy normal Registry [cont #1]

Metahub reduces the Manifest List down to what the runtime 'needs'.



MetaHub to proxy normal Registry [cont #2]

Each machine type has a special credentials to login to MetaHub.

Type1	broadwell	
Type2	skylake	
Type3	coffelake	
Type4	broadwell	Tesla M60

Machine Types		SIGN OUT
ADD		
Type1 Broadwell	CREDENTIALS	
Type2 Skylake	CREDENTIALS	
Type3	CREDENTIALS	
Type4 Broadwell, Tesla M60	CREDENTIALS	









```
$ docker login -u qnib-type1 -p $PASSWD1 metahub.qnib.org
Login Succeeded
```

```
$ docker login -u qnib-type2 -p $PASSWD2 metahub.qnib.org
Login Succeeded
```

```
$ docker login -u qnib-type3 -p $PASSWD3 metahub.qnib.org
Login Succeeded
```

```
$ docker login -u qnib-type4 -p $PASSWD4 metahub.qnib.org
Login Succeeded
```

MetaHub to proxy normal Registry [cont #3]

Machine Types		SIGN OUT
ADD		
Type1 Broadwell	CREDENTIALS	 
Type2 Skylake	CREDENTIALS	 
Type3	CREDENTIALS	 
Type4 Broadwell, Tesla M60	CREDENTIALS	 

Thus, the runtime will download the correct choice.

Type1
broadwell

```
$ docker run -ti --rm metahub.qnib.org/qnib/bench  
>> This container is optimized for: cpu:broadwell
```

Type2
skylake

```
$ docker run -ti --rm metahub.qnib.org/qnib/bench  
>> This container is optimized for: cpu:skylake
```

Type3
cofflake

```
$ docker run -ti --rm metahub.qnib.org/qnib/bench  
>> This container is not optimized for a specific microarchitecture
```

Type4
broadwell Tesla M60

```
$ docker run -ti --rm metahub.qnib.org/qnib/bench  
>> This container is optimized for: cpu:broadwell,nvcap:5.2
```


FOOS FTW! MetaHub released.

<https://qnib.org/2019/06/12/metahub/>

Metahub: Dynamic Registry Proxy

Jun 12, 2019 • Christian Kniep

I won't say "Long time, no post" - but...

As I had some time at my hands the last couple of month, I was iterating on my idea on hardware optimization using Manifest List from the last post [Match Node-Specific Needs Using Manifest Lists](#).


<https://github.com/qnib/metahub>

MetaHub - Dynamic OCI Registry Proxy

Announcement: qnib.org

The MetaHub project is meta-data registry, which serves images filtered via login so that a machine gets the image that fits the specifics of the host the image is going to run on.

That could be picking an image that not only fits the CPU Architecture (x86-64, ppcle, arm) but is optimized for the microarchitecture of the host (Broadwell, Skylake, ...). And it does not stop there - any host specific attribute can be used: Accelerators, network, configuration or the full depth of gcc options.



Thank you!
