Best Practices for the Political Scientist

J. Alexander Branham

Fall 2015

A Quick Overview...

A Quick Overview...

- 1. Write using plain text
- 2. Code well

A Quick Overview...

- 1. Write using plain text
- 2. Code well
- 3. Use a version control system

▶ What if we write an article now that gets famous?

- What if we write an article now that gets famous?
- ▶ 20 years later, some grad student wants to extend our work

- What if we write an article now that gets famous?
- ▶ 20 years later, some grad student wants to extend our work
- ▶ How did we make Figure 1?

- What if we write an article now that gets famous?
- ▶ 20 years later, some grad student wants to extend our work
- ► How did we make Figure 1?
- ▶ Non-plain text files may be unusable 20 years from now

- What if we write an article now that gets famous?
- ▶ 20 years later, some grad student wants to extend our work
- ▶ How did we make Figure 1?
- Non-plain text files may be unusable 20 years from now
- Word processors (like MS Word) are stupid and inefficient

Code well - DO NOT CLICK A MOUSE

▶ All results should be replicable from a source file

Code well - DO NOT CLICK A MOUSE

- ▶ All results should be replicable from a source file
- ► These source files (for example, .R for R scripts or .do for Stat do-files) should be liberally commented

Code well - DO NOT CLICK A MOUSE

- ▶ All results should be replicable from a source file
- ► These source files (for example, .R for R scripts or .do for Stat do-files) should be liberally commented
- Comments explain what you are doing to your future self, collaborators, and others

Comment example

```
# This code creates Fig 1
# I use the mtcars dataset (included with R)
library(ggplot2)
ggplot(mtcars, aes(mpg, wt)) +
   geom_point() +
   geom_smooth(method="lm") # Adds OLS line with SEs
ggsave("fig/fig1.pdf")
```

► Save this code snippit as fig1.R (or similar)

▶ Previous example - have two files for one plot in a paper

- ▶ Previous example have two files for one plot in a paper
 - ► The paper itself (document.tex or similar)

- Previous example have two files for one plot in a paper
 - ► The paper itself (document.tex or similar)
 - the script to create the figure (fig1.R or similar)

- Previous example have two files for one plot in a paper
 - ► The paper itself (document.tex or similar)
 - the script to create the figure (fig1.R or similar)
- ▶ What if we could combine these to have everything in one easy-to-read file?

- Previous example have two files for one plot in a paper
 - ► The paper itself (document.tex or similar)
 - the script to create the figure (fig1.R or similar)
- What if we could combine these to have everything in one easy-to-read file?
 - ▶ This is what literate programming is all about!

Literate programming example (using knitr)

```
\begin{section}
This is an example paragraph, writte in \LaTeX.
Using knitr, we can include R code in the following manner
I can reference the figure number by calling ref:
Figure \ref{fig:mpg-and-weight}.
% NTS - updating that figure with squared x doesn't change
\begin{figure}
\centering
<<fig1plot>>= # Starts R code, labels it `fig1plot`
# I use the mtcars dataset (included with R)
library(ggplot2)
ggplot(mtcars, aes(mpg, wt)) +
  geom point() +
  geom_smooth(method="lm") # Adds OLS line with SEs
@ % closes R code
\caption{Miles per gallon and weight}
\label{fig:mpg-and-weight}
                                   \end{figure}
```

Version Control

▶ YOU NEED TO USE VERSION CONTROL!!!!!

Version Control

- YOU NEED TO USE VERSION CONTROL!!!!!
- ► This can be as simple as putting things in Dropbox, which enables you to recover previous file versions automatically

Version Control

- YOU NEED TO USE VERSION CONTROL!!!!!
- ► This can be as simple as putting things in Dropbox, which enables you to recover previous file versions automatically
- ▶ Word's "track changes" feature...

Assumes they're both going to be around (in the same form(ish)) in the future

- Assumes they're both going to be around (in the same form(ish)) in the future
 - ▶ Remember computers 20 years ago???

- Assumes they're both going to be around (in the same form(ish)) in the future
 - ▶ Remember computers 20 years ago???
- You can "clobber" work (save over good work)

- Assumes they're both going to be around (in the same form(ish)) in the future
 - ▶ Remember computers 20 years ago???
- You can "clobber" work (save over good work)
- Must tell coauthors not to touch files while you're working on them

- Assumes they're both going to be around (in the same form(ish)) in the future
 - ▶ Remember computers 20 years ago???
- You can "clobber" work (save over good work)
- Must tell coauthors not to touch files while you're working on them
 - ► Though this may be changing...

- Assumes they're both going to be around (in the same form(ish)) in the future
 - ▶ Remember computers 20 years ago???
- You can "clobber" work (save over good work)
- Must tell coauthors not to touch files while you're working on them
 - ▶ Though this may be changing...
- You also tend to end up with many versions of the same project

- Assumes they're both going to be around (in the same form(ish)) in the future
 - ▶ Remember computers 20 years ago???
- You can "clobber" work (save over good work)
- Must tell coauthors not to touch files while you're working on them
 - ▶ Though this may be changing...
- You also tend to end up with many versions of the same project
 - ((show example paper))

▶ Git is a formal distributed version control system

- ▶ Git is a formal distributed version control system
 - ► There are others (Subversion and Mercurial are the big two), but we're going to focus on git

- ▶ Git is a formal distributed version control system
 - ► There are others (Subversion and Mercurial are the big two), but we're going to focus on git
- It is an easy way to keep track of all the revisions you have saved

- Git is a formal distributed version control system
 - ► There are others (Subversion and Mercurial are the big two), but we're going to focus on git
- It is an easy way to keep track of all the revisions you have saved
- It enables easy collaborating between many different people, without the need to email files back and forth or tell them when you're working on something

- Git is a formal distributed version control system
 - There are others (Subversion and Mercurial are the big two), but we're going to focus on git
- It is an easy way to keep track of all the revisions you have saved
- It enables easy collaborating between many different people, without the need to email files back and forth or tell them when you're working on something
- You only have one version of a file at any one time

- Git is a formal distributed version control system
 - There are others (Subversion and Mercurial are the big two), but we're going to focus on git
- It is an easy way to keep track of all the revisions you have saved
- It enables easy collaborating between many different people, without the need to email files back and forth or tell them when you're working on something
- You only have one version of a file at any one time
- You can see the entire history of a file easily

- Git is a formal distributed version control system
 - ► There are others (Subversion and Mercurial are the big two), but we're going to focus on git
- It is an easy way to keep track of all the revisions you have saved
- It enables easy collaborating between many different people, without the need to email files back and forth or tell them when you're working on something
- You only have one version of a file at any one time
- You can see the entire history of a file easily
- You can see exactly what changed in each new commit

Git

- Git is a formal distributed version control system
 - ► There are others (Subversion and Mercurial are the big two), but we're going to focus on git
- It is an easy way to keep track of all the revisions you have saved
- It enables easy collaborating between many different people, without the need to email files back and forth or tell them when you're working on something
- You only have one version of a file at any one time
- You can see the entire history of a file easily
- You can see exactly what changed in each new commit
- ► There are *many* different GUIs so you don't have to deal with the command line

Git

- Git is a formal distributed version control system
 - ► There are others (Subversion and Mercurial are the big two), but we're going to focus on git
- It is an easy way to keep track of all the revisions you have saved
- It enables easy collaborating between many different people, without the need to email files back and forth or tell them when you're working on something
- You only have one version of a file at any one time
- You can see the entire history of a file easily
- You can see exactly what changed in each new commit
- There are many different GUIs so you don't have to deal with the command line
 - ▶ I like Sourcetree (for Windows) and SmartGit (for Linux)

Git

- Git is a formal distributed version control system
 - ► There are others (Subversion and Mercurial are the big two), but we're going to focus on git
- It is an easy way to keep track of all the revisions you have saved
- It enables easy collaborating between many different people, without the need to email files back and forth or tell them when you're working on something
- You only have one version of a file at any one time
- You can see the entire history of a file easily
- You can see exactly what changed in each new commit
- There are many different GUIs so you don't have to deal with the command line
 - ▶ I like Sourcetree (for Windows) and SmartGit (for Linux)
- ((show example git history))



▶ Github is the most popular online git service

- ▶ Github is the most popular online git service
 - ▶ There are many others, such as BitBucket

- ▶ Github is the most popular online git service
 - ▶ There are many others, such as BitBucket
- ► Each project gets a repository ("repo")

- Github is the most popular online git service
 - ▶ There are many others, such as BitBucket
- Each project gets a repository ("repo")
- ► Each repo is version-controlled (using git)

- Github is the most popular online git service
 - ▶ There are many others, such as BitBucket
- Each project gets a repository ("repo")
- ► Each repo is version-controlled (using git)
- Default is open-source (public)

- Github is the most popular online git service
 - ▶ There are many others, such as BitBucket
- Each project gets a repository ("repo")
- ► Each repo is version-controlled (using git)
- Default is open-source (public)
- ➤ You can make repos private (for a fee students get 5 for free)

- Github is the most popular online git service
 - ▶ There are many others, such as BitBucket
- Each project gets a repository ("repo")
- Each repo is version-controlled (using git)
- Default is open-source (public)
- ➤ You can make repos private (for a fee students get 5 for free)
- ▶ This file is a part of my "math-camp" repo here

- Github is the most popular online git service
 - ▶ There are many others, such as BitBucket
- Each project gets a repository ("repo")
- Each repo is version-controlled (using git)
- Default is open-source (public)
- ➤ You can make repos private (for a fee students get 5 for free)
- ▶ This file is a part of my "math-camp" repo here
 - Feel free to fork-edit-pull request any changes!

- Github is the most popular online git service
 - ▶ There are many others, such as BitBucket
- Each project gets a repository ("repo")
- Each repo is version-controlled (using git)
- Default is open-source (public)
- ➤ You can make repos private (for a fee students get 5 for free)
- ▶ This file is a part of my "math-camp" repo here
 - ► Feel free to fork-edit-pull request any changes!
 - ▶ I included the PDFs, which is unusual since they aren't plain text

Bonus best practice - Test your code!

▶ If you write your own function, it is important to test it to make sure it does what you want it to do!

```
my_mean <- function(dat){</pre>
  the_sum <- numeric()</pre>
  N <- length(dat)
  for (i in 1:N){
    if(i==1){the_sum <- dat[1]}
    else{
    the sum <- the sum * dat[i]
 }}
  my mean <- the sum / N
  my_mean
mean of zero <-c(-2, -1, 1, 2)
my mean(mean_of_zero)
```

► For R:

- ► For R:
 - CRAN has a webpage dedicated to just this

- ► For R:
 - CRAN has a webpage dedicated to just this
 - ► Markdown: rmarkdown

- ► For R:
 - CRAN has a webpage dedicated to just this
 - ► Markdown: rmarkdown
 - ► LaTeX: knitr

- ► For R:
 - CRAN has a webpage dedicated to just this
 - ► Markdown: rmarkdown
 - ▶ LaTeX: knitr
 - ► WYSIWYM: Lyx + knitr

- ► For R:
 - CRAN has a webpage dedicated to just this
 - ► Markdown: rmarkdown
 - ► LaTeX: knitr
 - ► WYSIWYM: Lyx + knitr
 - ► Office: odfWeave

- ► For R:
 - CRAN has a webpage dedicated to just this
 - ► Markdown: rmarkdown
 - ► LaTeX: knitr
 - WYSIWYM: Lyx + knitr
 - ▶ Office: odfWeave
- ► For Stata:

- ► For R:
 - CRAN has a webpage dedicated to just this
 - ► Markdown: rmarkdown
 - ► LaTeX: knitr
 - ► WYSIWYM: Lyx + knitr
 - ▶ Office: odfWeave
- ► For Stata:
 - StatWeave

- For R:
 - CRAN has a webpage dedicated to just this
 - ► Markdown: rmarkdown
 - LaTeX: knitr
 - WYSIWYM: Lyx + knitr
 - Office: odfWeave
- ► For Stata:
 - StatWeave
 - Google "Sweave for Stata" or "reproducable research and Stata"

▶ Git

- ▶ Git
 - ► Nice tutorial here

- ▶ Git
 - Nice tutorial here
 - ▶ Here's more than you need to know about git

- ▶ Git
 - Nice tutorial here
 - Here's more than you need to know about git
 - Using GitFlow