

Field_Set	Field	Type	Example	Description
base	@timestamp	date	2016-05-23T08:05:34.853Z	Date/time when the event originated.
base	labels	object	{"application": "foo-bar", "env": "production"}	Custom key/value pairs.
base	message	match_only_text	Hello World	Log message optimized for viewing in a log viewer.
base	tags	keyword	["production", "env2"]	List of keywords used to tag each event.
agent	agent.build.origin	keyword	metricbeat version 7.6.0 (amd64), libbeat 7.6.0 [5a23e8f830f5001ba344e4e54d8cb82cb107c built 2020-02-05 23:10:10 +0000 UTC]	Extended build information for the agent.
agent	agent.ephemeral	keyword	8a4f500f	Ephemeral identifier of this agent.
agent	agent.id	keyword	8a4f500d	Unique identifier of this agent.
agent	agent.name	keyword	foo	Custom name of the agent.
agent	agent.type	keyword	filebeat	Type of the agent.
agent	agent.version	keyword	6.0.0-rc2	Version of the agent.
client	client.address	keyword		Client network address.
client	client.as.number	long		15169 Unique number allocated to the autonomous system.
client	client.as.organization	keyword	Google LLC	Organization name.
client	client.as.organization.match_only_text		Google LLC	Organization name.
client	client.bytes	long		184 Bytes sent from the client to the server.
client	client.domain	keyword	foo.example.com	The domain name of the client.
client	client.geo.city_name	keyword	Montreal	City name.
client	client.geo.continent	keyword	NA	Continent code.
client	client.geo.continents	keyword	North America	Name of the continent.
client	client.geo.country	keyword	CA	Country ISO code.
client	client.geo.countries	keyword	Canada	Country name.
client	client.geo.location_geo_point		{ "lon": -73.614830, "lat": 45.505918 }	Longitude and latitude.
client	client.geo.name	keyword	boston-dc	User-defined description of a location.
client	client.geo.postal	keyword		94040 Postal code.
client	client.geo.region	keyword	CA-QC	Region ISO code.
client	client.geo.region	keyword	Quebec	Region name.
client	client.geo.timezone	keyword	America/Argentina/Buenos_Aires	Time zone.
client	client.ip	ip		IP address of the client.
client	client.mac	keyword	00-00-5E-00-53-23	MAC address of the client.
client	client.nat.ip	ip		Client NAT IP address.
client	client.nat.port	long		Client NAT port.
client	client.packets	long		12 Packets sent from the client to the server.
client	client.port	long		Port of the client.
client	client.registered	keyword	example.com	The highest registered client domain, stripped of the subdomain.
client	client.subdomain	keyword	east	The subdomain of the domain.
client	client.top_level	keyword	co.uk	The effective top level domain (com, org, net, co.uk).
client	client.user.domain	keyword		Name of the directory the user is a member of.
client	client.user.email	keyword		User email address.
client	client.user.full_name	keyword	Albert Einstein	User's full name, if available.
client	client.user.full_name.match_only_text		Albert Einstein	User's full name, if available.
client	client.user.group	keyword		Name of the directory the group is a member of.
client	client.user.group	keyword		Unique identifier for the group on the system/platform.
client	client.user.group	keyword		Name of the group.
client	client.user.hash	keyword		Unique user hash to correlate information for a user in anonymized form.
client	client.user.id	keyword	S-1-5-21-202424012787-2692429404-2351956786-1000	Unique identifier of the user.
client	client.user.name	keyword	a.einstein	Short name or login of the user.
client	client.user.name.match_only_text		a.einstein	Short name or login of the user.
client	client.user.roles	keyword	["kibana_admin", "reporting_user"]	Array of user roles at the time of the event.
cloud	cloud.account.id	keyword		666777888999 The cloud account or organization id.
cloud	cloud.account.name	keyword	elastic-dev	The cloud account name.
cloud	cloud.availability	keyword	us-east-1c	Availability zone in which this host, resource, or service is located.
cloud	cloud.instance.id	keyword	i-1234567890abcdef0	Instance ID of the host machine.
cloud	cloud.instance.name	keyword		Instance name of the host machine.
cloud	cloud.machine.type	keyword	t2.medium	Machine type of the host machine.
cloud	cloud.origin.account	keyword		666777888999 The cloud account or organization id.
cloud	cloud.origin.account	keyword	elastic-dev	The cloud account name.
cloud	cloud.origin.avail	keyword	us-east-1c	Availability zone in which this host, resource, or service is located.
cloud	cloud.origin.id	keyword	i-1234567890abcdef0	Instance ID of the host machine.
cloud	cloud.origin.name	keyword	t2.medium	Instance name of the host machine.
cloud	cloud.origin.project	keyword	my-project	Machine type of the host machine.
cloud	cloud.origin.project	keyword	my-project	The cloud project id.
cloud	cloud.origin.project	keyword	my-project	The cloud project name.
cloud	cloud.origin.provider	keyword	aws	Name of the cloud provider.
cloud	cloud.origin.region	keyword	us-east-1	Region in which this host, resource, or service is located.
cloud	cloud.origin.service	keyword	lambda	The cloud service name.
cloud	cloud.project.id	keyword	my-project	The cloud project id.
cloud	cloud.project.name	keyword	my-project	The cloud project name.
cloud	cloud.provider	keyword	aws	Name of the cloud provider.
cloud	cloud.region	keyword	us-east-1	Region in which this host, resource, or service is located.
cloud	cloud.service.name	keyword	lambda	The cloud service name.
cloud	cloud.target.account	keyword		666777888999 The cloud account or organization id.
cloud	cloud.target.account	keyword	elastic-dev	The cloud account name.
cloud	cloud.target.avail	keyword	us-east-1c	Availability zone in which this host, resource, or service is located.
cloud	cloud.target.id	keyword	i-1234567890abcdef0	Instance ID of the host machine.
cloud	cloud.target.name	keyword	t2.medium	Instance name of the host machine.
cloud	cloud.target.project	keyword	my-project	Machine type of the host machine.
cloud	cloud.target.project	keyword	my-project	The cloud project id.
cloud	cloud.target.project	keyword	my-project	The cloud project name.
cloud	cloud.target.provider	keyword	aws	Name of the cloud provider.
cloud	cloud.target.region	keyword	us-east-1	Region in which this host, resource, or service is located.
cloud	cloud.target.service	keyword	lambda	The cloud service name.
container	container.cpu.used_scaled_float			Percent CPU used, between 0 and 1.
container	container.disk.read	long		The number of bytes read by all disks.
container	container.disk.write	long		The number of bytes written on all disks.
container	container.id	keyword		Unique container id.
container	container.image.id	keyword	[sha256:f8efc80e3273dc756f288a63945820d8476ad54883892c771b5e2ecebf1b26]	An array of digests of the image the container was built on.
container	container.image.name	keyword		Name of the image the container was built on.
container	container.image.id	keyword		Container image tags.
container	container.labels	object		Image labels.
container	container.memory_scaled_float			Percent memory used, between 0 and 1.
container	container.name	keyword		Container name.
container	container.network	long		The number of bytes sent on all network interfaces.
container	container.network	long		The number of bytes received on all network interfaces.
container	container.runtime	keyword	docker	Runtime managing this container.
container	container.security	boolean		Indicates whether the container is running in privileged mode.
data_stream	data_stream.data.constant_keyword	keyword	nginx.access	The field can contain anything that makes sense to signify the source of the data.
data_stream	data_stream.data.numeric_keyword	keyword	production	A user defined namespace. Namespaces are useful to allow grouping of data.
data_stream	data_stream.type.constant_keyword	keyword	logs	An overarching type for the data stream.
destination	destination.address	keyword		Destination network address.
destination	destination.as.number	long		15169 Unique number allocated to the autonomous system.
destination	destination.as.organization	keyword	Google LLC	Organization name.
destination	destination.as.organization.match_only_text		Google LLC	Organization name.
destination	destination.bytes	long		184 Bytes sent from the destination to the source.
destination	destination.domain	keyword	foo.example.com	The domain name of the destination.
destination	destination.geo.city	keyword	Montreal	City name.
destination	destination.geo.continent	keyword	NA	Continent code.
destination	destination.geo.continents	keyword	North America	Name of the continent.
destination	destination.geo.country	keyword	CA	Country ISO code.
destination	destination.geo.countries	keyword	Canada	Country name.
destination	destination.geo.location_geo_point		{ "lon": -73.614830, "lat": 45.505918 }	Longitude and latitude.
destination	destination.geo.name	keyword	boston-dc	User-defined description of a location.
destination	destination.geo.postal	keyword		94040 Postal code.
destination	destination.geo.region	keyword	CA-QC	Region ISO code.
destination	destination.geo.region	keyword	Quebec	Region name.
destination	destination.geo.timezone	keyword	America/Argentina/Buenos_Aires	Time zone.
destination	destination.ip	ip		IP address of the destination.
destination	destination.mac	keyword	00-00-5E-00-53-23	MAC address of the destination.
destination	destination.nat.ip	ip		Destination NAT IP.
destination	destination.nat.port	long		Destination NAT Port.
destination	destination.packets	long		12 Packets sent from the destination to the source.
destination	destination.port	long		Port of the destination.
destination	destination.register	keyword	example.com	The highest registered destination domain, stripped of the subdomain.
destination	destination.subdomain	keyword	east	The subdomain of the domain.
destination	destination.top_level	keyword	co.uk	The effective top level domain (com, org, net, co.uk).
destination	destination.user.domain	keyword		Name of the directory the user is a member of.
destination	destination.user.email	keyword		User email address.
destination	destination.user.full_name	keyword	Albert Einstein	User's full name, if available.
destination	destination.user.full_name.match_only_text		Albert Einstein	User's full name, if available.
destination	destination.user.group	keyword		Name of the directory the group is a member of.

destination	destination.user	keyword		Unique identifier for the group on the system/platform.
destination	destination.user	keyword		Name of the group.
destination	destination.user	keyword		Unique user hash to correlate information for a user in anonymized form.
destination	destination.user	keyword	S-1-5-21-202424912787-2692429404-2351956786-1000	Unique identifier of the user.
destination	destination.user	keyword	a.einstein	Short name or login of the user.
destination	destination.user	match_only_text	a.einstein	Short name or login of the user.
destination	destination.user	keyword	["kibana_admin", "reporting_user"]	Array of user roles at the time of the event.
device	device.id	keyword	00000000-54b3-e7c7-0000-000040bf997	The unique identifier of a device.
device	device.manufact	keyword	Samsung	The vendor name of the device manufacturer.
device	device.model.id	keyword	SM-G920F	The machine readable identifier of the device model.
device	device.model.name	keyword	Samsung Galaxy S6	The human readable marketing name of the device model.
device	device.serial	key	DJGAGS4CW5	Serial Number of the device.
dl	dl.code_signature	keyword	sha256	Hashing algorithm used to sign the process.
dl	dl.code_signature	boolean		Boolean to capture if a signature is present.
dl	dl.code_signature	keyword		570522385 Code signing flags of the process
dl	dl.code_signature	keyword	com.apple.xpc.proxy	The identifier used to sign the process.
dl	dl.code_signature	keyword	ERROR_UNTRUSTED_ROOT	Additional information about the certificate status.
dl	dl.code_signature	keyword	Microsoft Corporation	Subject name of the code signer
dl	dl.code_signature	keyword	EQHX28MBAV	The team identifier used to sign the process.
dl	dl.code_signature	date	2021-01-01T11:12:30Z	When the signature was generated and signed.
dl	dl.code_signature	boolean		Stores the trust status of the certificate chain.
dl	dl.code_signature	boolean		Boolean to capture if the digital signature is verified against the binary content.
dl	dl.hash.cdhash	keyword	3783b4052f6474dbe30670b45c329e7a6d44acd9	The Code Directory (CD) hash of an executable.
dl	dl.hash.md5	keyword		MD5 hash.
dl	dl.hash.sha1	keyword		SHA1 hash.
dl	dl.hash.sha256	keyword		SHA256 hash.
dl	dl.hash.sha384	keyword		SHA384 hash.
dl	dl.hash.sha512	keyword		SHA512 hash.
dl	dl.hash.ssdeep	keyword		SSDEEP hash.
dl	dl.hash.tlsh	keyword		TLSH hash.
dl	dl.name	keyword	kernel32.dll	Name of the library.
dl	dl.path	keyword	C:\Windows\System32\kernel32.dll	Full file path of the library.
dl	dl.pe.architectun	keyword	x64	CPU architecture target for the file.
dl	dl.pe.company	keyword	Microsoft Corporation	Internal company name of the file, provided at compile-time.
dl	dl.pe.description	keyword	Paint	Internal description of the file, provided at compile-time.
dl	dl.pe.file_version	keyword	6.3.9600.17415	Process name.
dl	dl.pe.go_import	keyword	10bd5cb4cee4208076c88d9f9964491	A hash of the Go language imports in a PE file.
dl	dl.pe.go_imports	flattened		List of imported Go language element names and types.
dl	dl.pe.go_imports	long		Shannon entropy calculation from the list of Go imports.
dl	dl.pe.go_imports	long		Variance for Shannon entropy calculation from the list of Go imports.
dl	dl.pe.imphash	keyword	0c6803c4e922103c40ca5963aad36ddf	Whether the file is a stripped or obfuscated Go executable.
dl	dl.pe.import_has	keyword	d41d8cd98f00b204e900999ecf8427e	A hash of the imports in a PE file.
dl	dl.pe.imports	flattened		List of imported element names and types.
dl	dl.pe.imports	na long		Shannon entropy calculation from the list of imported element names and types.
dl	dl.pe.imports	na long		Variance for Shannon entropy calculation from the list of imported element names and types.
dl	dl.pe.original_file	keyword	MSPaint.EXE	Internal name of the file, provided at compile-time.
dl	dl.pe.pehash	keyword	73ff189663cd6be375a7ff25179a38d347651975	A hash of the PE header and data from one or more PE sections.
dl	dl.pe.product	keyword	Microsoft® Windows® Operating System	Internal product name of the file, provided at compile-time.
dl	dl.pe.sections	keyword		Section information of the PE file.
dl	dl.pe.sections	er long		Shannon entropy calculation from the section.
dl	dl.pe.sections	is		PE Section List name.
dl	dl.pe.sections	of long		PE Section List physical size.
dl	dl.pe.sections	vi long		Variance for Shannon entropy calculation from the section.
dl	dl.pe.sections	vi long		PE Section List virtual size. This is always the same as 'physical_size'.
dns	dns.answers	object		Array of DNS answers.
dns	dns.answers.class	keyword	IN	The class of DNS data contained in this resource record.
dns	dns.answers.data	keyword	10.10.10.10	The data describing the resource.
dns	dns.answers.name	keyword	www.example.com	The domain name to which this resource record pertains.
dns	dns.answers.ttl	long		180 The time interval in seconds that this resource record may be cached before it should be discarded.
dns	dns.answers.type	keyword	CHNAME	The type of data contained in this resource record.
dns	dns.header.flags	keyword	["RD", "RA"]	Array of DNS header flags.
dns	dns.id	keyword		62111 The DNS packet identifier assigned by the program that generated the query. The identifier is copied to the response.
dns	dns.op_code	keyword	QUERY	The DNS operation code that specifies the kind of query in the message.
dns	dns.question.class	keyword	IN	The class of records being queried.
dns	dns.question.name	keyword	www.example.com	The name being queried.
dns	dns.question.reg	keyword	example.com	The highest registered domain, stripped of the subdomain.
dns	dns.question.sub	keyword	www	The subdomain of the domain.
dns	dns.question.top	keyword	co.uk	The effective top level domain (com, org, net, co.uk).
dns	dns.question.type	keyword	AAAA	The type of record being queried.
dns	dns.resolved_ip	ip	["10.10.10.10", "10.10.10.11"]	Array containing all IPs seen in answers.data
dns	dns.response.cc	keyword	NOERROR	The DNS response code.
dns	dns.type	keyword	answer	The type of DNS event captured, query or answer.
ecs	ecs.version	keyword	1.0.0	ECS version this event conforms to.
email	email.attachment	keyword		List of objects describing the attachments.
email	email.attachment	keyword	txt	Attachment file extension.
email	email.attachment	keyword	3783b4052f6474dbe30670b45c329e7a6d44acd9	The Code Directory (CD) hash of an executable.
email	email.attachment	keyword		MD5 hash.
email	email.attachment	keyword		SHA1 hash.
email	email.attachment	keyword		SHA256 hash.
email	email.attachment	keyword		SHA384 hash.
email	email.attachment	keyword		SHA512 hash.
email	email.attachment	keyword		SSDEEP hash.
email	email.attachment	keyword		TLSH hash.
email	email.attachment	keyword	text/plain	MIME type of the attachment file.
email	email.attachment	keyword	attachment.txt	Name of the attachment file.
email	email.attachment	long		64329 Attachment file size.
email	email.bcc.address	keyword	bcc.user1@example.com	Email address of BCC recipient
email	email.cc.address	keyword	cc.user1@example.com	Email address of CC recipient
email	email.content_type	keyword	text/plain	MIME type of the email message.
email	email.delivery_time	date	2020-11-10T22:12:34.8196921Z	Date and time when message was delivered.
email	email.direction	keyword	inbound	Direction of the message.
email	email.from.address	keyword	sender@example.com	The sender's email address.
email	email.local_id	keyword	c25d5ea0-80d5-463b-b53c-4e6b708219ce	Unique identifier given by the source.
email	email.message_id	keyword	81ce1558b2f9@mail01.example.com	Value from the Message-ID header.
email	email.origin	date	2020-11-10T22:12:34.8196921Z	Date and time the email was composed.
email	email.reply_to.address	keyword	reply.here@example.com	Address replies should be delivered to.
email	email.sender.address	keyword		Address of the message sender.
email	email.subject	keyword	Please see this important message.	The subject of the email message.
email	email.subject	match_only_text	Please see this important message.	The subject of the email message.
email	email.to.address	keyword	user1@example.com	Email address of recipient
email	email.x_mailer	keyword	Spambot v2.5	Application that drafted email.
error	error.code	keyword		Error code describing the error.
error	error.id	keyword		Unique identifier for the error.
error	error.message	match_only_text		Error message.
error	error.stack_trace	keyword		The stack trace of this error in plain text.
error	error.stack_trace	match_only_text		The stack trace of this error in plain text.
error	error.type	keyword	java.lang.NullPointerException	The type of the error, for example the class name of the exception.
event	event.action	keyword	user-password-change	The action captured by the event.
event	event.agent_id	keyword	verified	Validation status of the event's agent ID field.
event	event.category	keyword	authentication	Event category. The second categorization field in the hierarchy.
event	event.code	keyword		4648 Identification code for this event.
event	event.created	date	2016-05-23T08:05:34.857Z	Time when the event was first read by an agent or by your pipeline.
event	event.dataset	keyword	apache.access	Name of the dataset.
event	event.duration	long		Duration of the event in nanoseconds.
event	event.end	date		'event.end' contains the date when the event ended or when the activity was last observed.
event	event.hash	keyword	123456789012345678901234567890ABCD	Hash (perhaps logstash fingerprint) of raw field to be able to demonstrate log integrity.
event	event.id	keyword	8a4f500e	Unique ID to describe the event.
event	event.ingested	date	2016-05-23T08:05:35.101Z	Timestamp when an event arrived in the central data store.
event	event.kind	keyword	alert	The kind of the event. The highest categorization field in the hierarchy.
event	event.module	keyword	apache	Name of the module this data is coming from.
event	event.original	keyword	Sep 19 08:26:10 local CEFO|Security|threatmanager|1.0|100|worm successfully stopped|10|src=10.0.0.1 dst=2.1.2.2 spt=1232	Raw text message of entire event.
event	event.outcome	keyword	success	The outcome of the event. The lowest level categorization field in the hierarchy.
event	event.provider	keyword	kernel	Source of the event.
event	event.reason	keyword	Terminated an unexpected process	Reason why this event happened, according to the source
event	event.reference	keyword	https://system.example.com/event/H0001234	Event reference URL.
event	event.risk_score	float		Risk score or priority of the event (e.g. security solutions). Use your system's original value here.
event	event.risk_score	float		Normalized risk score or priority of the event (0-100).
event	event.sequence	long		Sequence number of the event.
event	event.severity	long		7 Numeric severity of the event.

event	event.start	date			'event.start' contains the date when the event started or when the activity was first observed.
event	event.timezone	keyword			Event time zone.
event	event.type	keyword			Event type. The third categorization field in the hierarchy.
event	event.url	keyword			Event investigation URL.
faas	faas.coldstart	boolean		https://mysystem.example.com/alert/5271?dedb-f5b0-4218-8700-4ac4879a38fe	Boolean value indicating a cold start of a function.
faas	faas.execution	keyword	af1d5aa4-a685-4c5f-a22b-44480b3cc28		The execution ID of the current function execution.
faas	faas.id	keyword	am.aws.lambda.us-west-2:123456789012:function:my-function		The unique identifier of a serverless function.
faas	faas.name	keyword	my-function		The name of a serverless function.
faas	faas.trigger.request	keyword		123456789	The ID of the trigger request , message, event, etc.
faas	faas.trigger.type	keyword	http		The trigger for the function execution.
faas	faas.version	keyword		123	The version of a serverless function.
file	file.accessed	date			Last time the file was accessed.
file	file.attributes	keyword	["readonly", "system"]		Array of file attributes.
file	file.code_signature	keyword	sha256		Hashing algorithm used to sign the process.
file	file.code_signature	boolean		TRUE	Boolean to capture if a signature is present.
file	file.code_signature	keyword		570522385	Code signing flags of the process
file	file.code_signature	keyword	com.apple.xpc.proxy		The identifier used to sign the process.
file	file.code_signature	keyword	ERROR_UNTRUSTED_ROOT		Additional information about the certificate status.
file	file.code_signature	keyword	Microsoft Corporation		Subject name of the code signer
file	file.code_signature	keyword	ECHCZ88MAV		The team identifier used to sign the process.
file	file.code_signature	date	2021-01-01T12:10:30Z		When the signature was generated and signed.
file	file.code_signature	boolean		TRUE	Stores the trust status of the certificate chain.
file	file.code_signature	boolean		TRUE	Boolean to capture if the digital signature is verified against the binary content.
file	file.created	date			File creation time.
file	file.ctime	date			Last time the file attributes or metadata changed.
file	file.device	keyword	sda		Device that is the source of the file.
file	file.directory	keyword	/home/alice		Directory where the file is located.
file	file.drive_letter	keyword	C		Drive letter where the file is located.
file	file.elf.architecture	keyword	x86_64		Machine architecture of the ELF file.
file	file.elf.byte_order	keyword	Little Endian		Byte sequence of ELF file.
file	file.elf.cpu_type	keyword	Intel		CPU type of the ELF file.
file	file.elf.creation_date				Build or compile date.
file	file.elf.exports	flattened			List of exported element names and types.
file	file.elf.go_import	keyword	10bddcb4cee4208076c88d9f9564491		A hash of the Go language imports in an ELF file.
file	file.elf.go_import	flattened			List of imported Go language element names and types.
file	file.elf.go_import	long			Shannon entropy calculation from the list of Go imports.
file	file.elf.go_import	long			Variance for Shannon entropy calculation from the list of Go imports.
file	file.elf.go_stripped	boolean			Whether the file is a stripped or obfuscated Go executable.
file	file.elf.header.abi	keyword			Version of the ELF Application Binary Interface (ABI).
file	file.elf.header.class	keyword			Header class of the ELF file.
file	file.elf.header.dta	keyword			Data table of the ELF header.
file	file.elf.header.ent	long			Header entypoint of the ELF file.
file	file.elf.header.obj	keyword			"0x1" for original ELF files.
file	file.elf.header.os	keyword			Application Binary Interface (ABI) of the Linux OS.
file	file.elf.header.type	keyword			Header type of the ELF file.
file	file.elf.header.version	keyword			Version of the ELF header.
file	file.elf.import_hai	keyword	d41d8cd98f0b204e9800998ecf8427e		A hash of the imports in an ELF file.
file	file.elf.imports	flattened			List of imported element names and types.
file	file.elf.imports	long			Shannon entropy calculation from the list of imported element names and types.
file	file.elf.imports	long			Variance for Shannon entropy calculation from the list of imported element names and types.
file	file.elf.sections	nested			Section information of the ELF file.
file	file.elf.sections.c	long			Chi-square probability distribution of the section .
file	file.elf.sections.e	long			Shannon entropy calculation from the section.
file	file.elf.sections.fl	keyword			ELF Section List flags.
file	file.elf.sections.g	keyword			ELF Section List name.
file	file.elf.sections.pl	keyword			ELF Section List offset.
file	file.elf.sections.pl	long			ELF Section List physical size.
file	file.elf.sections.ty	keyword			ELF Section List type.
file	file.elf.sections.vi	long			Variance for Shannon entropy calculation from the section.
file	file.elf.sections.vi	long			ELF Section List virtual address.
file	file.elf.sections.vi	long			ELF Section List virtual size.
file	file.elf.segments	nested			ELF object segment list.
file	file.elf.segments	keyword			ELF object segment sections.
file	file.elf.segments	keyword			ELF object segment type.
file	file.elf.shared_lib	keyword			List of shared libraries used by this ELF object.
file	file.elf.tefhash	keyword			tefhash hash for ELF file.
file	file.extension	keyword	png		File extension, excluding the leading dot.
file	file.fork_name	keyword	Zone.Identifier		A fork is additional data associated with a filesystem object.
file	file.gid	keyword		100	Primary group ID (GID) of the file.
file	file.group	keyword	alice		Primary group name of the file.
file	file.hash.cdhash	keyword	3783b4052f6474db30676b45c329e7a6d44acd9		The Code Directory (CD) hash of an executable.
file	file.hash.md5	keyword			MD5 hash.
file	file.hash.sha1	keyword			SHA1 hash.
file	file.hash.sha256	keyword			SHA256 hash.
file	file.hash.sha384	keyword			SHA384 hash.
file	file.hash.sha512	keyword			SHA512 hash.
file	file.hash.sosep	keyword			SOSEEP hash.
file	file.hash.tlsh	keyword			TLSh hash.
file	file.inode	keyword		256383	Inode representing the file in the filesystem.
file	file.macho.go_im	keyword	10bddcb4cee4208076c88d9f9564491		A hash of the Go language imports in a Mach-O file.
file	file.macho.go_im	flattened			List of imported Go language element names and types.
file	file.macho.go_im	long			Shannon entropy calculation from the list of Go imports.
file	file.macho.go_im	long			Variance for Shannon entropy calculation from the list of Go imports.
file	file.macho.go_is	boolean			Whether the file is a stripped or obfuscated Go executable.
file	file.macho.import	keyword	d41d8cd98f0b204e9800998ecf8427e		A hash of the imports in a Mach-O file.
file	file.macho.import	flattened			List of imported element names and types.
file	file.macho.import	long			Shannon entropy calculation from the list of imported element names and types.
file	file.macho.import	long			Variance for Shannon entropy calculation from the list of imported element names and types.
file	file.macho.sectio	nested			Section information of the Mach-O file.
file	file.macho.sectio	long			Shannon entropy calculation from the section.
file	file.macho.sectio	keyword			Mach-O Section List name.
file	file.macho.sectio	long			Mach-O Section List physical size.
file	file.macho.sectio	long			Variance for Shannon entropy calculation from the section.
file	file.macho.sectio	long			Mach-O Section List virtual size. This is always the same as 'physical_size'.
file	file.macho.synthi	keyword	d3ccf195b62a92793c3c19af1080497ec		A hash of the imports in a Mach-O file.
file	file.mime_type	keyword			Media type of file, document, or arrangement of bytes.
file	file.mode	keyword		640	Mode of the file in octal representation.
file	file.mtime	date			Last time the file content was modified.
file	file.name	keyword	example.png		Name of the file including the extension, without the directory.
file	file.owner	keyword	alice		File owner's username.
file	file.path	keyword	/home/alice/example.png		Full path to the file, including the file name.
file	file.path.text	match_only_text	/home/alice/example.png		Full path to the file, including the file name.
file	file.pe.architecture	keyword	x64		CPU architecture target for the file.
file	file.pe.company	keyword	Microsoft Corporation		Internal company name of the file, provided at compile-time.
file	file.pe.descriptor	keyword	Paint		Internal description of the file, provided at compile-time.
file	file.pe.file_version	keyword	6.3.9600.17415		Process name.
file	file.pe.go_import	keyword	10bddcb4cee4208076c88d9f9564491		A hash of the Go language imports in a PE file.
file	file.pe.go_import	flattened			List of imported Go language element names and types.
file	file.pe.go_import	long			Shannon entropy calculation from the list of Go imports.
file	file.pe.go_import	long			Variance for Shannon entropy calculation from the list of Go imports.
file	file.pe.go_stripped	boolean			Whether the file is a stripped or obfuscated Go executable.
file	file.pe.imphash	keyword	0c8803c4e922103c40ca5963aad36ddf		A hash of the imports in a PE file.
file	file.pe.import_ha	keyword	d41d8cd98f0b204e9800998ecf8427e		A hash of the imports in a PE file.
file	file.pe.imports	flattened			List of imported element names and types.
file	file.pe.imports	long			Shannon entropy calculation from the list of imported element names and types.
file	file.pe.imports	long			Variance for Shannon entropy calculation from the list of imported element names and types.
file	file.pe.original_file	keyword	MSPaint.EXE		Internal name of the file, provided at compile-time.
file	file.pe.peshash	keyword	73f1f89b630d6be375a7f25179a38d347651975		A hash of the PE header and data from one or more PE sections.
file	file.pe.product	keyword	Microsoft® Windows® Operating System		Internal product name of the file, provided at compile-time.
file	file.pe.sections	nested			Section information of the PE file.
file	file.pe.sections.e	long			Shannon entropy calculation from the section.
file	file.pe.sections.g	keyword			PE Section List name.
file	file.pe.sections.p	long			PE Section List physical size.
file	file.pe.sections.vi	long			Variance for Shannon entropy calculation from the section.
file	file.pe.sections.vi	long			PE Section List virtual size. This is always the same as 'physical_size'.
file	file.size	long		16384	File size in bytes.
file	file.target_path	keyword			Target path for symlinks.
file	file.target_path.text	match_only_text			Target path for symlinks.
file	file.type	keyword	file		File type (file, dir, or symlink).
file	file.uid	keyword		1001	The user ID (UID) or security identifier (SID) of the file owner.

file	file.x509.alternati	keyword	*.elastic.co	List of subject alternative names (SAN).
file	file.x509.issuer.o	keyword	Example SHA2 High Assurance Server CA	List of common name (CN) of issuing certificate authority.
file	file.x509.issuer.o	keyword	US	List of country (C) codes
file	file.x509.issuer.o	keyword	C=US, O=Example Inc. OU=www.example.com, CN=Example SHA2 High Assurance Server CA	Distinguished name (DN) of issuing certificate authority.
file	file.x509.issuer.o	keyword	Mountain View	List of locality names (L)
file	file.x509.issuer.o	keyword	Example Inc	List of organizations (O) of issuing certificate authority.
file	file.x509.issuer.o	keyword	www.example.com	List of organizational units (OU) of issuing certificate authority.
file	file.x509.issuer.sr	keyword	California	List of state or province names (ST, S, or P)
file	file.x509.not_after	date	2020-07-16T03:15:36Z	Time at which the certificate is no longer considered valid.
file	file.x509.not_before	date	2019-08-16T01:40:25Z	Time at which the certificate is first considered valid.
file	file.x509.public_k	keyword	RSA	Algorithm used to generate the public key.
file	file.x509.public_k	keyword	rsa2561	The curve used by the elliptic curve public key. This is algorithm specific.
file	file.x509.public_k	long		65537 Exponent used to derive the public key. This is algorithm specific.
file	file.x509.public_k	long		2048 The size of the public key space in bits.
file	file.x509.serial_n	keyword	55FB89C7DEBF09809D12CCAA	Unique serial number issued by the certificate authority.
file	file.x509.signatur	keyword	SHA256-RSA	Identifier for certificate signature algorithm.
file	file.x509.subject	keyword	shared.global.example.net	List of common names (CN) of subject.
file	file.x509.subject	keyword	US	List of country (C) code
file	file.x509.subject	keyword	C=US, ST=California, L=San Francisco, O=Example, Inc., CN=shared.global.example.net	Distinguished name (DN) of the certificate subject entity.
file	file.x509.subject	keyword	San Francisco	List of locality names (L)
file	file.x509.subject	keyword	Example, Inc.	List of organizations (O) of subject.
file	file.x509.subject	keyword		List of organizational units (OU) of subject.
file	file.x509.subject	keyword	California	List of state or province names (ST, S, or P)
file	file.x509.version	keyword		3 Version of x509 format.
group	group.domain	keyword		Name of the directory the group is a member of.
group	group.id	keyword		Unique identifier for the group on the system/platform.
group	group.name	keyword		Name of the group.
host	host.architecture	keyword	x86_64	Operating system architecture.
host	host.boot.id	keyword	88a1f0ed-5ae5-41ee-af6b-41921c311872	Linux boot uuid taken from /proc/sys/kernel/random/boot_id
host	host.cpu.usage	scaled_float		Percent CPU used, between 0 and 1.
host	host.disk.read.by	long		The number of bytes read by all disks.
host	host.disk.write.by	long		The number of bytes written on all disks.
host	host.domain	keyword	CONTOSO	Name of the directory the group is a member of.
host	host.geo.city_nar	keyword	Montreal	City name.
host	host.geo.continent	keyword	NA	Continent code.
host	host.geo.continent	keyword	North America	Name of the continent.
host	host.geo.country	keyword	CA	Country ISO code.
host	host.geo.country	keyword	Canada	Country name.
host	host.geo.location.geo_point		{ "lon": -73.614830, "lat": 45.505918 }	Longitude and latitude.
host	host.geo.name	keyword	boston-dc	User-defined description of a location.
host	host.geo.postal_k	keyword		94040 Postal code.
host	host.geo.region_k	keyword	CA-QC	Region ISO code.
host	host.geo.region_k	keyword	Quebec	Region name.
host	host.geo.timezone	keyword	America/Argentina/Buenos_Aires	Time zone.
host	host.hostname	keyword		Hostname of the host.
host	host.id	keyword		Unique host id.
host	host.ip	ip		Host ip addresses.
host	host.mac	keyword	["00-00-5E-00-53-23", "00-00-5E-00-53-24"]	Host MAC addresses.
host	host.name	keyword		Name of the host.
host	host.network.egm	long		The number of bytes sent on all network interfaces.
host	host.network.egm	long		The number of packets sent on all network interfaces.
host	host.network.ing	long		The number of bytes received on all network interfaces.
host	host.network.ing	long		The number of packets received on all network interfaces.
host	host.os.family	keyword	debian	OS family (such as redhat, debian, freebsd, windows).
host	host.os.full	keyword	Mac OS Mojave	Operating system name, including the version or code name.
host	host.os.full.text	match_only_text	Mac OS Mojave	Operating system name, including the version or code name.
host	host.os.kernel	keyword	4.4.0-112-generic	Operating system kernel version as a raw string.
host	host.os.name	keyword	Mac OS X	Operating system name, without the version.
host	host.os.name.text	match_only_text	Mac OS X	Operating system name, without the version.
host	host.os.platform	keyword	darwin	Operating system platform (such as centos, ubuntu, windows).
host	host.os.type	keyword	macos	Which commercial OS family (one of: linux, macos, unix, windows, ios or android).
host	host.os.version	keyword	10.14.1	Operating system version as a raw string.
host	host.pid_ns_ino	keyword		256383 Pid namespace inode
host	host.risk.calculate	keyword	High	A risk classification level calculated by an internal system as part of entity analytics and entity risk scoring.
host	host.risk.calculate	float		880.73 A risk classification score calculated by an internal system as part of entity analytics and entity risk scoring.
host	host.risk.calculate	float		88.73 A normalized risk score calculated by an internal system.
host	host.risk.static_le	keyword	High	A risk classification level obtained from outside the system, such as from some external Threat Intelligence Platform.
host	host.risk.static_s	float		830 A risk classification score obtained from outside the system, such as from some external Threat Intelligence Platform.
host	host.risk.static_s	float		83 A normalized risk score calculated by an external system.
host	host.type	keyword		Type of host.
host	host.uptime	long		1325 Seconds the host has been up.
http	http.request.body	long		887 Size in bytes of the request body.
http	http.request.body.wildcard		Hello world	The full HTTP request body.
http	http.request.body.match_only_text		Hello world	The full HTTP request body.
http	http.request.body	long		1437 Total size in bytes of the request (body and headers).
http	http.request.id	keyword	123e4567-e89b-1203-a456-426614174000	HTTP request ID.
http	http.request.method	keyword	POST	HTTP request method.
http	http.request.mime	keyword	image/gif	Mime type of the body of the request.
http	http.request.referrer	keyword	https://blog.example.com/	Referrer for this HTTP request.
http	http.response.bo	long		887 Size in bytes of the response body.
http	http.response.bo.wildcard		Hello world	The full HTTP response body.
http	http.response.bo.match_only_text		Hello world	The full HTTP response body.
http	http.response.bo	long		1437 Total size in bytes of the response (body and headers).
http	http.response.ms	keyword	image/gif	Mime type of the body of the response.
http	http.response.asa	long		404 HTTP response status code.
http	http.version	keyword		1.1 HTTP version.
log	log.file.path	keyword	/var/log/fun-times.log	Full path to the log file this event came from.
log	log.level	keyword	error	Log level of the log event.
log	log.logger	keyword	org.elasticsearch.bootstrap.Bootstrap	Name of the logger.
log	log.origin.file.line	long		42 The line number of the file which originated the log event.
log	log.origin.file.name	keyword	Bootstrap.java	The code file which originated the log event.
log	log.origin.function	keyword	init	The function which originated the log event.
log	log.syslog	object		Syslog metadata
log	log.syslog.appna	keyword	sshd	The device or application that originated the Syslog message.
log	log.syslog.facility	long		23 Syslog numeric facility of the event.
log	log.syslog.facility	keyword	local7	Syslog text-based facility of the event.
log	log.syslog.hostname	keyword	example-host	The host that originated the Syslog message.
log	log.syslog.msgid	keyword	ID47	An identifier for the type of Syslog message.
log	log.syslog.priority	long		135 Syslog priority of the event.
log	log.syslog.procid	keyword		12345 The process name or ID that originated the Syslog message.
log	log.syslog.severity	long		3 Syslog numeric severity of the event.
log	log.syslog.severity	keyword	Error	Syslog text-based severity of the event.
log	log.syslog.struct.flattened			Structured data expressed in RFC 5424 messages.
log	log.syslog.version	keyword		1 Syslog protocol version.
network	network.application	keyword	aim	Application level protocol name.
network	network.bytes	long		368 Total bytes transferred in both directions.
network	network.communication	keyword	170+N4H+MGSMY/8hIXPqo4ZQz0=	A hash of source and destination IPs and ports.
network	network.direction	keyword	inbound	Direction of the network traffic.
network	network.forward.ip	keyword	192.1.1.2	Host IP address when the source IP address is the proxy.
network	network.iana_nu	keyword		6 IANA Protocol Number.
network	network.inner	object		Inner VLAN tag information
network	network.inner.via	keyword		10 VLAN ID as reported by the observer.
network	network.inner.via	keyword	outside	Optional VLAN name as reported by the observer.
network	network.name	keyword	Guest Wifi	Name given by operators to sections of their network.
network	network.packets	long		24 Total packets transferred in both directions.
network	network.protocol	keyword	http	Application protocol name.
network	network.transport	keyword	tcp	Protocol Name corresponding to the field 'iana_number'.
network	network.type	keyword	ipv4	In the OSI Model this would be the Network Layer: ipv4, ipv6, ipsec, pim, etc
network	network.vlan.id	keyword		10 VLAN ID as reported by the observer.
network	network.vlan.name	keyword	outside	Optional VLAN name as reported by the observer.
observer	observer.egress	object		Object field for egress information
observer	observer.egress	keyword	outside	Interface alias
observer	observer.egress	keyword		10 Interface ID
observer	observer.egress	keyword	eth0	Interface name
observer	observer.egress	keyword		10 VLAN ID as reported by the observer.
observer	observer.egress	keyword	outside	Optional VLAN name as reported by the observer.
observer	observer.egress	keyword	Public_Internet	Observer Egress zone
observer	observer.geo.city	keyword	Montreal	City name.
observer	observer.geo.cor	keyword	NA	Continent code.
observer	observer.geo.cor	keyword	North America	Name of the continent.

observer	observer.geo.coi	keyword	CA		Country ISO code.
observer	observer.geo.coi	keyword	Canada		Country name.
observer	observer.geo.loc_geo_point		{ "lon": -73.614830, "lat": 45.505918 }		Longitude and latitude.
observer	observer.geo.loc	keyword	boston-dc		User-defined description of a location.
observer	observer.geo.pci	keyword			Postal code.
observer	observer.geo.reg	keyword	CA-QC	94040	Region ISO code.
observer	observer.geo.reg	keyword	Quebec		Region name.
observer	observer.geo.tlm	keyword	America/Argentina/Buenos_Aires		Time zone.
observer	observer.hostname	keyword			Hostname of the observer.
observer	observer.ingress	object			Object field for ingress information
observer	observer.ingress	keyword	outside		Interface alias
observer	observer.ingress	keyword		10	Interface ID
observer	observer.ingress	keyword	eth0		Interface name
observer	observer.ingress	keyword		10	VLAN ID as reported by the observer.
observer	observer.ingress	keyword	outside		Optional VLAN name as reported by the observer.
observer	observer.ingress	keyword	DMZ		Observer ingress zone
observer	observer.ip	ip			IP addresses of the observer.
observer	observer.ip	ip			MAC addresses of the observer.
observer	observer.mac	keyword	["00-00-5E-00-53-23", "00-00-5E-00-53-24"]		Custom name of the observer.
observer	observer.name	keyword	1_proxySG		OS family (such as redhat, debian, freebsd, windows).
observer	observer.os.family	keyword	debian		Operating system name, including the version or code name.
observer	observer.os.ful	keyword	Mac OS Mojave		Operating system name, including the version or code name.
observer	observer.os.ful.k.match_only_text		Mac OS Mojave		Operating system kernel version as a raw string.
observer	observer.os.kern	keyword	4.4.0-112-generic		Operating system name, without the version.
observer	observer.os.name	keyword	Mac OS X		Operating system name, without the version.
observer	observer.os.name.match_only_text		Mac OS X		Operating system platform (such centos, ubuntu, windows).
observer	observer.os.platform	keyword	darwin		Which commercial OS family (one of: linux, macos, unix, windows, ios or android).
observer	observer.os.type	keyword	macos		Operating system version as a raw string.
observer	observer.os.vers	keyword	10.14.1		The product name of the observer.
observer	observer.product	keyword	s200		Observer serial number.
observer	observer.serial_n	keyword			The type of the observer the data is coming from.
observer	observer.type	keyword	firewall		Vendor name of the observer.
observer	observer.vendor	keyword	Symantec		Observer version.
observer	observer.version	keyword			API version being used to carry out the action
orchestrator	orchestrator.api	keyword	v1beta1		Unique ID of the cluster.
orchestrator	orchestrator.cluster	keyword			Name of the cluster.
orchestrator	orchestrator.cluster	keyword			URL of the API used to manage the cluster.
orchestrator	orchestrator.cluster	keyword			The version of the cluster.
orchestrator	orchestrator.name	keyword	kube-system		Namespace in which the action is taking place.
orchestrator	orchestrator.orga	keyword	elastic		Organization affected by the event (for multi-tenant orchestrator setups).
orchestrator	orchestrator.reso	keyword	[key1: value1, key2: value2, key3: value3]		The list of annotations added to the resource.
orchestrator	orchestrator.reso	keyword			Unique ID of the resource being acted upon.
orchestrator	orchestrator.reso	keyword			IP address assigned to the resource associated with the event being observed.
orchestrator	orchestrator.reso	keyword	[key1: value1, key2: value2, key3: value3]		The list of labels added to the resource.
orchestrator	orchestrator.reso	keyword	test-pod-otods		Name of the resource being acted upon.
orchestrator	orchestrator.reso	keyword	DaemonSet		Type or kind of the parent resource associated with the event being observed.
orchestrator	orchestrator.reso	keyword	service		Type of resource being acted upon.
orchestrator	orchestrator.type	keyword	kubernetes		Orchestrator cluster type (e.g. kubernetes, nomad or cloudfoundry).
organization	organization.id	keyword			Unique identifier for the organization.
organization	organization.name	keyword			Organization name.
organization	organization.name.match_only_text				Organization name.
package	package.architec	keyword	x86_64		Package architecture.
package	package.build_v	keyword	354f7c89d4d61b0988b12ec000b8996867710cd		Build version information
package	package.checks	keyword	68b3294e983e34099c7d8ad5c0b2940		Checksum of the installed package for verification.
package	package.description	keyword	Open source programming language to build simple/reliable/efficient software.		Description of the package.
package	package.install_g	keyword	global		Indicating how the package was installed, e.g. user-local, global.
package	package.installec	date			Time when package was installed.
package	package.license	keyword	Apache License 2.0		Package license
package	package.name	keyword	go		Package name
package	package.path	keyword	/usr/local/Cellar/go/1.12.9/		Path where the package is installed.
package	package.referece	keyword	https://golang.org		Package home page or reference URL
package	package.size	long		62231	Package size in bytes.
package	package.type	keyword	rpm		Package type
package	package.version	keyword	1.12.9		Package version
process	process.args	keyword	["usr/bin/ssh", "-i", "user", "10.0.0.16"]		Array of process arguments.
process	process.args_coi	long			4 Length of the process.args array.
process	process.code_sig	keyword	sha256		Hashing algorithm used to sign the process.
process	process.code_sig	boolean		TRUE	Boolean to capture if a signature is present.
process	process.code_sig	keyword		570522386	Code signing flags of the process.
process	process.code_sig	keyword	com.apple.xpc.proxy		The identifier used to sign the process.
process	process.code_sig	keyword	ERROR_UNTRUSTED_ROOT		Additional information about the certificate status.
process	process.code_sig	keyword	Microsoft Corporation		Subject name of the code signer
process	process.code_sig	keyword	EQHXZ8MBAV		The team identifier used to sign the process.
process	process.code_sig	date	2021-01-01T11:12:10.30Z		When the signature was generated and signed.
process	process.code_sig	boolean		TRUE	Stores the trust status of the certificate chain.
process	process.code_sig	boolean		TRUE	Boolean to capture if the digital signature is verified against the binary content.
process	process.command	keyword	/usr/bin/ssh -i user 10.0.0.16		Full command line that started the process.
process	process.command.match_only_text		/usr/bin/ssh -i user 10.0.0.16		Full command line that started the process.
process	process.ef.archi	keyword	x86-64		Machine architecture of the ELF file.
process	process.ef.byte	keyword	Little Endian		Byte sequence of ELF file.
process	process.ef.cpu	keyword	Intel		CPU type of the ELF file.
process	process.ef.create	date			Build or compile date.
process	process.ef.expor	flattened			List of exported element names and types.
process	process.ef.go_in	keyword	10bdc5b4cee42080f76c88d9f9564491		A hash of the Go language imports in an ELF file.
process	process.ef.go_in	flattened			List of imported Go language element names and types.
process	process.ef.go_in	long			Shannon entropy calculation from the list of Go imports.
process	process.ef.go_in	long			Variance for Shannon entropy calculation from the list of Go imports.
process	process.ef.go_at	boolean			Whether the file is a stripped or obfuscated Go executable.
process	process.ef.head	keyword			Version of the ELF Application Binary Interface (ABI).
process	process.ef.head	keyword			Header class of the ELF file.
process	process.ef.head	keyword			Data table of the ELF header.
process	process.ef.head	keyword			Header endpoint of the ELF file.
process	process.ef.head	keyword			"0x1" for original ELF files.
process	process.ef.head	keyword			Application Binary Interface (ABI) of the Linux OS.
process	process.ef.head	keyword			Header type of the ELF file.
process	process.ef.head	keyword			Version of the ELF header.
process	process.ef.impor	keyword	d41dbcd98f0b204e9800998ecf8427e		A hash of the imports in an ELF file.
process	process.ef.impor	flattened			List of imported element names and types.
process	process.ef.impor	long			Shannon entropy calculation from the list of imported element names and types.
process	process.ef.impor	long			Variance for Shannon entropy calculation from the list of imported element names and types.
process	process.ef.secti	nested			Section information of the ELF file.
process	process.ef.secti	long			Chi-square probability distribution of the section.
process	process.ef.secti	long			Shannon entropy calculation from the section.
process	process.ef.secti	keyword			ELF Section List flags.
process	process.ef.secti	keyword			ELF Section List name.
process	process.ef.secti	keyword			ELF Section List offset.
process	process.ef.secti	long			ELF Section List physical size.
process	process.ef.secti	keyword			ELF Section List type.
process	process.ef.secti	long			Variance for Shannon entropy calculation from the section.
process	process.ef.secti	long			ELF Section List virtual address.
process	process.ef.secti	long			ELF Section List virtual size.
process	process.ef.segm	nested			ELF object segment list.
process	process.ef.segm	keyword			ELF object segment sections.
process	process.ef.segm	keyword			ELF object segment type.
process	process.ef.share	keyword			List of shared libraries used by this ELF object.
process	process.ef.tefha	keyword			tefhash hash for ELF file.
process	process.end	date	2016-05-23T08:05:34.853Z		The time the process ended.
process	process.entry_id	keyword	c2a455d999375d		Unique identifier for the process.
process	process.entry_le	keyword	["usr/bin/ssh", "-i", "user", "10.0.0.16"]		Array of process arguments.
process	process.entry_le	long			4 Length of the process.args array.
process	process.entry_le	keyword			Name of the group.
process	process.entry_le	keyword	S-1-5-21-2024249127872692429404-2351956786-1000		Unique identifier of the user.
process	process.entry_le	keyword	a.einstein		Short name or login of the user.
process	process.entry_le.match_only_text		a.einstein		Short name or login of the user.
process	process.entry_le.wildcard		/usr/bin/ssh -i user 10.0.0.16		Full command line that started the process.
process	process.entry_le.match_only_text		/usr/bin/ssh -i user 10.0.0.16		Full command line that started the process.
process	process.entry_le	keyword	c2a455d999375d		Unique identifier for the process.
process	process.entry_le	ip			IP address of the source.
process	process.entry_le	keyword			The entry type for the entry session leader.
process	process.entry_le	keyword	/usr/bin/ssh		Absolute path to the process executable.

	process.entry.le.match_only_text	/usr/bin/sh			Absolute path to the process executable.
process	process.entry.le.keyword				Unique identifier for the group on the system/platform.
process	process.entry.le.keyword				Name of the group.
process	process.entry.le.boolean		TRUE		Whether the process is connected to an interactive shell.
process	process.entry.le.keyword	ssh			Process name.
process	process.entry.le.match_only_text	ssh			Process name.
process	process.entry.le.keyword	c2c455d9f99375d			Unique identifier for the process.
process	process.entry.le.long			4242	Process id.
process	process.entry.le.keyword	c2c455d9f99375d			Unique identifier for the process.
process	process.entry.le.long			4242	Process id.
process	process.entry.le.date	2016-05-23T08:05:34.853Z			The time the process started.
process	process.entry.le.long			4242	Virtual process id.
process	process.entry.le.date	2016-05-23T08:05:34.853Z			The time the process started.
process	process.entry.le.long			4242	Virtual process id.
process	process.entry.le.long			4242	Process id.
process	process.entry.le.keyword				Unique identifier for the group on the system/platform.
process	process.entry.le.keyword				Name of the group.
process	process.entry.le.keyword	S-1-5-21-202424912787-2692429404-2351956786-1000			Unique identifier of the user.
process	process.entry.le.keyword	a.einstein			Short name or login of the user.
process	process.entry.le.match_only_text	a.einstein			Short name or login of the user.
process	process.entry.le.boolean		TRUE		This boolean is used to identify if a leader process is the same as the top level process.
process	process.entry.le.keyword				Unique identifier for the group on the system/platform.
process	process.entry.le.keyword				Name of the group.
process	process.entry.le.keyword	S-1-5-21-202424912787-2692429404-2351956786-1000			Unique identifier of the user.
process	process.entry.le.keyword	a.einstein			Short name or login of the user.
process	process.entry.le.match_only_text	a.einstein			Short name or login of the user.
process	process.entry.le.date	2016-05-23T08:05:34.853Z			The time the process started.
process	process.entry.le.keyword				Unique identifier for the group on the system/platform.
process	process.entry.le.keyword				Name of the group.
process	process.entry.le.object				Information about the controlling TTY device.
process	process.entry.le.long			4	The TTY character device's major number.
process	process.entry.le.long			1	The TTY character device's minor number.
process	process.entry.le.keyword	S-1-5-21-202424912787-2692429404-2351956786-1000			Unique identifier of the user.
process	process.entry.le.keyword	a.einstein			Short name or login of the user.
process	process.entry.le.match_only_text	a.einstein			Short name or login of the user.
process	process.entry.le.long			4242	Virtual process id.
process	process.entry.le.keyword	/home/alice			The working directory of the process.
process	process.entry.le.match_only_text	/home/alice			The working directory of the process.
process	process.env_var.keyword	[\"PATH=/usr/local/bin:/usr/bin\", \"USER=ubuntu\"]			Array of environment variable bindings.
process	process.executable.keyword	/usr/bin/sh			Absolute path to the process executable.
process	process.executable.match_only_text	/usr/bin/sh			Absolute path to the process executable.
process	process.exit_code.long			137	The exit code of the process.
process	process.group_id.keyword				Unique identifier for the group on the system/platform.
process	process.group_id.keyword				Name of the group.
process	process.group_id.keyword	[\"/usr/bin/shsh\", \"-t\", \"user\", \"10.0.0.16\"]			Array of process arguments.
process	process.group_id.long			4	Length of the process.args array.
process	process.group_id.wildcard	/usr/bin/sh -i user 10.0.0.16			Full command line that started the process.
process	process.group_id.match_only_text	/usr/bin/sh -i user 10.0.0.16			Full command line that started the process.
process	process.group_id.keyword	c2c455d9f99375d			Unique identifier for the process.
process	process.group_id.keyword	/usr/bin/sh			Absolute path to the process executable.
process	process.group_id.match_only_text	/usr/bin/sh			Absolute path to the process executable.
process	process.group_id.keyword				Unique identifier for the group on the system/platform.
process	process.group_id.keyword				Name of the group.
process	process.group_id.boolean		TRUE		Whether the process is connected to an interactive shell.
process	process.group_id.keyword	ssh			Process name.
process	process.group_id.match_only_text	ssh			Process name.
process	process.group_id.long			4242	Process id.
process	process.group_id.keyword				Unique identifier for the group on the system/platform.
process	process.group_id.keyword				Name of the group.
process	process.group_id.keyword	S-1-5-21-202424912787-2692429404-2351956786-1000			Unique identifier of the user.
process	process.group_id.keyword	a.einstein			Short name or login of the user.
process	process.group_id.match_only_text	a.einstein			Short name or login of the user.
process	process.group_id.boolean		TRUE		This boolean is used to identify if a leader process is the same as the top level process.
process	process.group_id.keyword				Unique identifier for the group on the system/platform.
process	process.group_id.keyword				Name of the group.
process	process.group_id.keyword	S-1-5-21-202424912787-2692429404-2351956786-1000			Unique identifier of the user.
process	process.group_id.keyword	a.einstein			Short name or login of the user.
process	process.group_id.match_only_text	a.einstein			Short name or login of the user.
process	process.group_id.date	2016-05-23T08:05:34.853Z			The time the process started.
process	process.group_id.keyword				Unique identifier for the group on the system/platform.
process	process.group_id.keyword				Name of the group.
process	process.group_id.object				Information about the controlling TTY device.
process	process.group_id.long			4	The TTY character device's major number.
process	process.group_id.long			1	The TTY character device's minor number.
process	process.group_id.keyword	S-1-5-21-202424912787-2692429404-2351956786-1000			Unique identifier of the user.
process	process.group_id.keyword	a.einstein			Short name or login of the user.
process	process.group_id.match_only_text	a.einstein			Short name or login of the user.
process	process.group_id.long			4242	Virtual process id.
process	process.group_id.keyword	/home/alice			The working directory of the process.
process	process.group_id.match_only_text	/home/alice			The working directory of the process.
process	process.hash.cd.keyword	3783b4052fd474dbe30767db45c329e7af6d44acd9			The Code Directory (CD) hash of an executable

process	process.parent.e keyword	x86-64	Machine architecture of the ELF file.
process	process.parent.e keyword	Little Endian	Byte sequence of ELF file.
process	process.parent.e keyword	Intel	CPU type of the ELF file.
process	process.parent.e date		Build or compile date.
process	process.parent.e flattened		List of exported element names and types.
process	process.parent.e keyword	10bddcb4cee4208076c88d9f964491	A hash of the Go language imports in an ELF file.
process	process.parent.e flattened		List of imported Go language element names and types.
process	process.parent.e long		Shannon entropy calculation from the list of Go imports.
process	process.parent.e long		Variance for Shannon entropy calculation from the list of Go imports.
process	process.parent.e boolean		Whether the file is a stripped or obfuscated Go executable.
process	process.parent.e keyword		Version of the ELF Application Binary Interface (ABI).
process	process.parent.e keyword		Header class of the ELF file.
process	process.parent.e keyword		Data table of the ELF header.
process	process.parent.e long		Header endpoint of the ELF file.
process	process.parent.e keyword		"0x1" for original ELF files.
process	process.parent.e keyword		Application Binary Interface (ABI) of the Linux OS.
process	process.parent.e keyword		Header type of the ELF file.
process	process.parent.e keyword		Version of the ELF header.
process	process.parent.e keyword	d41d8cd98f00b204e9800998ecf8427e	A hash of the imports in an ELF file.
process	process.parent.e flattened		List of imported element names and types.
process	process.parent.e long		Shannon entropy calculation from the list of imported element names and types.
process	process.parent.e long		Variance for Shannon entropy calculation from the list of imported element names and types.
process	process.parent.e nested		Section information of the ELF file.
process	process.parent.e long		Chi-square probability distribution of the section.
process	process.parent.e long		Shannon entropy calculation from the section.
process	process.parent.e keyword		ELF Section List flags.
process	process.parent.e keyword		ELF Section List name.
process	process.parent.e keyword		ELF Section List offset.
process	process.parent.e long		ELF Section List physical size.
process	process.parent.e keyword		ELF Section List type.
process	process.parent.e long		Variance for Shannon entropy calculation from the section.
process	process.parent.e long		ELF Section List virtual address.
process	process.parent.e long		ELF Section List virtual size.
process	process.parent.e nested		ELF object segment list.
process	process.parent.e keyword		ELF object segment sections.
process	process.parent.e keyword		ELF object segment type.
process	process.parent.e keyword		List of shared libraries used by this ELF object.
process	process.parent.e keyword		teflhash hash for ELF file.
process	process.parent.e date	2016-05-23T08:05:34.853Z	The time the process ended.
process	process.parent.e keyword	c2c455d999375d	Unique identifier for the process.
process	process.parent.e keyword	/usr/bin/ssh	Absolute path to the process executable.
process	process.parent.e match_only_text	/usr/bin/ssh	Absolute path to the process executable.
process	process.parent.e long		137 The exit code of the process.
process	process.parent.e keyword		Unique identifier for the group on the system/platform.
process	process.parent.g keyword		Name of the group.
process	process.parent.g keyword	c2c455d999375d	Unique identifier for the process.
process	process.parent.g long		4242 Process id.
process	process.parent.g date	2016-05-23T08:05:34.853Z	The time the process started.
process	process.parent.g long		4242 Virtual process id.
process	process.parent.h keyword	3783b4052fd9474dbe30676b45c329e7a644acd9	The Code Directory (CD) hash of an executable.
process	process.parent.h keyword		MD5 hash.
process	process.parent.h keyword		SHA1 hash.
process	process.parent.h keyword		SHA256 hash.
process	process.parent.h keyword		SHA384 hash.
process	process.parent.h keyword		SHA512 hash.
process	process.parent.h keyword		SSDEEP hash.
process	process.parent.h keyword		TLSH hash.
process	process.parent.ir boolean	TRUE	Whether the process is connected to an interactive shell.
process	process.parent.n keyword	10bddcb4cee4208076c88d9f964491	A hash of the Go language imports in a Mach-O file.
process	process.parent.n flattened		List of imported Go language element names and types.
process	process.parent.n long		Shannon entropy calculation from the list of Go imports.
process	process.parent.n long		Variance for Shannon entropy calculation from the list of Go imports.
process	process.parent.n boolean		Whether the file is a stripped or obfuscated Go executable.
process	process.parent.n keyword	d41d8cd98f00b204e9800998ecf8427e	A hash of the imports in a Mach-O file.
process	process.parent.n flattened		List of imported element names and types.
process	process.parent.n long		Shannon entropy calculation from the list of imported element names and types.
process	process.parent.n long		Variance for Shannon entropy calculation from the list of imported element names and types.
process	process.parent.n nested		Section information of the Mach-O file.
process	process.parent.n long		Shannon entropy calculation from the section.
process	process.parent.n keyword		Mach-O Section List name.
process	process.parent.n long		Mach-O Section List physical size.
process	process.parent.n long		Variance for Shannon entropy calculation from the section.
process	process.parent.n long		Mach-O Section List virtual size. This is always the same as 'physical_size'.
process	process.parent.n keyword	d3ccf195b62a9279c3c19af1080497ec	A hash of the imports in a Mach-O file.
process	process.parent.n keyword		Process name.
process	process.parent.n match_only_text	ssh	Process name.
process	process.parent.p keyword	x64	CPU architecture target for the file.
process	process.parent.p keyword	Microsoft Corporation	Internal company name of the file, provided at compile-time.
process	process.parent.p keyword	Paint	Internal description of the file, provided at compile-time.
process	process.parent.p keyword	6.3.9600.17415	Process name.
process	process.parent.p keyword	10bddcb4cee4208076c88d9f964491	A hash of the Go language imports in a PE file.
process	process.parent.p flattened		List of imported Go language element names and types.
process	process.parent.p long		Shannon entropy calculation from the list of Go imports.
process	process.parent.p long		Variance for Shannon entropy calculation from the list of Go imports.
process	process.parent.p boolean		Whether the file is a stripped or obfuscated Go executable.
process	process.parent.p keyword	0c5803c4e922103c4dca5963aad36d9f	A hash of the imports in a PE file.
process	process.parent.p keyword	d41d8cd98f00b204e9800998ecf8427e	A hash of the imports in a PE file.
process	process.parent.p flattened		List of imported element names and types.
process	process.parent.p long		Shannon entropy calculation from the list of imported element names and types.
process	process.parent.p long		Variance for Shannon entropy calculation from the list of imported element names and types.
process	process.parent.p keyword	MSPAINTEXE	Internal name of the file, provided at compile-time.
process	process.parent.p keyword	73ff189663cd0be375af7f25179e38d347651975	A hash of the PE header and data from one or more PE sections.
process	process.parent.p keyword	Microsoft® Windows® Operating System	Internal product name of the file, provided at compile-time.
process	process.parent.p nested		Section information of the PE file.
process	process.parent.p long		Shannon entropy calculation from the section.
process	process.parent.p keyword		PE Section List name.
process	process.parent.p long		PE Section List physical size.
process	process.parent.p long		Variance for Shannon entropy calculation from the section.
process	process.parent.p long		PE Section List virtual size. This is always the same as 'physical_size'.
process	process.parent.p long		Deprecated identifier of the group of processes the process belongs to.
process	process.parent.p keyword		4242 Process id.
process	process.parent.n keyword		Unique identifier for the group on the system/platform.
process	process.parent.n keyword	S-1-5-21-202424912787-2692429404-2351956786-1000	Name of the group.
process	process.parent.n keyword	a.einstein	Unique identifier of the user.
process	process.parent.n match_only_text	a.einstein	Short name or login of the user.
process	process.parent.e keyword		Short name or login of the user.
process	process.parent.e keyword		Unique identifier for the group on the system/platform.
process	process.parent.e keyword		Name of the group.
process	process.parent.e keyword	S-1-5-21-202424912787-2692429404-2351956786-1000	Unique identifier of the user.
process	process.parent.e keyword	a.einstein	Short name or login of the user.
process	process.parent.e match_only_text	a.einstein	Short name or login of the user.
process	process.parent.s date	2016-05-23T08:05:34.853Z	The time the process started.
process	process.parent.e keyword		Unique identifier for the group on the system/platform.
process	process.parent.e keyword		Name of the group.
process	process.parent.tr keyword	["CAP_BPF", "CAP_SYS_ADMIN"]	Array of capabilities used for permission checks.
process	process.parent.tr keyword	["CAP_BPF", "CAP_SYS_ADMIN"]	Array of capabilities a thread could assume.
process	process.parent.t long		4242 Thread ID.
process	process.parent.t keyword	thread-0	Thread name.
process	process.parent.t keyword		Process title.
process	process.parent.t match_only_text		Process title.
process	process.parent.t object		Information about the controlling TTY device.
process	process.parent.t long		4 The TTY character device's major number.
process	process.parent.t long		1 The TTY character device's minor number.
process	process.parent.u long		1325 Seconds the process has been up.
process	process.parent.u keyword	S-1-5-21-202424912787-2692429404-2351956786-1000	Unique identifier of the user.
process	process.parent.u keyword	a.einstein	Short name or login of the user.
process	process.parent.u match_only_text	a.einstein	Short name or login of the user.
process	process.parent.v long		4242 Virtual process id.
process	process.parent.w keyword	/home/alice	The working directory of the process.
process	process.parent.w match_only_text	/home/alice	The working directory of the process.

process	process.pe.archi keyword	x64	CPU architecture target for the file.
process	process.pe.comp keyword	Microsoft Corporation	Internal company name of the file, provided at compile-time.
process	process.pe.desci keyword	Paint	Internal description of the file, provided at compile-time.
process	process.pe.file_v keyword	6.3.8600.17415	Process name.
process	process.pe.go_in keyword	10bdcdb4cee420807f6c88d9f9564491	A hash of the Go language imports in a PE file.
process	process.pe.go_in_flattened		List of imported Go language element names and types.
process	process.pe.go_in_long		Shannon entropy calculation from the list of Go imports.
process	process.pe.go_in_long		Variance for Shannon entropy calculation from the list of Go imports.
process	process.pe.go_is_boolean		Whether the file is a stripped or obfuscated Go executable.
process	process.pe.imphs keyword	0c6803c4e922103c4dca5963aad36ddf	A hash of the imports in a PE file.
process	process.pe.impoi keyword	d41d8cd98f00b204e9800998ec8427e	A hash of the imports in a PE file.
process	process.pe.impoi_flattened		List of imported element names and types.
process	process.pe.impoi_long		Shannon entropy calculation from the list of imported element names and types.
process	process.pe.impoi_long		Variance for Shannon entropy calculation from the list of imported element names and types.
process	process.pe.origin keyword	MSPAINT.EXE	Internal name of the file, provided at compile-time.
process	process.pe.peha keyword	73ff189b63cd6be375a7f25179a38d347651975	A hash of the PE header and data from one or more PE sections.
process	process.pe.prodi keyword	Microsoft® Windows® Operating System	Internal product name of the file, provided at compile-time.
process	process.pe.sectic nested		Section information of the PE file.
process	process.pe.sectic long		Shannon entropy calculation from the section.
process	process.pe.sectic keyword		PE Section List name.
process	process.pe.sectic long		PE Section List physical size.
process	process.pe.sectic long		Variance for Shannon entropy calculation from the section.
process	process.pe.sectic long		PE Section List virtual size. This is always the same as 'physical_size'.
process	process.pgld long		Deprecated identifier of the group of processes the process belongs to.
process	process.pid long		4242 Process id.
process	process.previous keyword	["usr/bin/ssh", "i", "user", "10.0.0.16"]	Array of process arguments.
process	process.previous long		4 Length of the process.args array.
process	process.previous keyword	/usr/bin/ssh	Absolute path to the process executable.
process	process.previous_match_only_text	/usr/bin/ssh	Absolute path to the process executable.
process	process.real_group keyword		Unique identifier for the group on the system/platform.
process	process.real_group keyword		Name of the group.
process	process.real_user keyword	S-1-5-21-202424912787-2692429404-2351956786-1000	Unique identifier of the user.
process	process.real_user keyword	a.einstein	Short name or login of the user.
process	process.real_user_match_only_text	a.einstein	Short name or login of the user.
process	process.saved_group keyword		Unique identifier for the group on the system/platform.
process	process.saved_group keyword		Name of the group.
process	process.saved_group keyword	S-1-5-21-202424912787-2692429404-2351956786-1000	Unique identifier of the user.
process	process.saved_group keyword	a.einstein	Short name or login of the user.
process	process.saved_group_match_only_text	a.einstein	Short name or login of the user.
process	process.session_keyword	["usr/bin/ssh", "i", "user", "10.0.0.16"]	Array of process arguments.
process	process.session_long		4 Length of the process.args array.
process	process.session_wildcard	/usr/bin/ssh -i user 10.0.0.16	Full command line that started the process.
process	process.session_match_only_text	/usr/bin/ssh -i user 10.0.0.16	Full command line that started the process.
process	process.session_keyword	c2c455d989375d	Unique identifier for the process.
process	process.session_keyword	/usr/bin/ssh	Absolute path to the process executable.
process	process.session_match_only_text	/usr/bin/ssh	Absolute path to the process executable.
process	process.session_keyword		Unique identifier for the group on the system/platform.
process	process.session_keyword		Name of the group.
process	process.session_boolean	TRUE	Whether the process is connected to an interactive shell.
process	process.session_keyword	ssh	Process name.
process	process.session_match_only_text	ssh	Process name.
process	process.session_keyword	c2c455d989375d	Unique identifier for the process.
process	process.session_long	c2c455d989375d	4242 Process id.
process	process.session_date	2016-05-23T08:05:34.853Z	4242 Process id.
process	process.session_date	2016-05-23T08:05:34.853Z	The time the process started.
process	process.session_date	2016-05-23T08:05:34.853Z	4242 Virtual process id.
process	process.session_date	2016-05-23T08:05:34.853Z	The time the process started.
process	process.session_date	2016-05-23T08:05:34.853Z	4242 Virtual process id.
process	process.session_date	2016-05-23T08:05:34.853Z	4242 Process id.
process	process.session_keyword		Unique identifier for the group on the system/platform.
process	process.session_keyword		Name of the group.
process	process.session_keyword	S-1-5-21-202424912787-2692429404-2351956786-1000	Unique identifier of the user.
process	process.session_keyword	a.einstein	Short name or login of the user.
process	process.session_match_only_text	a.einstein	Short name or login of the user.
process	process.session_boolean	TRUE	This boolean is used to identify if a leader process is the same as the top level process.
process	process.session_keyword		Unique identifier for the group on the system/platform.
process	process.session_keyword		Name of the group.
process	process.session_keyword	S-1-5-21-202424912787-2692429404-2351956786-1000	Unique identifier of the user.
process	process.session_keyword	a.einstein	Short name or login of the user.
process	process.session_match_only_text	a.einstein	Short name or login of the user.
process	process.session_date	2016-05-23T08:05:34.853Z	Short name or login of the user.
process	process.session_date	2016-05-23T08:05:34.853Z	The time the process started.
process	process.session_keyword		Unique identifier for the group on the system/platform.
process	process.session_keyword		Name of the group.
process	process.session_object		Information about the controlling TTY device.
process	process.session_long		4 The TTY character device's major number.
process	process.session_long		1 The TTY character device's minor number.
process	process.session_keyword	S-1-5-21-202424912787-2692429404-2351956786-1000	Unique identifier of the user.
process	process.session_keyword	a.einstein	Short name or login of the user.
process	process.session_match_only_text	a.einstein	Short name or login of the user.
process	process.session_long		4242 Virtual process id.
process	process.session_keyword	/home/alice	The working directory of the process.
process	process.session_match_only_text	/home/alice	The working directory of the process.
process	process.start_date	2016-05-23T08:05:34.853Z	The time the process started.
process	process.suggest_keyword		Unique identifier for the group on the system/platform.
process	process.suggest_keyword		Name of the group.
process	process.thread_c keyword	["CAP_BPF", "CAP_SYS_ADMIN"]	Array of capabilities used for permission checks.
process	process.thread_c keyword	["CAP_BPF", "CAP_SYS_ADMIN"]	Array of capabilities a thread could assume.
process	process.thread_id long		4242 Thread ID.
process	process.thread_id keyword	thread-0	Thread name.
process	process.title keyword		Process title.
process	process.title_text match_only_text		Process title.
process	process.tty object		Information about the controlling TTY device.
process	process.tty_char_long		4 The TTY character device's major number.
process	process.tty_char_long		1 The TTY character device's minor number.
process	process.tty_colurt long		80 The number of character columns per line. e.g terminal width
process	process.tty_rows long		24 The number of character rows in the terminal. e.g terminal height
process	process.uptime long		1325 Seconds the process has been up.
process	process.user_id keyword	S-1-5-21-202424912787-2692429404-2351956786-1000	Unique identifier of the user.
process	process.user_id keyword	a.einstein	Short name or login of the user.
process	process.user_name match_only_text	a.einstein	Short name or login of the user.
process	process.vpid long		4242 Virtual process id.
process	process.working_keyword	/home/alice	The working directory of the process.
process	process.working_match_only_text	/home/alice	The working directory of the process.
registry	registry.data.byte keyword	Z0BuAC0A/QBTAAXZQBuaAAAAA==	Original bytes written with base64 encoding.
registry	registry.data.string wildcard	["C:\valued_tpl\bin\myapp.exe"]	List of strings representing what was written to the registry.
registry	registry.data.type keyword	REG_SZ	Standard registry type for encoding contents
registry	registry.hive keyword	HKLM	Abbreviated name for the hive.
registry	registry_key keyword	SOFTWARE\Microsoft\Windows NT\CurrentVersion\Image File Execution Options\winword.exe	Hive-relative path of keys.
registry	registry_path keyword	HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Image File Execution Options\winword.exe\Debugger	Full path, including hive, key and value
registry	registry.value keyword	Debugger	Name of the value written.
related	related.hash keyword		All the hashes seen on your event.
related	related.hosts keyword		All the host identifiers seen on your event.
related	related.ip ip		All of the IPs seen on your event.
related	related.user keyword		All the user names or other user identifiers seen on the event.
rule	rule.author keyword	["Star-Lord"]	Rule author
rule	rule.category keyword	Attempter Information Leak	Rule category
rule	rule.description keyword	Block requests to public DNS over HTTPS / TLS protocols	Rule description
rule	rule_id keyword		101 Rule ID
rule	rule.license keyword	Apache 2.0	Rule license
rule	rule.name keyword	BLOCK_DNS_over_TLS	Rule name
rule	rule.reference keyword	https://en.wikipedia.org/wiki/DNS_over_TLS	Rule reference URL.
rule	rule.ruleset keyword	Standard_Protocol_Filters	Rule ruleset
rule	rule.uuid keyword		1100110011 Rule UUID
rule	rule.version keyword		1.1 Rule version
server	server.address keyword		Server network address.
server	server.as.number long		15169 Unique number allocated to the autonomous system.
server	server.as.organization keyword	Google LLC	Organization name.
server	server.as.organization match_only_text	Google LLC	Organization name.
server	server.bytes long		184 Bytes sent from the server to the client.

server	server.domain	keyword	foo.example.com		The domain name of the server.
server	server.geo.city_n	keyword	Montreal		City name.
server	server.geo.contin	keyword	NA		Continent code.
server	server.geo.contin	keyword	North America		Name of the continent.
server	server.geo.coun	keyword	CA		Country ISO code.
server	server.geo.coun	keyword	Canada		Country name.
server	server.geo.local	geo_point	{ "lon": -73.614830, "lat": 45.505918 }		Longitude and latitude.
server	server.geo.name	keyword	boston-dc		User-defined description of a location.
server	server.geo.postal	keyword		94040	Postal code.
server	server.geo.region	keyword	CA-QC		Region ISO code.
server	server.geo.region	keyword	Quebec		Region name.
server	server.geo.timez	keyword	America/Argentina/Buenos_Aires		Time zone.
server	server.ip	ip			IP address of the server.
server	server.mac	keyword	00-00-5E-00-53-23		MAC address of the server.
server	server.nat.ip	ip			Server NAT ip
server	server.nat.port	long			Server NAT port
server	server.packets	long		12	Packets sent from the server to the client.
server	server.port	long			Port of the server.
server	server.registered	keyword	example.com		The highest registered server domain, stripped of the subdomain.
server	server.subdomain	keyword	east		The subdomain of the domain.
server	server.top_level	keyword	co.uk		The effective top level domain (com, org, net, co.uk).
server	server.user.dom	keyword			Name of the directory the user is a member of.
server	server.user.email	keyword			User email address.
server	server.user.full_n	keyword	Albert Einstein		User's full name, if available.
server	server.user.full_n	match_only_text	Albert Einstein		User's full name, if available.
server	server.user.group	keyword			Name of the directory the group is a member of.
server	server.user.group	keyword			Unique identifier for the group on the system/platform.
server	server.user.hash	keyword			Name of the group.
server	server.user.hash	keyword			Unique user hash to correlate information for a user in anonymized form.
server	server.user.id	keyword	S-1-5-21-202424912787-2692429404-2351956786-1000		Unique identifier of the user.
server	server.user.name	keyword	a.einstein		Short name or login of the user.
server	server.user.name	match_only_text	a.einstein		Short name or login of the user.
server	server.user.roles	keyword	["kibana_admin", "reporting_user"]		Array of user roles at the time of the event.
service	service.address	keyword	172.26.0.2.5432		Address of this service.
service	service.environment	keyword	production		Environment of the service.
service	service.ephe	keyword	8a4f50f		Ephemeral identifier of this service.
service	service.id	keyword	d37e5ebf0dae6c4972dbe9f0174a1637bb2478		Unique identifier of the running service.
service	service.name	keyword	elasticsearch-metrics		Name of the service.
service	service.node.na	keyword	instance-0000000016		Name of the service node.
service	service.node.role	keyword	background_tasks		Deprecated role (singular) of the service node.
service	service.node.role	keyword	["ul", "background_tasks"]		Roles of the service node.
service	service.origin.ad	keyword	172.26.0.2.5432		Address of this service.
service	service.origin.en	keyword	production		Environment of the service.
service	service.origin.epi	keyword	8a4f50f		Ephemeral identifier of this service.
service	service.origin.id	keyword	d37e5ebf0dae6c4972dbe9f0174a1637bb2478		Unique identifier of the running service.
service	service.origin.na	keyword	elasticsearch-metrics		Name of the service.
service	service.origin.no	keyword	instance-0000000016		Name of the service node.
service	service.origin.no	keyword	background_tasks		Deprecated role (singular) of the service node.
service	service.origin.no	keyword	["ul", "background_tasks"]		Roles of the service node.
service	service.origin.sta	keyword			Current state of the service.
service	service.origin.typ	keyword	elasticsearch		The type of the service.
service	service.origin.ver	keyword	3.2.4		Version of the service.
service	service.state	keyword			Current state of the service.
service	service.target.ad	keyword	172.26.0.2.5432		Address of this service.
service	service.target.en	keyword	production		Environment of the service.
service	service.target.epi	keyword	8a4f50f		Ephemeral identifier of this service.
service	service.target.id	keyword	d37e5ebf0dae6c4972dbe9f0174a1637bb2478		Unique identifier of the running service.
service	service.target.na	keyword	elasticsearch-metrics		Name of the service.
service	service.target.no	keyword	instance-0000000016		Name of the service node.
service	service.target.no	keyword	background_tasks		Deprecated role (singular) of the service node.
service	service.target.no	keyword	["ul", "background_tasks"]		Roles of the service node.
service	service.target.sta	keyword			Current state of the service.
service	service.target.typ	keyword	elasticsearch		The type of the service.
service	service.target.ver	keyword	3.2.4		Version of the service.
service	service.type	keyword	elasticsearch		The type of the service.
service	service.version	keyword	3.2.4		Version of the service.
source	source.address	keyword			Source network address.
source	source.as.num	long		15169	Unique number allocated to the autonomous system.
source	source.as.org	keyword	Google LLC		Organization name.
source	source.as.org	match_only_text	Google LLC		Organization name.
source	source.bytes	long		184	Bytes sent from the source to the destination.
source	source.domain	keyword	foo.example.com		The domain name of the source.
source	source.geo.city_i	keyword	Montreal		City name.
source	source.geo.conti	keyword	NA		Continent code.
source	source.geo.conti	keyword	North America		Name of the continent.
source	source.geo.coun	keyword	CA		Country ISO code.
source	source.geo.coun	keyword	Canada		Country name.
source	source.geo.local	geo_point	{ "lon": -73.614830, "lat": 45.505918 }		Longitude and latitude.
source	source.geo.name	keyword	boston-dc		User-defined description of a location.
source	source.geo.poste	keyword		94040	Postal code.
source	source.geo.region	keyword	CA-QC		Region ISO code.
source	source.geo.region	keyword	Quebec		Region name.
source	source.geo.timez	keyword	America/Argentina/Buenos_Aires		Time zone.
source	source.ip	ip			IP address of the source.
source	source.mac	keyword	00-00-5E-00-53-23		MAC address of the source.
source	source.nat.ip	ip			Source NAT ip
source	source.nat.port	long			Source NAT port
source	source.packets	long		12	Packets sent from the source to the destination.
source	source.port	long			Port of the source.
source	source.registered	keyword	example.com		The highest registered source domain, stripped of the subdomain.
source	source.subdomain	keyword	east		The subdomain of the domain.
source	source.top_level	keyword	co.uk		The effective top level domain (com, org, net, co.uk).
source	source.user.dom	keyword			Name of the directory the user is a member of.
source	source.user.email	keyword			User email address.
source	source.user.full_i	keyword	Albert Einstein		User's full name, if available.
source	source.user.full_i	match_only_text	Albert Einstein		User's full name, if available.
source	source.user.grou	keyword			Name of the directory the group is a member of.
source	source.user.grou	keyword			Unique identifier for the group on the system/platform.
source	source.user.hash	keyword			Name of the group.
source	source.user.hash	keyword			Unique user hash to correlate information for a user in anonymized form.
source	source.user.id	keyword	S-1-5-21-202424912787-2692429404-2351956786-1000		Unique identifier of the user.
source	source.user.name	keyword	a.einstein		Short name or login of the user.
source	source.user.name	match_only_text	a.einstein		Short name or login of the user.
source	source.user.roles	keyword	["kibana_admin", "reporting_user"]		Array of user roles at the time of the event.
span	span.id	keyword	3ff5a8981b7cc5da		Unique identifier of the span within the scope of its trace.
threat	threat.enrichmen	nested			List of objects containing indicators enriching the event.
threat	threat.enrichmen	object			Object containing indicators enriching the event.
threat	threat.enrichmen	long		15169	Unique number allocated to the autonomous system.
threat	threat.enrichmen	keyword	Google LLC		Organization name.
threat	threat.enrichmen	match_only_text	Google LLC		Organization name.
threat	threat.enrichmen	keyword	Medium		Indicator confidence rating
threat	threat.enrichmen	keyword	IP x.x.x.x was observed delivering the Angler EK.		Indicator description
threat	threat.enrichmen	keyword	phish@example.com		Indicator email address
threat	threat.enrichmen	date			Last time the file was accessed.
threat	threat.enrichmen	keyword	["readonly", "system"]		Array of file attributes.
threat	threat.enrichmen	keyword	sha256		Hashing algorithm used to sign the process.
threat	threat.enrichmen	boolean	TRUE	570522385	Boolean to capture if a signature is present.
threat	threat.enrichmen	keyword			Code signing flags of the process
threat	threat.enrichmen	keyword	com.apple.xpc.proxy		The identifier used to sign the process.
threat	threat.enrichmen	keyword	ERROR_UNTRUSTED_ROOT		Additional information about the certificate status.
threat	threat.enrichmen	keyword	Microsoft Corporation		Subject name of the code signer
threat	threat.enrichmen	keyword	EQHXZ8MBAV		The team identifier used to sign the process.
threat	threat.enrichmen	date	2021-01-01T11:12:30Z		When the signature was generated and signed.
threat	threat.enrichmen	boolean	TRUE	TRUE	Stores the trust status of the certificate chain.
threat	threat.enrichmen	boolean	TRUE		Boolean to capture if the digital signature is verified against the binary content.
threat	threat.enrichmen	date			File creation time.
threat	threat.enrichmen	date			Last time the file attributes or metadata changed.
threat	threat.enrichmen	keyword	sda		Device that is the source of the file.
threat	threat.enrichmen	keyword	/home/alice		Directory where the file is located.
threat	threat.enrichmen	keyword	C		Drive letter where the file is located.

threat	threat.enrichmen keyword	x86-64	Machine architecture of the ELF file.
threat	threat.enrichmen keyword	Little Endian	Byte sequence of ELF file.
threat	threat.enrichmen keyword	Intel	CPU type of the ELF file.
threat	threat.enrichmen date		Build or compile date.
threat	threat.enrichmen flattened		List of exported element names and types.
threat	threat.enrichmen keyword	10bddcb4cee4208076c88d9f964491	A hash of the Go language imports in an ELF file.
threat	threat.enrichmen flattened		List of imported Go language element names and types.
threat	threat.enrichmen long		Shannon entropy calculation from the list of Go imports.
threat	threat.enrichmen long		Variance for Shannon entropy calculation from the list of Go imports.
threat	threat.enrichmen boolean		Whether the file is a stripped or obfuscated Go executable.
threat	threat.enrichmen keyword		Version of the ELF Application Binary Interface (ABI).
threat	threat.enrichmen keyword		Header class of the ELF file.
threat	threat.enrichmen keyword		Data table of the ELF header.
threat	threat.enrichmen long		Header endpoint of the ELF file.
threat	threat.enrichmen keyword		"0x1" for original ELF files.
threat	threat.enrichmen keyword		Application Binary Interface (ABI) of the Linux OS.
threat	threat.enrichmen keyword		Header type of the ELF file.
threat	threat.enrichmen keyword		Version of the ELF header.
threat	threat.enrichmen keyword	d41d8cd98f00b204e9800998ecf8427e	A hash of the imports in an ELF file.
threat	threat.enrichmen flattened		List of imported element names and types.
threat	threat.enrichmen long		Shannon entropy calculation from the list of imported element names and types.
threat	threat.enrichmen long		Variance for Shannon entropy calculation from the list of imported element names and types.
threat	threat.enrichmen nested		Section information of the ELF file.
threat	threat.enrichmen long		Chi-square probability distribution of the section.
threat	threat.enrichmen long		Shannon entropy calculation from the section.
threat	threat.enrichmen keyword		ELF Section List flags.
threat	threat.enrichmen keyword		ELF Section List name.
threat	threat.enrichmen keyword		ELF Section List offset.
threat	threat.enrichmen long		ELF Section List physical size.
threat	threat.enrichmen keyword		ELF Section List type.
threat	threat.enrichmen long		Variance for Shannon entropy calculation from the section.
threat	threat.enrichmen long		ELF Section List virtual address.
threat	threat.enrichmen long		ELF Section List virtual size.
threat	threat.enrichmen nested		ELF object segment list.
threat	threat.enrichmen keyword		ELF object segment sections.
threat	threat.enrichmen keyword		ELF object segment type.
threat	threat.enrichmen keyword		List of shared libraries used by this ELF object.
threat	threat.enrichmen keyword		teflhash hash for ELF file.
threat	threat.enrichmen keyword	png	File extension, excluding the leading dot.
threat	threat.enrichmen keyword	Zone.Identifier	A fork is additional data associated with a filesystem object.
threat	threat.enrichmen keyword		1001 Primary group (GID) of the file.
threat	threat.enrichmen keyword	alice	Primary group name of the file.
threat	threat.enrichmen keyword	3783b4052f9474dbe30676b45c329e7a6d44acd9	The Code Directory (CD) hash of an executable.
threat	threat.enrichmen keyword		MD5 hash.
threat	threat.enrichmen keyword		SHA1 hash.
threat	threat.enrichmen keyword		SHA256 hash.
threat	threat.enrichmen keyword		SHA384 hash.
threat	threat.enrichmen keyword		SHA512 hash.
threat	threat.enrichmen keyword		SSDEEP hash.
threat	threat.enrichmen keyword		TLSH hash.
threat	threat.enrichmen keyword		256383 Inode representing the file in the filesystem.
threat	threat.enrichmen keyword		Media type of file, document, or arrangement of bytes.
threat	threat.enrichmen keyword		640 Mode of the file in octal representation.
threat	threat.enrichmen date		Last time the file content was modified.
threat	threat.enrichmen keyword	example.png	Name of the file including the extension, without the directory.
threat	threat.enrichmen keyword	alice	File owner's username.
threat	threat.enrichmen keyword	/home/alice/example.png	Full path to the file, including the file name.
threat	threat.enrichmen match_only_text	/home/alice/example.png	Full path to the file, including the file name.
threat	threat.enrichmen keyword	x64	CPU architecture target for the file.
threat	threat.enrichmen keyword	Microsoft Corporation	Internal company name of the file, provided at compile-time.
threat	threat.enrichmen keyword	Paint	Internal description of the file, provided at compile-time.
threat	threat.enrichmen keyword	6.3.9600.17415	Process name.
threat	threat.enrichmen keyword	10bddcb4cee4208076c88d9f964491	A hash of the Go language imports in a PE file.
threat	threat.enrichmen flattened		List of imported Go language element names and types.
threat	threat.enrichmen long		Shannon entropy calculation from the list of Go imports.
threat	threat.enrichmen long		Variance for Shannon entropy calculation from the list of Go imports.
threat	threat.enrichmen boolean		Whether the file is a stripped or obfuscated Go executable.
threat	threat.enrichmen keyword	0c8803c4e922103c4dca5963aad36ddf	A hash of the imports in a PE file.
threat	threat.enrichmen keyword	d41d8cd98f00b204e9800998ecf8427e	A hash of the imports in a PE file.
threat	threat.enrichmen flattened		List of imported element names and types.
threat	threat.enrichmen long		Shannon entropy calculation from the list of imported element names and types.
threat	threat.enrichmen long		Variance for Shannon entropy calculation from the list of imported element names and types.
threat	threat.enrichmen keyword	MSPAINTE.EXE	Internal name of the file, provided at compile-time.
threat	threat.enrichmen keyword	73ff189663cd6be375a7ff25179a36d347651975	A hash of the PE header and data from one or more PE sections.
threat	threat.enrichmen keyword	Microsoft® Windows® Operating System	Internal product name of the file, provided at compile-time.
threat	threat.enrichmen nested		Section information of the PE file.
threat	threat.enrichmen long		Shannon entropy calculation from the section.
threat	threat.enrichmen keyword		PE Section List name.
threat	threat.enrichmen long		PE Section List physical size.
threat	threat.enrichmen long		Variance for Shannon entropy calculation from the section.
threat	threat.enrichmen long		PE Section List virtual size. This is always the same as 'physical_size'.
threat	threat.enrichmen long		16384 File size in bytes.
threat	threat.enrichmen keyword		Target path for symlinks.
threat	threat.enrichmen match_only_text		Target path for symlinks.
threat	threat.enrichmen keyword	file	File type (file, dir, or symlink).
threat	threat.enrichmen keyword		1001 The user ID (UID) or security identifier (SID) of the file owner.
threat	threat.enrichmen keyword	*.elastic.co	List of subject alternative names (SAN).
threat	threat.enrichmen keyword	Example SHA2 High Assurance Server CA	List of common name (CN) of issuing certificate authority.
threat	threat.enrichmen keyword	US	List of country (VC) codes
threat	threat.enrichmen keyword	C=US, O=Example Inc. OU=www.example.com, CN=Example SHA2 High Assurance Server CA	Distinguished name (DN) of issuing certificate authority.
threat	threat.enrichmen keyword	Mountain View	List of locality names (L)
threat	threat.enrichmen keyword	Example Inc	List of organizations (O) of issuing certificate authority.
threat	threat.enrichmen keyword	www.example.com	List of organizational units (OU) of issuing certificate authority.
threat	threat.enrichmen keyword	California	List of state or province names (ST, S, or P)
threat	threat.enrichmen date	2020-07-16T03:15:30Z	Time at which the certificate is no longer considered valid.
threat	threat.enrichmen date	2019-08-16T01:40:25Z	Time at which the certificate is first considered valid.
threat	threat.enrichmen keyword	RSA	Algorithm used to generate the public key.
threat	threat.enrichmen keyword	nistp521	The curve used by the elliptic curve public key algorithm. This is algorithm specific.
threat	threat.enrichmen long		65537 Exponent used to derive the public key. This is algorithm specific.
threat	threat.enrichmen long		2048 The size of the public key space in bits.
threat	threat.enrichmen keyword	55f8b9c7debf09809d12ccaa	Unique serial number issued by the certificate authority.
threat	threat.enrichmen keyword	SHA256-RSA	Identifier for certificate signature algorithm.
threat	threat.enrichmen keyword	shared.global.example.net	List of common names (CN) of subject.
threat	threat.enrichmen keyword	US	List of country (VC) code
threat	threat.enrichmen keyword	C=US, ST=California, L=San Francisco, O=Example, Inc., CN=shared.global.example.net	Distinguished name (DN) of the certificate subject entity.
threat	threat.enrichmen keyword	San Francisco	List of locality names (L)
threat	threat.enrichmen keyword	Example, Inc.	List of organizations (O) of subject.
threat	threat.enrichmen keyword	California	List of organizational units (OU) of subject.
threat	threat.enrichmen keyword		List of state or province names (ST, S, or P)
threat	threat.enrichmen date	2020-11-05T17:25:47.000Z	3 Version of x509 format.
threat	threat.enrichmen keyword	Montreal	Date/time indicator was first reported.
threat	threat.enrichmen keyword	NA	City name.
threat	threat.enrichmen keyword	North America	Continent code.
threat	threat.enrichmen keyword	CA	Name of the continent.
threat	threat.enrichmen keyword	Canada	Country ISO code.
threat	threat.enrichmen keyword	("lon": -73.614830, "lat": 45.505918)	Country name.
threat	threat.enrichmen geo_point	boston-dc	Longitude and latitude.
threat	threat.enrichmen keyword		User-defined description of a location.
threat	threat.enrichmen keyword	CA-QC	94040 Postal code.
threat	threat.enrichmen keyword	Quebec	Region ISO code.
threat	threat.enrichmen keyword	America/Argentina/Buenos_Aires	Region name.
threat	threat.enrichmen ip	1.2.3.4	Time zone.
threat	threat.enrichmen date	2020-11-05T17:25:47.000Z	Indicator IP address
threat	threat.enrichmen keyword	CLEAR	Date/time indicator was last reported.
threat	threat.enrichmen keyword		Indicator TLP marking
threat	threat.enrichmen date	2020-11-05T17:25:47.000Z	2 Indicator TLP version
threat	threat.enrichmen keyword	5.2.75.227	Date/time indicator was last updated.
threat	threat.enrichmen keyword		Indicator display name
threat	threat.enrichmen long		443 Indicator port
threat	threat.enrichmen keyword	lrz_urthaus	Indicator provider

threat	threat.enrichmen	keyword	https://system.example.com/indicator/0001234	Indicator reference URL.
threat	threat.enrichmen	keyword	ZOBuACDvQBTAIAAZQBuAAAAA==	Original bytes written with base64 encoding.
threat	threat.enrichmen	wildcard	[C:\ntsvad_tpb\bin\myapp.exe]	List of strings representing what was written to the registry.
threat	threat.enrichmen	keyword	REG_SZ	Standard registry type for encoding contents
threat	threat.enrichmen	keyword	HKLM	Abbreviated name for the hive.
threat	threat.enrichmen	keyword	SOFTWARE\Microsoft\Windows NT\CurrentVersion\Image File Execution Options\winword.exe	Hive-relative path of keys.
threat	threat.enrichmen	keyword	HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Image File Execution Options\winword.exe\Debugger	Full path, including hive, key and value
threat	threat.enrichmen	keyword	Debugger	Name of the value written.
threat	threat.enrichmen	long		4 Scanner statistics
threat	threat.enrichmen	long		20 Number of times indicator observed
threat	threat.enrichmen	keyword	ipv4-addr	Type of indicator
threat	threat.enrichmen	keyword	www.elastic.co	Domain of the url.
threat	threat.enrichmen	keyword	png	File extension from the request url, excluding the leading dot.
threat	threat.enrichmen	keyword		Portion of the url after the "a".
threat	threat.enrichmen	wildcard	https://www.elastic.co/443/search?q=elasticsearch#top	Full unparsed URL.
threat	threat.enrichmen	match_only_text	https://www.elastic.co/443/search?q=elasticsearch#top	Full unparsed URL.
threat	threat.enrichmen	wildcard	https://www.elastic.co/443/search?q=elasticsearch#top	Unmodified original url as seen in the event source.
threat	threat.enrichmen	match_only_text	https://www.elastic.co/443/search?q=elasticsearch#top	Unmodified original url as seen in the event source.
threat	threat.enrichmen	keyword		Password of the request.
threat	threat.enrichmen	wildcard		Path of the request, such as "search".
threat	threat.enrichmen	long		443 Port of the request, such as 443.
threat	threat.enrichmen	keyword		Query string of the request.
threat	threat.enrichmen	keyword	example.com	The highest registered url domain, stripped of the subdomain.
threat	threat.enrichmen	keyword	https	Scheme of the url.
threat	threat.enrichmen	keyword	east	The subdomain of the domain.
threat	threat.enrichmen	keyword	co.uk	The effective top level domain (com, org, net, co.uk).
threat	threat.enrichmen	keyword		Username of the request.
threat	threat.enrichmen	keyword	*.elastic.co	List of subject alternative names (SAN).
threat	threat.enrichmen	keyword	Example SHA2 High Assurance Server CA	List of common name (CN) of issuing certificate authority.
threat	threat.enrichmen	keyword	US	List of country (VC) codes
threat	threat.enrichmen	keyword	C=US, O=Example Inc, OU=www.example.com, CN=Example SHA2 High Assurance Server CA	Distinguished name (DN) of issuing certificate authority.
threat	threat.enrichmen	keyword	Mountain View	List of locality names (L)
threat	threat.enrichmen	keyword	Example Inc	List of organizations (O) of issuing certificate authority.
threat	threat.enrichmen	keyword	www.example.com	List of organizational units (OU) of issuing certificate authority.
threat	threat.enrichmen	keyword	California	List of state or province names (ST, S, or P)
threat	threat.enrichmen	date	2020-07-16T03:15:38Z	Time at which the certificate is no longer considered valid.
threat	threat.enrichmen	date	2019-08-16T01:40:25Z	Time at which the certificate is first considered valid.
threat	threat.enrichmen	keyword	RSA	Algorithm used to generate the public key.
threat	threat.enrichmen	keyword	nistp521	The curve used by the elliptic curve public key algorithm. This is algorithm specific.
threat	threat.enrichmen	long		65537 Exponent used to derive the public key. This is algorithm specific.
threat	threat.enrichmen	long		2048 The size of the public key space in bits.
threat	threat.enrichmen	keyword	55FB89C7DEBF0809D12CCAA	Unique serial number issued by the certificate authority.
threat	threat.enrichmen	keyword	SHA256-RSA	Identifier for certificate signature algorithm.
threat	threat.enrichmen	keyword	shard.global.example.net	List of common names (CN) of subject.
threat	threat.enrichmen	keyword	US	List of country (VC) code
threat	threat.enrichmen	keyword	C=US, ST=California, L=San Francisco, O=Example, Inc., CN=shard.global.example.net	Distinguished name (DN) of the certificate subject entity.
threat	threat.enrichmen	keyword	San Francisco	List of locality names (L)
threat	threat.enrichmen	keyword	Example, Inc.	List of organizations (O) of subject.
threat	threat.enrichmen	keyword		List of organizational units (OU) of subject.
threat	threat.enrichmen	keyword	California	List of state or province names (ST, S, or P)
threat	threat.enrichmen	keyword		3 Version of x509 format.
threat	threat.enrichmen	keyword	test-domain.com	Matched indicator value
threat	threat.enrichmen	keyword	file hash sha256	Matched indicator field
threat	https://test.endpoint	keyword	#93aee5-86a1-4a61-b0e6-0cd313d01b5	Matched indicator identifier
threat	threat.enrichmen	keyword	filebeat-8.0.0-2021.05.23-000011	Matched indicator index
threat	threat.enrichmen	date	2021-10-05T17:00:58.326Z	Date of match
threat	threat.enrichmen	keyword	indicator_match_rule	Type of indicator match
threat	threat.feed.dashl	keyword	5ba16340-72e6-11eb-a3e3-b3cc7c78a70f	Feed dashboard ID.
threat	threat.feed.descr	keyword	Threat feed from the AlienVault Open Threat eXchange network.	Description of the threat feed.
threat	https://test.feed.refers	keyword	AlienVault OTX	Name of the threat feed.
threat	threat.feed.refers	keyword	https://otx.alienvault.com	Reference for the threat feed.
threat	threat.framework	keyword	MITRE ATTACK	Threat classification framework.
threat	threat.group.allat	keyword	["Magecart Group 6"]	Alias of the group.
threat	https://test.group.id	keyword	G0037	ID of the group.
threat	https://test.group.name	keyword	FIN6	Name of the group.
threat	threat.group.refe	keyword	https://attack.mitre.org/groups/G0037/	Reference URL of the group.
threat	threat.indicator.a	long		15169 Unique number allocated to the autonomous system.
threat	https://test.indicator.a	keyword	Google LLC	Organization name.
threat	threat.indicator.a	match_only_text	Google LLC	Organization name.
threat	threat.indicator.c	keyword	Medium	Indicator confidence rating
threat	threat.indicator.d	keyword	IP x.x.x.x was observed delivering the Angler EK.	Indicator description
threat	threat.indicator.e	keyword	phish@example.com	Indicator email address
threat	threat.indicator.f	date		Last time the file was accessed.
threat	threat.indicator.f	keyword	["readonly", "system"]	Array of file attributes.
threat	threat.indicator.f	keyword	sha256	Hashing algorithm used to sign the process.
threat	threat.indicator.f	boolean	TRUE	Boolean to capture if a signature is present.
threat	threat.indicator.f	keyword		570522385 Code signing flags of the process
threat	threat.indicator.f	keyword	com.apple.xpc.proxy	The identifier used to sign the process.
threat	threat.indicator.f	keyword	ERROR_UNTRUSTED_ROOT	Additional information about the certificate status.
threat	threat.indicator.f	keyword	Microsoft Corporation	Subject name of the code signer
threat	threat.indicator.f	keyword	EOHXZ8MBAV	The team identifier used to sign the process.
threat	threat.indicator.f	date	2021-01-01T12:10:30Z	When the signature was generated and signed.
threat	threat.indicator.f	boolean	TRUE	Stores the trust status of the certificate chain.
threat	threat.indicator.f	boolean	TRUE	Boolean to capture if the digital signature is verified against the binary content.
threat	threat.indicator.f	date		File creation time.
threat	threat.indicator.f	date		Last time the file attributes or metadata changed.
threat	threat.indicator.f	keyword	sda	Device that is the source of the file.
threat	threat.indicator.f	keyword	/home/alice	Directory where the file is located.
threat	threat.indicator.f	keyword	C	Drive letter where the file is located.
threat	threat.indicator.f	keyword	x86-64	Machine architecture of the ELF file.
threat	threat.indicator.f	keyword	Little Endian	Byte sequence of ELF file.
threat	threat.indicator.f	keyword	Intel	CPU type of the ELF file.
threat	threat.indicator.f	date		Build or compile date.
threat	threat.indicator.f	flattened		List of exported element names and types.
threat	threat.indicator.f	keyword	10bddcb4cee4208076c8b9f9964491	A hash of the Go language imports in an ELF file.
threat	threat.indicator.f	flattened		List of imported Go language element names and types.
threat	threat.indicator.f	long		Shannon entropy calculation from the list of Go imports.
threat	threat.indicator.f	long		Variance for Shannon entropy calculation from the list of Go imports.
threat	threat.indicator.f	boolean		Whether the file is a stripped or obfuscated Go executable.
threat	threat.indicator.f	keyword		Version of the ELF Application Binary Interface (ABI).
threat	threat.indicator.f	keyword		Header class of the ELF file.
threat	threat.indicator.f	long		Data table of the ELF header.
threat	threat.indicator.f	long		Header entripoint of the ELF file.
threat	threat.indicator.f	keyword		"0x1" for original ELF files.
threat	threat.indicator.f	keyword		Application Binary Interface (ABI) of the Linux OS.
threat	threat.indicator.f	keyword		Header type of the ELF file.
threat	threat.indicator.f	keyword		Version of the ELF header.
threat	threat.indicator.f	keyword	641dbcd98f0b204e9800998ecf8427e	A hash of the imports in an ELF file.
threat	threat.indicator.f	flattened		List of imported element names and types.
threat	threat.indicator.f	long		Shannon entropy calculation from the list of imported element names and types.
threat	threat.indicator.f	long		Variance for Shannon entropy calculation from the list of imported element names and types.
threat	threat.indicator.f	keyword		Section information of the ELF file.
threat	threat.indicator.f	long		Chi-square probability distribution of the section.
threat	threat.indicator.f	long		Shannon entropy calculation from the section.
threat	threat.indicator.f	keyword		ELF Section List flags.
threat	https://test.indicator.f	keyword		ELF Section List name.
threat	threat.indicator.f	long		ELF Section List offset.
threat	threat.indicator.f	keyword		ELF Section List physical size.
threat	threat.indicator.f	keyword		ELF Section List type.
threat	threat.indicator.f	long		Variance for Shannon entropy calculation from the section.
threat	threat.indicator.f	long		ELF Section List virtual address.
threat	threat.indicator.f	long		ELF Section List virtual size.
threat	threat.indicator.f	keyword		ELF object segment list.
threat	threat.indicator.f	keyword		ELF object segment sections.
threat	threat.indicator.f	keyword		ELF object segment type.
threat	threat.indicator.f	keyword		List of shared libraries used by this ELF object.
threat	threat.indicator.f	keyword		teflash hash for ELF file.
threat	threat.indicator.f	keyword	png	File extension, excluding the leading dot.
threat	threat.indicator.f	keyword	Zone.Identifier	A fork is additional data associated with a filesystem object.
threat	threat.indicator.f	keyword		1001 Primary group ID (GID) of the file.

threat	threat.indicator.fi keyword	alice	Primary group name of the file.
threat	threat.indicator.fi keyword	3783b4052f9474dbe30676b45c329e7a6d44acd9	The Code Directory (CD) hash of an executable.
threat	threat.indicator.fi keyword		MD5 hash.
threat	threat.indicator.fi keyword		SHA1 hash.
threat	threat.indicator.fi keyword		SHA256 hash.
threat	threat.indicator.fi keyword		SHA384 hash.
threat	threat.indicator.fi keyword		SHA512 hash.
threat	threat.indicator.fi keyword		SSDEEP hash.
threat	threat.indicator.fi keyword		TLSH hash.
threat	threat.indicator.fi keyword		256383 Inode representing the file in the filesystem.
threat	threat.indicator.fi keyword		Media type of file, document, or arrangement of bytes.
threat	threat.indicator.fi keyword		640 Mode of the file in octal representation.
threat	threat.indicator.fi date		Last time the file content was modified.
threat	threat.indicator.fi keyword	example.png	Name of the file including the extension, without the directory.
threat	threat.indicator.fi keyword	alice	File owner's username.
threat	threat.indicator.fi keyword	/home/alice/example.png	Full path to the file, including the file name.
threat	threat.indicator.fi match_only_text	/home/alice/example.png	Full path to the file, including the file name.
threat	threat.indicator.fi keyword	x64	CPU architecture target for the file.
threat	threat.indicator.fi keyword	Microsoft Corporation	Internal company name of the file, provided at compile-time.
threat	threat.indicator.fi keyword	Paint	Internal description of the file, provided at compile-time.
threat	threat.indicator.fi keyword	6.3.9600.17415	Process name.
threat	threat.indicator.fi keyword	10bdd5b4cee420807f6c88d9f964491	A hash of the Go language imports in a PE file.
threat	threat.indicator.fi flattened		List of imported Go language element names and types.
threat	threat.indicator.fi long		Shannon entropy calculation from the list of Go imports.
threat	threat.indicator.fi long		Variance for Shannon entropy calculation from the list of Go imports.
threat	threat.indicator.fi boolean		Whether the file is a stripped or obfuscated Go executable.
threat	threat.indicator.fi keyword	0c6803c4e922103c4dca5963aad36ddf	A hash of the imports in a PE file.
threat	threat.indicator.fi keyword	041d6cd98f06204e9600998ec6427e	A hash of the imports in a PE file.
threat	threat.indicator.fi flattened		List of imported element names and types.
threat	threat.indicator.fi long		Shannon entropy calculation from the list of imported element names and types.
threat	threat.indicator.fi long		Variance for Shannon entropy calculation from the list of imported element names and types.
threat	threat.indicator.fi keyword	MSPAIN.EXE	Internal name of the file, provided at compile-time.
threat	threat.indicator.fi keyword	73f189663cd6be375a7f25179a36d347651975	A hash of the PE header and data from one or more PE sections.
threat	threat.indicator.fi keyword	Microsoft® Windows® Operating System	Internal product name of the file, provided at compile-time.
threat	threat.indicator.fi nested		Section information of the PE file.
threat	threat.indicator.fi long		Shannon entropy calculation from the section.
threat	threat.indicator.fi keyword		PE Section List name.
threat	threat.indicator.fi long		PE Section List physical size.
threat	threat.indicator.fi long		Variance for Shannon entropy calculation from the section.
threat	threat.indicator.fi long		PE Section List virtual size. This is always the same as 'physical_size'.
threat	threat.indicator.fi keyword		16384 File size in bytes.
threat	threat.indicator.fi match_only_text		Target path for symlinks.
threat	threat.indicator.fi keyword	file	Target path for symlinks.
threat	threat.indicator.fi keyword		File type (file, dir, or symlink).
threat	threat.indicator.fi keyword	* elastic.co	1001 The user ID (UID) or security identifier (SID) of the file owner.
threat	threat.indicator.fi keyword	Example SHA2 High Assurance Server CA	List of subject alternative names (SAN).
threat	threat.indicator.fi keyword	US	List of common name (CN) of issuing certificate authority.
threat	threat.indicator.fi keyword	C=US, O=Example Inc. OU=www.example.com, CN=Example SHA2 High Assurance Server CA	List of country (C) codes
threat	threat.indicator.fi keyword	Mountain View	Distinguished name (DN) of issuing certificate authority.
threat	threat.indicator.fi keyword	Example Inc	List of locality names (L)
threat	threat.indicator.fi keyword	www.example.com	List of organizations (O) of issuing certificate authority.
threat	threat.indicator.fi keyword	California	List of organizational units (OU) of issuing certificate authority.
threat	threat.indicator.fi date	2020-07-16T03:15:39Z	List of state or province names (ST, S, or P)
threat	threat.indicator.fi date	2019-08-16T01:40:25Z	Time at which the certificate is no longer considered valid.
threat	threat.indicator.fi keyword	RSA	Time at which the certificate is first considered valid.
threat	threat.indicator.fi keyword	nistp521	Algorithm used to generate the public key.
threat	threat.indicator.fi long		The curve used by the elliptic curve public key algorithm. This is algorithm specific.
threat	threat.indicator.fi long		65537 Exponent used to derive the public key. This is algorithm specific.
threat	threat.indicator.fi long		2048 The size of the public key space in bits.
threat	threat.indicator.fi keyword	55f8b9c7d5ebf09809d12ccaa	Unique serial number issued by the certificate authority.
threat	threat.indicator.fi keyword	SHA256-RSA	Identifier for certificate signature algorithm.
threat	threat.indicator.fi keyword	shared.global.example.net	List of common names (CN) of subject.
threat	threat.indicator.fi keyword	US	List of country (C) code
threat	threat.indicator.fi keyword	C=US, ST=California, L=San Francisco, O=Example, Inc., CN=shared.global.example.net	Distinguished name (DN) of the certificate subject entity.
threat	threat.indicator.fi keyword	San Francisco	List of locality names (L)
threat	threat.indicator.fi keyword	Example, Inc.	List of organizations (O) of subject.
threat	threat.indicator.fi keyword	California	List of organizational units (OU) of subject.
threat	threat.indicator.fi keyword		List of state or province names (ST, S, or P)
threat	threat.indicator.fi date	2020-11-05T17:25:47.000Z	3 Version of ASN.1 format.
threat	threat.indicator.g keyword	Montreal	Date/time indicator was first reported.
threat	threat.indicator.g keyword	NA	City name.
threat	threat.indicator.g keyword	North America	Continent code.
threat	threat.indicator.g keyword	CA	Name of the continent.
threat	threat.indicator.g keyword	Canada	Country ISO code.
threat	threat.indicator.g geo_point	{ "lon": -73.614830, "lat": 45.505918 }	Country name.
threat	threat.indicator.g keyword	boston-dc	Longitude and latitude.
threat	threat.indicator.g keyword	CA-QC	User-defined description of a location.
threat	threat.indicator.g keyword	Quebec	94040 Postal code.
threat	threat.indicator.g keyword	America/Argentina/Buenos_Aires	Region ISO code.
threat	threat.indicator.g keyword	[indicator-d7008e06-ab86-415a-9803-3cd1ce23c37]	Region name.
threat	threat.indicator.g keyword	1.2.3.4	Time zone.
threat	threat.indicator.i date	2020-11-05T17:25:47.000Z	ID of the indicator
threat	threat.indicator.n keyword	CLEAR	Indicator IP address
threat	threat.indicator.n keyword		Date/time indicator was last reported.
threat	threat.indicator.n date	2020-11-05T17:25:47.000Z	Indicator TLP marking
threat	threat.indicator.n keyword	5.2.75.227	2 Indicator TLP version
threat	threat.indicator.p long		Date/time indicator was last updated.
threat	threat.indicator.p keyword	lrz_urthaus	Indicator display name
threat	threat.indicator.r keyword	https://system.example.com/indicator/0001234	443 Indicator port
threat	threat.indicator.r keyword	Z0BxJCDAVQB1AAAZQB0AIAAAAAAAAA+	Indicator provider
threat	threat.indicator.r keyword	{ "C": "us", "E": "t@bin/mysp.exe" }	Indicator reference URL
threat	threat.indicator.r keyword	REG_SZ	List of strings representing what was written to the registry.
threat	threat.indicator.r keyword	HKLM	Standard registry type for encoding contents
threat	threat.indicator.r keyword	SOFTWARE\Microsoft\Windows NT\CurrentVersion\Image File Execution Options\winword.exe	Abbreviated name for the hive.
threat	threat.indicator.r keyword	HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Image File Execution Options\winword.exe\Debugger	Hive-relative path of keys.
threat	threat.indicator.r keyword	Debugger	Full path, including hive, key and value
threat	threat.indicator.s long		Name of the value written.
threat	threat.indicator.s long		4 Scanner statistics
threat	threat.indicator.t keyword	ipw4-addr	20 Number of times indicator observed
threat	threat.indicator.u keyword	www.elastic.co	Type of indicator.
threat	threat.indicator.u keyword	png	Domain of the url.
threat	threat.indicator.u keyword	https://www.elastic.co/443/search?q=elasticsearch#top	File extension from the request url, excluding the leading dot.
threat	threat.indicator.u keyword	https://www.elastic.co/443/search?q=elasticsearch#top	Portion of the url after the "#".
threat	threat.indicator.u keyword	https://www.elastic.co/443/search?q=elasticsearch#top	Full unparsed URL.
threat	threat.indicator.u keyword	https://www.elastic.co/443/search?q=elasticsearch#top	Full unparsed URL.
threat	threat.indicator.u keyword	https://www.elastic.co/443/search?q=elasticsearch#top	Unmodified original url as seen in the event source.
threat	threat.indicator.u keyword	https://www.elastic.co/443/search?q=elasticsearch#top	Unmodified original url as seen in the event source.
threat	threat.indicator.u keyword		Path of the request, such as "/search".
threat	threat.indicator.u long		443 Port of the request, such as 443.
threat	threat.indicator.u keyword	example.com	Query string of the request.
threat	threat.indicator.u keyword	https	The highest registered url domain, stripped of the subdomain.
threat	threat.indicator.u keyword	east	Scheme of the url.
threat	threat.indicator.u keyword	co.uk	The subdomain of the domain.
threat	threat.indicator.u keyword		The effective top level domain (com, org, net, co.uk).
threat	threat.indicator.x keyword	* elastic.co	Username of the request.
threat	threat.indicator.x keyword	Example SHA2 High Assurance Server CA	List of subject alternative names (SAN).
threat	threat.indicator.x keyword	US	List of common name (CN) of issuing certificate authority.
threat	threat.indicator.x keyword	C=US, O=Example Inc. OU=www.example.com, CN=Example SHA2 High Assurance Server CA	List of country (C) codes
threat	threat.indicator.x keyword	Mountain View	Distinguished name (DN) of issuing certificate authority.
threat	threat.indicator.x keyword	Example Inc	List of locality names (L)
threat	threat.indicator.x keyword	www.example.com	List of organizations (O) of issuing certificate authority.
threat	threat.indicator.x keyword	California	List of organizational units (OU) of issuing certificate authority.
threat	threat.indicator.x date	2020-07-16T03:15:39Z	List of state or province names (ST, S, or P)
threat	threat.indicator.x date	2019-08-16T01:40:25Z	Time at which the certificate is no longer considered valid.
threat	threat.indicator.x keyword	RSA	Time at which the certificate is first considered valid.
threat	threat.indicator.x keyword	nistp521	Algorithm used to generate the public key.
threat	threat.indicator.x keyword		The curve used by the elliptic curve public key algorithm. This is algorithm specific.
threat	threat.indicator.x long		65537 Exponent used to derive the public key. This is algorithm specific.

threat	threat.indicator.xi	long		2048	The size of the public key space in bits.
threat	threat.indicator.xi	keyword	55FB89C7DEBF09809D12CCAA		Unique serial number issued by the certificate authority.
threat	threat.indicator.xi	keyword	SHA256-RSA		Identifier for certificate signature algorithm.
threat	threat.indicator.xi	keyword	shared.global.example.net		List of common names (CN) of subject.
threat	threat.indicator.xi	keyword	US		List of country (VC) code
threat	threat.indicator.xi	keyword	C=US, ST=California, L=San Francisco, O=Example, Inc., CN=shared.global.example.net		Distinguished name (DN) of the certificate subject entity.
threat	threat.indicator.xi	keyword	San Francisco		List of locality names (L)
threat	threat.indicator.xi	keyword	Example, Inc.		List of organizations (O) of subject.
threat	threat.indicator.xi	keyword			List of organizational units (OU) of subject.
threat	threat.indicator.xi	keyword	California		List of state or province names (ST, S, or P)
threat	threat.indicator.xi	keyword			3 Version of x509 format.
threat	threat.software.a	keyword	["X-Agent"]		Alias of the software
threat	threat.software.i	keyword	S0552		ID of the software
threat	threat.software.n	keyword	AdFind		Name of the software.
threat	threat.software.p	keyword	["Windows"]		Platforms of the software.
threat	threat.software.r	keyword	https://attack.mitre.org/software/S0552/		Software reference URL.
threat	threat.software.ty	keyword	Tool		Software type.
threat	threat.tactic.id	keyword	TA0002		Threat tactic id.
threat	threat.tactic.name	keyword	Execution		Threat tactic.
threat	threat.tactic.ref	keyword	https://attack.mitre.org/tactics/TA0002/		Threat tactic URL reference.
threat	threat.technique	keyword	T1059		Threat technique id.
threat	threat.technique	keyword	Command and Scripting Interpreter		Threat technique name.
threat	threat.technique..match_only_text		Command and Scripting Interpreter		Threat technique name.
threat	threat.technique..keyword		https://attack.mitre.org/techniques/T1059/		Threat technique URL reference.
threat	threat.technique	keyword	T1059.001		Threat subtechnique id.
threat	threat.technique	keyword	PowerShell		Threat subtechnique name.
threat	threat.technique..match_only_text		PowerShell		Threat subtechnique name.
threat	threat.technique..keyword		https://attack.mitre.org/techniques/T1059/001/		Threat subtechnique URL reference.
tls	tls.cipher	keyword	TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256		String indicating the cipher used during the current connection.
tls	tls.client.certical	keyword	Mill..		PEM-encoded stand-alone certificate offered by the client.
tls	tls.client.certical	keyword	["Mill..", "Mill.."]		Array of PEM-encoded certificates that make up the certificate chain offered by the client.
tls	tls.client.hash.m	keyword	0F76C7F2C55BF07D8EB8BF4BF8F0C9EC		Certificate fingerprint using the MD5 digest of DER-encoded version of certificate offered by the client.
tls	tls.client.hash.sh	keyword	9E393D9313888B0288266C2D915214D1D1CCEB2A		Certificate fingerprint using the SHA1 digest of DER-encoded version of certificate offered by the client.
tls	tls.client.hash.sh	keyword	0687F66A054EF17A08E2F2162EA84CB0C0D265E1D7875BE74BF3712CA92DAF0		Certificate fingerprint using the SHA256 digest of DER-encoded version of certificate offered by the client.
tls	tls.client.issuer	keyword	CN=Example Root CA, OU=Infrastructure Team, DC=example, DC=com		Distinguished name of subject of the issuer of the x.509 certificate presented by the client.
tls	tls.client.ja3	keyword	04e5b16a8bdc7f222893221c96ba240		A hash that identifies clients based on how they perform an SSL/TLS handshake.
tls	tls.client.not_after.date	keyword	2021-01-01T00:00:00.000Z		Date/Time indicating when client certificate is no longer considered valid.
tls	tls.client.not_before.date	keyword	1970-01-01T00:00:00.000Z		Date/Time indicating when client certificate is first considered valid.
tls	tls.client.server..r	keyword	www.elastic.co		Hostname the client is trying to connect to. Also called the SNI.
tls	tls.client.subject	keyword	CN=myclient, OU=Documentation Team, DC=example, DC=com		Distinguished name of subject of the x.509 certificate presented by the client.
tls	tls.client.supports	keyword	["TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384", "TLS_ECDHE_ECDSA_WITH_AES_256_GCM_SHA384", "..."]		Array of ciphers offered by the client during the client hello.
tls	tls.client.x509.al	keyword	*.elastic.co		List of subject alternative names (SAN).
tls	tls.client.x509.is	keyword	Example SHA2 High Assurance Server CA		List of common name (CN) of issuing certificate authority.
tls	tls.client.x509.is	keyword	US		List of country (VC) codes
tls	tls.client.x509.is	keyword	C=US, O=Example Inc., OU=www.example.com, CN=Example SHA2 High Assurance Server CA		Distinguished name (DN) of issuing certificate authority.
tls	tls.client.x509.is	keyword	Mountain View		List of locality names (L)
tls	tls.client.x509.is	keyword	Example Inc		List of organizations (O) of issuing certificate authority.
tls	tls.client.x509.is	keyword	www.example.com		List of organizational units (OU) of issuing certificate authority.
tls	tls.client.x509.is	keyword	California		List of state or province names (ST, S, or P)
tls	tls.client.x509.no.date	keyword	2020-07-16T03:15:39Z		Time at which the certificate is no longer considered valid.
tls	tls.client.x509.no.date	keyword	2019-08-16T01:40:25Z		Time at which the certificate is first considered valid.
tls	tls.client.x509.pu	keyword	RSA		Algorithm used to generate the public key.
tls	tls.client.x509.pu	keyword	nistp521		The curve used by the elliptic curve public key algorithm. This is algorithm specific.
tls	tls.client.x509.pu	keyword			65537 Exponent used to derive the public key. This is algorithm specific.
tls	tls.client.x509.pu	keyword			2048 The size of the public key space in bits.
tls	tls.client.x509.se	keyword	55FB89C7DEBF09809D12CCAA		Unique serial number issued by the certificate authority.
tls	tls.client.x509.sig	keyword	SHA256-RSA		Identifier for certificate signature algorithm.
tls	tls.client.x509.su	keyword	shared.global.example.net		List of common names (CN) of subject.
tls	tls.client.x509.su	keyword	US		List of country (VC) code
tls	tls.client.x509.su	keyword	C=US, ST=California, L=San Francisco, O=Example, Inc., CN=shared.global.example.net		Distinguished name (DN) of the certificate subject entity.
tls	tls.client.x509.su	keyword	San Francisco		List of locality names (L)
tls	tls.client.x509.su	keyword	Example, Inc.		List of organizations (O) of subject.
tls	tls.client.x509.su	keyword			List of organizational units (OU) of subject.
tls	tls.client.x509.su	keyword	California		List of state or province names (ST, S, or P)
tls	tls.client.x509.v	keyword			3 Version of x509 format.
tls	tls.curve	keyword	secp256r1		String indicating the curve used for the given cipher, when applicable.
tls	tls.established	boolean			Boolean flag indicating if the TLS negotiation was successful and transitioned to an encrypted tunnel.
tls	tls.next_protocol	keyword	http/1.1		String indicating the protocol being tunneled.
tls	tls.resumed	boolean			Boolean flag indicating if this TLS connection was resumed from an existing TLS negotiation.
tls	tls.server.certical	keyword	Mill..		PEM-encoded stand-alone certificate offered by the server.
tls	tls.server.certical	keyword	["Mill..", "Mill.."]		Array of PEM-encoded certificates that make up the certificate chain offered by the server.
tls	tls.server.hash.m	keyword	0F76C7F2C55BF07D8EB8BF4BF8F0C9EC		Certificate fingerprint using the MD5 digest of DER-encoded version of certificate offered by the server.
tls	tls.server.hash.al	keyword	9E393D9313888B0288266C2D915214D1D1CCEB2A		Certificate fingerprint using the SHA1 digest of DER-encoded version of certificate offered by the server.
tls	tls.server.hash.al	keyword	0687F66A054EF17A08E2F2162EA84CB0C0D265E1D7875BE74BF3712CA92DAF0		Certificate fingerprint using the SHA256 digest of DER-encoded version of certificate offered by the server.
tls	tls.server.issuer	keyword	CN=Example Root CA, OU=Infrastructure Team, DC=example, DC=com		Subject of the issuer of the x.509 certificate presented by the server.
tls	tls.server.ja3s	keyword	38441a68b754e2207b1e1d457b3641d		A hash that identifies servers based on how they perform an SSL/TLS handshake.
tls	tls.server.not_after.date	keyword	2021-01-01T00:00:00.000Z		Timestamp indicating when server certificate is no longer considered valid.
tls	tls.server.not_before.date	keyword	1970-01-01T00:00:00.000Z		Timestamp indicating when server certificate is first considered valid.
tls	tls.server.subject	keyword	CN=www.example.com, OU=Infrastructure Team, DC=example, DC=com		Subject of the x.509 certificate presented by the server.
tls	tls.server.x509.al	keyword	*.elastic.co		List of subject alternative names (SAN).
tls	tls.server.x509.is	keyword	Example SHA2 High Assurance Server CA		List of common name (CN) of issuing certificate authority.
tls	tls.server.x509.is	keyword	US		List of country (VC) codes
tls	tls.server.x509.is	keyword	C=US, O=Example Inc., OU=www.example.com, CN=Example SHA2 High Assurance Server CA		Distinguished name (DN) of issuing certificate authority.
tls	tls.server.x509.is	keyword	Mountain View		List of locality names (L)
tls	tls.server.x509.is	keyword	Example Inc		List of organizations (O) of issuing certificate authority.
tls	tls.server.x509.is	keyword	www.example.com		List of organizational units (OU) of issuing certificate authority.
tls	tls.server.x509.is	keyword	California		List of state or province names (ST, S, or P)
tls	tls.server.x509.n.date	keyword	2020-07-16T03:15:39Z		Time at which the certificate is no longer considered valid.
tls	tls.server.x509.n.date	keyword	2019-08-16T01:40:25Z		Time at which the certificate is first considered valid.
tls	tls.server.x509.pu	keyword	RSA		Algorithm used to generate the public key.
tls	tls.server.x509.pu	keyword	nistp521		The curve used by the elliptic curve public key algorithm. This is algorithm specific.
tls	tls.server.x509.pu	keyword			65537 Exponent used to derive the public key. This is algorithm specific.
tls	tls.server.x509.pu	keyword			2048 The size of the public key space in bits.
tls	tls.server.x509.su	keyword	55FB89C7DEBF09809D12CCAA		Unique serial number issued by the certificate authority.
tls	tls.server.x509.su	keyword	SHA256-RSA		Identifier for certificate signature algorithm.
tls	tls.server.x509.su	keyword	shared.global.example.net		List of common names (CN) of subject.
tls	tls.server.x509.su	keyword	US		List of country (VC) code
tls	tls.server.x509.su	keyword	C=US, ST=California, L=San Francisco, O=Example, Inc., CN=shared.global.example.net		Distinguished name (DN) of the certificate subject entity.
tls	tls.server.x509.su	keyword	San Francisco		List of locality names (L)
tls	tls.server.x509.su	keyword	Example, Inc.		List of organizations (O) of subject.
tls	tls.server.x509.su	keyword			List of organizational units (OU) of subject.
tls	tls.server.x509.v	keyword	California		List of state or province names (ST, S, or P)
tls	tls.version	keyword			3 Version of x509 format.
tls	tls.version..proto	keyword	tls		1.2 Numeric part of the version parsed from the original string.
trace	trace.id	keyword	4bf52f3577b34da6a3ce929d0e0e4736		Normalized lowercase protocol name parsed from original string.
transaction	transaction.id	keyword	0006f7aa0ba902b7		Unique identifier of the trace.
uri	uri.domain	keyword	www.elastic.co		Domain of the uri.
uri	uri.extension	keyword	png		File extension from the request uri, excluding the leading dot.
uri	uri.fragment	keyword			Portion of the uri after the '#'. Full unparsed URL.
uri	uri.full	wildcard	https://www.elastic.co/443/search?q=elasticsearch#top		Full unparsed URL.
uri	uri.full.text	match_only_text	https://www.elastic.co/443/search?q=elasticsearch#top		Full unparsed URL.
uri	uri.original	wildcard	https://www.elastic.co/443/search?q=elasticsearch#top or /search?q=elasticsearch		Unmodified original uri as seen in the event source.
uri	uri.original.text	match_only_text	https://www.elastic.co/443/search?q=elasticsearch#top or /search?q=elasticsearch		Unmodified original uri as seen in the event source.
uri	uri.password	keyword			Password of the request.
uri	uri.path	wildcard			Path of the request, such as "/search".
uri	uri.port	long			443 Port of the request, such as 443.
uri	uri.query	keyword			Query string of the request.
uri	uri.registered..do	keyword	example.com		The highest registered uri domain, stripped of the subdomain.
uri	uri.scheme	keyword	https		Scheme of the uri.
uri	uri.subdomain	keyword	east		The subdomain of the domain.
uri	uri.top_level..don	keyword	co.uk		The effective top level domain (com, org, net, co.uk).
uri	uri.username	keyword			Username of the request.
user	user.changes.do	keyword			Name of the directory the user is a member of.
user	user.changes.em	keyword			User email address.
user	user.changes.full	keyword	Albert Einstein		User's full name, if available.
user	user.changes.full.match_only_text		Albert Einstein		User's full name, if available.
user	user.changes.grc	keyword			Name of the directory the group is a member of.
user	user.changes.grc	keyword			Unique identifier for the group on the system/platform.
user	user.changes.grc	keyword			Name of the group.

user	user.changes.hai keyword		Unique user hash to correlate information for a user in anonymized form.
user	user.changes.id keyword	S-1-5-21-202424912787-2692429404-2351956786-1000	Unique identifier of the user.
user	user.changes.nai keyword	a.einstein	Short name or login of the user.
user	user.changes.nai match_only_text	a.einstein	Short name or login of the user.
user	user.changes.rok keyword	["kibana_admin", "reporting_user"]	Array of user roles at the time of the event.
user	user.domain keyword		Name of the directory the user is a member of.
user	user.effective.doi keyword		Name of the directory the user is a member of.
user	user.effective.em keyword		User email address.
user	user.effective.full keyword	Albert Einstein	User's full name, if available.
user	user.effective.full match_only_text	Albert Einstein	User's full name, if available.
user	user.effective.grc keyword		Name of the directory the group is a member of.
user	user.effective.grc keyword		Unique identifier for the group on the system/platform.
user	user.effective.grc keyword		Name of the group.
user	user.effective.hai keyword		Unique user hash to correlate information for a user in anonymized form.
user	user.effective.id keyword	S-1-5-21-202424912787-2692429404-2351956786-1000	Unique identifier of the user.
user	user.effective.nai keyword	a.einstein	Short name or login of the user.
user	user.effective.nai match_only_text	a.einstein	Short name or login of the user.
user	user.effective.rok keyword	["kibana_admin", "reporting_user"]	Array of user roles at the time of the event.
user	user.email keyword		User email address.
user	user.full_name keyword	Albert Einstein	User's full name, if available.
user	user.full_name.te match_only_text	Albert Einstein	User's full name, if available.
user	user.group.doma keyword		Name of the directory the group is a member of.
user	user.group.id keyword		Unique identifier for the group on the system/platform.
user	user.group.name keyword		Name of the group.
user	user.hash keyword		Unique user hash to correlate information for a user in anonymized form.
user	user.id keyword	S-1-5-21-202424912787-2692429404-2351956786-1000	Unique identifier of the user.
user	user.name keyword	a.einstein	Short name or login of the user.
user	user.name.text match_only_text	a.einstein	Short name or login of the user.
user	user.risk.calculat keyword	High	A risk classification level calculated by an internal system as part of entity analytics and entity risk scoring.
user	user.risk.calculat float		880.73 A risk classification score calculated by an internal system as part of entity analytics and entity risk scoring.
user	user.risk.calculat float		88.73 A normalized risk score calculated by an internal system.
user	user.risk.static.le keyword	High	A risk classification level obtained from outside the system, such as from some external Threat Intelligence Platform.
user	user.risk.static.le float		830 A risk classification score obtained from outside the system, such as from some external Threat Intelligence Platform.
user	user.risk.static.le float		83 A normalized risk score calculated by an external system.
user	user.roles keyword	["kibana_admin", "reporting_user"]	Array of user roles at the time of the event.
user	user.target.doma keyword		Name of the directory the user is a member of.
user	user.target.email keyword		User email address.
user	user.target.full_n keyword	Albert Einstein	User's full name, if available.
user	user.target.full_n match_only_text	Albert Einstein	User's full name, if available.
user	user.target.group keyword		Name of the directory the group is a member of.
user	user.target.group keyword		Unique identifier for the group on the system/platform.
user	user.target.group keyword		Name of the group.
user	user.target.hash keyword		Unique user hash to correlate information for a user in anonymized form.
user	user.target.id keyword	S-1-5-21-202424912787-2692429404-2351956786-1000	Unique identifier of the user.
user	user.target.name keyword	a.einstein	Short name or login of the user.
user	user.target.name match_only_text	a.einstein	Short name or login of the user.
user	user.target.roles keyword	["kibana_admin", "reporting_user"]	Array of user roles at the time of the event.
user_agent	user_agent.device keyword	iPhone	Name of the device.
user_agent	user_agent.name keyword	Safari	Name of the user agent.
user_agent	user_agent.orig keyword	Mozilla/5.0 (iPhone; CPU iPhone OS 12_1 like Mac OS X) AppleWebKit/605.1.15 (KHTML, like Gecko) Version/12.0 Mobile/15E148 Safari/604.1	Unparsed user_agent string.
user_agent	user_agent.orig keyword	Mozilla/5.0 (iPhone; CPU iPhone OS 12_1 like Mac OS X) AppleWebKit/605.1.15 (KHTML, like Gecko) Version/12.0 Mobile/15E148 Safari/604.1	Unparsed user_agent string.
user_agent	user_agent.os.fla keyword	debian	OS family (such as redhat, debian, freebsd, windows).
user_agent	user_agent.os.fu keyword	Mac OS Mojave	Operating system name, including the version or code name.
user_agent	user_agent.os.fu match_only_text	Mac OS Mojave	Operating system name, including the version or code name.
user_agent	user_agent.os.ke keyword	4.0-112-generic	Operating system kernel version as a raw string.
user_agent	user_agent.os.ni keyword	Mac OS X	Operating system name, without the version.
user_agent	user_agent.os.ni match_only_text	Mac OS X	Operating system name, without the version.
user_agent	user_agent.os.pi keyword	darwin	Operating system platform (such as centos, ubuntu, windows).
user_agent	user_agent.os.ty keyword	macos	Which commercial OS family (one of: linux, macos, unix, windows, ios or android).
user_agent	user_agent.os.vi keyword	10.14.1	Operating system version as a raw string.
user_agent	user_agent.versi keyword		12 Version of the user agent.
volume	volume.bus_type keyword	FileBackedVirtual	Bus type of the device.
volume	volume.default_s keyword		Bus type of the device.
volume	volume.device_n keyword		Device name of the volume.
volume	volume.device_ty keyword	CD-ROM File System	Volume device type.
volume	volume.dos_nam keyword	E:	DOS name of the device.
volume	volume.file_syste keyword		Volume device file system type.
volume	volume.mount_n keyword		Mount name of the volume.
volume	volume.nt_name keyword	\Device\Cdrom1	NT name of the device.
volume	volume.product_id keyword		ProductID of the device.
volume	volume.product_id keyword	Virtual DVD-ROM	Produce name of the volume.
volume	volume.removeabi boolean		Indicates if the volume is removable.
volume	volume.serial_nu keyword		Serial number of the device.
volume	volume.size long		Size of the volume device in bytes.
volume	volume.vendor_id keyword		VendorID of the device.
volume	volume.vendor_r keyword	Mft	Vendor name of the device.
volume	volume.writable boolean		Indicates if the volume is writable.
vulnerability	vulnerability.cate keyword	["Firewall"]	Category of a vulnerability.
vulnerability	vulnerability.class keyword	CVSS	Classification of the vulnerability.
vulnerability	vulnerability.desc keyword	In macOS before 2.12.6, there is a vulnerability in the RPC...	Description of the vulnerability.
vulnerability	vulnerability.desc match_only_text	In macOS before 2.12.6, there is a vulnerability in the RPC...	Description of the vulnerability.
vulnerability	vulnerability.enur keyword	CVE	Identifier of the vulnerability.
vulnerability	vulnerability.id keyword	CVE-2019-00001	ID of the vulnerability.
vulnerability	vulnerability.ref keyword	https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2019-6111	Reference of the vulnerability.
vulnerability	vulnerability.repo keyword		20191016 Scan identification number.
vulnerability	vulnerability.scan keyword	Tenable	Name of the scanner vendor.
vulnerability	vulnerability.scon float		5.5 Vulnerability Base score.
vulnerability	vulnerability.scon float		5.5 Vulnerability Environmental score.
vulnerability	vulnerability.scon float		Vulnerability Temporal score.
vulnerability	vulnerability.scon keyword		2 CVSS version.
vulnerability	vulnerability.seve keyword	Critical	Severity of the vulnerability.