

Field Set:

- **Field:** @timestamp
 - **Type:** date
 - **Example:** 2016-05-23T08:05:34.853Z
 - **Description:** Date/time when the event originated.
- **Field:** labels
 - **Type:** object
 - **Example:** {"application": "foo-bar", "env": "production"}
 - **Description:** Custom key/value pairs.
- **Field:** message
 - **Type:** match_only_text
 - **Example:** Hello World
 - **Description:** Log message optimized for viewing in a log viewer.
- **Field:** tags
 - **Type:** keyword
 - **Example:** ["production", "env2"]
 - **Description:** List of keywords used to tag each event.

Field Set: agent.build

- **Field:** agent.build.original
 - **Type:** keyword
 - **Example:** metricbeat version 7.6.0 (amd64), libbeat 7.6.0
[6a23e8f8f30f5001ba344e4e54d8d9cb82cb107c built 2020-02-05 23:10:10 +0000 UTC]
 - **Description:** Extended build information for the agent.

Field Set: agent

- **Field:** agent.ephemeral_id
 - **Type:** keyword
 - **Example:** 8a4f500f
 - **Description:** Ephemeral identifier of this agent.
- **Field:** agent.id
 - **Type:** keyword
 - **Example:** 8a4f500d
 - **Description:** Unique identifier of this agent.
- **Field:** agent.name
 - **Type:** keyword
 - **Example:** foo
 - **Description:** Custom name of the agent.
- **Field:** agent.type
 - **Type:** keyword
 - **Example:** filebeat
 - **Description:** Type of the agent.
- **Field:** agent.version
 - **Type:** keyword
 - **Example:** 6.0.0-rc2
 - **Description:** Version of the agent.

Field Set: client

- **Field:** client.address
- **Type:** keyword
- **Description:** Client network address.

Field Set: client.as

- **Field:** client.as.number
- **Type:** long
- **Example:** 15169
- **Description:** Unique number allocated to the autonomous system.

Field Set: client.as.organization

- **Field:** client.as.organization.name
- **Type:** keyword
- **Example:** Google LLC
- **Description:** Organization name.

Field Set: client.as.organization.name

- **Field:** client.as.organization.name.text
- **Type:** match_only_text
- **Example:** Google LLC
- **Description:** Organization name.

Field Set: client

- **Field:** client.bytes
- **Type:** long
- **Example:** 184
- **Description:** Bytes sent from the client to the server.
- **Field:** client.domain
- **Type:** keyword
- **Example:** foo.example.com
- **Description:** The domain name of the client.

Field Set: client.geo

- **Field:** client.geo.city_name
- **Type:** keyword
- **Example:** Montreal
- **Description:** City name.
- **Field:** client.geo.continent_code
- **Type:** keyword
- **Description:** Continent code.
- **Field:** client.geo.continent_name
- **Type:** keyword
- **Example:** North America
- **Description:** Name of the continent.
- **Field:** client.geo.country_iso_code
- **Type:** keyword
- **Example:** CA
- **Description:** Country ISO code.

- **Field:** client.geo.country_name
 - **Type:** keyword
 - **Example:** Canada
 - **Description:** Country name.
- **Field:** client.geo.location
 - **Type:** geo_point
 - **Example:** { "lon": -73.614830, "lat": 45.505918 }
 - **Description:** Longitude and latitude.
- **Field:** client.geo.name
 - **Type:** keyword
 - **Example:** boston-dc
 - **Description:** User-defined description of a location.
- **Field:** client.geo.postal_code
 - **Type:** keyword
 - **Example:** 94040
 - **Description:** Postal code.
- **Field:** client.geo.region_iso_code
 - **Type:** keyword
 - **Example:** CA-QC
 - **Description:** Region ISO code.
- **Field:** client.geo.region_name
 - **Type:** keyword
 - **Example:** Quebec
 - **Description:** Region name.
- **Field:** client.geo.timezone
 - **Type:** keyword
 - **Example:** America/Argentina/Buenos_Aires
 - **Description:** Time zone.

Field Set: client

- **Field:** client.ip
 - **Type:** ip
 - **Description:** IP address of the client.
- **Field:** client.mac
 - **Type:** keyword
 - **Example:** 00-00-5E-00-53-23
 - **Description:** MAC address of the client.

Field Set: client.nat

- **Field:** client.nat.ip
 - **Type:** ip
 - **Description:** Client NAT ip address
- **Field:** client.nat.port
 - **Type:** long
 - **Description:** Client NAT port

Field Set: client

- **Field:** client.packets
 - **Type:** long
 - **Example:** 12

- **Description:** Packets sent from the client to the server.
- **Field:** client.port
 - **Type:** long
 - **Description:** Port of the client.
- **Field:** client.registered_domain
 - **Type:** keyword
 - **Example:** example.com
 - **Description:** The highest registered client domain, stripped of the subdomain.
- **Field:** client.subdomain
 - **Type:** keyword
 - **Example:** east
 - **Description:** The subdomain of the domain.
- **Field:** client.top_level_domain
 - **Type:** keyword
 - **Example:** co.uk
 - **Description:** The effective top level domain (com, org, net, co.uk).

Field Set: client.user

- **Field:** client.user.domain
 - **Type:** keyword
 - **Description:** Name of the directory the user is a member of.
- **Field:** client.user.email
 - **Type:** keyword
 - **Description:** User email address.
- **Field:** client.user.full_name
 - **Type:** keyword
 - **Example:** Albert Einstein
 - **Description:** User's full name, if available.

Field Set: client.user.full_name

- **Field:** client.user.full_name.text
 - **Type:** match_only_text
 - **Example:** Albert Einstein
 - **Description:** User's full name, if available.

Field Set: client.user.group

- **Field:** client.user.group.domain
 - **Type:** keyword
 - **Description:** Name of the directory the group is a member of.
- **Field:** client.user.group.id
 - **Type:** keyword
 - **Description:** Unique identifier for the group on the system/platform.
- **Field:** client.user.group.name
 - **Type:** keyword
 - **Description:** Name of the group.

Field Set: client.user

- **Field:** client.user.hash
 - **Type:** keyword
 - **Description:** Unique user hash to correlate information for a user in anonymized form.
- **Field:** client.user.id
 - **Type:** keyword
 - **Example:** S-1-5-21-202424912787-2692429404-2351956786-1000
 - **Description:** Unique identifier of the user.
- **Field:** client.user.name
 - **Type:** keyword
 - **Example:** a.einstein
 - **Description:** Short name or login of the user.

Field Set: client.user.name

- **Field:** client.user.name.text
 - **Type:** match_only_text
 - **Example:** a.einstein
 - **Description:** Short name or login of the user.

Field Set: client.user

- **Field:** client.user.roles
 - **Type:** keyword
 - **Example:** ["kibana_admin", "reporting_user"]
 - **Description:** Array of user roles at the time of the event.

Field Set: cloud.account

- **Field:** cloud.account.id
 - **Type:** keyword
 - **Example:** 666777888999
 - **Description:** The cloud account or organization id.
- **Field:** cloud.account.name
 - **Type:** keyword
 - **Example:** elastic-dev
 - **Description:** The cloud account name.

Field Set: cloud

- **Field:** cloud.availability_zone
 - **Type:** keyword
 - **Example:** us-east-1c
 - **Description:** Availability zone in which this host, resource, or service is located.

Field Set: cloud.instance

- **Field:** cloud.instance.id
 - **Type:** keyword
 - **Example:** i-1234567890abcdef0
 - **Description:** Instance ID of the host machine.
- **Field:** cloud.instance.name
 - **Type:** keyword
 - **Description:** Instance name of the host machine.

Field Set: cloud.machine

- **Field:** cloud.machine.type
- **Type:** keyword
- **Example:** t2.medium
- **Description:** Machine type of the host machine.

Field Set: cloud.origin.account

- **Field:** cloud.origin.account.id
- **Type:** keyword
- **Example:** 666777888999
- **Description:** The cloud account or organization id.
- **Field:** cloud.origin.account.name
- **Type:** keyword
- **Example:** elastic-dev
- **Description:** The cloud account name.

Field Set: cloud.origin

- **Field:** cloud.origin.availability_zone
- **Type:** keyword
- **Example:** us-east-1c
- **Description:** Availability zone in which this host, resource, or service is located.

Field Set: cloud.origin.instance

- **Field:** cloud.origin.instance.id
- **Type:** keyword
- **Example:** i-1234567890abcdef0
- **Description:** Instance ID of the host machine.
- **Field:** cloud.origin.instance.name
- **Type:** keyword
- **Description:** Instance name of the host machine.

Field Set: cloud.origin.machine

- **Field:** cloud.origin.machine.type
- **Type:** keyword
- **Example:** t2.medium
- **Description:** Machine type of the host machine.

Field Set: cloud.origin.project

- **Field:** cloud.origin.project.id
- **Type:** keyword
- **Example:** my-project
- **Description:** The cloud project id.
- **Field:** cloud.origin.project.name
- **Type:** keyword
- **Example:** my project
- **Description:** The cloud project name.

Field Set: cloud.origin

- **Field:** cloud.origin.provider
 - **Type:** keyword
 - **Example:** aws
 - **Description:** Name of the cloud provider.
- **Field:** cloud.origin.region
 - **Type:** keyword
 - **Example:** us-east-1
 - **Description:** Region in which this host, resource, or service is located.

Field Set: cloud.origin.service

- **Field:** cloud.origin.service.name
 - **Type:** keyword
 - **Example:** lambda
 - **Description:** The cloud service name.

Field Set: cloud.project

- **Field:** cloud.project.id
 - **Type:** keyword
 - **Example:** my-project
 - **Description:** The cloud project id.
- **Field:** cloud.project.name
 - **Type:** keyword
 - **Example:** my project
 - **Description:** The cloud project name.

Field Set: cloud

- **Field:** cloud.provider
 - **Type:** keyword
 - **Example:** aws
 - **Description:** Name of the cloud provider.
- **Field:** cloud.region
 - **Type:** keyword
 - **Example:** us-east-1
 - **Description:** Region in which this host, resource, or service is located.

Field Set: cloud.service

- **Field:** cloud.service.name
 - **Type:** keyword
 - **Example:** lambda
 - **Description:** The cloud service name.

Field Set: cloud.target.account

- **Field:** cloud.target.account.id
 - **Type:** keyword
 - **Example:** 666777888999
 - **Description:** The cloud account or organization id.
- **Field:** cloud.target.account.name
 - **Type:** keyword
 - **Example:** elastic-dev
 - **Description:** The cloud account name.

Field Set: cloud.target

- **Field:** cloud.target.availability_zone
- **Type:** keyword
- **Example:** us-east-1c
- **Description:** Availability zone in which this host, resource, or service is located.

Field Set: cloud.target.instance

- **Field:** cloud.target.instance.id
- **Type:** keyword
- **Example:** i-1234567890abcdef0
- **Description:** Instance ID of the host machine.
- **Field:** cloud.target.instance.name
- **Type:** keyword
- **Description:** Instance name of the host machine.

Field Set: cloud.target.machine

- **Field:** cloud.target.machine.type
- **Type:** keyword
- **Example:** t2.medium
- **Description:** Machine type of the host machine.

Field Set: cloud.target.project

- **Field:** cloud.target.project.id
- **Type:** keyword
- **Example:** my-project
- **Description:** The cloud project id.
- **Field:** cloud.target.project.name
- **Type:** keyword
- **Example:** my project
- **Description:** The cloud project name.

Field Set: cloud.target

- **Field:** cloud.target.provider
- **Type:** keyword
- **Example:** aws
- **Description:** Name of the cloud provider.
- **Field:** cloud.target.region
- **Type:** keyword
- **Example:** us-east-1
- **Description:** Region in which this host, resource, or service is located.

Field Set: cloud.target.service

- **Field:** cloud.target.service.name
- **Type:** keyword
- **Example:** lambda
- **Description:** The cloud service name.

Field Set: container.cpu

- **Field:** container.cpu.usage
- **Type:** scaled_float
- **Description:** Percent CPU used, between 0 and 1.

Field Set: container.disk.read

- **Field:** container.disk.read.bytes
- **Type:** long
- **Description:** The number of bytes read by all disks.

Field Set: container.disk.write

- **Field:** container.disk.write.bytes
- **Type:** long
- **Description:** The number of bytes written on all disks.

Field Set: container

- **Field:** container.id
- **Type:** keyword
- **Description:** Unique container id.

Field Set: container.image.hash

- **Field:** container.image.hash.all
- **Type:** keyword
- **Example:**
[sha256:f8fefc80e3273dc756f288a63945820d6476ad64883892c771b5e2ece6bf1b26]
- **Description:** An array of digests of the image the container was built on.

Field Set: container.image

- **Field:** container.image.name
- **Type:** keyword
- **Description:** Name of the image the container was built on.
- **Field:** container.image.tag
- **Type:** keyword
- **Description:** Container image tags.

Field Set: container

- **Field:** container.labels
- **Type:** object
- **Description:** Image labels.

Field Set: container.memory

- **Field:** container.memory.usage
- **Type:** scaled_float
- **Description:** Percent memory used, between 0 and 1.

Field Set: container

- **Field:** container.name
- **Type:** keyword
- **Description:** Container name.

Field Set: container.network.egress

- **Field:** container.network.egress.bytes
- **Type:** long
- **Description:** The number of bytes sent on all network interfaces.

Field Set: container.network.ingress

- **Field:** container.network.ingress.bytes
- **Type:** long
- **Description:** The number of bytes received on all network interfaces.

Field Set: container

- **Field:** container.runtime
- **Type:** keyword
- **Example:** docker
- **Description:** Runtime managing this container.

Field Set: container.security_context

- **Field:** container.security_context.privileged
- **Type:** boolean
- **Description:** Indicates whether the container is running in privileged mode.

Field Set: data_stream

- **Field:** data_stream.dataset
- **Type:** constant_keyword
- **Example:** nginx.access
- **Description:** The field can contain anything that makes sense to signify the source of the data.
- **Field:** data_stream.namespace
- **Type:** constant_keyword
- **Example:** production
- **Description:** A user defined namespace. Namespaces are useful to allow grouping of data.
- **Field:** data_stream.type
- **Type:** constant_keyword
- **Example:** logs
- **Description:** An overarching type for the data stream.

Field Set: destination

- **Field:** destination.address
- **Type:** keyword
- **Description:** Destination network address.

Field Set: destination.as

- **Field:** destination.as.number
- **Type:** long
- **Example:** 15169
- **Description:** Unique number allocated to the autonomous system.

Field Set: destination.as.organization

- **Field:** destination.as.organization.name
- **Type:** keyword
- **Example:** Google LLC
- **Description:** Organization name.

Field Set: destination.as.organization.name

- **Field:** destination.as.organization.name.text
- **Type:** match_only_text
- **Example:** Google LLC
- **Description:** Organization name.

Field Set: destination

- **Field:** destination.bytes
- **Type:** long
- **Example:** 184
- **Description:** Bytes sent from the destination to the source.
- **Field:** destination.domain
- **Type:** keyword
- **Example:** foo.example.com
- **Description:** The domain name of the destination.

Field Set: destination.geo

- **Field:** destination.geo.city_name
- **Type:** keyword
- **Example:** Montreal
- **Description:** City name.
- **Field:** destination.geo.continent_code
- **Type:** keyword
- **Description:** Continent code.
- **Field:** destination.geo.continent_name
- **Type:** keyword
- **Example:** North America
- **Description:** Name of the continent.
- **Field:** destination.geo.country_iso_code
- **Type:** keyword
- **Example:** CA
- **Description:** Country ISO code.
- **Field:** destination.geo.country_name
- **Type:** keyword
- **Example:** Canada
- **Description:** Country name.
- **Field:** destination.geo.location
- **Type:** geo_point
- **Example:** { "lon": -73.614830, "lat": 45.505918 }
- **Description:** Longitude and latitude.
- **Field:** destination.geo.name
- **Type:** keyword
- **Example:** boston-dc
- **Description:** User-defined description of a location.

- **Field:** destination.geo.postal_code
 - **Type:** keyword
 - **Example:** 94040
 - **Description:** Postal code.
- **Field:** destination.geo.region_iso_code
 - **Type:** keyword
 - **Example:** CA-QC
 - **Description:** Region ISO code.
- **Field:** destination.geo.region_name
 - **Type:** keyword
 - **Example:** Quebec
 - **Description:** Region name.
- **Field:** destination.geo.timezone
 - **Type:** keyword
 - **Example:** America/Argentina/Buenos_Aires
 - **Description:** Time zone.

Field Set: destination

- **Field:** destination.ip
 - **Type:** ip
 - **Description:** IP address of the destination.
- **Field:** destination.mac
 - **Type:** keyword
 - **Example:** 00-00-5E-00-53-23
 - **Description:** MAC address of the destination.

Field Set: destination.nat

- **Field:** destination.nat.ip
 - **Type:** ip
 - **Description:** Destination NAT ip
- **Field:** destination.nat.port
 - **Type:** long
 - **Description:** Destination NAT Port

Field Set: destination

- **Field:** destination.packets
 - **Type:** long
 - **Example:** 12
 - **Description:** Packets sent from the destination to the source.
- **Field:** destination.port
 - **Type:** long
 - **Description:** Port of the destination.
- **Field:** destination.registered_domain
 - **Type:** keyword
 - **Example:** example.com
 - **Description:** The highest registered destination domain, stripped of the subdomain.
- **Field:** destination.subdomain
 - **Type:** keyword
 - **Example:** east
 - **Description:** The subdomain of the domain.

- **Field:** destination.top_level_domain
- **Type:** keyword
- **Example:** co.uk
- **Description:** The effective top level domain (com, org, net, co.uk).

Field Set: destination.user

- **Field:** destination.user.domain
- **Type:** keyword
- **Description:** Name of the directory the user is a member of.
- **Field:** destination.user.email
- **Type:** keyword
- **Description:** User email address.
- **Field:** destination.user.full_name
- **Type:** keyword
- **Example:** Albert Einstein
- **Description:** User's full name, if available.

Field Set: destination.user.full_name

- **Field:** destination.user.full_name.text
- **Type:** match_only_text
- **Example:** Albert Einstein
- **Description:** User's full name, if available.

Field Set: destination.user.group

- **Field:** destination.user.group.domain
- **Type:** keyword
- **Description:** Name of the directory the group is a member of.
- **Field:** destination.user.group.id
- **Type:** keyword
- **Description:** Unique identifier for the group on the system/platform.
- **Field:** destination.user.group.name
- **Type:** keyword
- **Description:** Name of the group.

Field Set: destination.user

- **Field:** destination.user.hash
- **Type:** keyword
- **Description:** Unique user hash to correlate information for a user in anonymized form.
- **Field:** destination.user.id
- **Type:** keyword
- **Example:** S-1-5-21-202424912787-2692429404-2351956786-1000
- **Description:** Unique identifier of the user.
- **Field:** destination.user.name
- **Type:** keyword
- **Example:** a.einstein
- **Description:** Short name or login of the user.

Field Set: destination.user.name

- **Field:** destination.user.name.text
- **Type:** match_only_text
- **Example:** a.einstein
- **Description:** Short name or login of the user.

Field Set: destination.user

- **Field:** destination.user.roles
- **Type:** keyword
- **Example:** ["kibana_admin", "reporting_user"]
- **Description:** Array of user roles at the time of the event.

Field Set: device

- **Field:** device.id
- **Type:** keyword
- **Example:** 00000000-54b3-e7c7-0000-000046bffd97
- **Description:** The unique identifier of a device.
- **Field:** device.manufacturer
- **Type:** keyword
- **Example:** Samsung
- **Description:** The vendor name of the device manufacturer.

Field Set: device.model

- **Field:** device.model.identifier
- **Type:** keyword
- **Example:** SM-G920F
- **Description:** The machine readable identifier of the device model.
- **Field:** device.model.name
- **Type:** keyword
- **Example:** Samsung Galaxy S6
- **Description:** The human readable marketing name of the device model.

Field Set: device

- **Field:** device.serial_number
- **Type:** keyword
- **Example:** DJGAQS4CW5
- **Description:** Serial Number of the device

Field Set: dll.code_signature

- **Field:** dll.code_signature.digest_algorithm
- **Type:** keyword
- **Example:** sha256
- **Description:** Hashing algorithm used to sign the process.
- **Field:** dll.code_signature.exists
- **Type:** boolean
- **Example:** true
- **Description:** Boolean to capture if a signature is present.
- **Field:** dll.code_signature.flags
- **Type:** keyword
- **Example:** 570522385
- **Description:** Code signing flags of the process

- **Field:** dll.code_signature.signing_id
 - **Type:** keyword
 - **Example:** com.apple.xpc.proxy
 - **Description:** The identifier used to sign the process.
- **Field:** dll.code_signature.status
 - **Type:** keyword
 - **Example:** ERROR_UNTRUSTED_ROOT
 - **Description:** Additional information about the certificate status.
- **Field:** dll.code_signature.subject_name
 - **Type:** keyword
 - **Example:** Microsoft Corporation
 - **Description:** Subject name of the code signer
- **Field:** dll.code_signature.team_id
 - **Type:** keyword
 - **Example:** EQHXZ8M8AV
 - **Description:** The team identifier used to sign the process.
- **Field:** dll.code_signature.timestamp
 - **Type:** date
 - **Example:** 2021-01-01T12:10:30Z
 - **Description:** When the signature was generated and signed.
- **Field:** dll.code_signature.trusted
 - **Type:** boolean
 - **Example:** true
 - **Description:** Stores the trust status of the certificate chain.
- **Field:** dll.code_signature.valid
 - **Type:** boolean
 - **Example:** true
 - **Description:** Boolean to capture if the digital signature is verified against the binary content.

Field Set: dll.hash

- **Field:** dll.hash.cdhash
 - **Type:** keyword
 - **Example:** 3783b4052fd474dbe30676b45c329e7a6d44acd9
 - **Description:** The Code Directory (CD) hash of an executable.
- **Field:** dll.hash.md5
 - **Type:** keyword
 - **Description:** MD5 hash.
- **Field:** dll.hash.sha1
 - **Type:** keyword
 - **Description:** SHA1 hash.
- **Field:** dll.hash.sha256
 - **Type:** keyword
 - **Description:** SHA256 hash.
- **Field:** dll.hash.sha384
 - **Type:** keyword
 - **Description:** SHA384 hash.
- **Field:** dll.hash.sha512
 - **Type:** keyword
 - **Description:** SHA512 hash.

- **Field:** dll.hash.ssdeep
- **Type:** keyword
- **Description:** SSDEEP hash.
- **Field:** dll.hash.tlsh
- **Type:** keyword
- **Description:** TLSH hash.

Field Set: dll

- **Field:** dll.name
- **Type:** keyword
- **Example:** kernel32.dll
- **Description:** Name of the library.
- **Field:** dll.path
- **Type:** keyword
- **Example:** C:\Windows\System32\kernel32.dll
- **Description:** Full file path of the library.

Field Set: dll.pe

- **Field:** dll.pe.architecture
- **Type:** keyword
- **Example:** x64
- **Description:** CPU architecture target for the file.
- **Field:** dll.pe.company
- **Type:** keyword
- **Example:** Microsoft Corporation
- **Description:** Internal company name of the file, provided at compile-time.
- **Field:** dll.pe.description
- **Type:** keyword
- **Example:** Paint
- **Description:** Internal description of the file, provided at compile-time.
- **Field:** dll.pe.file_version
- **Type:** keyword
- **Example:** 6.3.9600.17415
- **Description:** Process name.
- **Field:** dll.pe.go_import_hash
- **Type:** keyword
- **Example:** 10bddcb4cee42080f76c88d9ff964491
- **Description:** A hash of the Go language imports in a PE file.
- **Field:** dll.pe.go_imports
- **Type:** flattened
- **Description:** List of imported Go language element names and types.
- **Field:** dll.pe.go_imports_names_entropy
- **Type:** long
- **Description:** Shannon entropy calculation from the list of Go imports.
- **Field:** dll.pe.go_imports_names_var_entropy
- **Type:** long
- **Description:** Variance for Shannon entropy calculation from the list of Go imports.
- **Field:** dll.pe.go_stripped
- **Type:** boolean
- **Description:** Whether the file is a stripped or obfuscated Go executable.

- **Field:** dll.pe.imphash
 - **Type:** keyword
 - **Example:** 0c6803c4e922103c4dca5963aad36ddf
 - **Description:** A hash of the imports in a PE file.
- **Field:** dll.pe.import_hash
 - **Type:** keyword
 - **Example:** d41d8cd98f00b204e9800998ecf8427e
 - **Description:** A hash of the imports in a PE file.
- **Field:** dll.pe.imports
 - **Type:** flattened
 - **Description:** List of imported element names and types.
- **Field:** dll.pe.imports_names_entropy
 - **Type:** long
 - **Description:** Shannon entropy calculation from the list of imported element names and types.
- **Field:** dll.pe.imports_names_var_entropy
 - **Type:** long
 - **Description:** Variance for Shannon entropy calculation from the list of imported element names and types.
- **Field:** dll.pe.original_file_name
 - **Type:** keyword
 - **Example:** MSPAINT.EXE
 - **Description:** Internal name of the file, provided at compile-time.
- **Field:** dll.pe.pehash
 - **Type:** keyword
 - **Example:** 73ff189b63cd6be375a7ff25179a38d347651975
 - **Description:** A hash of the PE header and data from one or more PE sections.
- **Field:** dll.pe.product
 - **Type:** keyword
 - **Example:** Microsoft® Windows® Operating System
 - **Description:** Internal product name of the file, provided at compile-time.
- **Field:** dll.pe.sections
 - **Type:** nested
 - **Description:** Section information of the PE file.

Field Set: dll.pe.sections

- **Field:** dll.pe.sections.entropy
 - **Type:** long
 - **Description:** Shannon entropy calculation from the section.
- **Field:** dll.pe.sections.name
 - **Type:** keyword
 - **Description:** PE Section List name.
- **Field:** dll.pe.sections.physical_size
 - **Type:** long
 - **Description:** PE Section List physical size.
- **Field:** dll.pe.sections.var_entropy
 - **Type:** long
 - **Description:** Variance for Shannon entropy calculation from the section.
- **Field:** dll.pe.sections.virtual_size
 - **Type:** long
 - **Description:** PE Section List virtual size. This is always the same as `physical\_size`.

Field Set: dns

- **Field:** dns.answers
- **Type:** object
- **Description:** Array of DNS answers.

Field Set: dns.answers

- **Field:** dns.answers.class
- **Type:** keyword
- **Example:** IN
- **Description:** The class of DNS data contained in this resource record.
- **Field:** dns.answers.data
- **Type:** keyword
- **Example:** 10.10.10.10
- **Description:** The data describing the resource.
- **Field:** dns.answers.name
- **Type:** keyword
- **Example:** www.example.com
- **Description:** The domain name to which this resource record pertains.
- **Field:** dns.answers.ttl
- **Type:** long
- **Example:** 180
- **Description:** The time interval in seconds that this resource record may be cached before it should be discarded.
- **Field:** dns.answers.type
- **Type:** keyword
- **Example:** CNAME
- **Description:** The type of data contained in this resource record.

Field Set: dns

- **Field:** dns.header_flags
- **Type:** keyword
- **Example:** ["RD", "RA"]
- **Description:** Array of DNS header flags.
- **Field:** dns.id
- **Type:** keyword
- **Example:** 62111
- **Description:** The DNS packet identifier assigned by the program that generated the query. The identifier is copied to the response.
- **Field:** dns.op_code
- **Type:** keyword
- **Example:** QUERY
- **Description:** The DNS operation code that specifies the kind of query in the message.

Field Set: dns.question

- **Field:** dns.question.class
- **Type:** keyword
- **Example:** IN
- **Description:** The class of records being queried.

- **Field:** dns.question.name
 - **Type:** keyword
 - **Example:** www.example.com
 - **Description:** The name being queried.
- **Field:** dns.question.registered_domain
 - **Type:** keyword
 - **Example:** example.com
 - **Description:** The highest registered domain, stripped of the subdomain.
- **Field:** dns.question.subdomain
 - **Type:** keyword
 - **Example:** www
 - **Description:** The subdomain of the domain.
- **Field:** dns.question.top_level_domain
 - **Type:** keyword
 - **Example:** co.uk
 - **Description:** The effective top level domain (com, org, net, co.uk).
- **Field:** dns.question.type
 - **Type:** keyword
 - **Example:** AAAA
 - **Description:** The type of record being queried.

Field Set: dns

- **Field:** dns.resolved_ip
 - **Type:** ip
 - **Example:** ["10.10.10.10", "10.10.10.11"]
 - **Description:** Array containing all IPs seen in answers.data
- **Field:** dns.response_code
 - **Type:** keyword
 - **Example:** NOERROR
 - **Description:** The DNS response code.
- **Field:** dns.type
 - **Type:** keyword
 - **Example:** answer
 - **Description:** The type of DNS event captured, query or answer.

Field Set: ecs

- **Field:** ecs.version
 - **Type:** keyword
 - **Example:** 1.0.0
 - **Description:** ECS version this event conforms to.

Field Set: email

- **Field:** email.attachments
 - **Type:** nested
 - **Description:** List of objects describing the attachments.

Field Set: email.attachments.file

- **Field:** email.attachments.file.extension
 - **Type:** keyword
 - **Example:** txt

- **Description:** Attachment file extension.

Field Set: email.attachments.file.hash

- **Field:** email.attachments.file.hash.cdhash
 - **Type:** keyword
 - **Example:** 3783b4052fd474dbe30676b45c329e7a6d44acd9
 - **Description:** The Code Directory (CD) hash of an executable.
- **Field:** email.attachments.file.hash.md5
 - **Type:** keyword
 - **Description:** MD5 hash.
- **Field:** email.attachments.file.hash.sha1
 - **Type:** keyword
 - **Description:** SHA1 hash.
- **Field:** email.attachments.file.hash.sha256
 - **Type:** keyword
 - **Description:** SHA256 hash.
- **Field:** email.attachments.file.hash.sha384
 - **Type:** keyword
 - **Description:** SHA384 hash.
- **Field:** email.attachments.file.hash.sha512
 - **Type:** keyword
 - **Description:** SHA512 hash.
- **Field:** email.attachments.file.hash.ssdeep
 - **Type:** keyword
 - **Description:** SSDEEP hash.
- **Field:** email.attachments.file.hash.tlsh
 - **Type:** keyword
 - **Description:** TLSH hash.

Field Set: email.attachments.file

- **Field:** email.attachments.file.mime_type
 - **Type:** keyword
 - **Example:** text/plain
 - **Description:** MIME type of the attachment file.
- **Field:** email.attachments.file.name
 - **Type:** keyword
 - **Example:** attachment.txt
 - **Description:** Name of the attachment file.
- **Field:** email.attachments.file.size
 - **Type:** long
 - **Example:** 64329
 - **Description:** Attachment file size.

Field Set: email.bcc

- **Field:** email.bcc.address
 - **Type:** keyword
 - **Example:** bcc.user1@example.com
 - **Description:** Email address of BCC recipient

Field Set: email.cc

- **Field:** email.cc.address
- **Type:** keyword
- **Example:** cc.user1@example.com
- **Description:** Email address of CC recipient

Field Set: email

- **Field:** email.content_type
- **Type:** keyword
- **Example:** text/plain
- **Description:** MIME type of the email message.
- **Field:** email.delivery_timestamp
- **Type:** date
- **Example:** 2020-11-10T22:12:34.8196921Z
- **Description:** Date and time when message was delivered.
- **Field:** email.direction
- **Type:** keyword
- **Example:** inbound
- **Description:** Direction of the message.

Field Set: email.from

- **Field:** email.from.address
- **Type:** keyword
- **Example:** sender@example.com
- **Description:** The sender's email address.

Field Set: email

- **Field:** email.local_id
- **Type:** keyword
- **Example:** c26dbea0-80d5-463b-b93c-4e8b708219ce
- **Description:** Unique identifier given by the source.
- **Field:** email.message_id
- **Type:** wildcard
- **Example:** 81ce15\$8r2j59@mail01.example.com
- **Description:** Value from the Message-ID header.
- **Field:** email.origination_timestamp
- **Type:** date
- **Example:** 2020-11-10T22:12:34.8196921Z
- **Description:** Date and time the email was composed.

Field Set: email.reply_to

- **Field:** email.reply_to.address
- **Type:** keyword
- **Example:** reply.here@example.com
- **Description:** Address replies should be delivered to.

Field Set: email.sender

- **Field:** email.sender.address
- **Type:** keyword

- **Description:** Address of the message sender.

Field Set: email

- **Field:** email.subject
- **Type:** keyword
- **Example:** Please see this important message.
- **Description:** The subject of the email message.

Field Set: email.subject

- **Field:** email.subject.text
- **Type:** match_only_text
- **Example:** Please see this important message.
- **Description:** The subject of the email message.

Field Set: email.to

- **Field:** email.to.address
- **Type:** keyword
- **Example:** user1@example.com
- **Description:** Email address of recipient

Field Set: email

- **Field:** email.x_mailer
- **Type:** keyword
- **Example:** Spambot v2.5
- **Description:** Application that drafted email.

Field Set: error

- **Field:** error.code
- **Type:** keyword
- **Description:** Error code describing the error.
- **Field:** error.id
- **Type:** keyword
- **Description:** Unique identifier for the error.
- **Field:** error.message
- **Type:** match_only_text
- **Description:** Error message.
- **Field:** error.stack_trace
- **Type:** wildcard
- **Description:** The stack trace of this error in plain text.

Field Set: error.stack_trace

- **Field:** error.stack_trace.text
- **Type:** match_only_text
- **Description:** The stack trace of this error in plain text.

Field Set: error

- **Field:** error.type
- **Type:** keyword
- **Example:** java.lang.NullPointerException
- **Description:** The type of the error, for example the class name of the exception.

Field Set: event

- **Field:** event.action
- **Type:** keyword
- **Example:** user-password-change
- **Description:** The action captured by the event.
- **Field:** event.agent_id_status
- **Type:** keyword
- **Example:** verified
- **Description:** Validation status of the event's agent.id field.
- **Field:** event.category
- **Type:** keyword
- **Example:** authentication
- **Description:** Event category. The second categorization field in the hierarchy.
- **Field:** event.code
- **Type:** keyword
- **Example:** 4648
- **Description:** Identification code for this event.
- **Field:** event.created
- **Type:** date
- **Example:** 2016-05-23T08:05:34.857Z
- **Description:** Time when the event was first read by an agent or by your pipeline.
- **Field:** event.dataset
- **Type:** keyword
- **Example:** apache.access
- **Description:** Name of the dataset.
- **Field:** event.duration
- **Type:** long
- **Description:** Duration of the event in nanoseconds.
- **Field:** event.end
- **Type:** date
- **Description:** `event.end` contains the date when the event ended or when the activity was last observed.
- **Field:** event.hash
- **Type:** keyword
- **Example:** 123456789012345678901234567890ABCD
- **Description:** Hash (perhaps logstash fingerprint) of raw field to be able to demonstrate log integrity.
- **Field:** event.id
- **Type:** keyword
- **Example:** 8a4f500d
- **Description:** Unique ID to describe the event.
- **Field:** event.ingested
- **Type:** date
- **Example:** 2016-05-23T08:05:35.101Z
- **Description:** Timestamp when an event arrived in the central data store.

- **Field:** event.kind
 - **Type:** keyword
 - **Example:** alert
 - **Description:** The kind of the event. The highest categorization field in the hierarchy.
- **Field:** event.module
 - **Type:** keyword
 - **Example:** apache
 - **Description:** Name of the module this data is coming from.
- **Field:** event.original
 - **Type:** keyword
 - **Example:** Sep 19 08:26:10 host CEF:0|Security| threatmanager|1.0|100| worm successfully stopped|10|src=10.0.0.1 dst=2.1.2.2spt=1232
 - **Description:** Raw text message of entire event.
- **Field:** event.outcome
 - **Type:** keyword
 - **Example:** success
 - **Description:** The outcome of the event. The lowest level categorization field in the hierarchy.
- **Field:** event.provider
 - **Type:** keyword
 - **Example:** kernel
 - **Description:** Source of the event.
- **Field:** event.reason
 - **Type:** keyword
 - **Example:** Terminated an unexpected process
 - **Description:** Reason why this event happened, according to the source
- **Field:** event.reference
 - **Type:** keyword
 - **Example:** https://system.example.com/event/#0001234
 - **Description:** Event reference URL
- **Field:** event.risk_score
 - **Type:** float
 - **Description:** Risk score or priority of the event (e.g. security solutions). Use your system's original value here.
- **Field:** event.risk_score_norm
 - **Type:** float
 - **Description:** Normalized risk score or priority of the event (0-100).
- **Field:** event.sequence
 - **Type:** long
 - **Description:** Sequence number of the event.
- **Field:** event.severity
 - **Type:** long
 - **Example:** 7
 - **Description:** Numeric severity of the event.
- **Field:** event.start
 - **Type:** date
 - **Description:** `event.start` contains the date when the event started or when the activity was first observed.
- **Field:** event.timezone
 - **Type:** keyword
 - **Description:** Event time zone.

- **Field:** event.type
 - **Type:** keyword
 - **Description:** Event type. The third categorization field in the hierarchy.
- **Field:** event.url
 - **Type:** keyword
 - **Example:** https://mysystem.example.com/alert/5271dedb-f5b0-4218-87f0-4ac4870a38fe
 - **Description:** Event investigation URL

Field Set: faas

- **Field:** faas.coldstart
 - **Type:** boolean
 - **Description:** Boolean value indicating a cold start of a function.
- **Field:** faas.execution
 - **Type:** keyword
 - **Example:** af9d5aa4-a685-4c5f-a22b-444f80b3cc28
 - **Description:** The execution ID of the current function execution.
- **Field:** faas.id
 - **Type:** keyword
 - **Example:** arn:aws:lambda:us-west-2:123456789012:function:my-function
 - **Description:** The unique identifier of a serverless function.
- **Field:** faas.name
 - **Type:** keyword
 - **Example:** my-function
 - **Description:** The name of a serverless function.

Field Set: faas.trigger

- **Field:** faas.trigger.request_id
 - **Type:** keyword
 - **Example:** 123456789
 - **Description:** The ID of the trigger request , message, event, etc.
- **Field:** faas.trigger.type
 - **Type:** keyword
 - **Example:** http
 - **Description:** The trigger for the function execution.

Field Set: faas

- **Field:** faas.version
 - **Type:** keyword
 - **Example:** 123
 - **Description:** The version of a serverless function.

Field Set: file

- **Field:** file.accessed
 - **Type:** date
 - **Description:** Last time the file was accessed.
- **Field:** file.attributes
 - **Type:** keyword
 - **Example:** ["readonly", "system"]
 - **Description:** Array of file attributes.

Field Set: file.code_signature

- **Field:** file.code_signature.digest_algorithm
 - **Type:** keyword
 - **Example:** sha256
 - **Description:** Hashing algorithm used to sign the process.
- **Field:** file.code_signature.exists
 - **Type:** boolean
 - **Example:** true
 - **Description:** Boolean to capture if a signature is present.
- **Field:** file.code_signature.flags
 - **Type:** keyword
 - **Example:** 570522385
 - **Description:** Code signing flags of the process
- **Field:** file.code_signature.signing_id
 - **Type:** keyword
 - **Example:** com.apple.xpc.proxy
 - **Description:** The identifier used to sign the process.
- **Field:** file.code_signature.status
 - **Type:** keyword
 - **Example:** ERROR_UNTRUSTED_ROOT
 - **Description:** Additional information about the certificate status.
- **Field:** file.code_signature.subject_name
 - **Type:** keyword
 - **Example:** Microsoft Corporation
 - **Description:** Subject name of the code signer
- **Field:** file.code_signature.team_id
 - **Type:** keyword
 - **Example:** EQHXZ8M8AV
 - **Description:** The team identifier used to sign the process.
- **Field:** file.code_signature.timestamp
 - **Type:** date
 - **Example:** 2021-01-01T12:10:30Z
 - **Description:** When the signature was generated and signed.
- **Field:** file.code_signature.trusted
 - **Type:** boolean
 - **Example:** true
 - **Description:** Stores the trust status of the certificate chain.
- **Field:** file.code_signature.valid
 - **Type:** boolean
 - **Example:** true
 - **Description:** Boolean to capture if the digital signature is verified against the binary content.

Field Set: file

- **Field:** file.created
 - **Type:** date
 - **Description:** File creation time.
- **Field:** file.ctime
 - **Type:** date
 - **Description:** Last time the file attributes or metadata changed.

- **Field:** file.device
- **Type:** keyword
- **Example:** sda
- **Description:** Device that is the source of the file.
- **Field:** file.directory
- **Type:** keyword
- **Example:** /home/alice
- **Description:** Directory where the file is located.
- **Field:** file.drive_letter
- **Type:** keyword
- **Example:** C
- **Description:** Drive letter where the file is located.

Field Set: file.elf

- **Field:** file.elf.architecture
- **Type:** keyword
- **Example:** x86-64
- **Description:** Machine architecture of the ELF file.
- **Field:** file.elf.byte_order
- **Type:** keyword
- **Example:** Little Endian
- **Description:** Byte sequence of ELF file.
- **Field:** file.elf.cpu_type
- **Type:** keyword
- **Example:** Intel
- **Description:** CPU type of the ELF file.
- **Field:** file.elf.creation_date
- **Type:** date
- **Description:** Build or compile date.
- **Field:** file.elf.exports
- **Type:** flattened
- **Description:** List of exported element names and types.
- **Field:** file.elf.go_import_hash
- **Type:** keyword
- **Example:** 10bddcb4cee42080f76c88d9ff964491
- **Description:** A hash of the Go language imports in an ELF file.
- **Field:** file.elf.go_imports
- **Type:** flattened
- **Description:** List of imported Go language element names and types.
- **Field:** file.elf.go_imports_names_entropy
- **Type:** long
- **Description:** Shannon entropy calculation from the list of Go imports.
- **Field:** file.elf.go_imports_names_var_entropy
- **Type:** long
- **Description:** Variance for Shannon entropy calculation from the list of Go imports.
- **Field:** file.elf.go_stripped
- **Type:** boolean
- **Description:** Whether the file is a stripped or obfuscated Go executable.

Field Set: file.elf.header

- **Field:** file.elf.header.abi_version
 - **Type:** keyword
 - **Description:** Version of the ELF Application Binary Interface (ABI).
- **Field:** file.elf.header.class
 - **Type:** keyword
 - **Description:** Header class of the ELF file.
- **Field:** file.elf.header.data
 - **Type:** keyword
 - **Description:** Data table of the ELF header.
- **Field:** file.elf.header.entrypoint
 - **Type:** long
 - **Description:** Header entrypoint of the ELF file.
- **Field:** file.elf.header.object_version
 - **Type:** keyword
 - **Description:** "0x1" for original ELF files.
- **Field:** file.elf.header.os_abi
 - **Type:** keyword
 - **Description:** Application Binary Interface (ABI) of the Linux OS.
- **Field:** file.elf.header.type
 - **Type:** keyword
 - **Description:** Header type of the ELF file.
- **Field:** file.elf.header.version
 - **Type:** keyword
 - **Description:** Version of the ELF header.

Field Set: file.elf

- **Field:** file.elf.import_hash
 - **Type:** keyword
 - **Example:** d41d8cd98f00b204e9800998ecf8427e
 - **Description:** A hash of the imports in an ELF file.
- **Field:** file.elf.imports
 - **Type:** flattened
 - **Description:** List of imported element names and types.
- **Field:** file.elf.imports_names_entropy
 - **Type:** long
 - **Description:** Shannon entropy calculation from the list of imported element names and types.
- **Field:** file.elf.imports_names_var_entropy
 - **Type:** long
 - **Description:** Variance for Shannon entropy calculation from the list of imported element names and types.
- **Field:** file.elf.sections
 - **Type:** nested
 - **Description:** Section information of the ELF file.

Field Set: file.elf.sections

- **Field:** file.elf.sections.chi2
 - **Type:** long
 - **Description:** Chi-square probability distribution of the section.

- **Field:** file.elf.sections.entropy
 - **Type:** long
 - **Description:** Shannon entropy calculation from the section.
- **Field:** file.elf.sections.flags
 - **Type:** keyword
 - **Description:** ELF Section List flags.
- **Field:** file.elf.sections.name
 - **Type:** keyword
 - **Description:** ELF Section List name.
- **Field:** file.elf.sections.physical_offset
 - **Type:** keyword
 - **Description:** ELF Section List offset.
- **Field:** file.elf.sections.physical_size
 - **Type:** long
 - **Description:** ELF Section List physical size.
- **Field:** file.elf.sections.type
 - **Type:** keyword
 - **Description:** ELF Section List type.
- **Field:** file.elf.sections.var_entropy
 - **Type:** long
 - **Description:** Variance for Shannon entropy calculation from the section.
- **Field:** file.elf.sections.virtual_address
 - **Type:** long
 - **Description:** ELF Section List virtual address.
- **Field:** file.elf.sections.virtual_size
 - **Type:** long
 - **Description:** ELF Section List virtual size.

Field Set: file.elf

- **Field:** file.elf.segments
 - **Type:** nested
 - **Description:** ELF object segment list.

Field Set: file.elf.segments

- **Field:** file.elf.segments.sections
 - **Type:** keyword
 - **Description:** ELF object segment sections.
- **Field:** file.elf.segments.type
 - **Type:** keyword
 - **Description:** ELF object segment type.

Field Set: file.elf

- **Field:** file.elf.shared_libraries
 - **Type:** keyword
 - **Description:** List of shared libraries used by this ELF object.
- **Field:** file.elf.telfhash
 - **Type:** keyword
 - **Description:** telfhash hash for ELF file.

Field Set: file

- **Field:** file.extension
 - **Type:** keyword
 - **Example:** png
 - **Description:** File extension, excluding the leading dot.
- **Field:** file.fork_name
 - **Type:** keyword
 - **Example:** Zone.Identifier
 - **Description:** A fork is additional data associated with a filesystem object.
- **Field:** file.gid
 - **Type:** keyword
 - **Example:** 1001
 - **Description:** Primary group ID (GID) of the file.
- **Field:** file.group
 - **Type:** keyword
 - **Example:** alice
 - **Description:** Primary group name of the file.

Field Set: file.hash

- **Field:** file.hash.cdhash
 - **Type:** keyword
 - **Example:** 3783b4052fd474dbe30676b45c329e7a6d44acd9
 - **Description:** The Code Directory (CD) hash of an executable.
- **Field:** file.hash.md5
 - **Type:** keyword
 - **Description:** MD5 hash.
- **Field:** file.hash.sha1
 - **Type:** keyword
 - **Description:** SHA1 hash.
- **Field:** file.hash.sha256
 - **Type:** keyword
 - **Description:** SHA256 hash.
- **Field:** file.hash.sha384
 - **Type:** keyword
 - **Description:** SHA384 hash.
- **Field:** file.hash.sha512
 - **Type:** keyword
 - **Description:** SHA512 hash.
- **Field:** file.hash.ssdeep
 - **Type:** keyword
 - **Description:** SSDEEP hash.
- **Field:** file.hash.tlsh
 - **Type:** keyword
 - **Description:** TLSH hash.

Field Set: file

- **Field:** file.inode
 - **Type:** keyword
 - **Example:** 256383

- **Description:** Inode representing the file in the filesystem.

Field Set: file.macho

- **Field:** file.macho.go_import_hash
 - **Type:** keyword
 - **Example:** 10bddcb4cee42080f76c88d9ff964491
 - **Description:** A hash of the Go language imports in a Mach-O file.
- **Field:** file.macho.go_imports
 - **Type:** flattened
 - **Description:** List of imported Go language element names and types.
- **Field:** file.macho.go_imports_names_entropy
 - **Type:** long
 - **Description:** Shannon entropy calculation from the list of Go imports.
- **Field:** file.macho.go_imports_names_var_entropy
 - **Type:** long
 - **Description:** Variance for Shannon entropy calculation from the list of Go imports.
- **Field:** file.macho.go_stripped
 - **Type:** boolean
 - **Description:** Whether the file is a stripped or obfuscated Go executable.
- **Field:** file.macho.import_hash
 - **Type:** keyword
 - **Example:** d41d8cd98f00b204e9800998ecf8427e
 - **Description:** A hash of the imports in a Mach-O file.
- **Field:** file.macho.imports
 - **Type:** flattened
 - **Description:** List of imported element names and types.
- **Field:** file.macho.imports_names_entropy
 - **Type:** long
 - **Description:** Shannon entropy calculation from the list of imported element names and types.
- **Field:** file.macho.imports_names_var_entropy
 - **Type:** long
 - **Description:** Variance for Shannon entropy calculation from the list of imported element names and types.
- **Field:** file.macho.sections
 - **Type:** nested
 - **Description:** Section information of the Mach-O file.

Field Set: file.macho.sections

- **Field:** file.macho.sections.entropy
 - **Type:** long
 - **Description:** Shannon entropy calculation from the section.
- **Field:** file.macho.sections.name
 - **Type:** keyword
 - **Description:** Mach-O Section List name.
- **Field:** file.macho.sections.physical_size
 - **Type:** long
 - **Description:** Mach-O Section List physical size.

- **Field:** file.macho.sections.var_entropy
 - **Type:** long
 - **Description:** Variance for Shannon entropy calculation from the section.
- **Field:** file.macho.sections.virtual_size
 - **Type:** long
 - **Description:** Mach-O Section List virtual size. This is always the same as `physical\_size`.

Field Set: file.macho

- **Field:** file.macho.symhash
 - **Type:** keyword
 - **Example:** d3ccf195b62a9279c3c19af1080497ec
 - **Description:** A hash of the imports in a Mach-O file.

Field Set: file

- **Field:** file.mime_type
 - **Type:** keyword
 - **Description:** Media type of file, document, or arrangement of bytes.
- **Field:** file.mode
 - **Type:** keyword
 - **Example:** 0640
 - **Description:** Mode of the file in octal representation.
- **Field:** file.mtime
 - **Type:** date
 - **Description:** Last time the file content was modified.
- **Field:** file.name
 - **Type:** keyword
 - **Example:** example.png
 - **Description:** Name of the file including the extension, without the directory.
- **Field:** file.owner
 - **Type:** keyword
 - **Example:** alice
 - **Description:** File owner's username.
- **Field:** file.path
 - **Type:** keyword
 - **Example:** /home/alice/example.png
 - **Description:** Full path to the file, including the file name.

Field Set: file.path

- **Field:** file.path.text
 - **Type:** match_only_text
 - **Example:** /home/alice/example.png
 - **Description:** Full path to the file, including the file name.

Field Set: file.pe

- **Field:** file.pe.architecture
 - **Type:** keyword
 - **Example:** x64
 - **Description:** CPU architecture target for the file.

- **Field:** file.pe.company
 - **Type:** keyword
 - **Example:** Microsoft Corporation
 - **Description:** Internal company name of the file, provided at compile-time.
- **Field:** file.pe.description
 - **Type:** keyword
 - **Example:** Paint
 - **Description:** Internal description of the file, provided at compile-time.
- **Field:** file.pe.file_version
 - **Type:** keyword
 - **Example:** 6.3.9600.17415
 - **Description:** Process name.
- **Field:** file.pe.go_import_hash
 - **Type:** keyword
 - **Example:** 10bddcb4cee42080f76c88d9ff964491
 - **Description:** A hash of the Go language imports in a PE file.
- **Field:** file.pe.go_imports
 - **Type:** flattened
 - **Description:** List of imported Go language element names and types.
- **Field:** file.pe.go_imports_names_entropy
 - **Type:** long
 - **Description:** Shannon entropy calculation from the list of Go imports.
- **Field:** file.pe.go_imports_names_var_entropy
 - **Type:** long
 - **Description:** Variance for Shannon entropy calculation from the list of Go imports.
- **Field:** file.pe.go_stripped
 - **Type:** boolean
 - **Description:** Whether the file is a stripped or obfuscated Go executable.
- **Field:** file.pe.imphash
 - **Type:** keyword
 - **Example:** 0c6803c4e922103c4dca5963aad36ddf
 - **Description:** A hash of the imports in a PE file.
- **Field:** file.pe.import_hash
 - **Type:** keyword
 - **Example:** d41d8cd98f00b204e9800998ecf8427e
 - **Description:** A hash of the imports in a PE file.
- **Field:** file.pe.imports
 - **Type:** flattened
 - **Description:** List of imported element names and types.
- **Field:** file.pe.imports_names_entropy
 - **Type:** long
 - **Description:** Shannon entropy calculation from the list of imported element names and types.
- **Field:** file.pe.imports_names_var_entropy
 - **Type:** long
 - **Description:** Variance for Shannon entropy calculation from the list of imported element names and types.
- **Field:** file.pe.original_file_name
 - **Type:** keyword
 - **Example:** MSPAINT.EXE
 - **Description:** Internal name of the file, provided at compile-time.

- **Field:** file.pe.pehash
 - **Type:** keyword
 - **Example:** 73ff189b63cd6be375a7ff25179a38d347651975
 - **Description:** A hash of the PE header and data from one or more PE sections.
- **Field:** file.pe.product
 - **Type:** keyword
 - **Example:** Microsoft® Windows® Operating System
 - **Description:** Internal product name of the file, provided at compile-time.
- **Field:** file.pe.sections
 - **Type:** nested
 - **Description:** Section information of the PE file.

Field Set: file.pe.sections

- **Field:** file.pe.sections.entropy
 - **Type:** long
 - **Description:** Shannon entropy calculation from the section.
- **Field:** file.pe.sections.name
 - **Type:** keyword
 - **Description:** PE Section List name.
- **Field:** file.pe.sections.physical_size
 - **Type:** long
 - **Description:** PE Section List physical size.
- **Field:** file.pe.sections.var_entropy
 - **Type:** long
 - **Description:** Variance for Shannon entropy calculation from the section.
- **Field:** file.pe.sections.virtual_size
 - **Type:** long
 - **Description:** PE Section List virtual size. This is always the same as `physical\_size`.

Field Set: file

- **Field:** file.size
 - **Type:** long
 - **Example:** 16384
 - **Description:** File size in bytes.
- **Field:** file.target_path
 - **Type:** keyword
 - **Description:** Target path for symlinks.

Field Set: file.target_path

- **Field:** file.target_path.text
 - **Type:** match_only_text
 - **Description:** Target path for symlinks.

Field Set: file

- **Field:** file.type
 - **Type:** keyword
 - **Example:** file
 - **Description:** File type (file, dir, or symlink).

- **Field:** file.uid
- **Type:** keyword
- **Example:** 1001
- **Description:** The user ID (UID) or security identifier (SID) of the file owner.

Field Set: file.x509

- **Field:** file.x509.alternative_names
- **Type:** keyword
- **Example:** *.elastic.co
- **Description:** List of subject alternative names (SAN).

Field Set: file.x509.issuer

- **Field:** file.x509.issuer.common_name
- **Type:** keyword
- **Example:** Example SHA2 High Assurance Server CA
- **Description:** List of common name (CN) of issuing certificate authority.
- **Field:** file.x509.issuer.country
- **Type:** keyword
- **Example:** US
- **Description:** List of country \(\C\) codes
- **Field:** file.x509.issuer.distinguished_name
- **Type:** keyword
- **Example:** C=US, O=Example Inc, OU=www.example.com, CN=Example SHA2 High Assurance Server CA
- **Description:** Distinguished name (DN) of issuing certificate authority.
- **Field:** file.x509.issuer.locality
- **Type:** keyword
- **Example:** Mountain View
- **Description:** List of locality names (L)
- **Field:** file.x509.issuer.organization
- **Type:** keyword
- **Example:** Example Inc
- **Description:** List of organizations (O) of issuing certificate authority.
- **Field:** file.x509.issuer.organizational_unit
- **Type:** keyword
- **Example:** www.example.com
- **Description:** List of organizational units (OU) of issuing certificate authority.
- **Field:** file.x509.issuer.state_or_province
- **Type:** keyword
- **Example:** California
- **Description:** List of state or province names (ST, S, or P)

Field Set: file.x509

- **Field:** file.x509.not_after
- **Type:** date
- **Example:** 2020-07-16T03:15:39Z
- **Description:** Time at which the certificate is no longer considered valid.
- **Field:** file.x509.not_before
- **Type:** date
- **Example:** 2019-08-16T01:40:25Z

- **Description:** Time at which the certificate is first considered valid.
- **Field:** file.x509.public_key_algorithm
 - **Type:** keyword
 - **Example:** RSA
 - **Description:** Algorithm used to generate the public key.
- **Field:** file.x509.public_key_curve
 - **Type:** keyword
 - **Example:** nistp521
 - **Description:** The curve used by the elliptic curve public key algorithm. This is algorithm specific.
- **Field:** file.x509.public_key_exponent
 - **Type:** long
 - **Example:** 65537
 - **Description:** Exponent used to derive the public key. This is algorithm specific.
- **Field:** file.x509.public_key_size
 - **Type:** long
 - **Example:** 2048
 - **Description:** The size of the public key space in bits.
- **Field:** file.x509.serial_number
 - **Type:** keyword
 - **Example:** 55FBB9C7DEBF09809D12CCAA
 - **Description:** Unique serial number issued by the certificate authority.
- **Field:** file.x509.signature_algorithm
 - **Type:** keyword
 - **Example:** SHA256-RSA
 - **Description:** Identifier for certificate signature algorithm.

Field Set: file.x509.subject

- **Field:** file.x509.subject.common_name
 - **Type:** keyword
 - **Example:** shared.global.example.net
 - **Description:** List of common names (CN) of subject.
- **Field:** file.x509.subject.country
 - **Type:** keyword
 - **Example:** US
 - **Description:** List of country \(\C) code
- **Field:** file.x509.subject.distinguished_name
 - **Type:** keyword
 - **Example:** C=US, ST=California, L=San Francisco, O=Example, Inc., CN=shared.global.example.net
 - **Description:** Distinguished name (DN) of the certificate subject entity.
- **Field:** file.x509.subject.locality
 - **Type:** keyword
 - **Example:** San Francisco
 - **Description:** List of locality names (L)
- **Field:** file.x509.subject.organization
 - **Type:** keyword
 - **Example:** Example, Inc.
 - **Description:** List of organizations (O) of subject.

- **Field:** file.x509.subject.organizational_unit
- **Type:** keyword
- **Description:** List of organizational units (OU) of subject.
- **Field:** file.x509.subject.state_or_province
- **Type:** keyword
- **Example:** California
- **Description:** List of state or province names (ST, S, or P)

Field Set: file.x509

- **Field:** file.x509.version_number
- **Type:** keyword
- **Example:** 3
- **Description:** Version of x509 format.

Field Set: group

- **Field:** group.domain
- **Type:** keyword
- **Description:** Name of the directory the group is a member of.
- **Field:** group.id
- **Type:** keyword
- **Description:** Unique identifier for the group on the system/platform.
- **Field:** group.name
- **Type:** keyword
- **Description:** Name of the group.

Field Set: host

- **Field:** host.architecture
- **Type:** keyword
- **Example:** x86_64
- **Description:** Operating system architecture.

Field Set: host.boot

- **Field:** host.boot.id
- **Type:** keyword
- **Example:** 88a1f0ed-5ae5-41ee-af6b-41921c311872
- **Description:** Linux boot uuid taken from /proc/sys/kernel/random/boot_id

Field Set: host.cpu

- **Field:** host.cpu.usage
- **Type:** scaled_float
- **Description:** Percent CPU used, between 0 and 1.

Field Set: host.disk.read

- **Field:** host.disk.read.bytes
- **Type:** long
- **Description:** The number of bytes read by all disks.

Field Set: host.disk.write

- **Field:** host.disk.write.bytes
- **Type:** long
- **Description:** The number of bytes written on all disks.

Field Set: host

- **Field:** host.domain
- **Type:** keyword
- **Example:** CONTOSO
- **Description:** Name of the directory the group is a member of.

Field Set: host.geo

- **Field:** host.geo.city_name
- **Type:** keyword
- **Example:** Montreal
- **Description:** City name.
- **Field:** host.geo.continent_code
- **Type:** keyword
- **Description:** Continent code.
- **Field:** host.geo.continent_name
- **Type:** keyword
- **Example:** North America
- **Description:** Name of the continent.
- **Field:** host.geo.country_iso_code
- **Type:** keyword
- **Example:** CA
- **Description:** Country ISO code.
- **Field:** host.geo.country_name
- **Type:** keyword
- **Example:** Canada
- **Description:** Country name.
- **Field:** host.geo.location
- **Type:** geo_point
- **Example:** { "lon": -73.614830, "lat": 45.505918 }
- **Description:** Longitude and latitude.
- **Field:** host.geo.name
- **Type:** keyword
- **Example:** boston-dc
- **Description:** User-defined description of a location.
- **Field:** host.geo.postal_code
- **Type:** keyword
- **Example:** 94040
- **Description:** Postal code.
- **Field:** host.geo.region_iso_code
- **Type:** keyword
- **Example:** CA-QC
- **Description:** Region ISO code.
- **Field:** host.geo.region_name
- **Type:** keyword
- **Example:** Quebec
- **Description:** Region name.

- **Field:** host.geo.timezone
- **Type:** keyword
- **Example:** America/Argentina/Buenos_Aires
- **Description:** Time zone.

Field Set: host

- **Field:** host.hostname
- **Type:** keyword
- **Description:** Hostname of the host.
- **Field:** host.id
- **Type:** keyword
- **Description:** Unique host id.
- **Field:** host.ip
- **Type:** ip
- **Description:** Host ip addresses.
- **Field:** host.mac
- **Type:** keyword
- **Example:** ["00-00-5E-00-53-23", "00-00-5E-00-53-24"]
- **Description:** Host MAC addresses.
- **Field:** host.name
- **Type:** keyword
- **Description:** Name of the host.

Field Set: host.network.egress

- **Field:** host.network.egress.bytes
- **Type:** long
- **Description:** The number of bytes sent on all network interfaces.
- **Field:** host.network.egress.packets
- **Type:** long
- **Description:** The number of packets sent on all network interfaces.

Field Set: host.network.ingress

- **Field:** host.network.ingress.bytes
- **Type:** long
- **Description:** The number of bytes received on all network interfaces.
- **Field:** host.network.ingress.packets
- **Type:** long
- **Description:** The number of packets received on all network interfaces.

Field Set: host.os

- **Field:** host.os.family
- **Type:** keyword
- **Example:** debian
- **Description:** OS family (such as redhat, debian, freebsd, windows).
- **Field:** host.os.full
- **Type:** keyword
- **Example:** Mac OS Mojave
- **Description:** Operating system name, including the version or code name.

Field Set: host.os.full

- **Field:** host.os.full.text
- **Type:** match_only_text
- **Example:** Mac OS Mojave
- **Description:** Operating system name, including the version or code name.

Field Set: host.os

- **Field:** host.os.kernel
- **Type:** keyword
- **Example:** 4.4.0-112-generic
- **Description:** Operating system kernel version as a raw string.
- **Field:** host.os.name
- **Type:** keyword
- **Example:** Mac OS X
- **Description:** Operating system name, without the version.

Field Set: host.os.name

- **Field:** host.os.name.text
- **Type:** match_only_text
- **Example:** Mac OS X
- **Description:** Operating system name, without the version.

Field Set: host.os

- **Field:** host.os.platform
- **Type:** keyword
- **Example:** darwin
- **Description:** Operating system platform (such centos, ubuntu, windows).
- **Field:** host.os.type
- **Type:** keyword
- **Example:** macos
- **Description:** Which commercial OS family (one of: linux, macos, unix, windows, ios or android).
- **Field:** host.os.version
- **Type:** keyword
- **Example:** 10.14.1
- **Description:** Operating system version as a raw string.

Field Set: host

- **Field:** host.pid_ns_ino
- **Type:** keyword
- **Example:** 256383
- **Description:** Pid namespace inode

Field Set: host.risk

- **Field:** host.risk.calculated_level
- **Type:** keyword
- **Example:** High
- **Description:** A risk classification level calculated by an internal system as part of entity analytics and entity risk scoring.

- **Field:** host.risk.calculated_score
 - **Type:** float
 - **Example:** 880.73
 - **Description:** A risk classification score calculated by an internal system as part of entity analytics and entity risk scoring.
- **Field:** host.risk.calculated_score_norm
 - **Type:** float
 - **Example:** 88.73
 - **Description:** A normalized risk score calculated by an internal system.
- **Field:** host.risk.static_level
 - **Type:** keyword
 - **Example:** High
 - **Description:** A risk classification level obtained from outside the system, such as from some external Threat Intelligence Platform.
- **Field:** host.risk.static_score
 - **Type:** float
 - **Example:** 830.0
 - **Description:** A risk classification score obtained from outside the system, such as from some external Threat Intelligence Platform.
- **Field:** host.risk.static_score_norm
 - **Type:** float
 - **Example:** 83.0
 - **Description:** A normalized risk score calculated by an external system.

Field Set: host

- **Field:** host.type
 - **Type:** keyword
 - **Description:** Type of host.
- **Field:** host.uptime
 - **Type:** long
 - **Example:** 1325
 - **Description:** Seconds the host has been up.

Field Set: http.request.body

- **Field:** http.request.body.bytes
 - **Type:** long
 - **Example:** 887
 - **Description:** Size in bytes of the request body.
- **Field:** http.request.body.content
 - **Type:** wildcard
 - **Example:** Hello world
 - **Description:** The full HTTP request body.

Field Set: http.request.body.content

- **Field:** http.request.body.content.text
 - **Type:** match_only_text
 - **Example:** Hello world
 - **Description:** The full HTTP request body.

Field Set: http.request

- **Field:** http.request.bytes
 - **Type:** long
 - **Example:** 1437
 - **Description:** Total size in bytes of the request (body and headers).
- **Field:** http.request.id
 - **Type:** keyword
 - **Example:** 123e4567-e89b-12d3-a456-426614174000
 - **Description:** HTTP request ID.
- **Field:** http.request.method
 - **Type:** keyword
 - **Example:** POST
 - **Description:** HTTP request method.
- **Field:** http.request.mime_type
 - **Type:** keyword
 - **Example:** image/gif
 - **Description:** Mime type of the body of the request.
- **Field:** http.request.referrer
 - **Type:** keyword
 - **Example:** https://blog.example.com/
 - **Description:** Referrer for this HTTP request.

Field Set: http.response.body

- **Field:** http.response.body.bytes
 - **Type:** long
 - **Example:** 887
 - **Description:** Size in bytes of the response body.
- **Field:** http.response.body.content
 - **Type:** wildcard
 - **Example:** Hello world
 - **Description:** The full HTTP response body.

Field Set: http.response.body.content

- **Field:** http.response.body.content.text
 - **Type:** match_only_text
 - **Example:** Hello world
 - **Description:** The full HTTP response body.

Field Set: http.response

- **Field:** http.response.bytes
 - **Type:** long
 - **Example:** 1437
 - **Description:** Total size in bytes of the response (body and headers).
- **Field:** http.response.mime_type
 - **Type:** keyword
 - **Example:** image/gif
 - **Description:** Mime type of the body of the response.
- **Field:** http.response.status_code
 - **Type:** long
 - **Example:** 404
 - **Description:** HTTP response status code.

Field Set: http

- **Field:** http.version
- **Type:** keyword
- **Example:** 1.1
- **Description:** HTTP version.

Field Set: log.file

- **Field:** log.file.path
- **Type:** keyword
- **Example:** /var/log/fun-times.log
- **Description:** Full path to the log file this event came from.

Field Set: log

- **Field:** log.level
- **Type:** keyword
- **Example:** error
- **Description:** Log level of the log event.
- **Field:** log.logger
- **Type:** keyword
- **Example:** org.elasticsearch.bootstrap.Bootstrap
- **Description:** Name of the logger.

Field Set: log.origin.file

- **Field:** log.origin.file.line
- **Type:** long
- **Example:** 42
- **Description:** The line number of the file which originated the log event.
- **Field:** log.origin.file.name
- **Type:** keyword
- **Example:** Bootstrap.java
- **Description:** The code file which originated the log event.

Field Set: log.origin

- **Field:** log.origin.function
- **Type:** keyword
- **Example:** init
- **Description:** The function which originated the log event.

Field Set: log

- **Field:** log.syslog
- **Type:** object
- **Description:** Syslog metadata

Field Set: log.syslog

- **Field:** log.syslog.appname
- **Type:** keyword
- **Example:** sshd
- **Description:** The device or application that originated the Syslog message.

Field Set: log.syslog.facility

- **Field:** log.syslog.facility.code
 - **Type:** long
 - **Example:** 23
 - **Description:** Syslog numeric facility of the event.
- **Field:** log.syslog.facility.name
 - **Type:** keyword
 - **Example:** local7
 - **Description:** Syslog text-based facility of the event.

Field Set: log.syslog

- **Field:** log.syslog.hostname
 - **Type:** keyword
 - **Example:** example-host
 - **Description:** The host that originated the Syslog message.
- **Field:** log.syslog.msgid
 - **Type:** keyword
 - **Example:** ID47
 - **Description:** An identifier for the type of Syslog message.
- **Field:** log.syslog.priority
 - **Type:** long
 - **Example:** 135
 - **Description:** Syslog priority of the event.
- **Field:** log.syslog.procid
 - **Type:** keyword
 - **Example:** 12345
 - **Description:** The process name or ID that originated the Syslog message.

Field Set: log.syslog.severity

- **Field:** log.syslog.severity.code
 - **Type:** long
 - **Example:** 3
 - **Description:** Syslog numeric severity of the event.
- **Field:** log.syslog.severity.name
 - **Type:** keyword
 - **Example:** Error
 - **Description:** Syslog text-based severity of the event.

Field Set: log.syslog

- **Field:** log.syslog.structured_data
 - **Type:** flattened
 - **Description:** Structured data expressed in RFC 5424 messages.
- **Field:** log.syslog.version
 - **Type:** keyword
 - **Example:** 1
 - **Description:** Syslog protocol version.

Field Set: network

- **Field:** network.application
 - **Type:** keyword
 - **Example:** aim
 - **Description:** Application level protocol name.
- **Field:** network.bytes
 - **Type:** long
 - **Example:** 368
 - **Description:** Total bytes transferred in both directions.
- **Field:** network.community_id
 - **Type:** keyword
 - **Example:** 1:hO+sN4H+MG5MY/8hIrXPqc4ZQz0=
 - **Description:** A hash of source and destination IPs and ports.
- **Field:** network.direction
 - **Type:** keyword
 - **Example:** inbound
 - **Description:** Direction of the network traffic.
- **Field:** network.forwarded_ip
 - **Type:** ip
 - **Example:** 192.1.1.2
 - **Description:** Host IP address when the source IP address is the proxy.
- **Field:** network.iana_number
 - **Type:** keyword
 - **Example:** 6
 - **Description:** IANA Protocol Number.
- **Field:** network.inner
 - **Type:** object
 - **Description:** Inner VLAN tag information

Field Set: network.inner.vlan

- **Field:** network.inner.vlan.id
 - **Type:** keyword
 - **Example:** 10
 - **Description:** VLAN ID as reported by the observer.
- **Field:** network.inner.vlan.name
 - **Type:** keyword
 - **Example:** outside
 - **Description:** Optional VLAN name as reported by the observer.

Field Set: network

- **Field:** network.name
 - **Type:** keyword
 - **Example:** Guest Wifi
 - **Description:** Name given by operators to sections of their network.
- **Field:** network.packets
 - **Type:** long
 - **Example:** 24
 - **Description:** Total packets transferred in both directions.
- **Field:** network.protocol
 - **Type:** keyword
 - **Example:** http

- **Description:** Application protocol name.
- **Field:** network.transport
 - **Type:** keyword
 - **Example:** tcp
 - **Description:** Protocol Name corresponding to the field `iana\_number`.
- **Field:** network.type
 - **Type:** keyword
 - **Example:** ipv4
 - **Description:** In the OSI Model this would be the Network Layer. ipv4, ipv6, ipsec, pim, etc

Field Set: network.vlan

- **Field:** network.vlan.id
 - **Type:** keyword
 - **Example:** 10
 - **Description:** VLAN ID as reported by the observer.
- **Field:** network.vlan.name
 - **Type:** keyword
 - **Example:** outside
 - **Description:** Optional VLAN name as reported by the observer.

Field Set: observer

- **Field:** observer.egress
 - **Type:** object
 - **Description:** Object field for egress information

Field Set: observer.egress.interface

- **Field:** observer.egress.interface.alias
 - **Type:** keyword
 - **Example:** outside
 - **Description:** Interface alias
- **Field:** observer.egress.interface.id
 - **Type:** keyword
 - **Example:** 10
 - **Description:** Interface ID
- **Field:** observer.egress.interface.name
 - **Type:** keyword
 - **Example:** eth0
 - **Description:** Interface name

Field Set: observer.egress.vlan

- **Field:** observer.egress.vlan.id
 - **Type:** keyword
 - **Example:** 10
 - **Description:** VLAN ID as reported by the observer.
- **Field:** observer.egress.vlan.name
 - **Type:** keyword
 - **Example:** outside
 - **Description:** Optional VLAN name as reported by the observer.

Field Set: observer.egress

- **Field:** observer.egress.zone
- **Type:** keyword
- **Example:** Public_Internet
- **Description:** Observer Egress zone

Field Set: observer.geo

- **Field:** observer.geo.city_name
- **Type:** keyword
- **Example:** Montreal
- **Description:** City name.
- **Field:** observer.geo.continent_code
- **Type:** keyword
- **Description:** Continent code.
- **Field:** observer.geo.continent_name
- **Type:** keyword
- **Example:** North America
- **Description:** Name of the continent.
- **Field:** observer.geo.country_iso_code
- **Type:** keyword
- **Example:** CA
- **Description:** Country ISO code.
- **Field:** observer.geo.country_name
- **Type:** keyword
- **Example:** Canada
- **Description:** Country name.
- **Field:** observer.geo.location
- **Type:** geo_point
- **Example:** { "lon": -73.614830, "lat": 45.505918 }
- **Description:** Longitude and latitude.
- **Field:** observer.geo.name
- **Type:** keyword
- **Example:** boston-dc
- **Description:** User-defined description of a location.
- **Field:** observer.geo.postal_code
- **Type:** keyword
- **Example:** 94040
- **Description:** Postal code.
- **Field:** observer.geo.region_iso_code
- **Type:** keyword
- **Example:** CA-QC
- **Description:** Region ISO code.
- **Field:** observer.geo.region_name
- **Type:** keyword
- **Example:** Quebec
- **Description:** Region name.
- **Field:** observer.geo.timezone
- **Type:** keyword
- **Example:** America/Argentina/Buenos_Aires
- **Description:** Time zone.

Field Set: observer

- **Field:** observer.hostname
 - **Type:** keyword
 - **Description:** Hostname of the observer.
- **Field:** observer.ingress
 - **Type:** object
 - **Description:** Object field for ingress information

Field Set: observer.ingress.interface

- **Field:** observer.ingress.interface.alias
 - **Type:** keyword
 - **Example:** outside
 - **Description:** Interface alias
- **Field:** observer.ingress.interface.id
 - **Type:** keyword
 - **Example:** 10
 - **Description:** Interface ID
- **Field:** observer.ingress.interface.name
 - **Type:** keyword
 - **Example:** eth0
 - **Description:** Interface name

Field Set: observer.ingress.vlan

- **Field:** observer.ingress.vlan.id
 - **Type:** keyword
 - **Example:** 10
 - **Description:** VLAN ID as reported by the observer.
- **Field:** observer.ingress.vlan.name
 - **Type:** keyword
 - **Example:** outside
 - **Description:** Optional VLAN name as reported by the observer.

Field Set: observer.ingress

- **Field:** observer.ingress.zone
 - **Type:** keyword
 - **Example:** DMZ
 - **Description:** Observer ingress zone

Field Set: observer

- **Field:** observer.ip
 - **Type:** ip
 - **Description:** IP addresses of the observer.
- **Field:** observer.mac
 - **Type:** keyword
 - **Example:** ["00-00-5E-00-53-23", "00-00-5E-00-53-24"]
 - **Description:** MAC addresses of the observer.
- **Field:** observer.name
 - **Type:** keyword
 - **Example:** 1_proxySG

- **Description:** Custom name of the observer.

Field Set: observer.os

- **Field:** observer.os.family
 - **Type:** keyword
 - **Example:** debian
 - **Description:** OS family (such as redhat, debian, freebsd, windows).
- **Field:** observer.os.full
 - **Type:** keyword
 - **Example:** Mac OS Mojave
 - **Description:** Operating system name, including the version or code name.

Field Set: observer.os.full

- **Field:** observer.os.full.text
 - **Type:** match_only_text
 - **Example:** Mac OS Mojave
 - **Description:** Operating system name, including the version or code name.

Field Set: observer.os

- **Field:** observer.os.kernel
 - **Type:** keyword
 - **Example:** 4.4.0-112-generic
 - **Description:** Operating system kernel version as a raw string.
- **Field:** observer.os.name
 - **Type:** keyword
 - **Example:** Mac OS X
 - **Description:** Operating system name, without the version.

Field Set: observer.os.name

- **Field:** observer.os.name.text
 - **Type:** match_only_text
 - **Example:** Mac OS X
 - **Description:** Operating system name, without the version.

Field Set: observer.os

- **Field:** observer.os.platform
 - **Type:** keyword
 - **Example:** darwin
 - **Description:** Operating system platform (such centos, ubuntu, windows).
- **Field:** observer.os.type
 - **Type:** keyword
 - **Example:** macos
 - **Description:** Which commercial OS family (one of: linux, macos, unix, windows, ios or android).
- **Field:** observer.os.version
 - **Type:** keyword
 - **Example:** 10.14.1
 - **Description:** Operating system version as a raw string.

Field Set: observer

- **Field:** observer.product
 - **Type:** keyword
 - **Example:** s200
 - **Description:** The product name of the observer.
- **Field:** observer.serial_number
 - **Type:** keyword
 - **Description:** Observer serial number.
- **Field:** observer.type
 - **Type:** keyword
 - **Example:** firewall
 - **Description:** The type of the observer the data is coming from.
- **Field:** observer.vendor
 - **Type:** keyword
 - **Example:** Symantec
 - **Description:** Vendor name of the observer.
- **Field:** observer.version
 - **Type:** keyword
 - **Description:** Observer version.

Field Set: orchestrator

- **Field:** orchestrator.api_version
 - **Type:** keyword
 - **Example:** v1beta1
 - **Description:** API version being used to carry out the action

Field Set: orchestrator.cluster

- **Field:** orchestrator.cluster.id
 - **Type:** keyword
 - **Description:** Unique ID of the cluster.
- **Field:** orchestrator.cluster.name
 - **Type:** keyword
 - **Description:** Name of the cluster.
- **Field:** orchestrator.cluster.url
 - **Type:** keyword
 - **Description:** URL of the API used to manage the cluster.
- **Field:** orchestrator.cluster.version
 - **Type:** keyword
 - **Description:** The version of the cluster.

Field Set: orchestrator

- **Field:** orchestrator.namespace
 - **Type:** keyword
 - **Example:** kube-system
 - **Description:** Namespace in which the action is taking place.
- **Field:** orchestrator.organization
 - **Type:** keyword
 - **Example:** elastic
 - **Description:** Organization affected by the event (for multi-tenant orchestrator setups).

Field Set: orchestrator.resource

- **Field:** orchestrator.resource.annotation
 - **Type:** keyword
 - **Example:** ['key1:value1', 'key2:value2', 'key3:value3']
 - **Description:** The list of annotations added to the resource.
- **Field:** orchestrator.resource.id
 - **Type:** keyword
 - **Description:** Unique ID of the resource being acted upon.
- **Field:** orchestrator.resource.ip
 - **Type:** ip
 - **Description:** IP address assigned to the resource associated with the event being observed.
- **Field:** orchestrator.resource.label
 - **Type:** keyword
 - **Example:** ['key1:value1', 'key2:value2', 'key3:value3']
 - **Description:** The list of labels added to the resource.
- **Field:** orchestrator.resource.name
 - **Type:** keyword
 - **Example:** test-pod-cdcws
 - **Description:** Name of the resource being acted upon.

Field Set: orchestrator.resource.parent

- **Field:** orchestrator.resource.parent.type
 - **Type:** keyword
 - **Example:** DaemonSet
 - **Description:** Type or kind of the parent resource associated with the event being observed.

Field Set: orchestrator.resource

- **Field:** orchestrator.resource.type
 - **Type:** keyword
 - **Example:** service
 - **Description:** Type of resource being acted upon.

Field Set: orchestrator

- **Field:** orchestrator.type
 - **Type:** keyword
 - **Example:** kubernetes
 - **Description:** Orchestrator cluster type (e.g. kubernetes, nomad or cloudfoundry).

Field Set: organization

- **Field:** organization.id
 - **Type:** keyword
 - **Description:** Unique identifier for the organization.
- **Field:** organization.name
 - **Type:** keyword
 - **Description:** Organization name.

Field Set: organization.name

- **Field:** organization.name.text
- **Type:** match_only_text
- **Description:** Organization name.

Field Set: package

- **Field:** package.architecture
- **Type:** keyword
- **Example:** x86_64
- **Description:** Package architecture.
- **Field:** package.build_version
- **Type:** keyword
- **Example:** 36f4f7e89dd61b0988b12ee000b98966867710cd
- **Description:** Build version information
- **Field:** package.checksum
- **Type:** keyword
- **Example:** 68b329da9893e34099c7d8ad5cb9c940
- **Description:** Checksum of the installed package for verification.
- **Field:** package.description
- **Type:** keyword
- **Example:** Open source programming language to build simple/reliable/efficient software.
- **Description:** Description of the package.
- **Field:** package.install_scope
- **Type:** keyword
- **Example:** global
- **Description:** Indicating how the package was installed, e.g. user-local, global.
- **Field:** package.installed
- **Type:** date
- **Description:** Time when package was installed.
- **Field:** package.license
- **Type:** keyword
- **Example:** Apache License 2.0
- **Description:** Package license
- **Field:** package.name
- **Type:** keyword
- **Example:** go
- **Description:** Package name
- **Field:** package.path
- **Type:** keyword
- **Example:** /usr/local/Cellar/go/1.12.9/
- **Description:** Path where the package is installed.
- **Field:** package.reference
- **Type:** keyword
- **Example:** <https://golang.org>
- **Description:** Package home page or reference URL
- **Field:** package.size
- **Type:** long
- **Example:** 62231
- **Description:** Package size in bytes.
- **Field:** package.type
- **Type:** keyword

- **Example:** rpm
- **Description:** Package type
- **Field:** package.version
- **Type:** keyword
- **Example:** 1.12.9
- **Description:** Package version

Field Set: process

- **Field:** process.args
- **Type:** keyword
- **Example:** ["/usr/bin/ssh", "-l", "user", "10.0.0.16"]
- **Description:** Array of process arguments.
- **Field:** process.args_count
- **Type:** long
- **Example:** 4
- **Description:** Length of the process.args array.

Field Set: process.code_signature

- **Field:** process.code_signature.digest_algorithm
- **Type:** keyword
- **Example:** sha256
- **Description:** Hashing algorithm used to sign the process.
- **Field:** process.code_signature.exists
- **Type:** boolean
- **Example:** true
- **Description:** Boolean to capture if a signature is present.
- **Field:** process.code_signature.flags
- **Type:** keyword
- **Example:** 570522385
- **Description:** Code signing flags of the process
- **Field:** process.code_signature.signing_id
- **Type:** keyword
- **Example:** com.apple.xpc.proxy
- **Description:** The identifier used to sign the process.
- **Field:** process.code_signature.status
- **Type:** keyword
- **Example:** ERROR_UNTRUSTED_ROOT
- **Description:** Additional information about the certificate status.
- **Field:** process.code_signature.subject_name
- **Type:** keyword
- **Example:** Microsoft Corporation
- **Description:** Subject name of the code signer
- **Field:** process.code_signature.team_id
- **Type:** keyword
- **Example:** EQHXZ8M8AV
- **Description:** The team identifier used to sign the process.
- **Field:** process.code_signature.timestamp
- **Type:** date
- **Example:** 2021-01-01T12:10:30Z

- **Description:** When the signature was generated and signed.
- **Field:** process.code_signature.trusted
 - **Type:** boolean
 - **Example:** true
 - **Description:** Stores the trust status of the certificate chain.
- **Field:** process.code_signature.valid
 - **Type:** boolean
 - **Example:** true
 - **Description:** Boolean to capture if the digital signature is verified against the binary content.

Field Set: process

- **Field:** process.command_line
 - **Type:** wildcard
 - **Example:** /usr/bin/ssh -l user 10.0.0.16
 - **Description:** Full command line that started the process.

Field Set: process.command_line

- **Field:** process.command_line.text
 - **Type:** match_only_text
 - **Example:** /usr/bin/ssh -l user 10.0.0.16
 - **Description:** Full command line that started the process.

Field Set: process.elf

- **Field:** process.elf.architecture
 - **Type:** keyword
 - **Example:** x86-64
 - **Description:** Machine architecture of the ELF file.
- **Field:** process.elf.byte_order
 - **Type:** keyword
 - **Example:** Little Endian
 - **Description:** Byte sequence of ELF file.
- **Field:** process.elf.cpu_type
 - **Type:** keyword
 - **Example:** Intel
 - **Description:** CPU type of the ELF file.
- **Field:** process.elf.creation_date
 - **Type:** date
 - **Description:** Build or compile date.
- **Field:** process.elf.exports
 - **Type:** flattened
 - **Description:** List of exported element names and types.
- **Field:** process.elf.go_import_hash
 - **Type:** keyword
 - **Example:** 10bddcb4cee42080f76c88d9ff964491
 - **Description:** A hash of the Go language imports in an ELF file.
- **Field:** process.elf.go_imports
 - **Type:** flattened
 - **Description:** List of imported Go language element names and types.

- **Field:** process.elf.go_imports_names_entropy
 - **Type:** long
 - **Description:** Shannon entropy calculation from the list of Go imports.
- **Field:** process.elf.go_imports_names_var_entropy
 - **Type:** long
 - **Description:** Variance for Shannon entropy calculation from the list of Go imports.
- **Field:** process.elf.go_stripped
 - **Type:** boolean
 - **Description:** Whether the file is a stripped or obfuscated Go executable.

Field Set: process.elf.header

- **Field:** process.elf.header.abi_version
 - **Type:** keyword
 - **Description:** Version of the ELF Application Binary Interface (ABI).
- **Field:** process.elf.header.class
 - **Type:** keyword
 - **Description:** Header class of the ELF file.
- **Field:** process.elf.header.data
 - **Type:** keyword
 - **Description:** Data table of the ELF header.
- **Field:** process.elf.header.entrypoint
 - **Type:** long
 - **Description:** Header entrypoint of the ELF file.
- **Field:** process.elf.header.object_version
 - **Type:** keyword
 - **Description:** "0x1" for original ELF files.
- **Field:** process.elf.header.os_abi
 - **Type:** keyword
 - **Description:** Application Binary Interface (ABI) of the Linux OS.
- **Field:** process.elf.header.type
 - **Type:** keyword
 - **Description:** Header type of the ELF file.
- **Field:** process.elf.header.version
 - **Type:** keyword
 - **Description:** Version of the ELF header.

Field Set: process.elf

- **Field:** process.elf.import_hash
 - **Type:** keyword
 - **Example:** d41d8cd98f00b204e9800998ecf8427e
 - **Description:** A hash of the imports in an ELF file.
- **Field:** process.elf.imports
 - **Type:** flattened
 - **Description:** List of imported element names and types.
- **Field:** process.elf.imports_names_entropy
 - **Type:** long
 - **Description:** Shannon entropy calculation from the list of imported element names and types.
- **Field:** process.elf.imports_names_var_entropy
 - **Type:** long

- **Description:** Variance for Shannon entropy calculation from the list of imported element names and types.
- **Field:** process.elf.sections
 - **Type:** nested
 - **Description:** Section information of the ELF file.

Field Set: process.elf.sections

- **Field:** process.elf.sections.chi2
 - **Type:** long
 - **Description:** Chi-square probability distribution of the section.
- **Field:** process.elf.sections.entropy
 - **Type:** long
 - **Description:** Shannon entropy calculation from the section.
- **Field:** process.elf.sections.flags
 - **Type:** keyword
 - **Description:** ELF Section List flags.
- **Field:** process.elf.sections.name
 - **Type:** keyword
 - **Description:** ELF Section List name.
- **Field:** process.elf.sections.physical_offset
 - **Type:** keyword
 - **Description:** ELF Section List offset.
- **Field:** process.elf.sections.physical_size
 - **Type:** long
 - **Description:** ELF Section List physical size.
- **Field:** process.elf.sections.type
 - **Type:** keyword
 - **Description:** ELF Section List type.
- **Field:** process.elf.sections.var_entropy
 - **Type:** long
 - **Description:** Variance for Shannon entropy calculation from the section.
- **Field:** process.elf.sections.virtual_address
 - **Type:** long
 - **Description:** ELF Section List virtual address.
- **Field:** process.elf.sections.virtual_size
 - **Type:** long
 - **Description:** ELF Section List virtual size.

Field Set: process.elf

- **Field:** process.elf.segments
 - **Type:** nested
 - **Description:** ELF object segment list.

Field Set: process.elf.segments

- **Field:** process.elf.segments.sections
 - **Type:** keyword
 - **Description:** ELF object segment sections.

- **Field:** process.elf.segments.type
- **Type:** keyword
- **Description:** ELF object segment type.

Field Set: process.elf

- **Field:** process.elf.shared_libraries
- **Type:** keyword
- **Description:** List of shared libraries used by this ELF object.
- **Field:** process.elf.telfhash
- **Type:** keyword
- **Description:** telfhash hash for ELF file.

Field Set: process

- **Field:** process.end
- **Type:** date
- **Example:** 2016-05-23T08:05:34.853Z
- **Description:** The time the process ended.
- **Field:** process.entity_id
- **Type:** keyword
- **Example:** c2c455d9f99375d
- **Description:** Unique identifier for the process.

Field Set: process.entry_leader

- **Field:** process.entry_leader.args
- **Type:** keyword
- **Example:** ["/usr/bin/ssh", "-l", "user", "10.0.0.16"]
- **Description:** Array of process arguments.
- **Field:** process.entry_leader.args_count
- **Type:** long
- **Example:** 4
- **Description:** Length of the process.args array.

Field Set: process.entry_leader.attested_groups

- **Field:** process.entry_leader.attested_groups.name
- **Type:** keyword
- **Description:** Name of the group.

Field Set: process.entry_leader.attested_user

- **Field:** process.entry_leader.attested_user.id
- **Type:** keyword
- **Example:** S-1-5-21-202424912787-2692429404-2351956786-1000
- **Description:** Unique identifier of the user.
- **Field:** process.entry_leader.attested_user.name
- **Type:** keyword
- **Example:** a.einstein
- **Description:** Short name or login of the user.

Field Set: process.entry_leader.attested_user.name

- **Field:** process.entry_leader.attested_user.name.text
- **Type:** match_only_text
- **Example:** a.einstein
- **Description:** Short name or login of the user.

Field Set: process.entry_leader

- **Field:** process.entry_leader.command_line
- **Type:** wildcard
- **Example:** /usr/bin/ssh -l user 10.0.0.16
- **Description:** Full command line that started the process.

Field Set: process.entry_leader.command_line

- **Field:** process.entry_leader.command_line.text
- **Type:** match_only_text
- **Example:** /usr/bin/ssh -l user 10.0.0.16
- **Description:** Full command line that started the process.

Field Set: process.entry_leader

- **Field:** process.entry_leader.entity_id
- **Type:** keyword
- **Example:** c2c455d9f99375d
- **Description:** Unique identifier for the process.

Field Set: process.entry_leader.entry_meta.source

- **Field:** process.entry_leader.entry_meta.source.ip
- **Type:** ip
- **Description:** IP address of the source.

Field Set: process.entry_leader.entry_meta

- **Field:** process.entry_leader.entry_meta.type
- **Type:** keyword
- **Description:** The entry type for the entry session leader.

Field Set: process.entry_leader

- **Field:** process.entry_leader.executable
- **Type:** keyword
- **Example:** /usr/bin/ssh
- **Description:** Absolute path to the process executable.

Field Set: process.entry_leader.executable

- **Field:** process.entry_leader.executable.text
- **Type:** match_only_text
- **Example:** /usr/bin/ssh
- **Description:** Absolute path to the process executable.

Field Set: process.entry_leader.group

- **Field:** process.entry_leader.group.id
- **Type:** keyword
- **Description:** Unique identifier for the group on the system/platform.

- **Field:** process.entry_leader.group.name
- **Type:** keyword
- **Description:** Name of the group.

Field Set: process.entry_leader

- **Field:** process.entry_leader.interactive
- **Type:** boolean
- **Example:** True
- **Description:** Whether the process is connected to an interactive shell.
- **Field:** process.entry_leader.name
- **Type:** keyword
- **Example:** ssh
- **Description:** Process name.

Field Set: process.entry_leader.name

- **Field:** process.entry_leader.name.text
- **Type:** match_only_text
- **Example:** ssh
- **Description:** Process name.

Field Set: process.entry_leader.parent

- **Field:** process.entry_leader.parent.entity_id
- **Type:** keyword
- **Example:** c2c455d9f99375d
- **Description:** Unique identifier for the process.
- **Field:** process.entry_leader.parent.pid
- **Type:** long
- **Example:** 4242
- **Description:** Process id.

Field Set: process.entry_leader.parent.session_leader

- **Field:** process.entry_leader.parent.session_leader.entity_id
- **Type:** keyword
- **Example:** c2c455d9f99375d
- **Description:** Unique identifier for the process.
- **Field:** process.entry_leader.parent.session_leader.pid
- **Type:** long
- **Example:** 4242
- **Description:** Process id.
- **Field:** process.entry_leader.parent.session_leader.start
- **Type:** date
- **Example:** 2016-05-23T08:05:34.853Z
- **Description:** The time the process started.
- **Field:** process.entry_leader.parent.session_leader.vpid
- **Type:** long
- **Example:** 4242
- **Description:** Virtual process id.

Field Set: process.entry_leader.parent

- **Field:** process.entry_leader.parent.start
- **Type:** date
- **Example:** 2016-05-23T08:05:34.853Z
- **Description:** The time the process started.
- **Field:** process.entry_leader.parent.vpid
- **Type:** long
- **Example:** 4242
- **Description:** Virtual process id.

Field Set: process.entry_leader

- **Field:** process.entry_leader.pid
- **Type:** long
- **Example:** 4242
- **Description:** Process id.

Field Set: process.entry_leader.real_group

- **Field:** process.entry_leader.real_group.id
- **Type:** keyword
- **Description:** Unique identifier for the group on the system/platform.
- **Field:** process.entry_leader.real_group.name
- **Type:** keyword
- **Description:** Name of the group.

Field Set: process.entry_leader.real_user

- **Field:** process.entry_leader.real_user.id
- **Type:** keyword
- **Example:** S-1-5-21-202424912787-2692429404-2351956786-1000
- **Description:** Unique identifier of the user.
- **Field:** process.entry_leader.real_user.name
- **Type:** keyword
- **Example:** a.einstein
- **Description:** Short name or login of the user.

Field Set: process.entry_leader.real_user.name

- **Field:** process.entry_leader.real_user.name.text
- **Type:** match_only_text
- **Example:** a.einstein
- **Description:** Short name or login of the user.

Field Set: process.entry_leader

- **Field:** process.entry_leader.same_as_process
- **Type:** boolean
- **Example:** True
- **Description:** This boolean is used to identify if a leader process is the same as the top level process.

Field Set: process.entry_leader.saved_group

- **Field:** process.entry_leader.saved_group.id
- **Type:** keyword

- **Description:** Unique identifier for the group on the system/platform.
- **Field:** process.entry_leader.saved_group.name
 - **Type:** keyword
 - **Description:** Name of the group.

Field Set: process.entry_leader.saved_user

- **Field:** process.entry_leader.saved_user.id
 - **Type:** keyword
 - **Example:** S-1-5-21-202424912787-2692429404-2351956786-1000
 - **Description:** Unique identifier of the user.
- **Field:** process.entry_leader.saved_user.name
 - **Type:** keyword
 - **Example:** a.einstein
 - **Description:** Short name or login of the user.

Field Set: process.entry_leader.saved_user.name

- **Field:** process.entry_leader.saved_user.name.text
 - **Type:** match_only_text
 - **Example:** a.einstein
 - **Description:** Short name or login of the user.

Field Set: process.entry_leader

- **Field:** process.entry_leader.start
 - **Type:** date
 - **Example:** 2016-05-23T08:05:34.853Z
 - **Description:** The time the process started.

Field Set: process.entry_leader.supplemental_groups

- **Field:** process.entry_leader.supplemental_groups.id
 - **Type:** keyword
 - **Description:** Unique identifier for the group on the system/platform.
- **Field:** process.entry_leader.supplemental_groups.name
 - **Type:** keyword
 - **Description:** Name of the group.

Field Set: process.entry_leader

- **Field:** process.entry_leader.tty
 - **Type:** object
 - **Description:** Information about the controlling TTY device.

Field Set: process.entry_leader.tty.char_device

- **Field:** process.entry_leader.tty.char_device.major
 - **Type:** long
 - **Example:** 4
 - **Description:** The TTY character device's major number.
- **Field:** process.entry_leader.tty.char_device.minor
 - **Type:** long
 - **Example:** 1

- **Description:** The TTY character device's minor number.

Field Set: process.entry_leader.user

- **Field:** process.entry_leader.user.id
 - **Type:** keyword
 - **Example:** S-1-5-21-202424912787-2692429404-2351956786-1000
 - **Description:** Unique identifier of the user.
- **Field:** process.entry_leader.user.name
 - **Type:** keyword
 - **Example:** a.einstein
 - **Description:** Short name or login of the user.

Field Set: process.entry_leader.user.name

- **Field:** process.entry_leader.user.name.text
 - **Type:** match_only_text
 - **Example:** a.einstein
 - **Description:** Short name or login of the user.

Field Set: process.entry_leader

- **Field:** process.entry_leader.vpid
 - **Type:** long
 - **Example:** 4242
 - **Description:** Virtual process id.
- **Field:** process.entry_leader.working_directory
 - **Type:** keyword
 - **Example:** /home/alice
 - **Description:** The working directory of the process.

Field Set: process.entry_leader.working_directory

- **Field:** process.entry_leader.working_directory.text
 - **Type:** match_only_text
 - **Example:** /home/alice
 - **Description:** The working directory of the process.

Field Set: process

- **Field:** process.env_vars
 - **Type:** keyword
 - **Example:** ["PATH=/usr/local/bin:/usr/bin", "USER=ubuntu"]
 - **Description:** Array of environment variable bindings.
- **Field:** process.executable
 - **Type:** keyword
 - **Example:** /usr/bin/ssh
 - **Description:** Absolute path to the process executable.

Field Set: process.executable

- **Field:** process.executable.text
 - **Type:** match_only_text
 - **Example:** /usr/bin/ssh

- **Description:** Absolute path to the process executable.

Field Set: process

- **Field:** process.exit_code
- **Type:** long
- **Example:** 137
- **Description:** The exit code of the process.

Field Set: process.group

- **Field:** process.group.id
- **Type:** keyword
- **Description:** Unique identifier for the group on the system/platform.
- **Field:** process.group.name
- **Type:** keyword
- **Description:** Name of the group.

Field Set: process.group_leader

- **Field:** process.group_leader.args
- **Type:** keyword
- **Example:** ["/usr/bin/ssh", "-l", "user", "10.0.0.16"]
- **Description:** Array of process arguments.
- **Field:** process.group_leader.args_count
- **Type:** long
- **Example:** 4
- **Description:** Length of the process.args array.
- **Field:** process.group_leader.command_line
- **Type:** wildcard
- **Example:** /usr/bin/ssh -l user 10.0.0.16
- **Description:** Full command line that started the process.

Field Set: process.group_leader.command_line

- **Field:** process.group_leader.command_line.text
- **Type:** match_only_text
- **Example:** /usr/bin/ssh -l user 10.0.0.16
- **Description:** Full command line that started the process.

Field Set: process.group_leader

- **Field:** process.group_leader.entity_id
- **Type:** keyword
- **Example:** c2c455d9f99375d
- **Description:** Unique identifier for the process.
- **Field:** process.group_leader.executable
- **Type:** keyword
- **Example:** /usr/bin/ssh
- **Description:** Absolute path to the process executable.

Field Set: process.group_leader.executable

- **Field:** process.group_leader.executable.text
- **Type:** match_only_text
- **Example:** /usr/bin/ssh
- **Description:** Absolute path to the process executable.

Field Set: process.group_leader.group

- **Field:** process.group_leader.group.id
- **Type:** keyword
- **Description:** Unique identifier for the group on the system/platform.
- **Field:** process.group_leader.group.name
- **Type:** keyword
- **Description:** Name of the group.

Field Set: process.group_leader

- **Field:** process.group_leader.interactive
- **Type:** boolean
- **Example:** True
- **Description:** Whether the process is connected to an interactive shell.
- **Field:** process.group_leader.name
- **Type:** keyword
- **Example:** ssh
- **Description:** Process name.

Field Set: process.group_leader.name

- **Field:** process.group_leader.name.text
- **Type:** match_only_text
- **Example:** ssh
- **Description:** Process name.

Field Set: process.group_leader

- **Field:** process.group_leader.pid
- **Type:** long
- **Example:** 4242
- **Description:** Process id.

Field Set: process.group_leader.real_group

- **Field:** process.group_leader.real_group.id
- **Type:** keyword
- **Description:** Unique identifier for the group on the system/platform.
- **Field:** process.group_leader.real_group.name
- **Type:** keyword
- **Description:** Name of the group.

Field Set: process.group_leader.real_user

- **Field:** process.group_leader.real_user.id
- **Type:** keyword
- **Example:** S-1-5-21-202424912787-2692429404-2351956786-1000
- **Description:** Unique identifier of the user.

- **Field:** process.group_leader.real_user.name
- **Type:** keyword
- **Example:** a.einstein
- **Description:** Short name or login of the user.

Field Set: process.group_leader.real_user.name

- **Field:** process.group_leader.real_user.name.text
- **Type:** match_only_text
- **Example:** a.einstein
- **Description:** Short name or login of the user.

Field Set: process.group_leader

- **Field:** process.group_leader.same_as_process
- **Type:** boolean
- **Example:** True
- **Description:** This boolean is used to identify if a leader process is the same as the top level process.

Field Set: process.group_leader.saved_group

- **Field:** process.group_leader.saved_group.id
- **Type:** keyword
- **Description:** Unique identifier for the group on the system/platform.
- **Field:** process.group_leader.saved_group.name
- **Type:** keyword
- **Description:** Name of the group.

Field Set: process.group_leader.saved_user

- **Field:** process.group_leader.saved_user.id
- **Type:** keyword
- **Example:** S-1-5-21-202424912787-2692429404-2351956786-1000
- **Description:** Unique identifier of the user.
- **Field:** process.group_leader.saved_user.name
- **Type:** keyword
- **Example:** a.einstein
- **Description:** Short name or login of the user.

Field Set: process.group_leader.saved_user.name

- **Field:** process.group_leader.saved_user.name.text
- **Type:** match_only_text
- **Example:** a.einstein
- **Description:** Short name or login of the user.

Field Set: process.group_leader

- **Field:** process.group_leader.start
- **Type:** date
- **Example:** 2016-05-23T08:05:34.853Z
- **Description:** The time the process started.

Field Set: process.group_leader.supplemental_groups

- **Field:** process.group_leader.supplemental_groups.id
- **Type:** keyword
- **Description:** Unique identifier for the group on the system/platform.
- **Field:** process.group_leader.supplemental_groups.name
- **Type:** keyword
- **Description:** Name of the group.

Field Set: process.group_leader

- **Field:** process.group_leader.tty
- **Type:** object
- **Description:** Information about the controlling TTY device.

Field Set: process.group_leader.tty.char_device

- **Field:** process.group_leader.tty.char_device.major
- **Type:** long
- **Example:** 4
- **Description:** The TTY character device's major number.
- **Field:** process.group_leader.tty.char_device.minor
- **Type:** long
- **Example:** 1
- **Description:** The TTY character device's minor number.

Field Set: process.group_leader.user

- **Field:** process.group_leader.user.id
- **Type:** keyword
- **Example:** S-1-5-21-202424912787-2692429404-2351956786-1000
- **Description:** Unique identifier of the user.
- **Field:** process.group_leader.user.name
- **Type:** keyword
- **Example:** a.einstein
- **Description:** Short name or login of the user.

Field Set: process.group_leader.user.name

- **Field:** process.group_leader.user.name.text
- **Type:** match_only_text
- **Example:** a.einstein
- **Description:** Short name or login of the user.

Field Set: process.group_leader

- **Field:** process.group_leader.vpid
- **Type:** long
- **Example:** 4242
- **Description:** Virtual process id.
- **Field:** process.group_leader.working_directory
- **Type:** keyword
- **Example:** /home/alice
- **Description:** The working directory of the process.

Field Set: process.group_leader.working_directory

- **Field:** process.group_leader.working_directory.text
- **Type:** match_only_text
- **Example:** /home/alice
- **Description:** The working directory of the process.

Field Set: process.hash

- **Field:** process.hash.cdhash
- **Type:** keyword
- **Example:** 3783b4052fd474dbe30676b45c329e7a6d44acd9
- **Description:** The Code Directory (CD) hash of an executable.
- **Field:** process.hash.md5
- **Type:** keyword
- **Description:** MD5 hash.
- **Field:** process.hash.sha1
- **Type:** keyword
- **Description:** SHA1 hash.
- **Field:** process.hash.sha256
- **Type:** keyword
- **Description:** SHA256 hash.
- **Field:** process.hash.sha384
- **Type:** keyword
- **Description:** SHA384 hash.
- **Field:** process.hash.sha512
- **Type:** keyword
- **Description:** SHA512 hash.
- **Field:** process.hash.ssdeep
- **Type:** keyword
- **Description:** SSDEEP hash.
- **Field:** process.hash.tlsh
- **Type:** keyword
- **Description:** TLSH hash.

Field Set: process

- **Field:** process.interactive
- **Type:** boolean
- **Example:** True
- **Description:** Whether the process is connected to an interactive shell.
- **Field:** process.io
- **Type:** object
- **Description:** A chunk of input or output (IO) from a single process.

Field Set: process.io

- **Field:** process.io.bytes_skipped
- **Type:** object
- **Description:** An array of byte offsets and lengths denoting where IO data has been skipped.

Field Set: process.io.bytes_skipped

- **Field:** process.io.bytes_skipped.length
- **Type:** long

- **Description:** The length of bytes skipped.
- **Field:** process.io.bytes_skipped.offset
 - **Type:** long
 - **Description:** The byte offset into this event's io.text (or io.bytes in the future) where length bytes were skipped.

Field Set: process.io

- **Field:** process.io.max_bytes_per_process_exceeded
 - **Type:** boolean
 - **Description:** If true, the process producing the output has exceeded the max_kilobytes_per_process configuration setting.
- **Field:** process.io.text
 - **Type:** wildcard
 - **Description:** A chunk of output or input sanitized to UTF-8.
- **Field:** process.io.total_bytes_captured
 - **Type:** long
 - **Description:** The total number of bytes captured in this event.
- **Field:** process.io.total_bytes_skipped
 - **Type:** long
 - **Description:** The total number of bytes that were not captured due to implementation restrictions such as buffer size limits.
- **Field:** process.io.type
 - **Type:** keyword
 - **Description:** The type of object on which the IO action (read or write) was taken.

Field Set: process.macho

- **Field:** process.macho.go_import_hash
 - **Type:** keyword
 - **Example:** 10bddcb4cee42080f76c88d9ff964491
 - **Description:** A hash of the Go language imports in a Mach-O file.
- **Field:** process.macho.go_imports
 - **Type:** flattened
 - **Description:** List of imported Go language element names and types.
- **Field:** process.macho.go_imports_names_entropy
 - **Type:** long
 - **Description:** Shannon entropy calculation from the list of Go imports.
- **Field:** process.macho.go_imports_names_var_entropy
 - **Type:** long
 - **Description:** Variance for Shannon entropy calculation from the list of Go imports.
- **Field:** process.macho.go_stripped
 - **Type:** boolean
 - **Description:** Whether the file is a stripped or obfuscated Go executable.
- **Field:** process.macho.import_hash
 - **Type:** keyword
 - **Example:** d41d8cd98f00b204e9800998ecf8427e
 - **Description:** A hash of the imports in a Mach-O file.
- **Field:** process.macho.imports
 - **Type:** flattened

- **Description:** List of imported element names and types.
- **Field:** process.macho.imports_names_entropy
 - **Type:** long
 - **Description:** Shannon entropy calculation from the list of imported element names and types.
- **Field:** process.macho.imports_names_var_entropy
 - **Type:** long
 - **Description:** Variance for Shannon entropy calculation from the list of imported element names and types.
- **Field:** process.macho.sections
 - **Type:** nested
 - **Description:** Section information of the Mach-O file.

Field Set: process.macho.sections

- **Field:** process.macho.sections.entropy
 - **Type:** long
 - **Description:** Shannon entropy calculation from the section.
- **Field:** process.macho.sections.name
 - **Type:** keyword
 - **Description:** Mach-O Section List name.
- **Field:** process.macho.sections.physical_size
 - **Type:** long
 - **Description:** Mach-O Section List physical size.
- **Field:** process.macho.sections.var_entropy
 - **Type:** long
 - **Description:** Variance for Shannon entropy calculation from the section.
- **Field:** process.macho.sections.virtual_size
 - **Type:** long
 - **Description:** Mach-O Section List virtual size. This is always the same as `physical\_size`.

Field Set: process.macho

- **Field:** process.macho.symhash
 - **Type:** keyword
 - **Example:** d3ccf195b62a9279c3c19af1080497ec
 - **Description:** A hash of the imports in a Mach-O file.

Field Set: process

- **Field:** process.name
 - **Type:** keyword
 - **Example:** ssh
 - **Description:** Process name.

Field Set: process.name

- **Field:** process.name.text
 - **Type:** match_only_text
 - **Example:** ssh
 - **Description:** Process name.

Field Set: process.parent

- **Field:** process.parent.args
- **Type:** keyword
- **Example:** ["/usr/bin/ssh", "-l", "user", "10.0.0.16"]
- **Description:** Array of process arguments.
- **Field:** process.parent.args_count
- **Type:** long
- **Example:** 4
- **Description:** Length of the process.args array.

Field Set: process.parent.code_signature

- **Field:** process.parent.code_signature.digest_algorithm
- **Type:** keyword
- **Example:** sha256
- **Description:** Hashing algorithm used to sign the process.
- **Field:** process.parent.code_signature.exists
- **Type:** boolean
- **Example:** true
- **Description:** Boolean to capture if a signature is present.
- **Field:** process.parent.code_signature.flags
- **Type:** keyword
- **Example:** 570522385
- **Description:** Code signing flags of the process
- **Field:** process.parent.code_signature.signing_id
- **Type:** keyword
- **Example:** com.apple.xpc.proxy
- **Description:** The identifier used to sign the process.
- **Field:** process.parent.code_signature.status
- **Type:** keyword
- **Example:** ERROR_UNTRUSTED_ROOT
- **Description:** Additional information about the certificate status.
- **Field:** process.parent.code_signature.subject_name
- **Type:** keyword
- **Example:** Microsoft Corporation
- **Description:** Subject name of the code signer
- **Field:** process.parent.code_signature.team_id
- **Type:** keyword
- **Example:** EQHXZ8M8AV
- **Description:** The team identifier used to sign the process.
- **Field:** process.parent.code_signature.timestamp
- **Type:** date
- **Example:** 2021-01-01T12:10:30Z
- **Description:** When the signature was generated and signed.
- **Field:** process.parent.code_signature.trusted
- **Type:** boolean
- **Example:** true
- **Description:** Stores the trust status of the certificate chain.
- **Field:** process.parent.code_signature.valid
- **Type:** boolean
- **Example:** true
- **Description:** Boolean to capture if the digital signature is verified against the binary content.

Field Set: process.parent

- **Field:** process.parent.command_line
- **Type:** wildcard
- **Example:** /usr/bin/ssh -l user 10.0.0.16
- **Description:** Full command line that started the process.

Field Set: process.parent.command_line

- **Field:** process.parent.command_line.text
- **Type:** match_only_text
- **Example:** /usr/bin/ssh -l user 10.0.0.16
- **Description:** Full command line that started the process.

Field Set: process.parent.elf

- **Field:** process.parent.elf.architecture
- **Type:** keyword
- **Example:** x86-64
- **Description:** Machine architecture of the ELF file.
- **Field:** process.parent.elf.byte_order
- **Type:** keyword
- **Example:** Little Endian
- **Description:** Byte sequence of ELF file.
- **Field:** process.parent.elf.cpu_type
- **Type:** keyword
- **Example:** Intel
- **Description:** CPU type of the ELF file.
- **Field:** process.parent.elf.creation_date
- **Type:** date
- **Description:** Build or compile date.
- **Field:** process.parent.elf.exports
- **Type:** flattened
- **Description:** List of exported element names and types.
- **Field:** process.parent.elf.go_import_hash
- **Type:** keyword
- **Example:** 10bddcb4cee42080f76c88d9ff964491
- **Description:** A hash of the Go language imports in an ELF file.
- **Field:** process.parent.elf.go_imports
- **Type:** flattened
- **Description:** List of imported Go language element names and types.
- **Field:** process.parent.elf.go_imports_names_entropy
- **Type:** long
- **Description:** Shannon entropy calculation from the list of Go imports.
- **Field:** process.parent.elf.go_imports_names_var_entropy
- **Type:** long
- **Description:** Variance for Shannon entropy calculation from the list of Go imports.
- **Field:** process.parent.elf.go_stripped
- **Type:** boolean
- **Description:** Whether the file is a stripped or obfuscated Go executable.

Field Set: process.parent.elf.header

- **Field:** process.parent.elf.header.abi_version
 - **Type:** keyword
 - **Description:** Version of the ELF Application Binary Interface (ABI).
- **Field:** process.parent.elf.header.class
 - **Type:** keyword
 - **Description:** Header class of the ELF file.
- **Field:** process.parent.elf.header.data
 - **Type:** keyword
 - **Description:** Data table of the ELF header.
- **Field:** process.parent.elf.header.entrypoint
 - **Type:** long
 - **Description:** Header entrypoint of the ELF file.
- **Field:** process.parent.elf.header.object_version
 - **Type:** keyword
 - **Description:** "0x1" for original ELF files.
- **Field:** process.parent.elf.header.os_abi
 - **Type:** keyword
 - **Description:** Application Binary Interface (ABI) of the Linux OS.
- **Field:** process.parent.elf.header.type
 - **Type:** keyword
 - **Description:** Header type of the ELF file.
- **Field:** process.parent.elf.header.version
 - **Type:** keyword
 - **Description:** Version of the ELF header.

Field Set: process.parent.elf

- **Field:** process.parent.elf.import_hash
 - **Type:** keyword
 - **Example:** d41d8cd98f00b204e9800998ecf8427e
 - **Description:** A hash of the imports in an ELF file.
- **Field:** process.parent.elf.imports
 - **Type:** flattened
 - **Description:** List of imported element names and types.
- **Field:** process.parent.elf.imports_names_entropy
 - **Type:** long
 - **Description:** Shannon entropy calculation from the list of imported element names and types.
- **Field:** process.parent.elf.imports_names_var_entropy
 - **Type:** long
 - **Description:** Variance for Shannon entropy calculation from the list of imported element names and types.
- **Field:** process.parent.elf.sections
 - **Type:** nested
 - **Description:** Section information of the ELF file.

Field Set: process.parent.elf.sections

- **Field:** process.parent.elf.sections.chi2
 - **Type:** long
 - **Description:** Chi-square probability distribution of the section.

- **Field:** process.parent.elf.sections.entropy
 - **Type:** long
 - **Description:** Shannon entropy calculation from the section.
- **Field:** process.parent.elf.sections.flags
 - **Type:** keyword
 - **Description:** ELF Section List flags.
- **Field:** process.parent.elf.sections.name
 - **Type:** keyword
 - **Description:** ELF Section List name.
- **Field:** process.parent.elf.sections.physical_offset
 - **Type:** keyword
 - **Description:** ELF Section List offset.
- **Field:** process.parent.elf.sections.physical_size
 - **Type:** long
 - **Description:** ELF Section List physical size.
- **Field:** process.parent.elf.sections.type
 - **Type:** keyword
 - **Description:** ELF Section List type.
- **Field:** process.parent.elf.sections.var_entropy
 - **Type:** long
 - **Description:** Variance for Shannon entropy calculation from the section.
- **Field:** process.parent.elf.sections.virtual_address
 - **Type:** long
 - **Description:** ELF Section List virtual address.
- **Field:** process.parent.elf.sections.virtual_size
 - **Type:** long
 - **Description:** ELF Section List virtual size.

Field Set: process.parent.elf

- **Field:** process.parent.elf.segments
 - **Type:** nested
 - **Description:** ELF object segment list.

Field Set: process.parent.elf.segments

- **Field:** process.parent.elf.segments.sections
 - **Type:** keyword
 - **Description:** ELF object segment sections.
- **Field:** process.parent.elf.segments.type
 - **Type:** keyword
 - **Description:** ELF object segment type.

Field Set: process.parent.elf

- **Field:** process.parent.elf.shared_libraries
 - **Type:** keyword
 - **Description:** List of shared libraries used by this ELF object.
- **Field:** process.parent.elf.telfhash
 - **Type:** keyword
 - **Description:** telfhash hash for ELF file.

Field Set: process.parent

- **Field:** process.parent.end
 - **Type:** date
 - **Example:** 2016-05-23T08:05:34.853Z
 - **Description:** The time the process ended.
- **Field:** process.parent.entity_id
 - **Type:** keyword
 - **Example:** c2c455d9f99375d
 - **Description:** Unique identifier for the process.
- **Field:** process.parent.executable
 - **Type:** keyword
 - **Example:** /usr/bin/ssh
 - **Description:** Absolute path to the process executable.

Field Set: process.parent.executable

- **Field:** process.parent.executable.text
 - **Type:** match_only_text
 - **Example:** /usr/bin/ssh
 - **Description:** Absolute path to the process executable.

Field Set: process.parent

- **Field:** process.parent.exit_code
 - **Type:** long
 - **Example:** 137
 - **Description:** The exit code of the process.

Field Set: process.parent.group

- **Field:** process.parent.group.id
 - **Type:** keyword
 - **Description:** Unique identifier for the group on the system/platform.
- **Field:** process.parent.group.name
 - **Type:** keyword
 - **Description:** Name of the group.

Field Set: process.parent.group_leader

- **Field:** process.parent.group_leader.entity_id
 - **Type:** keyword
 - **Example:** c2c455d9f99375d
 - **Description:** Unique identifier for the process.
- **Field:** process.parent.group_leader.pid
 - **Type:** long
 - **Example:** 4242
 - **Description:** Process id.
- **Field:** process.parent.group_leader.start
 - **Type:** date
 - **Example:** 2016-05-23T08:05:34.853Z
 - **Description:** The time the process started.
- **Field:** process.parent.group_leader.vpid
 - **Type:** long

- **Example:** 4242
- **Description:** Virtual process id.

Field Set: process.parent.hash

- **Field:** process.parent.hash.cdhash
 - **Type:** keyword
 - **Example:** 3783b4052fd474dbe30676b45c329e7a6d44acd9
 - **Description:** The Code Directory (CD) hash of an executable.
- **Field:** process.parent.hash.md5
 - **Type:** keyword
 - **Description:** MD5 hash.
- **Field:** process.parent.hash.sha1
 - **Type:** keyword
 - **Description:** SHA1 hash.
- **Field:** process.parent.hash.sha256
 - **Type:** keyword
 - **Description:** SHA256 hash.
- **Field:** process.parent.hash.sha384
 - **Type:** keyword
 - **Description:** SHA384 hash.
- **Field:** process.parent.hash.sha512
 - **Type:** keyword
 - **Description:** SHA512 hash.
- **Field:** process.parent.hash.ssdeep
 - **Type:** keyword
 - **Description:** SSDEEP hash.
- **Field:** process.parent.hash.tlsh
 - **Type:** keyword
 - **Description:** TLSH hash.

Field Set: process.parent

- **Field:** process.parent.interactive
 - **Type:** boolean
 - **Example:** True
 - **Description:** Whether the process is connected to an interactive shell.

Field Set: process.parent.macho

- **Field:** process.parent.macho.go_import_hash
 - **Type:** keyword
 - **Example:** 10bddcb4cee42080f76c88d9ff964491
 - **Description:** A hash of the Go language imports in a Mach-O file.
- **Field:** process.parent.macho.go_imports
 - **Type:** flattened
 - **Description:** List of imported Go language element names and types.
- **Field:** process.parent.macho.go_imports_names_entropy
 - **Type:** long
 - **Description:** Shannon entropy calculation from the list of Go imports.

- **Field:** process.parent.macho.go_imports_names_var_entropy
 - **Type:** long
 - **Description:** Variance for Shannon entropy calculation from the list of Go imports.
- **Field:** process.parent.macho.go_stripped
 - **Type:** boolean
 - **Description:** Whether the file is a stripped or obfuscated Go executable.
- **Field:** process.parent.macho.import_hash
 - **Type:** keyword
 - **Example:** d41d8cd98f00b204e9800998ecf8427e
 - **Description:** A hash of the imports in a Mach-O file.
- **Field:** process.parent.macho.imports
 - **Type:** flattened
 - **Description:** List of imported element names and types.
- **Field:** process.parent.macho.imports_names_entropy
 - **Type:** long
 - **Description:** Shannon entropy calculation from the list of imported element names and types.
- **Field:** process.parent.macho.imports_names_var_entropy
 - **Type:** long
 - **Description:** Variance for Shannon entropy calculation from the list of imported element names and types.
- **Field:** process.parent.macho.sections
 - **Type:** nested
 - **Description:** Section information of the Mach-O file.

Field Set: process.parent.macho.sections

- **Field:** process.parent.macho.sections.entropy
 - **Type:** long
 - **Description:** Shannon entropy calculation from the section.
- **Field:** process.parent.macho.sections.name
 - **Type:** keyword
 - **Description:** Mach-O Section List name.
- **Field:** process.parent.macho.sections.physical_size
 - **Type:** long
 - **Description:** Mach-O Section List physical size.
- **Field:** process.parent.macho.sections.var_entropy
 - **Type:** long
 - **Description:** Variance for Shannon entropy calculation from the section.
- **Field:** process.parent.macho.sections.virtual_size
 - **Type:** long
 - **Description:** Mach-O Section List virtual size. This is always the same as `physical\_size`.

Field Set: process.parent.macho

- **Field:** process.parent.macho.symhash
 - **Type:** keyword
 - **Example:** d3ccf195b62a9279c3c19af1080497ec
 - **Description:** A hash of the imports in a Mach-O file.

Field Set: process.parent

- **Field:** process.parent.name
- **Type:** keyword
- **Example:** ssh
- **Description:** Process name.

Field Set: process.parent.name

- **Field:** process.parent.name.text
- **Type:** match_only_text
- **Example:** ssh
- **Description:** Process name.

Field Set: process.parent.pe

- **Field:** process.parent.pe.architecture
- **Type:** keyword
- **Example:** x64
- **Description:** CPU architecture target for the file.
- **Field:** process.parent.pe.company
- **Type:** keyword
- **Example:** Microsoft Corporation
- **Description:** Internal company name of the file, provided at compile-time.
- **Field:** process.parent.pe.description
- **Type:** keyword
- **Example:** Paint
- **Description:** Internal description of the file, provided at compile-time.
- **Field:** process.parent.pe.file_version
- **Type:** keyword
- **Example:** 6.3.9600.17415
- **Description:** Process name.
- **Field:** process.parent.pe.go_import_hash
- **Type:** keyword
- **Example:** 10bddcb4cee42080f76c88d9ff964491
- **Description:** A hash of the Go language imports in a PE file.
- **Field:** process.parent.pe.go_imports
- **Type:** flattened
- **Description:** List of imported Go language element names and types.
- **Field:** process.parent.pe.go_imports_names_entropy
- **Type:** long
- **Description:** Shannon entropy calculation from the list of Go imports.
- **Field:** process.parent.pe.go_imports_names_var_entropy
- **Type:** long
- **Description:** Variance for Shannon entropy calculation from the list of Go imports.
- **Field:** process.parent.pe.go_stripped
- **Type:** boolean
- **Description:** Whether the file is a stripped or obfuscated Go executable.
- **Field:** process.parent.pe.imphash
- **Type:** keyword
- **Example:** 0c6803c4e922103c4dca5963aad36ddf
- **Description:** A hash of the imports in a PE file.
- **Field:** process.parent.pe.import_hash
- **Type:** keyword

- **Example:** d41d8cd98f00b204e9800998ecf8427e
- **Description:** A hash of the imports in a PE file.
- **Field:** process.parent.pe.imports
 - **Type:** flattened
 - **Description:** List of imported element names and types.
- **Field:** process.parent.pe.imports_names_entropy
 - **Type:** long
 - **Description:** Shannon entropy calculation from the list of imported element names and types.
- **Field:** process.parent.pe.imports_names_var_entropy
 - **Type:** long
 - **Description:** Variance for Shannon entropy calculation from the list of imported element names and types.
- **Field:** process.parent.pe.original_file_name
 - **Type:** keyword
 - **Example:** MSPAINT.EXE
 - **Description:** Internal name of the file, provided at compile-time.
- **Field:** process.parent.pe.pehash
 - **Type:** keyword
 - **Example:** 73ff189b63cd6be375a7ff25179a38d347651975
 - **Description:** A hash of the PE header and data from one or more PE sections.
- **Field:** process.parent.pe.product
 - **Type:** keyword
 - **Example:** Microsoft® Windows® Operating System
 - **Description:** Internal product name of the file, provided at compile-time.
- **Field:** process.parent.pe.sections
 - **Type:** nested
 - **Description:** Section information of the PE file.

Field Set: process.parent.pe.sections

- **Field:** process.parent.pe.sections.entropy
 - **Type:** long
 - **Description:** Shannon entropy calculation from the section.
- **Field:** process.parent.pe.sections.name
 - **Type:** keyword
 - **Description:** PE Section List name.
- **Field:** process.parent.pe.sections.physical_size
 - **Type:** long
 - **Description:** PE Section List physical size.
- **Field:** process.parent.pe.sections.var_entropy
 - **Type:** long
 - **Description:** Variance for Shannon entropy calculation from the section.
- **Field:** process.parent.pe.sections.virtual_size
 - **Type:** long
 - **Description:** PE Section List virtual size. This is always the same as `physical\_size`.

Field Set: process.parent

- **Field:** process.parent.pgjid
 - **Type:** long

- **Description:** Deprecated identifier of the group of processes the process belongs to.
- **Field:** process.parent.pid
 - **Type:** long
 - **Example:** 4242
 - **Description:** Process id.

Field Set: process.parent.real_group

- **Field:** process.parent.real_group.id
 - **Type:** keyword
 - **Description:** Unique identifier for the group on the system/platform.
- **Field:** process.parent.real_group.name
 - **Type:** keyword
 - **Description:** Name of the group.

Field Set: process.parent.real_user

- **Field:** process.parent.real_user.id
 - **Type:** keyword
 - **Example:** S-1-5-21-202424912787-2692429404-2351956786-1000
 - **Description:** Unique identifier of the user.
- **Field:** process.parent.real_user.name
 - **Type:** keyword
 - **Example:** a.einstein
 - **Description:** Short name or login of the user.

Field Set: process.parent.real_user.name

- **Field:** process.parent.real_user.name.text
 - **Type:** match_only_text
 - **Example:** a.einstein
 - **Description:** Short name or login of the user.

Field Set: process.parent.saved_group

- **Field:** process.parent.saved_group.id
 - **Type:** keyword
 - **Description:** Unique identifier for the group on the system/platform.
- **Field:** process.parent.saved_group.name
 - **Type:** keyword
 - **Description:** Name of the group.

Field Set: process.parent.saved_user

- **Field:** process.parent.saved_user.id
 - **Type:** keyword
 - **Example:** S-1-5-21-202424912787-2692429404-2351956786-1000
 - **Description:** Unique identifier of the user.
- **Field:** process.parent.saved_user.name
 - **Type:** keyword
 - **Example:** a.einstein
 - **Description:** Short name or login of the user.

Field Set: process.parent.saved_user.name

- **Field:** process.parent.saved_user.name.text
- **Type:** match_only_text
- **Example:** a.einstein
- **Description:** Short name or login of the user.

Field Set: process.parent

- **Field:** process.parent.start
- **Type:** date
- **Example:** 2016-05-23T08:05:34.853Z
- **Description:** The time the process started.

Field Set: process.parent.supplemental_groups

- **Field:** process.parent.supplemental_groups.id
- **Type:** keyword
- **Description:** Unique identifier for the group on the system/platform.
- **Field:** process.parent.supplemental_groups.name
- **Type:** keyword
- **Description:** Name of the group.

Field Set: process.parent.thread.capabilities

- **Field:** process.parent.thread.capabilities.effective
- **Type:** keyword
- **Example:** ["CAP_BPF", "CAP_SYS_ADMIN"]
- **Description:** Array of capabilities used for permission checks.
- **Field:** process.parent.thread.capabilities.permitted
- **Type:** keyword
- **Example:** ["CAP_BPF", "CAP_SYS_ADMIN"]
- **Description:** Array of capabilities a thread could assume.

Field Set: process.parent.thread

- **Field:** process.parent.thread.id
- **Type:** long
- **Example:** 4242
- **Description:** Thread ID.
- **Field:** process.parent.thread.name
- **Type:** keyword
- **Example:** thread-0
- **Description:** Thread name.

Field Set: process.parent

- **Field:** process.parent.title
- **Type:** keyword
- **Description:** Process title.

Field Set: process.parent.title

- **Field:** process.parent.title.text
- **Type:** match_only_text

- **Description:** Process title.

Field Set: process.parent

- **Field:** process.parent.tty
- **Type:** object
- **Description:** Information about the controlling TTY device.

Field Set: process.parent.tty.char_device

- **Field:** process.parent.tty.char_device.major
- **Type:** long
- **Example:** 4
- **Description:** The TTY character device's major number.
- **Field:** process.parent.tty.char_device.minor
- **Type:** long
- **Example:** 1
- **Description:** The TTY character device's minor number.

Field Set: process.parent

- **Field:** process.parent.uptime
- **Type:** long
- **Example:** 1325
- **Description:** Seconds the process has been up.

Field Set: process.parent.user

- **Field:** process.parent.user.id
- **Type:** keyword
- **Example:** S-1-5-21-202424912787-2692429404-2351956786-1000
- **Description:** Unique identifier of the user.
- **Field:** process.parent.user.name
- **Type:** keyword
- **Example:** a.einstein
- **Description:** Short name or login of the user.

Field Set: process.parent.user.name

- **Field:** process.parent.user.name.text
- **Type:** match_only_text
- **Example:** a.einstein
- **Description:** Short name or login of the user.

Field Set: process.parent

- **Field:** process.parent.vpid
- **Type:** long
- **Example:** 4242
- **Description:** Virtual process id.
- **Field:** process.parent.working_directory
- **Type:** keyword
- **Example:** /home/alice
- **Description:** The working directory of the process.

Field Set: process.parent.working_directory

- **Field:** process.parent.working_directory.text
- **Type:** match_only_text
- **Example:** /home/alice
- **Description:** The working directory of the process.

Field Set: process.pe

- **Field:** process.pe.architecture
- **Type:** keyword
- **Example:** x64
- **Description:** CPU architecture target for the file.
- **Field:** process.pe.company
- **Type:** keyword
- **Example:** Microsoft Corporation
- **Description:** Internal company name of the file, provided at compile-time.
- **Field:** process.pe.description
- **Type:** keyword
- **Example:** Paint
- **Description:** Internal description of the file, provided at compile-time.
- **Field:** process.pe.file_version
- **Type:** keyword
- **Example:** 6.3.9600.17415
- **Description:** Process name.
- **Field:** process.pe.go_import_hash
- **Type:** keyword
- **Example:** 10bddcb4cee42080f76c88d9ff964491
- **Description:** A hash of the Go language imports in a PE file.
- **Field:** process.pe.go_imports
- **Type:** flattened
- **Description:** List of imported Go language element names and types.
- **Field:** process.pe.go_imports_names_entropy
- **Type:** long
- **Description:** Shannon entropy calculation from the list of Go imports.
- **Field:** process.pe.go_imports_names_var_entropy
- **Type:** long
- **Description:** Variance for Shannon entropy calculation from the list of Go imports.
- **Field:** process.pe.go_stripped
- **Type:** boolean
- **Description:** Whether the file is a stripped or obfuscated Go executable.
- **Field:** process.pe.imphash
- **Type:** keyword
- **Example:** 0c6803c4e922103c4dca5963aad36ddf
- **Description:** A hash of the imports in a PE file.
- **Field:** process.pe.import_hash
- **Type:** keyword
- **Example:** d41d8cd98f00b204e9800998ecf8427e
- **Description:** A hash of the imports in a PE file.
- **Field:** process.pe.imports
- **Type:** flattened

- **Description:** List of imported element names and types.
- **Field:** process.pe.imports_names_entropy
 - **Type:** long
 - **Description:** Shannon entropy calculation from the list of imported element names and types.
- **Field:** process.pe.imports_names_var_entropy
 - **Type:** long
 - **Description:** Variance for Shannon entropy calculation from the list of imported element names and types.
- **Field:** process.pe.original_file_name
 - **Type:** keyword
 - **Example:** MSPAINT.EXE
 - **Description:** Internal name of the file, provided at compile-time.
- **Field:** process.pe.pehash
 - **Type:** keyword
 - **Example:** 73ff189b63cd6be375a7ff25179a38d347651975
 - **Description:** A hash of the PE header and data from one or more PE sections.
- **Field:** process.pe.product
 - **Type:** keyword
 - **Example:** Microsoft® Windows® Operating System
 - **Description:** Internal product name of the file, provided at compile-time.
- **Field:** process.pe.sections
 - **Type:** nested
 - **Description:** Section information of the PE file.

Field Set: process.pe.sections

- **Field:** process.pe.sections.entropy
 - **Type:** long
 - **Description:** Shannon entropy calculation from the section.
- **Field:** process.pe.sections.name
 - **Type:** keyword
 - **Description:** PE Section List name.
- **Field:** process.pe.sections.physical_size
 - **Type:** long
 - **Description:** PE Section List physical size.
- **Field:** process.pe.sections.var_entropy
 - **Type:** long
 - **Description:** Variance for Shannon entropy calculation from the section.
- **Field:** process.pe.sections.virtual_size
 - **Type:** long
 - **Description:** PE Section List virtual size. This is always the same as `physical\_size`.

Field Set: process

- **Field:** process.pgid
 - **Type:** long
 - **Description:** Deprecated identifier of the group of processes the process belongs to.
- **Field:** process.pid
 - **Type:** long
 - **Example:** 4242

- **Description:** Process id.

Field Set: process.previous

- **Field:** process.previous.args
 - **Type:** keyword
 - **Example:** ["/usr/bin/ssh", "-l", "user", "10.0.0.16"]
 - **Description:** Array of process arguments.
- **Field:** process.previous.args_count
 - **Type:** long
 - **Example:** 4
 - **Description:** Length of the process.args array.
- **Field:** process.previous.executable
 - **Type:** keyword
 - **Example:** /usr/bin/ssh
 - **Description:** Absolute path to the process executable.

Field Set: process.previous.executable

- **Field:** process.previous.executable.text
 - **Type:** match_only_text
 - **Example:** /usr/bin/ssh
 - **Description:** Absolute path to the process executable.

Field Set: process.real_group

- **Field:** process.real_group.id
 - **Type:** keyword
 - **Description:** Unique identifier for the group on the system/platform.
- **Field:** process.real_group.name
 - **Type:** keyword
 - **Description:** Name of the group.

Field Set: process.real_user

- **Field:** process.real_user.id
 - **Type:** keyword
 - **Example:** S-1-5-21-202424912787-2692429404-2351956786-1000
 - **Description:** Unique identifier of the user.
- **Field:** process.real_user.name
 - **Type:** keyword
 - **Example:** a.einstein
 - **Description:** Short name or login of the user.

Field Set: process.real_user.name

- **Field:** process.real_user.name.text
 - **Type:** match_only_text
 - **Example:** a.einstein
 - **Description:** Short name or login of the user.

Field Set: process.saved_group

- **Field:** process.saved_group.id
 - **Type:** keyword
 - **Description:** Unique identifier for the group on the system/platform.
- **Field:** process.saved_group.name
 - **Type:** keyword
 - **Description:** Name of the group.

Field Set: process.saved_user

- **Field:** process.saved_user.id
 - **Type:** keyword
 - **Example:** S-1-5-21-202424912787-2692429404-2351956786-1000
 - **Description:** Unique identifier of the user.
- **Field:** process.saved_user.name
 - **Type:** keyword
 - **Example:** a.einstein
 - **Description:** Short name or login of the user.

Field Set: process.saved_user.name

- **Field:** process.saved_user.name.text
 - **Type:** match_only_text
 - **Example:** a.einstein
 - **Description:** Short name or login of the user.

Field Set: process.session_leader

- **Field:** process.session_leader.args
 - **Type:** keyword
 - **Example:** ["/usr/bin/ssh", "-l", "user", "10.0.0.16"]
 - **Description:** Array of process arguments.
- **Field:** process.session_leader.args_count
 - **Type:** long
 - **Example:** 4
 - **Description:** Length of the process.args array.
- **Field:** process.session_leader.command_line
 - **Type:** wildcard
 - **Example:** /usr/bin/ssh -l user 10.0.0.16
 - **Description:** Full command line that started the process.

Field Set: process.session_leader.command_line

- **Field:** process.session_leader.command_line.text
 - **Type:** match_only_text
 - **Example:** /usr/bin/ssh -l user 10.0.0.16
 - **Description:** Full command line that started the process.

Field Set: process.session_leader

- **Field:** process.session_leader.entity_id
 - **Type:** keyword
 - **Example:** c2c455d9f99375d
 - **Description:** Unique identifier for the process.

- **Field:** process.session_leader.executable
- **Type:** keyword
- **Example:** /usr/bin/ssh
- **Description:** Absolute path to the process executable.

Field Set: process.session_leader.executable

- **Field:** process.session_leader.executable.text
- **Type:** match_only_text
- **Example:** /usr/bin/ssh
- **Description:** Absolute path to the process executable.

Field Set: process.session_leader.group

- **Field:** process.session_leader.group.id
- **Type:** keyword
- **Description:** Unique identifier for the group on the system/platform.
- **Field:** process.session_leader.group.name
- **Type:** keyword
- **Description:** Name of the group.

Field Set: process.session_leader

- **Field:** process.session_leader.interactive
- **Type:** boolean
- **Example:** True
- **Description:** Whether the process is connected to an interactive shell.
- **Field:** process.session_leader.name
- **Type:** keyword
- **Example:** ssh
- **Description:** Process name.

Field Set: process.session_leader.name

- **Field:** process.session_leader.name.text
- **Type:** match_only_text
- **Example:** ssh
- **Description:** Process name.

Field Set: process.session_leader.parent

- **Field:** process.session_leader.parent.entity_id
- **Type:** keyword
- **Example:** c2c455d9f99375d
- **Description:** Unique identifier for the process.
- **Field:** process.session_leader.parent.pid
- **Type:** long
- **Example:** 4242
- **Description:** Process id.

Field Set: process.session_leader.parent.session_leader

- **Field:** process.session_leader.parent.session_leader.entity_id
- **Type:** keyword
- **Example:** c2c455d9f99375d

- **Description:** Unique identifier for the process.
- **Field:** process.session_leader.parent.session_leader.pid
 - **Type:** long
 - **Example:** 4242
 - **Description:** Process id.
- **Field:** process.session_leader.parent.session_leader.start
 - **Type:** date
 - **Example:** 2016-05-23T08:05:34.853Z
 - **Description:** The time the process started.
- **Field:** process.session_leader.parent.session_leader.vpid
 - **Type:** long
 - **Example:** 4242
 - **Description:** Virtual process id.

Field Set: process.session_leader.parent

- **Field:** process.session_leader.parent.start
 - **Type:** date
 - **Example:** 2016-05-23T08:05:34.853Z
 - **Description:** The time the process started.
- **Field:** process.session_leader.parent.vpid
 - **Type:** long
 - **Example:** 4242
 - **Description:** Virtual process id.

Field Set: process.session_leader

- **Field:** process.session_leader.pid
 - **Type:** long
 - **Example:** 4242
 - **Description:** Process id.

Field Set: process.session_leader.real_group

- **Field:** process.session_leader.real_group.id
 - **Type:** keyword
 - **Description:** Unique identifier for the group on the system/platform.
- **Field:** process.session_leader.real_group.name
 - **Type:** keyword
 - **Description:** Name of the group.

Field Set: process.session_leader.real_user

- **Field:** process.session_leader.real_user.id
 - **Type:** keyword
 - **Example:** S-1-5-21-202424912787-2692429404-2351956786-1000
 - **Description:** Unique identifier of the user.
- **Field:** process.session_leader.real_user.name
 - **Type:** keyword
 - **Example:** a.einstein
 - **Description:** Short name or login of the user.

Field Set: process.session_leader.real_user.name

- **Field:** process.session_leader.real_user.name.text
- **Type:** match_only_text
- **Example:** a.einstein
- **Description:** Short name or login of the user.

Field Set: process.session_leader

- **Field:** process.session_leader.same_as_process
- **Type:** boolean
- **Example:** True
- **Description:** This boolean is used to identify if a leader process is the same as the top level process.

Field Set: process.session_leader.saved_group

- **Field:** process.session_leader.saved_group.id
- **Type:** keyword
- **Description:** Unique identifier for the group on the system/platform.
- **Field:** process.session_leader.saved_group.name
- **Type:** keyword
- **Description:** Name of the group.

Field Set: process.session_leader.saved_user

- **Field:** process.session_leader.saved_user.id
- **Type:** keyword
- **Example:** S-1-5-21-202424912787-2692429404-2351956786-1000
- **Description:** Unique identifier of the user.
- **Field:** process.session_leader.saved_user.name
- **Type:** keyword
- **Example:** a.einstein
- **Description:** Short name or login of the user.

Field Set: process.session_leader.saved_user.name

- **Field:** process.session_leader.saved_user.name.text
- **Type:** match_only_text
- **Example:** a.einstein
- **Description:** Short name or login of the user.

Field Set: process.session_leader

- **Field:** process.session_leader.start
- **Type:** date
- **Example:** 2016-05-23T08:05:34.853Z
- **Description:** The time the process started.

Field Set: process.session_leader.supplemental_groups

- **Field:** process.session_leader.supplemental_groups.id
- **Type:** keyword
- **Description:** Unique identifier for the group on the system/platform.

- **Field:** process.session_leader.supplemental_groups.name
- **Type:** keyword
- **Description:** Name of the group.

Field Set: process.session_leader

- **Field:** process.session_leader.tty
- **Type:** object
- **Description:** Information about the controlling TTY device.

Field Set: process.session_leader.tty.char_device

- **Field:** process.session_leader.tty.char_device.major
- **Type:** long
- **Example:** 4
- **Description:** The TTY character device's major number.
- **Field:** process.session_leader.tty.char_device.minor
- **Type:** long
- **Example:** 1
- **Description:** The TTY character device's minor number.

Field Set: process.session_leader.user

- **Field:** process.session_leader.user.id
- **Type:** keyword
- **Example:** S-1-5-21-202424912787-2692429404-2351956786-1000
- **Description:** Unique identifier of the user.
- **Field:** process.session_leader.user.name
- **Type:** keyword
- **Example:** a.einstein
- **Description:** Short name or login of the user.

Field Set: process.session_leader.user.name

- **Field:** process.session_leader.user.name.text
- **Type:** match_only_text
- **Example:** a.einstein
- **Description:** Short name or login of the user.

Field Set: process.session_leader

- **Field:** process.session_leader.vpid
- **Type:** long
- **Example:** 4242
- **Description:** Virtual process id.
- **Field:** process.session_leader.working_directory
- **Type:** keyword
- **Example:** /home/alice
- **Description:** The working directory of the process.

Field Set: process.session_leader.working_directory

- **Field:** process.session_leader.working_directory.text
- **Type:** match_only_text
- **Example:** /home/alice

- **Description:** The working directory of the process.

Field Set: process

- **Field:** process.start
- **Type:** date
- **Example:** 2016-05-23T08:05:34.853Z
- **Description:** The time the process started.

Field Set: process.supplemental_groups

- **Field:** process.supplemental_groups.id
- **Type:** keyword
- **Description:** Unique identifier for the group on the system/platform.
- **Field:** process.supplemental_groups.name
- **Type:** keyword
- **Description:** Name of the group.

Field Set: process.thread.capabilities

- **Field:** process.thread.capabilities.effective
- **Type:** keyword
- **Example:** ["CAP_BPF", "CAP_SYS_ADMIN"]
- **Description:** Array of capabilities used for permission checks.
- **Field:** process.thread.capabilities.permitted
- **Type:** keyword
- **Example:** ["CAP_BPF", "CAP_SYS_ADMIN"]
- **Description:** Array of capabilities a thread could assume.

Field Set: process.thread

- **Field:** process.thread.id
- **Type:** long
- **Example:** 4242
- **Description:** Thread ID.
- **Field:** process.thread.name
- **Type:** keyword
- **Example:** thread-0
- **Description:** Thread name.

Field Set: process

- **Field:** process.title
- **Type:** keyword
- **Description:** Process title.

Field Set: process.title

- **Field:** process.title.text
- **Type:** match_only_text
- **Description:** Process title.

Field Set: process

- **Field:** process.tty
- **Type:** object
- **Description:** Information about the controlling TTY device.

Field Set: process.tty.char_device

- **Field:** process.tty.char_device.major
- **Type:** long
- **Example:** 4
- **Description:** The TTY character device's major number.
- **Field:** process.tty.char_device.minor
- **Type:** long
- **Example:** 1
- **Description:** The TTY character device's minor number.

Field Set: process.tty

- **Field:** process.tty.columns
- **Type:** long
- **Example:** 80
- **Description:** The number of character columns per line. e.g terminal width
- **Field:** process.tty.rows
- **Type:** long
- **Example:** 24
- **Description:** The number of character rows in the terminal. e.g terminal height

Field Set: process

- **Field:** process.uptime
- **Type:** long
- **Example:** 1325
- **Description:** Seconds the process has been up.

Field Set: process.user

- **Field:** process.user.id
- **Type:** keyword
- **Example:** S-1-5-21-202424912787-2692429404-2351956786-1000
- **Description:** Unique identifier of the user.
- **Field:** process.user.name
- **Type:** keyword
- **Example:** a.einstein
- **Description:** Short name or login of the user.

Field Set: process.user.name

- **Field:** process.user.name.text
- **Type:** match_only_text
- **Example:** a.einstein
- **Description:** Short name or login of the user.

Field Set: process

- **Field:** process.vpid
- **Type:** long

- **Example:** 4242
- **Description:** Virtual process id.
- **Field:** process.working_directory
 - **Type:** keyword
 - **Example:** /home/alice
 - **Description:** The working directory of the process.

Field Set: process.working_directory

- **Field:** process.working_directory.text
 - **Type:** match_only_text
 - **Example:** /home/alice
 - **Description:** The working directory of the process.

Field Set: registry.data

- **Field:** registry.data.bytes
 - **Type:** keyword
 - **Example:** ZQBuAC0AVQBTAAAAZQBuAAAAA==
 - **Description:** Original bytes written with base64 encoding.
- **Field:** registry.data.strings
 - **Type:** wildcard
 - **Example:** ["C:\rta\red_ttp\bin\myapp.exe"]
 - **Description:** List of strings representing what was written to the registry.
- **Field:** registry.data.type
 - **Type:** keyword
 - **Example:** REG_SZ
 - **Description:** Standard registry type for encoding contents

Field Set: registry

- **Field:** registry.hive
 - **Type:** keyword
 - **Example:** HKLM
 - **Description:** Abbreviated name for the hive.
- **Field:** registry.key
 - **Type:** keyword
 - **Example:** SOFTWARE\Microsoft\Windows NT\CurrentVersion\Image File Execution Options\winword.exe
 - **Description:** Hive-relative path of keys.
- **Field:** registry.path
 - **Type:** keyword
 - **Example:** HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Image File Execution Options\winword.exe\Debugger
 - **Description:** Full path, including hive, key and value
- **Field:** registry.value
 - **Type:** keyword
 - **Example:** Debugger
 - **Description:** Name of the value written.

Field Set: related

- **Field:** related.hash
 - **Type:** keyword
 - **Description:** All the hashes seen on your event.
- **Field:** related.hosts
 - **Type:** keyword
 - **Description:** All the host identifiers seen on your event.
- **Field:** related.ip
 - **Type:** ip
 - **Description:** All of the IPs seen on your event.
- **Field:** related.user
 - **Type:** keyword
 - **Description:** All the user names or other user identifiers seen on the event.

Field Set: rule

- **Field:** rule.author
 - **Type:** keyword
 - **Example:** ["Star-Lord"]
 - **Description:** Rule author
- **Field:** rule.category
 - **Type:** keyword
 - **Example:** Attempted Information Leak
 - **Description:** Rule category
- **Field:** rule.description
 - **Type:** keyword
 - **Example:** Block requests to public DNS over HTTPS / TLS protocols
 - **Description:** Rule description
- **Field:** rule.id
 - **Type:** keyword
 - **Example:** 101
 - **Description:** Rule ID
- **Field:** rule.license
 - **Type:** keyword
 - **Example:** Apache 2.0
 - **Description:** Rule license
- **Field:** rule.name
 - **Type:** keyword
 - **Example:** BLOCK_DNS_over_TLS
 - **Description:** Rule name
- **Field:** rule.reference
 - **Type:** keyword
 - **Example:** https://en.wikipedia.org/wiki/DNS_over_TLS
 - **Description:** Rule reference URL
- **Field:** rule.ruleset
 - **Type:** keyword
 - **Example:** Standard_Protocol_Filters
 - **Description:** Rule ruleset
- **Field:** rule.uuid
 - **Type:** keyword
 - **Example:** 1100110011
 - **Description:** Rule UUID

- **Field:** rule.version
- **Type:** keyword
- **Example:** 1.1
- **Description:** Rule version

Field Set: server

- **Field:** server.address
- **Type:** keyword
- **Description:** Server network address.

Field Set: server.as

- **Field:** server.as.number
- **Type:** long
- **Example:** 15169
- **Description:** Unique number allocated to the autonomous system.

Field Set: server.as.organization

- **Field:** server.as.organization.name
- **Type:** keyword
- **Example:** Google LLC
- **Description:** Organization name.

Field Set: server.as.organization.name

- **Field:** server.as.organization.name.text
- **Type:** match_only_text
- **Example:** Google LLC
- **Description:** Organization name.

Field Set: server

- **Field:** server.bytes
- **Type:** long
- **Example:** 184
- **Description:** Bytes sent from the server to the client.
- **Field:** server.domain
- **Type:** keyword
- **Example:** foo.example.com
- **Description:** The domain name of the server.

Field Set: server.geo

- **Field:** server.geo.city_name
- **Type:** keyword
- **Example:** Montreal
- **Description:** City name.
- **Field:** server.geo.continent_code
- **Type:** keyword
- **Description:** Continent code.
- **Field:** server.geo.continent_name
- **Type:** keyword
- **Example:** North America

- **Description:** Name of the continent.
- **Field:** server.geo.country_iso_code
 - **Type:** keyword
 - **Example:** CA
 - **Description:** Country ISO code.
- **Field:** server.geo.country_name
 - **Type:** keyword
 - **Example:** Canada
 - **Description:** Country name.
- **Field:** server.geo.location
 - **Type:** geo_point
 - **Example:** { "lon": -73.614830, "lat": 45.505918 }
 - **Description:** Longitude and latitude.
- **Field:** server.geo.name
 - **Type:** keyword
 - **Example:** boston-dc
 - **Description:** User-defined description of a location.
- **Field:** server.geo.postal_code
 - **Type:** keyword
 - **Example:** 94040
 - **Description:** Postal code.
- **Field:** server.geo.region_iso_code
 - **Type:** keyword
 - **Example:** CA-QC
 - **Description:** Region ISO code.
- **Field:** server.geo.region_name
 - **Type:** keyword
 - **Example:** Quebec
 - **Description:** Region name.
- **Field:** server.geo.timezone
 - **Type:** keyword
 - **Example:** America/Argentina/Buenos_Aires
 - **Description:** Time zone.

Field Set: server

- **Field:** server.ip
 - **Type:** ip
 - **Description:** IP address of the server.
- **Field:** server.mac
 - **Type:** keyword
 - **Example:** 00-00-5E-00-53-23
 - **Description:** MAC address of the server.

Field Set: server.nat

- **Field:** server.nat.ip
 - **Type:** ip
 - **Description:** Server NAT ip
- **Field:** server.nat.port
 - **Type:** long

- **Description:** Server NAT port

Field Set: server

- **Field:** server.packets
 - **Type:** long
 - **Example:** 12
 - **Description:** Packets sent from the server to the client.
- **Field:** server.port
 - **Type:** long
 - **Description:** Port of the server.
- **Field:** server.registered_domain
 - **Type:** keyword
 - **Example:** example.com
 - **Description:** The highest registered server domain, stripped of the subdomain.
- **Field:** server.subdomain
 - **Type:** keyword
 - **Example:** east
 - **Description:** The subdomain of the domain.
- **Field:** server.top_level_domain
 - **Type:** keyword
 - **Example:** co.uk
 - **Description:** The effective top level domain (com, org, net, co.uk).

Field Set: server.user

- **Field:** server.user.domain
 - **Type:** keyword
 - **Description:** Name of the directory the user is a member of.
- **Field:** server.user.email
 - **Type:** keyword
 - **Description:** User email address.
- **Field:** server.user.full_name
 - **Type:** keyword
 - **Example:** Albert Einstein
 - **Description:** User's full name, if available.

Field Set: server.user.full_name

- **Field:** server.user.full_name.text
 - **Type:** match_only_text
 - **Example:** Albert Einstein
 - **Description:** User's full name, if available.

Field Set: server.user.group

- **Field:** server.user.group.domain
 - **Type:** keyword
 - **Description:** Name of the directory the group is a member of.
- **Field:** server.user.group.id
 - **Type:** keyword
 - **Description:** Unique identifier for the group on the system/platform.

- **Field:** server.user.group.name
- **Type:** keyword
- **Description:** Name of the group.

Field Set: server.user

- **Field:** server.user.hash
- **Type:** keyword
- **Description:** Unique user hash to correlate information for a user in anonymized form.
- **Field:** server.user.id
- **Type:** keyword
- **Example:** S-1-5-21-202424912787-2692429404-2351956786-1000
- **Description:** Unique identifier of the user.
- **Field:** server.user.name
- **Type:** keyword
- **Example:** a.einstein
- **Description:** Short name or login of the user.

Field Set: server.user.name

- **Field:** server.user.name.text
- **Type:** match_only_text
- **Example:** a.einstein
- **Description:** Short name or login of the user.

Field Set: server.user

- **Field:** server.user.roles
- **Type:** keyword
- **Example:** ["kibana_admin", "reporting_user"]
- **Description:** Array of user roles at the time of the event.

Field Set: service

- **Field:** service.address
- **Type:** keyword
- **Example:** 172.26.0.2:5432
- **Description:** Address of this service.
- **Field:** service.environment
- **Type:** keyword
- **Example:** production
- **Description:** Environment of the service.
- **Field:** service.ephemeral_id
- **Type:** keyword
- **Example:** 8a4f500f
- **Description:** Ephemeral identifier of this service.
- **Field:** service.id
- **Type:** keyword
- **Example:** d37e5ebfe0ae6c4972dbe9f0174a1637bb8247f6
- **Description:** Unique identifier of the running service.
- **Field:** service.name
- **Type:** keyword
- **Example:** elasticsearch-metrics
- **Description:** Name of the service.

Field Set: service.node

- **Field:** service.node.name
 - **Type:** keyword
 - **Example:** instance-0000000016
 - **Description:** Name of the service node.
- **Field:** service.node.role
 - **Type:** keyword
 - **Example:** background_tasks
 - **Description:** Deprecated role (singular) of the service node.
- **Field:** service.node.roles
 - **Type:** keyword
 - **Example:** ["ui", "background_tasks"]
 - **Description:** Roles of the service node.

Field Set: service.origin

- **Field:** service.origin.address
 - **Type:** keyword
 - **Example:** 172.26.0.2:5432
 - **Description:** Address of this service.
- **Field:** service.origin.environment
 - **Type:** keyword
 - **Example:** production
 - **Description:** Environment of the service.
- **Field:** service.origin.ephemeral_id
 - **Type:** keyword
 - **Example:** 8a4f500f
 - **Description:** Ephemeral identifier of this service.
- **Field:** service.origin.id
 - **Type:** keyword
 - **Example:** d37e5ebfe0ae6c4972dbe9f0174a1637bb8247f6
 - **Description:** Unique identifier of the running service.
- **Field:** service.origin.name
 - **Type:** keyword
 - **Example:** elasticsearch-metrics
 - **Description:** Name of the service.

Field Set: service.origin.node

- **Field:** service.origin.node.name
 - **Type:** keyword
 - **Example:** instance-0000000016
 - **Description:** Name of the service node.
- **Field:** service.origin.node.role
 - **Type:** keyword
 - **Example:** background_tasks
 - **Description:** Deprecated role (singular) of the service node.
- **Field:** service.origin.node.roles
 - **Type:** keyword
 - **Example:** ["ui", "background_tasks"]
 - **Description:** Roles of the service node.

Field Set: service.origin

- **Field:** service.origin.state
 - **Type:** keyword
 - **Description:** Current state of the service.
- **Field:** service.origin.type
 - **Type:** keyword
 - **Example:** elasticsearch
 - **Description:** The type of the service.
- **Field:** service.origin.version
 - **Type:** keyword
 - **Example:** 3.2.4
 - **Description:** Version of the service.

Field Set: service

- **Field:** service.state
 - **Type:** keyword
 - **Description:** Current state of the service.

Field Set: service.target

- **Field:** service.target.address
 - **Type:** keyword
 - **Example:** 172.26.0.2:5432
 - **Description:** Address of this service.
- **Field:** service.target.environment
 - **Type:** keyword
 - **Example:** production
 - **Description:** Environment of the service.
- **Field:** service.target.ephemeral_id
 - **Type:** keyword
 - **Example:** 8a4f500f
 - **Description:** Ephemeral identifier of this service.
- **Field:** service.target.id
 - **Type:** keyword
 - **Example:** d37e5ebfe0ae6c4972dbe9f0174a1637bb8247f6
 - **Description:** Unique identifier of the running service.
- **Field:** service.target.name
 - **Type:** keyword
 - **Example:** elasticsearch-metrics
 - **Description:** Name of the service.

Field Set: service.target.node

- **Field:** service.target.node.name
 - **Type:** keyword
 - **Example:** instance-0000000016
 - **Description:** Name of the service node.
- **Field:** service.target.node.role
 - **Type:** keyword
 - **Example:** background_tasks
 - **Description:** Deprecated role (singular) of the service node.

- **Field:** service.target.node.roles
- **Type:** keyword
- **Example:** ["ui", "background_tasks"]
- **Description:** Roles of the service node.

Field Set: service.target

- **Field:** service.target.state
- **Type:** keyword
- **Description:** Current state of the service.
- **Field:** service.target.type
- **Type:** keyword
- **Example:** elasticsearch
- **Description:** The type of the service.
- **Field:** service.target.version
- **Type:** keyword
- **Example:** 3.2.4
- **Description:** Version of the service.

Field Set: service

- **Field:** service.type
- **Type:** keyword
- **Example:** elasticsearch
- **Description:** The type of the service.
- **Field:** service.version
- **Type:** keyword
- **Example:** 3.2.4
- **Description:** Version of the service.

Field Set: source

- **Field:** source.address
- **Type:** keyword
- **Description:** Source network address.

Field Set: source.as

- **Field:** source.as.number
- **Type:** long
- **Example:** 15169
- **Description:** Unique number allocated to the autonomous system.

Field Set: source.as.organization

- **Field:** source.as.organization.name
- **Type:** keyword
- **Example:** Google LLC
- **Description:** Organization name.

Field Set: source.as.organization.name

- **Field:** source.as.organization.name.text
- **Type:** match_only_text
- **Example:** Google LLC

- **Description:** Organization name.

Field Set: source

- **Field:** source.bytes
 - **Type:** long
 - **Example:** 184
 - **Description:** Bytes sent from the source to the destination.
- **Field:** source.domain
 - **Type:** keyword
 - **Example:** foo.example.com
 - **Description:** The domain name of the source.

Field Set: source.geo

- **Field:** source.geo.city_name
 - **Type:** keyword
 - **Example:** Montreal
 - **Description:** City name.
- **Field:** source.geo.continent_code
 - **Type:** keyword
 - **Description:** Continent code.
- **Field:** source.geo.continent_name
 - **Type:** keyword
 - **Example:** North America
 - **Description:** Name of the continent.
- **Field:** source.geo.country_iso_code
 - **Type:** keyword
 - **Example:** CA
 - **Description:** Country ISO code.
- **Field:** source.geo.country_name
 - **Type:** keyword
 - **Example:** Canada
 - **Description:** Country name.
- **Field:** source.geo.location
 - **Type:** geo_point
 - **Example:** { "lon": -73.614830, "lat": 45.505918 }
 - **Description:** Longitude and latitude.
- **Field:** source.geo.name
 - **Type:** keyword
 - **Example:** boston-dc
 - **Description:** User-defined description of a location.
- **Field:** source.geo.postal_code
 - **Type:** keyword
 - **Example:** 94040
 - **Description:** Postal code.
- **Field:** source.geo.region_iso_code
 - **Type:** keyword
 - **Example:** CA-QC
 - **Description:** Region ISO code.

- **Field:** source.geo.region_name
 - **Type:** keyword
 - **Example:** Quebec
 - **Description:** Region name.
- **Field:** source.geo.timezone
 - **Type:** keyword
 - **Example:** America/Argentina/Buenos_Aires
 - **Description:** Time zone.

Field Set: source

- **Field:** source.ip
 - **Type:** ip
 - **Description:** IP address of the source.
- **Field:** source.mac
 - **Type:** keyword
 - **Example:** 00-00-5E-00-53-23
 - **Description:** MAC address of the source.

Field Set: source.nat

- **Field:** source.nat.ip
 - **Type:** ip
 - **Description:** Source NAT ip
- **Field:** source.nat.port
 - **Type:** long
 - **Description:** Source NAT port

Field Set: source

- **Field:** source.packets
 - **Type:** long
 - **Example:** 12
 - **Description:** Packets sent from the source to the destination.
- **Field:** source.port
 - **Type:** long
 - **Description:** Port of the source.
- **Field:** source.registered_domain
 - **Type:** keyword
 - **Example:** example.com
 - **Description:** The highest registered source domain, stripped of the subdomain.
- **Field:** source.subdomain
 - **Type:** keyword
 - **Example:** east
 - **Description:** The subdomain of the domain.
- **Field:** source.top_level_domain
 - **Type:** keyword
 - **Example:** co.uk
 - **Description:** The effective top level domain (com, org, net, co.uk).

Field Set: source.user

- **Field:** source.user.domain
- **Type:** keyword
- **Description:** Name of the directory the user is a member of.
- **Field:** source.user.email
- **Type:** keyword
- **Description:** User email address.
- **Field:** source.user.full_name
- **Type:** keyword
- **Example:** Albert Einstein
- **Description:** User's full name, if available.

Field Set: source.user.full_name

- **Field:** source.user.full_name.text
- **Type:** match_only_text
- **Example:** Albert Einstein
- **Description:** User's full name, if available.

Field Set: source.user.group

- **Field:** source.user.group.domain
- **Type:** keyword
- **Description:** Name of the directory the group is a member of.
- **Field:** source.user.group.id
- **Type:** keyword
- **Description:** Unique identifier for the group on the system/platform.
- **Field:** source.user.group.name
- **Type:** keyword
- **Description:** Name of the group.

Field Set: source.user

- **Field:** source.user.hash
- **Type:** keyword
- **Description:** Unique user hash to correlate information for a user in anonymized form.
- **Field:** source.user.id
- **Type:** keyword
- **Example:** S-1-5-21-202424912787-2692429404-2351956786-1000
- **Description:** Unique identifier of the user.
- **Field:** source.user.name
- **Type:** keyword
- **Example:** a.einstein
- **Description:** Short name or login of the user.

Field Set: source.user.name

- **Field:** source.user.name.text
- **Type:** match_only_text
- **Example:** a.einstein
- **Description:** Short name or login of the user.

Field Set: source.user

- **Field:** source.user.roles
- **Type:** keyword
- **Example:** ["kibana_admin", "reporting_user"]
- **Description:** Array of user roles at the time of the event.

Field Set: span

- **Field:** span.id
- **Type:** keyword
- **Example:** 3ff9a8981b7ccd5a
- **Description:** Unique identifier of the span within the scope of its trace.

Field Set: threat

- **Field:** threat.enrichments
- **Type:** nested
- **Description:** List of objects containing indicators enriching the event.

Field Set: threat.enrichments

- **Field:** threat.enrichments.indicator
- **Type:** object
- **Description:** Object containing indicators enriching the event.

Field Set: threat.enrichments.indicator.as

- **Field:** threat.enrichments.indicator.as.number
- **Type:** long
- **Example:** 15169
- **Description:** Unique number allocated to the autonomous system.

Field Set: threat.enrichments.indicator.as.organization

- **Field:** threat.enrichments.indicator.as.organization.name
- **Type:** keyword
- **Example:** Google LLC
- **Description:** Organization name.

Field Set: threat.enrichments.indicator.as.organization.name

- **Field:** threat.enrichments.indicator.as.organization.name.text
- **Type:** match_only_text
- **Example:** Google LLC
- **Description:** Organization name.

Field Set: threat.enrichments.indicator

- **Field:** threat.enrichments.indicator.confidence
- **Type:** keyword
- **Example:** Medium
- **Description:** Indicator confidence rating
- **Field:** threat.enrichments.indicator.description
- **Type:** keyword
- **Example:** IP x.x.x.x was observed delivering the Angler EK.
- **Description:** Indicator description

Field Set: threat.enrichments.indicator.email

- **Field:** threat.enrichments.indicator.email.address
- **Type:** keyword
- **Example:** phish@example.com
- **Description:** Indicator email address

Field Set: threat.enrichments.indicator.file

- **Field:** threat.enrichments.indicator.file.accessed
- **Type:** date
- **Description:** Last time the file was accessed.
- **Field:** threat.enrichments.indicator.file.attributes
- **Type:** keyword
- **Example:** ["readonly", "system"]
- **Description:** Array of file attributes.

Field Set: threat.enrichments.indicator.file.code_signature

- **Field:** threat.enrichments.indicator.file.code_signature.digest_algorithm
- **Type:** keyword
- **Example:** sha256
- **Description:** Hashing algorithm used to sign the process.
- **Field:** threat.enrichments.indicator.file.code_signature.exists
- **Type:** boolean
- **Example:** true
- **Description:** Boolean to capture if a signature is present.
- **Field:** threat.enrichments.indicator.file.code_signature.flags
- **Type:** keyword
- **Example:** 570522385
- **Description:** Code signing flags of the process
- **Field:** threat.enrichments.indicator.file.code_signature.signing_id
- **Type:** keyword
- **Example:** com.apple.xpc.proxy
- **Description:** The identifier used to sign the process.
- **Field:** threat.enrichments.indicator.file.code_signature.status
- **Type:** keyword
- **Example:** ERROR_UNTRUSTED_ROOT
- **Description:** Additional information about the certificate status.
- **Field:** threat.enrichments.indicator.file.code_signature.subject_name
- **Type:** keyword
- **Example:** Microsoft Corporation
- **Description:** Subject name of the code signer
- **Field:** threat.enrichments.indicator.file.code_signature.team_id
- **Type:** keyword
- **Example:** EQHXZ8M8AV
- **Description:** The team identifier used to sign the process.
- **Field:** threat.enrichments.indicator.file.code_signature.timestamp
- **Type:** date
- **Example:** 2021-01-01T12:10:30Z
- **Description:** When the signature was generated and signed.

- **Field:** threat.enrichments.indicator.file.code_signature.trusted
 - **Type:** boolean
 - **Example:** true
 - **Description:** Stores the trust status of the certificate chain.
- **Field:** threat.enrichments.indicator.file.code_signature.valid
 - **Type:** boolean
 - **Example:** true
 - **Description:** Boolean to capture if the digital signature is verified against the binary content.

Field Set: threat.enrichments.indicator.file

- **Field:** threat.enrichments.indicator.file.created
 - **Type:** date
 - **Description:** File creation time.
- **Field:** threat.enrichments.indicator.file.ctime
 - **Type:** date
 - **Description:** Last time the file attributes or metadata changed.
- **Field:** threat.enrichments.indicator.file.device
 - **Type:** keyword
 - **Example:** sda
 - **Description:** Device that is the source of the file.
- **Field:** threat.enrichments.indicator.file.directory
 - **Type:** keyword
 - **Example:** /home/alice
 - **Description:** Directory where the file is located.
- **Field:** threat.enrichments.indicator.file.drive_letter
 - **Type:** keyword
 - **Example:** C
 - **Description:** Drive letter where the file is located.

Field Set: threat.enrichments.indicator.file.elf

- **Field:** threat.enrichments.indicator.file.elf.architecture
 - **Type:** keyword
 - **Example:** x86-64
 - **Description:** Machine architecture of the ELF file.
- **Field:** threat.enrichments.indicator.file.elf.byte_order
 - **Type:** keyword
 - **Example:** Little Endian
 - **Description:** Byte sequence of ELF file.
- **Field:** threat.enrichments.indicator.file.elf.cpu_type
 - **Type:** keyword
 - **Example:** Intel
 - **Description:** CPU type of the ELF file.
- **Field:** threat.enrichments.indicator.file.elf.creation_date
 - **Type:** date
 - **Description:** Build or compile date.
- **Field:** threat.enrichments.indicator.file.elf.exports
 - **Type:** flattened
 - **Description:** List of exported element names and types.
- **Field:** threat.enrichments.indicator.file.elf.go_import_hash
 - **Type:** keyword

- **Example:** 10bddcb4cee42080f76c88d9ff964491
- **Description:** A hash of the Go language imports in an ELF file.
- **Field:** threat.enrichments.indicator.file.elf.go_imports
 - **Type:** flattened
 - **Description:** List of imported Go language element names and types.
- **Field:** threat.enrichments.indicator.file.elf.go_imports_names_entropy
 - **Type:** long
 - **Description:** Shannon entropy calculation from the list of Go imports.
- **Field:** threat.enrichments.indicator.file.elf.go_imports_names_var_entropy
 - **Type:** long
 - **Description:** Variance for Shannon entropy calculation from the list of Go imports.
- **Field:** threat.enrichments.indicator.file.elf.go_stripped
 - **Type:** boolean
 - **Description:** Whether the file is a stripped or obfuscated Go executable.

Field Set: threat.enrichments.indicator.file.elf.header

- **Field:** threat.enrichments.indicator.file.elf.header.abi_version
 - **Type:** keyword
 - **Description:** Version of the ELF Application Binary Interface (ABI).
- **Field:** threat.enrichments.indicator.file.elf.header.class
 - **Type:** keyword
 - **Description:** Header class of the ELF file.
- **Field:** threat.enrichments.indicator.file.elf.header.data
 - **Type:** keyword
 - **Description:** Data table of the ELF header.
- **Field:** threat.enrichments.indicator.file.elf.header.entrypoint
 - **Type:** long
 - **Description:** Header entrypoint of the ELF file.
- **Field:** threat.enrichments.indicator.file.elf.header.object_version
 - **Type:** keyword
 - **Description:** "0x1" for original ELF files.
- **Field:** threat.enrichments.indicator.file.elf.header.os_abi
 - **Type:** keyword
 - **Description:** Application Binary Interface (ABI) of the Linux OS.
- **Field:** threat.enrichments.indicator.file.elf.header.type
 - **Type:** keyword
 - **Description:** Header type of the ELF file.
- **Field:** threat.enrichments.indicator.file.elf.header.version
 - **Type:** keyword
 - **Description:** Version of the ELF header.

Field Set: threat.enrichments.indicator.file.elf

- **Field:** threat.enrichments.indicator.file.elf.import_hash
 - **Type:** keyword
 - **Example:** d41d8cd98f00b204e9800998ecf8427e
 - **Description:** A hash of the imports in an ELF file.
- **Field:** threat.enrichments.indicator.file.elf.imports
 - **Type:** flattened

- **Description:** List of imported element names and types.
- **Field:** threat.enrichments.indicator.file.elf.imports_names_entropy
 - **Type:** long
 - **Description:** Shannon entropy calculation from the list of imported element names and types.
- **Field:** threat.enrichments.indicator.file.elf.imports_names_var_entropy
 - **Type:** long
 - **Description:** Variance for Shannon entropy calculation from the list of imported element names and types.
- **Field:** threat.enrichments.indicator.file.elf.sections
 - **Type:** nested
 - **Description:** Section information of the ELF file.

Field Set: threat.enrichments.indicator.file.elf.sections

- **Field:** threat.enrichments.indicator.file.elf.sections.chi2
 - **Type:** long
 - **Description:** Chi-square probability distribution of the section.
- **Field:** threat.enrichments.indicator.file.elf.sections.entropy
 - **Type:** long
 - **Description:** Shannon entropy calculation from the section.
- **Field:** threat.enrichments.indicator.file.elf.sections.flags
 - **Type:** keyword
 - **Description:** ELF Section List flags.
- **Field:** threat.enrichments.indicator.file.elf.sections.name
 - **Type:** keyword
 - **Description:** ELF Section List name.
- **Field:** threat.enrichments.indicator.file.elf.sections.physical_offset
 - **Type:** keyword
 - **Description:** ELF Section List offset.
- **Field:** threat.enrichments.indicator.file.elf.sections.physical_size
 - **Type:** long
 - **Description:** ELF Section List physical size.
- **Field:** threat.enrichments.indicator.file.elf.sections.type
 - **Type:** keyword
 - **Description:** ELF Section List type.
- **Field:** threat.enrichments.indicator.file.elf.sections.var_entropy
 - **Type:** long
 - **Description:** Variance for Shannon entropy calculation from the section.
- **Field:** threat.enrichments.indicator.file.elf.sections.virtual_address
 - **Type:** long
 - **Description:** ELF Section List virtual address.
- **Field:** threat.enrichments.indicator.file.elf.sections.virtual_size
 - **Type:** long
 - **Description:** ELF Section List virtual size.

Field Set: threat.enrichments.indicator.file.elf

- **Field:** threat.enrichments.indicator.file.elf.segments
 - **Type:** nested
 - **Description:** ELF object segment list.

Field Set: threat.enrichments.indicator.file.elf.segments

- **Field:** threat.enrichments.indicator.file.elf.segments.sections
 - **Type:** keyword
 - **Description:** ELF object segment sections.
- **Field:** threat.enrichments.indicator.file.elf.segments.type
 - **Type:** keyword
 - **Description:** ELF object segment type.

Field Set: threat.enrichments.indicator.file.elf

- **Field:** threat.enrichments.indicator.file.elf.shared_libraries
 - **Type:** keyword
 - **Description:** List of shared libraries used by this ELF object.
- **Field:** threat.enrichments.indicator.file.elf.telfhash
 - **Type:** keyword
 - **Description:** telfhash hash for ELF file.

Field Set: threat.enrichments.indicator.file

- **Field:** threat.enrichments.indicator.file.extension
 - **Type:** keyword
 - **Example:** png
 - **Description:** File extension, excluding the leading dot.
- **Field:** threat.enrichments.indicator.file.fork_name
 - **Type:** keyword
 - **Example:** Zone.Identifier
 - **Description:** A fork is additional data associated with a filesystem object.
- **Field:** threat.enrichments.indicator.file.gid
 - **Type:** keyword
 - **Example:** 1001
 - **Description:** Primary group ID (GID) of the file.
- **Field:** threat.enrichments.indicator.file.group
 - **Type:** keyword
 - **Example:** alice
 - **Description:** Primary group name of the file.

Field Set: threat.enrichments.indicator.file.hash

- **Field:** threat.enrichments.indicator.file.hash.cdhash
 - **Type:** keyword
 - **Example:** 3783b4052fd474dbe30676b45c329e7a6d44acd9
 - **Description:** The Code Directory (CD) hash of an executable.
- **Field:** threat.enrichments.indicator.file.hash.md5
 - **Type:** keyword
 - **Description:** MD5 hash.
- **Field:** threat.enrichments.indicator.file.hash.sha1
 - **Type:** keyword
 - **Description:** SHA1 hash.
- **Field:** threat.enrichments.indicator.file.hash.sha256
 - **Type:** keyword
 - **Description:** SHA256 hash.

- **Field:** threat.enrichments.indicator.file.hash.sha384
 - **Type:** keyword
 - **Description:** SHA384 hash.
- **Field:** threat.enrichments.indicator.file.hash.sha512
 - **Type:** keyword
 - **Description:** SHA512 hash.
- **Field:** threat.enrichments.indicator.file.hash.ssdeep
 - **Type:** keyword
 - **Description:** SSDEEP hash.
- **Field:** threat.enrichments.indicator.file.hash.tlsh
 - **Type:** keyword
 - **Description:** TLSH hash.

Field Set: threat.enrichments.indicator.file

- **Field:** threat.enrichments.indicator.file.inode
 - **Type:** keyword
 - **Example:** 256383
 - **Description:** Inode representing the file in the filesystem.
- **Field:** threat.enrichments.indicator.file.mime_type
 - **Type:** keyword
 - **Description:** Media type of file, document, or arrangement of bytes.
- **Field:** threat.enrichments.indicator.file.mode
 - **Type:** keyword
 - **Example:** 0640
 - **Description:** Mode of the file in octal representation.
- **Field:** threat.enrichments.indicator.file.mtime
 - **Type:** date
 - **Description:** Last time the file content was modified.
- **Field:** threat.enrichments.indicator.file.name
 - **Type:** keyword
 - **Example:** example.png
 - **Description:** Name of the file including the extension, without the directory.
- **Field:** threat.enrichments.indicator.file.owner
 - **Type:** keyword
 - **Example:** alice
 - **Description:** File owner's username.
- **Field:** threat.enrichments.indicator.file.path
 - **Type:** keyword
 - **Example:** /home/alice/example.png
 - **Description:** Full path to the file, including the file name.

Field Set: threat.enrichments.indicator.file.path

- **Field:** threat.enrichments.indicator.file.path.text
 - **Type:** match_only_text
 - **Example:** /home/alice/example.png
 - **Description:** Full path to the file, including the file name.

Field Set: threat.enrichments.indicator.file.pe

- **Field:** threat.enrichments.indicator.file.pe.architecture
 - **Type:** keyword
 - **Example:** x64
 - **Description:** CPU architecture target for the file.
- **Field:** threat.enrichments.indicator.file.pe.company
 - **Type:** keyword
 - **Example:** Microsoft Corporation
 - **Description:** Internal company name of the file, provided at compile-time.
- **Field:** threat.enrichments.indicator.file.pe.description
 - **Type:** keyword
 - **Example:** Paint
 - **Description:** Internal description of the file, provided at compile-time.
- **Field:** threat.enrichments.indicator.file.pe.file_version
 - **Type:** keyword
 - **Example:** 6.3.9600.17415
 - **Description:** Process name.
- **Field:** threat.enrichments.indicator.file.pe.go_import_hash
 - **Type:** keyword
 - **Example:** 10bddcb4cee42080f76c88d9ff964491
 - **Description:** A hash of the Go language imports in a PE file.
- **Field:** threat.enrichments.indicator.file.pe.go_imports
 - **Type:** flattened
 - **Description:** List of imported Go language element names and types.
- **Field:** threat.enrichments.indicator.file.pe.go_imports_names_entropy
 - **Type:** long
 - **Description:** Shannon entropy calculation from the list of Go imports.
- **Field:** threat.enrichments.indicator.file.pe.go_imports_names_var_entropy
 - **Type:** long
 - **Description:** Variance for Shannon entropy calculation from the list of Go imports.
- **Field:** threat.enrichments.indicator.file.pe.go_stripped
 - **Type:** boolean
 - **Description:** Whether the file is a stripped or obfuscated Go executable.
- **Field:** threat.enrichments.indicator.file.pe.imphash
 - **Type:** keyword
 - **Example:** 0c6803c4e922103c4dca5963aad36ddf
 - **Description:** A hash of the imports in a PE file.
- **Field:** threat.enrichments.indicator.file.pe.import_hash
 - **Type:** keyword
 - **Example:** d41d8cd98f00b204e9800998ecf8427e
 - **Description:** A hash of the imports in a PE file.
- **Field:** threat.enrichments.indicator.file.pe.imports
 - **Type:** flattened
 - **Description:** List of imported element names and types.
- **Field:** threat.enrichments.indicator.file.pe.imports_names_entropy
 - **Type:** long
 - **Description:** Shannon entropy calculation from the list of imported element names and types.
- **Field:** threat.enrichments.indicator.file.pe.imports_names_var_entropy
 - **Type:** long
 - **Description:** Variance for Shannon entropy calculation from the list of imported element names and types.

- **Field:** threat.enrichments.indicator.file.pe.original_file_name
 - **Type:** keyword
 - **Example:** MSPAINT.EXE
 - **Description:** Internal name of the file, provided at compile-time.
- **Field:** threat.enrichments.indicator.file.pe.pehash
 - **Type:** keyword
 - **Example:** 73ff189b63cd6be375a7ff25179a38d347651975
 - **Description:** A hash of the PE header and data from one or more PE sections.
- **Field:** threat.enrichments.indicator.file.pe.product
 - **Type:** keyword
 - **Example:** Microsoft® Windows® Operating System
 - **Description:** Internal product name of the file, provided at compile-time.
- **Field:** threat.enrichments.indicator.file.pe.sections
 - **Type:** nested
 - **Description:** Section information of the PE file.

Field Set: threat.enrichments.indicator.file.pe.sections

- **Field:** threat.enrichments.indicator.file.pe.sections.entropy
 - **Type:** long
 - **Description:** Shannon entropy calculation from the section.
- **Field:** threat.enrichments.indicator.file.pe.sections.name
 - **Type:** keyword
 - **Description:** PE Section List name.
- **Field:** threat.enrichments.indicator.file.pe.sections.physical_size
 - **Type:** long
 - **Description:** PE Section List physical size.
- **Field:** threat.enrichments.indicator.file.pe.sections.var_entropy
 - **Type:** long
 - **Description:** Variance for Shannon entropy calculation from the section.
- **Field:** threat.enrichments.indicator.file.pe.sections.virtual_size
 - **Type:** long
 - **Description:** PE Section List virtual size. This is always the same as `physical\_size`.

Field Set: threat.enrichments.indicator.file

- **Field:** threat.enrichments.indicator.file.size
 - **Type:** long
 - **Example:** 16384
 - **Description:** File size in bytes.
- **Field:** threat.enrichments.indicator.file.target_path
 - **Type:** keyword
 - **Description:** Target path for symlinks.

Field Set: threat.enrichments.indicator.file.target_path

- **Field:** threat.enrichments.indicator.file.target_path.text
 - **Type:** match_only_text
 - **Description:** Target path for symlinks.

Field Set: threat.enrichments.indicator.file

- **Field:** threat.enrichments.indicator.file.type
- **Type:** keyword
- **Example:** file
- **Description:** File type (file, dir, or symlink).
- **Field:** threat.enrichments.indicator.file.uid
- **Type:** keyword
- **Example:** 1001
- **Description:** The user ID (UID) or security identifier (SID) of the file owner.

Field Set: threat.enrichments.indicator.file.x509

- **Field:** threat.enrichments.indicator.file.x509.alternative_names
- **Type:** keyword
- **Example:** *.elastic.co
- **Description:** List of subject alternative names (SAN).

Field Set: threat.enrichments.indicator.file.x509.issuer

- **Field:** threat.enrichments.indicator.file.x509.issuer.common_name
- **Type:** keyword
- **Example:** Example SHA2 High Assurance Server CA
- **Description:** List of common name (CN) of issuing certificate authority.
- **Field:** threat.enrichments.indicator.file.x509.issuer.country
- **Type:** keyword
- **Example:** US
- **Description:** List of country \(\C\) codes
- **Field:** threat.enrichments.indicator.file.x509.issuer.distinguished_name
- **Type:** keyword
- **Example:** C=US, O=Example Inc, OU=www.example.com, CN=Example SHA2 High Assurance Server CA
- **Description:** Distinguished name (DN) of issuing certificate authority.
- **Field:** threat.enrichments.indicator.file.x509.issuer.locality
- **Type:** keyword
- **Example:** Mountain View
- **Description:** List of locality names (L)
- **Field:** threat.enrichments.indicator.file.x509.issuer.organization
- **Type:** keyword
- **Example:** Example Inc
- **Description:** List of organizations (O) of issuing certificate authority.
- **Field:** threat.enrichments.indicator.file.x509.issuer.organizational_unit
- **Type:** keyword
- **Example:** www.example.com
- **Description:** List of organizational units (OU) of issuing certificate authority.
- **Field:** threat.enrichments.indicator.file.x509.issuer.state_or_province
- **Type:** keyword
- **Example:** California
- **Description:** List of state or province names (ST, S, or P)

Field Set: threat.enrichments.indicator.file.x509

- **Field:** threat.enrichments.indicator.file.x509.not_after
- **Type:** date
- **Example:** 2020-07-16T03:15:39Z

- **Description:** Time at which the certificate is no longer considered valid.
- **Field:** threat.enrichments.indicator.file.x509.not_before
 - **Type:** date
 - **Example:** 2019-08-16T01:40:25Z
 - **Description:** Time at which the certificate is first considered valid.
- **Field:** threat.enrichments.indicator.file.x509.public_key_algorithm
 - **Type:** keyword
 - **Example:** RSA
 - **Description:** Algorithm used to generate the public key.
- **Field:** threat.enrichments.indicator.file.x509.public_key_curve
 - **Type:** keyword
 - **Example:** nistp521
 - **Description:** The curve used by the elliptic curve public key algorithm. This is algorithm specific.
- **Field:** threat.enrichments.indicator.file.x509.public_key_exponent
 - **Type:** long
 - **Example:** 65537
 - **Description:** Exponent used to derive the public key. This is algorithm specific.
- **Field:** threat.enrichments.indicator.file.x509.public_key_size
 - **Type:** long
 - **Example:** 2048
 - **Description:** The size of the public key space in bits.
- **Field:** threat.enrichments.indicator.file.x509.serial_number
 - **Type:** keyword
 - **Example:** 55FBB9C7DEBF09809D12CCAA
 - **Description:** Unique serial number issued by the certificate authority.
- **Field:** threat.enrichments.indicator.file.x509.signature_algorithm
 - **Type:** keyword
 - **Example:** SHA256-RSA
 - **Description:** Identifier for certificate signature algorithm.

Field Set: threat.enrichments.indicator.file.x509.subject

- **Field:** threat.enrichments.indicator.file.x509.subject.common_name
 - **Type:** keyword
 - **Example:** shared.global.example.net
 - **Description:** List of common names (CN) of subject.
- **Field:** threat.enrichments.indicator.file.x509.subject.country
 - **Type:** keyword
 - **Example:** US
 - **Description:** List of country \(\C\) code
- **Field:** threat.enrichments.indicator.file.x509.subject.distinguished_name
 - **Type:** keyword
 - **Example:** C=US, ST=California, L=San Francisco, O=Example, Inc., CN=shared.global.example.net
 - **Description:** Distinguished name (DN) of the certificate subject entity.
- **Field:** threat.enrichments.indicator.file.x509.subject.locality
 - **Type:** keyword
 - **Example:** San Francisco
 - **Description:** List of locality names (L)

- **Field:** threat.enrichments.indicator.file.x509.subject.organization
- **Type:** keyword
- **Example:** Example, Inc.
- **Description:** List of organizations (O) of subject.
- **Field:** threat.enrichments.indicator.file.x509.subject.organizational_unit
- **Type:** keyword
- **Description:** List of organizational units (OU) of subject.
- **Field:** threat.enrichments.indicator.file.x509.subject.state_or_province
- **Type:** keyword
- **Example:** California
- **Description:** List of state or province names (ST, S, or P)

Field Set: threat.enrichments.indicator.file.x509

- **Field:** threat.enrichments.indicator.file.x509.version_number
- **Type:** keyword
- **Example:** 3
- **Description:** Version of x509 format.

Field Set: threat.enrichments.indicator

- **Field:** threat.enrichments.indicator.first_seen
- **Type:** date
- **Example:** 2020-11-05T17:25:47.000Z
- **Description:** Date/time indicator was first reported.

Field Set: threat.enrichments.indicator.geo

- **Field:** threat.enrichments.indicator.geo.city_name
- **Type:** keyword
- **Example:** Montreal
- **Description:** City name.
- **Field:** threat.enrichments.indicator.geo.continent_code
- **Type:** keyword
- **Description:** Continent code.
- **Field:** threat.enrichments.indicator.geo.continent_name
- **Type:** keyword
- **Example:** North America
- **Description:** Name of the continent.
- **Field:** threat.enrichments.indicator.geo.country_iso_code
- **Type:** keyword
- **Example:** CA
- **Description:** Country ISO code.
- **Field:** threat.enrichments.indicator.geo.country_name
- **Type:** keyword
- **Example:** Canada
- **Description:** Country name.
- **Field:** threat.enrichments.indicator.geo.location
- **Type:** geo_point
- **Example:** { "lon": -73.614830, "lat": 45.505918 }
- **Description:** Longitude and latitude.
- **Field:** threat.enrichments.indicator.geo.name
- **Type:** keyword

- **Example:** boston-dc
- **Description:** User-defined description of a location.
- **Field:** threat.enrichments.indicator.geo.postal_code
 - **Type:** keyword
 - **Example:** 94040
 - **Description:** Postal code.
- **Field:** threat.enrichments.indicator.geo.region_iso_code
 - **Type:** keyword
 - **Example:** CA-QC
 - **Description:** Region ISO code.
- **Field:** threat.enrichments.indicator.geo.region_name
 - **Type:** keyword
 - **Example:** Quebec
 - **Description:** Region name.
- **Field:** threat.enrichments.indicator.geo.timezone
 - **Type:** keyword
 - **Example:** America/Argentina/Buenos_Aires
 - **Description:** Time zone.

Field Set: threat.enrichments.indicator

- **Field:** threat.enrichments.indicator.ip
 - **Type:** ip
 - **Example:** 1.2.3.4
 - **Description:** Indicator IP address
- **Field:** threat.enrichments.indicator.last_seen
 - **Type:** date
 - **Example:** 2020-11-05T17:25:47.000Z
 - **Description:** Date/time indicator was last reported.

Field Set: threat.enrichments.indicator.marking

- **Field:** threat.enrichments.indicator.marking.tlp
 - **Type:** keyword
 - **Example:** CLEAR
 - **Description:** Indicator TLP marking
- **Field:** threat.enrichments.indicator.marking.tlp_version
 - **Type:** keyword
 - **Example:** 2.0
 - **Description:** Indicator TLP version

Field Set: threat.enrichments.indicator

- **Field:** threat.enrichments.indicator.modified_at
 - **Type:** date
 - **Example:** 2020-11-05T17:25:47.000Z
 - **Description:** Date/time indicator was last updated.
- **Field:** threat.enrichments.indicator.name
 - **Type:** keyword
 - **Example:** 5.2.75.227
 - **Description:** Indicator display name

- **Field:** threat.enrichments.indicator.port
 - **Type:** long
 - **Example:** 443
 - **Description:** Indicator port
- **Field:** threat.enrichments.indicator.provider
 - **Type:** keyword
 - **Example:** lrz_urlhaus
 - **Description:** Indicator provider
- **Field:** threat.enrichments.indicator.reference
 - **Type:** keyword
 - **Example:** https://system.example.com/indicator/0001234
 - **Description:** Indicator reference URL

Field Set: threat.enrichments.indicator.registry.data

- **Field:** threat.enrichments.indicator.registry.data.bytes
 - **Type:** keyword
 - **Example:** ZQBuAC0AVQBTAAAAZQBuAAAAA=
 - **Description:** Original bytes written with base64 encoding.
- **Field:** threat.enrichments.indicator.registry.data.strings
 - **Type:** wildcard
 - **Example:** ["C:\rta\red_ttp\bin\myapp.exe"]
 - **Description:** List of strings representing what was written to the registry.
- **Field:** threat.enrichments.indicator.registry.data.type
 - **Type:** keyword
 - **Example:** REG_SZ
 - **Description:** Standard registry type for encoding contents

Field Set: threat.enrichments.indicator.registry

- **Field:** threat.enrichments.indicator.registry.hive
 - **Type:** keyword
 - **Example:** HKLM
 - **Description:** Abbreviated name for the hive.
- **Field:** threat.enrichments.indicator.registry.key
 - **Type:** keyword
 - **Example:** SOFTWARE\Microsoft\Windows NT\CurrentVersion\Image File Execution Options\winword.exe
 - **Description:** Hive-relative path of keys.
- **Field:** threat.enrichments.indicator.registry.path
 - **Type:** keyword
 - **Example:** HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Image File Execution Options\winword.exe\Debugger
 - **Description:** Full path, including hive, key and value
- **Field:** threat.enrichments.indicator.registry.value
 - **Type:** keyword
 - **Example:** Debugger
 - **Description:** Name of the value written.

Field Set: threat.enrichments.indicator

- **Field:** threat.enrichments.indicator.scanner_stats
 - **Type:** long

- **Example:** 4
- **Description:** Scanner statistics
- **Field:** threat.enrichments.indicator.sightings
 - **Type:** long
 - **Example:** 20
 - **Description:** Number of times indicator observed
- **Field:** threat.enrichments.indicator.type
 - **Type:** keyword
 - **Example:** ipv4-addr
 - **Description:** Type of indicator

Field Set: threat.enrichments.indicator.url

- **Field:** threat.enrichments.indicator.url.domain
 - **Type:** keyword
 - **Example:** www.elastic.co
 - **Description:** Domain of the url.
- **Field:** threat.enrichments.indicator.url.extension
 - **Type:** keyword
 - **Example:** png
 - **Description:** File extension from the request url, excluding the leading dot.
- **Field:** threat.enrichments.indicator.url.fragment
 - **Type:** keyword
 - **Description:** Portion of the url after the `#`.
- **Field:** threat.enrichments.indicator.url.full
 - **Type:** wildcard
 - **Example:** https://www.elastic.co:443/search?q=elasticsearch#top
 - **Description:** Full unparsed URL.

Field Set: threat.enrichments.indicator.url.full

- **Field:** threat.enrichments.indicator.url.full.text
 - **Type:** match_only_text
 - **Example:** https://www.elastic.co:443/search?q=elasticsearch#top
 - **Description:** Full unparsed URL.

Field Set: threat.enrichments.indicator.url

- **Field:** threat.enrichments.indicator.url.original
 - **Type:** wildcard
 - **Example:** https://www.elastic.co:443/search?q=elasticsearch#top or /search?q=elasticsearch
 - **Description:** Unmodified original url as seen in the event source.

Field Set: threat.enrichments.indicator.url.original

- **Field:** threat.enrichments.indicator.url.original.text
 - **Type:** match_only_text
 - **Example:** https://www.elastic.co:443/search?q=elasticsearch#top or /search?q=elasticsearch
 - **Description:** Unmodified original url as seen in the event source.

Field Set: threat.enrichments.indicator.url

- **Field:** threat.enrichments.indicator.url.password
 - **Type:** keyword
 - **Description:** Password of the request.
- **Field:** threat.enrichments.indicator.url.path
 - **Type:** wildcard
 - **Description:** Path of the request, such as "/search".
- **Field:** threat.enrichments.indicator.url.port
 - **Type:** long
 - **Example:** 443
 - **Description:** Port of the request, such as 443.
- **Field:** threat.enrichments.indicator.url.query
 - **Type:** keyword
 - **Description:** Query string of the request.
- **Field:** threat.enrichments.indicator.url.registered_domain
 - **Type:** keyword
 - **Example:** example.com
 - **Description:** The highest registered url domain, stripped of the subdomain.
- **Field:** threat.enrichments.indicator.url.scheme
 - **Type:** keyword
 - **Example:** https
 - **Description:** Scheme of the url.
- **Field:** threat.enrichments.indicator.url.subdomain
 - **Type:** keyword
 - **Example:** east
 - **Description:** The subdomain of the domain.
- **Field:** threat.enrichments.indicator.url.top_level_domain
 - **Type:** keyword
 - **Example:** co.uk
 - **Description:** The effective top level domain (com, org, net, co.uk).
- **Field:** threat.enrichments.indicator.url.username
 - **Type:** keyword
 - **Description:** Username of the request.

Field Set: threat.enrichments.indicator.x509

- **Field:** threat.enrichments.indicator.x509.alternative_names
 - **Type:** keyword
 - **Example:** *.elastic.co
 - **Description:** List of subject alternative names (SAN).

Field Set: threat.enrichments.indicator.x509.issuer

- **Field:** threat.enrichments.indicator.x509.issuer.common_name
 - **Type:** keyword
 - **Example:** Example SHA2 High Assurance Server CA
 - **Description:** List of common name (CN) of issuing certificate authority.
- **Field:** threat.enrichments.indicator.x509.issuer.country
 - **Type:** keyword
 - **Example:** US
 - **Description:** List of country \(\C\) codes
- **Field:** threat.enrichments.indicator.x509.issuer.distinguished_name
 - **Type:** keyword

- **Example:** C=US, O=Example Inc, OU=www.example.com, CN=Example SHA2 High Assurance Server CA
- **Description:** Distinguished name (DN) of issuing certificate authority.
- **Field:** threat.enrichments.indicator.x509.issuer.locality
 - **Type:** keyword
 - **Example:** Mountain View
 - **Description:** List of locality names (L)
- **Field:** threat.enrichments.indicator.x509.issuer.organization
 - **Type:** keyword
 - **Example:** Example Inc
 - **Description:** List of organizations (O) of issuing certificate authority.
- **Field:** threat.enrichments.indicator.x509.issuer.organizational_unit
 - **Type:** keyword
 - **Example:** www.example.com
 - **Description:** List of organizational units (OU) of issuing certificate authority.
- **Field:** threat.enrichments.indicator.x509.issuer.state_or_province
 - **Type:** keyword
 - **Example:** California
 - **Description:** List of state or province names (ST, S, or P)

Field Set: threat.enrichments.indicator.x509

- **Field:** threat.enrichments.indicator.x509.not_after
 - **Type:** date
 - **Example:** 2020-07-16T03:15:39Z
 - **Description:** Time at which the certificate is no longer considered valid.
- **Field:** threat.enrichments.indicator.x509.not_before
 - **Type:** date
 - **Example:** 2019-08-16T01:40:25Z
 - **Description:** Time at which the certificate is first considered valid.
- **Field:** threat.enrichments.indicator.x509.public_key_algorithm
 - **Type:** keyword
 - **Example:** RSA
 - **Description:** Algorithm used to generate the public key.
- **Field:** threat.enrichments.indicator.x509.public_key_curve
 - **Type:** keyword
 - **Example:** nistp521
 - **Description:** The curve used by the elliptic curve public key algorithm. This is algorithm specific.
- **Field:** threat.enrichments.indicator.x509.public_key_exponent
 - **Type:** long
 - **Example:** 65537
 - **Description:** Exponent used to derive the public key. This is algorithm specific.
- **Field:** threat.enrichments.indicator.x509.public_key_size
 - **Type:** long
 - **Example:** 2048
 - **Description:** The size of the public key space in bits.
- **Field:** threat.enrichments.indicator.x509.serial_number
 - **Type:** keyword
 - **Example:** 55FBB9C7DEBF09809D12CCAA
 - **Description:** Unique serial number issued by the certificate authority.

- **Field:** threat.enrichments.indicator.x509.signature_algorithm
- **Type:** keyword
- **Example:** SHA256-RSA
- **Description:** Identifier for certificate signature algorithm.

Field Set: threat.enrichments.indicator.x509.subject

- **Field:** threat.enrichments.indicator.x509.subject.common_name
- **Type:** keyword
- **Example:** shared.global.example.net
- **Description:** List of common names (CN) of subject.
- **Field:** threat.enrichments.indicator.x509.subject.country
- **Type:** keyword
- **Example:** US
- **Description:** List of country \(\C\) code
- **Field:** threat.enrichments.indicator.x509.subject.distinguished_name
- **Type:** keyword
- **Example:** C=US, ST=California, L=San Francisco, O=Example, Inc., CN=shared.global.example.net
- **Description:** Distinguished name (DN) of the certificate subject entity.
- **Field:** threat.enrichments.indicator.x509.subject.locality
- **Type:** keyword
- **Example:** San Francisco
- **Description:** List of locality names (L)
- **Field:** threat.enrichments.indicator.x509.subject.organization
- **Type:** keyword
- **Example:** Example, Inc.
- **Description:** List of organizations (O) of subject.
- **Field:** threat.enrichments.indicator.x509.subject.organizational_unit
- **Type:** keyword
- **Description:** List of organizational units (OU) of subject.
- **Field:** threat.enrichments.indicator.x509.subject.state_or_province
- **Type:** keyword
- **Example:** California
- **Description:** List of state or province names (ST, S, or P)

Field Set: threat.enrichments.indicator.x509

- **Field:** threat.enrichments.indicator.x509.version_number
- **Type:** keyword
- **Example:** 3
- **Description:** Version of x509 format.

Field Set: threat.enrichments.matched

- **Field:** threat.enrichments.matched.atomic
- **Type:** keyword
- **Example:** bad-domain.com
- **Description:** Matched indicator value
- **Field:** threat.enrichments.matched.field
- **Type:** keyword
- **Example:** file.hash.sha256
- **Description:** Matched indicator field

- **Field:** threat.enrichments.matched.id
 - **Type:** keyword
 - **Example:** ff93aee5-86a1-4a61-b0e6-0cdc313d01b5
 - **Description:** Matched indicator identifier
- **Field:** threat.enrichments.matched.index
 - **Type:** keyword
 - **Example:** filebeat-8.0.0-2021.05.23-000011
 - **Description:** Matched indicator index
- **Field:** threat.enrichments.matched.occurred
 - **Type:** date
 - **Example:** 2021-10-05T17:00:58.326Z
 - **Description:** Date of match
- **Field:** threat.enrichments.matched.type
 - **Type:** keyword
 - **Example:** indicator_match_rule
 - **Description:** Type of indicator match

Field Set: threat.feed

- **Field:** threat.feed.dashboard_id
 - **Type:** keyword
 - **Example:** 5ba16340-72e6-11eb-a3e3-b3cc7c78a70f
 - **Description:** Feed dashboard ID.
- **Field:** threat.feed.description
 - **Type:** keyword
 - **Example:** Threat feed from the AlienVault Open Threat eXchange network.
 - **Description:** Description of the threat feed.
- **Field:** threat.feed.name
 - **Type:** keyword
 - **Example:** AlienVault OTX
 - **Description:** Name of the threat feed.
- **Field:** threat.feed.reference
 - **Type:** keyword
 - **Example:** <https://otx.alienvault.com>
 - **Description:** Reference for the threat feed.

Field Set: threat

- **Field:** threat.framework
 - **Type:** keyword
 - **Example:** MITRE ATT&CK;
 - **Description:** Threat classification framework.

Field Set: threat.group

- **Field:** threat.group.alias
 - **Type:** keyword
 - **Example:** ["Magecart Group 6"]
 - **Description:** Alias of the group.
- **Field:** threat.group.id
 - **Type:** keyword
 - **Example:** G0037
 - **Description:** ID of the group.

- **Field:** threat.group.name
 - **Type:** keyword
 - **Example:** FIN6
 - **Description:** Name of the group.
- **Field:** threat.group.reference
 - **Type:** keyword
 - **Example:** <https://attack.mitre.org/groups/G0037/>
 - **Description:** Reference URL of the group.

Field Set: threat.indicator.as

- **Field:** threat.indicator.as.number
 - **Type:** long
 - **Example:** 15169
 - **Description:** Unique number allocated to the autonomous system.

Field Set: threat.indicator.as.organization

- **Field:** threat.indicator.as.organization.name
 - **Type:** keyword
 - **Example:** Google LLC
 - **Description:** Organization name.

Field Set: threat.indicator.as.organization.name

- **Field:** threat.indicator.as.organization.name.text
 - **Type:** match_only_text
 - **Example:** Google LLC
 - **Description:** Organization name.

Field Set: threat.indicator

- **Field:** threat.indicator.confidence
 - **Type:** keyword
 - **Example:** Medium
 - **Description:** Indicator confidence rating
- **Field:** threat.indicator.description
 - **Type:** keyword
 - **Example:** IP x.x.x.x was observed delivering the Angler EK.
 - **Description:** Indicator description

Field Set: threat.indicator.email

- **Field:** threat.indicator.email.address
 - **Type:** keyword
 - **Example:** phish@example.com
 - **Description:** Indicator email address

Field Set: threat.indicator.file

- **Field:** threat.indicator.file.accessed
 - **Type:** date
 - **Description:** Last time the file was accessed.
- **Field:** threat.indicator.file.attributes
 - **Type:** keyword

- **Example:** ["readonly", "system"]
- **Description:** Array of file attributes.

Field Set: threat.indicator.file.code_signature

- **Field:** threat.indicator.file.code_signature.digest_algorithm
 - **Type:** keyword
 - **Example:** sha256
 - **Description:** Hashing algorithm used to sign the process.
- **Field:** threat.indicator.file.code_signature.exists
 - **Type:** boolean
 - **Example:** true
 - **Description:** Boolean to capture if a signature is present.
- **Field:** threat.indicator.file.code_signature.flags
 - **Type:** keyword
 - **Example:** 570522385
 - **Description:** Code signing flags of the process
- **Field:** threat.indicator.file.code_signature.signing_id
 - **Type:** keyword
 - **Example:** com.apple.xpc.proxy
 - **Description:** The identifier used to sign the process.
- **Field:** threat.indicator.file.code_signature.status
 - **Type:** keyword
 - **Example:** ERROR_UNTRUSTED_ROOT
 - **Description:** Additional information about the certificate status.
- **Field:** threat.indicator.file.code_signature.subject_name
 - **Type:** keyword
 - **Example:** Microsoft Corporation
 - **Description:** Subject name of the code signer
- **Field:** threat.indicator.file.code_signature.team_id
 - **Type:** keyword
 - **Example:** EQHXZ8M8AV
 - **Description:** The team identifier used to sign the process.
- **Field:** threat.indicator.file.code_signature.timestamp
 - **Type:** date
 - **Example:** 2021-01-01T12:10:30Z
 - **Description:** When the signature was generated and signed.
- **Field:** threat.indicator.file.code_signature.trusted
 - **Type:** boolean
 - **Example:** true
 - **Description:** Stores the trust status of the certificate chain.
- **Field:** threat.indicator.file.code_signature.valid
 - **Type:** boolean
 - **Example:** true
 - **Description:** Boolean to capture if the digital signature is verified against the binary content.

Field Set: threat.indicator.file

- **Field:** threat.indicator.file.created
 - **Type:** date
 - **Description:** File creation time.

- **Field:** threat.indicator.file.ctime
 - **Type:** date
 - **Description:** Last time the file attributes or metadata changed.
- **Field:** threat.indicator.file.device
 - **Type:** keyword
 - **Example:** sda
 - **Description:** Device that is the source of the file.
- **Field:** threat.indicator.file.directory
 - **Type:** keyword
 - **Example:** /home/alice
 - **Description:** Directory where the file is located.
- **Field:** threat.indicator.file.drive_letter
 - **Type:** keyword
 - **Example:** C
 - **Description:** Drive letter where the file is located.

Field Set: threat.indicator.file.elf

- **Field:** threat.indicator.file.elf.architecture
 - **Type:** keyword
 - **Example:** x86-64
 - **Description:** Machine architecture of the ELF file.
- **Field:** threat.indicator.file.elf.byte_order
 - **Type:** keyword
 - **Example:** Little Endian
 - **Description:** Byte sequence of ELF file.
- **Field:** threat.indicator.file.elf.cpu_type
 - **Type:** keyword
 - **Example:** Intel
 - **Description:** CPU type of the ELF file.
- **Field:** threat.indicator.file.elf.creation_date
 - **Type:** date
 - **Description:** Build or compile date.
- **Field:** threat.indicator.file.elf.exports
 - **Type:** flattened
 - **Description:** List of exported element names and types.
- **Field:** threat.indicator.file.elf.go_import_hash
 - **Type:** keyword
 - **Example:** 10bddcb4cee42080f76c88d9ff964491
 - **Description:** A hash of the Go language imports in an ELF file.
- **Field:** threat.indicator.file.elf.go_imports
 - **Type:** flattened
 - **Description:** List of imported Go language element names and types.
- **Field:** threat.indicator.file.elf.go_imports_names_entropy
 - **Type:** long
 - **Description:** Shannon entropy calculation from the list of Go imports.
- **Field:** threat.indicator.file.elf.go_imports_names_var_entropy
 - **Type:** long
 - **Description:** Variance for Shannon entropy calculation from the list of Go imports.
- **Field:** threat.indicator.file.elf.go_stripped
 - **Type:** boolean

- **Description:** Whether the file is a stripped or obfuscated Go executable.

Field Set: threat.indicator.file.elf.header

- **Field:** threat.indicator.file.elf.header.abi_version
 - **Type:** keyword
 - **Description:** Version of the ELF Application Binary Interface (ABI).
- **Field:** threat.indicator.file.elf.header.class
 - **Type:** keyword
 - **Description:** Header class of the ELF file.
- **Field:** threat.indicator.file.elf.header.data
 - **Type:** keyword
 - **Description:** Data table of the ELF header.
- **Field:** threat.indicator.file.elf.header.entrypoint
 - **Type:** long
 - **Description:** Header entrypoint of the ELF file.
- **Field:** threat.indicator.file.elf.header.object_version
 - **Type:** keyword
 - **Description:** "0x1" for original ELF files.
- **Field:** threat.indicator.file.elf.header.os_abi
 - **Type:** keyword
 - **Description:** Application Binary Interface (ABI) of the Linux OS.
- **Field:** threat.indicator.file.elf.header.type
 - **Type:** keyword
 - **Description:** Header type of the ELF file.
- **Field:** threat.indicator.file.elf.header.version
 - **Type:** keyword
 - **Description:** Version of the ELF header.

Field Set: threat.indicator.file.elf

- **Field:** threat.indicator.file.elf.import_hash
 - **Type:** keyword
 - **Example:** d41d8cd98f00b204e9800998ecf8427e
 - **Description:** A hash of the imports in an ELF file.
- **Field:** threat.indicator.file.elf.imports
 - **Type:** flattened
 - **Description:** List of imported element names and types.
- **Field:** threat.indicator.file.elf.imports_names_entropy
 - **Type:** long
 - **Description:** Shannon entropy calculation from the list of imported element names and types.
- **Field:** threat.indicator.file.elf.imports_names_var_entropy
 - **Type:** long
 - **Description:** Variance for Shannon entropy calculation from the list of imported element names and types.
- **Field:** threat.indicator.file.elf.sections
 - **Type:** nested
 - **Description:** Section information of the ELF file.

Field Set: threat.indicator.file.elf.sections

- **Field:** threat.indicator.file.elf.sections.chi2
 - **Type:** long
 - **Description:** Chi-square probability distribution of the section.
- **Field:** threat.indicator.file.elf.sections.entropy
 - **Type:** long
 - **Description:** Shannon entropy calculation from the section.
- **Field:** threat.indicator.file.elf.sections.flags
 - **Type:** keyword
 - **Description:** ELF Section List flags.
- **Field:** threat.indicator.file.elf.sections.name
 - **Type:** keyword
 - **Description:** ELF Section List name.
- **Field:** threat.indicator.file.elf.sections.physical_offset
 - **Type:** keyword
 - **Description:** ELF Section List offset.
- **Field:** threat.indicator.file.elf.sections.physical_size
 - **Type:** long
 - **Description:** ELF Section List physical size.
- **Field:** threat.indicator.file.elf.sections.type
 - **Type:** keyword
 - **Description:** ELF Section List type.
- **Field:** threat.indicator.file.elf.sections.var_entropy
 - **Type:** long
 - **Description:** Variance for Shannon entropy calculation from the section.
- **Field:** threat.indicator.file.elf.sections.virtual_address
 - **Type:** long
 - **Description:** ELF Section List virtual address.
- **Field:** threat.indicator.file.elf.sections.virtual_size
 - **Type:** long
 - **Description:** ELF Section List virtual size.

Field Set: threat.indicator.file.elf

- **Field:** threat.indicator.file.elf.segments
 - **Type:** nested
 - **Description:** ELF object segment list.

Field Set: threat.indicator.file.elf.segments

- **Field:** threat.indicator.file.elf.segments.sections
 - **Type:** keyword
 - **Description:** ELF object segment sections.
- **Field:** threat.indicator.file.elf.segments.type
 - **Type:** keyword
 - **Description:** ELF object segment type.

Field Set: threat.indicator.file.elf

- **Field:** threat.indicator.file.elf.shared_libraries
 - **Type:** keyword
 - **Description:** List of shared libraries used by this ELF object.

- **Field:** threat.indicator.file.elf.telfhash
- **Type:** keyword
- **Description:** telfhash hash for ELF file.

Field Set: threat.indicator.file

- **Field:** threat.indicator.file.extension
- **Type:** keyword
- **Example:** png
- **Description:** File extension, excluding the leading dot.
- **Field:** threat.indicator.file.fork_name
- **Type:** keyword
- **Example:** Zone.Identifier
- **Description:** A fork is additional data associated with a filesystem object.
- **Field:** threat.indicator.file.gid
- **Type:** keyword
- **Example:** 1001
- **Description:** Primary group ID (GID) of the file.
- **Field:** threat.indicator.file.group
- **Type:** keyword
- **Example:** alice
- **Description:** Primary group name of the file.

Field Set: threat.indicator.file.hash

- **Field:** threat.indicator.file.hash.cdhash
- **Type:** keyword
- **Example:** 3783b4052fd474dbe30676b45c329e7a6d44acd9
- **Description:** The Code Directory (CD) hash of an executable.
- **Field:** threat.indicator.file.hash.md5
- **Type:** keyword
- **Description:** MD5 hash.
- **Field:** threat.indicator.file.hash.sha1
- **Type:** keyword
- **Description:** SHA1 hash.
- **Field:** threat.indicator.file.hash.sha256
- **Type:** keyword
- **Description:** SHA256 hash.
- **Field:** threat.indicator.file.hash.sha384
- **Type:** keyword
- **Description:** SHA384 hash.
- **Field:** threat.indicator.file.hash.sha512
- **Type:** keyword
- **Description:** SHA512 hash.
- **Field:** threat.indicator.file.hash.ssdeep
- **Type:** keyword
- **Description:** SSDEEP hash.
- **Field:** threat.indicator.file.hash.tlsh
- **Type:** keyword
- **Description:** TLSH hash.

Field Set: threat.indicator.file

- **Field:** threat.indicator.file.inode
 - **Type:** keyword
 - **Example:** 256383
 - **Description:** Inode representing the file in the filesystem.
- **Field:** threat.indicator.file.mime_type
 - **Type:** keyword
 - **Description:** Media type of file, document, or arrangement of bytes.
- **Field:** threat.indicator.file.mode
 - **Type:** keyword
 - **Example:** 0640
 - **Description:** Mode of the file in octal representation.
- **Field:** threat.indicator.file.mtime
 - **Type:** date
 - **Description:** Last time the file content was modified.
- **Field:** threat.indicator.file.name
 - **Type:** keyword
 - **Example:** example.png
 - **Description:** Name of the file including the extension, without the directory.
- **Field:** threat.indicator.file.owner
 - **Type:** keyword
 - **Example:** alice
 - **Description:** File owner's username.
- **Field:** threat.indicator.file.path
 - **Type:** keyword
 - **Example:** /home/alice/example.png
 - **Description:** Full path to the file, including the file name.

Field Set: threat.indicator.file.path

- **Field:** threat.indicator.file.path.text
 - **Type:** match_only_text
 - **Example:** /home/alice/example.png
 - **Description:** Full path to the file, including the file name.

Field Set: threat.indicator.file.pe

- **Field:** threat.indicator.file.pe.architecture
 - **Type:** keyword
 - **Example:** x64
 - **Description:** CPU architecture target for the file.
- **Field:** threat.indicator.file.pe.company
 - **Type:** keyword
 - **Example:** Microsoft Corporation
 - **Description:** Internal company name of the file, provided at compile-time.
- **Field:** threat.indicator.file.pe.description
 - **Type:** keyword
 - **Example:** Paint
 - **Description:** Internal description of the file, provided at compile-time.
- **Field:** threat.indicator.file.pe.file_version
 - **Type:** keyword

- **Example:** 6.3.9600.17415
- **Description:** Process name.
- **Field:** threat.indicator.file.pe.go_import_hash
 - **Type:** keyword
 - **Example:** 10bddcb4cee42080f76c88d9ff964491
 - **Description:** A hash of the Go language imports in a PE file.
- **Field:** threat.indicator.file.pe.go_imports
 - **Type:** flattened
 - **Description:** List of imported Go language element names and types.
- **Field:** threat.indicator.file.pe.go_imports_names_entropy
 - **Type:** long
 - **Description:** Shannon entropy calculation from the list of Go imports.
- **Field:** threat.indicator.file.pe.go_imports_names_var_entropy
 - **Type:** long
 - **Description:** Variance for Shannon entropy calculation from the list of Go imports.
- **Field:** threat.indicator.file.pe.go_stripped
 - **Type:** boolean
 - **Description:** Whether the file is a stripped or obfuscated Go executable.
- **Field:** threat.indicator.file.pe.imphash
 - **Type:** keyword
 - **Example:** 0c6803c4e922103c4dca5963aad36ddf
 - **Description:** A hash of the imports in a PE file.
- **Field:** threat.indicator.file.pe.import_hash
 - **Type:** keyword
 - **Example:** d41d8cd98f00b204e9800998ecf8427e
 - **Description:** A hash of the imports in a PE file.
- **Field:** threat.indicator.file.pe.imports
 - **Type:** flattened
 - **Description:** List of imported element names and types.
- **Field:** threat.indicator.file.pe.imports_names_entropy
 - **Type:** long
 - **Description:** Shannon entropy calculation from the list of imported element names and types.
- **Field:** threat.indicator.file.pe.imports_names_var_entropy
 - **Type:** long
 - **Description:** Variance for Shannon entropy calculation from the list of imported element names and types.
- **Field:** threat.indicator.file.pe.original_file_name
 - **Type:** keyword
 - **Example:** MSPAINT.EXE
 - **Description:** Internal name of the file, provided at compile-time.
- **Field:** threat.indicator.file.pe.pehash
 - **Type:** keyword
 - **Example:** 73ff189b63cd6be375a7ff25179a38d347651975
 - **Description:** A hash of the PE header and data from one or more PE sections.
- **Field:** threat.indicator.file.pe.product
 - **Type:** keyword
 - **Example:** Microsoft® Windows® Operating System
 - **Description:** Internal product name of the file, provided at compile-time.

- **Field:** threat.indicator.file.pe.sections
- **Type:** nested
- **Description:** Section information of the PE file.

Field Set: threat.indicator.file.pe.sections

- **Field:** threat.indicator.file.pe.sections.entropy
- **Type:** long
- **Description:** Shannon entropy calculation from the section.
- **Field:** threat.indicator.file.pe.sections.name
- **Type:** keyword
- **Description:** PE Section List name.
- **Field:** threat.indicator.file.pe.sections.physical_size
- **Type:** long
- **Description:** PE Section List physical size.
- **Field:** threat.indicator.file.pe.sections.var_entropy
- **Type:** long
- **Description:** Variance for Shannon entropy calculation from the section.
- **Field:** threat.indicator.file.pe.sections.virtual_size
- **Type:** long
- **Description:** PE Section List virtual size. This is always the same as `physical\_size`.

Field Set: threat.indicator.file

- **Field:** threat.indicator.file.size
- **Type:** long
- **Example:** 16384
- **Description:** File size in bytes.
- **Field:** threat.indicator.file.target_path
- **Type:** keyword
- **Description:** Target path for symlinks.

Field Set: threat.indicator.file.target_path

- **Field:** threat.indicator.file.target_path.text
- **Type:** match_only_text
- **Description:** Target path for symlinks.

Field Set: threat.indicator.file

- **Field:** threat.indicator.file.type
- **Type:** keyword
- **Example:** file
- **Description:** File type (file, dir, or symlink).
- **Field:** threat.indicator.file.uid
- **Type:** keyword
- **Example:** 1001
- **Description:** The user ID (UID) or security identifier (SID) of the file owner.

Field Set: threat.indicator.file.x509

- **Field:** threat.indicator.file.x509.alternative_names
- **Type:** keyword
- **Example:** *.elastic.co

- **Description:** List of subject alternative names (SAN).

Field Set: threat.indicator.file.x509.issuer

- **Field:** threat.indicator.file.x509.issuer.common_name
 - **Type:** keyword
 - **Example:** Example SHA2 High Assurance Server CA
 - **Description:** List of common name (CN) of issuing certificate authority.
- **Field:** threat.indicator.file.x509.issuer.country
 - **Type:** keyword
 - **Example:** US
 - **Description:** List of country \(\C\) codes
- **Field:** threat.indicator.file.x509.issuer.distinguished_name
 - **Type:** keyword
 - **Example:** C=US, O=Example Inc, OU=www.example.com, CN=Example SHA2 High Assurance Server CA
 - **Description:** Distinguished name (DN) of issuing certificate authority.
- **Field:** threat.indicator.file.x509.issuer.locality
 - **Type:** keyword
 - **Example:** Mountain View
 - **Description:** List of locality names (L)
- **Field:** threat.indicator.file.x509.issuer.organization
 - **Type:** keyword
 - **Example:** Example Inc
 - **Description:** List of organizations (O) of issuing certificate authority.
- **Field:** threat.indicator.file.x509.issuer.organizational_unit
 - **Type:** keyword
 - **Example:** www.example.com
 - **Description:** List of organizational units (OU) of issuing certificate authority.
- **Field:** threat.indicator.file.x509.issuer.state_or_province
 - **Type:** keyword
 - **Example:** California
 - **Description:** List of state or province names (ST, S, or P)

Field Set: threat.indicator.file.x509

- **Field:** threat.indicator.file.x509.not_after
 - **Type:** date
 - **Example:** 2020-07-16T03:15:39Z
 - **Description:** Time at which the certificate is no longer considered valid.
- **Field:** threat.indicator.file.x509.not_before
 - **Type:** date
 - **Example:** 2019-08-16T01:40:25Z
 - **Description:** Time at which the certificate is first considered valid.
- **Field:** threat.indicator.file.x509.public_key_algorithm
 - **Type:** keyword
 - **Example:** RSA
 - **Description:** Algorithm used to generate the public key.
- **Field:** threat.indicator.file.x509.public_key_curve
 - **Type:** keyword
 - **Example:** nistp521

- **Description:** The curve used by the elliptic curve public key algorithm. This is algorithm specific.
- **Field:** threat.indicator.file.x509.public_key_exponent
 - **Type:** long
 - **Example:** 65537
 - **Description:** Exponent used to derive the public key. This is algorithm specific.
- **Field:** threat.indicator.file.x509.public_key_size
 - **Type:** long
 - **Example:** 2048
 - **Description:** The size of the public key space in bits.
- **Field:** threat.indicator.file.x509.serial_number
 - **Type:** keyword
 - **Example:** 55FBB9C7DEBF09809D12CCAA
 - **Description:** Unique serial number issued by the certificate authority.
- **Field:** threat.indicator.file.x509.signature_algorithm
 - **Type:** keyword
 - **Example:** SHA256-RSA
 - **Description:** Identifier for certificate signature algorithm.

Field Set: threat.indicator.file.x509.subject

- **Field:** threat.indicator.file.x509.subject.common_name
 - **Type:** keyword
 - **Example:** shared.global.example.net
 - **Description:** List of common names (CN) of subject.
- **Field:** threat.indicator.file.x509.subject.country
 - **Type:** keyword
 - **Example:** US
 - **Description:** List of country \(\C\) code
- **Field:** threat.indicator.file.x509.subject.distinguished_name
 - **Type:** keyword
 - **Example:** C=US, ST=California, L=San Francisco, O=Example, Inc., CN=shared.global.example.net
 - **Description:** Distinguished name (DN) of the certificate subject entity.
- **Field:** threat.indicator.file.x509.subject.locality
 - **Type:** keyword
 - **Example:** San Francisco
 - **Description:** List of locality names (L)
- **Field:** threat.indicator.file.x509.subject.organization
 - **Type:** keyword
 - **Example:** Example, Inc.
 - **Description:** List of organizations (O) of subject.
- **Field:** threat.indicator.file.x509.subject.organizational_unit
 - **Type:** keyword
 - **Description:** List of organizational units (OU) of subject.
- **Field:** threat.indicator.file.x509.subject.state_or_province
 - **Type:** keyword
 - **Example:** California
 - **Description:** List of state or province names (ST, S, or P)

Field Set: threat.indicator.file.x509

- **Field:** threat.indicator.file.x509.version_number
- **Type:** keyword
- **Example:** 3
- **Description:** Version of x509 format.

Field Set: threat.indicator

- **Field:** threat.indicator.first_seen
- **Type:** date
- **Example:** 2020-11-05T17:25:47.000Z
- **Description:** Date/time indicator was first reported.

Field Set: threat.indicator.geo

- **Field:** threat.indicator.geo.city_name
- **Type:** keyword
- **Example:** Montreal
- **Description:** City name.
- **Field:** threat.indicator.geo.continent_code
- **Type:** keyword
- **Description:** Continent code.
- **Field:** threat.indicator.geo.continent_name
- **Type:** keyword
- **Example:** North America
- **Description:** Name of the continent.
- **Field:** threat.indicator.geo.country_iso_code
- **Type:** keyword
- **Example:** CA
- **Description:** Country ISO code.
- **Field:** threat.indicator.geo.country_name
- **Type:** keyword
- **Example:** Canada
- **Description:** Country name.
- **Field:** threat.indicator.geo.location
- **Type:** geo_point
- **Example:** { "lon": -73.614830, "lat": 45.505918 }
- **Description:** Longitude and latitude.
- **Field:** threat.indicator.geo.name
- **Type:** keyword
- **Example:** boston-dc
- **Description:** User-defined description of a location.
- **Field:** threat.indicator.geo.postal_code
- **Type:** keyword
- **Example:** 94040
- **Description:** Postal code.
- **Field:** threat.indicator.geo.region_iso_code
- **Type:** keyword
- **Example:** CA-QC
- **Description:** Region ISO code.
- **Field:** threat.indicator.geo.region_name
- **Type:** keyword
- **Example:** Quebec

- **Description:** Region name.
- **Field:** threat.indicator.geo.timezone
 - **Type:** keyword
 - **Example:** America/Argentina/Buenos_Aires
 - **Description:** Time zone.

Field Set: threat.indicator

- **Field:** threat.indicator.id
 - **Type:** keyword
 - **Example:** [indicator--d7008e06-ab86-415a-9803-3c81ce2d3c37]
 - **Description:** ID of the indicator
- **Field:** threat.indicator.ip
 - **Type:** ip
 - **Example:** 1.2.3.4
 - **Description:** Indicator IP address
- **Field:** threat.indicator.last_seen
 - **Type:** date
 - **Example:** 2020-11-05T17:25:47.000Z
 - **Description:** Date/time indicator was last reported.

Field Set: threat.indicator.marking

- **Field:** threat.indicator.marking.tlp
 - **Type:** keyword
 - **Example:** CLEAR
 - **Description:** Indicator TLP marking
- **Field:** threat.indicator.marking.tlp_version
 - **Type:** keyword
 - **Example:** 2.0
 - **Description:** Indicator TLP version

Field Set: threat.indicator

- **Field:** threat.indicator.modified_at
 - **Type:** date
 - **Example:** 2020-11-05T17:25:47.000Z
 - **Description:** Date/time indicator was last updated.
- **Field:** threat.indicator.name
 - **Type:** keyword
 - **Example:** 5.2.75.227
 - **Description:** Indicator display name
- **Field:** threat.indicator.port
 - **Type:** long
 - **Example:** 443
 - **Description:** Indicator port
- **Field:** threat.indicator.provider
 - **Type:** keyword
 - **Example:** lrz_urlhaus
 - **Description:** Indicator provider
- **Field:** threat.indicator.reference
 - **Type:** keyword

- **Example:** <https://system.example.com/indicator/0001234>
- **Description:** Indicator reference URL

Field Set: threat.indicator.registry.data

- **Field:** threat.indicator.registry.data.bytes
 - **Type:** keyword
 - **Example:** ZQBuAC0AVQBTAAAAZQBuAAAAA=
 - **Description:** Original bytes written with base64 encoding.
- **Field:** threat.indicator.registry.data.strings
 - **Type:** wildcard
 - **Example:** ["C:\rta\red_ttp\bin\myapp.exe"]
 - **Description:** List of strings representing what was written to the registry.
- **Field:** threat.indicator.registry.data.type
 - **Type:** keyword
 - **Example:** REG_SZ
 - **Description:** Standard registry type for encoding contents

Field Set: threat.indicator.registry

- **Field:** threat.indicator.registry.hive
 - **Type:** keyword
 - **Example:** HKLM
 - **Description:** Abbreviated name for the hive.
- **Field:** threat.indicator.registry.key
 - **Type:** keyword
 - **Example:** SOFTWARE\Microsoft\Windows NT\CurrentVersion\Image File Execution Options\winword.exe
 - **Description:** Hive-relative path of keys.
- **Field:** threat.indicator.registry.path
 - **Type:** keyword
 - **Example:** HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Image File Execution Options\winword.exe\Debugger
 - **Description:** Full path, including hive, key and value
- **Field:** threat.indicator.registry.value
 - **Type:** keyword
 - **Example:** Debugger
 - **Description:** Name of the value written.

Field Set: threat.indicator

- **Field:** threat.indicator.scanner_stats
 - **Type:** long
 - **Example:** 4
 - **Description:** Scanner statistics
- **Field:** threat.indicator.sightings
 - **Type:** long
 - **Example:** 20
 - **Description:** Number of times indicator observed
- **Field:** threat.indicator.type
 - **Type:** keyword
 - **Example:** ipv4-addr

- **Description:** Type of indicator

Field Set: threat.indicator.url

- **Field:** threat.indicator.url.domain
 - **Type:** keyword
 - **Example:** www.elastic.co
 - **Description:** Domain of the url.
- **Field:** threat.indicator.url.extension
 - **Type:** keyword
 - **Example:** png
 - **Description:** File extension from the request url, excluding the leading dot.
- **Field:** threat.indicator.url.fragment
 - **Type:** keyword
 - **Description:** Portion of the url after the `#`.
- **Field:** threat.indicator.url.full
 - **Type:** wildcard
 - **Example:** https://www.elastic.co:443/search?q=elasticsearch#top
 - **Description:** Full unparsed URL.

Field Set: threat.indicator.url.full

- **Field:** threat.indicator.url.full.text
 - **Type:** match_only_text
 - **Example:** https://www.elastic.co:443/search?q=elasticsearch#top
 - **Description:** Full unparsed URL.

Field Set: threat.indicator.url

- **Field:** threat.indicator.url.original
 - **Type:** wildcard
 - **Example:** https://www.elastic.co:443/search?q=elasticsearch#top or /search?q=elasticsearch
 - **Description:** Unmodified original url as seen in the event source.

Field Set: threat.indicator.url.original

- **Field:** threat.indicator.url.original.text
 - **Type:** match_only_text
 - **Example:** https://www.elastic.co:443/search?q=elasticsearch#top or /search?q=elasticsearch
 - **Description:** Unmodified original url as seen in the event source.

Field Set: threat.indicator.url

- **Field:** threat.indicator.url.password
 - **Type:** keyword
 - **Description:** Password of the request.
- **Field:** threat.indicator.url.path
 - **Type:** wildcard
 - **Description:** Path of the request, such as "/search".
- **Field:** threat.indicator.url.port
 - **Type:** long
 - **Example:** 443
 - **Description:** Port of the request, such as 443.

- **Field:** threat.indicator.url.query
 - **Type:** keyword
 - **Description:** Query string of the request.
- **Field:** threat.indicator.url.registered_domain
 - **Type:** keyword
 - **Example:** example.com
 - **Description:** The highest registered url domain, stripped of the subdomain.
- **Field:** threat.indicator.url.scheme
 - **Type:** keyword
 - **Example:** https
 - **Description:** Scheme of the url.
- **Field:** threat.indicator.url.subdomain
 - **Type:** keyword
 - **Example:** east
 - **Description:** The subdomain of the domain.
- **Field:** threat.indicator.url.top_level_domain
 - **Type:** keyword
 - **Example:** co.uk
 - **Description:** The effective top level domain (com, org, net, co.uk).
- **Field:** threat.indicator.url.username
 - **Type:** keyword
 - **Description:** Username of the request.

Field Set: threat.indicator.x509

- **Field:** threat.indicator.x509.alternative_names
 - **Type:** keyword
 - **Example:** *.elastic.co
 - **Description:** List of subject alternative names (SAN).

Field Set: threat.indicator.x509.issuer

- **Field:** threat.indicator.x509.issuer.common_name
 - **Type:** keyword
 - **Example:** Example SHA2 High Assurance Server CA
 - **Description:** List of common name (CN) of issuing certificate authority.
- **Field:** threat.indicator.x509.issuer.country
 - **Type:** keyword
 - **Example:** US
 - **Description:** List of country \(\C\) codes
- **Field:** threat.indicator.x509.issuer.distinguished_name
 - **Type:** keyword
 - **Example:** C=US, O=Example Inc, OU=www.example.com, CN=Example SHA2 High Assurance Server CA
 - **Description:** Distinguished name (DN) of issuing certificate authority.
- **Field:** threat.indicator.x509.issuer.locality
 - **Type:** keyword
 - **Example:** Mountain View
 - **Description:** List of locality names (L)
- **Field:** threat.indicator.x509.issuer.organization
 - **Type:** keyword
 - **Example:** Example Inc

- **Description:** List of organizations (O) of issuing certificate authority.
- **Field:** threat.indicator.x509.issuer.organizational_unit
 - **Type:** keyword
 - **Example:** www.example.com
 - **Description:** List of organizational units (OU) of issuing certificate authority.
- **Field:** threat.indicator.x509.issuer.state_or_province
 - **Type:** keyword
 - **Example:** California
 - **Description:** List of state or province names (ST, S, or P)

Field Set: threat.indicator.x509

- **Field:** threat.indicator.x509.not_after
 - **Type:** date
 - **Example:** 2020-07-16T03:15:39Z
 - **Description:** Time at which the certificate is no longer considered valid.
- **Field:** threat.indicator.x509.not_before
 - **Type:** date
 - **Example:** 2019-08-16T01:40:25Z
 - **Description:** Time at which the certificate is first considered valid.
- **Field:** threat.indicator.x509.public_key_algorithm
 - **Type:** keyword
 - **Example:** RSA
 - **Description:** Algorithm used to generate the public key.
- **Field:** threat.indicator.x509.public_key_curve
 - **Type:** keyword
 - **Example:** nistp521
 - **Description:** The curve used by the elliptic curve public key algorithm. This is algorithm specific.
- **Field:** threat.indicator.x509.public_key_exponent
 - **Type:** long
 - **Example:** 65537
 - **Description:** Exponent used to derive the public key. This is algorithm specific.
- **Field:** threat.indicator.x509.public_key_size
 - **Type:** long
 - **Example:** 2048
 - **Description:** The size of the public key space in bits.
- **Field:** threat.indicator.x509.serial_number
 - **Type:** keyword
 - **Example:** 55FBB9C7DEBF09809D12CCAA
 - **Description:** Unique serial number issued by the certificate authority.
- **Field:** threat.indicator.x509.signature_algorithm
 - **Type:** keyword
 - **Example:** SHA256-RSA
 - **Description:** Identifier for certificate signature algorithm.

Field Set: threat.indicator.x509.subject

- **Field:** threat.indicator.x509.subject.common_name
 - **Type:** keyword
 - **Example:** shared.global.example.net
 - **Description:** List of common names (CN) of subject.

- **Field:** threat.indicator.x509.subject.country
 - **Type:** keyword
 - **Example:** US
 - **Description:** List of country \(\C\) code
- **Field:** threat.indicator.x509.subject.distinguished_name
 - **Type:** keyword
 - **Example:** C=US, ST=California, L=San Francisco, O=Example, Inc., CN=shared.global.example.net
 - **Description:** Distinguished name (DN) of the certificate subject entity.
- **Field:** threat.indicator.x509.subject.locality
 - **Type:** keyword
 - **Example:** San Francisco
 - **Description:** List of locality names (L)
- **Field:** threat.indicator.x509.subject.organization
 - **Type:** keyword
 - **Example:** Example, Inc.
 - **Description:** List of organizations (O) of subject.
- **Field:** threat.indicator.x509.subject.organizational_unit
 - **Type:** keyword
 - **Description:** List of organizational units (OU) of subject.
- **Field:** threat.indicator.x509.subject.state_or_province
 - **Type:** keyword
 - **Example:** California
 - **Description:** List of state or province names (ST, S, or P)

Field Set: threat.indicator.x509

- **Field:** threat.indicator.x509.version_number
 - **Type:** keyword
 - **Example:** 3
 - **Description:** Version of x509 format.

Field Set: threat.software

- **Field:** threat.software.alias
 - **Type:** keyword
 - **Example:** ["X-Agent"]
 - **Description:** Alias of the software
- **Field:** threat.software.id
 - **Type:** keyword
 - **Example:** S0552
 - **Description:** ID of the software
- **Field:** threat.software.name
 - **Type:** keyword
 - **Example:** AdFind
 - **Description:** Name of the software.
- **Field:** threat.software.platforms
 - **Type:** keyword
 - **Example:** ["Windows"]
 - **Description:** Platforms of the software.
- **Field:** threat.software.reference
 - **Type:** keyword

- **Example:** <https://attack.mitre.org/software/S0552/>
- **Description:** Software reference URL.
- **Field:** threat.software.type
- **Type:** keyword
- **Example:** Tool
- **Description:** Software type.

Field Set: threat.tactic

- **Field:** threat.tactic.id
- **Type:** keyword
- **Example:** TA0002
- **Description:** Threat tactic id.
- **Field:** threat.tactic.name
- **Type:** keyword
- **Example:** Execution
- **Description:** Threat tactic.
- **Field:** threat.tactic.reference
- **Type:** keyword
- **Example:** <https://attack.mitre.org/tactics/TA0002/>
- **Description:** Threat tactic URL reference.

Field Set: threat.technique

- **Field:** threat.technique.id
- **Type:** keyword
- **Example:** T1059
- **Description:** Threat technique id.
- **Field:** threat.technique.name
- **Type:** keyword
- **Example:** Command and Scripting Interpreter
- **Description:** Threat technique name.

Field Set: threat.technique.name

- **Field:** threat.technique.name.text
- **Type:** match_only_text
- **Example:** Command and Scripting Interpreter
- **Description:** Threat technique name.

Field Set: threat.technique

- **Field:** threat.technique.reference
- **Type:** keyword
- **Example:** <https://attack.mitre.org/techniques/T1059/>
- **Description:** Threat technique URL reference.

Field Set: threat.technique.subtechnique

- **Field:** threat.technique.subtechnique.id
- **Type:** keyword
- **Example:** T1059.001
- **Description:** Threat subtechnique id.

- **Field:** threat.technique.subtechnique.name
- **Type:** keyword
- **Example:** PowerShell
- **Description:** Threat subtechnique name.

Field Set: threat.technique.subtechnique.name

- **Field:** threat.technique.subtechnique.name.text
- **Type:** match_only_text
- **Example:** PowerShell
- **Description:** Threat subtechnique name.

Field Set: threat.technique.subtechnique

- **Field:** threat.technique.subtechnique.reference
- **Type:** keyword
- **Example:** <https://attack.mitre.org/techniques/T1059/001/>
- **Description:** Threat subtechnique URL reference.

Field Set: tls

- **Field:** tls.cipher
- **Type:** keyword
- **Example:** TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256
- **Description:** String indicating the cipher used during the current connection.

Field Set: tls.client

- **Field:** tls.client.certificate
- **Type:** keyword
- **Example:** MII...
- **Description:** PEM-encoded stand-alone certificate offered by the client.
- **Field:** tls.client.certificate_chain
- **Type:** keyword
- **Example:** ["MII...", "MII..."]
- **Description:** Array of PEM-encoded certificates that make up the certificate chain offered by the client.

Field Set: tls.client.hash

- **Field:** tls.client.hash.md5
- **Type:** keyword
- **Example:** 0F76C7F2C55BFD7D8E8B8F4BFBF0C9EC
- **Description:** Certificate fingerprint using the MD5 digest of DER-encoded version of certificate offered by the client.
- **Field:** tls.client.hash.sha1
- **Type:** keyword
- **Example:** 9E393D93138888D288266C2D915214D1D1CCEB2A
- **Description:** Certificate fingerprint using the SHA1 digest of DER-encoded version of certificate offered by the client.
- **Field:** tls.client.hash.sha256
- **Type:** keyword
- **Example:** 0687F666A054EF17A08E2F2162EAB4CBC0D265E1D7875BE74BF3C712CA92DAF0
- **Description:** Certificate fingerprint using the SHA256 digest of DER-encoded version of

certificate offered by the client.

Field Set: **tls.client**

- **Field:** `tls.client.issuer`
 - **Type:** keyword
 - **Example:** CN=Example Root CA, OU=Infrastructure Team, DC=example, DC=com
 - **Description:** Distinguished name of subject of the issuer of the x.509 certificate presented by the client.
- **Field:** `tls.client.ja3`
 - **Type:** keyword
 - **Example:** d4e5b18d6b55c71272893221c96ba240
 - **Description:** A hash that identifies clients based on how they perform an SSL/TLS handshake.
- **Field:** `tls.client.not_after`
 - **Type:** date
 - **Example:** 2021-01-01T00:00:00.000Z
 - **Description:** Date/Time indicating when client certificate is no longer considered valid.
- **Field:** `tls.client.not_before`
 - **Type:** date
 - **Example:** 1970-01-01T00:00:00.000Z
 - **Description:** Date/Time indicating when client certificate is first considered valid.
- **Field:** `tls.client.server_name`
 - **Type:** keyword
 - **Example:** www.elastic.co
 - **Description:** Hostname the client is trying to connect to. Also called the SNI.
- **Field:** `tls.client.subject`
 - **Type:** keyword
 - **Example:** CN=myclient, OU=Documentation Team, DC=example, DC=com
 - **Description:** Distinguished name of subject of the x.509 certificate presented by the client.
- **Field:** `tls.client.supported_ciphers`
 - **Type:** keyword
 - **Example:** ["TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384", "TLS_ECDHE_ECDSA_WITH_AES_256_GCM_SHA384", "..."]
 - **Description:** Array of ciphers offered by the client during the client hello.

Field Set: **tls.client.x509**

- **Field:** `tls.client.x509.alternative_names`
 - **Type:** keyword
 - **Example:** *.elastic.co
 - **Description:** List of subject alternative names (SAN).

Field Set: **tls.client.x509.issuer**

- **Field:** `tls.client.x509.issuer.common_name`
 - **Type:** keyword
 - **Example:** Example SHA2 High Assurance Server CA
 - **Description:** List of common name (CN) of issuing certificate authority.
- **Field:** `tls.client.x509.issuer.country`
 - **Type:** keyword
 - **Example:** US
 - **Description:** List of country \(\C\) codes

- **Field:** tls.client.x509.issuer.distinguished_name
 - **Type:** keyword
 - **Example:** C=US, O=Example Inc, OU=www.example.com, CN=Example SHA2 High Assurance Server CA
 - **Description:** Distinguished name (DN) of issuing certificate authority.
- **Field:** tls.client.x509.issuer.locality
 - **Type:** keyword
 - **Example:** Mountain View
 - **Description:** List of locality names (L)
- **Field:** tls.client.x509.issuer.organization
 - **Type:** keyword
 - **Example:** Example Inc
 - **Description:** List of organizations (O) of issuing certificate authority.
- **Field:** tls.client.x509.issuer.organizational_unit
 - **Type:** keyword
 - **Example:** www.example.com
 - **Description:** List of organizational units (OU) of issuing certificate authority.
- **Field:** tls.client.x509.issuer.state_or_province
 - **Type:** keyword
 - **Example:** California
 - **Description:** List of state or province names (ST, S, or P)

Field Set: tls.client.x509

- **Field:** tls.client.x509.not_after
 - **Type:** date
 - **Example:** 2020-07-16T03:15:39Z
 - **Description:** Time at which the certificate is no longer considered valid.
- **Field:** tls.client.x509.not_before
 - **Type:** date
 - **Example:** 2019-08-16T01:40:25Z
 - **Description:** Time at which the certificate is first considered valid.
- **Field:** tls.client.x509.public_key_algorithm
 - **Type:** keyword
 - **Example:** RSA
 - **Description:** Algorithm used to generate the public key.
- **Field:** tls.client.x509.public_key_curve
 - **Type:** keyword
 - **Example:** nistp521
 - **Description:** The curve used by the elliptic curve public key algorithm. This is algorithm specific.
- **Field:** tls.client.x509.public_key_exponent
 - **Type:** long
 - **Example:** 65537
 - **Description:** Exponent used to derive the public key. This is algorithm specific.
- **Field:** tls.client.x509.public_key_size
 - **Type:** long
 - **Example:** 2048
 - **Description:** The size of the public key space in bits.
- **Field:** tls.client.x509.serial_number
 - **Type:** keyword
 - **Example:** 55FBB9C7DEBF09809D12CCAA
 - **Description:** Unique serial number issued by the certificate authority.

- **Field:** tls.client.x509.signature_algorithm
- **Type:** keyword
- **Example:** SHA256-RSA
- **Description:** Identifier for certificate signature algorithm.

Field Set: tls.client.x509.subject

- **Field:** tls.client.x509.subject.common_name
- **Type:** keyword
- **Example:** shared.global.example.net
- **Description:** List of common names (CN) of subject.
- **Field:** tls.client.x509.subject.country
- **Type:** keyword
- **Example:** US
- **Description:** List of country \(\C\) code
- **Field:** tls.client.x509.subject.distinguished_name
- **Type:** keyword
- **Example:** C=US, ST=California, L=San Francisco, O=Example, Inc., CN=shared.global.example.net
- **Description:** Distinguished name (DN) of the certificate subject entity.
- **Field:** tls.client.x509.subject.locality
- **Type:** keyword
- **Example:** San Francisco
- **Description:** List of locality names (L)
- **Field:** tls.client.x509.subject.organization
- **Type:** keyword
- **Example:** Example, Inc.
- **Description:** List of organizations (O) of subject.
- **Field:** tls.client.x509.subject.organizational_unit
- **Type:** keyword
- **Description:** List of organizational units (OU) of subject.
- **Field:** tls.client.x509.subject.state_or_province
- **Type:** keyword
- **Example:** California
- **Description:** List of state or province names (ST, S, or P)

Field Set: tls.client.x509

- **Field:** tls.client.x509.version_number
- **Type:** keyword
- **Example:** 3
- **Description:** Version of x509 format.

Field Set: tls

- **Field:** tls.curve
- **Type:** keyword
- **Example:** secp256r1
- **Description:** String indicating the curve used for the given cipher, when applicable.
- **Field:** tls.established
- **Type:** boolean
- **Description:** Boolean flag indicating if the TLS negotiation was successful and transitioned to an encrypted tunnel.

- **Field:** tls.next_protocol
- **Type:** keyword
- **Example:** http/1.1
- **Description:** String indicating the protocol being tunneled.
- **Field:** tls.resumed
- **Type:** boolean
- **Description:** Boolean flag indicating if this TLS connection was resumed from an existing TLS negotiation.

Field Set: tls.server

- **Field:** tls.server.certificate
- **Type:** keyword
- **Example:** MII...
- **Description:** PEM-encoded stand-alone certificate offered by the server.
- **Field:** tls.server.certificate_chain
- **Type:** keyword
- **Example:** ["MII...", "MII..."]
- **Description:** Array of PEM-encoded certificates that make up the certificate chain offered by the server.

Field Set: tls.server.hash

- **Field:** tls.server.hash.md5
- **Type:** keyword
- **Example:** 0F76C7F2C55BFD7D8E8B8F4BFBF0C9EC
- **Description:** Certificate fingerprint using the MD5 digest of DER-encoded version of certificate offered by the server.
- **Field:** tls.server.hash.sha1
- **Type:** keyword
- **Example:** 9E393D93138888D288266C2D915214D1D1CCEB2A
- **Description:** Certificate fingerprint using the SHA1 digest of DER-encoded version of certificate offered by the server.
- **Field:** tls.server.hash.sha256
- **Type:** keyword
- **Example:**
0687F666A054EF17A08E2F2162EAB4CBC0D265E1D7875BE74BF3C712CA92DAF0
- **Description:** Certificate fingerprint using the SHA256 digest of DER-encoded version of certificate offered by the server.

Field Set: tls.server

- **Field:** tls.server.issuer
- **Type:** keyword
- **Example:** CN=Example Root CA, OU=Infrastructure Team, DC=example, DC=com
- **Description:** Subject of the issuer of the x.509 certificate presented by the server.
- **Field:** tls.server.ja3s
- **Type:** keyword
- **Example:** 394441ab65754e2207b1e1b457b3641d
- **Description:** A hash that identifies servers based on how they perform an SSL/TLS handshake.
- **Field:** tls.server.not_after
- **Type:** date
- **Example:** 2021-01-01T00:00:00.000Z
- **Description:** Timestamp indicating when server certificate is no longer considered valid.

- **Field:** tls.server.not_before
- **Type:** date
- **Example:** 1970-01-01T00:00:00.000Z
- **Description:** Timestamp indicating when server certificate is first considered valid.
- **Field:** tls.server.subject
- **Type:** keyword
- **Example:** CN=www.example.com, OU=Infrastructure Team, DC=example, DC=com
- **Description:** Subject of the x.509 certificate presented by the server.

Field Set: tls.server.x509

- **Field:** tls.server.x509.alternative_names
- **Type:** keyword
- **Example:** *.elastic.co
- **Description:** List of subject alternative names (SAN).

Field Set: tls.server.x509.issuer

- **Field:** tls.server.x509.issuer.common_name
- **Type:** keyword
- **Example:** Example SHA2 High Assurance Server CA
- **Description:** List of common name (CN) of issuing certificate authority.
- **Field:** tls.server.x509.issuer.country
- **Type:** keyword
- **Example:** US
- **Description:** List of country \(\C\) codes
- **Field:** tls.server.x509.issuer.distinguished_name
- **Type:** keyword
- **Example:** C=US, O=Example Inc, OU=www.example.com, CN=Example SHA2 High Assurance Server CA
- **Description:** Distinguished name (DN) of issuing certificate authority.
- **Field:** tls.server.x509.issuer.locality
- **Type:** keyword
- **Example:** Mountain View
- **Description:** List of locality names (L)
- **Field:** tls.server.x509.issuer.organization
- **Type:** keyword
- **Example:** Example Inc
- **Description:** List of organizations (O) of issuing certificate authority.
- **Field:** tls.server.x509.issuer.organizational_unit
- **Type:** keyword
- **Example:** www.example.com
- **Description:** List of organizational units (OU) of issuing certificate authority.
- **Field:** tls.server.x509.issuer.state_or_province
- **Type:** keyword
- **Example:** California
- **Description:** List of state or province names (ST, S, or P)

Field Set: tls.server.x509

- **Field:** tls.server.x509.not_after
- **Type:** date
- **Example:** 2020-07-16T03:15:39Z

- **Description:** Time at which the certificate is no longer considered valid.
- **Field:** `tls.server.x509.not_before`
 - **Type:** date
 - **Example:** 2019-08-16T01:40:25Z
 - **Description:** Time at which the certificate is first considered valid.
- **Field:** `tls.server.x509.public_key_algorithm`
 - **Type:** keyword
 - **Example:** RSA
 - **Description:** Algorithm used to generate the public key.
- **Field:** `tls.server.x509.public_key_curve`
 - **Type:** keyword
 - **Example:** nistp521
 - **Description:** The curve used by the elliptic curve public key algorithm. This is algorithm specific.
- **Field:** `tls.server.x509.public_key_exponent`
 - **Type:** long
 - **Example:** 65537
 - **Description:** Exponent used to derive the public key. This is algorithm specific.
- **Field:** `tls.server.x509.public_key_size`
 - **Type:** long
 - **Example:** 2048
 - **Description:** The size of the public key space in bits.
- **Field:** `tls.server.x509.serial_number`
 - **Type:** keyword
 - **Example:** 55FBB9C7DEBF09809D12CCAA
 - **Description:** Unique serial number issued by the certificate authority.
- **Field:** `tls.server.x509.signature_algorithm`
 - **Type:** keyword
 - **Example:** SHA256-RSA
 - **Description:** Identifier for certificate signature algorithm.

Field Set: `tls.server.x509.subject`

- **Field:** `tls.server.x509.subject.common_name`
 - **Type:** keyword
 - **Example:** shared.global.example.net
 - **Description:** List of common names (CN) of subject.
- **Field:** `tls.server.x509.subject.country`
 - **Type:** keyword
 - **Example:** US
 - **Description:** List of country \(\C\) code
- **Field:** `tls.server.x509.subject.distinguished_name`
 - **Type:** keyword
 - **Example:** C=US, ST=California, L=San Francisco, O=Example, Inc., CN=shared.global.example.net
 - **Description:** Distinguished name (DN) of the certificate subject entity.
- **Field:** `tls.server.x509.subject.locality`
 - **Type:** keyword
 - **Example:** San Francisco
 - **Description:** List of locality names (L)

- **Field:** `tls.server.x509.subject.organization`
- **Type:** keyword
- **Example:** Example, Inc.
- **Description:** List of organizations (O) of subject.
- **Field:** `tls.server.x509.subject.organizational_unit`
- **Type:** keyword
- **Description:** List of organizational units (OU) of subject.
- **Field:** `tls.server.x509.subject.state_or_province`
- **Type:** keyword
- **Example:** California
- **Description:** List of state or province names (ST, S, or P)

Field Set: `tls.server.x509`

- **Field:** `tls.server.x509.version_number`
- **Type:** keyword
- **Example:** 3
- **Description:** Version of x509 format.

Field Set: `tls`

- **Field:** `tls.version`
- **Type:** keyword
- **Example:** 1.2
- **Description:** Numeric part of the version parsed from the original string.
- **Field:** `tls.version_protocol`
- **Type:** keyword
- **Example:** `tls`
- **Description:** Normalized lowercase protocol name parsed from original string.

Field Set: `trace`

- **Field:** `trace.id`
- **Type:** keyword
- **Example:** `4bf92f3577b34da6a3ce929d0e0e4736`
- **Description:** Unique identifier of the trace.

Field Set: `transaction`

- **Field:** `transaction.id`
- **Type:** keyword
- **Example:** `00f067aa0ba902b7`
- **Description:** Unique identifier of the transaction within the scope of its trace.

Field Set: `url`

- **Field:** `url.domain`
- **Type:** keyword
- **Example:** `www.elastic.co`
- **Description:** Domain of the url.
- **Field:** `url.extension`
- **Type:** keyword
- **Example:** `png`
- **Description:** File extension from the request url, excluding the leading dot.

- **Field:** url.fragment
- **Type:** keyword
- **Description:** Portion of the url after the `#`.
- **Field:** url.full
- **Type:** wildcard
- **Example:** https://www.elastic.co:443/search?q=elasticsearch#top
- **Description:** Full unparsed URL.

Field Set: url.full

- **Field:** url.full.text
- **Type:** match_only_text
- **Example:** https://www.elastic.co:443/search?q=elasticsearch#top
- **Description:** Full unparsed URL.

Field Set: url

- **Field:** url.original
- **Type:** wildcard
- **Example:** https://www.elastic.co:443/search?q=elasticsearch#top or /search?q=elasticsearch
- **Description:** Unmodified original url as seen in the event source.

Field Set: url.original

- **Field:** url.original.text
- **Type:** match_only_text
- **Example:** https://www.elastic.co:443/search?q=elasticsearch#top or /search?q=elasticsearch
- **Description:** Unmodified original url as seen in the event source.

Field Set: url

- **Field:** url.password
- **Type:** keyword
- **Description:** Password of the request.
- **Field:** url.path
- **Type:** wildcard
- **Description:** Path of the request, such as "/search".
- **Field:** url.port
- **Type:** long
- **Example:** 443
- **Description:** Port of the request, such as 443.
- **Field:** url.query
- **Type:** keyword
- **Description:** Query string of the request.
- **Field:** url.registered_domain
- **Type:** keyword
- **Example:** example.com
- **Description:** The highest registered url domain, stripped of the subdomain.
- **Field:** url.scheme
- **Type:** keyword
- **Example:** https
- **Description:** Scheme of the url.

- **Field:** url.subdomain
 - **Type:** keyword
 - **Example:** east
 - **Description:** The subdomain of the domain.
- **Field:** url.top_level_domain
 - **Type:** keyword
 - **Example:** co.uk
 - **Description:** The effective top level domain (com, org, net, co.uk).
- **Field:** url.username
 - **Type:** keyword
 - **Description:** Username of the request.

Field Set: user.changes

- **Field:** user.changes.domain
 - **Type:** keyword
 - **Description:** Name of the directory the user is a member of.
- **Field:** user.changes.email
 - **Type:** keyword
 - **Description:** User email address.
- **Field:** user.changes.full_name
 - **Type:** keyword
 - **Example:** Albert Einstein
 - **Description:** User's full name, if available.

Field Set: user.changes.full_name

- **Field:** user.changes.full_name.text
 - **Type:** match_only_text
 - **Example:** Albert Einstein
 - **Description:** User's full name, if available.

Field Set: user.changes.group

- **Field:** user.changes.group.domain
 - **Type:** keyword
 - **Description:** Name of the directory the group is a member of.
- **Field:** user.changes.group.id
 - **Type:** keyword
 - **Description:** Unique identifier for the group on the system/platform.
- **Field:** user.changes.group.name
 - **Type:** keyword
 - **Description:** Name of the group.

Field Set: user.changes

- **Field:** user.changes.hash
 - **Type:** keyword
 - **Description:** Unique user hash to correlate information for a user in anonymized form.
- **Field:** user.changes.id
 - **Type:** keyword
 - **Example:** S-1-5-21-202424912787-2692429404-2351956786-1000
 - **Description:** Unique identifier of the user.

- **Field:** user.changes.name
- **Type:** keyword
- **Example:** a.einstein
- **Description:** Short name or login of the user.

Field Set: user.changes.name

- **Field:** user.changes.name.text
- **Type:** match_only_text
- **Example:** a.einstein
- **Description:** Short name or login of the user.

Field Set: user.changes

- **Field:** user.changes.roles
- **Type:** keyword
- **Example:** ["kibana_admin", "reporting_user"]
- **Description:** Array of user roles at the time of the event.

Field Set: user

- **Field:** user.domain
- **Type:** keyword
- **Description:** Name of the directory the user is a member of.

Field Set: user.effective

- **Field:** user.effective.domain
- **Type:** keyword
- **Description:** Name of the directory the user is a member of.
- **Field:** user.effective.email
- **Type:** keyword
- **Description:** User email address.
- **Field:** user.effective.full_name
- **Type:** keyword
- **Example:** Albert Einstein
- **Description:** User's full name, if available.

Field Set: user.effective.full_name

- **Field:** user.effective.full_name.text
- **Type:** match_only_text
- **Example:** Albert Einstein
- **Description:** User's full name, if available.

Field Set: user.effective.group

- **Field:** user.effective.group.domain
- **Type:** keyword
- **Description:** Name of the directory the group is a member of.
- **Field:** user.effective.group.id
- **Type:** keyword
- **Description:** Unique identifier for the group on the system/platform.
- **Field:** user.effective.group.name
- **Type:** keyword

- **Description:** Name of the group.

Field Set: user.effective

- **Field:** user.effective.hash
 - **Type:** keyword
 - **Description:** Unique user hash to correlate information for a user in anonymized form.
- **Field:** user.effective.id
 - **Type:** keyword
 - **Example:** S-1-5-21-202424912787-2692429404-2351956786-1000
 - **Description:** Unique identifier of the user.
- **Field:** user.effective.name
 - **Type:** keyword
 - **Example:** a.einstein
 - **Description:** Short name or login of the user.

Field Set: user.effective.name

- **Field:** user.effective.name.text
 - **Type:** match_only_text
 - **Example:** a.einstein
 - **Description:** Short name or login of the user.

Field Set: user.effective

- **Field:** user.effective.roles
 - **Type:** keyword
 - **Example:** ["kibana_admin", "reporting_user"]
 - **Description:** Array of user roles at the time of the event.

Field Set: user

- **Field:** user.email
 - **Type:** keyword
 - **Description:** User email address.
- **Field:** user.full_name
 - **Type:** keyword
 - **Example:** Albert Einstein
 - **Description:** User's full name, if available.

Field Set: user.full_name

- **Field:** user.full_name.text
 - **Type:** match_only_text
 - **Example:** Albert Einstein
 - **Description:** User's full name, if available.

Field Set: user.group

- **Field:** user.group.domain
 - **Type:** keyword
 - **Description:** Name of the directory the group is a member of.
- **Field:** user.group.id
 - **Type:** keyword

- **Description:** Unique identifier for the group on the system/platform.
- **Field:** user.group.name
 - **Type:** keyword
 - **Description:** Name of the group.

Field Set: user

- **Field:** user.hash
 - **Type:** keyword
 - **Description:** Unique user hash to correlate information for a user in anonymized form.
- **Field:** user.id
 - **Type:** keyword
 - **Example:** S-1-5-21-202424912787-2692429404-2351956786-1000
 - **Description:** Unique identifier of the user.
- **Field:** user.name
 - **Type:** keyword
 - **Example:** a.einstein
 - **Description:** Short name or login of the user.

Field Set: user.name

- **Field:** user.name.text
 - **Type:** match_only_text
 - **Example:** a.einstein
 - **Description:** Short name or login of the user.

Field Set: user.risk

- **Field:** user.risk.calculated_level
 - **Type:** keyword
 - **Example:** High
 - **Description:** A risk classification level calculated by an internal system as part of entity analytics and entity risk scoring.
- **Field:** user.risk.calculated_score
 - **Type:** float
 - **Example:** 880.73
 - **Description:** A risk classification score calculated by an internal system as part of entity analytics and entity risk scoring.
- **Field:** user.risk.calculated_score_norm
 - **Type:** float
 - **Example:** 88.73
 - **Description:** A normalized risk score calculated by an internal system.
- **Field:** user.risk.static_level
 - **Type:** keyword
 - **Example:** High
 - **Description:** A risk classification level obtained from outside the system, such as from some external Threat Intelligence Platform.
- **Field:** user.risk.static_score
 - **Type:** float
 - **Example:** 830.0
 - **Description:** A risk classification score obtained from outside the system, such as from some external Threat Intelligence Platform.

- **Field:** user.risk.static_score_norm
- **Type:** float
- **Example:** 83.0
- **Description:** A normalized risk score calculated by an external system.

Field Set: user

- **Field:** user.roles
- **Type:** keyword
- **Example:** ["kibana_admin", "reporting_user"]
- **Description:** Array of user roles at the time of the event.

Field Set: user.target

- **Field:** user.target.domain
- **Type:** keyword
- **Description:** Name of the directory the user is a member of.
- **Field:** user.target.email
- **Type:** keyword
- **Description:** User email address.
- **Field:** user.target.full_name
- **Type:** keyword
- **Example:** Albert Einstein
- **Description:** User's full name, if available.

Field Set: user.target.full_name

- **Field:** user.target.full_name.text
- **Type:** match_only_text
- **Example:** Albert Einstein
- **Description:** User's full name, if available.

Field Set: user.target.group

- **Field:** user.target.group.domain
- **Type:** keyword
- **Description:** Name of the directory the group is a member of.
- **Field:** user.target.group.id
- **Type:** keyword
- **Description:** Unique identifier for the group on the system/platform.
- **Field:** user.target.group.name
- **Type:** keyword
- **Description:** Name of the group.

Field Set: user.target

- **Field:** user.target.hash
- **Type:** keyword
- **Description:** Unique user hash to correlate information for a user in anonymized form.
- **Field:** user.target.id
- **Type:** keyword
- **Example:** S-1-5-21-202424912787-2692429404-2351956786-1000
- **Description:** Unique identifier of the user.

- **Field:** user.target.name
- **Type:** keyword
- **Example:** a.einstein
- **Description:** Short name or login of the user.

Field Set: user.target.name

- **Field:** user.target.name.text
- **Type:** match_only_text
- **Example:** a.einstein
- **Description:** Short name or login of the user.

Field Set: user.target

- **Field:** user.target.roles
- **Type:** keyword
- **Example:** ["kibana_admin", "reporting_user"]
- **Description:** Array of user roles at the time of the event.

Field Set: user_agent.device

- **Field:** user_agent.device.name
- **Type:** keyword
- **Example:** iPhone
- **Description:** Name of the device.

Field Set: user_agent

- **Field:** user_agent.name
- **Type:** keyword
- **Example:** Safari
- **Description:** Name of the user agent.
- **Field:** user_agent.original
- **Type:** keyword
- **Example:** Mozilla/5.0 (iPhone; CPU iPhone OS 12_1 like Mac OS X) AppleWebKit/605.1.15 (KHTML, like Gecko) Version/12.0 Mobile/15E148 Safari/604.1
- **Description:** Unparsed user_agent string.

Field Set: user_agent.original

- **Field:** user_agent.original.text
- **Type:** match_only_text
- **Example:** Mozilla/5.0 (iPhone; CPU iPhone OS 12_1 like Mac OS X) AppleWebKit/605.1.15 (KHTML, like Gecko) Version/12.0 Mobile/15E148 Safari/604.1
- **Description:** Unparsed user_agent string.

Field Set: user_agent.os

- **Field:** user_agent.os.family
- **Type:** keyword
- **Example:** debian
- **Description:** OS family (such as redhat, debian, freebsd, windows).
- **Field:** user_agent.os.full
- **Type:** keyword
- **Example:** Mac OS Mojave
- **Description:** Operating system name, including the version or code name.

Field Set: user_agent.os.full

- **Field:** user_agent.os.full.text
- **Type:** match_only_text
- **Example:** Mac OS Mojave
- **Description:** Operating system name, including the version or code name.

Field Set: user_agent.os

- **Field:** user_agent.os.kernel
- **Type:** keyword
- **Example:** 4.4.0-112-generic
- **Description:** Operating system kernel version as a raw string.
- **Field:** user_agent.os.name
- **Type:** keyword
- **Example:** Mac OS X
- **Description:** Operating system name, without the version.

Field Set: user_agent.os.name

- **Field:** user_agent.os.name.text
- **Type:** match_only_text
- **Example:** Mac OS X
- **Description:** Operating system name, without the version.

Field Set: user_agent.os

- **Field:** user_agent.os.platform
- **Type:** keyword
- **Example:** darwin
- **Description:** Operating system platform (such centos, ubuntu, windows).
- **Field:** user_agent.os.type
- **Type:** keyword
- **Example:** macos
- **Description:** Which commercial OS family (one of: linux, macos, unix, windows, ios or android).
- **Field:** user_agent.os.version
- **Type:** keyword
- **Example:** 10.14.1
- **Description:** Operating system version as a raw string.

Field Set: user_agent

- **Field:** user_agent.version
- **Type:** keyword
- **Example:** 12.0
- **Description:** Version of the user agent.

Field Set: volume

- **Field:** volume.bus_type
- **Type:** keyword
- **Example:** FileBackedVirtual
- **Description:** Bus type of the device.
- **Field:** volume.default_access
- **Type:** keyword

- **Description:** Bus type of the device.
- **Field:** volume.device_name
 - **Type:** keyword
 - **Description:** Device name of the volume.
- **Field:** volume.device_type
 - **Type:** keyword
 - **Example:** CD-ROM File System
 - **Description:** Volume device type.
- **Field:** volume.dos_name
 - **Type:** keyword
 - **Example:** E:
 - **Description:** DOS name of the device.
- **Field:** volume.file_system_type
 - **Type:** keyword
 - **Description:** Volume device file system type.
- **Field:** volume.mount_name
 - **Type:** keyword
 - **Description:** Mount name of the volume.
- **Field:** volume.nt_name
 - **Type:** keyword
 - **Example:** \Device\Cdrom1
 - **Description:** NT name of the device.
- **Field:** volume.product_id
 - **Type:** keyword
 - **Description:** ProductID of the device.
- **Field:** volume.product_name
 - **Type:** keyword
 - **Example:** Virtual DVD-ROM
 - **Description:** Produce name of the volume.
- **Field:** volume.removable
 - **Type:** boolean
 - **Description:** Indicates if the volume is removable.
- **Field:** volume.serial_number
 - **Type:** keyword
 - **Description:** Serial number of the device.
- **Field:** volume.size
 - **Type:** long
 - **Description:** Size of the volume device in bytes.
- **Field:** volume.vendor_id
 - **Type:** keyword
 - **Description:** VendorID of the device.
- **Field:** volume.vendor_name
 - **Type:** keyword
 - **Example:** Msft
 - **Description:** Vendor name of the device.
- **Field:** volume.writable
 - **Type:** boolean
 - **Description:** Indicates if the volume is writable.

Field Set: vulnerability

- **Field:** vulnerability.category
 - **Type:** keyword
 - **Example:** ["Firewall"]
 - **Description:** Category of a vulnerability.
- **Field:** vulnerability.classification
 - **Type:** keyword
 - **Example:** CVSS
 - **Description:** Classification of the vulnerability.
- **Field:** vulnerability.description
 - **Type:** keyword
 - **Example:** In macOS before 2.12.6, there is a vulnerability in the RPC...
 - **Description:** Description of the vulnerability.

Field Set: vulnerability.description

- **Field:** vulnerability.description.text
 - **Type:** match_only_text
 - **Example:** In macOS before 2.12.6, there is a vulnerability in the RPC...
 - **Description:** Description of the vulnerability.

Field Set: vulnerability

- **Field:** vulnerability.enumeration
 - **Type:** keyword
 - **Example:** CVE
 - **Description:** Identifier of the vulnerability.
- **Field:** vulnerability.id
 - **Type:** keyword
 - **Example:** CVE-2019-00001
 - **Description:** ID of the vulnerability.
- **Field:** vulnerability.reference
 - **Type:** keyword
 - **Example:** <https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2019-6111>
 - **Description:** Reference of the vulnerability.
- **Field:** vulnerability.report_id
 - **Type:** keyword
 - **Example:** 20191018.0001
 - **Description:** Scan identification number.

Field Set: vulnerability.scanner

- **Field:** vulnerability.scanner.vendor
 - **Type:** keyword
 - **Example:** Tenable
 - **Description:** Name of the scanner vendor.

Field Set: vulnerability.score

- **Field:** vulnerability.score.base
 - **Type:** float
 - **Example:** 5.5
 - **Description:** Vulnerability Base score.

- **Field:** vulnerability.score.environmental
- **Type:** float
- **Example:** 5.5
- **Description:** Vulnerability Environmental score.
- **Field:** vulnerability.score.temporal
- **Type:** float
- **Description:** Vulnerability Temporal score.
- **Field:** vulnerability.score.version
- **Type:** keyword
- **Example:** 2.0
- **Description:** CVSS version.

Field Set: vulnerability

- **Field:** vulnerability.severity
- **Type:** keyword
- **Example:** Critical
- **Description:** Severity of the vulnerability.