

Field Set: destinationdestination.user.group.idkeyword | Field: Unique | Type: identifier |
Example: for the group on the system/platform.destinationdestination.user.group.namekeyword |
Description: Name of the group.destinationdestination.user.hashkeyword Unique user hash to
correlate information for a user in anonymized
form.destinationdestination.user.idkeywordS-1-5-21-202424912787-2692429404-2351956786-1
000Unique identifier of the user.destinationdestination.user.namekeyworda.einstein Short name
or login of the user.destinationdestination.user.name.textmatch_only_texta.einstein Short name
or login of the user.destinationdestination.user.roleskeyword["kibana_admin", "reporting_user"]
Array of user roles at the time of the
event.devicedevice.idkeyword000000000-54b3-e7c7-0000-000046bfd97 The unique identifier of
a device.devicedevice.manufacturerkeywordSamsung The vendor name of the device
manufacturer.devicedevice.model.identifierkeywordSM-G920F The machine readable identifier
of the device model.devicedevice.model.namekeywordSamsung Galaxy S6 The human
readable marketing name of the device
model.devicedevice.serial_numberkeywordDJGAQS4CW5 Serial Number of the devicedll
dll.code_signature.digest_algorithmkeywordsha256 Hashing algorithm used to sign the
process.dll dll.code_signature.existsboolean TRUE Boolean to capture if a signature is
present.dll dll.code_signature.flagskeyword 570522385Code signing flags of the processdll
dll.code_signature.signing_idkeywordcom.apple.xpc.proxy The identifier used to sign the
process.dll dll.code_signature.statuskeywordERROR_UNTRUSTED_ROOT Additional
information about the certificate status.dll dll.code_signature.subject_namekeywordMicrosoft
Corporation Subject name of the code signerdll
dll.code_signature.team_idkeywordEQHXZ8M8AV The team identifier used to sign the
process.dll dll.code_signature.timestampdate 2021-01-01T12:10:30Z When the signature was
generated and signed.dll dll.code_signature.trustedboolean TRUE Stores the trust status of the
certificate chain.dll dll.code_signature.validboolean TRUE Boolean to capture if the digital
signature is verified against the binary content.dll
dll.hash.cdhashkeyword3783b4052fd474dbe30676b45c329e7a6d44acd9The Code Directory
(CD) hash of an executable.dll dll.hash.md5keyword MD5 hash.dll dll.hash.sha1keyword SHA1
hash.dll dll.hash.sha256keyword SHA256 hash.dll dll.hash.sha384keyword SHA384 hash.dll
dll.hash.sha512keyword SHA512 hash.dll dll.hash.ssdeepkeyword SSDEEP hash.dll
dll.hash.tlshkeyword TLSH hash.dll dll.namekeywordkernel32.dll Name of the library.dll
dll.pathkeywordC:\Windows\System32\kernel32.dll Full file path of the library.dll
dll.pe.architecturekeywordx64 CPU architecture target for the file.dll
dll.pe.companykeywordMicrosoft Corporation Internal company name of the file, provided at
compile-time.dll dll.pe.descriptionkeywordPaint Internal description of the file, provided at
compile-time.dll dll.pe.file_versionkeyword6.3.9600.17415 Process name.dll
dll.pe.go_import_hashkeyword10bddcb4cee42080f76c88d9ff964491 A hash of the Go language
imports in a PE file.dll dll.pe.go_importsflattened List of imported Go language element names
and types.dll dll.pe.go_imports_names_entropylong Shannon entropy calculation from the list of
Go imports.dll dll.pe.go_imports_names_var_entropylong Variance for Shannon entropy
calculation from the list of Go imports.dll dll.pe.go_strippedboolean Whether the file is a stripped
or obfuscated Go executable.dll dll.pe.imphashkeyword0c6803c4e922103c4dca5963aad36ddf

A hash of the imports in a PE file.dll

dll.pe.import_hashkeywordd41d8cd98f00b204e9800998ecf8427e A hash of the imports in a PE file.dll dll.pe.importsflattened List of imported element names and types.dll

dll.pe.imports_names_entropylong Shannon entropy calculation from the list of imported element names and types.dll dll.pe.imports_names_var_entropylong Variance for Shannon entropy calculation from the list of imported element names and types.dll

dll.pe.original_file_namekeywordMSPAINTEXE Internal name of the file, provided at compile-time.dll dll.pe.pehashkeyword73ff189b63cd6be375a7ff25179a38d347651975A hash of the PE header and data from one or more PE sections.dll dll.pe.productkeywordMicrosoft® Windows® Operating System Internal product name of the file, provided at compile-time.dll

dll.pe.sectionsnested Section information of the PE file.dll dll.pe.sections_entropylong Shannon entropy calculation from the section.dll dll.pe.sections.namekeyword PE Section List name.dll

dll.pe.sections.physical_sizekeyword PE Section List physical size.dll

dll.pe.sections.var_entropylong Variance for Shannon entropy calculation from the section.dll

dll.pe.sections.virtual_sizekeyword PE Section List virtual size. This is always the same as `physical\_size`.dns dns.answersobject Array of DNS answers.dns dns.answers.classkeywordIN The class of DNS data contained in this resource record.dns

dns.answers.datakeyword10.10.10.10 The data describing the resource.dns

dns.answers.namekeywordwww.example.com The domain name to which this resource record pertains.dns dns.answers.ttlkeyword 180The time interval in seconds that this resource record may be cached before it should be discarded.dns dns.answers.typekeywordCNAME The type of data contained in this resource record.dns dns.header_flagskeyword["RD", "RA"] Array of DNS header flags.dns dns.idkeyword 62111The DNS packet identifier assigned by the program that generated the query. The identifier is copied to the response.dns dns.op_codekeywordQUERY The DNS operation code that specifies the kind of query in the message.dns

dns.question.classkeywordIN The class of records being queried.dns

dns.question.namekeywordwww.example.com The name being queried.dns

dns.question.registered_domainkeywordexample.com The highest registered domain, stripped of the subdomain.dns dns.question.subdomainkeywordwww The subdomain of the domain.dns

dns.question.top_level_domainkeywordco.uk The effective top level domain (com, org, net, co.uk).dns dns.question.typekeywordAAAA The type of record being queried.dns

dns.resolved_ipip ["10.10.10.10", "10.10.10.11"] Array containing all IPs seen in answers.datadns dns.response_codekeywordNOERROR The DNS response code.dns

dns.typekeywordanswer The type of DNS event captured, query or answer.ecs

ecs.versionkeyword1.0.0 ECS version this event conforms to.emailmail.attachmentsnested List of objects describing the attachments.emailmail.attachments.file.extensionkeywordtxt Attachment file

extension.emailmail.attachments.file.hash.cdhashkeyword3783b4052fd474dbe30676b45c329e7a6d44acd9The Code Directory (CD) hash of an

executable.emailmail.attachments.file.hash.md5keyword MD5

hash.emailmail.attachments.file.hash.sha1keyword SHA1

hash.emailmail.attachments.file.hash.sha256keyword SHA256

hash.emailmail.attachments.file.hash.sha384keyword SHA384

hash.email.attachments.file.hash.sha512keyword SHA512
hash.email.attachments.file.hash.ssdeepkeyword SSDEEP
hash.email.attachments.file.hash.tlshkeyword TLSH
hash.email.attachments.file.mime_typekeywordtext/plain MIME type of the attachment
file.email.attachments.file.namekeywordattachment.txt Name of the attachment
file.email.attachments.file.sizelong 64329Attachment file
size.email.bcc.addresskeywordbcc.user1@example.com Email address of BCC
recipientemail.cc.addresskeywordcc.user1@example.com Email address of CC
recipientemail.content_typekeywordtext/plain MIME type of the email
message.email.delivery_timestampdate 2020-11-10T22:12:34.8196921Z Date and time
when message was delivered.email.directionkeywordinbound Direction of the
message.email.from.addresskeywordsender@example.com The sender's email
address.email.local_idkeywordc26dbea0-80d5-463b-b93c-4e8b708219ce Unique identifier
given by the source.email.message_idwildcard81ce15\$8r2j59@mail01.example.com
Value from the Message-ID header.email.Origination_timestampdate
2020-11-10T22:12:34.8196921Z Date and time the email was
composed.email.reply_to.addresskeywordreply.here@example.com Address replies
should be delivered to.email.sender.addresskeyword Address of the message
sender.email.subjectkeywordPlease see this important message. The subject of the email
message.email.subject.textmatch_only_textPlease see this important message. The
subject of the email message.email.to.addresskeyworduser1@example.com Email
address of recipientemail.x_mailerkeywordSpambot v2.5 Application that drafted
email.error.error.codekeyword Error code describing the error.error.error.idkeyword Unique
identifier for the error.error.error.messagekeywordmatch_only_text Error
message.error.error.stack_tracewildcard The stack trace of this error in plain
text.error.error.stack_trace.textmatch_only_text The stack trace of this error in plain
text.error.error.typekeywordjava.lang.NullPointerException The type of the error, for example the
class name of the exception.event.event.actionkeyworduser-password-change The action
captured by the event.event.event.agent_id_statuskeywordverified Validation status of the
event's agent.id field.event.event.categorykeywordauthentication Event category. The second
categorization field in the hierarchy.event.event.codekeyword 4648Identification code for this
event.event.event.createddate 2016-05-23T08:05:34.857Z Time when the event was first read
by an agent or by your pipeline.event.event.datasetkeywordapache.access Name of the
dataset.event.event.durationlong Duration of the event in nanoseconds.event.event.enddate
'event.end' contains the date when the event ended or when the activity was last
observed.event.event.hashkeyword123456789012345678901234567890ABCD Hash (perhaps
logstash fingerprint) of raw field to be able to demonstrate log
integrity.event.event.idkeyword8a4f500d Unique ID to describe the
event.event.event.ingesteddate 2016-05-23T08:05:35.101Z Timestamp when an event arrived in
the central data store.event.event.kindkeywordalert The kind of the event. The highest
categorization field in the hierarchy.event.event.modulekeywordapache Name of the module this
data is coming from.event.event.originalkeywordSep 19 08:26:10 host
CEF:0|Security| threatmanager|1.0|100| worm successfully

stopped|10|src=10.0.0.1 dst=2.1.2.2spt=1232Raw text message of entire event.eventevent.outcomekeywordsuccess The outcome of the event. The lowest level categorization field in the hierarchy.eventevent.providerkeywordkernel Source of the event.eventevent.reasonkeywordTerminated an unexpected process Reason why this event happened, according to the

sourceeventevent.referencekeywordhttps://system.example.com/event/#0001234Event reference URLeventevent.risk_scorefloat Risk score or priority of the event (e.g. security solutions). Use your system's original value here.eventevent.risk_score_normfloat Normalized risk score or priority of the event (0-100).eventevent.sequencelong Sequence number of the event.eventevent.severitylong 7Numeric severity of the event.

Field Set: eventevent.startdate | Field: `event.start` | Type: contains | Example: the date when the event started or when the activity was first observed.eventevent.timezonekeyword |

Description: Event time zone.eventevent.typekeyword Event type. The third categorization field in the

hierarchy.eventevent.urlkeywordhttps://mysystem.example.com/alert/5271dedb-f5b0-4218-87f0-4ac4870a38feEvent investigation URLfaasfaas.coldstartboolean Boolean value indicating a cold start of a function.faasfaas.executionkeywordaf9d5aa4-a685-4c5f-a22b-444f80b3cc28 The execution ID of the current function

execution.faasfaas.idkeywordarn:aws:lambda:us-west-2:123456789012:function:my-functionThe unique identifier of a serverless function.faasfaas.namekeywordmy-function The name of a serverless function.faasfaas.trigger.request_idkeyword 123456789The ID of the trigger request , message, event, etc.faasfaas.trigger.typekeywordhttp The trigger for the function

execution.faasfaas.versionkeyword 123The version of a serverless function.file

file.accesseddate Last time the file was accessed.file file.attributeskeyword["readonly", "system"] Array of file attributes.file file.code_signature.digest_algorithmkeywordsha256

Hashing algorithm used to sign the process.file file.code_signature.existsboolean TRUE Boolean to capture if a signature is present.file file.code_signature.flagskeyword

570522385Code signing flags of the processfile

file.code_signature.signing_idkeywordcom.apple.xpc.proxy The identifier used to sign the process.file file.code_signature.statuskeywordERROR_UNTRUSTED_ROOT Additional

information about the certificate status.file file.code_signature.subject_namekeywordMicrosoft Corporation Subject name of the code signerfile

file.code_signature.team_idkeywordEQHXZ8M8AV The team identifier used to sign the

process.file file.code_signature.timestampdate 2021-01-01T12:10:30Z When the signature was generated and signed.file file.code_signature.trustedboolean TRUE Stores the trust status of

the certificate chain.file file.code_signature.validboolean TRUE Boolean to capture if the digital signature is verified against the binary content.file file.createddate File creation time.file

file.ctimedate Last time the file attributes or metadata changed.file file.devicekeywordsda Device that is the source of the file.file file.directorykeyword/home/alice Directory where the file is

located.file file.drive_letterkeywordC Drive letter where the file is located.file

file.elf.architecturekeywordx86-64 Machine architecture of the ELF file.file

file.elf.byte_orderkeywordLittle Endian Byte sequence of ELF file.file

file.elf.cpu_typekeywordIntel CPU type of the ELF file.file file.elf.creation_datedate Build or

compile date.file file.elf.exportsflattened List of exported element names and types.file
file.elf.go_import_hashkeyword10bddcb4cee42080f76c88d9ff964491 A hash of the Go
language imports in an ELF file.file file.elf.go_importsflattened List of imported Go language
element names and types.file file.elf.go_imports_names_entropylong Shannon entropy
calculation from the list of Go imports.file file.elf.go_imports_names_var_entropylong Variance
for Shannon entropy calculation from the list of Go imports.file file.elf.go_strippedboolean
Whether the file is a stripped or obfuscated Go executable.file
file.elf.header.abi_versionkeyword Version of the ELF Application Binary Interface (ABI).file
file.elf.header.classkeyword Header class of the ELF file.file file.elf.header.datakeyword Data
table of the ELF header.file file.elf.header.entripointlong Header entripoint of the ELF file.file
file.elf.header.object_versionkeyword "0x1" for original ELF files.file
file.elf.header.os_abikeyword Application Binary Interface (ABI) of the Linux OS.file
file.elf.header.typekeyword Header type of the ELF file.file file.elf.header.versionkeyword
Version of the ELF header.file
file.elf.import_hashkeywordd41d8cd98f00b204e9800998ecf8427e A hash of the imports in an
ELF file.file file.elf.importsflattened List of imported element names and types.file
file.elf.imports_names_entropylong Shannon entropy calculation from the list of imported
element names and types.file file.elf.imports_names_var_entropylong Variance for Shannon
entropy calculation from the list of imported element names and types.file file.elf.sectionsnested
Section information of the ELF file.file file.elf.sections.chi2long Chi-square probability distribution
of the section.file file.elf.sections.entripointlong Shannon entropy calculation from the section.file
file.elf.sections.flagskeyword ELF Section List flags.file file.elf.sections.namekeyword ELF
Section List name.file file.elf.sections.physical_offsetkeyword ELF Section List offset.file
file.elf.sections.physical_sizekeyword ELF Section List physical size.file file.elf.sections.typekeyword
ELF Section List type.file file.elf.sections.var_entropylong Variance for Shannon entropy
calculation from the section.file file.elf.sections.virtual_addresskeyword ELF Section List virtual
address.file file.elf.sections.virtual_sizekeyword ELF Section List virtual size.file
file.elf.segmentsnested ELF object segment list.file file.elf.segments.sectionskeyword ELF
object segment sections.file file.elf.segments.typekeyword ELF object segment type.file
file.elf.shared_librarieskeyword List of shared libraries used by this ELF object.file
file.elf.telfhashkeyword telfhash hash for ELF file.file file.extensionkeywordpng File extension,
excluding the leading dot.file file.fork_namekeywordZone.Identifier A fork is additional data
associated with a filesystem object.file file.gidkeyword 1001Primary group ID (GID) of the file.file
file.groupkeywordalice Primary group name of the file.file
file.hash.cdhashkeyword3783b4052fd474dbe30676b45c329e7a6d44acd9The Code Directory
(CD) hash of an executable.file file.hash.md5keyword MD5 hash.file file.hash.sha1keyword
SHA1 hash.file file.hash.sha256keyword SHA256 hash.file file.hash.sha384keyword SHA384
hash.file file.hash.sha512keyword SHA512 hash.file file.hash.ssdeepkeyword SSDEEP
hash.file file.hash.tlshkeyword TLSH hash.file file.inodekeyword 256383Inode representing the
file in the filesystem.file
file.macho.go_import_hashkeyword10bddcb4cee42080f76c88d9ff964491 A hash of the Go
language imports in a Mach-O file.file file.macho.go_importsflattened List of imported Go
language element names and types.file file.macho.go_imports_names_entropylong Shannon

entropy calculation from the list of Go imports.file

file.macho.go_imports_names_var_entropylong Variance for Shannon entropy calculation from the list of Go imports.file file.macho.go_strippedboolean Whether the file is a stripped or obfuscated Go executable.file

file.macho.import_hashkeywordd41d8cd98f00b204e9800998ecf8427e A hash of the imports in a Mach-O file.file file.macho.importsflattened List of imported element names and types.file

file.macho.imports_names_entropylong Shannon entropy calculation from the list of imported element names and types.file file.macho.imports_names_var_entropylong Variance for Shannon entropy calculation from the list of imported element names and types.file

file.macho.sectionsnested Section information of the Mach-O file.file

file.macho.sections.entropylong Shannon entropy calculation from the section.file

file.macho.sections.namekeyword Mach-O Section List name.file

file.macho.sections.physical_sizelong Mach-O Section List physical size.file

file.macho.sections.var_entropylong Variance for Shannon entropy calculation from the section.file file.macho.sections.virtual_sizelong Mach-O Section List virtual size. This is always the same as `physical\_size`.file

file.macho.symhashkeywordd3ccf195b62a9279c3c19af1080497ec A hash of the imports in a Mach-O file.file file.mime_typekeyword Media type of file, document, or arrangement of bytes.file file.modekeyword 640Mode of the file in octal representation.file file.mtimedate Last time the file content was modified.file file.namekeywordexample.png Name of the file including the extension, without the directory.file file.ownerkeywordalice File owner's username.file

file.pathkeyword/home/alice/example.png Full path to the file, including the file name.file

file.path.textmatch_only_text/home/alice/example.png Full path to the file, including the file name.file file.pe.architecturekeywordx64 CPU architecture target for the file.file

file.pe.companykeywordMicrosoft Corporation Internal company name of the file, provided at compile-time.file file.pe.descriptionkeywordPaint Internal description of the file, provided at compile-time.file file.pe.file_versionkeyword6.3.9600.17415 Process name.file

file.pe.go_import_hashkeyword10bddcb4cee42080f76c88d9ff964491 A hash of the Go language imports in a PE file.file file.pe.go_importsflattened List of imported Go language element names and types.file file.pe.go_imports_names_entropylong Shannon entropy calculation from the list of Go imports.file file.pe.go_imports_names_var_entropylong Variance for Shannon entropy calculation from the list of Go imports.file file.pe.go_strippedboolean Whether the file is a stripped or obfuscated Go executable.file

file.pe.imphashkeyword0c6803c4e922103c4dca5963aad36ddf A hash of the imports in a PE file.file file.pe.import_hashkeywordd41d8cd98f00b204e9800998ecf8427e A hash of the imports in a PE file.file file.pe.importsflattened List of imported element names and types.file

file.pe.imports_names_entropylong Shannon entropy calculation from the list of imported element names and types.file file.pe.imports_names_var_entropylong Variance for Shannon entropy calculation from the list of imported element names and types.file

file.pe.original_file_namekeywordMSPAINTE.EXE Internal name of the file, provided at compile-time.file file.pe.pehashkeyword73ff189b63cd6be375a7ff25179a38d347651975A hash of the PE header and data from one or more PE sections.file file.pe.productkeywordMicrosoft® Windows® Operating System Internal product name of the file, provided at compile-time.file

file.pe.sections.nested Section information of the PE file.
file file.pe.sections.entropy.long Shannon entropy calculation from the section.
file file.pe.sections.name.keyword PE Section List name.
file file.pe.sections.physical_size.long PE Section List physical size.
file file.pe.sections.var_entropy.long Variance for Shannon entropy calculation from the section.
file file.pe.sections.virtual_size.long PE Section List virtual size. This is always the same as `physical\_size`.
file file.size.long 16384 File size in bytes.
file file.target_path.keyword Target path for symlinks.
file file.target_path.textmatch_only_text Target path for symlinks.
file file.type.keyword File type (file, dir, or symlink).
file file.uid.keyword 1001 The user ID (UID) or security identifier (SID) of the file owner.

Field Set: file | Field: file.x509.alternative_names.keyword*.elastic.co | Type: List | Example: of subject alternative names (SAN).
file file.x509.issuer.common_name.keyword Example | Description: SHA2 High Assurance Server CA List of common name (CN) of issuing certificate authority.
file file.x509.issuer.country.keyword US List of country \(\C\) codes.
file file.x509.issuer.distinguished_name.keyword C=US, O=Example Inc, OU=www.example.com, CN=Example SHA2 High Assurance Server CA Distinguished name (DN) of issuing certificate authority.
file file.x509.issuer.locality.keyword Mountain View List of locality names (L).
file file.x509.issuer.organization.keyword Example Inc List of organizations (O) of issuing certificate authority.
file file.x509.issuer.organizational_unit.keyword www.example.com List of organizational units (OU) of issuing certificate authority.
file file.x509.issuer.state_or_province.keyword California List of state or province names (ST, S, or P).
file file.x509.not_after.date 2020-07-16T03:15:39Z Time at which the certificate is no longer considered valid.
file file.x509.not_before.date 2019-08-16T01:40:25Z Time at which the certificate is first considered valid.
file file.x509.public_key_algorithm.keyword RSA Algorithm used to generate the public key.
file file.x509.public_key_curve.keyword nistp521 The curve used by the elliptic curve public key algorithm. This is algorithm specific.
file file.x509.public_key_exponent.long 65537 Exponent used to derive the public key. This is algorithm specific.
file file.x509.public_key_size.long 2048 The size of the public key space in bits.
file file.x509.serial_number.keyword 55FBB9C7DEBF09809D12CCAA Unique serial number issued by the certificate authority.
file file.x509.signature_algorithm.keyword SHA256-RSA Identifier for certificate signature algorithm.
file file.x509.subject.common_name.keyword shared.global.example.net List of common names (CN) of subject.
file file.x509.subject.country.keyword US List of country \(\C\) code.
file file.x509.subject.distinguished_name.keyword C=US, ST=California, L=San Francisco, O=Example, Inc., CN=shared.global.example.net Distinguished name (DN) of the certificate subject entity.
file file.x509.subject.locality.keyword San Francisco List of locality names (L).
file file.x509.subject.organization.keyword Example, Inc. List of organizations (O) of subject.
file file.x509.subject.organizational_unit.keyword List of organizational units (OU) of subject.
file file.x509.subject.state_or_province.keyword California List of state or province names (ST, S, or P).
file file.x509.version_number.keyword 3 Version of x509 format.
group group.domain.keyword Name of the directory the group is a member of.
group group.id.keyword Unique identifier for the group on the system/platform.
group group.name.keyword Name of the group.
host host.architecture.keyword x86_64 Operating system architecture.
host host.boot.id.keyword 88a1f0ed-5ae5-41ee-af6b-41921c311872 Linux boot uuid

taken from /proc/sys/kernel/random/boot_idhosthost.cpu.usagescaled_float Percent CPU used, between 0 and 1.hosthost.disk.read.byteslong The number of bytes read by all disks.hosthost.disk.write.byteslong The number of bytes written on all disks.hosthost.domainkeywordCONTOSO Name of the directory the group is a member of.hosthost.geo.city_namekeywordMontreal City name.hosthost.geo.continent_codekeywordNA Continent code.hosthost.geo.continent_namekeywordNorth America Name of the continent.hosthost.geo.country_iso_codekeywordCA Country ISO code.hosthost.geo.country_namekeywordCanada Country name.hosthost.geo.locationgeo_point{ "lon": -73.614830, "lat": 45.505918 } Longitude and latitude.hosthost.geo.namekeywordboston-dc User-defined description of a location.hosthost.geo.postal_codekeyword 94040Postal code.hosthost.geo.region_iso_codekeywordCA-QC Region ISO code.hosthost.geo.region_namekeywordQuebec Region name.hosthost.geo.timezonekeywordAmerica/Argentina/Buenos_Aires Time zone.hosthost.hostnamekeyword Hostname of the host.hosthost.idkeyword Unique host id.hosthost.ipip Host ip addresses.hosthost.mackeyword["00-00-5E-00-53-23", "00-00-5E-00-53-24"] Host MAC addresses.hosthost.namekeyword Name of the host.hosthost.network.egress.byteslong The number of bytes sent on all network interfaces.hosthost.network.egress.packetslong The number of packets sent on all network interfaces.hosthost.network.ingress.byteslong The number of bytes received on all network interfaces.hosthost.network.ingress.packetslong The number of packets received on all network interfaces.hosthost.os.familykeyworddebian OS family (such as redhat, debian, freebsd, windows).hosthost.os.fullkeywordMac OS Mojave Operating system name, including the version or code name.hosthost.os.full.textmatch_only_textMac OS Mojave Operating system name, including the version or code name.hosthost.os.kernelkeyword4.4.0-112-generic Operating system kernel version as a raw string.hosthost.os.namekeywordMac OS X Operating system name, without the version.hosthost.os.name.textmatch_only_textMac OS X Operating system name, without the version.hosthost.os.platformkeyworddarwin Operating system platform (such as centos, ubuntu, windows).hosthost.os.typekeywordmacos Which commercial OS family (one of: linux, macos, unix, windows, ios or android).hosthost.os.versionkeyword10.14.1 Operating system version as a raw string.hosthost.pid_ns_inokeyword 256383Pid namespace inodehosthost.risk.calculated_levelkeywordHigh A risk classification level calculated by an internal system as part of entity analytics and entity risk scoring.hosthost.risk.calculated_scorefloat 880.73A risk classification score calculated by an internal system as part of entity analytics and entity risk scoring.hosthost.risk.calculated_score_normfloat 88.73A normalized risk score calculated by an internal system.hosthost.risk.static_levelkeywordHigh A risk classification level obtained from outside the system, such as from some external Threat Intelligence Platform.hosthost.risk.static_scorefloat 830A risk classification score obtained from outside the system, such as from some external Threat Intelligence Platform.hosthost.risk.static_score_normfloat 83A normalized risk score calculated by an external system.hosthost.typekeyword Type of host.hosthost.uptime1325Seconds the host has been up.http http.request.body.byteslong 887Size in bytes of the request body.http

http.request.body.contentwildcardHello world The full HTTP request body.http
http.request.body.content.textmatch_only_textHello world The full HTTP request body.http
http.request.byteslong 1437Total size in bytes of the request (body and headers).http
http.request.idkeyword123e4567-e89b-12d3-a456-426614174000 HTTP request ID.http
http.request.methodkeywordPOST HTTP request method.http
http.request.mime_typekeywordimage/gif Mime type of the body of the request.http
http.request.referrerkeywordhttps://blog.example.com/ Referrer for this HTTP request.http
http.response.body.byteslong 887Size in bytes of the response body.http
http.response.body.contentwildcardHello world The full HTTP response body.http
http.response.body.content.textmatch_only_textHello world The full HTTP response body.http
http.response.byteslong 1437Total size in bytes of the response (body and headers).http
http.response.mime_typekeywordimage/gif Mime type of the body of the response.http
http.response.status_codelong 404HTTP response status code.http http.versionkeyword
1.1HTTP version.log log.file.pathkeyword/var/log/fun-times.log Full path to the log file this event
came from.log log.levelkeyworderror Log level of the log event.log
log.loggerkeywordorg.elasticsearch.bootstrap.Bootstrap Name of the logger.log
log.origin.file.linelong 42The line number of the file which originated the log event.log
log.origin.file.namekeywordBootstrap.java The code file which originated the log event.log
log.origin.functionkeywordinit The function which originated the log event.log log.syslogobject
Syslog metadatalog log.syslog.appnamekeywordsshd The device or application that originated
the Syslog message.log log.syslog.facility.codelong 23Syslog numeric facility of the event.log
log.syslog.facility.namekeywordlocal7 Syslog text-based facility of the event.log
log.syslog.hostnamekeywordexample-host The host that originated the Syslog message.log
log.syslog.msgidkeywordID47 An identifier for the type of Syslog message.log
log.syslog.prioritylong 135Syslog priority of the event.log log.syslog.procidkeyword 12345The
process name or ID that originated the Syslog message.log log.syslog.severity.codelong
3Syslog numeric severity of the event.log log.syslog.severity.namekeywordError Syslog
text-based severity of the event.log log.syslog.structured_dataflattened Structured data
expressed in RFC 5424 messages.log log.syslog.versionkeyword 1Syslog protocol
version.networknetwork.applicationkeywordaim Application level protocol
name.networknetwork.byteslong 368Total bytes transferred in both
directions.networknetwork.community_idkeyword1:hO+sN4H+MG5MY/8hIXPqc4ZQz0= A
hash of source and destination IPs and ports.networknetwork.directionkeywordinbound
Direction of the network traffic.networknetwork.forwarded_ipip 192.1.1.2 Host IP address when
the source IP address is the proxy.networknetwork.iana_numberkeyword 6IANA Protocol
Number.networknetwork.innerobject Inner VLAN tag
informationnetworknetwork.inner.vlan.idkeyword 10VLAN ID as reported by the
observer.networknetwork.inner.vlan.namekeywordoutside Optional VLAN name as reported by
the observer.networknetwork.namekeywordGuest Wifi Name given by operators to sections of
their network.networknetwork.packetslong 24Total packets transferred in both
directions.networknetwork.protocolkeywordhttp Application protocol
name.networknetwork.transportkeywordtcp Protocol Name corresponding to the field
`iana\_number`.networknetwork.typekeywordipv4 In the OSI Model this would be the Network

Layer. ipv4, ipv6, ipsec, pim, etcnetworknetwork.vlan.idkeyword 10VLAN ID as reported by the observer.networknetwork.vlan.namekeywordoutside Optional VLAN name as reported by the observer.observerobserver.egressobject Object field for egress informationobserverobserver.egress.interface.aliaskeywordoutside Interface aliasobserverobserver.egress.interface.idkeyword 10Interface IDobserverobserver.egress.interface.namekeywordeth0 Interface nameobserverobserver.egress.vlan.idkeyword 10VLAN ID as reported by the observer.observerobserver.egress.vlan.namekeywordoutside Optional VLAN name as reported by the observer.observerobserver.egress.zonekeywordPublic_Internet Observer Egress zoneobserverobserver.geo.city_namekeywordMontreal City name.observerobserver.geo.continent_codekeywordNA Continent code.observerobserver.geo.continent_namekeywordNorth America Name of the continent. Field Set: observerobserver.geo.country_iso_codekeywordCA | Field: Country | Type: ISO | Example: code.observerobserver.geo.country_namekeywordCanada | Description: Country name.observerobserver.geo.locationgeo_point{ "lon": -73.614830, "lat": 45.505918 } Longitude and latitude.observerobserver.geo.namekeywordboston-dc User-defined description of a location.observerobserver.geo.postal_codekeyword 94040Postal code.observerobserver.geo.region_iso_codekeywordCA-QC Region ISO code.observerobserver.geo.region_namekeywordQuebec Region name.observerobserver.geo.timezonekeywordAmerica/Argentina/Buenos_Aires Time zone.observerobserver.hostnamekeyword Hostname of the observer.observerobserver.ingressobject Object field for ingress informationobserverobserver.ingress.interface.aliaskeywordoutside Interface aliasobserverobserver.ingress.interface.idkeyword 10Interface IDobserverobserver.ingress.interface.namekeywordeth0 Interface nameobserverobserver.ingress.vlan.idkeyword 10VLAN ID as reported by the observer.observerobserver.ingress.vlan.namekeywordoutside Optional VLAN name as reported by the observer.observerobserver.ingress.zonekeywordDMZ Observer ingress zoneobserverobserver.ipip IP addresses of the observer.observerobserver.mackeyword["00-00-5E-00-53-23", "00-00-5E-00-53-24"] MAC addresses of the observer.observerobserver.namekeyword1_proxySG Custom name of the observer.observerobserver.os.familykeyworddebian OS family (such as redhat, debian, freebsd, windows).observerobserver.os.fullkeywordMac OS Mojave Operating system name, including the version or code name.observerobserver.os.full.textmatch_only_textMac OS Mojave Operating system name, including the version or code name.observerobserver.os.kernelkeyword4.4.0-112-generic Operating system kernel version as a raw string.observerobserver.os.namekeywordMac OS X Operating system name, without the version.observerobserver.os.name.textmatch_only_textMac OS X Operating system name, without the version.observerobserver.os.platformkeyworddarwin Operating system platform (such centos, ubuntu, windows).observerobserver.os.typekeywordmacos Which commercial OS family (one of: linux, macos, unix, windows, ios or android).observerobserver.os.versionkeyword10.14.1 Operating system version as a raw string.observerobserver.productkeywords200 The product name of the

observer.observerobserver.serial_numberkeyword Observer serial number.observerobserver.typekeywordfirewall The type of the observer the data is coming from.observerobserver.vendorkeywordSymantec Vendor name of the observer.observerobserver.versionkeyword Observer version.orchestratororchestrator.api_versionkeywordv1beta1 API version being used to carry out the actionorchestratororchestrator.cluster.idkeyword Unique ID of the cluster.orchestratororchestrator.cluster.namekeyword Name of the cluster.orchestratororchestrator.cluster.urlkeyword URL of the API used to manage the cluster.orchestratororchestrator.cluster.versionkeyword The version of the cluster.orchestratororchestrator.namespacekeywordkube-system Namespace in which the action is taking place.orchestratororchestrator.organizationkeywordelastic Organization affected by the event (for multi-tenant orchestrator setups).orchestratororchestrator.resource.annotationkeyword["key1:value1", 'key2:value2', 'key3:value3'] The list of annotations added to the resource.orchestratororchestrator.resource.idkeyword Unique ID of the resource being acted upon.orchestratororchestrator.resource.ipip IP address assigned to the resource associated with the event being observed.orchestratororchestrator.resource.labelkeyword["key1:value1", 'key2:value2', 'key3:value3'] The list of labels added to the resource.orchestratororchestrator.resource.namekeywordtest-pod-cdcws Name of the resource being acted upon.orchestratororchestrator.resource.parent.typekeywordDaemonSet Type or kind of the parent resource associated with the event being observed.orchestratororchestrator.resource.typekeywordservice Type of resource being acted upon.orchestratororchestrator.typekeywordkubernetes Orchestrator cluster type (e.g. kubernetes, nomad or cloudfoundry).organizationorganization.idkeyword Unique identifier for the organization.organizationorganization.namekeyword Organization name.organizationorganization.name.textmatch_only_text Organization name.packagepackage.architecturekeywordx86_64 Package architecture.packagepackage.build_versionkeyword36f4f7e89dd61b0988b12ee000b98966867710cdBuild version information.packagepackage.checksumkeyword68b329da9893e34099c7d8ad5cb9c940 Checksum of the installed package for verification.packagepackage.descriptionkeywordOpen source programming language to build simple/reliable/efficient software.Description of the package.packagepackage.install_scopekeywordglobal Indicating how the package was installed, e.g. user-local, global.packagepackage.installdate Time when package was installed.packagepackage.licensekeywordApache License 2.0 Package license.packagepackage.namekeywordgo Package name.packagepackage.pathkeyword/usr/local/Cellar/go/1.12.9/ Path where the package is installed.packagepackage.referencekeywordhttps://golang.org Package home page or reference URL.packagepackage.sizelong 62231Package size in bytes.packagepackage.typekeywordrpm Package type.packagepackage.versionkeyword1.12.9 Package versionprocessprocess.argskeyword["/usr/bin/ssh", "-l", "user", "10.0.0.16"] Array of process arguments.processprocess.args_countlong 4Length of the process.args array.processprocess.code_signature.digest_algorithmkeywordsha256 Hashing algorithm used

to sign the process.processprocess.code_signature.existsboolean TRUE Boolean to capture if a signature is present.processprocess.code_signature.flagskeyword 570522385Code signing flags of the processprocessprocess.code_signature.signing_idkeywordcom.apple.xpc.proxy The identifier used to sign the process.processprocess.code_signature.statuskeywordERROR_UNTRUSTED_ROOT Additional information about the certificate status.processprocess.code_signature.subject_namekeywordMicrosoft Corporation Subject name of the code signerprocessprocess.code_signature.team_idkeywordEQHXZ8M8AV The team identifier used to sign the process.processprocess.code_signature.timestampdate 2021-01-01T12:10:30Z When the signature was generated and signed.processprocess.code_signature.trustedboolean TRUE Stores the trust status of the certificate chain.processprocess.code_signature.validboolean TRUE Boolean to capture if the digital signature is verified against the binary content.processprocess.command_linewildcard/usr/bin/ssh -l user 10.0.0.16 Full command line that started the process.processprocess.command_line.textmatch_only_text/usr/bin/ssh -l user 10.0.0.16 Full command line that started the process.processprocess.elf.architecturekeywordx86-64 Machine architecture of the ELF file.processprocess.elf.byte_orderkeywordLittle Endian Byte sequence of ELF file.processprocess.elf.cpu_typekeywordIntel CPU type of the ELF file.processprocess.elf.creation_datedate Build or compile date.processprocess.elf.exportsflattened List of exported element names and types.processprocess.elf.go_import_hashkeyword10bddcb4cee42080f76c88d9ff964491 A hash of the Go language imports in an ELF file.processprocess.elf.go_importsflattened List of imported Go language element names and types.processprocess.elf.go_imports_names_entropylong Shannon entropy calculation from the list of Go imports.processprocess.elf.go_imports_names_var_entropylong Variance for Shannon entropy calculation from the list of Go imports.processprocess.elf.go_strippedboolean Whether the file is a stripped or obfuscated Go executable.processprocess.elf.header.abi_versionkeyword Version of the ELF Application Binary Interface (ABI).processprocess.elf.header.classkeyword Header class of the ELF file.processprocess.elf.header.datakeyword Data table of the ELF header.processprocess.elf.header.entrypointlong Header entrypoint of the ELF file.processprocess.elf.header.object_versionkeyword "0x1" for original ELF files.processprocess.elf.header.os_abikeyword Application Binary Interface (ABI) of the Linux OS.processprocess.elf.header.typekeyword Header type of the ELF file.processprocess.elf.header.versionkeyword Version of the ELF header.processprocess.elf.import_hashkeywordd41d8cd98f00b204e9800998ecf8427e A hash of the imports in an ELF file.processprocess.elf.importsflattened List of imported element names and types.processprocess.elf.imports_names_entropylong Shannon entropy calculation from the list of imported element names and types.processprocess.elf.imports_names_var_entropylong Variance for Shannon entropy calculation from the list of imported element names and types.processprocess.elf.sectionsnested Section information of the ELF

file.processprocess.elf.sections.chi2long Chi-square probability distribution of the section.
section.processprocess.elf.sections.entropylong Shannon entropy calculation from the section.
section.processprocess.elf.sections.flagskeyword ELF Section List
flags.processprocess.elf.sections.namekeyword ELF Section List
name.processprocess.elf.sections.physical_offsetkeyword ELF Section List
offset.processprocess.elf.sections.physical_sizelong ELF Section List physical size.
size.processprocess.elf.sections.typekeyword ELF Section List
type.processprocess.elf.sections.var_entropylong Variance for Shannon entropy calculation from the section.
section.processprocess.elf.sections.virtual_addresslong ELF Section List virtual address.
address.processprocess.elf.sections.virtual_sizelong ELF Section List virtual size.
size.processprocess.elf.segmentsnested ELF object segment
list.processprocess.elf.segments.sectionskeyword ELF object segment
sections.processprocess.elf.segments.typekeyword ELF object segment
type.processprocess.elf.shared_librarieskeyword List of shared libraries used by this ELF object.
object.processprocess.elf.telfhashkeyword telfhash hash for ELF file.
processprocess.enddate 2016-05-23T08:05:34.853Z The time the process ended.
processprocess.entity_idkeywordc2c455d9f99375d Unique identifier for the process.
processprocess.entry_leader.argskeyword["/usr/bin/ssh", "-l", "user", "10.0.0.16"] Array of process arguments.
processprocess.entry_leader.args_countlong 4Length of the process.args array.
processprocess.entry_leader.attested_groups.namekeyword Name of the group.
processprocess.entry_leader.attested_user.idkeywordS-1-5-21-202424912787-2692429404-2351956786-1000Unique identifier of the user.
processprocess.entry_leader.attested_user.namekeyworda.einstein Short name or login of the user.
processprocess.entry_leader.attested_user.name.textmatch_only_texta.einstein Short name or login of the user.
processprocess.entry_leader.command_linewildcard/usr/bin/ssh -l user 10.0.0.16 Full command line that started the process.
processprocess.entry_leader.command_line.textmatch_only_text/usr/bin/ssh -l user 10.0.0.16 Full command line that started the process.
processprocess.entry_leader.entity_idkeywordc2c455d9f99375d Unique identifier for the process.
processprocess.entry_leader.entry_meta.source.ipip IP address of the source.
processprocess.entry_leader.entry_meta.typekeyword The entry type for the entry session leader.
processprocess.entry_leader.executablekeyword/usr/bin/ssh Absolute path to the process executable.
Field Set: processprocess.entry_leader.executable.textmatch_only_text/usr/bin/ssh | Field: Absolute | Type: path | Example: to the process
executable.processprocess.entry_leader.group.idkeyword | Description: Unique identifier for the group on the system/platform.
processprocess.entry_leader.group.namekeyword Name of the group.
processprocess.entry_leader.interactiveboolean TRUE Whether the process is connected to an interactive shell.
processprocess.entry_leader.namekeywordssh Process
name.processprocess.entry_leader.name.textmatch_only_textssh Process
name.processprocess.entry_leader.parent.entity_idkeywordc2c455d9f99375d Unique identifier for the process.
processprocess.entry_leader.parent.pidlong 4242Process
id.processprocess.entry_leader.parent.session_leader.entity_idkeywordc2c455d9f99375d

Unique identifier for the process.processprocess.entry_leader.parent.session_leader.pidlong 4242Process id.processprocess.entry_leader.parent.session_leader.startdate 2016-05-23T08:05:34.853Z The time the process started.processprocess.entry_leader.parent.session_leader.vpidlong 4242Virtual process id.processprocess.entry_leader.parent.startdate 2016-05-23T08:05:34.853Z The time the process started.processprocess.entry_leader.parent.vpidlong 4242Virtual process id.processprocess.entry_leader.pidlong 4242Process id.processprocess.entry_leader.real_group.idkeyword Unique identifier for the group on the system/platform.processprocess.entry_leader.real_group.namekeyword Name of the group.processprocess.entry_leader.real_user.idkeywordS-1-5-21-202424912787-2692429404-2351956786-1000Unique identifier of the user.processprocess.entry_leader.real_user.namekeyworda.einstein Short name or login of the user.processprocess.entry_leader.real_user.name.textmatch_only_texta.einstein Short name or login of the user.processprocess.entry_leader.same_as_processboolean TRUE This boolean is used to identify if a leader process is the same as the top level process.processprocess.entry_leader.saved_group.idkeyword Unique identifier for the group on the system/platform.processprocess.entry_leader.saved_group.namekeyword Name of the group.processprocess.entry_leader.saved_user.idkeywordS-1-5-21-202424912787-2692429404-2351956786-1000Unique identifier of the user.processprocess.entry_leader.saved_user.namekeyworda.einstein Short name or login of the user.processprocess.entry_leader.saved_user.name.textmatch_only_texta.einstein Short name or login of the user.processprocess.entry_leader.startdate 2016-05-23T08:05:34.853Z The time the process started.processprocess.entry_leader.supplemental_groups.idkeyword Unique identifier for the group on the system/platform.processprocess.entry_leader.supplemental_groups.namekeyword Name of the group.processprocess.entry_leader.ttyobject Information about the controlling TTY device.processprocess.entry_leader.tty.char_device.majorlong 4The TTY character device's major number.processprocess.entry_leader.tty.char_device.minorlong 1The TTY character device's minor number.processprocess.entry_leader.user.idkeywordS-1-5-21-202424912787-2692429404-2351956786-1000Unique identifier of the user.processprocess.entry_leader.user.namekeyworda.einstein Short name or login of the user.processprocess.entry_leader.user.name.textmatch_only_texta.einstein Short name or login of the user.processprocess.entry_leader.vpidlong 4242Virtual process id.processprocess.entry_leader.working_directorykeyword/home/alice The working directory of the process.processprocess.entry_leader.working_directory.textmatch_only_text/home/alice The working directory of the process.processprocess.env_varskeyword["PATH=/usr/local/bin:/usr/bin", "USER=ubuntu"]Array of environment variable bindings.processprocess.executablekeyword/usr/bin/ssh Absolute path to the process executable.processprocess.executable.textmatch_only_text/usr/bin/ssh Absolute path to the process executable.processprocess.exit_codelong 137The exit code of the process.processprocess.group.idkeyword Unique identifier for the group on the system/platform.processprocess.group.namekeyword Name of the

group.processprocess.group_leader.argskeyword["/usr/bin/ssh", "-l", "user", "10.0.0.16"] Array of process arguments.processprocess.group_leader.args_countlong 4Length of the process.args array.processprocess.group_leader.command_linewildcard/usr/bin/ssh -l user 10.0.0.16 Full command line that started the process.processprocess.group_leader.command_line.textmatch_only_text/usr/bin/ssh -l user 10.0.0.16 Full command line that started the process.processprocess.group_leader.entity_idkeywordc2c455d9f99375d Unique identifier for the process.processprocess.group_leader.executablekeyword/usr/bin/ssh Absolute path to the process executable.processprocess.group_leader.executable.textmatch_only_text/usr/bin/ssh Absolute path to the process executable.processprocess.group_leader.group_idkeyword Unique identifier for the group on the system/platform.processprocess.group_leader.group.namekeyword Name of the group.processprocess.group_leader.interactiveboolean TRUE Whether the process is connected to an interactive shell.processprocess.group_leader.namekeywordssh Process name.processprocess.group_leader.name.textmatch_only_textssh Process name.processprocess.group_leader.pidlong 4242Process id.processprocess.group_leader.real_group.idkeyword Unique identifier for the group on the system/platform.processprocess.group_leader.real_group.namekeyword Name of the group.processprocess.group_leader.real_user.idkeywordS-1-5-21-202424912787-2692429404-2351956786-1000Unique identifier of the user.processprocess.group_leader.real_user.namekeyworda.einstein Short name or login of the user.processprocess.group_leader.real_user.name.textmatch_only_texta.einstein Short name or login of the user.processprocess.group_leader.same_as_processboolean TRUE This boolean is used to identify if a leader process is the same as the top level process.processprocess.group_leader.saved_group.idkeyword Unique identifier for the group on the system/platform.processprocess.group_leader.saved_group.namekeyword Name of the group.processprocess.group_leader.saved_user.idkeywordS-1-5-21-202424912787-2692429404-2351956786-1000Unique identifier of the user.processprocess.group_leader.saved_user.namekeyworda.einstein Short name or login of the user.processprocess.group_leader.saved_user.name.textmatch_only_texta.einstein Short name or login of the user.processprocess.group_leader.startdate 2016-05-23T08:05:34.853Z The time the process started.processprocess.group_leader.supplemental_groups.idkeyword Unique identifier for the group on the system/platform.processprocess.group_leader.supplemental_groups.namekeyword Name of the group.processprocess.group_leader.ttyobject Information about the controlling TTY device.processprocess.group_leader.tty.char_device.majorlong 4The TTY character device's major number.processprocess.group_leader.tty.char_device.minorlong 1The TTY character device's minor number.processprocess.group_leader.user.idkeywordS-1-5-21-202424912787-2692429404-2351956786-1000Unique identifier of the user.processprocess.group_leader.user.namekeyworda.einstein Short name or login of the user.processprocess.group_leader.user.name.textmatch_only_texta.einstein Short name or login of the user.processprocess.group_leader.vpidlong 4242Virtual process

id.processprocess.group_leader.working_directorykeyword/home/alice The working directory of the process.processprocess.group_leader.working_directory.textmatch_only_text/home/alice The working directory of the process.processprocess.hash.cdhashkeyword3783b4052fd474dbe30676b45c329e7a6d44acd9 The Code Directory (CD) hash of an executable.processprocess.hash.md5keyword MD5 hash.processprocess.hash.sha1keyword SHA1 hash.processprocess.hash.sha256keyword SHA256 hash.processprocess.hash.sha384keyword SHA384 hash.processprocess.hash.sha512keyword SHA512 hash.processprocess.hash.ssdeepkeyword SSDEEP hash.processprocess.hash.tlshkeyword TLSH hash.processprocess.interactiveboolean TRUE Whether the process is connected to an interactive shell.processprocess.ioobject A chunk of input or output (IO) from a single process.processprocess.io.bytes_skippedobject An array of byte offsets and lengths denoting where IO data has been skipped.processprocess.io.bytes_skipped.lengthlong The length of bytes skipped.processprocess.io.bytes_skipped.offsetlong The byte offset into this event's io.text (or io.bytes in the future) where length bytes were skipped.processprocess.io.max_bytes_per_process_exceededboolean If true, the process producing the output has exceeded the max_kilobytes_per_process configuration setting.processprocess.io.textwildcard A chunk of output or input sanitized to UTF-8.processprocess.io.total_bytes_capturedlong The total number of bytes captured in this event.processprocess.io.total_bytes_skippedlong The total number of bytes that were not captured due to implementation restrictions such as buffer size limits.processprocess.io.typekeyword The type of object on which the IO action (read or write) was taken.processprocess.macho.go_import_hashkeyword10bddcb4cee42080f76c88d9ff964491 A hash of the Go language imports in a Mach-O file.processprocess.macho.go_importsflattened List of imported Go language element names and types.processprocess.macho.go_imports_names_entropylong Shannon entropy calculation from the list of Go imports.processprocess.macho.go_imports_names_var_entropylong Variance for Shannon entropy calculation from the list of Go imports.processprocess.macho.go_strippedboolean Whether the file is a stripped or obfuscated Go executable.processprocess.macho.import_hashkeyworddd41d8cd98f00b204e9800998ecf8427e A hash of the imports in a Mach-O file.processprocess.macho.importsflattened List of imported element names and types.processprocess.macho.imports_names_entropylong Shannon entropy calculation from the list of imported element names and types.processprocess.macho.imports_names_var_entropylong Variance for Shannon entropy calculation from the list of imported element names and types.processprocess.macho.sectionsnested Section information of the Mach-O file.processprocess.macho.sections_entropylong Shannon entropy calculation from the section.processprocess.macho.sections.namekeyword Mach-O Section List name.processprocess.macho.sections.physical_sizealong Mach-O Section List physical size.processprocess.macho.sections.var_entropylong Variance for Shannon entropy calculation from the section.processprocess.macho.sections.virtual_sizealong Mach-O Section List virtual

size. This is always the same as

``physical_size`.processprocess.macho.symhashkeywordd3ccf195b62a9279c3c19af1080497ec`

A hash of the imports in a Mach-O file.`processprocess.namekeywordssh` Process

`name.processprocess.name.textmatch_only_textssh` Process

`name.processprocess.parent.argskeyword["/usr/bin/ssh", "-l", "user", "10.0.0.16"]` Array of

process arguments.`processprocess.parent.args_countlong 4`Length of the process.args

`array.processprocess.parent.code_signature.digest_algorithmkeywordsha256` Hashing

algorithm used to sign the process.`processprocess.parent.code_signature.existsboolean TRUE`

Boolean to capture if a signature is

present.`processprocess.parent.code_signature.flagskeyword 570522385`Code signing flags of

the process.`processprocess.parent.code_signature.signing_idkeywordcom.apple.xpc.proxy` The

identifier used to sign the

process.`processprocess.parent.code_signature.statuskeywordERROR_UNTRUSTED_ROOT`

Additional information about the certificate

`status.processprocess.parent.code_signature.subject_namekeywordMicrosoft Corporation`

Subject name of the code

`signerprocessprocess.parent.code_signature.team_idkeywordEQHXZ8M8AV` The team

identifier used to sign the process.`processprocess.parent.code_signature.timestampdate`

2021-01-01T12:10:30Z When the signature was generated and

signed.`processprocess.parent.code_signature.trustedboolean TRUE` Stores the trust status of

the certificate chain.`processprocess.parent.code_signature.validboolean TRUE` Boolean to

capture if the digital signature is verified against the binary

`content.processprocess.parent.command_linekeyword/usr/bin/ssh -l user 10.0.0.16` Full

command line that started the

process.`processprocess.parent.command_line.textmatch_only_text/usr/bin/ssh -l user 10.0.0.16`

Full command line that started the process.

Field Set: `processprocess.parent.elf.architecturekeywordx86-64` | Field: Machine | Type:

architecture | Example: of the | Description: ELF

`file.processprocess.parent.elf.byte_orderkeywordLittle` Endian Byte sequence of ELF

`file.processprocess.parent.elf.cpu_typekeywordIntel` CPU type of the ELF

`file.processprocess.parent.elf.creation_datedate` Build or compile

date.`processprocess.parent.elf.exportsflattened` List of exported element names and

types.`processprocess.parent.elf.go_import_hashkeyword10bddcb4cee42080f76c88d9ff964491`

A hash of the Go language imports in an ELF file.`processprocess.parent.elf.go_importsflattened`

List of imported Go language element names and

types.`processprocess.parent.elf.go_imports_names_entropylong` Shannon entropy calculation

from the list of Go imports.`processprocess.parent.elf.go_imports_names_var_entropylong`

Variance for Shannon entropy calculation from the list of Go

`imports.processprocess.parent.elf.go_strippedboolean` Whether the file is a stripped or

obfuscated Go executable.`processprocess.parent.elf.header.abi_versionkeyword` Version of the

ELF Application Binary Interface (ABI).`processprocess.parent.elf.header.classkeyword` Header

class of the ELF file.`processprocess.parent.elf.header.datakeyword` Data table of the ELF

header.`processprocess.parent.elf.header.entrypointlong` Header entrypoint of the ELF

file.processprocess.parent.elf.header.object_versionkeyword "0x1" for original ELF
files.processprocess.parent.elf.header.os_abikeyword Application Binary Interface (ABI) of the
Linux OS.processprocess.parent.elf.header.typekeyword Header type of the ELF
file.processprocess.parent.elf.header.versionkeyword Version of the ELF
header.processprocess.parent.elf.import_hashkeyworddd41d8cd98f00b204e9800998ecf8427e A
hash of the imports in an ELF file.processprocess.parent.elf.importsflattened List of imported
element names and types.processprocess.parent.elf.imports_names_entropylong Shannon
entropy calculation from the list of imported element names and
types.processprocess.parent.elf.imports_names_var_entropylong Variance for Shannon entropy
calculation from the list of imported element names and
types.processprocess.parent.elf.sectionsnested Section information of the ELF
file.processprocess.parent.elf.sections.chi2long Chi-square probability distribution of the
section.processprocess.parent.elf.sections.entropylong Shannon entropy calculation from the
section.processprocess.parent.elf.sections.flagskeyword ELF Section List
flags.processprocess.parent.elf.sections.namekeyword ELF Section List
name.processprocess.parent.elf.sections.physical_offsetkeyword ELF Section List
offset.processprocess.parent.elf.sections.physical_sizelong ELF Section List physical
size.processprocess.parent.elf.sections.typekeyword ELF Section List
type.processprocess.parent.elf.sections.var_entropylong Variance for Shannon entropy
calculation from the section.processprocess.parent.elf.sections.virtual_addresslong ELF Section
List virtual address.processprocess.parent.elf.sections.virtual_sizelong ELF Section List virtual
size.processprocess.parent.elf.segmentsnested ELF object segment
list.processprocess.parent.elf.segments.sectionskeyword ELF object segment
sections.processprocess.parent.elf.segments.typekeyword ELF object segment
type.processprocess.parent.elf.shared_librarieskeyword List of shared libraries used by this ELF
object.processprocess.parent.elf.telfhashkeyword telfhash hash for ELF
file.processprocess.parent.enddate 2016-05-23T08:05:34.853Z The time the process
ended.processprocess.parent.entity_idkeywordc2c455d9f99375d Unique identifier for the
process.processprocess.parent.executablekeyword/usr/bin/ssh Absolute path to the process
executable.processprocess.parent.executable.textmatch_only_text/usr/bin/ssh Absolute path to
the process executable.processprocess.parent.exit_codelong 137The exit code of the
process.processprocess.parent.group.idkeyword Unique identifier for the group on the
system/platform.processprocess.parent.group.namekeyword Name of the
group.processprocess.parent.group_leader.entity_idkeywordc2c455d9f99375d Unique identifier
for the process.processprocess.parent.group_leader.pidlong 4242Process
id.processprocess.parent.group_leader.startdate 2016-05-23T08:05:34.853Z The time the
process started.processprocess.parent.group_leader.vpidlong 4242Virtual process
id.processprocess.parent.hash.cdhashkeyword3783b4052fd474dbe30676b45c329e7a6d44acd
9The Code Directory (CD) hash of an executable.processprocess.parent.hash.md5keyword
MD5 hash.processprocess.parent.hash.sha1keyword SHA1
hash.processprocess.parent.hash.sha256keyword SHA256
hash.processprocess.parent.hash.sha384keyword SHA384
hash.processprocess.parent.hash.sha512keyword SHA512

hash.processprocess.parent.hash.ssdeepkeyword SSDEEP
hash.processprocess.parent.hash.tlshkeyword TLSH
hash.processprocess.parent.interactiveboolean TRUE Whether the process is connected to an interactive
shell.processprocess.parent.macho.go_import_hashkeyword10bddcb4cee42080f76c88d9ff964491 A hash of the Go language imports in a Mach-O
file.processprocess.parent.macho.go_importsflattened List of imported Go language element names and types.processprocess.parent.macho.go_imports_names_entropylong Shannon entropy calculation from the list of Go
imports.processprocess.parent.macho.go_imports_names_var_entropylong Variance for Shannon entropy calculation from the list of Go
imports.processprocess.parent.macho.go_strippedboolean Whether the file is a stripped or obfuscated Go
executable.processprocess.parent.macho.import_hashkeywordd41d8cd98f00b204e9800998ecf8427e A hash of the imports in a Mach-O file.processprocess.parent.macho.importsflattened List of imported element names and
types.processprocess.parent.macho.imports_names_entropylong Shannon entropy calculation from the list of imported element names and
types.processprocess.parent.macho.imports_names_var_entropylong Variance for Shannon entropy calculation from the list of imported element names and
types.processprocess.parent.macho.sectionsnested Section information of the Mach-O file.processprocess.parent.macho.sections_entropylong Shannon entropy calculation from the section.processprocess.parent.macho.sections.namekeyword Mach-O Section List
name.processprocess.parent.macho.sections.physical_sizekeyword Mach-O Section List physical size.processprocess.parent.macho.sections.var_entropylong Variance for Shannon entropy calculation from the section.processprocess.parent.macho.sections.virtual_sizekeyword Mach-O Section List virtual size. This is always the same as
`physical\_size`.processprocess.parent.macho.symhashkeywordd3ccf195b62a9279c3c19af1080497ec A hash of the imports in a Mach-O file.processprocess.parent.namekeywordssh Process name.processprocess.parent.name.textmatch_only_textssh Process
name.processprocess.parent.pe.architecturekeywordx64 CPU architecture target for the file.processprocess.parent.pe.companykeywordMicrosoft Corporation Internal company name of the file, provided at compile-time.processprocess.parent.pe.descriptionkeywordPaint Internal description of the file, provided at
compile-time.processprocess.parent.pe.file_versionkeyword6.3.9600.17415 Process name.processprocess.parent.pe.go_import_hashkeyword10bddcb4cee42080f76c88d9ff964491 A hash of the Go language imports in a PE file.processprocess.parent.pe.go_importsflattened List of imported Go language element names and
types.processprocess.parent.pe.go_imports_names_entropylong Shannon entropy calculation from the list of Go imports.processprocess.parent.pe.go_imports_names_var_entropylong Variance for Shannon entropy calculation from the list of Go
imports.processprocess.parent.pe.go_strippedboolean Whether the file is a stripped or obfuscated Go

executable.processprocess.parent.pe.imphashkeyword0c6803c4e922103c4dca5963aad36ddf
A hash of the imports in a PE

file.processprocess.parent.pe.import_hashkeywordd41d8cd98f00b204e9800998ecf8427e A
hash of the imports in a PE file.processprocess.parent.pe.importsflattened List of imported
element names and types.processprocess.parent.pe.imports_names_entropylong Shannon
entropy calculation from the list of imported element names and
types.processprocess.parent.pe.imports_names_var_entropylong Variance for Shannon entropy
calculation from the list of imported element names and
types.processprocess.parent.pe.original_file_namekeywordMSPAIN.T.EXE Internal name of the
file, provided at

compile-time.processprocess.parent.pe.pehashkeyword73ff189b63cd6be375a7ff25179a38d347
651975A hash of the PE header and data from one or more PE

sections.processprocess.parent.pe.productkeywordMicrosoft® Windows® Operating System
Internal product name of the file, provided at

compile-time.processprocess.parent.pe.sectionsnested Section information of the PE
file.processprocess.parent.pe.sections_entropylong Shannon entropy calculation from the
section.processprocess.parent.pe.sections.namekeyword PE Section List
name.processprocess.parent.pe.sections.physical_sizeelong PE Section List physical
size.processprocess.parent.pe.sections.var_entropylong Variance for Shannon entropy
calculation from the section.processprocess.parent.pe.sections.virtual_sizeelong PE Section List
virtual size. This is always the same as `physical\_size`.processprocess.parent.pgidlong
Deprecated identifier of the group of processes the process belongs
to.processprocess.parent.pidlong 4242Process id.processprocess.parent.real_group.idkeyword
Unique identifier for the group on the
system/platform.processprocess.parent.real_group.namekeyword Name of the
group.processprocess.parent.real_user.idkeywordS-1-5-21-202424912787-2692429404-23519
56786-1000Unique identifier of the
user.processprocess.parent.real_user.namekeyworda.einstein Short name or login of the
user.processprocess.parent.real_user.name.textmatch_only_texta.einstein Short name or login
of the user.processprocess.parent.saved_group.idkeyword Unique identifier for the group on the
system/platform.processprocess.parent.saved_group.namekeyword Name of the
group.processprocess.parent.saved_user.idkeywordS-1-5-21-202424912787-2692429404-2351
956786-1000Unique identifier of the
user.processprocess.parent.saved_user.namekeyworda.einstein Short name or login of the
user.processprocess.parent.saved_user.name.textmatch_only_texta.einstein Short name or
login of the user.processprocess.parent.startdate 2016-05-23T08:05:34.853Z The time the
process started.processprocess.parent.supplemental_groups.idkeyword Unique identifier for the
group on the system/platform.processprocess.parent.supplemental_groups.namekeyword
Name of the group.processprocess.parent.thread.capabilities.effectivekeyword["CAP_BPF",
"CAP_SYS_ADMIN"] Array of capabilities used for permission
checks.processprocess.parent.thread.capabilities.permittedkeyword["CAP_BPF",
"CAP_SYS_ADMIN"] Array of capabilities a thread could
assume.processprocess.parent.thread.idlong 4242Thread

ID.processprocess.parent.thread.namekeywordthread-0 Thread
 name.processprocess.parent.titlekeyword Process
 title.processprocess.parent.title.textmatch_only_text Process
 title.processprocess.parent.ttyobject Information about the controlling TTY
 device.processprocess.parent.tty.char_device.majorlong 4The TTY character device's major
 number.processprocess.parent.tty.char_device.minorlong 1The TTY character device's minor
 number.processprocess.parent.uptimekeyword 1325Seconds the process has been
 up.processprocess.parent.user.idkeywordS-1-5-21-202424912787-2692429404-2351956786-1
 000Unique identifier of the user.processprocess.parent.user.namekeyworda.einstein Short
 name or login of the user.processprocess.parent.user.name.textmatch_only_texta.einstein Short
 name or login of the user.processprocess.parent.vpidlong 4242Virtual process
 id.processprocess.parent.working_directorykeyword/home/alice The working directory of the
 process.processprocess.parent.working_directory.textmatch_only_text/home/alice The working
 directory of the process.
 Field Set: processprocess.pe.architecturekeywordx64 | Field: CPU | Type: architecture |
 Example: target for the file.processprocess.pe.companykeywordMicrosoft | Description:
 Corporation Internal company name of the file, provided at
 compile-time.processprocess.pe.descriptionkeywordPaint Internal description of the file,
 provided at compile-time.processprocess.pe.file_versionkeyword6.3.9600.17415 Process
 name.processprocess.pe.go_import_hashkeyword10bddcb4cee42080f76c88d9ff964491 A hash
 of the Go language imports in a PE file.processprocess.pe.go_importsflattened List of imported
 Go language element names and types.processprocess.pe.go_imports_names_entropylong
 Shannon entropy calculation from the list of Go
 imports.processprocess.pe.go_imports_names_var_entropylong Variance for Shannon entropy
 calculation from the list of Go imports.processprocess.pe.go_strippedboolean Whether the file is
 a stripped or obfuscated Go
 executable.processprocess.pe.imphashkeyword0c6803c4e922103c4dca5963aad36ddf A hash
 of the imports in a PE
 file.processprocess.pe.import_hashkeyworddd41d8cd98f00b204e9800998ecf8427e A hash of
 the imports in a PE file.processprocess.pe.importsflattened List of imported element names and
 types.processprocess.pe.imports_names_entropylong Shannon entropy calculation from the list
 of imported element names and types.processprocess.pe.imports_names_var_entropylong
 Variance for Shannon entropy calculation from the list of imported element names and
 types.processprocess.pe.original_file_namekeywordMSPAINTEXE Internal name of the file,
 provided at
 compile-time.processprocess.pe.pehashkeyword73ff189b63cd6be375a7ff25179a38d34765197
 5A hash of the PE header and data from one or more PE
 sections.processprocess.pe.productkeywordMicrosoft® Windows® Operating System Internal
 product name of the file, provided at compile-time.processprocess.pe.sectionsnested Section
 information of the PE file.processprocess.pe.sections_entropylong Shannon entropy calculation
 from the section.processprocess.pe.sections.namekeyword PE Section List
 name.processprocess.pe.sections.physical_sizekeyword PE Section List physical
 size.processprocess.pe.sections.var_entropylong Variance for Shannon entropy calculation

from the section.processprocess.pe.sections.virtual_size:long PE Section List virtual size. This is always the same as `physical\_size`.processprocess.pgid:long Deprecated identifier of the group of processes the process belongs to.processprocess.pid:long 4242Process id.processprocess.previous.args:keyword["/usr/bin/ssh", "-l", "user", "10.0.0.16"] Array of process arguments.processprocess.previous.args_count:long 4Length of the process.args array.processprocess.previous.executable:keyword/usr/bin/ssh Absolute path to the process executable.processprocess.previous.executable.textmatch_only_text/usr/bin/ssh Absolute path to the process executable.processprocess.real_group.id:keyword Unique identifier for the group on the system/platform.processprocess.real_group.name:keyword Name of the group.processprocess.real_user.id:keywordS-1-5-21-202424912787-2692429404-2351956786-1000Unique identifier of the user.processprocess.real_user.name:keyworda.einstein Short name or login of the user.processprocess.real_user.name.textmatch_only_texta.einstein Short name or login of the user.processprocess.saved_group.id:keyword Unique identifier for the group on the system/platform.processprocess.saved_group.name:keyword Name of the group.processprocess.saved_user.id:keywordS-1-5-21-202424912787-2692429404-2351956786-1000Unique identifier of the user.processprocess.saved_user.name:keyworda.einstein Short name or login of the user.processprocess.saved_user.name.textmatch_only_texta.einstein Short name or login of the user.processprocess.session_leader.args:keyword["/usr/bin/ssh", "-l", "user", "10.0.0.16"] Array of process arguments.processprocess.session_leader.args_count:long 4Length of the process.args array.processprocess.session_leader.command_line:wildcard/usr/bin/ssh -l user 10.0.0.16 Full command line that started the process.processprocess.session_leader.command_line.textmatch_only_text/usr/bin/ssh -l user 10.0.0.16 Full command line that started the process.processprocess.session_leader.entity_id:keywordc2c455d9f99375d Unique identifier for the process.processprocess.session_leader.executable:keyword/usr/bin/ssh Absolute path to the process executable.processprocess.session_leader.executable.textmatch_only_text/usr/bin/ssh Absolute path to the process executable.processprocess.session_leader.group.id:keyword Unique identifier for the group on the system/platform.processprocess.session_leader.group.name:keyword Name of the group.processprocess.session_leader.interactive:boolean TRUE Whether the process is connected to an interactive shell.processprocess.session_leader.name:keywordssh Process name.processprocess.session_leader.name.textmatch_only_textssh Process name.processprocess.session_leader.parent.entity_id:keywordc2c455d9f99375d Unique identifier for the process.processprocess.session_leader.parent.pid:long 4242Process id.processprocess.session_leader.parent.session_leader.entity_id:keywordc2c455d9f99375d Unique identifier for the process.processprocess.session_leader.parent.session_leader.pid:long 4242Process id.processprocess.session_leader.parent.session_leader.startdate 2016-05-23T08:05:34.853Z The time the process started.processprocess.session_leader.parent.session_leader.vpid:long 4242Virtual process id.processprocess.session_leader.parent.startdate 2016-05-23T08:05:34.853Z The time the process started.processprocess.session_leader.parent.vpid:long 4242Virtual process id.processprocess.session_leader.pid:long 4242Process

id.processprocess.session_leader.real_group.idkeyword Unique identifier for the group on the system/platform.processprocess.session_leader.real_group.namekeyword Name of the group.processprocess.session_leader.real_user.idkeywordS-1-5-21-202424912787-2692429404-2351956786-1000Unique identifier of the user.processprocess.session_leader.real_user.namekeyworda.einstein Short name or login of the user.processprocess.session_leader.real_user.name.textmatch_only_texta.einstein Short name or login of the user.processprocess.session_leader.same_as_processboolean TRUE This boolean is used to identify if a leader process is the same as the top level process.processprocess.session_leader.saved_group.idkeyword Unique identifier for the group on the system/platform.processprocess.session_leader.saved_group.namekeyword Name of the group.processprocess.session_leader.saved_user.idkeywordS-1-5-21-202424912787-2692429404-2351956786-1000Unique identifier of the user.processprocess.session_leader.saved_user.namekeyworda.einstein Short name or login of the user.processprocess.session_leader.saved_user.name.textmatch_only_texta.einstein Short name or login of the user.processprocess.session_leader.startdate 2016-05-23T08:05:34.853Z The time the process started.processprocess.session_leader.supplemental_groups.idkeyword Unique identifier for the group on the system/platform.processprocess.session_leader.supplemental_groups.namekeyword Name of the group.processprocess.session_leader.ttyobject Information about the controlling TTY device.processprocess.session_leader.tty.char_device.majorlong 4The TTY character device's major number.processprocess.session_leader.tty.char_device.minorlong 1The TTY character device's minor number.processprocess.session_leader.user.idkeywordS-1-5-21-202424912787-2692429404-2351956786-1000Unique identifier of the user.processprocess.session_leader.user.namekeyworda.einstein Short name or login of the user.processprocess.session_leader.user.name.textmatch_only_texta.einstein Short name or login of the user.processprocess.session_leader.vpidlong 4242Virtual process id.processprocess.session_leader.working_directorykeyword/home/alice The working directory of the process.processprocess.session_leader.working_directory.textmatch_only_text/home/alice The working directory of the process.processprocess.startdate 2016-05-23T08:05:34.853Z The time the process started.processprocess.supplemental_groups.idkeyword Unique identifier for the group on the system/platform.processprocess.supplemental_groups.namekeyword Name of the group.processprocess.thread.capabilities.effectivekeyword["CAP_BPF", "CAP_SYS_ADMIN"] Array of capabilities used for permission checks.processprocess.thread.capabilities.permittedkeyword["CAP_BPF", "CAP_SYS_ADMIN"] Array of capabilities a thread could assume.processprocess.thread.idlong 4242Thread ID.processprocess.thread.namekeywordthread-0 Thread name.processprocess.titlekeyword Process title.processprocess.title.textmatch_only_text Process title.processprocess.ttyobject Information about the controlling TTY device.processprocess.tty.char_device.majorlong 4The TTY character device's major number.processprocess.tty.char_device.minorlong 1The TTY character device's minor number.processprocess.tty.columnslong 80The number of character

columns per line. e.g terminal widthprocessprocess.tty.rowslong 24The number of character rows in the terminal. e.g terminal heightprocessprocess.uptimelong 1325Seconds the process has been

up.processprocess.user.idkeywordS-1-5-21-202424912787-2692429404-2351956786-1000Unique identifier of the user.processprocess.user.namekeyworda.einstein Short name or login of the user.processprocess.user.name.textmatch_only_texta.einstein Short name or login of the user.processprocess.vpidlong 4242Virtual process

id.processprocess.working_directorykeyword/home/alice The working directory of the process.processprocess.working_directory.textmatch_only_text/home/alice The working directory of the

process.registryregistry.data.byteskeywordZQBuAC0AVQBTAAAAZQBuAAAAAAA= Original bytes written with base64 encoding.registryregistry.data.stringswildcard["C:\rta\red_ttp\bin\myapp.exe"] List of strings representing what was written to the registry.registryregistry.data.typekeywordREG_SZ Standard registry type for encoding contentsregistryregistry.hivekeywordHKLM Abbreviated name for the hive.registryregistry.keykeywordSOFTWARE\Microsoft\Windows NT\CurrentVersion\Image File Execution Options\winword.exeHive-relative path of keys.registryregistry.pathkeywordHKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Image File Execution Options\winword.exe\DebuggerFull path, including hive, key and valueregistryregistry.valuekeywordDebugger Name of the value written.relatedrelated.hashkeyword All the hashes seen on your event.relatedrelated.hostskeyword All the host identifiers seen on your event.relatedrelated.ipip All of the IPs seen on your event.relatedrelated.userkeyword All the user names or other user identifiers seen on the event.rule.rule.authorkeyword["Star-Lord"] Rule authorrule.rule.categorykeywordAttempted Information Leak Rule categoryrule.rule.descriptionkeywordBlock requests to public DNS over HTTPS / TLS protocolsRule descriptionrule.rule.idkeyword 101Rule IDrule.rule.licensekeywordApache 2.0 Rule licenserule.rule.namekeywordBLOCK_DNS_over_TLS Rule namerule.rule.referencekeywordhttps://en.wikipedia.org/wiki/DNS_over_TLS Rule reference URLrule.rule.rulesetkeywordStandard_Protocol_Filters Rule rulesetrule.rule.uuidkeyword 1100110011Rule UUIDrule.rule.versionkeyword 1.1Rule versionserverserver.addresskeyword Server network address.serverserver.as.numberlong 15169Unique number allocated to the autonomous system.serverserver.as.organization.namekeywordGoogle LLC Organization name.serverserver.as.organization.name.textmatch_only_textGoogle LLC Organization name.serverserver.byteslong 184Bytes sent from the server to the client.

Field Set: serverserver.domainkeywordfoo.example.com | Field: The | Type: domain | Example: name of the server.serverserver.geo.city_namekeywordMontreal | Description: City name.serverserver.geo.continent_codekeywordNA Continent code.serverserver.geo.continent_namekeywordNorth America Name of the continent.serverserver.geo.country_iso_codekeywordCA Country ISO code.serverserver.geo.country_namekeywordCanada Country name.serverserver.geo.locationgeo_point{ "lon": -73.614830, "lat": 45.505918 } Longitude and latitude.serverserver.geo.namekeywordboston-dc User-defined description of a

location.serverserver.geo.postal_codekeyword 94040Postal
code.serverserver.geo.region_iso_codekeywordCA-QC Region ISO
code.serverserver.geo.region_namekeywordQuebec Region
name.serverserver.geo.timezonekeywordAmerica/Argentina/Buenos_Aires Time
zone.serverserver.ipip IP address of the server.serverserver.mackeyword00-00-5E-00-53-23
MAC address of the server.serverserver.nat.ipip Server NAT ipserverserver.nat.portlong Server
NAT portserverserver.packetslong 12Packets sent from the server to the
client.serverserver.portlong Port of the
server.serverserver.registered_domainkeywordexample.com The highest registered server
domain, stripped of the subdomain.serverserver.subdomainkeywordeast The subdomain of the
domain.serverserver.top_level_domainkeywordco.uk The effective top level domain (com, org,
net, co.uk).serverserver.user.domainkeyword Name of the directory the user is a member
of.serverserver.user.emailkeyword User email
address.serverserver.user.full_namekeywordAlbert Einstein User's full name, if
available.serverserver.user.full_name.textmatch_only_textAlbert Einstein User's full name, if
available.serverserver.user.group.domainkeyword Name of the directory the group is a member
of.serverserver.user.group.idkeyword Unique identifier for the group on the
system/platform.serverserver.user.group.namekeyword Name of the
group.serverserver.user.hashkeyword Unique user hash to correlate information for a user in
anonymized
form.serverserver.user.idkeywordS-1-5-21-202424912787-2692429404-2351956786-1000Uniq
ue identifier of the user.serverserver.user.namekeyworda.einstein Short name or login of the
user.serverserver.user.name.textmatch_only_texta.einstein Short name or login of the
user.serverserver.user.roleskeyword["kibana_admin", "reporting_user"] Array of user roles at the
time of the event.serviceservice.addresskeyword172.26.0.2:5432 Address of this
service.serviceservice.environmentkeywordproduction Environment of the
service.serviceservice.ephemeral_idkeyword8a4f500f Ephemeral identifier of this
service.serviceservice.idkeywordd37e5ebfe0ae6c4972dbe9f0174a1637bb8247f6Unique
identifier of the running service.serviceservice.namekeywordelasticsearch-metrics Name of the
service.serviceservice.node.namekeywordinstance-0000000016 Name of the service
node.serviceservice.node.rolekeywordbackground_tasks Deprecated role (singular) of the
service node.serviceservice.node.roleskeyword["ui", "background_tasks"] Roles of the service
node.serviceservice.origin.addresskeyword172.26.0.2:5432 Address of this
service.serviceservice.origin.environmentkeywordproduction Environment of the
service.serviceservice.origin.ephemeral_idkeyword8a4f500f Ephemeral identifier of this
service.serviceservice.origin.idkeywordd37e5ebfe0ae6c4972dbe9f0174a1637bb8247f6Unique
identifier of the running service.serviceservice.origin.namekeywordelasticsearch-metrics Name
of the service.serviceservice.origin.node.namekeywordinstance-0000000016 Name of the
service node.serviceservice.origin.node.rolekeywordbackground_tasks Deprecated role
(singular) of the service node.serviceservice.origin.node.roleskeyword["ui", "background_tasks"]
Roles of the service node.serviceservice.origin.statekeyword Current state of the
service.serviceservice.origin.typekeywordelasticsearch The type of the
service.serviceservice.origin.versionkeyword3.2.4 Version of the

service.serviceservice.statekeyword Current state of the
 service.serviceservice.target.addresskeyword172.26.0.2:5432 Address of this
 service.serviceservice.target.environmentkeywordproduction Environment of the
 service.serviceservice.target.ephemeral_idkeyword8a4f500f Ephemeral identifier of this
 service.serviceservice.target.idkeyworddd37e5ebfe0ae6c4972dbe9f0174a1637bb8247f6Unique
 identifier of the running service.serviceservice.target.namekeywordelasticsearch-metrics Name
 of the service.serviceservice.target.node.namekeywordinstance-0000000016 Name of the
 service node.serviceservice.target.node.rolekeywordbackground_tasks Deprecated role
 (singular) of the service node.serviceservice.target.node.roleskeyword["ui", "background_tasks"]
 Roles of the service node.serviceservice.target.statekeyword Current state of the
 service.serviceservice.target.typekeywordelasticsearch The type of the
 service.serviceservice.target.versionkeyword3.2.4 Version of the
 service.serviceservice.typekeywordelasticsearch The type of the
 service.serviceservice.versionkeyword3.2.4 Version of the
 service.sourcesource.addresskeyword Source network address.sourcesource.as.numberlong
 15169Unique number allocated to the autonomous
 system.sourcesource.as.organization.namekeywordGoogle LLC Organization
 name.sourcesource.as.organization.name.textmatch_only_textGoogle LLC Organization
 name.sourcesource.byteslong 184Bytes sent from the source to the
 destination.sourcesource.domainkeywordfoo.example.com The domain name of the
 source.sourcesource.geo.city_namekeywordMontreal City
 name.sourcesource.geo.continent_codekeywordNA Continent
 code.sourcesource.geo.continent_namekeywordNorth America Name of the
 continent.sourcesource.geo.country_iso_codekeywordCA Country ISO
 code.sourcesource.geo.country_namekeywordCanada Country
 name.sourcesource.geo.locationgeo_point{ "lon": -73.614830, "lat": 45.505918 } Longitude and
 latitude.sourcesource.geo.namekeywordboston-dc User-defined description of a
 location.sourcesource.geo.postal_codekeyword 94040Postal
 code.sourcesource.geo.region_iso_codekeywordCA-QC Region ISO
 code.sourcesource.geo.region_namekeywordQuebec Region
 name.sourcesource.geo.timezonekeywordAmerica/Argentina/Buenos_Aires Time
 zone.sourcesource.ipip IP address of the source.sourcesource.mackeyword00-00-5E-00-53-23
 MAC address of the source.sourcesource.nat.ipip Source NAT ipsourcesource.nat.portlong
 Source NAT portsourcesource.packetslong 12Packets sent from the source to the
 destination.sourcesource.portlong Port of the
 source.sourcesource.registered_domainkeywordexample.com The highest registered source
 domain, stripped of the subdomain.sourcesource.subdomainkeywordeast The subdomain of the
 domain.sourcesource.top_level_domainkeywordco.uk The effective top level domain (com, org,
 net, co.uk).sourcesource.user.domainkeyword Name of the directory the user is a member
 of.sourcesource.user.emailkeyword User email
 address.sourcesource.user.full_namekeywordAlbert Einstein User's full name, if
 available.sourcesource.user.full_name.textmatch_only_textAlbert Einstein User's full name, if
 available.sourcesource.user.group.domainkeyword Name of the directory the group is a

member of.source.source.user.group.id.keyword Unique identifier for the group on the system/platform.source.source.user.group.name.keyword Name of the group.source.source.user.hash.keyword Unique user hash to correlate information for a user in anonymized form.source.source.user.id.keyword S-1-5-21-202424912787-2692429404-2351956786-1000 Unique identifier of the user.source.source.user.name.keyword a.einstein Short name or login of the user.source.source.user.name.textmatch_only_text a.einstein Short name or login of the user.source.source.user.roles.keyword ["kibana_admin", "reporting_user"] Array of user roles at the time of the event.span.span.id.keyword 3ff9a8981b7ccd5a Unique identifier of the span within the scope of its trace.threat.threat.enrichments.nested List of objects containing indicators enriching the event.threat.threat.enrichments.indicator.object Object containing indicators enriching the event.threat.threat.enrichments.indicator.as.number.long 15169 Unique number allocated to the autonomous system.threat.threat.enrichments.indicator.as.organization.name.keyword Google LLC Organization name.threat.threat.enrichments.indicator.as.organization.name.textmatch_only_text Google LLC Organization name.threat.threat.enrichments.indicator.confidence.keyword Medium Indicator confidence rating.threat.threat.enrichments.indicator.description.keyword IP x.x.x.x was observed delivering the Angler EK.Indicator description.threat.threat.enrichments.indicator.email.address.keyword phishing@example.com Indicator email address.threat.threat.enrichments.indicator.file.accessed.date Last time the file was accessed.threat.threat.enrichments.indicator.file.attributes.keyword ["readonly", "system"] Array of file attributes.threat.threat.enrichments.indicator.file.code_signature.digest_algorithm.keyword sha256 Hashing algorithm used to sign the process.threat.threat.enrichments.indicator.file.code_signature.exists.boolean TRUE Boolean to capture if a signature is present.threat.threat.enrichments.indicator.file.code_signature.flags.keyword 570522385 Code signing flags of the process.threat.threat.enrichments.indicator.file.code_signature.signing_id.keyword com.apple.xpc.proxy The identifier used to sign the process.threat.threat.enrichments.indicator.file.code_signature.status.keyword ERROR_UNTRUSTED_ROOT Additional information about the certificate status.threat.threat.enrichments.indicator.file.code_signature.subject_name.keyword Microsoft Corporation Subject name of the code signer.threat.threat.enrichments.indicator.file.code_signature.team_id.keyword EQHXZ8M8AV The team identifier used to sign the process.threat.threat.enrichments.indicator.file.code_signature.timestamp.date 2021-01-01T12:10:30Z When the signature was generated and signed.threat.threat.enrichments.indicator.file.code_signature.trusted.boolean TRUE Stores the trust status of the certificate chain.threat.threat.enrichments.indicator.file.code_signature.valid.boolean TRUE Boolean to capture if the digital signature is verified against the binary

content.threatthreat.enrichments.indicator.file.createddate File creation time.threatthreat.enrichments.indicator.file.ctimedate Last time the file attributes or metadata changed.threatthreat.enrichments.indicator.file.devicekeywordssa Device that is the source of the file.threatthreat.enrichments.indicator.file.directorykeyword/home/alice Directory where the file is located.threatthreat.enrichments.indicator.file.drive_letterkeywordC Drive letter where the file is located.

Field Set: threatthreat.enrichments.indicator.file.elf.architecturekeywordx86-64 | Field: Machine | Type: architecture | Example: of the | Description: ELF

file.threatthreat.enrichments.indicator.file.elf.byte_orderkeywordLittle Endian Byte sequence of ELF file.threatthreat.enrichments.indicator.file.elf.cpu_typekeywordIntel CPU type of the ELF file.threatthreat.enrichments.indicator.file.elf.creation_datedate Build or compile date.threatthreat.enrichments.indicator.file.elf.exportsflattened List of exported element names and types.threatthreat.enrichments.indicator.file.elf.go_import_hashkeyword10bddcb4cee42080f76c88d9ff964491 A hash of the Go language imports in an ELF file.threatthreat.enrichments.indicator.file.elf.go_importsflattened List of imported Go language element names and types.threatthreat.enrichments.indicator.file.elf.go_imports_names_entropylong Shannon entropy calculation from the list of Go imports.threatthreat.enrichments.indicator.file.elf.go_imports_names_var_entropylong Variance for Shannon entropy calculation from the list of Go imports.threatthreat.enrichments.indicator.file.elf.go_strippedboolean Whether the file is a stripped or obfuscated Go executable.threatthreat.enrichments.indicator.file.elf.header.abi_versionkeyword Version of the ELF Application Binary Interface (ABI).threatthreat.enrichments.indicator.file.elf.header.classkeyword Header class of the ELF file.threatthreat.enrichments.indicator.file.elf.header.datakeyword Data table of the ELF header.threatthreat.enrichments.indicator.file.elf.header.entripointlong Header entripoint of the ELF file.threatthreat.enrichments.indicator.file.elf.header.object_versionkeyword "0x1" for original ELF files.threatthreat.enrichments.indicator.file.elf.header.os_abikeyword Application Binary Interface (ABI) of the Linux OS.threatthreat.enrichments.indicator.file.elf.header.typekeyword Header type of the ELF file.threatthreat.enrichments.indicator.file.elf.header.versionkeyword Version of the ELF header.threatthreat.enrichments.indicator.file.elf.import_hashkeywordd41d8cd98f00b204e9800998ecf8427e A hash of the imports in an ELF file.threatthreat.enrichments.indicator.file.elf.importsflattened List of imported element names and types.threatthreat.enrichments.indicator.file.elf.imports_names_entropylong Shannon entropy calculation from the list of imported element names and types.threatthreat.enrichments.indicator.file.elf.imports_names_var_entropylong Variance for Shannon entropy calculation from the list of imported element names and types.threatthreat.enrichments.indicator.file.elf.sectionsnested Section information of the ELF file.threatthreat.enrichments.indicator.file.elf.sections.chi2long Chi-square probability distribution of the section.threatthreat.enrichments.indicator.file.elf.sections.entropylong Shannon entropy

calculation from the section.threatthreat.enrichments.indicator.file.elf.sections.flagskeyword ELF
 Section List flags.threatthreat.enrichments.indicator.file.elf.sections.namekeyword ELF Section
 List name.threatthreat.enrichments.indicator.file.elf.sections.physical_offsetkeyword ELF
 Section List offset.threatthreat.enrichments.indicator.file.elf.sections.physical_sizekeyword ELF
 Section List physical size.threatthreat.enrichments.indicator.file.elf.sections.typekeyword ELF
 Section List type.threatthreat.enrichments.indicator.file.elf.sections.var_entropylong Variance for
 Shannon entropy calculation from the
 section.threatthreat.enrichments.indicator.file.elf.sections.virtual_addresslong ELF Section List
 virtual address.threatthreat.enrichments.indicator.file.elf.sections.virtual_sizekeyword ELF Section
 List virtual size.threatthreat.enrichments.indicator.file.elf.segmentsnested ELF object segment
 list.threatthreat.enrichments.indicator.file.elf.segments.sectionskeyword ELF object segment
 sections.threatthreat.enrichments.indicator.file.elf.segments.typekeyword ELF object segment
 type.threatthreat.enrichments.indicator.file.elf.shared_librarieskeyword List of shared libraries
 used by this ELF object.threatthreat.enrichments.indicator.file.elf.telfhashkeyword telfhash hash
 for ELF file.threatthreat.enrichments.indicator.file.extensionkeywordpng File extension,
 excluding the leading
 dot.threatthreat.enrichments.indicator.file.fork_namekeywordZone.Identifier A fork is additional
 data associated with a filesystem object.threatthreat.enrichments.indicator.file.gidkeyword
 1001Primary group ID (GID) of the file.threatthreat.enrichments.indicator.file.groupkeywordalice
 Primary group name of the
 file.threatthreat.enrichments.indicator.file.hash.cdhashkeyword3783b4052fd474dbe30676b45c3
 29e7a6d44acd9The Code Directory (CD) hash of an
 executable.threatthreat.enrichments.indicator.file.hash.md5keyword MD5
 hash.threatthreat.enrichments.indicator.file.hash.sha1keyword SHA1
 hash.threatthreat.enrichments.indicator.file.hash.sha256keyword SHA256
 hash.threatthreat.enrichments.indicator.file.hash.sha384keyword SHA384
 hash.threatthreat.enrichments.indicator.file.hash.sha512keyword SHA512
 hash.threatthreat.enrichments.indicator.file.hash.ssdeepkeyword SSDEEP
 hash.threatthreat.enrichments.indicator.file.hash.tlshkeyword TLSH
 hash.threatthreat.enrichments.indicator.file.inodekeyword 256383Inode representing the file in
 the filesystem.threatthreat.enrichments.indicator.file.mime_typekeyword Media type of file,
 document, or arrangement of bytes.threatthreat.enrichments.indicator.file.modekeyword
 640Mode of the file in octal representation.threatthreat.enrichments.indicator.file.mtimedate Last
 time the file content was
 modified.threatthreat.enrichments.indicator.file.namekeywordexample.png Name of the file
 including the extension, without the
 directory.threatthreat.enrichments.indicator.file.ownerkeywordalice File owner's
 username.threatthreat.enrichments.indicator.file.pathkeyword/home/alice/example.png Full path
 to the file, including the file
 name.threatthreat.enrichments.indicator.file.path.textmatch_only_text/home/alice/example.png
 Full path to the file, including the file
 name.threatthreat.enrichments.indicator.file.pe.architecturekeywordx64 CPU architecture target
 for the file.threatthreat.enrichments.indicator.file.pe.companykeywordMicrosoft Corporation

Internal company name of the file, provided at
compile-time.threatthreat.enrichments.indicator.file.pe.descriptionkeywordPaint Internal
description of the file, provided at
compile-time.threatthreat.enrichments.indicator.file.pe.file_versionkeyword6.3.9600.17415
Process
name.threatthreat.enrichments.indicator.file.pe.go_import_hashkeyword10bddcb4cee42080f76c
88d9ff964491 A hash of the Go language imports in a PE
file.threatthreat.enrichments.indicator.file.pe.go_importsflattened List of imported Go language
element names and
types.threatthreat.enrichments.indicator.file.pe.go_imports_names_entropylong Shannon
entropy calculation from the list of Go
imports.threatthreat.enrichments.indicator.file.pe.go_imports_names_var_entropylong Variance
for Shannon entropy calculation from the list of Go
imports.threatthreat.enrichments.indicator.file.pe.go_strippedboolean Whether the file is a
stripped or obfuscated Go
executable.threatthreat.enrichments.indicator.file.pe.imphashkeyword0c6803c4e922103c4dca5
963aad36ddf A hash of the imports in a PE
file.threatthreat.enrichments.indicator.file.pe.import_hashkeywordd41d8cd98f00b204e9800998e
cf8427e A hash of the imports in a PE
file.threatthreat.enrichments.indicator.file.pe.importsflattened List of imported element names
and types.threatthreat.enrichments.indicator.file.pe.imports_names_entropylong Shannon
entropy calculation from the list of imported element names and
types.threatthreat.enrichments.indicator.file.pe.imports_names_var_entropylong Variance for
Shannon entropy calculation from the list of imported element names and
types.threatthreat.enrichments.indicator.file.pe.original_file_namekeywordMSPAIN.T.EXE
Internal name of the file, provided at
compile-time.threatthreat.enrichments.indicator.file.pe.pehashkeyword73ff189b63cd6be375a7ff
25179a38d347651975A hash of the PE header and data from one or more PE
sections.threatthreat.enrichments.indicator.file.pe.productkeywordMicrosoft® Windows®
Operating System Internal product name of the file, provided at
compile-time.threatthreat.enrichments.indicator.file.pe.sectionsnested Section information of the
PE file.threatthreat.enrichments.indicator.file.pe.sections_entropylong Shannon entropy
calculation from the section.threatthreat.enrichments.indicator.file.pe.sections.namekeyword PE
Section List name.threatthreat.enrichments.indicator.file.pe.sections.physical_size PE
Section List physical size.threatthreat.enrichments.indicator.file.pe.sections.var_entropylong
Variance for Shannon entropy calculation from the
section.threatthreat.enrichments.indicator.file.pe.sections.virtual_size PE Section List virtual
size. This is always the same as `physical\_size`.threatthreat.enrichments.indicator.file.size
16384File size in bytes.threatthreat.enrichments.indicator.file.target_pathkeyword Target path
for symlinks.threatthreat.enrichments.indicator.file.target_path.textmatch_only_text Target path
for symlinks.threatthreat.enrichments.indicator.file.typekeywordfile File type (file, dir, or
symlink).threatthreat.enrichments.indicator.file.uidkeyword 1001The user ID (UID) or security
identifier (SID) of the file

owner.threatthreat.enrichments.indicator.file.x509.alternative_namekeyword*.elastic.co List of subject alternative names

(SAN).threatthreat.enrichments.indicator.file.x509.issuer.common_namekeywordExample SHA2 High Assurance Server CA List of common name (CN) of issuing certificate

authority.threatthreat.enrichments.indicator.file.x509.issuer.countrykeywordUS List of country \(\C\) code

threatthreat.enrichments.indicator.file.x509.issuer.distinguished_namekeywordC=US, O=Example Inc, OU=www.example.com, CN=Example SHA2 High Assurance Server CADistinguished name (DN) of issuing certificate

authority.threatthreat.enrichments.indicator.file.x509.issuer.localitykeywordMountain View List of locality names

(L).threatthreat.enrichments.indicator.file.x509.issuer.organizationkeywordExample Inc List of organizations (O) of issuing certificate

authority.threatthreat.enrichments.indicator.file.x509.issuer.organizational_unitkeywordwww.example.com List of organizational units (OU) of issuing certificate

authority.threatthreat.enrichments.indicator.file.x509.issuer.state_or_provincekeywordCalifornia List of state or province names (ST, S, or P)

threatthreat.enrichments.indicator.file.x509.not_afterdate 2020-07-16T03:15:39Z Time at which the certificate is no longer considered valid

threatthreat.enrichments.indicator.file.x509.not_beforedate 2019-08-16T01:40:25Z Time at which the certificate is first considered valid

threatthreat.enrichments.indicator.file.x509.public_key_algorithmkeywordRSA Algorithm used to generate the public key

key.threatthreat.enrichments.indicator.file.x509.public_key_curvekeywordnistp521 The curve used by the elliptic curve public key algorithm. This is algorithm specific

threatthreat.enrichments.indicator.file.x509.public_key_exponentlong 65537Exponent used to derive the public key. This is algorithm specific

threatthreat.enrichments.indicator.file.x509.public_key_size2048The size of the public key space in bits

threatthreat.enrichments.indicator.file.x509.serial_numberkeyword55FBB9C7DEBF09809D12CCAA Unique serial number issued by the certificate

authority.threatthreat.enrichments.indicator.file.x509.signature_algorithmkeywordSHA256-RSA Identifier for certificate signature algorithm

threatthreat.enrichments.indicator.file.x509.subject.common_namekeywordshared.global.example.net List of common names (CN) of subject

threatthreat.enrichments.indicator.file.x509.subject.countrykeywordUS List of country \(\C\) code

threatthreat.enrichments.indicator.file.x509.subject.distinguished_namekeywordC=US, ST=California, L=San Francisco, O=Example, Inc., CN=shared.global.example.netDistinguished name (DN) of the certificate subject

entity.threatthreat.enrichments.indicator.file.x509.subject.localitykeywordSan Francisco List of locality names

(L).threatthreat.enrichments.indicator.file.x509.subject.organizationkeywordExample, Inc. List of organizations (O) of subject

subject.threatthreat.enrichments.indicator.file.x509.subject.organizational_unitkeyword List of

organizational units (OU) of

subject.threatthreat.enrichments.indicator.file.x509.subject.state_or_provincekeywordCalifornia
List of state or province names (ST, S, or

P)threatthreat.enrichments.indicator.file.x509.version_numberkeyword 3Version of x509

format.threatthreat.enrichments.indicator.first_seendate 2020-11-05T17:25:47.000Z Date/time

indicator was first reported.threatthreat.enrichments.indicator.geo.city_namekeywordMontreal

City name.threatthreat.enrichments.indicator.geo.continent_codekeywordNA Continent

code.threatthreat.enrichments.indicator.geo.continent_namekeywordNorth America Name of the

continent.threatthreat.enrichments.indicator.geo.country_iso_codekeywordCA Country ISO

code.threatthreat.enrichments.indicator.geo.country_namekeywordCanada Country

name.threatthreat.enrichments.indicator.geo.locationgeo_point{ "lon": -73.614830, "lat":

45.505918 } Longitude and

latitude.threatthreat.enrichments.indicator.geo.namekeywordboston-dc User-defined description

of a location.threatthreat.enrichments.indicator.geo.postal_codekeyword 94040Postal

code.threatthreat.enrichments.indicator.geo.region_iso_codekeywordCA-QC Region ISO

code.threatthreat.enrichments.indicator.geo.region_namekeywordQuebec Region

name.threatthreat.enrichments.indicator.geo.timezonekeywordAmerica/Argentina/Buenos_Aires

Time zone.threatthreat.enrichments.indicator.ipip 1.2.3.4 Indicator IP

addressthreatthreat.enrichments.indicator.last_seendate 2020-11-05T17:25:47.000Z Date/time

indicator was last reported.threatthreat.enrichments.indicator.marking.tlpkeywordCLEAR

Indicator TLP markingthreatthreat.enrichments.indicator.marking.tlp_versionkeyword 2Indicator

TLP versionthreatthreat.enrichments.indicator.modified_atdate 2020-11-05T17:25:47.000Z

Date/time indicator was last updated.threatthreat.enrichments.indicator.namekeyword5.2.75.227

Indicator display namethreatthreat.enrichments.indicator.portlong 443Indicator

portthreatthreat.enrichments.indicator.providerkeywordlrz_urlhaus Indicator provider

Field Set:

threatthreat.enrichments.indicator.referencekeywordhttps://system.example.com/indicator/0001
234Indicator | Field: reference | Type:

URLthreatthreat.enrichments.indicator.registry.data.byteskeywordZQBuAC0AVQBTAAAAZQBu
AAAAAAA= | Example: Original bytes written with base64

encoding.threatthreat.enrichments.indicator.registry.data.stringswildcard["C:\\rta\\red_\\t\\bin\\mya
pp.exe"] | Description: List of strings representing what was written to the

registry.threatthreat.enrichments.indicator.registry.data.typekeywordREG_SZ Standard registry
type for encoding contentsthreatthreat.enrichments.indicator.registry.hivekeywordHKLM

Abbreviated name for the

hive.threatthreat.enrichments.indicator.registry.keykeywordSOFTWARE\\Microsoft\\Windows
NT\\CurrentVersion\\Image File Execution Options\\winword.exeHive-relative path of

keys.threatthreat.enrichments.indicator.registry.pathkeywordHKLM\\SOFTWARE\\Microsoft\\Wind
ows NT\\CurrentVersion\\Image File Execution Options\\winword.exe\\DebuggerFull path, including

hive, key and valuethreatthreat.enrichments.indicator.registry.valuekeywordDebugger Name of
the value written.threatthreat.enrichments.indicator.scanner_statslong 4Scanner

statisticsthreatthreat.enrichments.indicator.sightingslong 20Number of times indicator

observedthreatthreat.enrichments.indicator.typekeywordipv4-addr Type of

indicator.threatthreat.enrichments.indicator.url.domainkeywordwww.elastic.co Domain of the url.
threatthreat.enrichments.indicator.url.extensionkeywordpng File extension from the request url, excluding the leading dot.
threatthreat.enrichments.indicator.url.fragmentkeyword Portion of the url after the

`#`.threatthreat.enrichments.indicator.url.fullwildcardhttps://www.elastic.co:443/search?q=elasticsearch#topFull unparsed

URL.threatthreat.enrichments.indicator.url.full.textmatch_only_texthttps://www.elastic.co:443/search?q=elasticsearch#topFull unparsed

URL.threatthreat.enrichments.indicator.url.originalwildcardhttps://www.elastic.co:443/search?q=elasticsearch#top or /search?q=elasticsearchUnmodified original url as seen in the event

source.threatthreat.enrichments.indicator.url.original.textmatch_only_texthttps://www.elastic.co:443/search?q=elasticsearch#top or /search?q=elasticsearchUnmodified original url as seen in

the event source.threatthreat.enrichments.indicator.url.passwordkeyword Password of the request.
threatthreat.enrichments.indicator.url.pathwildcard Path of the request, such as

"/search".threatthreat.enrichments.indicator.url.portlong 443Port of the request, such as

443.threatthreat.enrichments.indicator.url.querykeyword Query string of the

request.threatthreat.enrichments.indicator.url.registered_domainkeywordexample.com The highest registered url domain, stripped of the

subdomain.threatthreat.enrichments.indicator.url.schemekeywordhttps Scheme of the

url.threatthreat.enrichments.indicator.url.subdomainkeywordeast The subdomain of the

domain.threatthreat.enrichments.indicator.url.top_level_domainkeywordco.uk The effective top

level domain (com, org, net, co.uk).threatthreat.enrichments.indicator.url.usernamekeyword Username of the

request.threatthreat.enrichments.indicator.x509.alternative_nameskeyword*.elastic.co List of subject alternative names

(SAN).threatthreat.enrichments.indicator.x509.issuer.common_namekeywordExample SHA2 High Assurance Server CA List of common name (CN) of issuing certificate

authority.threatthreat.enrichments.indicator.x509.issuer.countrykeywordUS List of country \(\C)

codesthreatthreat.enrichments.indicator.x509.issuer.distinguished_namekeywordC=US,

O=Example Inc, OU=www.example.com, CN=Example SHA2 High Assurance Server

CADistinguished name (DN) of issuing certificate

authority.threatthreat.enrichments.indicator.x509.issuer.localitykeywordMountain View List of

locality names (L)threatthreat.enrichments.indicator.x509.issuer.organizationkeywordExample

Inc List of organizations (O) of issuing certificate

authority.threatthreat.enrichments.indicator.x509.issuer.organizational_unitkeywordwww.example.com List of organizational units (OU) of issuing certificate

authority.threatthreat.enrichments.indicator.x509.issuer.state_or_provincekeywordCalifornia List of state or province names (ST, S, or P)threatthreat.enrichments.indicator.x509.not_afterdate

2020-07-16T03:15:39Z Time at which the certificate is no longer considered

valid.threatthreat.enrichments.indicator.x509.not_beforedate 2019-08-16T01:40:25Z Time at which the certificate is first considered

valid.threatthreat.enrichments.indicator.x509.public_key_algorithmkeywordRSA Algorithm used to generate the public

key.threatthreat.enrichments.indicator.x509.public_key_curvekeywordnistp521 The curve used by the elliptic curve public key algorithm. This is algorithm

specific.threatthreat.enrichments.indicator.x509.public_key_exponentlong 65537Exponent used to derive the public key. This is algorithm

specific.threatthreat.enrichments.indicator.x509.public_key_sizelong 2048The size of the public key space in

bits.threatthreat.enrichments.indicator.x509.serial_numberkeyword55FBB9C7DEBF09809D12CAA Unique serial number issued by the certificate

authority.threatthreat.enrichments.indicator.x509.signature_algorithmkeywordSHA256-RSA Identifier for certificate signature

algorithm.threatthreat.enrichments.indicator.x509.subject.common_namekeywordshared.global.example.net List of common names (CN) of

subject.threatthreat.enrichments.indicator.x509.subject.countrykeywordUS List of country \(\C) codethreatthreat.enrichments.indicator.x509.subject.distinguished_namekeywordC=US, ST=California, L=San Francisco, O=Example, Inc., CN=shared.global.example.netDistinguished name (DN) of the certificate subject

entity.threatthreat.enrichments.indicator.x509.subject.localitykeywordSan Francisco List of locality names (L)threatthreat.enrichments.indicator.x509.subject.organizationkeywordExample, Inc. List of organizations (O) of

subject.threatthreat.enrichments.indicator.x509.subject.organizational_unitkeyword List of organizational units (OU) of

subject.threatthreat.enrichments.indicator.x509.subject.state_or_provincekeywordCalifornia List of state or province names (ST, S, or P)threatthreat.enrichments.indicator.x509.version_numberkeyword 3Version of x509 format.threatthreat.enrichments.matched.atomickeywordbad-domain.com Matched indicator valuethreatthreat.enrichments.matched.fieldkeywordfile.hash.sha256 Matched indicator fieldthreatthreat.enrichments.matched.idkeywordff93aee5-86a1-4a61-b0e6-0cdc313d01b5 Matched indicator

identifiertthreatthreat.enrichments.matched.indexkeywordfilebeat-8.0.0-2021.05.23-000011 Matched indicator indexthreatthreat.enrichments.matched.occurreddate 2021-10-05T17:00:58.326Z Date of

matchthreatthreat.enrichments.matched.typekeywordindicator_match_rule Type of indicator matchthreatthreat.feed.dashboard_idkeyword5ba16340-72e6-11eb-a3e3-b3cc7c78a70f Feed dashboard ID.threatthreat.feed.descriptionkeywordThreat feed from the AlienVault Open Threat eXchange network.Description of the threat feed.threatthreat.feed.namekeywordAlienVault OTX Name of the threat feed.threatthreat.feed.referencekeywordhttps://otx.alienvault.com Reference for the threat feed.threatthreat.frameworkkeywordMITRE ATT&CK Threat classification framework.threatthreat.group.aliaskeyword["Magecart Group 6"] Alias of the group.threatthreat.group.idkeywordG0037 ID of the group.threatthreat.group.namekeywordFIN6 Name of the group.threatthreat.group.referencekeywordhttps://attack.mitre.org/groups/G0037/ Reference URL of the group.threatthreat.indicator.as.numberlong 15169Unique number allocated to the autonomous system.threatthreat.indicator.as.organization.namekeywordGoogle LLC Organization name.threatthreat.indicator.as.organization.name.textmatch_only_textGoogle

LLC Organization name.threatthreat.indicator.confidencekeywordMedium Indicator confidence ratingthreatthreat.indicator.descriptionkeywordIP x.x.x.x was observed delivering the Angler EK.Indicator descriptionthreatthreat.indicator.email.addresskeywordphish@example.com Indicator email addressthreatthreat.indicator.file.accesseddate Last time the file was accessed.threatthreat.indicator.file.attributeskeyword["readonly", "system"] Array of file attributes.threatthreat.indicator.file.code_signature.digest_algorithmkeywordsha256 Hashing algorithm used to sign the process.threatthreat.indicator.file.code_signature.existsboolean TRUE Boolean to capture if a signature is present.threatthreat.indicator.file.code_signature.flagskeyword 570522385Code signing flags of the processthreatthreat.indicator.file.code_signature.signing_idkeywordcom.apple.xpc.proxy The identifier used to sign the process.threatthreat.indicator.file.code_signature.statuskeywordERROR_UNTRUSTED_ROOT Additional information about the certificate status.threatthreat.indicator.file.code_signature.subject_namekeywordMicrosoft Corporation Subject name of the code signerthreatthreat.indicator.file.code_signature.team_idkeywordEQHXZ8M8AV The team identifier used to sign the process.threatthreat.indicator.file.code_signature.timestampdate 2021-01-01T12:10:30Z When the signature was generated and signed.threatthreat.indicator.file.code_signature.trustedboolean TRUE Stores the trust status of the certificate chain.threatthreat.indicator.file.code_signature.validboolean TRUE Boolean to capture if the digital signature is verified against the binary content.threatthreat.indicator.file.createddate File creation time.threatthreat.indicator.file.ctimedate Last time the file attributes or metadata changed.threatthreat.indicator.file.devicekeywordsda Device that is the source of the file.threatthreat.indicator.file.directorykeyword/home/alice Directory where the file is located.threatthreat.indicator.file.drive_letterkeywordC Drive letter where the file is located.threatthreat.indicator.file.elf.architecturekeywordx86-64 Machine architecture of the ELF file.threatthreat.indicator.file.elf.byte_orderkeywordLittle Endian Byte sequence of ELF file.threatthreat.indicator.file.elf.cpu_typekeywordIntel CPU type of the ELF file.threatthreat.indicator.file.elf.creation_datedate Build or compile date.threatthreat.indicator.file.elf.exportsflattened List of exported element names and types.threatthreat.indicator.file.elf.go_import_hashkeyword10bddcb4cee42080f76c88d9ff964491 A hash of the Go language imports in an ELF file.threatthreat.indicator.file.elf.go_importsflattened List of imported Go language element names and types.threatthreat.indicator.file.elf.go_imports_names_entropylong Shannon entropy calculation from the list of Go imports.threatthreat.indicator.file.elf.go_imports_names_var_entropylong Variance for Shannon entropy calculation from the list of Go imports.threatthreat.indicator.file.elf.go_strippedboolean Whether the file is a stripped or obfuscated Go executable.threatthreat.indicator.file.elf.header.abi_versionkeyword Version of the ELF Application Binary Interface (ABI).threatthreat.indicator.file.elf.header.classkeyword Header class of the ELF file.threatthreat.indicator.file.elf.header.datakeyword Data table of the ELF header.threatthreat.indicator.file.elf.header.entrypointlong Header entrypoint of the ELF

file.threatthreat.indicator.file.elf.header.object_versionkeyword "0x1" for original ELF

files.threatthreat.indicator.file.elf.header.os_abikeyword Application Binary Interface (ABI) of the Linux OS.

threatthreat.indicator.file.elf.header.typekeyword Header type of the ELF

file.threatthreat.indicator.file.elf.header.versionkeyword Version of the ELF

header.threatthreat.indicator.file.elf.import_hashkeywordd41d8cd98f00b204e9800998ecf8427e
A hash of the imports in an ELF file.

threatthreat.indicator.file.elf.importsflattened List of imported element names and types.

threatthreat.indicator.file.elf.imports_names_entropylong Shannon entropy calculation from the list of imported element names and types.

threatthreat.indicator.file.elf.imports_names_var_entropylong Variance for Shannon entropy calculation from the list of imported element names and types.

threatthreat.indicator.file.elf.sectionsnested Section information of the ELF

file.threatthreat.indicator.file.elf.sections.chi2long Chi-square probability distribution of the section.

threatthreat.indicator.file.elf.sections.entropylong Shannon entropy calculation from the section.

threatthreat.indicator.file.elf.sections.flagskeyword ELF Section List

flags.threatthreat.indicator.file.elf.sections.namekeyword ELF Section List

name.threatthreat.indicator.file.elf.sections.physical_offsetkeyword ELF Section List

offset.threatthreat.indicator.file.elf.sections.physical_sizekeyword ELF Section List physical size.

threatthreat.indicator.file.elf.sections.typekeyword ELF Section List

type.threatthreat.indicator.file.elf.sections.var_entropylong Variance for Shannon entropy calculation from the section.

threatthreat.indicator.file.elf.sections.virtual_addresskeyword ELF Section List virtual address.

threatthreat.indicator.file.elf.sections.virtual_sizekeyword ELF Section List virtual size.

threatthreat.indicator.file.elf.segmentsnested ELF object segment list.

threatthreat.indicator.file.elf.segments.sectionskeyword ELF object segment

sections.threatthreat.indicator.file.elf.segments.typekeyword ELF object segment

type.threatthreat.indicator.file.elf.shared_librarieskeyword List of shared libraries used by this ELF object.

threatthreat.indicator.file.elf.telfhashkeyword telfhash hash for ELF

file.threatthreat.indicator.file.extensionkeywordpng File extension, excluding the leading dot.

threatthreat.indicator.file.fork_namekeywordZone.Identifier A fork is additional data associated with a filesystem object.

threatthreat.indicator.file.gidkeyword 1001Primary group ID (GID) of the file.

Field Set: threatthreat.indicator.file.groupkeywordalice | Field: Primary | Type: group | Example: name of the

file.threatthreat.indicator.file.hash.cdhashkeyword3783b4052fd474dbe30676b45c329e7a6d44acd9The | Description: Code Directory (CD) hash of an executable.

threatthreat.indicator.file.hash.md5keyword MD5

hash.threatthreat.indicator.file.hash.sha1keyword SHA1

hash.threatthreat.indicator.file.hash.sha256keyword SHA256

hash.threatthreat.indicator.file.hash.sha384keyword SHA384

hash.threatthreat.indicator.file.hash.sha512keyword SHA512

hash.threatthreat.indicator.file.hash.ssdeepkeyword SSDEEP

hash.threatthreat.indicator.file.hash.tlshkeyword TLSH

hash.threatthreat.indicator.file.inodekeyword 256383Inode representing the file in the filesystem.

threatthreat.indicator.file.mime_typekeyword Media type of file, document, or

arrangement of bytes.threatthreat.indicator.file.modekeyword 640Mode of the file in octal representation.threatthreat.indicator.file.mtimedate Last time the file content was modified.threatthreat.indicator.file.namekeywordexample.png Name of the file including the extension, without the directory.threatthreat.indicator.file.ownerkeywordalice File owner's username.threatthreat.indicator.file.pathkeyword/home/alice/example.png Full path to the file, including the file
 name.threatthreat.indicator.file.path.textmatch_only_text/home/alice/example.png Full path to the file, including the file name.threatthreat.indicator.file.pe.architecturekeywordx64 CPU architecture target for the file.threatthreat.indicator.file.pe.companykeywordMicrosoft Corporation Internal company name of the file, provided at compile-time.threatthreat.indicator.file.pe.descriptionkeywordPaint Internal description of the file, provided at compile-time.threatthreat.indicator.file.pe.file_versionkeyword6.3.9600.17415 Process
 name.threatthreat.indicator.file.pe.go_import_hashkeyword10bddcb4cee42080f76c88d9ff964491 A hash of the Go language imports in a PE
 file.threatthreat.indicator.file.pe.go_importsflattened List of imported Go language element names and types.threatthreat.indicator.file.pe.go_imports_names_entropylong Shannon entropy calculation from the list of Go
 imports.threatthreat.indicator.file.pe.go_imports_names_var_entropylong Variance for Shannon entropy calculation from the list of Go imports.threatthreat.indicator.file.pe.go_strippedboolean Whether the file is a stripped or obfuscated Go
 executable.threatthreat.indicator.file.pe.imphashkeyword0c6803c4e922103c4dca5963aad36ddf A hash of the imports in a PE
 file.threatthreat.indicator.file.pe.import_hashkeyworddd41d8cd98f00b204e9800998ecf8427e A hash of the imports in a PE file.threatthreat.indicator.file.pe.importsflattened List of imported element names and types.threatthreat.indicator.file.pe.imports_names_entropylong Shannon entropy calculation from the list of imported element names and
 types.threatthreat.indicator.file.pe.imports_names_var_entropylong Variance for Shannon entropy calculation from the list of imported element names and
 types.threatthreat.indicator.file.pe.original_file_namekeywordMSPAINTEXE Internal name of the file, provided at compile-time.threatthreat.indicator.file.pe.pehashkeyword73ff189b63cd6be375a7ff25179a38d347651975A hash of the PE header and data from one or more PE
 sections.threatthreat.indicator.file.pe.productkeywordMicrosoft® Windows® Operating System Internal product name of the file, provided at compile-time.threatthreat.indicator.file.pe.sectionsnested Section information of the PE
 file.threatthreat.indicator.file.pe.sections_entropylong Shannon entropy calculation from the section.threatthreat.indicator.file.pe.sections.namekeyword PE Section List
 name.threatthreat.indicator.file.pe.sections.physical_sizealong PE Section List physical size.threatthreat.indicator.file.pe.sections.var_entropylong Variance for Shannon entropy calculation from the section.threatthreat.indicator.file.pe.sections.virtual_sizealong PE Section List virtual size. This is always the same as `physical\_size`.threatthreat.indicator.file.sizealong 16384File size in bytes.threatthreat.indicator.file.target_pathkeyword Target path for

symlinks.threatthreat.indicator.file.target_path.textmatch_only_text Target path for
 symlinks.threatthreat.indicator.file.typekeywordfile File type (file, dir, or
 symlink).threatthreat.indicator.file.uidkeyword 1001The user ID (UID) or security identifier (SID)
 of the file owner.threatthreat.indicator.file.x509.alternative_nameskeyword*.elastic.co List of
 subject alternative names
 (SAN).threatthreat.indicator.file.x509.issuer.common_namekeywordExample SHA2 High
 Assurance Server CA List of common name (CN) of issuing certificate
 authority.threatthreat.indicator.file.x509.issuer.countrykeywordUS List of country \(\C)
 codesthreatthreat.indicator.file.x509.issuer.distinguished_namekeywordC=US, O=Example Inc,
 OU=www.example.com, CN=Example SHA2 High Assurance Server CADistinguished name
 (DN) of issuing certificate
 authority.threatthreat.indicator.file.x509.issuer.localitykeywordMountain View List of locality
 names (L)threatthreat.indicator.file.x509.issuer.organizationkeywordExample Inc List of
 organizations (O) of issuing certificate
 authority.threatthreat.indicator.file.x509.issuer.organizational_unitkeywordwww.example.com
 List of organizational units (OU) of issuing certificate
 authority.threatthreat.indicator.file.x509.issuer.state_or_provincekeywordCalifornia List of state
 or province names (ST, S, or P)threatthreat.indicator.file.x509.not_afterdate
 2020-07-16T03:15:39Z Time at which the certificate is no longer considered
 valid.threatthreat.indicator.file.x509.not_beforedate 2019-08-16T01:40:25Z Time at which the
 certificate is first considered
 valid.threatthreat.indicator.file.x509.public_key_algorithmkeywordRSA Algorithm used to
 generate the public key.threatthreat.indicator.file.x509.public_key_curvekeywordnistp521 The
 curve used by the elliptic curve public key algorithm. This is algorithm
 specific.threatthreat.indicator.file.x509.public_key_exponentlong 65537Exponent used to derive
 the public key. This is algorithm specific.threatthreat.indicator.file.x509.public_key_sizelong
 2048The size of the public key space in
 bits.threatthreat.indicator.file.x509.serial_numberkeyword55FBB9C7DEBF09809D12CCAA
 Unique serial number issued by the certificate
 authority.threatthreat.indicator.file.x509.signature_algorithmkeywordSHA256-RSA Identifier for
 certificate signature
 algorithm.threatthreat.indicator.file.x509.subject.common_namekeywordshared.global.example.
 net List of common names (CN) of
 subject.threatthreat.indicator.file.x509.subject.countrykeywordUS List of country \(\C)
 codesthreatthreat.indicator.file.x509.subject.distinguished_namekeywordC=US, ST=California,
 L=San Francisco, O=Example, Inc., CN=shared.global.example.netDistinguished name (DN) of
 the certificate subject entity.threatthreat.indicator.file.x509.subject.localitykeywordSan Francisco
 List of locality names (L)threatthreat.indicator.file.x509.subject.organizationkeywordExample,
 Inc. List of organizations (O) of
 subject.threatthreat.indicator.file.x509.subject.organizational_unitkeyword List of organizational
 units (OU) of subject.threatthreat.indicator.file.x509.subject.state_or_provincekeywordCalifornia
 List of state or province names (ST, S, or
 P)threatthreat.indicator.file.x509.version_numberkeyword 3Version of x509

format.threatthreat.indicator.first_seendate 2020-11-05T17:25:47.000Z Date/time indicator was first reported.threatthreat.indicator.geo.city_namekeywordMontreal City
name.threatthreat.indicator.geo.continent_codekeywordNA Continent
code.threatthreat.indicator.geo.continent_namekeywordNorth America Name of the continent.threatthreat.indicator.geo.country_iso_codekeywordCA Country ISO
code.threatthreat.indicator.geo.country_namekeywordCanada Country
name.threatthreat.indicator.geo.locationgeo_point{ "lon": -73.614830, "lat": 45.505918 } Longitude and latitude.threatthreat.indicator.geo.namekeywordboston-dc User-defined description of a location.threatthreat.indicator.geo.postal_codekeyword 94040Postal code.threatthreat.indicator.geo.region_iso_codekeywordCA-QC Region ISO
code.threatthreat.indicator.geo.region_namekeywordQuebec Region
name.threatthreat.indicator.geo.timezonekeywordAmerica/Argentina/Buenos_Aires Time zone.threatthreat.indicator.idkeyword[indicator--d7008e06-ab86-415a-9803-3c81ce2d3c37]ID of the indicatorthreatthreat.indicator.ipip 1.2.3.4 Indicator IP
addressthreatthreat.indicator.last_seendate 2020-11-05T17:25:47.000Z Date/time indicator was last reported.threatthreat.indicator.marking.tlpkeywordCLEAR Indicator TLP
markingthreatthreat.indicator.marking.tlp_versionkeyword 2Indicator TLP
versionthreatthreat.indicator.modified_atdate 2020-11-05T17:25:47.000Z Date/time indicator was last updated.threatthreat.indicator.namekeyword5.2.75.227 Indicator display name.threatthreat.indicator.portlong 443Indicator
portthreatthreat.indicator.providerkeywordlrz_urlhaus Indicator
providerthreatthreat.indicator.referencekeywordhttps://system.example.com/indicator/0001234Indicator reference
URLthreatthreat.indicator.registry.data.byteskeywordZQBuAC0AVQBTAAAAZQBuAAAAAA= Original bytes written with base64
encoding.threatthreat.indicator.registry.data.stringswildcard["C:\rta\red_ttp\bin\myapp.exe"] List of strings representing what was written to the
registry.threatthreat.indicator.registry.data.typekeywordREG_SZ Standard registry type for encoding contentsthreatthreat.indicator.registry.hivekeywordHKLM Abbreviated name for the hive.threatthreat.indicator.registry.keykeywordSOFTWARE\Microsoft\Windows NT\CurrentVersion\Image File Execution Options\winword.exeHive-relative path of keys.threatthreat.indicator.registry.pathkeywordHKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Image File Execution Options\winword.exe\DebuggerFull path, including hive, key and valuethreatthreat.indicator.registry.valuekeywordDebugger Name of the value written.threatthreat.indicator.scanner_statslong 4Scanner
statisticsthreatthreat.indicator.sightingslong 20Number of times indicator observedthreatthreat.indicator.typekeywordipv4-addr Type of
indicatorthreatthreat.indicator.url.domainkeywordwww.elastic.co Domain of the url.threatthreat.indicator.url.extensionkeywordpng File extension from the request url, excluding the leading dot.threatthreat.indicator.url.fragmentkeyword Portion of the url after the `#`.threatthreat.indicator.url.fullwildcardhttps://www.elastic.co:443/search?q=elasticsearch#topFull unparsed
URL.threatthreat.indicator.url.full.textmatch_only_texthttps://www.elastic.co:443/search?q=elastic

csearch#topFull unparsed

URL.threatthreat.indicator.url.originalwildcardhttps://www.elastic.co:443/search?q=elasticsearch
#top or /search?q=elasticsearchUnmodified original url as seen in the event

source.threatthreat.indicator.url.original.textmatch_only_texthttps://www.elastic.co:443/search?q
=elasticsearch#top or /search?q=elasticsearchUnmodified original url as seen in the event

source.threatthreat.indicator.url.passwordkeyword Password of the

request.threatthreat.indicator.url.pathwildcard Path of the request, such as

"/search".threatthreat.indicator.url.portlong 443Port of the request, such as

443.threatthreat.indicator.url.querykeyword Query string of the

request.threatthreat.indicator.url.registered_domainkeywordexample.com The highest

registered url domain, stripped of the subdomain.threatthreat.indicator.url.schemekeywordhttps

Scheme of the url.threatthreat.indicator.url.subdomainkeywordeast The subdomain of the

domain.threatthreat.indicator.url.top_level_domainkeywordco.uk The effective top level domain

(com, org, net, co.uk).threatthreat.indicator.url.usernamekeyword Username of the

request.threatthreat.indicator.x509.alternative_nameskeyword*.elastic.co List of subject

alternative names (SAN).threatthreat.indicator.x509.issuer.common_namekeywordExample

SHA2 High Assurance Server CA List of common name (CN) of issuing certificate

authority.threatthreat.indicator.x509.issuer.countrykeywordUS List of country \(\C)

codesthreatthreat.indicator.x509.issuer.distinguished_namekeywordC=US, O=Example Inc,

OU=www.example.com, CN=Example SHA2 High Assurance Server CADistinguished name

(DN) of issuing certificate authority.threatthreat.indicator.x509.issuer.localitykeywordMountain

View List of locality names (L)threatthreat.indicator.x509.issuer.organizationkeywordExample

Inc List of organizations (O) of issuing certificate

authority.threatthreat.indicator.x509.issuer.organizational_unitkeywordwww.example.com List of
organizational units (OU) of issuing certificate

authority.threatthreat.indicator.x509.issuer.state_or_provincekeywordCalifornia List of state or

province names (ST, S, or P)threatthreat.indicator.x509.not_afterdate 2020-07-16T03:15:39Z

Time at which the certificate is no longer considered

valid.threatthreat.indicator.x509.not_beforedate 2019-08-16T01:40:25Z Time at which the

certificate is first considered valid.threatthreat.indicator.x509.public_key_algorithmkeywordRSA

Algorithm used to generate the public

key.threatthreat.indicator.x509.public_key_curvekeywordnistp521 The curve used by the elliptic
curve public key algorithm. This is algorithm

specific.threatthreat.indicator.x509.public_key_exponentlong 65537Exponent used to derive the
public key. This is algorithm specific.

Field Set: threatthreat.indicator.x509.public_key_sizelong | Field: 2048The | Type: size |

Example: of the public key space in

bits.threatthreat.indicator.x509.serial_numberkeyword55FBB9C7DEBF09809D12CCAA |

Description: Unique serial number issued by the certificate

authority.threatthreat.indicator.x509.signature_algorithmkeywordSHA256-RSA Identifier for
certificate signature

algorithm.threatthreat.indicator.x509.subject.common_namekeywordshared.global.example.net

List of common names (CN) of subject.threatthreat.indicator.x509.subject.countrykeywordUS

List of country \ (C) code threat.indicator.x509.subject.distinguished_name keyword C=US, ST=California, L=San Francisco, O=Example, Inc., CN=shared.global.example.net Distinguished name (DN) of the certificate subject entity. threat.indicator.x509.subject.locality keyword San Francisco List of locality names
 (L) threat.indicator.x509.subject.organization keyword Example, Inc. List of organizations (O) of subject. threat.indicator.x509.subject.organizational_unit keyword List of organizational units (OU) of
 subject. threat.indicator.x509.subject.state_or_province keyword California List of state or province names (ST, S, or P) threat.indicator.x509.version_number keyword 3 Version of x509 format. threat.software.alias keyword ["X-Agent"] Alias of the
 software threat.software.id keyword S0552 ID of the
 software threat.software.name keyword AdFind Name of the
 software. threat.software.platforms keyword ["Windows"] Platforms of the
 software. threat.software.reference keyword https://attack.mitre.org/software/S0552/ Software reference URL. threat.software.type keyword Tool Software
 type. threat.tactic.id keyword TA0002 Threat tactic
 id. threat.tactic.name keyword Execution Threat
 tactic. threat.tactic.reference keyword https://attack.mitre.org/tactics/TA0002/ Threat tactic URL reference. threat.technique.id keyword T1059 Threat technique
 id. threat.technique.name keyword Command and Scripting Interpreter Threat technique name. threat.technique.name.textmatch_only_text Command and Scripting Interpreter Threat technique
 name. threat.technique.reference keyword https://attack.mitre.org/techniques/T1059/ Threat technique URL reference. threat.technique.subtechnique.id keyword T1059.001 Threat subtechnique id. threat.technique.subtechnique.name keyword PowerShell Threat subtechnique name. threat.technique.subtechnique.name.textmatch_only_text PowerShell Threat subtechnique
 name. threat.technique.subtechnique.reference keyword https://attack.mitre.org/techniques/T1059/001/Threat subtechnique URL reference. tls
 tls.cipher keyword TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256 String indicating the cipher used during the current connection. tls tls.client.certificate keyword MII... PEM-encoded stand-alone certificate offered by the client. tls tls.client.certificate_chain keyword ["MI...", "MI..."] Array of PEM-encoded certificates that make up the certificate chain offered by the client. tls
 tls.client.hash.md5 keyword 0F76C7F2C55BFD7D8E8B8F4BFBF0C9EC Certificate fingerprint using the MD5 digest of DER-encoded version of certificate offered by the client. tls
 tls.client.hash.sha1 keyword 9E393D93138888D288266C2D915214D1D1CCEB2A Certificate fingerprint using the SHA1 digest of DER-encoded version of certificate offered by the client. tls
 tls.client.hash.sha256 keyword 0687F666A054EF17A08E2F2162EAB4CBC0D265E1D7875BE74BF3C712CA92DAF0 Certificate fingerprint using the SHA256 digest of DER-encoded version of certificate offered by the client. tls tls.client.issuer keyword CN=Example Root CA, OU=Infrastructure Team, DC=example, DC=com Distinguished name of subject of the issuer of the x.509 certificate presented by the client. tls
 tls.client.ja3 keyword dd4e5b18d6b55c71272893221c96ba240 A hash that identifies clients based

on how they perform an SSL/TLS handshake.
`tls.tls.client.not_afterdate` 2021-01-01T00:00:00.000Z Date/Time indicating when client certificate is no longer considered valid.
`tls.tls.client.not_beforedate` 1970-01-01T00:00:00.000Z Date/Time indicating when client certificate is first considered valid.
`tls.tls.client.server_namekeyword` www.elastic.co Hostname the client is trying to connect to. Also called the SNI.
`tls.tls.client.subjectkeyword` CN=myclient, OU=Documentation Team, DC=example, DC=com Distinguished name of subject of the x.509 certificate presented by the client.
`tls.tls.client.supported_cipherskeyword` ["TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384", "TLS_ECDHE_ECDSA_WITH_AES_256_GCM_SHA384", "..."] Array of ciphers offered by the client during the client hello.
`tls.tls.client.x509.alternative_nameskeyword` *.elastic.co List of subject alternative names (SAN).
`tls.tls.client.x509.issuer.common_namekeyword` Example SHA2 High Assurance Server CA List of common name (CN) of issuing certificate authority.
`tls.tls.client.x509.issuer.countrykeyword` US List of country (C) code.
`tls.tls.client.x509.issuer.distinguished_namekeyword` C=US, O=Example Inc, OU=www.example.com, CN=Example SHA2 High Assurance Server CA Distinguished name (DN) of issuing certificate authority.
`tls.tls.client.x509.issuer.localitykeyword` Mountain View List of locality names (L).
`tls.tls.client.x509.issuer.organizationkeyword` Example Inc List of organizations (O) of issuing certificate authority.
`tls.tls.client.x509.issuer.organizational_unitkeyword` www.example.com List of organizational units (OU) of issuing certificate authority.
`tls.tls.client.x509.issuer.state_or_provincekeyword` California List of state or province names (ST, S, or P).
`tls.tls.client.x509.not_afterdate` 2020-07-16T03:15:39Z Time at which the certificate is no longer considered valid.
`tls.tls.client.x509.not_beforedate` 2019-08-16T01:40:25Z Time at which the certificate is first considered valid.
`tls.tls.client.x509.public_key_algorithmkeyword` RSA Algorithm used to generate the public key.
`tls.tls.client.x509.public_key_curvekeyword` nistp521 The curve used by the elliptic curve public key algorithm. This is algorithm specific.
`tls.tls.client.x509.public_key_exponentlong` 65537 Exponent used to derive the public key. This is algorithm specific.
`tls.tls.client.x509.public_key_sizelong` 2048 The size of the public key space in bits.
`tls.tls.client.x509.serial_numberkeyword` 55FBB9C7DEBF09809D12CCAA Unique serial number issued by the certificate authority.
`tls.tls.client.x509.signature_algorithmkeyword` SHA256-RSA Identifier for certificate signature algorithm.
`tls.tls.client.x509.subject.common_namekeyword` shared.global.example.net List of common names (CN) of subject.
`tls.tls.client.x509.subject.countrykeyword` US List of country (C) code.
`tls.tls.client.x509.subject.distinguished_namekeyword` C=US, ST=California, L=San Francisco, O=Example, Inc., CN=shared.global.example.net Distinguished name (DN) of the certificate subject entity.
`tls.tls.client.x509.subject.localitykeyword` San Francisco List of locality names (L).
`tls.tls.client.x509.subject.organizationkeyword` Example, Inc. List of organizations (O) of subject.
`tls.tls.client.x509.subject.organizational_unitkeyword` List of organizational units (OU) of subject.
`tls.tls.client.x509.subject.state_or_provincekeyword` California List of state or province names (ST, S, or P).
`tls.tls.client.x509.version_numberkeyword` 3 Version of x509 format.
`tls.curvekeyword` secp256r1 String indicating the curve used for the given cipher, when applicable.
`tls.tls.establishedboolean` Boolean flag indicating if the TLS negotiation was successful and transitioned to an encrypted tunnel.
`tls.tls.next_protocolkeyword` http/1.1 String

indicating the protocol being tunneled.tls tls.resumedboolean Boolean flag indicating if this TLS connection was resumed from an existing TLS negotiation.tls tls.server.certificatekeywordMII... PEM-encoded stand-alone certificate offered by the server.tls
tls.server.certificate_chainkeyword["MII...", "MII..."] Array of PEM-encoded certificates that make up the certificate chain offered by the server.tls
tls.server.hash.md5keyword0F76C7F2C55BFD7D8E8B8F4BFBF0C9ECCertificate fingerprint using the MD5 digest of DER-encoded version of certificate offered by the server.tls
tls.server.hash.sha1keyword9E393D93138888D288266C2D915214D1D1CCEB2ACertificate fingerprint using the SHA1 digest of DER-encoded version of certificate offered by the server.tls
tls.server.hash.sha256keyword0687F666A054EF17A08E2F2162EAB4CBC0D265E1D7875BE74BF3C712CA92DAF0Certificate fingerprint using the SHA256 digest of DER-encoded version of certificate offered by the server.tls
tls.server.issuerkeywordCN=Example Root CA, OU=Infrastructure Team, DC=example, DC=comSubject of the issuer of the x.509 certificate presented by the server.tls
tls.server.ja3skeyword394441ab65754e2207b1e1b457b3641d A hash that identifies servers based on how they perform an SSL/TLS handshake.tls
tls.server.not_afterdate 2021-01-01T00:00:00.000Z Timestamp indicating when server certificate is no longer considered valid.tls
tls.server.not_beforedate 1970-01-01T00:00:00.000Z Timestamp indicating when server certificate is first considered valid.tls
tls.server.subjectkeywordCN=www.example.com, OU=Infrastructure Team, DC=example, DC=comSubject of the x.509 certificate presented by the server.tls
tls.server.x509.alternative_nameskeyword*.elastic.co List of subject alternative names (SAN).tls
tls.server.x509.issuer.common_namekeywordExample SHA2 High Assurance Server CA List of common name (CN) of issuing certificate authority.tls
tls.server.x509.issuer.countrykeywordUS List of country \(\C\) code.tls
tls.server.x509.issuer.distinguished_namekeywordC=US, O=Example Inc, OU=www.example.com, CN=Example SHA2 High Assurance Server CADistinguished name (DN) of issuing certificate authority.tls
tls.server.x509.issuer.localitykeywordMountain View List of locality names (L).tls
tls.server.x509.issuer.organizationkeywordExample Inc List of organizations (O) of issuing certificate authority.tls
tls.server.x509.issuer.organizational_unitkeywordwww.example.com List of organizational units (OU) of issuing certificate authority.tls
tls.server.x509.issuer.state_or_provincekeywordCalifornia List of state or province names (ST, S, or P).tls
tls.server.x509.not_afterdate 2020-07-16T03:15:39Z Time at which the certificate is no longer considered valid.tls
tls.server.x509.not_beforedate 2019-08-16T01:40:25Z Time at which the certificate is first considered valid.tls
tls.server.x509.public_key_algorithmkeywordRSA Algorithm used to generate the public key.tls
tls.server.x509.public_key_curvekeywordnistp521 The curve used by the elliptic curve public key algorithm. This is algorithm specific.tls
tls.server.x509.public_key_exponentlong 65537Exponent used to derive the public key. This is algorithm specific.tls
tls.server.x509.public_key_sizeint 2048The size of the public key space in bits.tls
tls.server.x509.serial_numberkeyword55FBB9C7DEBF09809D12CCAA Unique serial number issued by the certificate authority.tls
tls.server.x509.signature_algorithmkeywordSHA256-RSA Identifier for certificate signature algorithm.tls
tls.server.x509.subject.common_namekeywordshared.global.example.net List of common

names (CN) of subject.tls tls.server.x509.subject.countrykeywordUS List of country \ (C) code.tls
 tls.server.x509.subject.distinguished_namekeywordC=US, ST=California, L=San Francisco,
 O=Example, Inc., CN=shared.global.example.netDistinguished name (DN) of the certificate
 subject entity.tls tls.server.x509.subject.localitykeywordSan Francisco List of locality names
 (L).tls tls.server.x509.subject.organizationkeywordExample, Inc. List of organizations (O) of
 subject.tls tls.server.x509.subject.organizational_unitkeyword List of organizational units (OU) of
 subject.tls tls.server.x509.subject.state_or_provincekeywordCalifornia List of state or province
 names (ST, S, or P).tls tls.server.x509.version_numberkeyword3Version of x509 format.tls
 tls.versionkeyword1.2Numeric part of the version parsed from the original string.tls
 tls.version_protocolkeywordtls Normalized lowercase protocol name parsed from original
 string.trace.trace.idkeyword4bf92f3577b34da6a3ce929d0e0e4736 Unique identifier of the
 trace.transaction.transaction.idkeyword00f067aa0ba902b7 Unique identifier of the transaction
 within the scope of its trace.url url.domainkeywordwww.elastic.co Domain of the url.url
 url.extensionkeywordpng File extension from the request url, excluding the leading dot.url
 url.fragmentkeyword Portion of the url after the '#' .url
 url.fullwildcardhttps://www.elastic.co:443/search?q=elasticsearch#topFull unparsed URL.url
 url.full.textmatch_only_texthttps://www.elastic.co:443/search?q=elasticsearch#topFull unparsed
 URL.url url.originalwildcardhttps://www.elastic.co:443/search?q=elasticsearch#top or
 /search?q=elasticsearchUnmodified original url as seen in the event source.url
 url.original.textmatch_only_texthttps://www.elastic.co:443/search?q=elasticsearch#top or
 /search?q=elasticsearchUnmodified original url as seen in the event source.url
 url.passwordkeyword Password of the request.url url.pathwildcard Path of the request, such as
 "/search".url url.portlong443Port of the request, such as 443.url url.querykeyword Query string
 of the request.url url.registered_domainkeywordexample.com The highest registered url
 domain, stripped of the subdomain.url url.schemekeywordhttps Scheme of the url.url
 url.subdomainkeywordeast The subdomain of the domain.url url.top_level_domainkeywordco.uk
 The effective top level domain (com, org, net, co.uk).url url.usernamekeyword Username of the
 request.user.user.changes.domainkeyword Name of the directory the user is a member
 of.user.user.changes.emailkeyword User email
 address.user.user.changes.full_namekeywordAlbert Einstein User's full name, if
 available.user.user.changes.full_name.textmatch_only_textAlbert Einstein User's full name, if
 available.user.user.changes.group.domainkeyword Name of the directory the group is a member
 of.user.user.changes.group.idkeyword Unique identifier for the group on the
 system/platform.user.user.changes.group.namekeyword Name of the group.
 Field Set: user.user.changes.hashkeyword | Field: Unique | Type: user | Example: hash to
 correlate information for a user in anonymized
 form.user.user.changes.idkeywordS-1-5-21-202424912787-2692429404-2351956786-1000Uniq
 ue identifier of the user.user.user.changes.namekeyworda.einstein | Description: Short name or
 login of the user.user.user.changes.name.textmatch_only_texta.einstein Short name or login of
 the user.user.user.changes.roleskeyword["kibana_admin", "reporting_user"] Array of user roles
 at the time of the event.user.user.domainkeyword Name of the directory the user is a member
 of.user.user.effective.domainkeyword Name of the directory the user is a member
 of.user.user.effective.emailkeyword User email

address.useruser.effective.full_namekeywordAlbert Einstein User's full name, if available.useruser.effective.full_name.textmatch_only_textAlbert Einstein User's full name, if available.useruser.effective.group.domainkeyword Name of the directory the group is a member of.useruser.effective.group.idkeyword Unique identifier for the group on the system/platform.useruser.effective.group.namekeyword Name of the group.useruser.effective.hashkeyword Unique user hash to correlate information for a user in anonymized form.useruser.effective.idkeywordS-1-5-21-202424912787-2692429404-2351956786-1000Unique identifier of the user.useruser.effective.namekeyworda.einstein Short name or login of the user.useruser.effective.name.textmatch_only_texta.einstein Short name or login of the user.useruser.effective.roleskeyword["kibana_admin", "reporting_user"] Array of user roles at the time of the event.useruser.emailkeyword User email

address.useruser.full_namekeywordAlbert Einstein User's full name, if available.useruser.full_name.textmatch_only_textAlbert Einstein User's full name, if available.useruser.group.domainkeyword Name of the directory the group is a member of.useruser.group.idkeyword Unique identifier for the group on the system/platform.useruser.group.namekeyword Name of the group.useruser.hashkeyword Unique user hash to correlate information for a user in anonymized form.useruser.idkeywordS-1-5-21-202424912787-2692429404-2351956786-1000Unique identifier of the user.useruser.namekeyworda.einstein Short name or login of the user.useruser.name.textmatch_only_texta.einstein Short name or login of the user.useruser.risk.calculated_levelkeywordHigh A risk classification level calculated by an internal system as part of entity analytics and entity risk

scoring.useruser.risk.calculated_scorefloat 880.73A risk classification score calculated by an internal system as part of entity analytics and entity risk

scoring.useruser.risk.calculated_score_normfloat 88.73A normalized risk score calculated by an internal system.useruser.risk.static_levelkeywordHigh A risk classification level obtained from outside the system, such as from some external Threat Intelligence

Platform.useruser.risk.static_scorefloat 830A risk classification score obtained from outside the system, such as from some external Threat Intelligence

Platform.useruser.risk.static_score_normfloat 83A normalized risk score calculated by an external system.useruser.roleskeyword["kibana_admin", "reporting_user"] Array of user roles at the time of the event.useruser.target.domainkeyword Name of the directory the user is a member of.useruser.target.emailkeyword User email

address.useruser.target.full_namekeywordAlbert Einstein User's full name, if available.useruser.target.full_name.textmatch_only_textAlbert Einstein User's full name, if available.useruser.target.group.domainkeyword Name of the directory the group is a member of.useruser.target.group.idkeyword Unique identifier for the group on the system/platform.useruser.target.group.namekeyword Name of the group.useruser.target.hashkeyword Unique user hash to correlate information for a user in anonymized form

form.useruser.target.idkeywordS-1-5-21-202424912787-2692429404-2351956786-1000Unique identifier of the user.useruser.target.namekeyworda.einstein Short name or login of the

user.useruser.target.name.textmatch_only_texta.einstein Short name or login of the user.
user.useruser.target.roleskeyword["kibana_admin", "reporting_user"] Array of user roles at the time of the event.
user_agentuser_agent.device.namekeywordiPhone Name of the device.
user_agentuser_agent.namekeywordSafari Name of the user agent.
user_agentuser_agent.originalkeywordMozilla/5.0 (iPhone; CPU iPhone OS 12_1 like Mac OS X) AppleWebKit/605.1.15 (KHTML, like Gecko) Version/12.0 Mobile/15E148 Safari/604.1Unparsed user_agent string.
user_agentuser_agent.original.textmatch_only_textMozilla/5.0 (iPhone; CPU iPhone OS 12_1 like Mac OS X) AppleWebKit/605.1.15 (KHTML, like Gecko) Version/12.0 Mobile/15E148 Safari/604.1Unparsed user_agent string.
user_agentuser_agent.os.familykeyworddebian OS family (such as redhat, debian, freebsd, windows).
user_agentuser_agent.os.fullkeywordMac OS Mojave Operating system name, including the version or code name.
user_agentuser_agent.os.full.textmatch_only_textMac OS Mojave Operating system name, including the version or code name.
user_agentuser_agent.os.kernelkeyword4.4.0-112-generic Operating system kernel version as a raw string.
user_agentuser_agent.os.namekeywordMac OS X Operating system name, without the version.
user_agentuser_agent.os.name.textmatch_only_textMac OS X Operating system name, without the version.
user_agentuser_agent.os.platformkeyworddarwin Operating system platform (such centos, ubuntu, windows).
user_agentuser_agent.os.typekeywordmacos Which commercial OS family (one of: linux, macos, unix, windows, ios or android).
user_agentuser_agent.os.versionkeyword10.14.1 Operating system version as a raw string.
user_agentuser_agent.versionkeyword 12Version of the user agent.
volumevolume.bus_typekeywordFileBackedVirtual Bus type of the device.
volumevolume.default_accesskeyword Bus type of the device.
volumevolume.device_namekeyword Device name of the volume.
volumevolume.device_typekeywordCD-ROM File System Volume device type.
volumevolume.dos_namekeywordE: DOS name of the device.
volumevolume.file_system_typekeyword Volume device file system type.
volumevolume.mount_namekeyword Mount name of the volume.
volumevolume.nt_namekeyword\\Device\\Cdrom1 NT name of the device.
volumevolume.product_idkeyword ProductID of the device.
volumevolume.product_namekeywordVirtual DVD-ROM Produce name of the volume.
volumevolume.removableboolean Indicates if the volume is removable.
volumevolume.serial_numberkeyword Serial number of the device.
volumevolume.sizekeyword Size of the volume device in bytes.
volumevolume.vendor_idkeyword VendorID of the device.
volumevolume.vendor_namekeywordMsft Vendor name of the device.
volumevolume.writableboolean Indicates if the volume is writable.
vulnerabilityvulnerability.categorykeyword["Firewall"] Category of a vulnerability.
vulnerabilityvulnerability.classificationkeywordCVSS Classification of the vulnerability.
vulnerabilityvulnerability.descriptionkeywordIn macOS before 2.12.6, there is a vulnerability in the RPC...Description of the vulnerability.
vulnerabilityvulnerability.description.textmatch_only_textIn macOS before 2.12.6,

there is a vulnerability in the RPC...Description of the
vulnerability.vulnerabilityvulnerability.enumerationkeywordCVE Identifier of the
vulnerability.vulnerabilityvulnerability.idkeywordCVE-2019-00001 ID of the
vulnerability.vulnerabilityvulnerability.referencekeywordhttps://cve.mitre.org/cgi-bin/cvename.cgi
?name=CVE-2019-6111Reference of the vulnerability.vulnerabilityvulnerability.report_idkeyword
20191018Scan identification number.vulnerabilityvulnerability.scanner.vendorkeywordTenable
Name of the scanner vendor.vulnerabilityvulnerability.score.basefloat 5.5Vulnerability Base
score.vulnerabilityvulnerability.score.environmentalfloat 5.5Vulnerability Environmental
score.vulnerabilityvulnerability.score.temporalfloat Vulnerability Temporal
score.vulnerabilityvulnerability.score.versionkeyword 2CVSS
version.vulnerabilityvulnerability.severitykeywordCritical Severity of the vulnerability.