

Field	Description
@timestamp	Date/time when the event originated.
labels	Custom key/value pairs.
message	Log message optimized for viewing in a log viewer.
tags	List of keywords used to tag each event.
agent.build.original	Extended build information for the agent.
agent.ephemeral_id	Ephemeral identifier of this agent.
agent.id	Unique identifier of this agent.
agent.name	Custom name of the agent.
agent.type	Type of the agent.
agent.version	Version of the agent.
client.address	Client network address.
client.as.number	Unique number allocated to the autonomous system.
client.as.organization.name	Organization name.
client.as.organization.name.text	Organization name.
client.bytes	Bytes sent from the client to the server.
client.domain	The domain name of the client.
client.geo.city_name	City name.
client.geo.continent_code	Continent code.
client.geo.continent_name	Name of the continent.
client.geo.country_iso_code	Country ISO code.
client.geo.country_name	Country name.
client.geo.location	Longitude and latitude.
client.geo.name	User-defined description of a location.
client.geo.postal_code	Postal code.
client.geo.region_iso_code	Region ISO code.
client.geo.region_name	Region name.
client.geo.timezone	Time zone.
client.ip	IP address of the client.
client.mac	MAC address of the client.
client.nat.ip	Client NAT ip address
client.nat.port	Client NAT port
client.packets	Packets sent from the client to the server.
client.port	Port of the client.
client.registered_domain	The highest registered client domain, stripped of the subdomain.
client.subdomain	The subdomain of the domain.
client.top_level_domain	The effective top level domain (com, org, net, co.uk).
client.user.domain	Name of the directory the user is a member of.

client.user.email	User email address.
client.user.full_name	User's full name, if available.
client.user.full_name.text	User's full name, if available.
client.user.group.domain	Name of the directory the group is a member of.
client.user.group.id	Unique identifier for the group on the system/platform.
client.user.group.name	Name of the group.
client.user.hash	Unique user hash to correlate information for a user in anonymized form.
client.user.id	Unique identifier of the user.
client.user.name	Short name or login of the user.
client.user.name.text	Short name or login of the user.
client.user.roles	Array of user roles at the time of the event.
cloud.account.id	The cloud account or organization id.
cloud.account.name	The cloud account name.
cloud.availability_zone	Availability zone in which this host, resource, or service is located.
cloud.entity.attributes.known_redirects	Known redirect URIs or URLs associated with this entity.
cloud.entity.attributes.managed	Indicates whether the entity is managed by an external system.
cloud.entity.attributes.mfa_enabled	Indicates whether multi-factor authentication is enabled for this entity.
cloud.entity.attributes.oauth_consent_restriction	Restriction applied to OAuth consent for this entity.
cloud.entity.attributes.permissions	Action-level permissions associated with this entity.
cloud.entity.attributes.storage_class	Storage tier or class assigned to an object storage resource.
cloud.entity.behavior	A set of ephemeral characteristics of the entity, derived from observed behaviors during a specific time period.
cloud.entity.display_name	An optional field used when a pretty name is desired for entity-centric operations.
cloud.entity.display_name.text	An optional field used when a pretty name is desired for entity-centric operations.
cloud.entity.id	Unique identifier for the entity.
cloud.entity.last_seen_timestamp	Indicates the date/time when this entity was last "seen."
cloud.entity.lifecycle.last_activity	Timestamp of the most recent action performed by or attributed to this entity.
cloud.entity.metrics	Field set for any fields containing numeric entity metrics.
cloud.entity.name	The name of the entity.
cloud.entity.name.text	The name of the entity.
cloud.entity.raw	Original, unmodified fields from the source system.
cloud.entity.reference	A URI, URL, or other direct reference to access or locate the entity.
cloud.entity.relationships.administers.entity.id	Identifiers of referenced entities.
cloud.entity.relationships.administers.host.id	Referenced host ids.
cloud.entity.relationships.administers.host.name	Referenced host names.
cloud.entity.relationships.administers.service.id	Referenced service ids.
cloud.entity.relationships.administers.service.name	Referenced service names.
cloud.entity.relationships.administers.user.domain	Referenced user directory or AD/LDAP domain names.
cloud.entity.relationships.administers.user.email	Referenced user email addresses.

cloud.entity.relationships.administers.user.id	Referenced user ids.
cloud.entity.relationships.administers.user.name	Referenced user short names or logins.
cloud.entity.relationships.depends_on.entity.id	Identifiers of referenced entities.
cloud.entity.relationships.depends_on.host.id	Referenced host ids.
cloud.entity.relationships.depends_on.host.name	Referenced host names.
cloud.entity.relationships.depends_on.service.id	Referenced service ids.
cloud.entity.relationships.depends_on.service.name	Referenced service names.
cloud.entity.relationships.depends_on.user.domain	Referenced user directory or AD/LDAP domain names.
cloud.entity.relationships.depends_on.user.email	Referenced user email addresses.
cloud.entity.relationships.depends_on.user.id	Referenced user ids.
cloud.entity.relationships.depends_on.user.name	Referenced user short names or logins.
cloud.entity.relationships.owns.entity.id	Identifiers of referenced entities.
cloud.entity.relationships.owns.host.id	Referenced host ids.
cloud.entity.relationships.owns.host.name	Referenced host names.
cloud.entity.relationships.owns.service.id	Referenced service ids.
cloud.entity.relationships.owns.service.name	Referenced service names.
cloud.entity.relationships.owns.user.domain	Referenced user directory or AD/LDAP domain names.
cloud.entity.relationships.owns.user.email	Referenced user email addresses.
cloud.entity.relationships.owns.user.id	Referenced user ids.
cloud.entity.relationships.owns.user.name	Referenced user short names or logins.
cloud.entity.relationships.supervises.entity.id	Identifiers of referenced entities.
cloud.entity.relationships.supervises.host.id	Referenced host ids.
cloud.entity.relationships.supervises.host.name	Referenced host names.
cloud.entity.relationships.supervises.service.id	Referenced service ids.
cloud.entity.relationships.supervises.service.name	Referenced service names.
cloud.entity.relationships.supervises.user.domain	Referenced user directory or AD/LDAP domain names.
cloud.entity.relationships.supervises.user.email	Referenced user email addresses.
cloud.entity.relationships.supervises.user.id	Referenced user ids.
cloud.entity.relationships.supervises.user.name	Referenced user short names or logins.
cloud.entity.source	Source module or integration that provided the entity data.
cloud.entity.sub_type	The specific type designation for the entity as defined by its provider or system.
cloud.entity.type	Standardized high-level classification of the entity.
cloud.instance.id	Instance ID of the host machine.
cloud.instance.name	Instance name of the host machine.
cloud.machine.type	Machine type of the host machine.
cloud.origin.account.id	The cloud account or organization id.
cloud.origin.account.name	The cloud account name.
cloud.origin.availability_zone	Availability zone in which this host, resource, or service is located.

cloud.origin.entity.attributes.known_redirects	Known redirect URIs or URLs associated with this entity.
cloud.origin.entity.attributes.managed	Indicates whether the entity is managed by an external system.
cloud.origin.entity.attributes.mfa_enabled	Indicates whether multi-factor authentication is enabled for this entity.
cloud.origin.entity.attributes.oauth_consent_restriction	Restriction applied to OAuth consent for this entity.
cloud.origin.entity.attributes.permissions	Action-level permissions associated with this entity.
cloud.origin.entity.attributes.storage_class	Storage tier or class assigned to an object storage resource.
cloud.origin.entity.behavior	A set of ephemeral characteristics of the entity, derived from observed behaviors during a specific time period.
cloud.origin.entity.display_name	An optional field used when a pretty name is desired for entity-centric operations.
cloud.origin.entity.display_name.text	An optional field used when a pretty name is desired for entity-centric operations.
cloud.origin.entity.id	Unique identifier for the entity.
cloud.origin.entity.last_seen_timestamp	Indicates the date/time when this entity was last "seen."
cloud.origin.entity.lifecycle.last_activity	Timestamp of the most recent action performed by or attributed to this entity.
cloud.origin.entity.metrics	Field set for any fields containing numeric entity metrics.
cloud.origin.entity.name	The name of the entity.
cloud.origin.entity.name.text	The name of the entity.
cloud.origin.entity.raw	Original, unmodified fields from the source system.
cloud.origin.entity.reference	A URI, URL, or other direct reference to access or locate the entity.
cloud.origin.entity.relationships.administers.entity.id	Identifiers of referenced entities.
cloud.origin.entity.relationships.administers.host.id	Referenced host ids.
cloud.origin.entity.relationships.administers.host.name	Referenced host names.
cloud.origin.entity.relationships.administers.service.id	Referenced service ids.
cloud.origin.entity.relationships.administers.service.name	Referenced service names.
cloud.origin.entity.relationships.administers.user.domain	Referenced user directory or AD/LDAP domain names.
cloud.origin.entity.relationships.administers.user.email	Referenced user email addresses.
cloud.origin.entity.relationships.administers.user.id	Referenced user ids.
cloud.origin.entity.relationships.administers.user.name	Referenced user short names or logins.
cloud.origin.entity.relationships.depends_on.entity.id	Identifiers of referenced entities.
cloud.origin.entity.relationships.depends_on.host.id	Referenced host ids.
cloud.origin.entity.relationships.depends_on.host.name	Referenced host names.
cloud.origin.entity.relationships.depends_on.service.id	Referenced service ids.
cloud.origin.entity.relationships.depends_on.service.name	Referenced service names.
cloud.origin.entity.relationships.depends_on.user.domain	Referenced user directory or AD/LDAP domain names.
cloud.origin.entity.relationships.depends_on.user.email	Referenced user email addresses.
cloud.origin.entity.relationships.depends_on.user.id	Referenced user ids.
cloud.origin.entity.relationships.depends_on.user.name	Referenced user short names or logins.
cloud.origin.entity.relationships.owns.entity.id	Identifiers of referenced entities.
cloud.origin.entity.relationships.owns.host.id	Referenced host ids.
cloud.origin.entity.relationships.owns.host.name	Referenced host names.

cloud.origin.entity.relationships.owns.service.id	Referenced service ids.
cloud.origin.entity.relationships.owns.service.name	Referenced service names.
cloud.origin.entity.relationships.owns.user.domain	Referenced user directory or AD/LDAP domain names.
cloud.origin.entity.relationships.owns.user.email	Referenced user email addresses.
cloud.origin.entity.relationships.owns.user.id	Referenced user ids.
cloud.origin.entity.relationships.owns.user.name	Referenced user short names or logins.
cloud.origin.entity.relationships.supervises.entity.id	Identifiers of referenced entities.
cloud.origin.entity.relationships.supervises.host.id	Referenced host ids.
cloud.origin.entity.relationships.supervises.host.name	Referenced host names.
cloud.origin.entity.relationships.supervises.service.id	Referenced service ids.
cloud.origin.entity.relationships.supervises.service.name	Referenced service names.
cloud.origin.entity.relationships.supervises.user.domain	Referenced user directory or AD/LDAP domain names.
cloud.origin.entity.relationships.supervises.user.email	Referenced user email addresses.
cloud.origin.entity.relationships.supervises.user.id	Referenced user ids.
cloud.origin.entity.relationships.supervises.user.name	Referenced user short names or logins.
cloud.origin.entity.source	Source module or integration that provided the entity data.
cloud.origin.entity.sub_type	The specific type designation for the entity as defined by its provider or system.
cloud.origin.entity.type	Standardized high-level classification of the entity.
cloud.origin.instance.id	Instance ID of the host machine.
cloud.origin.instance.name	Instance name of the host machine.
cloud.origin.machine.type	Machine type of the host machine.
cloud.origin.project.id	The cloud project id.
cloud.origin.project.name	The cloud project name.
cloud.origin.provider	Name of the cloud provider.
cloud.origin.region	Region in which this host, resource, or service is located.
cloud.origin.service.name	The cloud service name.
cloud.project.id	The cloud project id.
cloud.project.name	The cloud project name.
cloud.provider	Name of the cloud provider.
cloud.region	Region in which this host, resource, or service is located.
cloud.service.name	The cloud service name.
cloud.target.account.id	The cloud account or organization id.
cloud.target.account.name	The cloud account name.
cloud.target.availability_zone	Availability zone in which this host, resource, or service is located.
cloud.target.entity.attributes.known_redirects	Known redirect URIs or URLs associated with this entity.
cloud.target.entity.attributes.managed	Indicates whether the entity is managed by an external system.
cloud.target.entity.attributes.mfa_enabled	Indicates whether multi-factor authentication is enabled for this entity.
cloud.target.entity.attributes.oauth_consent_restriction	Restriction applied to OAuth consent for this entity.

cloud.target.entity.attributes.permissions	Action-level permissions associated with this entity.
cloud.target.entity.attributes.storage_class	Storage tier or class assigned to an object storage resource.
cloud.target.entity.behavior	A set of ephemeral characteristics of the entity, derived from observed behaviors during a specific time period.
cloud.target.entity.display_name	An optional field used when a pretty name is desired for entity-centric operations.
cloud.target.entity.display_name.text	An optional field used when a pretty name is desired for entity-centric operations.
cloud.target.entity.id	Unique identifier for the entity.
cloud.target.entity.last_seen_timestamp	Indicates the date/time when this entity was last "seen."
cloud.target.entity.lifecycle.last_activity	Timestamp of the most recent action performed by or attributed to this entity.
cloud.target.entity.metrics	Field set for any fields containing numeric entity metrics.
cloud.target.entity.name	The name of the entity.
cloud.target.entity.name.text	The name of the entity.
cloud.target.entity.raw	Original, unmodified fields from the source system.
cloud.target.entity.reference	A URI, URL, or other direct reference to access or locate the entity.
cloud.target.entity.relationships.administers.entity.id	Identifiers of referenced entities.
cloud.target.entity.relationships.administers.host.id	Referenced host ids.
cloud.target.entity.relationships.administers.host.name	Referenced host names.
cloud.target.entity.relationships.administers.service.id	Referenced service ids.
cloud.target.entity.relationships.administers.service.name	Referenced service names.
cloud.target.entity.relationships.administers.user.domain	Referenced user directory or AD/LDAP domain names.
cloud.target.entity.relationships.administers.user.email	Referenced user email addresses.
cloud.target.entity.relationships.administers.user.id	Referenced user ids.
cloud.target.entity.relationships.administers.user.name	Referenced user short names or logins.
cloud.target.entity.relationships.depends_on.entity.id	Identifiers of referenced entities.
cloud.target.entity.relationships.depends_on.host.id	Referenced host ids.
cloud.target.entity.relationships.depends_on.host.name	Referenced host names.
cloud.target.entity.relationships.depends_on.service.id	Referenced service ids.
cloud.target.entity.relationships.depends_on.service.name	Referenced service names.
cloud.target.entity.relationships.depends_on.user.domain	Referenced user directory or AD/LDAP domain names.
cloud.target.entity.relationships.depends_on.user.email	Referenced user email addresses.
cloud.target.entity.relationships.depends_on.user.id	Referenced user ids.
cloud.target.entity.relationships.depends_on.user.name	Referenced user short names or logins.
cloud.target.entity.relationships.owns.entity.id	Identifiers of referenced entities.
cloud.target.entity.relationships.owns.host.id	Referenced host ids.
cloud.target.entity.relationships.owns.host.name	Referenced host names.
cloud.target.entity.relationships.owns.service.id	Referenced service ids.
cloud.target.entity.relationships.owns.service.name	Referenced service names.
cloud.target.entity.relationships.owns.user.domain	Referenced user directory or AD/LDAP domain names.
cloud.target.entity.relationships.owns.user.email	Referenced user email addresses.

cloud.target.entity.relationships.owns.user.id	Referenced user ids.
cloud.target.entity.relationships.owns.user.name	Referenced user short names or logins.
cloud.target.entity.relationships.supervises.entity.id	Identifiers of referenced entities.
cloud.target.entity.relationships.supervises.host.id	Referenced host ids.
cloud.target.entity.relationships.supervises.host.name	Referenced host names.
cloud.target.entity.relationships.supervises.service.id	Referenced service ids.
cloud.target.entity.relationships.supervises.service.name	Referenced service names.
cloud.target.entity.relationships.supervises.user.domain	Referenced user directory or AD/LDAP domain names.
cloud.target.entity.relationships.supervises.user.email	Referenced user email addresses.
cloud.target.entity.relationships.supervises.user.id	Referenced user ids.
cloud.target.entity.relationships.supervises.user.name	Referenced user short names or logins.
cloud.target.entity.source	Source module or integration that provided the entity data.
cloud.target.entity.sub_type	The specific type designation for the entity as defined by its provider or system.
cloud.target.entity.type	Standardized high-level classification of the entity.
cloud.target.instance.id	Instance ID of the host machine.
cloud.target.instance.name	Instance name of the host machine.
cloud.target.machine.type	Machine type of the host machine.
cloud.target.project.id	The cloud project id.
cloud.target.project.name	The cloud project name.
cloud.target.provider	Name of the cloud provider.
cloud.target.region	Region in which this host, resource, or service is located.
cloud.target.service.name	The cloud service name.
container.cpu.usage	Percent CPU used, between 0 and 1.
container.disk.read.bytes	The number of bytes read by all disks.
container.disk.write.bytes	The number of bytes written on all disks.
container.id	Unique container id.
container.image.hash.all	An array of digests of the image the container was built on.
container.image.name	Name of the image the container was built on.
container.image.tag	Container image tags.
container.labels	Image labels.
container.memory.usage	Percent memory used, between 0 and 1.
container.name	Container name.
container.network.egress.bytes	The number of bytes sent on all network interfaces.
container.network.ingress.bytes	The number of bytes received on all network interfaces.
container.runtime	Runtime managing this container.
container.security_context.privileged	Indicates whether the container is running in privileged mode.
data_stream.dataset	The field can contain anything that makes sense to signify the source of the data.
data_stream.namespace	A user defined namespace. Namespaces are useful to allow grouping of data.

data_stream.type	An overarching type for the data stream.
destination.address	Destination network address.
destination.as.number	Unique number allocated to the autonomous system.
destination.as.organization.name	Organization name.
destination.as.organization.name.text	Organization name.
destination.bytes	Bytes sent from the destination to the source.
destination.domain	The domain name of the destination.
destination.geo.city_name	City name.
destination.geo.continent_code	Continent code.
destination.geo.continent_name	Name of the continent.
destination.geo.country_iso_code	Country ISO code.
destination.geo.country_name	Country name.
destination.geo.location	Longitude and latitude.
destination.geo.name	User-defined description of a location.
destination.geo.postal_code	Postal code.
destination.geo.region_iso_code	Region ISO code.
destination.geo.region_name	Region name.
destination.geo.timezone	Time zone.
destination.ip	IP address of the destination.
destination.mac	MAC address of the destination.
destination.nat.ip	Destination NAT ip
destination.nat.port	Destination NAT Port
destination.packets	Packets sent from the destination to the source.
destination.port	Port of the destination.
destination.registered_domain	The highest registered destination domain, stripped of the subdomain.
destination.subdomain	The subdomain of the domain.
destination.top_level_domain	The effective top level domain (com, org, net, co.uk).
destination.user.domain	Name of the directory the user is a member of.
destination.user.email	User email address.
destination.user.full_name	User's full name, if available.
destination.user.full_name.text	User's full name, if available.
destination.user.group.domain	Name of the directory the group is a member of.
destination.user.group.id	Unique identifier for the group on the system/platform.
destination.user.group.name	Name of the group.
destination.user.hash	Unique user hash to correlate information for a user in anonymized form.
destination.user.id	Unique identifier of the user.
destination.user.name	Short name or login of the user.
destination.user.name.text	Short name or login of the user.

destination.user.roles	Array of user roles at the time of the event.
device.id	The unique identifier of a device.
device.manufacturer	The vendor name of the device manufacturer.
device.model.identifier	The machine readable identifier of the device model.
device.model.name	The human readable marketing name of the device model.
device.product.id	ProductID of the device
device.product.name	Product name of the device
device.serial_number	Serial Number of the device
device.type	Device type classification
device.vendor.id	VendorID of the device
device.vendor.name	Vendor name of the device
dll.code_signature.digest_algorithm	Hashing algorithm used to sign the process.
dll.code_signature.exists	Boolean to capture if a signature is present.
dll.code_signature.flags	Code signing flags of the process
dll.code_signature.signing_id	The identifier used to sign the process.
dll.code_signature.status	Additional information about the certificate status.
dll.code_signature.subject_name	Subject name of the code signer
dll.code_signature.team_id	The team identifier used to sign the process.
dll.code_signature.thumbprint_sha256	SHA256 hash of the certificate.
dll.code_signature.timestamp	When the signature was generated and signed.
dll.code_signature.trusted	Stores the trust status of the certificate chain.
dll.code_signature.valid	Boolean to capture if the digital signature is verified against the binary content.
dll.hash.cdhash	The Code Directory (CD) hash of an executable.
dll.hash.md5	MD5 hash.
dll.hash.sha1	SHA1 hash.
dll.hash.sha256	SHA256 hash.
dll.hash.sha384	SHA384 hash.
dll.hash.sha512	SHA512 hash.
dll.hash.ssdeep	SSDEEP hash.
dll.hash.tlsh	TLSH hash.
dll.name	Name of the library.
dll.origin_referrer_url	The URL of the webpage that linked to the dll file.
dll.origin_url	The URL where the dll file is hosted.
dll.path	Full file path of the library.
dll.pe.architecture	CPU architecture target for the file.
dll.pe.company	Internal company name of the file, provided at compile-time.
dll.pe.description	Internal description of the file, provided at compile-time.
dll.pe.file_version	Process name.

dll.pe.go_import_hash	A hash of the Go language imports in a PE file.
dll.pe.go_imports	List of imported Go language element names and types.
dll.pe.go_imports_names_entropy	Shannon entropy calculation from the list of Go imports.
dll.pe.go_imports_names_var_entropy	Variance for Shannon entropy calculation from the list of Go imports.
dll.pe.go_stripped	Whether the file is a stripped or obfuscated Go executable.
dll.pe.imphash	A hash of the imports in a PE file.
dll.pe.import_hash	A hash of the imports in a PE file.
dll.pe.imports	List of imported element names and types.
dll.pe.imports_names_entropy	Shannon entropy calculation from the list of imported element names and types.
dll.pe.imports_names_var_entropy	Variance for Shannon entropy calculation from the list of imported element names and types.
dll.pe.original_file_name	Internal name of the file, provided at compile-time.
dll.pe.pehash	A hash of the PE header and data from one or more PE sections.
dll.pe.product	Internal product name of the file, provided at compile-time.
dll.pe.sections	Section information of the PE file.
dll.pe.sections.entropy	Shannon entropy calculation from the section.
dll.pe.sections.name	PE Section List name.
dll.pe.sections.physical_size	PE Section List physical size.
dll.pe.sections.var_entropy	Variance for Shannon entropy calculation from the section.
dll.pe.sections.virtual_size	PE Section List virtual size. This is always the same as `physical_size`.
dns.answers	Array of DNS answers.
dns.answers.class	The class of DNS data contained in this resource record.
dns.answers.data	The data describing the resource.
dns.answers.name	The domain name to which this resource record pertains.
dns.answers.ttl	The time interval in seconds that this resource record may be cached before it should be discarded.
dns.answers.type	The type of data contained in this resource record.
dns.header_flags	Array of DNS header flags.
dns.id	The DNS packet identifier assigned by the program that generated the query. The identifier is copied to the response.
dns.op_code	The DNS operation code that specifies the kind of query in the message.
dns.question.class	The class of records being queried.
dns.question.name	The name being queried.
dns.question.registered_domain	The highest registered domain, stripped of the subdomain.
dns.question.subdomain	The subdomain of the domain.
dns.question.top_level_domain	The effective top level domain (com, org, net, co.uk).
dns.question.type	The type of record being queried.
dns.resolved_ip	Array containing all IPs seen in answers.data
dns.response_code	The DNS response code.
dns.type	The type of DNS event captured, query or answer.
ecs.version	ECS version this event conforms to.

email.attachments	List of objects describing the attachments.
email.attachments.file.extension	Attachment file extension.
email.attachments.file.hash.cdhash	The Code Directory (CD) hash of an executable.
email.attachments.file.hash.md5	MD5 hash.
email.attachments.file.hash.sha1	SHA1 hash.
email.attachments.file.hash.sha256	SHA256 hash.
email.attachments.file.hash.sha384	SHA384 hash.
email.attachments.file.hash.sha512	SHA512 hash.
email.attachments.file.hash.ssdeep	SSDEEP hash.
email.attachments.file.hash.tlsh	TLSH hash.
email.attachments.file.mime_type	MIME type of the attachment file.
email.attachments.file.name	Name of the attachment file.
email.attachments.file.size	Attachment file size.
email.bcc.address	Email address of BCC recipient
email.cc.address	Email address of CC recipient
email.content_type	MIME type of the email message.
email.delivery_timestamp	Date and time when message was delivered.
email.direction	Direction of the message.
email.from.address	The sender's email address.
email.local_id	Unique identifier given by the source.
email.message_id	Value from the Message-ID header.
email.origination_timestamp	Date and time the email was composed.
email.reply_to.address	Address replies should be delivered to.
email.sender.address	Address of the message sender.
email.subject	The subject of the email message.
email.subject.text	The subject of the email message.
email.to.address	Email address of recipient
email.x_mailer	Application that drafted email.
entity.attributes.known_redirects	Known redirect URIs or URLs associated with this entity.
entity.attributes.managed	Indicates whether the entity is managed by an external system.
entity.attributes.mfa_enabled	Indicates whether multi-factor authentication is enabled for this entity.
entity.attributes.oauth_consent_restriction	Restriction applied to OAuth consent for this entity.
entity.attributes.permissions	Action-level permissions associated with this entity.
entity.attributes.storage_class	Storage tier or class assigned to an object storage resource.
entity.behavior	A set of ephemeral characteristics of the entity, derived from observed behaviors during a specific time period.
entity.display_name	An optional field used when a pretty name is desired for entity-centric operations.
entity.display_name.text	An optional field used when a pretty name is desired for entity-centric operations.
entity.id	Unique identifier for the entity.

entity.last_seen_timestamp	Indicates the date/time when this entity was last "seen."
entity.lifecycle.last_activity	Timestamp of the most recent action performed by or attributed to this entity.
entity.metrics	Field set for any fields containing numeric entity metrics.
entity.name	The name of the entity.
entity.name.text	The name of the entity.
entity.raw	Original, unmodified fields from the source system.
entity.reference	A URI, URL, or other direct reference to access or locate the entity.
entity.relationships.administers.entity.id	Identifiers of referenced entities.
entity.relationships.administers.host.id	Referenced host ids.
entity.relationships.administers.host.name	Referenced host names.
entity.relationships.administers.service.id	Referenced service ids.
entity.relationships.administers.service.name	Referenced service names.
entity.relationships.administers.user.domain	Referenced user directory or AD/LDAP domain names.
entity.relationships.administers.user.email	Referenced user email addresses.
entity.relationships.administers.user.id	Referenced user ids.
entity.relationships.administers.user.name	Referenced user short names or logins.
entity.relationships.depends_on.entity.id	Identifiers of referenced entities.
entity.relationships.depends_on.host.id	Referenced host ids.
entity.relationships.depends_on.host.name	Referenced host names.
entity.relationships.depends_on.service.id	Referenced service ids.
entity.relationships.depends_on.service.name	Referenced service names.
entity.relationships.depends_on.user.domain	Referenced user directory or AD/LDAP domain names.
entity.relationships.depends_on.user.email	Referenced user email addresses.
entity.relationships.depends_on.user.id	Referenced user ids.
entity.relationships.depends_on.user.name	Referenced user short names or logins.
entity.relationships.owns.entity.id	Identifiers of referenced entities.
entity.relationships.owns.host.id	Referenced host ids.
entity.relationships.owns.host.name	Referenced host names.
entity.relationships.owns.service.id	Referenced service ids.
entity.relationships.owns.service.name	Referenced service names.
entity.relationships.owns.user.domain	Referenced user directory or AD/LDAP domain names.
entity.relationships.owns.user.email	Referenced user email addresses.
entity.relationships.owns.user.id	Referenced user ids.
entity.relationships.owns.user.name	Referenced user short names or logins.
entity.relationships.supervises.entity.id	Identifiers of referenced entities.
entity.relationships.supervises.host.id	Referenced host ids.
entity.relationships.supervises.host.name	Referenced host names.
entity.relationships.supervises.service.id	Referenced service ids.

entity.relationships.supervises.service.name	Referenced service names.
entity.relationships.supervises.user.domain	Referenced user directory or AD/LDAP domain names.
entity.relationships.supervises.user.email	Referenced user email addresses.
entity.relationships.supervises.user.id	Referenced user ids.
entity.relationships.supervises.user.name	Referenced user short names or logins.
entity.source	Source module or integration that provided the entity data.
entity.sub_type	The specific type designation for the entity as defined by its provider or system.
entity.target.attributes.known_redirects	Known redirect URIs or URLs associated with this entity.
entity.target.attributes.managed	Indicates whether the entity is managed by an external system.
entity.target.attributes.mfa_enabled	Indicates whether multi-factor authentication is enabled for this entity.
entity.target.attributes.oauth_consent_restriction	Restriction applied to OAuth consent for this entity.
entity.target.attributes.permissions	Action-level permissions associated with this entity.
entity.target.attributes.storage_class	Storage tier or class assigned to an object storage resource.
entity.target.behavior	A set of ephemeral characteristics of the entity, derived from observed behaviors during a specific time period.
entity.target.display_name	An optional field used when a pretty name is desired for entity-centric operations.
entity.target.display_name.text	An optional field used when a pretty name is desired for entity-centric operations.
entity.target.id	Unique identifier for the entity.
entity.target.last_seen_timestamp	Indicates the date/time when this entity was last "seen."
entity.target.lifecycle.last_activity	Timestamp of the most recent action performed by or attributed to this entity.
entity.target.metrics	Field set for any fields containing numeric entity metrics.
entity.target.name	The name of the entity.
entity.target.name.text	The name of the entity.
entity.target.raw	Original, unmodified fields from the source system.
entity.target.reference	A URI, URL, or other direct reference to access or locate the entity.
entity.target.relationships.administers.entity.id	Identifiers of referenced entities.
entity.target.relationships.administers.host.id	Referenced host ids.
entity.target.relationships.administers.host.name	Referenced host names.
entity.target.relationships.administers.service.id	Referenced service ids.
entity.target.relationships.administers.service.name	Referenced service names.
entity.target.relationships.administers.user.domain	Referenced user directory or AD/LDAP domain names.
entity.target.relationships.administers.user.email	Referenced user email addresses.
entity.target.relationships.administers.user.id	Referenced user ids.
entity.target.relationships.administers.user.name	Referenced user short names or logins.
entity.target.relationships.depends_on.entity.id	Identifiers of referenced entities.
entity.target.relationships.depends_on.host.id	Referenced host ids.
entity.target.relationships.depends_on.host.name	Referenced host names.
entity.target.relationships.depends_on.service.id	Referenced service ids.
entity.target.relationships.depends_on.service.name	Referenced service names.

entity.target.relationships.depends_on.user.domain	Referenced user directory or AD/LDAP domain names.
entity.target.relationships.depends_on.user.email	Referenced user email addresses.
entity.target.relationships.depends_on.user.id	Referenced user ids.
entity.target.relationships.depends_on.user.name	Referenced user short names or logins.
entity.target.relationships.owns.entity.id	Identifiers of referenced entities.
entity.target.relationships.owns.host.id	Referenced host ids.
entity.target.relationships.owns.host.name	Referenced host names.
entity.target.relationships.owns.service.id	Referenced service ids.
entity.target.relationships.owns.service.name	Referenced service names.
entity.target.relationships.owns.user.domain	Referenced user directory or AD/LDAP domain names.
entity.target.relationships.owns.user.email	Referenced user email addresses.
entity.target.relationships.owns.user.id	Referenced user ids.
entity.target.relationships.owns.user.name	Referenced user short names or logins.
entity.target.relationships.supervises.entity.id	Identifiers of referenced entities.
entity.target.relationships.supervises.host.id	Referenced host ids.
entity.target.relationships.supervises.host.name	Referenced host names.
entity.target.relationships.supervises.service.id	Referenced service ids.
entity.target.relationships.supervises.service.name	Referenced service names.
entity.target.relationships.supervises.user.domain	Referenced user directory or AD/LDAP domain names.
entity.target.relationships.supervises.user.email	Referenced user email addresses.
entity.target.relationships.supervises.user.id	Referenced user ids.
entity.target.relationships.supervises.user.name	Referenced user short names or logins.
entity.target.source	Source module or integration that provided the entity data.
entity.target.sub_type	The specific type designation for the entity as defined by its provider or system.
entity.target.type	Standardized high-level classification of the entity.
entity.type	Standardized high-level classification of the entity.
error.code	Error code describing the error.
error.id	Unique identifier for the error.
error.message	Error message.
error.stack_trace	The stack trace of this error in plain text.
error.stack_trace.text	The stack trace of this error in plain text.
error.type	The type of the error, for example the class name of the exception.
event.action	The action captured by the event.
event.agent_id_status	Validation status of the event's agent.id field.
event.category	Event category. The second categorization field in the hierarchy.
event.code	Identification code for this event.
event.created	Time when the event was first read by an agent or by your pipeline.
event.dataset	Name of the dataset.

event.duration	Duration of the event in nanoseconds.
event.end	`event.end` contains the date when the event ended or when the activity was last observed.
event.hash	Hash (perhaps logstash fingerprint) of raw field to be able to demonstrate log integrity.
event.id	Unique ID to describe the event.
event.ingested	Timestamp when an event arrived in the central data store.
event.kind	The kind of the event. The highest categorization field in the hierarchy.
event.module	Name of the module this data is coming from.
event.original	Raw text message of entire event.
event.outcome	The outcome of the event. The lowest level categorization field in the hierarchy.
event.provider	Source of the event.
event.reason	Reason why this event happened, according to the source
event.reference	Event reference URL
event.risk_score	Risk score or priority of the event (e.g. security solutions). Use your system's original value here.
event.risk_score_norm	Normalized risk score or priority of the event (0-100).
event.sequence	Sequence number of the event.
event.severity	Numeric severity of the event.
event.start	`event.start` contains the date when the event started or when the activity was first observed.
event.timezone	Event time zone.
event.type	Event type. The third categorization field in the hierarchy.
event.url	Event investigation URL
faas.coldstart	Boolean value indicating a cold start of a function.
faas.execution	The execution ID of the current function execution.
faas.id	The unique identifier of a serverless function.
faas.name	The name of a serverless function.
faas.trigger.request_id	The ID of the trigger request , message, event, etc.
faas.trigger.type	The trigger for the function execution.
faas.version	The version of a serverless function.
file.accessed	Last time the file was accessed.
file.attributes	Array of file attributes.
file.code_signature.digest_algorithm	Hashing algorithm used to sign the process.
file.code_signature.exists	Boolean to capture if a signature is present.
file.code_signature.flags	Code signing flags of the process
file.code_signature.signing_id	The identifier used to sign the process.
file.code_signature.status	Additional information about the certificate status.
file.code_signature.subject_name	Subject name of the code signer
file.code_signature.team_id	The team identifier used to sign the process.
file.code_signature.thumbprint_sha256	SHA256 hash of the certificate.
file.code_signature.timestamp	When the signature was generated and signed.

file.code_signature.trusted	Stores the trust status of the certificate chain.
file.code_signature.valid	Boolean to capture if the digital signature is verified against the binary content.
file.created	File creation time.
file.ctime	Last time the file attributes or metadata changed.
file.device	Device that is the source of the file.
file.directory	Directory where the file is located.
file.drive_letter	Drive letter where the file is located.
file.elf.architecture	Machine architecture of the ELF file.
file.elf.byte_order	Byte sequence of ELF file.
file.elf.cpu_type	CPU type of the ELF file.
file.elf.creation_date	Build or compile date.
file.elf.exports	List of exported element names and types.
file.elf.go_import_hash	A hash of the Go language imports in an ELF file.
file.elf.go_imports	List of imported Go language element names and types.
file.elf.go_imports_names_entropy	Shannon entropy calculation from the list of Go imports.
file.elf.go_imports_names_var_entropy	Variance for Shannon entropy calculation from the list of Go imports.
file.elf.go_stripped	Whether the file is a stripped or obfuscated Go executable.
file.elf.header.abi_version	Version of the ELF Application Binary Interface (ABI).
file.elf.header.class	Header class of the ELF file.
file.elf.header.data	Data table of the ELF header.
file.elf.header.entrypoint	Header entrypoint of the ELF file.
file.elf.header.object_version	"0x1" for original ELF files.
file.elf.header.os_abi	Application Binary Interface (ABI) of the Linux OS.
file.elf.header.type	Header type of the ELF file.
file.elf.header.version	Version of the ELF header.
file.elf.import_hash	A hash of the imports in an ELF file.
file.elf.imports	List of imported element names and types.
file.elf.imports_names_entropy	Shannon entropy calculation from the list of imported element names and types.
file.elf.imports_names_var_entropy	Variance for Shannon entropy calculation from the list of imported element names and types.
file.elf.sections	Section information of the ELF file.
file.elf.sections.chi2	Chi-square probability distribution of the section.
file.elf.sections.entropy	Shannon entropy calculation from the section.
file.elf.sections.flags	ELF Section List flags.
file.elf.sections.name	ELF Section List name.
file.elf.sections.physical_offset	ELF Section List offset.
file.elf.sections.physical_size	ELF Section List physical size.
file.elf.sections.type	ELF Section List type.
file.elf.sections.var_entropy	Variance for Shannon entropy calculation from the section.

file.elf.sections.virtual_address	ELF Section List virtual address.
file.elf.sections.virtual_size	ELF Section List virtual size.
file.elf.segments	ELF object segment list.
file.elf.segments.sections	ELF object segment sections.
file.elf.segments.type	ELF object segment type.
file.elf.shared_libraries	List of shared libraries used by this ELF object.
file.elf.telfhash	telfhash hash for ELF file.
file.extension	File extension, excluding the leading dot.
file.fork_name	A fork is additional data associated with a filesystem object.
file.gid	Primary group ID (GID) of the file.
file.group	Primary group name of the file.
file.hash.cdhash	The Code Directory (CD) hash of an executable.
file.hash.md5	MD5 hash.
file.hash.sha1	SHA1 hash.
file.hash.sha256	SHA256 hash.
file.hash.sha384	SHA384 hash.
file.hash.sha512	SHA512 hash.
file.hash.ssdeep	SSDEEP hash.
file.hash.tlsh	TLSH hash.
file.inode	Inode representing the file in the filesystem.
file.macho.go_import_hash	A hash of the Go language imports in a Mach-O file.
file.macho.go_imports	List of imported Go language element names and types.
file.macho.go_imports_names_entropy	Shannon entropy calculation from the list of Go imports.
file.macho.go_imports_names_var_entropy	Variance for Shannon entropy calculation from the list of Go imports.
file.macho.go_stripped	Whether the file is a stripped or obfuscated Go executable.
file.macho.import_hash	A hash of the imports in a Mach-O file.
file.macho.imports	List of imported element names and types.
file.macho.imports_names_entropy	Shannon entropy calculation from the list of imported element names and types.
file.macho.imports_names_var_entropy	Variance for Shannon entropy calculation from the list of imported element names and types.
file.macho.sections	Section information of the Mach-O file.
file.macho.sections.entropy	Shannon entropy calculation from the section.
file.macho.sections.name	Mach-O Section List name.
file.macho.sections.physical_size	Mach-O Section List physical size.
file.macho.sections.var_entropy	Variance for Shannon entropy calculation from the section.
file.macho.sections.virtual_size	Mach-O Section List virtual size. This is always the same as `physical_size`.
file.macho.symhash	A hash of the imports in a Mach-O file.
file.mime_type	Media type of file, document, or arrangement of bytes.
file.mode	Mode of the file in octal representation.

file.mtime	Last time the file content was modified.
file.name	Name of the file including the extension, without the directory.
file.origin_referrer_url	The URL of the webpage that linked to the file.
file.origin_url	The URL where the file is hosted.
file.owner	File owner's username.
file.path	Full path to the file, including the file name.
file.path.text	Full path to the file, including the file name.
file.pe.architecture	CPU architecture target for the file.
file.pe.company	Internal company name of the file, provided at compile-time.
file.pe.description	Internal description of the file, provided at compile-time.
file.pe.file_version	Process name.
file.pe.go_import_hash	A hash of the Go language imports in a PE file.
file.pe.go_imports	List of imported Go language element names and types.
file.pe.go_imports_names_entropy	Shannon entropy calculation from the list of Go imports.
file.pe.go_imports_names_var_entropy	Variance for Shannon entropy calculation from the list of Go imports.
file.pe.go_stripped	Whether the file is a stripped or obfuscated Go executable.
file.pe.imphash	A hash of the imports in a PE file.
file.pe.import_hash	A hash of the imports in a PE file.
file.pe.imports	List of imported element names and types.
file.pe.imports_names_entropy	Shannon entropy calculation from the list of imported element names and types.
file.pe.imports_names_var_entropy	Variance for Shannon entropy calculation from the list of imported element names and types.
file.pe.original_file_name	Internal name of the file, provided at compile-time.
file.pe.pehash	A hash of the PE header and data from one or more PE sections.
file.pe.product	Internal product name of the file, provided at compile-time.
file.pe.sections	Section information of the PE file.
file.pe.sections_entropy	Shannon entropy calculation from the section.
file.pe.sections.name	PE Section List name.
file.pe.sections.physical_size	PE Section List physical size.
file.pe.sections.var_entropy	Variance for Shannon entropy calculation from the section.
file.pe.sections.virtual_size	PE Section List virtual size. This is always the same as `physical_size`.
file.size	File size in bytes.
file.target_path	Target path for symlinks.
file.target_path.text	Target path for symlinks.
file.type	File type (file, dir, or symlink).
file.uid	The user ID (UID) or security identifier (SID) of the file owner.
file.x509.alternative_names	List of subject alternative names (SAN).
file.x509.issuer.common_name	List of common name (CN) of issuing certificate authority.
file.x509.issuer.country	List of country \(\C\) codes

file.x509.issuer.distinguished_name	Distinguished name (DN) of issuing certificate authority.
file.x509.issuer.locality	List of locality names (L)
file.x509.issuer.organization	List of organizations (O) of issuing certificate authority.
file.x509.issuer.organizational_unit	List of organizational units (OU) of issuing certificate authority.
file.x509.issuer.state_or_province	List of state or province names (ST, S, or P)
file.x509.not_after	Time at which the certificate is no longer considered valid.
file.x509.not_before	Time at which the certificate is first considered valid.
file.x509.public_key_algorithm	Algorithm used to generate the public key.
file.x509.public_key_curve	The curve used by the elliptic curve public key algorithm. This is algorithm specific.
file.x509.public_key_exponent	Exponent used to derive the public key. This is algorithm specific.
file.x509.public_key_size	The size of the public key space in bits.
file.x509.serial_number	Unique serial number issued by the certificate authority.
file.x509.signature_algorithm	Identifier for certificate signature algorithm.
file.x509.subject.common_name	List of common names (CN) of subject.
file.x509.subject.country	List of country \(\C\) code
file.x509.subject.distinguished_name	Distinguished name (DN) of the certificate subject entity.
file.x509.subject.locality	List of locality names (L)
file.x509.subject.organization	List of organizations (O) of subject.
file.x509.subject.organizational_unit	List of organizational units (OU) of subject.
file.x509.subject.state_or_province	List of state or province names (ST, S, or P)
file.x509.version_number	Version of x509 format.
gen_ai.agent.description	Free-form description of the GenAI agent provided by the application.
gen_ai.agent.id	The unique identifier of the GenAI agent.
gen_ai.agent.name	Human-readable name of the GenAI agent provided by the application.

<code>gen_ai.input.messages</code>	The chat history provided to the model as an input.
<code>gen_ai.operation.name</code>	The name of the operation being performed.
<code>gen_ai.output.messages</code>	Messages returned by the model where each message represents a specific model response (choice, candidate).
<code>gen_ai.output.type</code>	Represents the content type requested by the client.
<code>gen_ai.provider.name</code>	The Generative AI provider as identified by the client or server instrumentation.
<code>gen_ai.request.choice.count</code>	The target number of candidate completions to return.
<code>gen_ai.request.encoding_formats</code>	The encoding formats requested in an embeddings operation, if specified.
<code>gen_ai.request.frequency_penalty</code>	The frequency penalty setting for the GenAI request.
<code>gen_ai.request.max_tokens</code>	The maximum number of tokens the model generates for a request.
<code>gen_ai.request.model</code>	The name of the GenAI model a request is being made to.
<code>gen_ai.request.presence_penalty</code>	The presence penalty setting for the GenAI request.

gen_ai.request.seed	Requests with same seed value more likely to return same result.
gen_ai.request.stop_sequences	List of sequences that the model will use to stop generating further tokens.
gen_ai.request.temperature	The temperature setting for the GenAI request.
gen_ai.request.top_k	The top_k sampling setting for the GenAI request.
gen_ai.request.top_p	The top_p sampling setting for the GenAI request.
gen_ai.response.finish_reasons	Array of reasons the model stopped generating tokens, corresponding to each generation received.
gen_ai.response.id	The unique identifier for the completion.
gen_ai.response.model	The name of the model that generated the response.
gen_ai.system_instructions	The system message or instructions provided to the GenAI model separately from the chat history.
gen_ai.token.type	The type of token being counted.
gen_ai.tool.call.arguments	Parameters passed to the tool call.
gen_ai.tool.call.id	The tool call identifier.
gen_ai.tool.call.result	The result returned by the tool call (if any and if execution was successful).

gen_ai.tool.definitions	The list of source system tool definitions available to the GenAI agent or model.
gen_ai.tool.name	Name of the tool utilized by the agent.
gen_ai.tool.type	Type of the tool utilized by the agent
gen_ai.usage.input_tokens	The number of tokens used in the GenAI input (prompt).
gen_ai.usage.output_tokens	The number of tokens used in the GenAI response (completion).
group.domain	Name of the directory the group is a member of.
group.id	Unique identifier for the group on the system/platform.
group.name	Name of the group.
host.architecture	Operating system architecture.
host.boot.id	Linux boot uuid taken from /proc/sys/kernel/random/boot_id
host.cpu.usage	Percent CPU used, between 0 and 1.
host.disk.read.bytes	The number of bytes read by all disks.
host.disk.write.bytes	The number of bytes written on all disks.
host.domain	Name of the directory the group is a member of.
host.entity.attributes.known_redirects	Known redirect URIs or URLs associated with this entity.
host.entity.attributes.managed	Indicates whether the entity is managed by an external system.
host.entity.attributes.mfa_enabled	Indicates whether multi-factor authentication is enabled for this entity.
host.entity.attributes.oauth_consent_restriction	Restriction applied to OAuth consent for this entity.
host.entity.attributes.permissions	Action-level permissions associated with this entity.
host.entity.attributes.storage_class	Storage tier or class assigned to an object storage resource.
host.entity.behavior	A set of ephemeral characteristics of the entity, derived from observed behaviors during a specific time period.

host.entity.display_name	An optional field used when a pretty name is desired for entity-centric operations.
host.entity.display_name.text	An optional field used when a pretty name is desired for entity-centric operations.
host.entity.id	Unique identifier for the entity.
host.entity.last_seen_timestamp	Indicates the date/time when this entity was last "seen."
host.entity.lifecycle.last_activity	Timestamp of the most recent action performed by or attributed to this entity.
host.entity.metrics	Field set for any fields containing numeric entity metrics.
host.entity.name	The name of the entity.
host.entity.name.text	The name of the entity.
host.entity.raw	Original, unmodified fields from the source system.
host.entity.reference	A URI, URL, or other direct reference to access or locate the entity.
host.entity.relationships.administers.entity.id	Identifiers of referenced entities.
host.entity.relationships.administers.host.id	Referenced host ids.
host.entity.relationships.administers.host.name	Referenced host names.
host.entity.relationships.administers.service.id	Referenced service ids.
host.entity.relationships.administers.service.name	Referenced service names.
host.entity.relationships.administers.user.domain	Referenced user directory or AD/LDAP domain names.
host.entity.relationships.administers.user.email	Referenced user email addresses.
host.entity.relationships.administers.user.id	Referenced user ids.
host.entity.relationships.administers.user.name	Referenced user short names or logins.
host.entity.relationships.depends_on.entity.id	Identifiers of referenced entities.
host.entity.relationships.depends_on.host.id	Referenced host ids.
host.entity.relationships.depends_on.host.name	Referenced host names.
host.entity.relationships.depends_on.service.id	Referenced service ids.
host.entity.relationships.depends_on.service.name	Referenced service names.
host.entity.relationships.depends_on.user.domain	Referenced user directory or AD/LDAP domain names.
host.entity.relationships.depends_on.user.email	Referenced user email addresses.
host.entity.relationships.depends_on.user.id	Referenced user ids.
host.entity.relationships.depends_on.user.name	Referenced user short names or logins.
host.entity.relationships.owns.entity.id	Identifiers of referenced entities.
host.entity.relationships.owns.host.id	Referenced host ids.
host.entity.relationships.owns.host.name	Referenced host names.
host.entity.relationships.owns.service.id	Referenced service ids.
host.entity.relationships.owns.service.name	Referenced service names.
host.entity.relationships.owns.user.domain	Referenced user directory or AD/LDAP domain names.
host.entity.relationships.owns.user.email	Referenced user email addresses.
host.entity.relationships.owns.user.id	Referenced user ids.
host.entity.relationships.owns.user.name	Referenced user short names or logins.
host.entity.relationships.supervises.entity.id	Identifiers of referenced entities.

host.entity.relationships.supervises.host.id	Referenced host ids.
host.entity.relationships.supervises.host.name	Referenced host names.
host.entity.relationships.supervises.service.id	Referenced service ids.
host.entity.relationships.supervises.service.name	Referenced service names.
host.entity.relationships.supervises.user.domain	Referenced user directory or AD/LDAP domain names.
host.entity.relationships.supervises.user.email	Referenced user email addresses.
host.entity.relationships.supervises.user.id	Referenced user ids.
host.entity.relationships.supervises.user.name	Referenced user short names or logins.
host.entity.source	Source module or integration that provided the entity data.
host.entity.sub_type	The specific type designation for the entity as defined by its provider or system.
host.entity.type	Standardized high-level classification of the entity.
host.geo.city_name	City name.
host.geo.continent_code	Continent code.
host.geo.continent_name	Name of the continent.
host.geo.country_iso_code	Country ISO code.
host.geo.country_name	Country name.
host.geo.location	Longitude and latitude.
host.geo.name	User-defined description of a location.
host.geo.postal_code	Postal code.
host.geo.region_iso_code	Region ISO code.
host.geo.region_name	Region name.
host.geo.timezone	Time zone.
host.hostname	Hostname of the host.
host.id	Unique host id.
host.ip	Host ip addresses.
host.mac	Host MAC addresses.
host.name	Name of the host.
host.network.egress.bytes	The number of bytes sent on all network interfaces.
host.network.egress.packets	The number of packets sent on all network interfaces.
host.network.ingress.bytes	The number of bytes received on all network interfaces.
host.network.ingress.packets	The number of packets received on all network interfaces.
host.os.family	OS family (such as redhat, debian, freebsd, windows).
host.os.full	Operating system name, including the version or code name.
host.os.full.text	Operating system name, including the version or code name.
host.os.kernel	Operating system kernel version as a raw string.
host.os.name	Operating system name, without the version.
host.os.name.text	Operating system name, without the version.
host.os.platform	Operating system platform (such centos, ubuntu, windows).

host.os.type	Which commercial OS family (one of: linux, macos, unix, windows, ios or android).
host.os.version	Operating system version as a raw string.
host.pid_ns_ino	Pid namespace inode
host.risk.calculated_level	A risk classification level calculated by an internal system as part of entity analytics and entity risk scoring.
host.risk.calculated_score	A risk classification score calculated by an internal system as part of entity analytics and entity risk scoring.
host.risk.calculated_score_norm	A normalized risk score calculated by an internal system.
host.risk.static_level	A risk classification level obtained from outside the system, such as from some external Threat Intelligence Platform.
host.risk.static_score	A risk classification score obtained from outside the system, such as from some external Threat Intelligence Platform.
host.risk.static_score_norm	A normalized risk score calculated by an external system.
host.target.architecture	Operating system architecture.
host.target.boot.id	Linux boot uuid taken from /proc/sys/kernel/random/boot_id
host.target.cpu.usage	Percent CPU used, between 0 and 1.
host.target.disk.read.bytes	The number of bytes read by all disks.
host.target.disk.write.bytes	The number of bytes written on all disks.
host.target.domain	Name of the directory the group is a member of.
host.target.entity.attributes.known_redirects	Known redirect URIs or URLs associated with this entity.
host.target.entity.attributes.managed	Indicates whether the entity is managed by an external system.
host.target.entity.attributes.mfa_enabled	Indicates whether multi-factor authentication is enabled for this entity.
host.target.entity.attributes.oauth_consent_restriction	Restriction applied to OAuth consent for this entity.
host.target.entity.attributes.permissions	Action-level permissions associated with this entity.
host.target.entity.attributes.storage_class	Storage tier or class assigned to an object storage resource.
host.target.entity.behavior	A set of ephemeral characteristics of the entity, derived from observed behaviors during a specific time period.
host.target.entity.display_name	An optional field used when a pretty name is desired for entity-centric operations.
host.target.entity.display_name.text	An optional field used when a pretty name is desired for entity-centric operations.
host.target.entity.id	Unique identifier for the entity.
host.target.entity.last_seen_timestamp	Indicates the date/time when this entity was last "seen."
host.target.entity.lifecycle.last_activity	Timestamp of the most recent action performed by or attributed to this entity.
host.target.entity.metrics	Field set for any fields containing numeric entity metrics.
host.target.entity.name	The name of the entity.
host.target.entity.name.text	The name of the entity.
host.target.entity.raw	Original, unmodified fields from the source system.
host.target.entity.reference	A URI, URL, or other direct reference to access or locate the entity.
host.target.entity.relationships.administers.entity.id	Identifiers of referenced entities.
host.target.entity.relationships.administers.host.id	Referenced host ids.
host.target.entity.relationships.administers.host.name	Referenced host names.
host.target.entity.relationships.administers.service.id	Referenced service ids.
host.target.entity.relationships.administers.service.name	Referenced service names.
host.target.entity.relationships.administers.user.domain	Referenced user directory or AD/LDAP domain names.

host.target.entity.relationships.administers.user.email	Referenced user email addresses.
host.target.entity.relationships.administers.user.id	Referenced user ids.
host.target.entity.relationships.administers.user.name	Referenced user short names or logins.
host.target.entity.relationships.depends_on.entity.id	Identifiers of referenced entities.
host.target.entity.relationships.depends_on.host.id	Referenced host ids.
host.target.entity.relationships.depends_on.host.name	Referenced host names.
host.target.entity.relationships.depends_on.service.id	Referenced service ids.
host.target.entity.relationships.depends_on.service.name	Referenced service names.
host.target.entity.relationships.depends_on.user.domain	Referenced user directory or AD/LDAP domain names.
host.target.entity.relationships.depends_on.user.email	Referenced user email addresses.
host.target.entity.relationships.depends_on.user.id	Referenced user ids.
host.target.entity.relationships.depends_on.user.name	Referenced user short names or logins.
host.target.entity.relationships.owns.entity.id	Identifiers of referenced entities.
host.target.entity.relationships.owns.host.id	Referenced host ids.
host.target.entity.relationships.owns.host.name	Referenced host names.
host.target.entity.relationships.owns.service.id	Referenced service ids.
host.target.entity.relationships.owns.service.name	Referenced service names.
host.target.entity.relationships.owns.user.domain	Referenced user directory or AD/LDAP domain names.
host.target.entity.relationships.owns.user.email	Referenced user email addresses.
host.target.entity.relationships.owns.user.id	Referenced user ids.
host.target.entity.relationships.owns.user.name	Referenced user short names or logins.
host.target.entity.relationships.supervises.entity.id	Identifiers of referenced entities.
host.target.entity.relationships.supervises.host.id	Referenced host ids.
host.target.entity.relationships.supervises.host.name	Referenced host names.
host.target.entity.relationships.supervises.service.id	Referenced service ids.
host.target.entity.relationships.supervises.service.name	Referenced service names.
host.target.entity.relationships.supervises.user.domain	Referenced user directory or AD/LDAP domain names.
host.target.entity.relationships.supervises.user.email	Referenced user email addresses.
host.target.entity.relationships.supervises.user.id	Referenced user ids.
host.target.entity.relationships.supervises.user.name	Referenced user short names or logins.
host.target.entity.source	Source module or integration that provided the entity data.
host.target.entity.sub_type	The specific type designation for the entity as defined by its provider or system.
host.target.entity.type	Standardized high-level classification of the entity.
host.target.geo.city_name	City name.
host.target.geo.continent_code	Continent code.
host.target.geo.continent_name	Name of the continent.
host.target.geo.country_iso_code	Country ISO code.
host.target.geo.country_name	Country name.

host.target.geo.location	Longitude and latitude.
host.target.geo.name	User-defined description of a location.
host.target.geo.postal_code	Postal code.
host.target.geo.region_iso_code	Region ISO code.
host.target.geo.region_name	Region name.
host.target.geo.timezone	Time zone.
host.target.hostname	Hostname of the host.
host.target.id	Unique host id.
host.target.ip	Host ip addresses.
host.target.mac	Host MAC addresses.
host.target.name	Name of the host.
host.target.network.egress.bytes	The number of bytes sent on all network interfaces.
host.target.network.egress.packets	The number of packets sent on all network interfaces.
host.target.network.ingress.bytes	The number of bytes received on all network interfaces.
host.target.network.ingress.packets	The number of packets received on all network interfaces.
host.target.os.family	OS family (such as redhat, debian, freebsd, windows).
host.target.os.full	Operating system name, including the version or code name.
host.target.os.full.text	Operating system name, including the version or code name.
host.target.os.kernel	Operating system kernel version as a raw string.
host.target.os.name	Operating system name, without the version.
host.target.os.name.text	Operating system name, without the version.
host.target.os.platform	Operating system platform (such centos, ubuntu, windows).
host.target.os.type	Which commercial OS family (one of: linux, macos, unix, windows, ios or android).
host.target.os.version	Operating system version as a raw string.
host.target.pid_ns_ino	Pid namespace inode
host.target.risk.calculated_level	A risk classification level calculated by an internal system as part of entity analytics and entity risk scoring.
host.target.risk.calculated_score	A risk classification score calculated by an internal system as part of entity analytics and entity risk scoring.
host.target.risk.calculated_score_norm	A normalized risk score calculated by an internal system.
host.target.risk.static_level	A risk classification level obtained from outside the system, such as from some external Threat Intelligence Platform.
host.target.risk.static_score	A risk classification score obtained from outside the system, such as from some external Threat Intelligence Platform.
host.target.risk.static_score_norm	A normalized risk score calculated by an external system.
host.target.type	Type of host.
host.target.uptime	Seconds the host has been up.
host.type	Type of host.
host.uptime	Seconds the host has been up.
http.request.body.bytes	Size in bytes of the request body.
http.request.body.content	The full HTTP request body.
http.request.body.content.text	The full HTTP request body.

http.request.bytes	Total size in bytes of the request (body and headers).
http.request.id	HTTP request ID.
http.request.method	HTTP request method.
http.request.mime_type	Mime type of the body of the request.
http.request.referrer	Referrer for this HTTP request.
http.response.body.bytes	Size in bytes of the response body.
http.response.body.content	The full HTTP response body.
http.response.body.content.text	The full HTTP response body.
http.response.bytes	Total size in bytes of the response (body and headers).
http.response.mime_type	Mime type of the body of the response.
http.response.status_code	HTTP response status code.
http.version	HTTP version.
log.file.path	Full path to the log file this event came from.
log.level	Log level of the log event.
log.logger	Name of the logger.
log.origin.file.line	The line number of the file which originated the log event.
log.origin.file.name	The code file which originated the log event.
log.origin.function	The function which originated the log event.
log.syslog	Syslog metadata
log.syslog.appname	The device or application that originated the Syslog message.
log.syslog.facility.code	Syslog numeric facility of the event.
log.syslog.facility.name	Syslog text-based facility of the event.
log.syslog.hostname	The host that originated the Syslog message.
log.syslog.msgid	An identifier for the type of Syslog message.
log.syslog.priority	Syslog priority of the event.
log.syslog.procid	The process name or ID that originated the Syslog message.
log.syslog.severity.code	Syslog numeric severity of the event.
log.syslog.severity.name	Syslog text-based severity of the event.
log.syslog.structured_data	Structured data expressed in RFC 5424 messages.
log.syslog.version	Syslog protocol version.
network.application	Application level protocol name.
network.bytes	Total bytes transferred in both directions.
network.community_id	A hash of source and destination IPs and ports.
network.direction	Direction of the network traffic.
network.forwarded_ip	Host IP address when the source IP address is the proxy.
network.iana_number	IANA Protocol Number.
network.inner	Inner VLAN tag information
network.inner.vlan.id	VLAN ID as reported by the observer.

network.inner.vlan.name	Optional VLAN name as reported by the observer.
network.name	Name given by operators to sections of their network.
network.packets	Total packets transferred in both directions.
network.protocol	Application protocol name.
network.transport	Protocol Name corresponding to the field `iana_number`.
network.type	In the OSI Model this would be the Network Layer. ipv4, ipv6, ipsec, pim, etc
network.vlan.id	VLAN ID as reported by the observer.
network.vlan.name	Optional VLAN name as reported by the observer.
observer.egress	Object field for egress information
observer.egress.interface.alias	Interface alias
observer.egress.interface.id	Interface ID
observer.egress.interface.name	Interface name
observer.egress.vlan.id	VLAN ID as reported by the observer.
observer.egress.vlan.name	Optional VLAN name as reported by the observer.
observer.egress.zone	Observer Egress zone
observer.geo.city_name	City name.
observer.geo.continent_code	Continent code.
observer.geo.continent_name	Name of the continent.
observer.geo.country_iso_code	Country ISO code.
observer.geo.country_name	Country name.
observer.geo.location	Longitude and latitude.
observer.geo.name	User-defined description of a location.
observer.geo.postal_code	Postal code.
observer.geo.region_iso_code	Region ISO code.
observer.geo.region_name	Region name.
observer.geo.timezone	Time zone.
observer.hostname	Hostname of the observer.
observer.ingress	Object field for ingress information
observer.ingress.interface.alias	Interface alias
observer.ingress.interface.id	Interface ID
observer.ingress.interface.name	Interface name
observer.ingress.vlan.id	VLAN ID as reported by the observer.
observer.ingress.vlan.name	Optional VLAN name as reported by the observer.
observer.ingress.zone	Observer ingress zone
observer.ip	IP addresses of the observer.
observer.mac	MAC addresses of the observer.
observer.name	Custom name of the observer.
observer.os.family	OS family (such as redhat, debian, freebsd, windows).

observer.os.full	Operating system name, including the version or code name.
observer.os.full.text	Operating system name, including the version or code name.
observer.os.kernel	Operating system kernel version as a raw string.
observer.os.name	Operating system name, without the version.
observer.os.name.text	Operating system name, without the version.
observer.os.platform	Operating system platform (such centos, ubuntu, windows).
observer.os.type	Which commercial OS family (one of: linux, macos, unix, windows, ios or android).
observer.os.version	Operating system version as a raw string.
observer.product	The product name of the observer.
observer.serial_number	Observer serial number.
observer.type	The type of the observer the data is coming from.
observer.vendor	Vendor name of the observer.
observer.version	Observer version.
orchestrator.api_version	API version being used to carry out the action
orchestrator.cluster.id	Unique ID of the cluster.
orchestrator.cluster.name	Name of the cluster.
orchestrator.cluster.url	URL of the API used to manage the cluster.
orchestrator.cluster.version	The version of the cluster.
orchestrator.entity.attributes.known_redirects	Known redirect URIs or URLs associated with this entity.
orchestrator.entity.attributes.managed	Indicates whether the entity is managed by an external system.
orchestrator.entity.attributes.mfa_enabled	Indicates whether multi-factor authentication is enabled for this entity.
orchestrator.entity.attributes.oauth_consent_restriction	Restriction applied to OAuth consent for this entity.
orchestrator.entity.attributes.permissions	Action-level permissions associated with this entity.
orchestrator.entity.attributes.storage_class	Storage tier or class assigned to an object storage resource.
orchestrator.entity.behavior	A set of ephemeral characteristics of the entity, derived from observed behaviors during a specific time period.
orchestrator.entity.display_name	An optional field used when a pretty name is desired for entity-centric operations.
orchestrator.entity.display_name.text	An optional field used when a pretty name is desired for entity-centric operations.
orchestrator.entity.id	Unique identifier for the entity.
orchestrator.entity.last_seen_timestamp	Indicates the date/time when this entity was last "seen."
orchestrator.entity.lifecycle.last_activity	Timestamp of the most recent action performed by or attributed to this entity.
orchestrator.entity.metrics	Field set for any fields containing numeric entity metrics.
orchestrator.entity.name	The name of the entity.
orchestrator.entity.name.text	The name of the entity.
orchestrator.entity.raw	Original, unmodified fields from the source system.
orchestrator.entity.reference	A URI, URL, or other direct reference to access or locate the entity.
orchestrator.entity.relationships.administers.entity.id	Identifiers of referenced entities.
orchestrator.entity.relationships.administers.host.id	Referenced host ids.
orchestrator.entity.relationships.administers.host.name	Referenced host names.

orchestrator.entity.relationships.administers.service.id	Referenced service ids.
orchestrator.entity.relationships.administers.service.name	Referenced service names.
orchestrator.entity.relationships.administers.user.domain	Referenced user directory or AD/LDAP domain names.
orchestrator.entity.relationships.administers.user.email	Referenced user email addresses.
orchestrator.entity.relationships.administers.user.id	Referenced user ids.
orchestrator.entity.relationships.administers.user.name	Referenced user short names or logins.
orchestrator.entity.relationships.depends_on.entity.id	Identifiers of referenced entities.
orchestrator.entity.relationships.depends_on.host.id	Referenced host ids.
orchestrator.entity.relationships.depends_on.host.name	Referenced host names.
orchestrator.entity.relationships.depends_on.service.id	Referenced service ids.
orchestrator.entity.relationships.depends_on.service.name	Referenced service names.
orchestrator.entity.relationships.depends_on.user.domain	Referenced user directory or AD/LDAP domain names.
orchestrator.entity.relationships.depends_on.user.email	Referenced user email addresses.
orchestrator.entity.relationships.depends_on.user.id	Referenced user ids.
orchestrator.entity.relationships.depends_on.user.name	Referenced user short names or logins.
orchestrator.entity.relationships.owns.entity.id	Identifiers of referenced entities.
orchestrator.entity.relationships.owns.host.id	Referenced host ids.
orchestrator.entity.relationships.owns.host.name	Referenced host names.
orchestrator.entity.relationships.owns.service.id	Referenced service ids.
orchestrator.entity.relationships.owns.service.name	Referenced service names.
orchestrator.entity.relationships.owns.user.domain	Referenced user directory or AD/LDAP domain names.
orchestrator.entity.relationships.owns.user.email	Referenced user email addresses.
orchestrator.entity.relationships.owns.user.id	Referenced user ids.
orchestrator.entity.relationships.owns.user.name	Referenced user short names or logins.
orchestrator.entity.relationships.supervises.entity.id	Identifiers of referenced entities.
orchestrator.entity.relationships.supervises.host.id	Referenced host ids.
orchestrator.entity.relationships.supervises.host.name	Referenced host names.
orchestrator.entity.relationships.supervises.service.id	Referenced service ids.
orchestrator.entity.relationships.supervises.service.name	Referenced service names.
orchestrator.entity.relationships.supervises.user.domain	Referenced user directory or AD/LDAP domain names.
orchestrator.entity.relationships.supervises.user.email	Referenced user email addresses.
orchestrator.entity.relationships.supervises.user.id	Referenced user ids.
orchestrator.entity.relationships.supervises.user.name	Referenced user short names or logins.
orchestrator.entity.source	Source module or integration that provided the entity data.
orchestrator.entity.sub_type	The specific type designation for the entity as defined by its provider or system.
orchestrator.entity.type	Standardized high-level classification of the entity.
orchestrator.namespace	Namespace in which the action is taking place.
orchestrator.organization	Organization affected by the event (for multi-tenant orchestrator setups).

orchestrator.resource.annotation	The list of annotations added to the resource.
orchestrator.resource.id	Unique ID of the resource being acted upon.
orchestrator.resource.ip	IP address assigned to the resource associated with the event being observed.
orchestrator.resource.label	The list of labels added to the resource.
orchestrator.resource.name	Name of the resource being acted upon.
orchestrator.resource.parent.type	Type or kind of the parent resource associated with the event being observed.
orchestrator.resource.type	Type of resource being acted upon.
orchestrator.type	Orchestrator cluster type (e.g. kubernetes, nomad or cloudfoundry).
organization.id	Unique identifier for the organization.
organization.name	Organization name.
organization.name.text	Organization name.
package.architecture	Package architecture.
package.build_version	Build version information
package.checksum	Checksum of the installed package for verification.
package.description	Description of the package.
package.install_scope	Indicating how the package was installed, e.g. user-local, global.
package.installed	Time when package was installed.
package.license	Package license
package.name	Package name
package.path	Path where the package is installed.
package.reference	Package home page or reference URL
package.size	Package size in bytes.
package.type	Package type
package.version	Package version
process.args	Array of process arguments.
process.args_count	Length of the process.args array.
process.code_signature.digest_algorithm	Hashing algorithm used to sign the process.
process.code_signature.exists	Boolean to capture if a signature is present.
process.code_signature.flags	Code signing flags of the process
process.code_signature.signing_id	The identifier used to sign the process.
process.code_signature.status	Additional information about the certificate status.
process.code_signature.subject_name	Subject name of the code signer
process.code_signature.team_id	The team identifier used to sign the process.
process.code_signature.thumbprint_sha256	SHA256 hash of the certificate.
process.code_signature.timestamp	When the signature was generated and signed.
process.code_signature.trusted	Stores the trust status of the certificate chain.
process.code_signature.valid	Boolean to capture if the digital signature is verified against the binary content.
process.command_line	Full command line that started the process.

process.command_line.text	Full command line that started the process.
process.elf.architecture	Machine architecture of the ELF file.
process.elf.byte_order	Byte sequence of ELF file.
process.elf.cpu_type	CPU type of the ELF file.
process.elf.creation_date	Build or compile date.
process.elf.exports	List of exported element names and types.
process.elf.go_import_hash	A hash of the Go language imports in an ELF file.
process.elf.go_imports	List of imported Go language element names and types.
process.elf.go_imports_names_entropy	Shannon entropy calculation from the list of Go imports.
process.elf.go_imports_names_var_entropy	Variance for Shannon entropy calculation from the list of Go imports.
process.elf.go_stripped	Whether the file is a stripped or obfuscated Go executable.
process.elf.header.abi_version	Version of the ELF Application Binary Interface (ABI).
process.elf.header.class	Header class of the ELF file.
process.elf.header.data	Data table of the ELF header.
process.elf.header.entrypoint	Header entrypoint of the ELF file.
process.elf.header.object_version	"0x1" for original ELF files.
process.elf.header.os_abi	Application Binary Interface (ABI) of the Linux OS.
process.elf.header.type	Header type of the ELF file.
process.elf.header.version	Version of the ELF header.
process.elf.import_hash	A hash of the imports in an ELF file.
process.elf.imports	List of imported element names and types.
process.elf.imports_names_entropy	Shannon entropy calculation from the list of imported element names and types.
process.elf.imports_names_var_entropy	Variance for Shannon entropy calculation from the list of imported element names and types.
process.elf.sections	Section information of the ELF file.
process.elf.sections.chi2	Chi-square probability distribution of the section.
process.elf.sections.entropy	Shannon entropy calculation from the section.
process.elf.sections.flags	ELF Section List flags.
process.elf.sections.name	ELF Section List name.
process.elf.sections.physical_offset	ELF Section List offset.
process.elf.sections.physical_size	ELF Section List physical size.
process.elf.sections.type	ELF Section List type.
process.elf.sections.var_entropy	Variance for Shannon entropy calculation from the section.
process.elf.sections.virtual_address	ELF Section List virtual address.
process.elf.sections.virtual_size	ELF Section List virtual size.
process.elf.segments	ELF object segment list.
process.elf.segments.sections	ELF object segment sections.
process.elf.segments.type	ELF object segment type.
process.elf.shared_libraries	List of shared libraries used by this ELF object.

process.elf.telfhash	telfhash hash for ELF file.
process.end	The time the process ended.
process.entity_id	Unique identifier for the process.
process.entry_leader.args	Array of process arguments.
process.entry_leader.args_count	Length of the process.args array.
process.entry_leader.attested_groups.name	Name of the group.
process.entry_leader.attested_user.id	Unique identifier of the user.
process.entry_leader.attested_user.name	Short name or login of the user.
process.entry_leader.attested_user.name.text	Short name or login of the user.
process.entry_leader.command_line	Full command line that started the process.
process.entry_leader.command_line.text	Full command line that started the process.
process.entry_leader.entity_id	Unique identifier for the process.
process.entry_leader.entry_meta.source.ip	IP address of the source.
process.entry_leader.entry_meta.type	The entry type for the entry session leader.
process.entry_leader.executable	Absolute path to the process executable.
process.entry_leader.executable.text	Absolute path to the process executable.
process.entry_leader.group.id	Unique identifier for the group on the system/platform.
process.entry_leader.group.name	Name of the group.
process.entry_leader.interactive	Whether the process is connected to an interactive shell.
process.entry_leader.name	Process name.
process.entry_leader.name.text	Process name.
process.entry_leader.parent.entity_id	Unique identifier for the process.
process.entry_leader.parent.pid	Process id.
process.entry_leader.parent.session_leader.entity_id	Unique identifier for the process.
process.entry_leader.parent.session_leader.pid	Process id.
process.entry_leader.parent.session_leader.start	The time the process started.
process.entry_leader.parent.session_leader.vpid	Virtual process id.
process.entry_leader.parent.start	The time the process started.
process.entry_leader.parent.vpid	Virtual process id.
process.entry_leader.pid	Process id.
process.entry_leader.real_group.id	Unique identifier for the group on the system/platform.
process.entry_leader.real_group.name	Name of the group.
process.entry_leader.real_user.id	Unique identifier of the user.
process.entry_leader.real_user.name	Short name or login of the user.
process.entry_leader.real_user.name.text	Short name or login of the user.
process.entry_leader.same_as_process	This boolean is used to identify if a leader process is the same as the top level process.
process.entry_leader.saved_group.id	Unique identifier for the group on the system/platform.
process.entry_leader.saved_group.name	Name of the group.

process.entry_leader.saved_user.id	Unique identifier of the user.
process.entry_leader.saved_user.name	Short name or login of the user.
process.entry_leader.saved_user.name.text	Short name or login of the user.
process.entry_leader.start	The time the process started.
process.entry_leader.supplemental_groups.id	Unique identifier for the group on the system/platform.
process.entry_leader.supplemental_groups.name	Name of the group.
process.entry_leader.tty	Information about the controlling TTY device.
process.entry_leader.tty.char_device.major	The TTY character device's major number.
process.entry_leader.tty.char_device.minor	The TTY character device's minor number.
process.entry_leader.user.id	Unique identifier of the user.
process.entry_leader.user.name	Short name or login of the user.
process.entry_leader.user.name.text	Short name or login of the user.
process.entry_leader.vpid	Virtual process id.
process.entry_leader.working_directory	The working directory of the process.
process.entry_leader.working_directory.text	The working directory of the process.
process.env_vars	Array of environment variable bindings.
process.executable	Absolute path to the process executable.
process.executable.text	Absolute path to the process executable.
process.exit_code	The exit code of the process.
process.group.id	Unique identifier for the group on the system/platform.
process.group.name	Name of the group.
process.group_leader.args	Array of process arguments.
process.group_leader.args_count	Length of the process.args array.
process.group_leader.command_line	Full command line that started the process.
process.group_leader.command_line.text	Full command line that started the process.
process.group_leader.entity_id	Unique identifier for the process.
process.group_leader.executable	Absolute path to the process executable.
process.group_leader.executable.text	Absolute path to the process executable.
process.group_leader.group.id	Unique identifier for the group on the system/platform.
process.group_leader.group.name	Name of the group.
process.group_leader.interactive	Whether the process is connected to an interactive shell.
process.group_leader.name	Process name.
process.group_leader.name.text	Process name.
process.group_leader.pid	Process id.
process.group_leader.real_group.id	Unique identifier for the group on the system/platform.
process.group_leader.real_group.name	Name of the group.
process.group_leader.real_user.id	Unique identifier of the user.
process.group_leader.real_user.name	Short name or login of the user.

process.group_leader.real_user.name.text	Short name or login of the user.
process.group_leader.same_as_process	This boolean is used to identify if a leader process is the same as the top level process.
process.group_leader.saved_group.id	Unique identifier for the group on the system/platform.
process.group_leader.saved_group.name	Name of the group.
process.group_leader.saved_user.id	Unique identifier of the user.
process.group_leader.saved_user.name	Short name or login of the user.
process.group_leader.saved_user.name.text	Short name or login of the user.
process.group_leader.start	The time the process started.
process.group_leader.supplemental_groups.id	Unique identifier for the group on the system/platform.
process.group_leader.supplemental_groups.name	Name of the group.
process.group_leader.tty	Information about the controlling TTY device.
process.group_leader.tty.char_device.major	The TTY character device's major number.
process.group_leader.tty.char_device.minor	The TTY character device's minor number.
process.group_leader.user.id	Unique identifier of the user.
process.group_leader.user.name	Short name or login of the user.
process.group_leader.user.name.text	Short name or login of the user.
process.group_leader.vpid	Virtual process id.
process.group_leader.working_directory	The working directory of the process.
process.group_leader.working_directory.text	The working directory of the process.
process.hash.cdhash	The Code Directory (CD) hash of an executable.
process.hash.md5	MD5 hash.
process.hash.sha1	SHA1 hash.
process.hash.sha256	SHA256 hash.
process.hash.sha384	SHA384 hash.
process.hash.sha512	SHA512 hash.
process.hash.ssdeep	SSDEEP hash.
process.hash.tlsh	TLSH hash.
process.interactive	Whether the process is connected to an interactive shell.
process.io	A chunk of input or output (IO) from a single process.
process.io.bytes_skipped	An array of byte offsets and lengths denoting where IO data has been skipped.
process.io.bytes_skipped.length	The length of bytes skipped.
process.io.bytes_skipped.offset	The byte offset into this event's io.text (or io.bytes in the future) where length bytes were skipped.
process.io.max_bytes_per_process_exceeded	If true, the process producing the output has exceeded the max_kilobytes_per_process configuration setting.
process.io.text	A chunk of output or input sanitized to UTF-8.
process.io.total_bytes_captured	The total number of bytes captured in this event.
process.io.total_bytes_skipped	The total number of bytes that were not captured due to implementation restrictions such as buffer size limits.
process.io.type	The type of object on which the IO action (read or write) was taken.
process.macho.go_import_hash	A hash of the Go language imports in a Mach-O file.

process.macho.go_imports	List of imported Go language element names and types.
process.macho.go_imports_names_entropy	Shannon entropy calculation from the list of Go imports.
process.macho.go_imports_names_var_entropy	Variance for Shannon entropy calculation from the list of Go imports.
process.macho.go_stripped	Whether the file is a stripped or obfuscated Go executable.
process.macho.import_hash	A hash of the imports in a Mach-O file.
process.macho.imports	List of imported element names and types.
process.macho.imports_names_entropy	Shannon entropy calculation from the list of imported element names and types.
process.macho.imports_names_var_entropy	Variance for Shannon entropy calculation from the list of imported element names and types.
process.macho.sections	Section information of the Mach-O file.
process.macho.sections.entropy	Shannon entropy calculation from the section.
process.macho.sections.name	Mach-O Section List name.
process.macho.sections.physical_size	Mach-O Section List physical size.
process.macho.sections.var_entropy	Variance for Shannon entropy calculation from the section.
process.macho.sections.virtual_size	Mach-O Section List virtual size. This is always the same as `physical_size`.
process.macho.symhash	A hash of the imports in a Mach-O file.
process.name	Process name.
process.name.text	Process name.
process.parent.args	Array of process arguments.
process.parent.args_count	Length of the process.args array.
process.parent.code_signature.digest_algorithm	Hashing algorithm used to sign the process.
process.parent.code_signature.exists	Boolean to capture if a signature is present.
process.parent.code_signature.flags	Code signing flags of the process
process.parent.code_signature.signing_id	The identifier used to sign the process.
process.parent.code_signature.status	Additional information about the certificate status.
process.parent.code_signature.subject_name	Subject name of the code signer
process.parent.code_signature.team_id	The team identifier used to sign the process.
process.parent.code_signature.thumbprint_sha256	SHA256 hash of the certificate.
process.parent.code_signature.timestamp	When the signature was generated and signed.
process.parent.code_signature.trusted	Stores the trust status of the certificate chain.
process.parent.code_signature.valid	Boolean to capture if the digital signature is verified against the binary content.
process.parent.command_line	Full command line that started the process.
process.parent.command_line.text	Full command line that started the process.
process.parent.elf.architecture	Machine architecture of the ELF file.
process.parent.elf.byte_order	Byte sequence of ELF file.
process.parent.elf.cpu_type	CPU type of the ELF file.
process.parent.elf.creation_date	Build or compile date.
process.parent.elf.exports	List of exported element names and types.
process.parent.elf.go_import_hash	A hash of the Go language imports in an ELF file.

process.parent.elf.go_imports	List of imported Go language element names and types.
process.parent.elf.go_imports_names_entropy	Shannon entropy calculation from the list of Go imports.
process.parent.elf.go_imports_names_var_entropy	Variance for Shannon entropy calculation from the list of Go imports.
process.parent.elf.go_stripped	Whether the file is a stripped or obfuscated Go executable.
process.parent.elf.header.abi_version	Version of the ELF Application Binary Interface (ABI).
process.parent.elf.header.class	Header class of the ELF file.
process.parent.elf.header.data	Data table of the ELF header.
process.parent.elf.header.entripoint	Header entripoint of the ELF file.
process.parent.elf.header.object_version	"0x1" for original ELF files.
process.parent.elf.header.os_abi	Application Binary Interface (ABI) of the Linux OS.
process.parent.elf.header.type	Header type of the ELF file.
process.parent.elf.header.version	Version of the ELF header.
process.parent.elf.import_hash	A hash of the imports in an ELF file.
process.parent.elf.imports	List of imported element names and types.
process.parent.elf.imports_names_entropy	Shannon entropy calculation from the list of imported element names and types.
process.parent.elf.imports_names_var_entropy	Variance for Shannon entropy calculation from the list of imported element names and types.
process.parent.elf.sections	Section information of the ELF file.
process.parent.elf.sections.chi2	Chi-square probability distribution of the section.
process.parent.elf.sections.entropy	Shannon entropy calculation from the section.
process.parent.elf.sections.flags	ELF Section List flags.
process.parent.elf.sections.name	ELF Section List name.
process.parent.elf.sections.physical_offset	ELF Section List offset.
process.parent.elf.sections.physical_size	ELF Section List physical size.
process.parent.elf.sections.type	ELF Section List type.
process.parent.elf.sections.var_entropy	Variance for Shannon entropy calculation from the section.
process.parent.elf.sections.virtual_address	ELF Section List virtual address.
process.parent.elf.sections.virtual_size	ELF Section List virtual size.
process.parent.elf.segments	ELF object segment list.
process.parent.elf.segments.sections	ELF object segment sections.
process.parent.elf.segments.type	ELF object segment type.
process.parent.elf.shared_libraries	List of shared libraries used by this ELF object.
process.parent.elf.telfhash	telfhash hash for ELF file.
process.parent.end	The time the process ended.
process.parent.entity_id	Unique identifier for the process.
process.parent.executable	Absolute path to the process executable.
process.parent.executable.text	Absolute path to the process executable.
process.parent.exit_code	The exit code of the process.
process.parent.group.id	Unique identifier for the group on the system/platform.

process.parent.group.name	Name of the group.
process.parent.group_leader.entity_id	Unique identifier for the process.
process.parent.group_leader.pid	Process id.
process.parent.group_leader.start	The time the process started.
process.parent.group_leader.vpid	Virtual process id.
process.parent.hash.cdhash	The Code Directory (CD) hash of an executable.
process.parent.hash.md5	MD5 hash.
process.parent.hash.sha1	SHA1 hash.
process.parent.hash.sha256	SHA256 hash.
process.parent.hash.sha384	SHA384 hash.
process.parent.hash.sha512	SHA512 hash.
process.parent.hash.ssdeep	SSDEEP hash.
process.parent.hash.tlsh	TLSH hash.
process.parent.interactive	Whether the process is connected to an interactive shell.
process.parent.macho.go_import_hash	A hash of the Go language imports in a Mach-O file.
process.parent.macho.go_imports	List of imported Go language element names and types.
process.parent.macho.go_imports_names_entropy	Shannon entropy calculation from the list of Go imports.
process.parent.macho.go_imports_names_var_entropy	Variance for Shannon entropy calculation from the list of Go imports.
process.parent.macho.go_stripped	Whether the file is a stripped or obfuscated Go executable.
process.parent.macho.import_hash	A hash of the imports in a Mach-O file.
process.parent.macho.imports	List of imported element names and types.
process.parent.macho.imports_names_entropy	Shannon entropy calculation from the list of imported element names and types.
process.parent.macho.imports_names_var_entropy	Variance for Shannon entropy calculation from the list of imported element names and types.
process.parent.macho.sections	Section information of the Mach-O file.
process.parent.macho.sections_entropy	Shannon entropy calculation from the section.
process.parent.macho.sections.name	Mach-O Section List name.
process.parent.macho.sections.physical_size	Mach-O Section List physical size.
process.parent.macho.sections.var_entropy	Variance for Shannon entropy calculation from the section.
process.parent.macho.sections.virtual_size	Mach-O Section List virtual size. This is always the same as `physical_size`.
process.parent.macho.symhash	A hash of the imports in a Mach-O file.
process.parent.name	Process name.
process.parent.name.text	Process name.
process.parent.pe.architecture	CPU architecture target for the file.
process.parent.pe.company	Internal company name of the file, provided at compile-time.
process.parent.pe.description	Internal description of the file, provided at compile-time.
process.parent.pe.file_version	Process name.
process.parent.pe.go_import_hash	A hash of the Go language imports in a PE file.
process.parent.pe.go_imports	List of imported Go language element names and types.

process.parent.pe.go_imports_names_entropy	Shannon entropy calculation from the list of Go imports.
process.parent.pe.go_imports_names_var_entropy	Variance for Shannon entropy calculation from the list of Go imports.
process.parent.pe.go_stripped	Whether the file is a stripped or obfuscated Go executable.
process.parent.pe.imphash	A hash of the imports in a PE file.
process.parent.pe.import_hash	A hash of the imports in a PE file.
process.parent.pe.imports	List of imported element names and types.
process.parent.pe.imports_names_entropy	Shannon entropy calculation from the list of imported element names and types.
process.parent.pe.imports_names_var_entropy	Variance for Shannon entropy calculation from the list of imported element names and types.
process.parent.pe.original_file_name	Internal name of the file, provided at compile-time.
process.parent.pe.pehash	A hash of the PE header and data from one or more PE sections.
process.parent.pe.product	Internal product name of the file, provided at compile-time.
process.parent.pe.sections	Section information of the PE file.
process.parent.pe.sections.entropy	Shannon entropy calculation from the section.
process.parent.pe.sections.name	PE Section List name.
process.parent.pe.sections.physical_size	PE Section List physical size.
process.parent.pe.sections.var_entropy	Variance for Shannon entropy calculation from the section.
process.parent.pe.sections.virtual_size	PE Section List virtual size. This is always the same as `physical_size`.
process.parent.pid	Process id.
process.parent.real_group.id	Unique identifier for the group on the system/platform.
process.parent.real_group.name	Name of the group.
process.parent.real_user.id	Unique identifier of the user.
process.parent.real_user.name	Short name or login of the user.
process.parent.real_user.name.text	Short name or login of the user.
process.parent.saved_group.id	Unique identifier for the group on the system/platform.
process.parent.saved_group.name	Name of the group.
process.parent.saved_user.id	Unique identifier of the user.
process.parent.saved_user.name	Short name or login of the user.
process.parent.saved_user.name.text	Short name or login of the user.
process.parent.start	The time the process started.
process.parent.supplemental_groups.id	Unique identifier for the group on the system/platform.
process.parent.supplemental_groups.name	Name of the group.
process.parent.thread.capabilities.effective	Array of capabilities used for permission checks.
process.parent.thread.capabilities.permitted	Array of capabilities a thread could assume.
process.parent.thread.id	Thread ID.
process.parent.thread.name	Thread name.
process.parent.title	Process title.
process.parent.title.text	Process title.
process.parent.tty	Information about the controlling TTY device.

process.parent.tty.char_device.major	The TTY character device's major number.
process.parent.tty.char_device.minor	The TTY character device's minor number.
process.parent.uptime	Seconds the process has been up.
process.parent.user.id	Unique identifier of the user.
process.parent.user.name	Short name or login of the user.
process.parent.user.name.text	Short name or login of the user.
process.parent.vpid	Virtual process id.
process.parent.working_directory	The working directory of the process.
process.parent.working_directory.text	The working directory of the process.
process.pe.architecture	CPU architecture target for the file.
process.pe.company	Internal company name of the file, provided at compile-time.
process.pe.description	Internal description of the file, provided at compile-time.
process.pe.file_version	Process name.
process.pe.go_import_hash	A hash of the Go language imports in a PE file.
process.pe.go_imports	List of imported Go language element names and types.
process.pe.go_imports_names_entropy	Shannon entropy calculation from the list of Go imports.
process.pe.go_imports_names_var_entropy	Variance for Shannon entropy calculation from the list of Go imports.
process.pe.go_stripped	Whether the file is a stripped or obfuscated Go executable.
process.pe.imphash	A hash of the imports in a PE file.
process.pe.import_hash	A hash of the imports in a PE file.
process.pe.imports	List of imported element names and types.
process.pe.imports_names_entropy	Shannon entropy calculation from the list of imported element names and types.
process.pe.imports_names_var_entropy	Variance for Shannon entropy calculation from the list of imported element names and types.
process.pe.original_file_name	Internal name of the file, provided at compile-time.
process.pe.pehash	A hash of the PE header and data from one or more PE sections.
process.pe.product	Internal product name of the file, provided at compile-time.
process.pe.sections	Section information of the PE file.
process.pe.sections.entropy	Shannon entropy calculation from the section.
process.pe.sections.name	PE Section List name.
process.pe.sections.physical_size	PE Section List physical size.
process.pe.sections.var_entropy	Variance for Shannon entropy calculation from the section.
process.pe.sections.virtual_size	PE Section List virtual size. This is always the same as `physical_size`.
process.pid	Process id.
process.previous.args	Array of process arguments.
process.previous.args_count	Length of the process.args array.
process.previous.executable	Absolute path to the process executable.
process.previous.executable.text	Absolute path to the process executable.
process.real_group.id	Unique identifier for the group on the system/platform.

process.real_group.name	Name of the group.
process.real_user.id	Unique identifier of the user.
process.real_user.name	Short name or login of the user.
process.real_user.name.text	Short name or login of the user.
process.saved_group.id	Unique identifier for the group on the system/platform.
process.saved_group.name	Name of the group.
process.saved_user.id	Unique identifier of the user.
process.saved_user.name	Short name or login of the user.
process.saved_user.name.text	Short name or login of the user.
process.session_leader.args	Array of process arguments.
process.session_leader.args_count	Length of the process.args array.
process.session_leader.command_line	Full command line that started the process.
process.session_leader.command_line.text	Full command line that started the process.
process.session_leader.entity_id	Unique identifier for the process.
process.session_leader.executable	Absolute path to the process executable.
process.session_leader.executable.text	Absolute path to the process executable.
process.session_leader.group.id	Unique identifier for the group on the system/platform.
process.session_leader.group.name	Name of the group.
process.session_leader.interactive	Whether the process is connected to an interactive shell.
process.session_leader.name	Process name.
process.session_leader.name.text	Process name.
process.session_leader.parent.entity_id	Unique identifier for the process.
process.session_leader.parent.pid	Process id.
process.session_leader.parent.session_leader.entity_id	Unique identifier for the process.
process.session_leader.parent.session_leader.pid	Process id.
process.session_leader.parent.session_leader.start	The time the process started.
process.session_leader.parent.session_leader.vpid	Virtual process id.
process.session_leader.parent.start	The time the process started.
process.session_leader.parent.vpid	Virtual process id.
process.session_leader.pid	Process id.
process.session_leader.real_group.id	Unique identifier for the group on the system/platform.
process.session_leader.real_group.name	Name of the group.
process.session_leader.real_user.id	Unique identifier of the user.
process.session_leader.real_user.name	Short name or login of the user.
process.session_leader.real_user.name.text	Short name or login of the user.
process.session_leader.same_as_process	This boolean is used to identify if a leader process is the same as the top level process.
process.session_leader.saved_group.id	Unique identifier for the group on the system/platform.
process.session_leader.saved_group.name	Name of the group.

process.session_leader.saved_user.id	Unique identifier of the user.
process.session_leader.saved_user.name	Short name or login of the user.
process.session_leader.saved_user.name.text	Short name or login of the user.
process.session_leader.start	The time the process started.
process.session_leader.supplemental_groups.id	Unique identifier for the group on the system/platform.
process.session_leader.supplemental_groups.name	Name of the group.
process.session_leader.tty	Information about the controlling TTY device.
process.session_leader.tty.char_device.major	The TTY character device's major number.
process.session_leader.tty.char_device.minor	The TTY character device's minor number.
process.session_leader.user.id	Unique identifier of the user.
process.session_leader.user.name	Short name or login of the user.
process.session_leader.user.name.text	Short name or login of the user.
process.session_leader.vpid	Virtual process id.
process.session_leader.working_directory	The working directory of the process.
process.session_leader.working_directory.text	The working directory of the process.
process.start	The time the process started.
process.supplemental_groups.id	Unique identifier for the group on the system/platform.
process.supplemental_groups.name	Name of the group.
process.thread.capabilities.effective	Array of capabilities used for permission checks.
process.thread.capabilities.permitted	Array of capabilities a thread could assume.
process.thread.id	Thread ID.
process.thread.name	Thread name.
process.title	Process title.
process.title.text	Process title.
process.tty	Information about the controlling TTY device.
process.tty.char_device.major	The TTY character device's major number.
process.tty.char_device.minor	The TTY character device's minor number.
process.tty.columns	The number of character columns per line. e.g terminal width
process.tty.rows	The number of character rows in the terminal. e.g terminal height
process.uptime	Seconds the process has been up.
process.user.id	Unique identifier of the user.
process.user.name	Short name or login of the user.
process.user.name.text	Short name or login of the user.
process.vpid	Virtual process id.
process.working_directory	The working directory of the process.
process.working_directory.text	The working directory of the process.
registry.data.bytes	Original bytes written with base64 encoding.
registry.data.strings	List of strings representing what was written to the registry.

registry.data.type	Standard registry type for encoding contents
registry.hive	Abbreviated name for the hive.
registry.key	Hive-relative path of keys.
registry.path	Full path, including hive, key and value
registry.value	Name of the value written.
related.hash	All the hashes seen on your event.
related.hosts	All the host identifiers seen on your event.
related.ip	All of the IPs seen on your event.
related.user	All the user names or other user identifiers seen on the event.
rule.author	Rule author
rule.category	Rule category
rule.description	Rule description
rule.id	Rule ID
rule.license	Rule license
rule.name	Rule name
rule.reference	Rule reference URL
rule.ruleset	Rule ruleset
rule.uuid	Rule UUID
rule.version	Rule version
server.address	Server network address.
server.as.number	Unique number allocated to the autonomous system.
server.as.organization.name	Organization name.
server.as.organization.name.text	Organization name.
server.bytes	Bytes sent from the server to the client.
server.domain	The domain name of the server.
server.geo.city_name	City name.
server.geo.continent_code	Continent code.
server.geo.continent_name	Name of the continent.
server.geo.country_iso_code	Country ISO code.
server.geo.country_name	Country name.
server.geo.location	Longitude and latitude.
server.geo.name	User-defined description of a location.
server.geo.postal_code	Postal code.
server.geo.region_iso_code	Region ISO code.
server.geo.region_name	Region name.
server.geo.timezone	Time zone.
server.ip	IP address of the server.
server.mac	MAC address of the server.

server.nat.ip	Server NAT ip
server.nat.port	Server NAT port
server.packets	Packets sent from the server to the client.
server.port	Port of the server.
server.registered_domain	The highest registered server domain, stripped of the subdomain.
server.subdomain	The subdomain of the domain.
server.top_level_domain	The effective top level domain (com, org, net, co.uk).
server.user.domain	Name of the directory the user is a member of.
server.user.email	User email address.
server.user.full_name	User's full name, if available.
server.user.full_name.text	User's full name, if available.
server.user.group.domain	Name of the directory the group is a member of.
server.user.group.id	Unique identifier for the group on the system/platform.
server.user.group.name	Name of the group.
server.user.hash	Unique user hash to correlate information for a user in anonymized form.
server.user.id	Unique identifier of the user.
server.user.name	Short name or login of the user.
server.user.name.text	Short name or login of the user.
server.user.roles	Array of user roles at the time of the event.
service.address	Address of this service.
service.entity.attributes.known_redirects	Known redirect URIs or URLs associated with this entity.
service.entity.attributes.managed	Indicates whether the entity is managed by an external system.
service.entity.attributes.mfa_enabled	Indicates whether multi-factor authentication is enabled for this entity.
service.entity.attributes.oauth_consent_restriction	Restriction applied to OAuth consent for this entity.
service.entity.attributes.permissions	Action-level permissions associated with this entity.
service.entity.attributes.storage_class	Storage tier or class assigned to an object storage resource.
service.entity.behavior	A set of ephemeral characteristics of the entity, derived from observed behaviors during a specific time period.
service.entity.display_name	An optional field used when a pretty name is desired for entity-centric operations.
service.entity.display_name.text	An optional field used when a pretty name is desired for entity-centric operations.
service.entity.id	Unique identifier for the entity.
service.entity.last_seen_timestamp	Indicates the date/time when this entity was last "seen."
service.entity.lifecycle.last_activity	Timestamp of the most recent action performed by or attributed to this entity.
service.entity.metrics	Field set for any fields containing numeric entity metrics.
service.entity.name	The name of the entity.
service.entity.name.text	The name of the entity.
service.entity.raw	Original, unmodified fields from the source system.
service.entity.reference	A URI, URL, or other direct reference to access or locate the entity.
service.entity.relationships.administers.entity.id	Identifiers of referenced entities.

service.entity.relationships.administers.host.id	Referenced host ids.
service.entity.relationships.administers.host.name	Referenced host names.
service.entity.relationships.administers.service.id	Referenced service ids.
service.entity.relationships.administers.service.name	Referenced service names.
service.entity.relationships.administers.user.domain	Referenced user directory or AD/LDAP domain names.
service.entity.relationships.administers.user.email	Referenced user email addresses.
service.entity.relationships.administers.user.id	Referenced user ids.
service.entity.relationships.administers.user.name	Referenced user short names or logins.
service.entity.relationships.depends_on.entity.id	Identifiers of referenced entities.
service.entity.relationships.depends_on.host.id	Referenced host ids.
service.entity.relationships.depends_on.host.name	Referenced host names.
service.entity.relationships.depends_on.service.id	Referenced service ids.
service.entity.relationships.depends_on.service.name	Referenced service names.
service.entity.relationships.depends_on.user.domain	Referenced user directory or AD/LDAP domain names.
service.entity.relationships.depends_on.user.email	Referenced user email addresses.
service.entity.relationships.depends_on.user.id	Referenced user ids.
service.entity.relationships.depends_on.user.name	Referenced user short names or logins.
service.entity.relationships.owns.entity.id	Identifiers of referenced entities.
service.entity.relationships.owns.host.id	Referenced host ids.
service.entity.relationships.owns.host.name	Referenced host names.
service.entity.relationships.owns.service.id	Referenced service ids.
service.entity.relationships.owns.service.name	Referenced service names.
service.entity.relationships.owns.user.domain	Referenced user directory or AD/LDAP domain names.
service.entity.relationships.owns.user.email	Referenced user email addresses.
service.entity.relationships.owns.user.id	Referenced user ids.
service.entity.relationships.owns.user.name	Referenced user short names or logins.
service.entity.relationships.supervises.entity.id	Identifiers of referenced entities.
service.entity.relationships.supervises.host.id	Referenced host ids.
service.entity.relationships.supervises.host.name	Referenced host names.
service.entity.relationships.supervises.service.id	Referenced service ids.
service.entity.relationships.supervises.service.name	Referenced service names.
service.entity.relationships.supervises.user.domain	Referenced user directory or AD/LDAP domain names.
service.entity.relationships.supervises.user.email	Referenced user email addresses.
service.entity.relationships.supervises.user.id	Referenced user ids.
service.entity.relationships.supervises.user.name	Referenced user short names or logins.
service.entity.source	Source module or integration that provided the entity data.
service.entity.sub_type	The specific type designation for the entity as defined by its provider or system.
service.entity.type	Standardized high-level classification of the entity.

service.environment	Environment of the service.
service.ephemeral_id	Ephemeral identifier of this service.
service.id	Unique identifier of the running service.
service.name	Name of the service.
service.node.name	Name of the service node.
service.node.role	Deprecated role (singular) of the service node.
service.node.roles	Roles of the service node.
service.origin.address	Address of this service.
service.origin.entity.attributes.known_redirects	Known redirect URIs or URLs associated with this entity.
service.origin.entity.attributes.managed	Indicates whether the entity is managed by an external system.
service.origin.entity.attributes.mfa_enabled	Indicates whether multi-factor authentication is enabled for this entity.
service.origin.entity.attributes.oauth_consent_restriction	Restriction applied to OAuth consent for this entity.
service.origin.entity.attributes.permissions	Action-level permissions associated with this entity.
service.origin.entity.attributes.storage_class	Storage tier or class assigned to an object storage resource.
service.origin.entity.behavior	A set of ephemeral characteristics of the entity, derived from observed behaviors during a specific time period.
service.origin.entity.display_name	An optional field used when a pretty name is desired for entity-centric operations.
service.origin.entity.display_name.text	An optional field used when a pretty name is desired for entity-centric operations.
service.origin.entity.id	Unique identifier for the entity.
service.origin.entity.last_seen_timestamp	Indicates the date/time when this entity was last "seen."
service.origin.entity.lifecycle.last_activity	Timestamp of the most recent action performed by or attributed to this entity.
service.origin.entity.metrics	Field set for any fields containing numeric entity metrics.
service.origin.entity.name	The name of the entity.
service.origin.entity.name.text	The name of the entity.
service.origin.entity.raw	Original, unmodified fields from the source system.
service.origin.entity.reference	A URI, URL, or other direct reference to access or locate the entity.
service.origin.entity.relationships.administers.entity.id	Identifiers of referenced entities.
service.origin.entity.relationships.administers.host.id	Referenced host ids.
service.origin.entity.relationships.administers.host.name	Referenced host names.
service.origin.entity.relationships.administers.service.id	Referenced service ids.
service.origin.entity.relationships.administers.service.name	Referenced service names.
service.origin.entity.relationships.administers.user.domain	Referenced user directory or AD/LDAP domain names.
service.origin.entity.relationships.administers.user.email	Referenced user email addresses.
service.origin.entity.relationships.administers.user.id	Referenced user ids.
service.origin.entity.relationships.administers.user.name	Referenced user short names or logins.
service.origin.entity.relationships.depends_on.entity.id	Identifiers of referenced entities.
service.origin.entity.relationships.depends_on.host.id	Referenced host ids.
service.origin.entity.relationships.depends_on.host.name	Referenced host names.
service.origin.entity.relationships.depends_on.service.id	Referenced service ids.

service.origin.entity.relationships.depends_on.service.name	Referenced service names.
service.origin.entity.relationships.depends_on.user.domain	Referenced user directory or AD/LDAP domain names.
service.origin.entity.relationships.depends_on.user.email	Referenced user email addresses.
service.origin.entity.relationships.depends_on.user.id	Referenced user ids.
service.origin.entity.relationships.depends_on.user.name	Referenced user short names or logins.
service.origin.entity.relationships.owns.entity.id	Identifiers of referenced entities.
service.origin.entity.relationships.owns.host.id	Referenced host ids.
service.origin.entity.relationships.owns.host.name	Referenced host names.
service.origin.entity.relationships.owns.service.id	Referenced service ids.
service.origin.entity.relationships.owns.service.name	Referenced service names.
service.origin.entity.relationships.owns.user.domain	Referenced user directory or AD/LDAP domain names.
service.origin.entity.relationships.owns.user.email	Referenced user email addresses.
service.origin.entity.relationships.owns.user.id	Referenced user ids.
service.origin.entity.relationships.owns.user.name	Referenced user short names or logins.
service.origin.entity.relationships.supervises.entity.id	Identifiers of referenced entities.
service.origin.entity.relationships.supervises.host.id	Referenced host ids.
service.origin.entity.relationships.supervises.host.name	Referenced host names.
service.origin.entity.relationships.supervises.service.id	Referenced service ids.
service.origin.entity.relationships.supervises.service.name	Referenced service names.
service.origin.entity.relationships.supervises.user.domain	Referenced user directory or AD/LDAP domain names.
service.origin.entity.relationships.supervises.user.email	Referenced user email addresses.
service.origin.entity.relationships.supervises.user.id	Referenced user ids.
service.origin.entity.relationships.supervises.user.name	Referenced user short names or logins.
service.origin.entity.source	Source module or integration that provided the entity data.
service.origin.entity.sub_type	The specific type designation for the entity as defined by its provider or system.
service.origin.entity.type	Standardized high-level classification of the entity.
service.origin.environment	Environment of the service.
service.origin.ephemeral_id	Ephemeral identifier of this service.
service.origin.id	Unique identifier of the running service.
service.origin.name	Name of the service.
service.origin.node.name	Name of the service node.
service.origin.node.role	Deprecated role (singular) of the service node.
service.origin.node.roles	Roles of the service node.
service.origin.state	Current state of the service.
service.origin.type	The type of the service.
service.origin.version	Version of the service.
service.state	Current state of the service.
service.target.address	Address of this service.

service.target.entity.attributes.known_redirects	Known redirect URIs or URLs associated with this entity.
service.target.entity.attributes.managed	Indicates whether the entity is managed by an external system.
service.target.entity.attributes.mfa_enabled	Indicates whether multi-factor authentication is enabled for this entity.
service.target.entity.attributes.oauth_consent_restriction	Restriction applied to OAuth consent for this entity.
service.target.entity.attributes.permissions	Action-level permissions associated with this entity.
service.target.entity.attributes.storage_class	Storage tier or class assigned to an object storage resource.
service.target.entity.behavior	A set of ephemeral characteristics of the entity, derived from observed behaviors during a specific time period.
service.target.entity.display_name	An optional field used when a pretty name is desired for entity-centric operations.
service.target.entity.display_name.text	An optional field used when a pretty name is desired for entity-centric operations.
service.target.entity.id	Unique identifier for the entity.
service.target.entity.last_seen_timestamp	Indicates the date/time when this entity was last "seen."
service.target.entity.lifecycle.last_activity	Timestamp of the most recent action performed by or attributed to this entity.
service.target.entity.metrics	Field set for any fields containing numeric entity metrics.
service.target.entity.name	The name of the entity.
service.target.entity.name.text	The name of the entity.
service.target.entity.raw	Original, unmodified fields from the source system.
service.target.entity.reference	A URI, URL, or other direct reference to access or locate the entity.
service.target.entity.relationships.administers.entity.id	Identifiers of referenced entities.
service.target.entity.relationships.administers.host.id	Referenced host ids.
service.target.entity.relationships.administers.host.name	Referenced host names.
service.target.entity.relationships.administers.service.id	Referenced service ids.
service.target.entity.relationships.administers.service.name	Referenced service names.
service.target.entity.relationships.administers.user.domain	Referenced user directory or AD/LDAP domain names.
service.target.entity.relationships.administers.user.email	Referenced user email addresses.
service.target.entity.relationships.administers.user.id	Referenced user ids.
service.target.entity.relationships.administers.user.name	Referenced user short names or logins.
service.target.entity.relationships.depends_on.entity.id	Identifiers of referenced entities.
service.target.entity.relationships.depends_on.host.id	Referenced host ids.
service.target.entity.relationships.depends_on.host.name	Referenced host names.
service.target.entity.relationships.depends_on.service.id	Referenced service ids.
service.target.entity.relationships.depends_on.service.name	Referenced service names.
service.target.entity.relationships.depends_on.user.domain	Referenced user directory or AD/LDAP domain names.
service.target.entity.relationships.depends_on.user.email	Referenced user email addresses.
service.target.entity.relationships.depends_on.user.id	Referenced user ids.
service.target.entity.relationships.depends_on.user.name	Referenced user short names or logins.
service.target.entity.relationships.owns.entity.id	Identifiers of referenced entities.
service.target.entity.relationships.owns.host.id	Referenced host ids.
service.target.entity.relationships.owns.host.name	Referenced host names.

service.target.entity.relationships.owns.service.id	Referenced service ids.
service.target.entity.relationships.owns.service.name	Referenced service names.
service.target.entity.relationships.owns.user.domain	Referenced user directory or AD/LDAP domain names.
service.target.entity.relationships.owns.user.email	Referenced user email addresses.
service.target.entity.relationships.owns.user.id	Referenced user ids.
service.target.entity.relationships.owns.user.name	Referenced user short names or logins.
service.target.entity.relationships.supervises.entity.id	Identifiers of referenced entities.
service.target.entity.relationships.supervises.host.id	Referenced host ids.
service.target.entity.relationships.supervises.host.name	Referenced host names.
service.target.entity.relationships.supervises.service.id	Referenced service ids.
service.target.entity.relationships.supervises.service.name	Referenced service names.
service.target.entity.relationships.supervises.user.domain	Referenced user directory or AD/LDAP domain names.
service.target.entity.relationships.supervises.user.email	Referenced user email addresses.
service.target.entity.relationships.supervises.user.id	Referenced user ids.
service.target.entity.relationships.supervises.user.name	Referenced user short names or logins.
service.target.entity.source	Source module or integration that provided the entity data.
service.target.entity.sub_type	The specific type designation for the entity as defined by its provider or system.
service.target.entity.type	Standardized high-level classification of the entity.
service.target.environment	Environment of the service.
service.target.ephemeral_id	Ephemeral identifier of this service.
service.target.id	Unique identifier of the running service.
service.target.name	Name of the service.
service.target.node.name	Name of the service node.
service.target.node.role	Deprecated role (singular) of the service node.
service.target.node.roles	Roles of the service node.
service.target.state	Current state of the service.
service.target.type	The type of the service.
service.target.version	Version of the service.
service.type	The type of the service.
service.version	Version of the service.
source.address	Source network address.
source.as.number	Unique number allocated to the autonomous system.
source.as.organization.name	Organization name.
source.as.organization.name.text	Organization name.
source.bytes	Bytes sent from the source to the destination.
source.domain	The domain name of the source.
source.geo.city_name	City name.
source.geo.continent_code	Continent code.

source.geo.continent_name	Name of the continent.
source.geo.country_iso_code	Country ISO code.
source.geo.country_name	Country name.
source.geo.location	Longitude and latitude.
source.geo.name	User-defined description of a location.
source.geo.postal_code	Postal code.
source.geo.region_iso_code	Region ISO code.
source.geo.region_name	Region name.
source.geo.timezone	Time zone.
source.ip	IP address of the source.
source.mac	MAC address of the source.
source.nat.ip	Source NAT ip
source.nat.port	Source NAT port
source.packets	Packets sent from the source to the destination.
source.port	Port of the source.
source.registered_domain	The highest registered source domain, stripped of the subdomain.
source.subdomain	The subdomain of the domain.
source.top_level_domain	The effective top level domain (com, org, net, co.uk).
source.user.domain	Name of the directory the user is a member of.
source.user.email	User email address.
source.user.full_name	User's full name, if available.
source.user.full_name.text	User's full name, if available.
source.user.group.domain	Name of the directory the group is a member of.
source.user.group.id	Unique identifier for the group on the system/platform.
source.user.group.name	Name of the group.
source.user.hash	Unique user hash to correlate information for a user in anonymized form.
source.user.id	Unique identifier of the user.
source.user.name	Short name or login of the user.
source.user.name.text	Short name or login of the user.
source.user.roles	Array of user roles at the time of the event.
span.id	Unique identifier of the span within the scope of its trace.
threat.enrichments	List of objects containing indicators enriching the event.
threat.enrichments.indicator	Object containing indicators enriching the event.
threat.enrichments.indicator.as.number	Unique number allocated to the autonomous system.
threat.enrichments.indicator.as.organization.name	Organization name.
threat.enrichments.indicator.as.organization.name.text	Organization name.
threat.enrichments.indicator.confidence	Indicator confidence rating
threat.enrichments.indicator.description	Indicator description

threat.enrichments.indicator.email.address	Indicator email address
threat.enrichments.indicator.file.accessed	Last time the file was accessed.
threat.enrichments.indicator.file.attributes	Array of file attributes.
threat.enrichments.indicator.file.code_signature.digest_algorithm	Hashing algorithm used to sign the process.
threat.enrichments.indicator.file.code_signature.exists	Boolean to capture if a signature is present.
threat.enrichments.indicator.file.code_signature.flags	Code signing flags of the process
threat.enrichments.indicator.file.code_signature.signing_id	The identifier used to sign the process.
threat.enrichments.indicator.file.code_signature.status	Additional information about the certificate status.
threat.enrichments.indicator.file.code_signature.subject_name	Subject name of the code signer
threat.enrichments.indicator.file.code_signature.team_id	The team identifier used to sign the process.
threat.enrichments.indicator.file.code_signature.thumbprint_sha256	SHA256 hash of the certificate.
threat.enrichments.indicator.file.code_signature.timestamp	When the signature was generated and signed.
threat.enrichments.indicator.file.code_signature.trusted	Stores the trust status of the certificate chain.
threat.enrichments.indicator.file.code_signature.valid	Boolean to capture if the digital signature is verified against the binary content.
threat.enrichments.indicator.file.created	File creation time.
threat.enrichments.indicator.file.ctime	Last time the file attributes or metadata changed.
threat.enrichments.indicator.file.device	Device that is the source of the file.
threat.enrichments.indicator.file.directory	Directory where the file is located.
threat.enrichments.indicator.file.drive_letter	Drive letter where the file is located.
threat.enrichments.indicator.file.elf.architecture	Machine architecture of the ELF file.
threat.enrichments.indicator.file.elf.byte_order	Byte sequence of ELF file.
threat.enrichments.indicator.file.elf.cpu_type	CPU type of the ELF file.
threat.enrichments.indicator.file.elf.creation_date	Build or compile date.
threat.enrichments.indicator.file.elf.exports	List of exported element names and types.
threat.enrichments.indicator.file.elf.go_import_hash	A hash of the Go language imports in an ELF file.
threat.enrichments.indicator.file.elf.go_imports	List of imported Go language element names and types.
threat.enrichments.indicator.file.elf.go_imports_names_entropy	Shannon entropy calculation from the list of Go imports.
threat.enrichments.indicator.file.elf.go_imports_names_var_entropy	Variance for Shannon entropy calculation from the list of Go imports.
threat.enrichments.indicator.file.elf.go_stripped	Whether the file is a stripped or obfuscated Go executable.
threat.enrichments.indicator.file.elf.header.abi_version	Version of the ELF Application Binary Interface (ABI).
threat.enrichments.indicator.file.elf.header.class	Header class of the ELF file.
threat.enrichments.indicator.file.elf.header.data	Data table of the ELF header.
threat.enrichments.indicator.file.elf.header.entrypoint	Header entrypoint of the ELF file.
threat.enrichments.indicator.file.elf.header.object_version	"0x1" for original ELF files.
threat.enrichments.indicator.file.elf.header.os_abi	Application Binary Interface (ABI) of the Linux OS.
threat.enrichments.indicator.file.elf.header.type	Header type of the ELF file.
threat.enrichments.indicator.file.elf.header.version	Version of the ELF header.
threat.enrichments.indicator.file.elf.import_hash	A hash of the imports in an ELF file.

threat.enrichments.indicator.file.elf.imports	List of imported element names and types.
threat.enrichments.indicator.file.elf.imports_names_entropy	Shannon entropy calculation from the list of imported element names and types.
threat.enrichments.indicator.file.elf.imports_names_var_entropy	Variance for Shannon entropy calculation from the list of imported element names and types.
threat.enrichments.indicator.file.elf.sections	Section information of the ELF file.
threat.enrichments.indicator.file.elf.sections.chi2	Chi-square probability distribution of the section.
threat.enrichments.indicator.file.elf.sections.entropy	Shannon entropy calculation from the section.
threat.enrichments.indicator.file.elf.sections.flags	ELF Section List flags.
threat.enrichments.indicator.file.elf.sections.name	ELF Section List name.
threat.enrichments.indicator.file.elf.sections.physical_offset	ELF Section List offset.
threat.enrichments.indicator.file.elf.sections.physical_size	ELF Section List physical size.
threat.enrichments.indicator.file.elf.sections.type	ELF Section List type.
threat.enrichments.indicator.file.elf.sections.var_entropy	Variance for Shannon entropy calculation from the section.
threat.enrichments.indicator.file.elf.sections.virtual_address	ELF Section List virtual address.
threat.enrichments.indicator.file.elf.sections.virtual_size	ELF Section List virtual size.
threat.enrichments.indicator.file.elf.segments	ELF object segment list.
threat.enrichments.indicator.file.elf.segments.sections	ELF object segment sections.
threat.enrichments.indicator.file.elf.segments.type	ELF object segment type.
threat.enrichments.indicator.file.elf.shared_libraries	List of shared libraries used by this ELF object.
threat.enrichments.indicator.file.elf.telfhash	telfhash hash for ELF file.
threat.enrichments.indicator.file.extension	File extension, excluding the leading dot.
threat.enrichments.indicator.file.fork_name	A fork is additional data associated with a filesystem object.
threat.enrichments.indicator.file.gid	Primary group ID (GID) of the file.
threat.enrichments.indicator.file.group	Primary group name of the file.
threat.enrichments.indicator.file.hash.cdhash	The Code Directory (CD) hash of an executable.
threat.enrichments.indicator.file.hash.md5	MD5 hash.
threat.enrichments.indicator.file.hash.sha1	SHA1 hash.
threat.enrichments.indicator.file.hash.sha256	SHA256 hash.
threat.enrichments.indicator.file.hash.sha384	SHA384 hash.
threat.enrichments.indicator.file.hash.sha512	SHA512 hash.
threat.enrichments.indicator.file.hash.ssdeep	SSDEEP hash.
threat.enrichments.indicator.file.hash.tlsh	TLSH hash.
threat.enrichments.indicator.file.inode	Inode representing the file in the filesystem.
threat.enrichments.indicator.file.mime_type	Media type of file, document, or arrangement of bytes.
threat.enrichments.indicator.file.mode	Mode of the file in octal representation.
threat.enrichments.indicator.file.mtime	Last time the file content was modified.
threat.enrichments.indicator.file.name	Name of the file including the extension, without the directory.
threat.enrichments.indicator.file.origin_referrer_url	The URL of the webpage that linked to the file.
threat.enrichments.indicator.file.origin_url	The URL where the file is hosted.

threat.enrichments.indicator.file.owner	File owner's username.
threat.enrichments.indicator.file.path	Full path to the file, including the file name.
threat.enrichments.indicator.file.path.text	Full path to the file, including the file name.
threat.enrichments.indicator.file.pe.architecture	CPU architecture target for the file.
threat.enrichments.indicator.file.pe.company	Internal company name of the file, provided at compile-time.
threat.enrichments.indicator.file.pe.description	Internal description of the file, provided at compile-time.
threat.enrichments.indicator.file.pe.file_version	Process name.
threat.enrichments.indicator.file.pe.go_import_hash	A hash of the Go language imports in a PE file.
threat.enrichments.indicator.file.pe.go_imports	List of imported Go language element names and types.
threat.enrichments.indicator.file.pe.go_imports_names_entropy	Shannon entropy calculation from the list of Go imports.
threat.enrichments.indicator.file.pe.go_imports_names_var_entropy	Variance for Shannon entropy calculation from the list of Go imports.
threat.enrichments.indicator.file.pe.go_stripped	Whether the file is a stripped or obfuscated Go executable.
threat.enrichments.indicator.file.pe.imphash	A hash of the imports in a PE file.
threat.enrichments.indicator.file.pe.import_hash	A hash of the imports in a PE file.
threat.enrichments.indicator.file.pe.imports	List of imported element names and types.
threat.enrichments.indicator.file.pe.imports_names_entropy	Shannon entropy calculation from the list of imported element names and types.
threat.enrichments.indicator.file.pe.imports_names_var_entropy	Variance for Shannon entropy calculation from the list of imported element names and types.
threat.enrichments.indicator.file.pe.original_file_name	Internal name of the file, provided at compile-time.
threat.enrichments.indicator.file.pe.pehash	A hash of the PE header and data from one or more PE sections.
threat.enrichments.indicator.file.pe.product	Internal product name of the file, provided at compile-time.
threat.enrichments.indicator.file.pe.sections	Section information of the PE file.
threat.enrichments.indicator.file.pe.sections.entropy	Shannon entropy calculation from the section.
threat.enrichments.indicator.file.pe.sections.name	PE Section List name.
threat.enrichments.indicator.file.pe.sections.physical_size	PE Section List physical size.
threat.enrichments.indicator.file.pe.sections.var_entropy	Variance for Shannon entropy calculation from the section.
threat.enrichments.indicator.file.pe.sections.virtual_size	PE Section List virtual size. This is always the same as `physical_size`.
threat.enrichments.indicator.file.size	File size in bytes.
threat.enrichments.indicator.file.target_path	Target path for symlinks.
threat.enrichments.indicator.file.target_path.text	Target path for symlinks.
threat.enrichments.indicator.file.type	File type (file, dir, or symlink).
threat.enrichments.indicator.file.uid	The user ID (UID) or security identifier (SID) of the file owner.
threat.enrichments.indicator.file.x509.alternative_names	List of subject alternative names (SAN).
threat.enrichments.indicator.file.x509.issuer.common_name	List of common name (CN) of issuing certificate authority.
threat.enrichments.indicator.file.x509.issuer.country	List of country \(\C\) codes
threat.enrichments.indicator.file.x509.issuer.distinguished_name	Distinguished name (DN) of issuing certificate authority.
threat.enrichments.indicator.file.x509.issuer.locality	List of locality names (L)
threat.enrichments.indicator.file.x509.issuer.organization	List of organizations (O) of issuing certificate authority.
threat.enrichments.indicator.file.x509.issuer.organizational_unit	List of organizational units (OU) of issuing certificate authority.

threat.enrichments.indicator.file.x509.issuer.state_or_province	List of state or province names (ST, S, or P)
threat.enrichments.indicator.file.x509.not_after	Time at which the certificate is no longer considered valid.
threat.enrichments.indicator.file.x509.not_before	Time at which the certificate is first considered valid.
threat.enrichments.indicator.file.x509.public_key_algorithm	Algorithm used to generate the public key.
threat.enrichments.indicator.file.x509.public_key_curve	The curve used by the elliptic curve public key algorithm. This is algorithm specific.
threat.enrichments.indicator.file.x509.public_key_exponent	Exponent used to derive the public key. This is algorithm specific.
threat.enrichments.indicator.file.x509.public_key_size	The size of the public key space in bits.
threat.enrichments.indicator.file.x509.serial_number	Unique serial number issued by the certificate authority.
threat.enrichments.indicator.file.x509.signature_algorithm	Identifier for certificate signature algorithm.
threat.enrichments.indicator.file.x509.subject.common_name	List of common names (CN) of subject.
threat.enrichments.indicator.file.x509.subject.country	List of country \(\text{C}\) code
threat.enrichments.indicator.file.x509.subject.distinguished_name	Distinguished name (DN) of the certificate subject entity.
threat.enrichments.indicator.file.x509.subject.locality	List of locality names (L)
threat.enrichments.indicator.file.x509.subject.organization	List of organizations (O) of subject.
threat.enrichments.indicator.file.x509.subject.organizational_unit	List of organizational units (OU) of subject.
threat.enrichments.indicator.file.x509.subject.state_or_province	List of state or province names (ST, S, or P)
threat.enrichments.indicator.file.x509.version_number	Version of x509 format.
threat.enrichments.indicator.first_seen	Date/time indicator was first reported.
threat.enrichments.indicator.geo.city_name	City name.
threat.enrichments.indicator.geo.continent_code	Continent code.
threat.enrichments.indicator.geo.continent_name	Name of the continent.
threat.enrichments.indicator.geo.country_iso_code	Country ISO code.
threat.enrichments.indicator.geo.country_name	Country name.
threat.enrichments.indicator.geo.location	Longitude and latitude.
threat.enrichments.indicator.geo.name	User-defined description of a location.
threat.enrichments.indicator.geo.postal_code	Postal code.
threat.enrichments.indicator.geo.region_iso_code	Region ISO code.
threat.enrichments.indicator.geo.region_name	Region name.
threat.enrichments.indicator.geo.timezone	Time zone.
threat.enrichments.indicator.ip	Indicator IP address
threat.enrichments.indicator.last_seen	Date/time indicator was last reported.
threat.enrichments.indicator.marking.tlp	Indicator TLP marking
threat.enrichments.indicator.marking.tlp_version	Indicator TLP version
threat.enrichments.indicator.modified_at	Date/time indicator was last updated.
threat.enrichments.indicator.name	Indicator display name
threat.enrichments.indicator.port	Indicator port
threat.enrichments.indicator.provider	Indicator provider
threat.enrichments.indicator.reference	Indicator reference URL

threat.enrichments.indicator.registry.data.bytes	Original bytes written with base64 encoding.
threat.enrichments.indicator.registry.data.strings	List of strings representing what was written to the registry.
threat.enrichments.indicator.registry.data.type	Standard registry type for encoding contents
threat.enrichments.indicator.registry.hive	Abbreviated name for the hive.
threat.enrichments.indicator.registry.key	Hive-relative path of keys.
threat.enrichments.indicator.registry.path	Full path, including hive, key and value
threat.enrichments.indicator.registry.value	Name of the value written.
threat.enrichments.indicator.scanner_stats	Scanner statistics
threat.enrichments.indicator.sightings	Number of times indicator observed
threat.enrichments.indicator.type	Type of indicator
threat.enrichments.indicator.url.domain	Domain of the url.
threat.enrichments.indicator.url.extension	File extension from the request url, excluding the leading dot.
threat.enrichments.indicator.url.fragment	Portion of the url after the '#'.
threat.enrichments.indicator.url.full	Full unparsed URL.
threat.enrichments.indicator.url.full.text	Full unparsed URL.
threat.enrichments.indicator.url.original	Unmodified original url as seen in the event source.
threat.enrichments.indicator.url.original.text	Unmodified original url as seen in the event source.
threat.enrichments.indicator.url.password	Password of the request.
threat.enrichments.indicator.url.path	Path of the request, such as "/search".
threat.enrichments.indicator.url.port	Port of the request, such as 443.
threat.enrichments.indicator.url.query	Query string of the request.
threat.enrichments.indicator.url.registered_domain	The highest registered url domain, stripped of the subdomain.
threat.enrichments.indicator.url.scheme	Scheme of the url.
threat.enrichments.indicator.url.subdomain	The subdomain of the domain.
threat.enrichments.indicator.url.top_level_domain	The effective top level domain (com, org, net, co.uk).
threat.enrichments.indicator.url.username	Username of the request.
threat.enrichments.indicator.x509.alternative_names	List of subject alternative names (SAN).
threat.enrichments.indicator.x509.issuer.common_name	List of common name (CN) of issuing certificate authority.
threat.enrichments.indicator.x509.issuer.country	List of country \(\C\) codes
threat.enrichments.indicator.x509.issuer.distinguished_name	Distinguished name (DN) of issuing certificate authority.
threat.enrichments.indicator.x509.issuer.locality	List of locality names (L)
threat.enrichments.indicator.x509.issuer.organization	List of organizations (O) of issuing certificate authority.
threat.enrichments.indicator.x509.issuer.organizational_unit	List of organizational units (OU) of issuing certificate authority.
threat.enrichments.indicator.x509.issuer.state_or_province	List of state or province names (ST, S, or P)
threat.enrichments.indicator.x509.not_after	Time at which the certificate is no longer considered valid.
threat.enrichments.indicator.x509.not_before	Time at which the certificate is first considered valid.
threat.enrichments.indicator.x509.public_key_algorithm	Algorithm used to generate the public key.
threat.enrichments.indicator.x509.public_key_curve	The curve used by the elliptic curve public key algorithm. This is algorithm specific.

threat.enrichments.indicator.x509.public_key_exponent	Exponent used to derive the public key. This is algorithm specific.
threat.enrichments.indicator.x509.public_key_size	The size of the public key space in bits.
threat.enrichments.indicator.x509.serial_number	Unique serial number issued by the certificate authority.
threat.enrichments.indicator.x509.signature_algorithm	Identifier for certificate signature algorithm.
threat.enrichments.indicator.x509.subject.common_name	List of common names (CN) of subject.
threat.enrichments.indicator.x509.subject.country	List of country \(\C\) code
threat.enrichments.indicator.x509.subject.distinguished_name	Distinguished name (DN) of the certificate subject entity.
threat.enrichments.indicator.x509.subject.locality	List of locality names (L)
threat.enrichments.indicator.x509.subject.organization	List of organizations (O) of subject.
threat.enrichments.indicator.x509.subject.organizational_unit	List of organizational units (OU) of subject.
threat.enrichments.indicator.x509.subject.state_or_province	List of state or province names (ST, S, or P)
threat.enrichments.indicator.x509.version_number	Version of x509 format.
threat.enrichments.matched.atomic	Matched indicator value
threat.enrichments.matched.field	Matched indicator field
threat.enrichments.matched.id	Matched indicator identifier
threat.enrichments.matched.index	Matched indicator index
threat.enrichments.matched.occurred	Date of match
threat.enrichments.matched.type	Type of indicator match
threat.feed.dashboard_id	Feed dashboard ID.
threat.feed.description	Description of the threat feed.
threat.feed.name	Name of the threat feed.
threat.feed.reference	Reference for the threat feed.
threat.framework	Threat classification framework.
threat.group.alias	Alias of the group.
threat.group.id	ID of the group.
threat.group.name	Name of the group.
threat.group.reference	Reference URL of the group.
threat.indicator.as.number	Unique number allocated to the autonomous system.
threat.indicator.as.organization.name	Organization name.
threat.indicator.as.organization.name.text	Organization name.
threat.indicator.confidence	Indicator confidence rating
threat.indicator.description	Indicator description
threat.indicator.email.address	Indicator email address
threat.indicator.file.accessed	Last time the file was accessed.
threat.indicator.file.attributes	Array of file attributes.
threat.indicator.file.code_signature.digest_algorithm	Hashing algorithm used to sign the process.
threat.indicator.file.code_signature.exists	Boolean to capture if a signature is present.
threat.indicator.file.code_signature.flags	Code signing flags of the process

threat.indicator.file.code_signature.signing_id	The identifier used to sign the process.
threat.indicator.file.code_signature.status	Additional information about the certificate status.
threat.indicator.file.code_signature.subject_name	Subject name of the code signer
threat.indicator.file.code_signature.team_id	The team identifier used to sign the process.
threat.indicator.file.code_signature.thumbprint_sha256	SHA256 hash of the certificate.
threat.indicator.file.code_signature.timestamp	When the signature was generated and signed.
threat.indicator.file.code_signature.trusted	Stores the trust status of the certificate chain.
threat.indicator.file.code_signature.valid	Boolean to capture if the digital signature is verified against the binary content.
threat.indicator.file.created	File creation time.
threat.indicator.file.ctime	Last time the file attributes or metadata changed.
threat.indicator.file.device	Device that is the source of the file.
threat.indicator.file.directory	Directory where the file is located.
threat.indicator.file.drive_letter	Drive letter where the file is located.
threat.indicator.file.elf.architecture	Machine architecture of the ELF file.
threat.indicator.file.elf.byte_order	Byte sequence of ELF file.
threat.indicator.file.elf.cpu_type	CPU type of the ELF file.
threat.indicator.file.elf.creation_date	Build or compile date.
threat.indicator.file.elf.exports	List of exported element names and types.
threat.indicator.file.elf.go_import_hash	A hash of the Go language imports in an ELF file.
threat.indicator.file.elf.go_imports	List of imported Go language element names and types.
threat.indicator.file.elf.go_imports_names_entropy	Shannon entropy calculation from the list of Go imports.
threat.indicator.file.elf.go_imports_names_var_entropy	Variance for Shannon entropy calculation from the list of Go imports.
threat.indicator.file.elf.go_stripped	Whether the file is a stripped or obfuscated Go executable.
threat.indicator.file.elf.header.abi_version	Version of the ELF Application Binary Interface (ABI).
threat.indicator.file.elf.header.class	Header class of the ELF file.
threat.indicator.file.elf.header.data	Data table of the ELF header.
threat.indicator.file.elf.header.entrypoint	Header entrypoint of the ELF file.
threat.indicator.file.elf.header.object_version	"0x1" for original ELF files.
threat.indicator.file.elf.header.os_abi	Application Binary Interface (ABI) of the Linux OS.
threat.indicator.file.elf.header.type	Header type of the ELF file.
threat.indicator.file.elf.header.version	Version of the ELF header.
threat.indicator.file.elf.import_hash	A hash of the imports in an ELF file.
threat.indicator.file.elf.imports	List of imported element names and types.
threat.indicator.file.elf.imports_names_entropy	Shannon entropy calculation from the list of imported element names and types.
threat.indicator.file.elf.imports_names_var_entropy	Variance for Shannon entropy calculation from the list of imported element names and types.
threat.indicator.file.elf.sections	Section information of the ELF file.
threat.indicator.file.elf.sections.chi2	Chi-square probability distribution of the section.
threat.indicator.file.elf.sections.entropy	Shannon entropy calculation from the section.

threat.indicator.file.elf.sections.flags	ELF Section List flags.
threat.indicator.file.elf.sections.name	ELF Section List name.
threat.indicator.file.elf.sections.physical_offset	ELF Section List offset.
threat.indicator.file.elf.sections.physical_size	ELF Section List physical size.
threat.indicator.file.elf.sections.type	ELF Section List type.
threat.indicator.file.elf.sections.var_entropy	Variance for Shannon entropy calculation from the section.
threat.indicator.file.elf.sections.virtual_address	ELF Section List virtual address.
threat.indicator.file.elf.sections.virtual_size	ELF Section List virtual size.
threat.indicator.file.elf.segments	ELF object segment list.
threat.indicator.file.elf.segments.sections	ELF object segment sections.
threat.indicator.file.elf.segments.type	ELF object segment type.
threat.indicator.file.elf.shared_libraries	List of shared libraries used by this ELF object.
threat.indicator.file.elf.telfhash	telfhash hash for ELF file.
threat.indicator.file.extension	File extension, excluding the leading dot.
threat.indicator.file.fork_name	A fork is additional data associated with a filesystem object.
threat.indicator.file.gid	Primary group ID (GID) of the file.
threat.indicator.file.group	Primary group name of the file.
threat.indicator.file.hash.cdhash	The Code Directory (CD) hash of an executable.
threat.indicator.file.hash.md5	MD5 hash.
threat.indicator.file.hash.sha1	SHA1 hash.
threat.indicator.file.hash.sha256	SHA256 hash.
threat.indicator.file.hash.sha384	SHA384 hash.
threat.indicator.file.hash.sha512	SHA512 hash.
threat.indicator.file.hash.ssdeep	SSDEEP hash.
threat.indicator.file.hash.tlsh	TLSH hash.
threat.indicator.file.inode	Inode representing the file in the filesystem.
threat.indicator.file.mime_type	Media type of file, document, or arrangement of bytes.
threat.indicator.file.mode	Mode of the file in octal representation.
threat.indicator.file.mtime	Last time the file content was modified.
threat.indicator.file.name	Name of the file including the extension, without the directory.
threat.indicator.file.origin_referrer_url	The URL of the webpage that linked to the file.
threat.indicator.file.origin_url	The URL where the file is hosted.
threat.indicator.file.owner	File owner's username.
threat.indicator.file.path	Full path to the file, including the file name.
threat.indicator.file.path.text	Full path to the file, including the file name.
threat.indicator.file.pe.architecture	CPU architecture target for the file.
threat.indicator.file.pe.company	Internal company name of the file, provided at compile-time.
threat.indicator.file.pe.description	Internal description of the file, provided at compile-time.

threat.indicator.file.pe.file_version	Process name.
threat.indicator.file.pe.go_import_hash	A hash of the Go language imports in a PE file.
threat.indicator.file.pe.go_imports	List of imported Go language element names and types.
threat.indicator.file.pe.go_imports_names_entropy	Shannon entropy calculation from the list of Go imports.
threat.indicator.file.pe.go_imports_names_var_entropy	Variance for Shannon entropy calculation from the list of Go imports.
threat.indicator.file.pe.go_stripped	Whether the file is a stripped or obfuscated Go executable.
threat.indicator.file.pe.imphash	A hash of the imports in a PE file.
threat.indicator.file.pe.import_hash	A hash of the imports in a PE file.
threat.indicator.file.pe.imports	List of imported element names and types.
threat.indicator.file.pe.imports_names_entropy	Shannon entropy calculation from the list of imported element names and types.
threat.indicator.file.pe.imports_names_var_entropy	Variance for Shannon entropy calculation from the list of imported element names and types.
threat.indicator.file.pe.original_file_name	Internal name of the file, provided at compile-time.
threat.indicator.file.pe.pehash	A hash of the PE header and data from one or more PE sections.
threat.indicator.file.pe.product	Internal product name of the file, provided at compile-time.
threat.indicator.file.pe.sections	Section information of the PE file.
threat.indicator.file.pe.sections_entropy	Shannon entropy calculation from the section.
threat.indicator.file.pe.sections.name	PE Section List name.
threat.indicator.file.pe.sections.physical_size	PE Section List physical size.
threat.indicator.file.pe.sections.var_entropy	Variance for Shannon entropy calculation from the section.
threat.indicator.file.pe.sections.virtual_size	PE Section List virtual size. This is always the same as `physical_size`.
threat.indicator.file.size	File size in bytes.
threat.indicator.file.target_path	Target path for symlinks.
threat.indicator.file.target_path.text	Target path for symlinks.
threat.indicator.file.type	File type (file, dir, or symlink).
threat.indicator.file.uid	The user ID (UID) or security identifier (SID) of the file owner.
threat.indicator.file.x509.alternative_names	List of subject alternative names (SAN).
threat.indicator.file.x509.issuer.common_name	List of common name (CN) of issuing certificate authority.
threat.indicator.file.x509.issuer.country	List of country \C) codes
threat.indicator.file.x509.issuer.distinguished_name	Distinguished name (DN) of issuing certificate authority.
threat.indicator.file.x509.issuer.locality	List of locality names (L)
threat.indicator.file.x509.issuer.organization	List of organizations (O) of issuing certificate authority.
threat.indicator.file.x509.issuer.organizational_unit	List of organizational units (OU) of issuing certificate authority.
threat.indicator.file.x509.issuer.state_or_province	List of state or province names (ST, S, or P)
threat.indicator.file.x509.not_after	Time at which the certificate is no longer considered valid.
threat.indicator.file.x509.not_before	Time at which the certificate is first considered valid.
threat.indicator.file.x509.public_key_algorithm	Algorithm used to generate the public key.
threat.indicator.file.x509.public_key_curve	The curve used by the elliptic curve public key algorithm. This is algorithm specific.
threat.indicator.file.x509.public_key_exponent	Exponent used to derive the public key. This is algorithm specific.

threat.indicator.file.x509.public_key_size	The size of the public key space in bits.
threat.indicator.file.x509.serial_number	Unique serial number issued by the certificate authority.
threat.indicator.file.x509.signature_algorithm	Identifier for certificate signature algorithm.
threat.indicator.file.x509.subject.common_name	List of common names (CN) of subject.
threat.indicator.file.x509.subject.country	List of country \(\C\) code
threat.indicator.file.x509.subject.distinguished_name	Distinguished name (DN) of the certificate subject entity.
threat.indicator.file.x509.subject.locality	List of locality names (L)
threat.indicator.file.x509.subject.organization	List of organizations (O) of subject.
threat.indicator.file.x509.subject.organizational_unit	List of organizational units (OU) of subject.
threat.indicator.file.x509.subject.state_or_province	List of state or province names (ST, S, or P)
threat.indicator.file.x509.version_number	Version of x509 format.
threat.indicator.first_seen	Date/time indicator was first reported.
threat.indicator.geo.city_name	City name.
threat.indicator.geo.continent_code	Continent code.
threat.indicator.geo.continent_name	Name of the continent.
threat.indicator.geo.country_iso_code	Country ISO code.
threat.indicator.geo.country_name	Country name.
threat.indicator.geo.location	Longitude and latitude.
threat.indicator.geo.name	User-defined description of a location.
threat.indicator.geo.postal_code	Postal code.
threat.indicator.geo.region_iso_code	Region ISO code.
threat.indicator.geo.region_name	Region name.
threat.indicator.geo.timezone	Time zone.
threat.indicator.id	ID of the indicator
threat.indicator.ip	Indicator IP address
threat.indicator.last_seen	Date/time indicator was last reported.
threat.indicator.marking.tlp	Indicator TLP marking
threat.indicator.marking.tlp_version	Indicator TLP version
threat.indicator.modified_at	Date/time indicator was last updated.
threat.indicator.name	Indicator display name
threat.indicator.port	Indicator port
threat.indicator.provider	Indicator provider
threat.indicator.reference	Indicator reference URL
threat.indicator.registry.data.bytes	Original bytes written with base64 encoding.
threat.indicator.registry.data.strings	List of strings representing what was written to the registry.
threat.indicator.registry.data.type	Standard registry type for encoding contents
threat.indicator.registry.hive	Abbreviated name for the hive.
threat.indicator.registry.key	Hive-relative path of keys.

threat.indicator.registry.path	Full path, including hive, key and value
threat.indicator.registry.value	Name of the value written.
threat.indicator.scanner_stats	Scanner statistics
threat.indicator.sightings	Number of times indicator observed
threat.indicator.type	Type of indicator
threat.indicator.url.domain	Domain of the url.
threat.indicator.url.extension	File extension from the request url, excluding the leading dot.
threat.indicator.url.fragment	Portion of the url after the '#'.
threat.indicator.url.full	Full unparsed URL.
threat.indicator.url.full.text	Full unparsed URL.
threat.indicator.url.original	Unmodified original url as seen in the event source.
threat.indicator.url.original.text	Unmodified original url as seen in the event source.
threat.indicator.url.password	Password of the request.
threat.indicator.url.path	Path of the request, such as "/search".
threat.indicator.url.port	Port of the request, such as 443.
threat.indicator.url.query	Query string of the request.
threat.indicator.url.registered_domain	The highest registered url domain, stripped of the subdomain.
threat.indicator.url.scheme	Scheme of the url.
threat.indicator.url.subdomain	The subdomain of the domain.
threat.indicator.url.top_level_domain	The effective top level domain (com, org, net, co.uk).
threat.indicator.url.username	Username of the request.
threat.indicator.x509.alternative_names	List of subject alternative names (SAN).
threat.indicator.x509.issuer.common_name	List of common name (CN) of issuing certificate authority.
threat.indicator.x509.issuer.country	List of country \(\C\) codes
threat.indicator.x509.issuer.distinguished_name	Distinguished name (DN) of issuing certificate authority.
threat.indicator.x509.issuer.locality	List of locality names (L)
threat.indicator.x509.issuer.organization	List of organizations (O) of issuing certificate authority.
threat.indicator.x509.issuer.organizational_unit	List of organizational units (OU) of issuing certificate authority.
threat.indicator.x509.issuer.state_or_province	List of state or province names (ST, S, or P)
threat.indicator.x509.not_after	Time at which the certificate is no longer considered valid.
threat.indicator.x509.not_before	Time at which the certificate is first considered valid.
threat.indicator.x509.public_key_algorithm	Algorithm used to generate the public key.
threat.indicator.x509.public_key_curve	The curve used by the elliptic curve public key algorithm. This is algorithm specific.
threat.indicator.x509.public_key_exponent	Exponent used to derive the public key. This is algorithm specific.
threat.indicator.x509.public_key_size	The size of the public key space in bits.
threat.indicator.x509.serial_number	Unique serial number issued by the certificate authority.
threat.indicator.x509.signature_algorithm	Identifier for certificate signature algorithm.
threat.indicator.x509.subject.common_name	List of common names (CN) of subject.

threat.indicator.x509.subject.country	List of country \(\C\) code
threat.indicator.x509.subject.distinguished_name	Distinguished name (DN) of the certificate subject entity.
threat.indicator.x509.subject.locality	List of locality names (L)
threat.indicator.x509.subject.organization	List of organizations (O) of subject.
threat.indicator.x509.subject.organizational_unit	List of organizational units (OU) of subject.
threat.indicator.x509.subject.state_or_province	List of state or province names (ST, S, or P)
threat.indicator.x509.version_number	Version of x509 format.
threat.software.alias	Alias of the software
threat.software.id	ID of the software
threat.software.name	Name of the software.
threat.software.platforms	Platforms of the software.
threat.software.reference	Software reference URL.
threat.software.type	Software type.
threat.tactic.id	Threat tactic id.
threat.tactic.name	Threat tactic.
threat.tactic.reference	Threat tactic URL reference.
threat.technique.id	Threat technique id.
threat.technique.name	Threat technique name.
threat.technique.name.text	Threat technique name.
threat.technique.reference	Threat technique URL reference.
threat.technique.subtechnique.id	Threat subtechnique id.
threat.technique.subtechnique.name	Threat subtechnique name.
threat.technique.subtechnique.name.text	Threat subtechnique name.
threat.technique.subtechnique.reference	Threat subtechnique URL reference.
tls.cipher	String indicating the cipher used during the current connection.
tls.client.certificate	PEM-encoded stand-alone certificate offered by the client.
tls.client.certificate_chain	Array of PEM-encoded certificates that make up the certificate chain offered by the client.
tls.client.hash.md5	Certificate fingerprint using the MD5 digest of DER-encoded version of certificate offered by the client.
tls.client.hash.sha1	Certificate fingerprint using the SHA1 digest of DER-encoded version of certificate offered by the client.
tls.client.hash.sha256	Certificate fingerprint using the SHA256 digest of DER-encoded version of certificate offered by the client.
tls.client.issuer	Distinguished name of subject of the issuer of the x.509 certificate presented by the client.
tls.client.ja3	A hash that identifies clients based on how they perform an SSL/TLS handshake.
tls.client.not_after	Date/Time indicating when client certificate is no longer considered valid.
tls.client.not_before	Date/Time indicating when client certificate is first considered valid.
tls.client.server_name	Hostname the client is trying to connect to. Also called the SNI.
tls.client.subject	Distinguished name of subject of the x.509 certificate presented by the client.
tls.client.supported_ciphers	Array of ciphers offered by the client during the client hello.
tls.client.x509.alternative_names	List of subject alternative names (SAN).

tls.client.x509.issuer.common_name	List of common name (CN) of issuing certificate authority.
tls.client.x509.issuer.country	List of country \(\C\) codes
tls.client.x509.issuer.distinguished_name	Distinguished name (DN) of issuing certificate authority.
tls.client.x509.issuer.locality	List of locality names (L)
tls.client.x509.issuer.organization	List of organizations (O) of issuing certificate authority.
tls.client.x509.issuer.organizational_unit	List of organizational units (OU) of issuing certificate authority.
tls.client.x509.issuer.state_or_province	List of state or province names (ST, S, or P)
tls.client.x509.not_after	Time at which the certificate is no longer considered valid.
tls.client.x509.not_before	Time at which the certificate is first considered valid.
tls.client.x509.public_key_algorithm	Algorithm used to generate the public key.
tls.client.x509.public_key_curve	The curve used by the elliptic curve public key algorithm. This is algorithm specific.
tls.client.x509.public_key_exponent	Exponent used to derive the public key. This is algorithm specific.
tls.client.x509.public_key_size	The size of the public key space in bits.
tls.client.x509.serial_number	Unique serial number issued by the certificate authority.
tls.client.x509.signature_algorithm	Identifier for certificate signature algorithm.
tls.client.x509.subject.common_name	List of common names (CN) of subject.
tls.client.x509.subject.country	List of country \(\C\) code
tls.client.x509.subject.distinguished_name	Distinguished name (DN) of the certificate subject entity.
tls.client.x509.subject.locality	List of locality names (L)
tls.client.x509.subject.organization	List of organizations (O) of subject.
tls.client.x509.subject.organizational_unit	List of organizational units (OU) of subject.
tls.client.x509.subject.state_or_province	List of state or province names (ST, S, or P)
tls.client.x509.version_number	Version of x509 format.
tls.curve	String indicating the curve used for the given cipher, when applicable.
tls.established	Boolean flag indicating if the TLS negotiation was successful and transitioned to an encrypted tunnel.
tls.next_protocol	String indicating the protocol being tunneled.
tls.resumed	Boolean flag indicating if this TLS connection was resumed from an existing TLS negotiation.
tls.server.certificate	PEM-encoded stand-alone certificate offered by the server.
tls.server.certificate_chain	Array of PEM-encoded certificates that make up the certificate chain offered by the server.
tls.server.hash.md5	Certificate fingerprint using the MD5 digest of DER-encoded version of certificate offered by the server.
tls.server.hash.sha1	Certificate fingerprint using the SHA1 digest of DER-encoded version of certificate offered by the server.
tls.server.hash.sha256	Certificate fingerprint using the SHA256 digest of DER-encoded version of certificate offered by the server.
tls.server.issuer	Subject of the issuer of the x.509 certificate presented by the server.
tls.server.ja3s	A hash that identifies servers based on how they perform an SSL/TLS handshake.
tls.server.not_after	Timestamp indicating when server certificate is no longer considered valid.
tls.server.not_before	Timestamp indicating when server certificate is first considered valid.
tls.server.subject	Subject of the x.509 certificate presented by the server.
tls.server.x509.alternative_names	List of subject alternative names (SAN).

tls.server.x509.issuer.common_name	List of common name (CN) of issuing certificate authority.
tls.server.x509.issuer.country	List of country \(\C\) codes
tls.server.x509.issuer.distinguished_name	Distinguished name (DN) of issuing certificate authority.
tls.server.x509.issuer.locality	List of locality names (L)
tls.server.x509.issuer.organization	List of organizations (O) of issuing certificate authority.
tls.server.x509.issuer.organizational_unit	List of organizational units (OU) of issuing certificate authority.
tls.server.x509.issuer.state_or_province	List of state or province names (ST, S, or P)
tls.server.x509.not_after	Time at which the certificate is no longer considered valid.
tls.server.x509.not_before	Time at which the certificate is first considered valid.
tls.server.x509.public_key_algorithm	Algorithm used to generate the public key.
tls.server.x509.public_key_curve	The curve used by the elliptic curve public key algorithm. This is algorithm specific.
tls.server.x509.public_key_exponent	Exponent used to derive the public key. This is algorithm specific.
tls.server.x509.public_key_size	The size of the public key space in bits.
tls.server.x509.serial_number	Unique serial number issued by the certificate authority.
tls.server.x509.signature_algorithm	Identifier for certificate signature algorithm.
tls.server.x509.subject.common_name	List of common names (CN) of subject.
tls.server.x509.subject.country	List of country \(\C\) code
tls.server.x509.subject.distinguished_name	Distinguished name (DN) of the certificate subject entity.
tls.server.x509.subject.locality	List of locality names (L)
tls.server.x509.subject.organization	List of organizations (O) of subject.
tls.server.x509.subject.organizational_unit	List of organizational units (OU) of subject.
tls.server.x509.subject.state_or_province	List of state or province names (ST, S, or P)
tls.server.x509.version_number	Version of x509 format.
tls.version	Numeric part of the version parsed from the original string.
tls.version_protocol	Normalized lowercase protocol name parsed from original string.
trace.id	Unique identifier of the trace.
transaction.id	Unique identifier of the transaction within the scope of its trace.
url.domain	Domain of the url.
url.extension	File extension from the request url, excluding the leading dot.
url.fragment	Portion of the url after the '#'.
url.full	Full unparsed URL.
url.full.text	Full unparsed URL.
url.original	Unmodified original url as seen in the event source.
url.original.text	Unmodified original url as seen in the event source.
url.password	Password of the request.
url.path	Path of the request, such as "/search".
url.port	Port of the request, such as 443.
url.query	Query string of the request.

url.registered_domain	The highest registered url domain, stripped of the subdomain.
url.scheme	Scheme of the url.
url.subdomain	The subdomain of the domain.
url.top_level_domain	The effective top level domain (com, org, net, co.uk).
url.username	Username of the request.
user.changes.domain	Name of the directory the user is a member of.
user.changes.email	User email address.
user.changes.entity.attributes.known_redirects	Known redirect URIs or URLs associated with this entity.
user.changes.entity.attributes.managed	Indicates whether the entity is managed by an external system.
user.changes.entity.attributes.mfa_enabled	Indicates whether multi-factor authentication is enabled for this entity.
user.changes.entity.attributes.oauth_consent_restriction	Restriction applied to OAuth consent for this entity.
user.changes.entity.attributes.permissions	Action-level permissions associated with this entity.
user.changes.entity.attributes.storage_class	Storage tier or class assigned to an object storage resource.
user.changes.entity.behavior	A set of ephemeral characteristics of the entity, derived from observed behaviors during a specific time period.
user.changes.entity.display_name	An optional field used when a pretty name is desired for entity-centric operations.
user.changes.entity.display_name.text	An optional field used when a pretty name is desired for entity-centric operations.
user.changes.entity.id	Unique identifier for the entity.
user.changes.entity.last_seen_timestamp	Indicates the date/time when this entity was last "seen."
user.changes.entity.lifecycle.last_activity	Timestamp of the most recent action performed by or attributed to this entity.
user.changes.entity.metrics	Field set for any fields containing numeric entity metrics.
user.changes.entity.name	The name of the entity.
user.changes.entity.name.text	The name of the entity.
user.changes.entity.raw	Original, unmodified fields from the source system.
user.changes.entity.reference	A URI, URL, or other direct reference to access or locate the entity.
user.changes.entity.relationships.administers.entity.id	Identifiers of referenced entities.
user.changes.entity.relationships.administers.host.id	Referenced host ids.
user.changes.entity.relationships.administers.host.name	Referenced host names.
user.changes.entity.relationships.administers.service.id	Referenced service ids.
user.changes.entity.relationships.administers.service.name	Referenced service names.
user.changes.entity.relationships.administers.user.domain	Referenced user directory or AD/LDAP domain names.
user.changes.entity.relationships.administers.user.email	Referenced user email addresses.
user.changes.entity.relationships.administers.user.id	Referenced user ids.
user.changes.entity.relationships.administers.user.name	Referenced user short names or logins.
user.changes.entity.relationships.depends_on.entity.id	Identifiers of referenced entities.
user.changes.entity.relationships.depends_on.host.id	Referenced host ids.
user.changes.entity.relationships.depends_on.host.name	Referenced host names.
user.changes.entity.relationships.depends_on.service.id	Referenced service ids.
user.changes.entity.relationships.depends_on.service.name	Referenced service names.

user.changes.entity.relationships.depends_on.user.domain	Referenced user directory or AD/LDAP domain names.
user.changes.entity.relationships.depends_on.user.email	Referenced user email addresses.
user.changes.entity.relationships.depends_on.user.id	Referenced user ids.
user.changes.entity.relationships.depends_on.user.name	Referenced user short names or logins.
user.changes.entity.relationships.owns.entity.id	Identifiers of referenced entities.
user.changes.entity.relationships.owns.host.id	Referenced host ids.
user.changes.entity.relationships.owns.host.name	Referenced host names.
user.changes.entity.relationships.owns.service.id	Referenced service ids.
user.changes.entity.relationships.owns.service.name	Referenced service names.
user.changes.entity.relationships.owns.user.domain	Referenced user directory or AD/LDAP domain names.
user.changes.entity.relationships.owns.user.email	Referenced user email addresses.
user.changes.entity.relationships.owns.user.id	Referenced user ids.
user.changes.entity.relationships.owns.user.name	Referenced user short names or logins.
user.changes.entity.relationships.supervises.entity.id	Identifiers of referenced entities.
user.changes.entity.relationships.supervises.host.id	Referenced host ids.
user.changes.entity.relationships.supervises.host.name	Referenced host names.
user.changes.entity.relationships.supervises.service.id	Referenced service ids.
user.changes.entity.relationships.supervises.service.name	Referenced service names.
user.changes.entity.relationships.supervises.user.domain	Referenced user directory or AD/LDAP domain names.
user.changes.entity.relationships.supervises.user.email	Referenced user email addresses.
user.changes.entity.relationships.supervises.user.id	Referenced user ids.
user.changes.entity.relationships.supervises.user.name	Referenced user short names or logins.
user.changes.entity.source	Source module or integration that provided the entity data.
user.changes.entity.sub_type	The specific type designation for the entity as defined by its provider or system.
user.changes.entity.type	Standardized high-level classification of the entity.
user.changes.full_name	User's full name, if available.
user.changes.full_name.text	User's full name, if available.
user.changes.group.domain	Name of the directory the group is a member of.
user.changes.group.id	Unique identifier for the group on the system/platform.
user.changes.group.name	Name of the group.
user.changes.hash	Unique user hash to correlate information for a user in anonymized form.
user.changes.id	Unique identifier of the user.
user.changes.name	Short name or login of the user.
user.changes.name.text	Short name or login of the user.
user.changes.risk.calculated_level	A risk classification level calculated by an internal system as part of entity analytics and entity risk scoring.
user.changes.risk.calculated_score	A risk classification score calculated by an internal system as part of entity analytics and entity risk scoring.
user.changes.risk.calculated_score_norm	A normalized risk score calculated by an internal system.
user.changes.risk.static_level	A risk classification level obtained from outside the system, such as from some external Threat Intelligence Platform.

user.changes.risk.static_score	A risk classification score obtained from outside the system, such as from some external Threat Intelligence Platform.
user.changes.risk.static_score_norm	A normalized risk score calculated by an external system.
user.changes.roles	Array of user roles at the time of the event.
user.domain	Name of the directory the user is a member of.
user.effective.domain	Name of the directory the user is a member of.
user.effective.email	User email address.
user.effective.entity.attributes.known_redirects	Known redirect URIs or URLs associated with this entity.
user.effective.entity.attributes.managed	Indicates whether the entity is managed by an external system.
user.effective.entity.attributes.mfa_enabled	Indicates whether multi-factor authentication is enabled for this entity.
user.effective.entity.attributes.oauth_consent_restriction	Restriction applied to OAuth consent for this entity.
user.effective.entity.attributes.permissions	Action-level permissions associated with this entity.
user.effective.entity.attributes.storage_class	Storage tier or class assigned to an object storage resource.
user.effective.entity.behavior	A set of ephemeral characteristics of the entity, derived from observed behaviors during a specific time period.
user.effective.entity.display_name	An optional field used when a pretty name is desired for entity-centric operations.
user.effective.entity.display_name.text	An optional field used when a pretty name is desired for entity-centric operations.
user.effective.entity.id	Unique identifier for the entity.
user.effective.entity.last_seen_timestamp	Indicates the date/time when this entity was last "seen."
user.effective.entity.lifecycle.last_activity	Timestamp of the most recent action performed by or attributed to this entity.
user.effective.entity.metrics	Field set for any fields containing numeric entity metrics.
user.effective.entity.name	The name of the entity.
user.effective.entity.name.text	The name of the entity.
user.effective.entity.raw	Original, unmodified fields from the source system.
user.effective.entity.reference	A URI, URL, or other direct reference to access or locate the entity.
user.effective.entity.relationships.administers.entity.id	Identifiers of referenced entities.
user.effective.entity.relationships.administers.host.id	Referenced host ids.
user.effective.entity.relationships.administers.host.name	Referenced host names.
user.effective.entity.relationships.administers.service.id	Referenced service ids.
user.effective.entity.relationships.administers.service.name	Referenced service names.
user.effective.entity.relationships.administers.user.domain	Referenced user directory or AD/LDAP domain names.
user.effective.entity.relationships.administers.user.email	Referenced user email addresses.
user.effective.entity.relationships.administers.user.id	Referenced user ids.
user.effective.entity.relationships.administers.user.name	Referenced user short names or logins.
user.effective.entity.relationships.depends_on.entity.id	Identifiers of referenced entities.
user.effective.entity.relationships.depends_on.host.id	Referenced host ids.
user.effective.entity.relationships.depends_on.host.name	Referenced host names.
user.effective.entity.relationships.depends_on.service.id	Referenced service ids.
user.effective.entity.relationships.depends_on.service.name	Referenced service names.
user.effective.entity.relationships.depends_on.user.domain	Referenced user directory or AD/LDAP domain names.

user.effective.entity.relationships.depends_on.user.email	Referenced user email addresses.
user.effective.entity.relationships.depends_on.user.id	Referenced user ids.
user.effective.entity.relationships.depends_on.user.name	Referenced user short names or logins.
user.effective.entity.relationships.owns.entity.id	Identifiers of referenced entities.
user.effective.entity.relationships.owns.host.id	Referenced host ids.
user.effective.entity.relationships.owns.host.name	Referenced host names.
user.effective.entity.relationships.owns.service.id	Referenced service ids.
user.effective.entity.relationships.owns.service.name	Referenced service names.
user.effective.entity.relationships.owns.user.domain	Referenced user directory or AD/LDAP domain names.
user.effective.entity.relationships.owns.user.email	Referenced user email addresses.
user.effective.entity.relationships.owns.user.id	Referenced user ids.
user.effective.entity.relationships.owns.user.name	Referenced user short names or logins.
user.effective.entity.relationships.supervises.entity.id	Identifiers of referenced entities.
user.effective.entity.relationships.supervises.host.id	Referenced host ids.
user.effective.entity.relationships.supervises.host.name	Referenced host names.
user.effective.entity.relationships.supervises.service.id	Referenced service ids.
user.effective.entity.relationships.supervises.service.name	Referenced service names.
user.effective.entity.relationships.supervises.user.domain	Referenced user directory or AD/LDAP domain names.
user.effective.entity.relationships.supervises.user.email	Referenced user email addresses.
user.effective.entity.relationships.supervises.user.id	Referenced user ids.
user.effective.entity.relationships.supervises.user.name	Referenced user short names or logins.
user.effective.entity.source	Source module or integration that provided the entity data.
user.effective.entity.sub_type	The specific type designation for the entity as defined by its provider or system.
user.effective.entity.type	Standardized high-level classification of the entity.
user.effective.full_name	User's full name, if available.
user.effective.full_name.text	User's full name, if available.
user.effective.group.domain	Name of the directory the group is a member of.
user.effective.group.id	Unique identifier for the group on the system/platform.
user.effective.group.name	Name of the group.
user.effective.hash	Unique user hash to correlate information for a user in anonymized form.
user.effective.id	Unique identifier of the user.
user.effective.name	Short name or login of the user.
user.effective.name.text	Short name or login of the user.
user.effective.risk.calculated_level	A risk classification level calculated by an internal system as part of entity analytics and entity risk scoring.
user.effective.risk.calculated_score	A risk classification score calculated by an internal system as part of entity analytics and entity risk scoring.
user.effective.risk.calculated_score_norm	A normalized risk score calculated by an internal system.
user.effective.risk.static_level	A risk classification level obtained from outside the system, such as from some external Threat Intelligence Platform.
user.effective.risk.static_score	A risk classification score obtained from outside the system, such as from some external Threat Intelligence Platform.

user.effective.risk.static_score_norm	A normalized risk score calculated by an external system.
user.effective.roles	Array of user roles at the time of the event.
user.email	User email address.
user.entity.attributes.known_redirects	Known redirect URIs or URLs associated with this entity.
user.entity.attributes.managed	Indicates whether the entity is managed by an external system.
user.entity.attributes.mfa_enabled	Indicates whether multi-factor authentication is enabled for this entity.
user.entity.attributes.oauth_consent_restriction	Restriction applied to OAuth consent for this entity.
user.entity.attributes.permissions	Action-level permissions associated with this entity.
user.entity.attributes.storage_class	Storage tier or class assigned to an object storage resource.
user.entity.behavior	A set of ephemeral characteristics of the entity, derived from observed behaviors during a specific time period.
user.entity.display_name	An optional field used when a pretty name is desired for entity-centric operations.
user.entity.display_name.text	An optional field used when a pretty name is desired for entity-centric operations.
user.entity.id	Unique identifier for the entity.
user.entity.last_seen_timestamp	Indicates the date/time when this entity was last "seen."
user.entity.lifecycle.last_activity	Timestamp of the most recent action performed by or attributed to this entity.
user.entity.metrics	Field set for any fields containing numeric entity metrics.
user.entity.name	The name of the entity.
user.entity.name.text	The name of the entity.
user.entity.raw	Original, unmodified fields from the source system.
user.entity.reference	A URI, URL, or other direct reference to access or locate the entity.
user.entity.relationships.administers.entity.id	Identifiers of referenced entities.
user.entity.relationships.administers.host.id	Referenced host ids.
user.entity.relationships.administers.host.name	Referenced host names.
user.entity.relationships.administers.service.id	Referenced service ids.
user.entity.relationships.administers.service.name	Referenced service names.
user.entity.relationships.administers.user.domain	Referenced user directory or AD/LDAP domain names.
user.entity.relationships.administers.user.email	Referenced user email addresses.
user.entity.relationships.administers.user.id	Referenced user ids.
user.entity.relationships.administers.user.name	Referenced user short names or logins.
user.entity.relationships.depends_on.entity.id	Identifiers of referenced entities.
user.entity.relationships.depends_on.host.id	Referenced host ids.
user.entity.relationships.depends_on.host.name	Referenced host names.
user.entity.relationships.depends_on.service.id	Referenced service ids.
user.entity.relationships.depends_on.service.name	Referenced service names.
user.entity.relationships.depends_on.user.domain	Referenced user directory or AD/LDAP domain names.
user.entity.relationships.depends_on.user.email	Referenced user email addresses.
user.entity.relationships.depends_on.user.id	Referenced user ids.
user.entity.relationships.depends_on.user.name	Referenced user short names or logins.

user.entity.relationships.owns.entity.id	Identifiers of referenced entities.
user.entity.relationships.owns.host.id	Referenced host ids.
user.entity.relationships.owns.host.name	Referenced host names.
user.entity.relationships.owns.service.id	Referenced service ids.
user.entity.relationships.owns.service.name	Referenced service names.
user.entity.relationships.owns.user.domain	Referenced user directory or AD/LDAP domain names.
user.entity.relationships.owns.user.email	Referenced user email addresses.
user.entity.relationships.owns.user.id	Referenced user ids.
user.entity.relationships.owns.user.name	Referenced user short names or logins.
user.entity.relationships.supervises.entity.id	Identifiers of referenced entities.
user.entity.relationships.supervises.host.id	Referenced host ids.
user.entity.relationships.supervises.host.name	Referenced host names.
user.entity.relationships.supervises.service.id	Referenced service ids.
user.entity.relationships.supervises.service.name	Referenced service names.
user.entity.relationships.supervises.user.domain	Referenced user directory or AD/LDAP domain names.
user.entity.relationships.supervises.user.email	Referenced user email addresses.
user.entity.relationships.supervises.user.id	Referenced user ids.
user.entity.relationships.supervises.user.name	Referenced user short names or logins.
user.entity.source	Source module or integration that provided the entity data.
user.entity.sub_type	The specific type designation for the entity as defined by its provider or system.
user.entity.type	Standardized high-level classification of the entity.
user.full_name	User's full name, if available.
user.full_name.text	User's full name, if available.
user.group.domain	Name of the directory the group is a member of.
user.group.id	Unique identifier for the group on the system/platform.
user.group.name	Name of the group.
user.hash	Unique user hash to correlate information for a user in anonymized form.
user.id	Unique identifier of the user.
user.name	Short name or login of the user.
user.name.text	Short name or login of the user.
user.risk.calculated_level	A risk classification level calculated by an internal system as part of entity analytics and entity risk scoring.
user.risk.calculated_score	A risk classification score calculated by an internal system as part of entity analytics and entity risk scoring.
user.risk.calculated_score_norm	A normalized risk score calculated by an internal system.
user.risk.static_level	A risk classification level obtained from outside the system, such as from some external Threat Intelligence Platform.
user.risk.static_score	A risk classification score obtained from outside the system, such as from some external Threat Intelligence Platform.
user.risk.static_score_norm	A normalized risk score calculated by an external system.
user.roles	Array of user roles at the time of the event.
user.target.domain	Name of the directory the user is a member of.

user.target.email	User email address.
user.target.entity.attributes.known_redirects	Known redirect URIs or URLs associated with this entity.
user.target.entity.attributes.managed	Indicates whether the entity is managed by an external system.
user.target.entity.attributes.mfa_enabled	Indicates whether multi-factor authentication is enabled for this entity.
user.target.entity.attributes.oauth_consent_restriction	Restriction applied to OAuth consent for this entity.
user.target.entity.attributes.permissions	Action-level permissions associated with this entity.
user.target.entity.attributes.storage_class	Storage tier or class assigned to an object storage resource.
user.target.entity.behavior	A set of ephemeral characteristics of the entity, derived from observed behaviors during a specific time period.
user.target.entity.display_name	An optional field used when a pretty name is desired for entity-centric operations.
user.target.entity.display_name.text	An optional field used when a pretty name is desired for entity-centric operations.
user.target.entity.id	Unique identifier for the entity.
user.target.entity.last_seen_timestamp	Indicates the date/time when this entity was last "seen."
user.target.entity.lifecycle.last_activity	Timestamp of the most recent action performed by or attributed to this entity.
user.target.entity.metrics	Field set for any fields containing numeric entity metrics.
user.target.entity.name	The name of the entity.
user.target.entity.name.text	The name of the entity.
user.target.entity.raw	Original, unmodified fields from the source system.
user.target.entity.reference	A URI, URL, or other direct reference to access or locate the entity.
user.target.entity.relationships.administers.entity.id	Identifiers of referenced entities.
user.target.entity.relationships.administers.host.id	Referenced host ids.
user.target.entity.relationships.administers.host.name	Referenced host names.
user.target.entity.relationships.administers.service.id	Referenced service ids.
user.target.entity.relationships.administers.service.name	Referenced service names.
user.target.entity.relationships.administers.user.domain	Referenced user directory or AD/LDAP domain names.
user.target.entity.relationships.administers.user.email	Referenced user email addresses.
user.target.entity.relationships.administers.user.id	Referenced user ids.
user.target.entity.relationships.administers.user.name	Referenced user short names or logins.
user.target.entity.relationships.depends_on.entity.id	Identifiers of referenced entities.
user.target.entity.relationships.depends_on.host.id	Referenced host ids.
user.target.entity.relationships.depends_on.host.name	Referenced host names.
user.target.entity.relationships.depends_on.service.id	Referenced service ids.
user.target.entity.relationships.depends_on.service.name	Referenced service names.
user.target.entity.relationships.depends_on.user.domain	Referenced user directory or AD/LDAP domain names.
user.target.entity.relationships.depends_on.user.email	Referenced user email addresses.
user.target.entity.relationships.depends_on.user.id	Referenced user ids.
user.target.entity.relationships.depends_on.user.name	Referenced user short names or logins.
user.target.entity.relationships.owns.entity.id	Identifiers of referenced entities.
user.target.entity.relationships.owns.host.id	Referenced host ids.

user.target.entity.relationships.owns.host.name	Referenced host names.
user.target.entity.relationships.owns.service.id	Referenced service ids.
user.target.entity.relationships.owns.service.name	Referenced service names.
user.target.entity.relationships.owns.user.domain	Referenced user directory or AD/LDAP domain names.
user.target.entity.relationships.owns.user.email	Referenced user email addresses.
user.target.entity.relationships.owns.user.id	Referenced user ids.
user.target.entity.relationships.owns.user.name	Referenced user short names or logins.
user.target.entity.relationships.supervises.entity.id	Identifiers of referenced entities.
user.target.entity.relationships.supervises.host.id	Referenced host ids.
user.target.entity.relationships.supervises.host.name	Referenced host names.
user.target.entity.relationships.supervises.service.id	Referenced service ids.
user.target.entity.relationships.supervises.service.name	Referenced service names.
user.target.entity.relationships.supervises.user.domain	Referenced user directory or AD/LDAP domain names.
user.target.entity.relationships.supervises.user.email	Referenced user email addresses.
user.target.entity.relationships.supervises.user.id	Referenced user ids.
user.target.entity.relationships.supervises.user.name	Referenced user short names or logins.
user.target.entity.source	Source module or integration that provided the entity data.
user.target.entity.sub_type	The specific type designation for the entity as defined by its provider or system.
user.target.entity.type	Standardized high-level classification of the entity.
user.target.full_name	User's full name, if available.
user.target.full_name.text	User's full name, if available.
user.target.group.domain	Name of the directory the group is a member of.
user.target.group.id	Unique identifier for the group on the system/platform.
user.target.group.name	Name of the group.
user.target.hash	Unique user hash to correlate information for a user in anonymized form.
user.target.id	Unique identifier of the user.
user.target.name	Short name or login of the user.
user.target.name.text	Short name or login of the user.
user.target.risk.calculated_level	A risk classification level calculated by an internal system as part of entity analytics and entity risk scoring.
user.target.risk.calculated_score	A risk classification score calculated by an internal system as part of entity analytics and entity risk scoring.
user.target.risk.calculated_score_norm	A normalized risk score calculated by an internal system.
user.target.risk.static_level	A risk classification level obtained from outside the system, such as from some external Threat Intelligence Platform.
user.target.risk.static_score	A risk classification score obtained from outside the system, such as from some external Threat Intelligence Platform.
user.target.risk.static_score_norm	A normalized risk score calculated by an external system.
user.target.roles	Array of user roles at the time of the event.
user_agent.device.name	Name of the device.
user_agent.name	Name of the user agent.
user_agent.original	Unparsed user_agent string.

user_agent.original.text	Unparsed user_agent string.
user_agent.os.family	OS family (such as redhat, debian, freebsd, windows).
user_agent.os.full	Operating system name, including the version or code name.
user_agent.os.full.text	Operating system name, including the version or code name.
user_agent.os.kernel	Operating system kernel version as a raw string.
user_agent.os.name	Operating system name, without the version.
user_agent.os.name.text	Operating system name, without the version.
user_agent.os.platform	Operating system platform (such centos, ubuntu, windows).
user_agent.os.type	Which commercial OS family (one of: linux, macos, unix, windows, ios or android).
user_agent.os.version	Operating system version as a raw string.
user_agent.version	Version of the user agent.
volume.bus_type	Bus type of the device.
volume.default_access	Bus type of the device.
volume.device_name	Device name of the volume.
volume.device_type	Volume device type.
volume.dos_name	DOS name of the device.
volume.file_system_type	Volume device file system type.
volume.mount_name	Mount name of the volume.
volume.nt_name	NT name of the device.
volume.product_id	ProductID of the device.
volume.product_name	Produce name of the volume.
volume.removable	Indicates if the volume is removable.
volume.serial_number	Serial number of the device.
volume.size	Size of the volume device in bytes.
volume.vendor_id	VendorID of the device.
volume.vendor_name	Vendor name of the device.
volume.writable	Indicates if the volume is writable.
vulnerability.category	Category of a vulnerability.
vulnerability.classification	Classification of the vulnerability.
vulnerability.description	Description of the vulnerability.
vulnerability.description.text	Description of the vulnerability.
vulnerability.enumeration	Identifier of the vulnerability.
vulnerability.id	ID of the vulnerability.
vulnerability.reference	Reference of the vulnerability.
vulnerability.report_id	Scan identification number.
vulnerability.scanner.vendor	Name of the scanner vendor.
vulnerability.score.base	Vulnerability Base score.
vulnerability.score.environmental	Vulnerability Environmental score.

vulnerability.score.temporal	Vulnerability Temporal score.
vulnerability.score.version	CVSS version.
vulnerability.severity	Severity of the vulnerability.
vulnerability.status	Lifecycle state of a vulnerability finding.