

ECS / Field Reference (RAG-Optimized)

This document preserves every field as a standalone semantic chunk.

Recommended chunking: 100-300 lines with 20-line overlap.

@timestamp

- **@timestamp**: Date/time when the event originated.

labels

- **labels**: Custom key/value pairs.

message

- **message**: Log message optimized for viewing in a log viewer.

tags

- **tags**: List of keywords used to tag each event.

agent

- **agent.build.original**: Extended build information for the agent.
- **agent.ephemeral_id**: Ephemeral identifier of this agent.
- **agent.id**: Unique identifier of this agent.
- **agent.name**: Custom name of the agent.
- **agent.type**: Type of the agent.
- **agent.version**: Version of the agent.

client

- **client.address**: Client network address.
- **client.as.number**: Unique number allocated to the autonomous system.
- **client.as.organization.name**: Organization name.
- **client.as.organization.name.text**: Organization name.
- **client.bytes**: Bytes sent from the client to the server.
- **client.domain**: The domain name of the client.
- **client.geo.city_name**: City name.
- **client.geo.continent_code**: Continent code.

- **client.geo.continent_name**: Name of the continent.
- **client.geo.country_iso_code**: Country ISO code.
- **client.geo.country_name**: Country name.
- **client.geo.location**: Longitude and latitude.
- **client.geo.name**: User-defined description of a location.
- **client.geo.postal_code**: Postal code.
- **client.geo.region_iso_code**: Region ISO code.
- **client.geo.region_name**: Region name.
- **client.geo.timezone**: Time zone.
- **client.ip**: IP address of the client.
- **client.mac**: MAC address of the client.
- **client.nat.ip**: Client NAT ip address
- **client.nat.port**: Client NAT port
- **client.packets**: Packets sent from the client to the server.
- **client.port**: Port of the client.
- **client.registered_domain**: The highest registered client domain, stripped of the subdomain.
- **client.subdomain**: The subdomain of the domain.
- **client.top_level_domain**: The effective top level domain (com, org, net, co.uk).
- **client.user.domain**: Name of the directory the user is a member of.
- **client.user.email**: User email address.
- **client.user.full_name**: User's full name, if available.
- **client.user.full_name.text**: User's full name, if available.
- **client.user.group.domain**: Name of the directory the group is a member of.
- **client.user.group.id**: Unique identifier for the group on the system/platform.
- **client.user.group.name**: Name of the group.
- **client.user.hash**: Unique user hash to correlate information for a user in anonymized form.
- **client.user.id**: Unique identifier of the user.
- **client.user.name**: Short name or login of the user.
- **client.user.name.text**: Short name or login of the user.
- **client.user.roles**: Array of user roles at the time of the event.

cloud

- **cloud.account.id**: The cloud account or organization id.
- **cloud.account.name**: The cloud account name.
- **cloud.availability_zone**: Availability zone in which this host, resource, or service is located.
- **cloud.entity.attributes.known_redirects**: Known redirect URIs or URLs associated with this entity.
- **cloud.entity.attributes.managed**: Indicates whether the entity is managed by an external system.

- **cloud.entity.attributes.mfa_enabled**: Indicates whether multi-factor authentication is enabled for this entity.
- **cloud.entity.attributes.oauth_consent_restrictionRestriction**: applied to OAuth consent for this entity.
- **cloud.entity.attributes.permissions**: Action-level permissions associated with this entity.
- **cloud.entity.attributes.storage_class**: Storage tier or class assigned to an object storage resource.
- **cloud.entity.behavior**: A set of ephemeral characteristics of the entity, derived from observed behaviors during a specific time period.
- **cloud.entity.display_name**: An optional field used when a pretty name is desired for entity-centric operations.
- **cloud.entity.display_name.text**: An optional field used when a pretty name is desired for entity-centric operations.
- **cloud.entity.id**: Unique identifier for the entity.
- **cloud.entity.last_seen_timestamp**: Indicates the date/time when this entity was last "seen."
- **cloud.entity.lifecycle.last_activity**: Timestamp of the most recent action performed by or attributed to this entity.
- **cloud.entity.metrics**: Field set for any fields containing numeric entity metrics.
- **cloud.entity.name**: The name of the entity.
- **cloud.entity.name.text**: The name of the entity.
- **cloud.entity.raw**: Original, unmodified fields from the source system.
- **cloud.entity.reference**: A URI, URL, or other direct reference to access or locate the entity.
- **cloud.entity.relationships.administers.entity.idIdentifiers**: of referenced entities.
- **cloud.entity.relationships.administers.host.idReferenced**: host ids.
- **cloud.entity.relationships.administers.host.nameReferenced**: host names.
- **cloud.entity.relationships.administers.service.idReferenced**: service ids.
- **cloud.entity.relationships.administers.service.nameReferenced**: service names.
- **cloud.entity.relationships.administers.user.domainReferenced**: user directory or AD/LDAP domain names.
- **cloud.entity.relationships.administers.user.emailReferenced**: user email addresses.
- **cloud.entity.relationships.administers.user.idReferenced**: user ids.
- **cloud.entity.relationships.administers.user.nameReferenced**: user short names or logins.
- **cloud.entity.relationships.depends_on.entity.idIdentifiers**: of referenced entities.
- **cloud.entity.relationships.depends_on.host.idReferenced**: host ids.
- **cloud.entity.relationships.depends_on.host.nameReferenced**: host names.
- **cloud.entity.relationships.depends_on.service.idReferenced**: service ids.
- **cloud.entity.relationships.depends_on.service.nameReferenced**: service names.
- **cloud.entity.relationships.depends_on.user.domainReferenced**: user directory or AD/LDAP domain names.

- **cloud.entity.relationships.depends_on.user.emailReferenced**: user email addresses.
- **cloud.entity.relationships.depends_on.user.idReferenced**: user ids.
- **cloud.entity.relationships.depends_on.user.nameReferenced**: user short names or logins.
- **cloud.entity.relationships.owns.entity.id**: Identifiers of referenced entities.
- **cloud.entity.relationships.owns.host.id**: Referenced host ids.
- **cloud.entity.relationships.owns.host.name**: Referenced host names.
- **cloud.entity.relationships.owns.service.id**: Referenced service ids.
- **cloud.entity.relationships.owns.service.nameReferenced**: service names.
- **cloud.entity.relationships.owns.user.domain**: Referenced user directory or AD/LDAP domain names.
- **cloud.entity.relationships.owns.user.email**: Referenced user email addresses.
- **cloud.entity.relationships.owns.user.id**: Referenced user ids.
- **cloud.entity.relationships.owns.user.name**: Referenced user short names or logins.
- **cloud.entity.relationships.supervises.entity.idIdentifiers**: of referenced entities.
- **cloud.entity.relationships.supervises.host.id**: Referenced host ids.
- **cloud.entity.relationships.supervises.host.nameReferenced**: host names.
- **cloud.entity.relationships.supervises.service.idReferenced**: service ids.
- **cloud.entity.relationships.supervises.service.nameReferenced**: service names.
- **cloud.entity.relationships.supervises.user.domainReferenced**: user directory or AD/LDAP domain names.
- **cloud.entity.relationships.supervises.user.emailReferenced**: user email addresses.
- **cloud.entity.relationships.supervises.user.id**: Referenced user ids.
- **cloud.entity.relationships.supervises.user.nameReferenced**: user short names or logins.
- **cloud.entity.source**: Source module or integration that provided the entity data.
- **cloud.entity.sub_type**: The specific type designation for the entity as defined by its provider or system.
- **cloud.entity.type**: Standardized high-level classification of the entity.
- **cloud.instance.id**: Instance ID of the host machine.
- **cloud.instance.name**: Instance name of the host machine.
- **cloud.machine.type**: Machine type of the host machine.
- **cloud.origin.account.id**: The cloud account or organization id.
- **cloud.origin.account.name**: The cloud account name.
- **cloud.origin.availability_zone**: Availability zone in which this host, resource, or service is located.
- **cloud.origin.entity.attributes.known_redirectsKnown**: redirect URIs or URLs associated with this entity.
- **cloud.origin.entity.attributes.managed**: Indicates whether the entity is managed by an external system.
- **cloud.origin.entity.attributes.mfa_enabled**: Indicates whether multi-factor authentication is enabled for this entity.

- **cloud.origin.entity.attributes.oauth_consent_restrictionRestriction**: applied to OAuth consent for this entity.
- **cloud.origin.entity.attributes.permissions**: Action-level permissions associated with this entity.
- **cloud.origin.entity.attributes.storage_class**: Storage tier or class assigned to an object storage resource.
- **cloud.origin.entity.behavior**: A set of ephemeral characteristics of the entity, derived from observed behaviors during a specific time period.
- **cloud.origin.entity.display_name**: An optional field used when a pretty name is desired for entity-centric operations.
- **cloud.origin.entity.display_name.text**: An optional field used when a pretty name is desired for entity-centric operations.
- **cloud.origin.entity.id**: Unique identifier for the entity.
- **cloud.origin.entity.last_seen_timestamp**: Indicates the date/time when this entity was last "seen."
- **cloud.origin.entity.lifecycle.last_activity**: Timestamp of the most recent action performed by or attributed to this entity.
- **cloud.origin.entity.metrics**: Field set for any fields containing numeric entity metrics.
- **cloud.origin.entity.name**: The name of the entity.
- **cloud.origin.entity.name.text**: The name of the entity.
- **cloud.origin.entity.raw**: Original, unmodified fields from the source system.
- **cloud.origin.entity.reference**: A URI, URL, or other direct reference to access or locate the entity.
- **cloud.origin.entity.relationships.administers.entity.idIdentifiers**: of referenced entities.
- **cloud.origin.entity.relationships.administers.host.idReferenced**: host ids.
- **cloud.origin.entity.relationships.administers.host.nameReferenced**: host names.
- **cloud.origin.entity.relationships.administers.service.idReferenced**: service ids.
- **cloud.origin.entity.relationships.administers.service.nameReferenced**: service names.
- **cloud.origin.entity.relationships.administers.user.domainReferenced**: user directory or AD/LDAP domain names.
- **cloud.origin.entity.relationships.administers.user.emailReferenced**: user email addresses.
- **cloud.origin.entity.relationships.administers.user.idReferenced**: user ids.
- **cloud.origin.entity.relationships.administers.user.nameReferenced**: user short names or logins.
- **cloud.origin.entity.relationships.depends_on.entity.idIdentifiers**: of referenced entities.
- **cloud.origin.entity.relationships.depends_on.host.idReferenced**: host ids.
- **cloud.origin.entity.relationships.depends_on.host.nameReferenced**: host names.
- **cloud.origin.entity.relationships.depends_on.service.idReferenced**: service ids.

- **cloud.origin.entity.relationships.depends_on.service.nameReferenced**: service names.
- **cloud.origin.entity.relationships.depends_on.user.domainReferenced**: user directory or AD/LDAP domain names.
- **cloud.origin.entity.relationships.depends_on.user.emailReferenced**: user email addresses.
- **cloud.origin.entity.relationships.depends_on.user.idReferenced**: user ids.
- **cloud.origin.entity.relationships.depends_on.user.nameReferenced**: user short names or logins.
- **cloud.origin.entity.relationships.owns.entity.idIdentifiers**: of referenced entities.
- **cloud.origin.entity.relationships.owns.host.idReferenced**: host ids.
- **cloud.origin.entity.relationships.owns.host.nameReferenced**: host names.
- **cloud.origin.entity.relationships.owns.service.idReferenced**: service ids.
- **cloud.origin.entity.relationships.owns.service.nameReferenced**: service names.
- **cloud.origin.entity.relationships.owns.user.domainReferenced**: user directory or AD/LDAP domain names.
- **cloud.origin.entity.relationships.owns.user.emailReferenced**: user email addresses.
- **cloud.origin.entity.relationships.owns.user.idReferenced**: user ids.
- **cloud.origin.entity.relationships.owns.user.nameReferenced**: user short names or logins.
- **cloud.origin.entity.relationships.supervises.entity.idIdentifiers**: of referenced entities.
- **cloud.origin.entity.relationships.supervises.host.idReferenced**: host ids.
- **cloud.origin.entity.relationships.supervises.host.nameReferenced**: host names.
- **cloud.origin.entity.relationships.supervises.service.idReferenced**: service ids.
- **cloud.origin.entity.relationships.supervises.service.nameReferenced**: service names.
- **cloud.origin.entity.relationships.supervises.user.domainReferenced**: user directory or AD/LDAP domain names.
- **cloud.origin.entity.relationships.supervises.user.emailReferenced**: user email addresses.
- **cloud.origin.entity.relationships.supervises.user.idReferenced**: user ids.
- **cloud.origin.entity.relationships.supervises.user.nameReferenced**: user short names or logins.
- **cloud.origin.entity.source**: Source module or integration that provided the entity data.
- **cloud.origin.entity.sub_type**: The specific type designation for the entity as defined by its provider or system.
- **cloud.origin.entity.type**: Standardized high-level classification of the entity.
- **cloud.origin.instance.id**: Instance ID of the host machine.
- **cloud.origin.instance.name**: Instance name of the host machine.
- **cloud.origin.machine.type**: Machine type of the host machine.
- **cloud.origin.project.id**: The cloud project id.
- **cloud.origin.project.name**: The cloud project name.

- **cloud.origin.provider**: Name of the cloud provider.
- **cloud.origin.region**: Region in which this host, resource, or service is located.
- **cloud.origin.service.name**: The cloud service name.
- **cloud.project.id**: The cloud project id.
- **cloud.project.name**: The cloud project name.
- **cloud.provider**: Name of the cloud provider.
- **cloud.region**: Region in which this host, resource, or service is located.
- **cloud.service.name**: The cloud service name.
- **cloud.target.account.id**: The cloud account or organization id.
- **cloud.target.account.name**: The cloud account name.
- **cloud.target.availability_zone**: Availability zone in which this host, resource, or service is located.
- **cloud.target.entity.attributes.known_redirectsKnown**: redirect URIs or URLs associated with this entity.
- **cloud.target.entity.attributes.managed**: Indicates whether the entity is managed by an external system.
- **cloud.target.entity.attributes.mfa_enabled**: Indicates whether multi-factor authentication is enabled for this entity.
- **cloud.target.entity.attributes.oauth_consent_restrictionRestriction**: applied to OAuth consent for this entity.
- **cloud.target.entity.attributes.permissions**: Action-level permissions associated with this entity.
- **cloud.target.entity.attributes.storage_class**: Storage tier or class assigned to an object storage resource.
- **cloud.target.entity.behavior**: A set of ephemeral characteristics of the entity, derived from observed behaviors during a specific time period.
- **cloud.target.entity.display_name**: An optional field used when a pretty name is desired for entity-centric operations.
- **cloud.target.entity.display_name.text**: An optional field used when a pretty name is desired for entity-centric operations.
- **cloud.target.entity.id**: Unique identifier for the entity.
- **cloud.target.entity.last_seen_timestamp**: Indicates the date/time when this entity was last "seen."
- **cloud.target.entity.lifecycle.last_activity**: Timestamp of the most recent action performed by or attributed to this entity.
- **cloud.target.entity.metrics**: Field set for any fields containing numeric entity metrics.
- **cloud.target.entity.name**: The name of the entity.
- **cloud.target.entity.name.text**: The name of the entity.
- **cloud.target.entity.raw**: Original, unmodified fields from the source system.
- **cloud.target.entity.reference**: A URI, URL, or other direct reference to access or locate the entity.
- **cloud.target.entity.relationships.administers.entity.idIdentifiers**: of referenced entities.

- **cloud.target.entity.relationships.administers.host.idReferenced**: host ids.
- **cloud.target.entity.relationships.administers.host.nameReferenced**: host names.
- **cloud.target.entity.relationships.administers.service.idReferenced**: service ids.
- **cloud.target.entity.relationships.administers.service.nameReferenced**: service names.
- **cloud.target.entity.relationships.administers.user.domainReferenced**: user directory or AD/LDAP domain names.
- **cloud.target.entity.relationships.administers.user.emailReferenced**: user email addresses.
- **cloud.target.entity.relationships.administers.user.idReferenced**: user ids.
- **cloud.target.entity.relationships.administers.user.nameReferenced**: user short names or logins.
- **cloud.target.entity.relationships.depends_on.entity.idIdentifiers**: of referenced entities.
- **cloud.target.entity.relationships.depends_on.host.idReferenced**: host ids.
- **cloud.target.entity.relationships.depends_on.host.nameReferenced**: host names.
- **cloud.target.entity.relationships.depends_on.service.idReferenced**: service ids.
- **cloud.target.entity.relationships.depends_on.service.nameReferenced**: service names.
- **cloud.target.entity.relationships.depends_on.user.domainReferenced**: user directory or AD/LDAP domain names.
- **cloud.target.entity.relationships.depends_on.user.emailReferenced**: user email addresses.
- **cloud.target.entity.relationships.depends_on.user.idReferenced**: user ids.
- **cloud.target.entity.relationships.depends_on.user.nameReferenced**: user short names or logins.
- **cloud.target.entity.relationships.owns.entity.idIdentifiers**: of referenced entities.
- **cloud.target.entity.relationships.owns.host.idReferenced**: host ids.
- **cloud.target.entity.relationships.owns.host.nameReferenced**: host names.
- **cloud.target.entity.relationships.owns.service.idReferenced**: service ids.
- **cloud.target.entity.relationships.owns.service.nameReferenced**: service names.
- **cloud.target.entity.relationships.owns.user.domainReferenced**: user directory or AD/LDAP domain names.
- **cloud.target.entity.relationships.owns.user.emailReferenced**: user email addresses.
- **cloud.target.entity.relationships.owns.user.idReferenced**: user ids.
- **cloud.target.entity.relationships.owns.user.nameReferenced**: user short names or logins.
- **cloud.target.entity.relationships.supervises.entity.idIdentifiers**: of referenced entities.
- **cloud.target.entity.relationships.supervises.host.idReferenced**: host ids.
- **cloud.target.entity.relationships.supervises.host.nameReferenced**: host names.
- **cloud.target.entity.relationships.supervises.service.idReferenced**: service ids.

- **cloud.target.entity.relationships.supervises.service.nameReferenced**: service names.
- **cloud.target.entity.relationships.supervises.user.domainReferenced**: user directory or AD/LDAP domain names.
- **cloud.target.entity.relationships.supervises.user.emailReferenced**: user email addresses.
- **cloud.target.entity.relationships.supervises.user.idReferenced**: user ids.
- **cloud.target.entity.relationships.supervises.user.nameReferenced**: user short names or logins.
- **cloud.target.entity.source**: Source module or integration that provided the entity data.
- **cloud.target.entity.sub_type**: The specific type designation for the entity as defined by its provider or system.
- **cloud.target.entity.type**: Standardized high-level classification of the entity.
- **cloud.target.instance.id**: Instance ID of the host machine.
- **cloud.target.instance.name**: Instance name of the host machine.
- **cloud.target.machine.type**: Machine type of the host machine.
- **cloud.target.project.id**: The cloud project id.
- **cloud.target.project.name**: The cloud project name.
- **cloud.target.provider**: Name of the cloud provider.
- **cloud.target.region**: Region in which this host, resource, or service is located.
- **cloud.target.service.name**: The cloud service name.

container

- **container.cpu.usage**: Percent CPU used, between 0 and 1.
- **container.disk.read.bytes**: The number of bytes read by all disks.
- **container.disk.write.bytes**: The number of bytes written on all disks.
- **container.id**: Unique container id.
- **container.image.hash.all**: An array of digests of the image the container was built on.
- **container.image.name**: Name of the image the container was built on.
- **container.image.tag**: Container image tags.
- **container.labels**: Image labels.
- **container.memory.usage**: Percent memory used, between 0 and 1.
- **container.name**: Container name.
- **container.network.egress.bytes**: The number of bytes sent on all network interfaces.
- **container.network.ingress.bytes**: The number of bytes received on all network interfaces.
- **container.runtime**: Runtime managing this container.
- **container.security_context.privileged**: Indicates whether the container is running in privileged mode.

data_stream

- **data_stream.dataset:** The field can contain anything that makes sense to signify the source of the data.
- **data_stream.namespace:** A user defined namespace. Namespaces are useful to allow grouping of data.
- **data_stream.type:** An overarching type for the data stream.

destination

- **destination.address:** Destination network address.
- **destination.as.number:** Unique number allocated to the autonomous system.
- **destination.as.organization.name:** Organization name.
- **destination.as.organization.name.text:** Organization name.
- **destination.bytes:** Bytes sent from the destination to the source.
- **destination.domain:** The domain name of the destination.
- **destination.geo.city_name:** City name.
- **destination.geo.continent_code:** Continent code.
- **destination.geo.continent_name:** Name of the continent.
- **destination.geo.country_iso_code:** Country ISO code.
- **destination.geo.country_name:** Country name.
- **destination.geo.location:** Longitude and latitude.
- **destination.geo.name:** User-defined description of a location.
- **destination.geo.postal_code:** Postal code.
- **destination.geo.region_iso_code:** Region ISO code.
- **destination.geo.region_name:** Region name.
- **destination.geo.timezone:** Time zone.
- **destination.ip:** IP address of the destination.
- **destination.mac:** MAC address of the destination.
- **destination.nat.ip:** Destination NAT ip
- **destination.nat.port:** Destination NAT Port
- **destination.packets:** Packets sent from the destination to the source.
- **destination.port:** Port of the destination.
- **destination.registered_domain:** The highest registered destination domain, stripped of the subdomain.
- **destination.subdomain:** The subdomain of the domain.
- **destination.top_level_domain:** The effective top level domain (com, org, net, co.uk).
- **destination.user.domain:** Name of the directory the user is a member of.
- **destination.user.email:** User email address.
- **destination.user.full_name:** User's full name, if available.
- **destination.user.full_name.text:** User's full name, if available.
- **destination.user.group.domain:** Name of the directory the group is a member of.

- **destination.user.group.id**: Unique identifier for the group on the system/platform.
- **destination.user.group.name**: Name of the group.
- **destination.user.hash**: Unique user hash to correlate information for a user in anonymized form.
- **destination.user.id**: Unique identifier of the user.
- **destination.user.name**: Short name or login of the user.
- **destination.user.name.text**: Short name or login of the user.
- **destination.user.roles**: Array of user roles at the time of the event.

device

- **device.id**: The unique identifier of a device.
- **device.manufacturer**: The vendor name of the device manufacturer.
- **device.model.identifier**: The machine readable identifier of the device model.
- **device.model.name**: The human readable marketing name of the device model.
- **device.product.id**: ProductID of the device
- **device.product.name**: Product name of the device
- **device.serial_number**: Serial Number of the device
- **device.type**: Device type classification
- **device.vendor.id**: VendorID of the device
- **device.vendor.name**: Vendor name of the device

dll

- **dll.code_signature.digest_algorithm**: Hashing algorithm used to sign the process.
- **dll.code_signature.exists**: Boolean to capture if a signature is present.
- **dll.code_signature.flags**: Code signing flags of the process
- **dll.code_signature.signing_id**: The identifier used to sign the process.
- **dll.code_signature.status**: Additional information about the certificate status.
- **dll.code_signature.subject_name**: Subject name of the code signer
- **dll.code_signature.team_id**: The team identifier used to sign the process.
- **dll.code_signature.thumbprint_sha256**: SHA256 hash of the certificate.
- **dll.code_signature.timestamp**: When the signature was generated and signed.
- **dll.code_signature.trusted**: Stores the trust status of the certificate chain.
- **dll.code_signature.valid**: Boolean to capture if the digital signature is verified against the binary content.
- **dll.hash.cdhash**: The Code Directory (CD) hash of an executable.
- **dll.hash.md5**: MD5 hash.
- **dll.hash.sha1**: SHA1 hash.
- **dll.hash.sha256**: SHA256 hash.
- **dll.hash.sha384**: SHA384 hash.
- **dll.hash.sha512**: SHA512 hash.
- **dll.hash.ssdeep**: SSDEEP hash.

- **dll.hash.tlsh**: TLSH hash.
- **dll.name**: Name of the library.
- **dll.origin_referrer_url**: The URL of the webpage that linked to the dll file.
- **dll.origin_url**: The URL where the dll file is hosted.
- **dll.path**: Full file path of the library.
- **dll.pe.architecture**: CPU architecture target for the file.
- **dll.pe.company**: Internal company name of the file, provided at compile-time.
- **dll.pe.description**: Internal description of the file, provided at compile-time.
- **dll.pe.file_version**: Process name.
- **dll.pe.go_import_hash**: A hash of the Go language imports in a PE file.
- **dll.pe.go_imports**: List of imported Go language element names and types.
- **dll.pe.go_imports_names_entropy**: Shannon entropy calculation from the list of Go imports.
- **dll.pe.go_imports_names_var_entropy**: Variance for Shannon entropy calculation from the list of Go imports.
- **dll.pe.go_stripped**: Whether the file is a stripped or obfuscated Go executable.
- **dll.pe.imphash**: A hash of the imports in a PE file.
- **dll.pe.import_hash**: A hash of the imports in a PE file.
- **dll.pe.imports**: List of imported element names and types.
- **dll.pe.imports_names_entropy**: Shannon entropy calculation from the list of imported element names and types.
- **dll.pe.imports_names_var_entropy**: Variance for Shannon entropy calculation from the list of imported element names and types.
- **dll.pe.original_file_name**: Internal name of the file, provided at compile-time.
- **dll.pe.pehash**: A hash of the PE header and data from one or more PE sections.
- **dll.pe.product**: Internal product name of the file, provided at compile-time.
- **dll.pe.sections**: Section information of the PE file.
- **dll.pe.sections_entropy**: Shannon entropy calculation from the section.
- **dll.pe.sections.name**: PE Section List name.
- **dll.pe.sections.physical_size**: PE Section List physical size.
- **dll.pe.sections.var_entropy**: Variance for Shannon entropy calculation from the section.
- **dll.pe.sections.virtual_size**: PE Section List virtual size. This is always the same as **physical_size**.

dns

- **dns.answers**: Array of DNS answers.
- **dns.answers.class**: The class of DNS data contained in this resource record.
- **dns.answers.data**: The data describing the resource.
- **dns.answers.name**: The domain name to which this resource record pertains.
- **dns.answers.ttl**: The time interval in seconds that this resource record may be cached before it should be discarded.

- **dns.answers.type**: The type of data contained in this resource record.
- **dns.header_flags**: Array of DNS header flags.
- **dns.id**: The DNS packet identifier assigned by the program that generated the query. The identifier is copied to the response.
- **dns.op_code**: The DNS operation code that specifies the kind of query in the message.
- **dns.question.class**: The class of records being queried.
- **dns.question.name**: The name being queried.
- **dns.question.registered_domain**: The highest registered domain, stripped of the subdomain.
- **dns.question.subdomain**: The subdomain of the domain.
- **dns.question.top_level_domain**: The effective top level domain (com, org, net, co.uk).
- **dns.question.type**: The type of record being queried.
- **dns.resolved_ip**: Array containing all IPs seen in answers.data
- **dns.response_code**: The DNS response code.
- **dns.type**: The type of DNS event captured, query or answer.

ecs

- **ecs.version**: ECS version this event conforms to.

email

- **email.attachments**: List of objects describing the attachments.
- **email.attachments.file.extension**: Attachment file extension.
- **email.attachments.file.hash.cdhash**: The Code Directory (CD) hash of an executable.
- **email.attachments.file.hash.md5**: MD5 hash.
- **email.attachments.file.hash.sha1**: SHA1 hash.
- **email.attachments.file.hash.sha256**: SHA256 hash.
- **email.attachments.file.hash.sha384**: SHA384 hash.
- **email.attachments.file.hash.sha512**: SHA512 hash.
- **email.attachments.file.hash.ssdeep**: SSDEEP hash.
- **email.attachments.file.hash.tlsh**: TLSH hash.
- **email.attachments.file.mime_type**: MIME type of the attachment file.
- **email.attachments.file.name**: Name of the attachment file.
- **email.attachments.file.size**: Attachment file size.
- **email.bcc.address**: Email address of BCC recipient
- **email.cc.address**: Email address of CC recipient
- **email.content_type**: MIME type of the email message.
- **email.delivery_timestamp**: Date and time when message was delivered.
- **email.direction**: Direction of the message.
- **email.from.address**: The sender's email address.
- **email.local_id**: Unique identifier given by the source.
- **email.message_id**: Value from the Message-ID header.

- **email.origination_timestamp**: Date and time the email was composed.
- **email.reply_to.address**: Address replies should be delivered to.
- **email.sender.address**: Address of the message sender.
- **email.subject**: The subject of the email message.
- **email.subject.text**: The subject of the email message.
- **email.to.address**: Email address of recipient
- **email.x_mailer**: Application that drafted email.

entity

- **entity.attributes.known_redirects**: Known redirect URIs or URLs associated with this entity.
- **entity.attributes.managed**: Indicates whether the entity is managed by an external system.
- **entity.attributes.mfa_enabled**: Indicates whether multi-factor authentication is enabled for this entity.
- **entity.attributes.oauth_consent_restriction**: Restriction applied to OAuth consent for this entity.
- **entity.attributes.permissions**: Action-level permissions associated with this entity.
- **entity.attributes.storage_class**: Storage tier or class assigned to an object storage resource.
- **entity.behavior**: A set of ephemeral characteristics of the entity, derived from observed behaviors during a specific time period.
- **entity.display_name**: An optional field used when a pretty name is desired for entity-centric operations.
- **entity.display_name.text**: An optional field used when a pretty name is desired for entity-centric operations.
- **entity.id**: Unique identifier for the entity.
- **entity.last_seen_timestamp**: Indicates the date/time when this entity was last "seen."
- **entity.lifecycle.last_activity**: Timestamp of the most recent action performed by or attributed to this entity.
- **entity.metrics**: Field set for any fields containing numeric entity metrics.
- **entity.name**: The name of the entity.
- **entity.name.text**: The name of the entity.
- **entity.raw**: Original, unmodified fields from the source system.
- **entity.reference**: A URI, URL, or other direct reference to access or locate the entity.
- **entity.relationships.administers.entity.id**: Identifiers of referenced entities.
- **entity.relationships.administers.host.id**: Referenced host ids.
- **entity.relationships.administers.host.name**: Referenced host names.
- **entity.relationships.administers.service.id**: Referenced service ids.
- **entity.relationships.administers.service.nameReferenced**: service names.
- **entity.relationships.administers.user.domainReferenced**: user directory or AD/LDAP domain names.

- **entity.relationships.administers.user.email**: Referenced user email addresses.
- **entity.relationships.administers.user.id**: Referenced user ids.
- **entity.relationships.administers.user.name**: Referenced user short names or logins.
- **entity.relationships.depends_on.entity.id**: Identifiers of referenced entities.
- **entity.relationships.depends_on.host.id**: Referenced host ids.
- **entity.relationships.depends_on.host.name**: Referenced host names.
- **entity.relationships.depends_on.service.id**: Referenced service ids.
- **entity.relationships.depends_on.service.nameReferenced**: service names.
- **entity.relationships.depends_on.user.domainReferenced**: user directory or AD/LDAP domain names.
- **entity.relationships.depends_on.user.email**: Referenced user email addresses.
- **entity.relationships.depends_on.user.id**: Referenced user ids.
- **entity.relationships.depends_on.user.name**: Referenced user short names or logins.
- **entity.relationships.owns.entity.id**: Identifiers of referenced entities.
- **entity.relationships.owns.host.id**: Referenced host ids.
- **entity.relationships.owns.host.name**: Referenced host names.
- **entity.relationships.owns.service.id**: Referenced service ids.
- **entity.relationships.owns.service.name**: Referenced service names.
- **entity.relationships.owns.user.domain**: Referenced user directory or AD/LDAP domain names.
- **entity.relationships.owns.user.email**: Referenced user email addresses.
- **entity.relationships.owns.user.id**: Referenced user ids.
- **entity.relationships.owns.user.name**: Referenced user short names or logins.
- **entity.relationships.supervises.entity.id**: Identifiers of referenced entities.
- **entity.relationships.supervises.host.id**: Referenced host ids.
- **entity.relationships.supervises.host.name**: Referenced host names.
- **entity.relationships.supervises.service.id**: Referenced service ids.
- **entity.relationships.supervises.service.nameReferenced**: service names.
- **entity.relationships.supervises.user.domain**: Referenced user directory or AD/LDAP domain names.
- **entity.relationships.supervises.user.email**: Referenced user email addresses.
- **entity.relationships.supervises.user.id**: Referenced user ids.
- **entity.relationships.supervises.user.name**: Referenced user short names or logins.
- **entity.source**: Source module or integration that provided the entity data.
- **entity.sub_type**: The specific type designation for the entity as defined by its provider or system.
- **entity.target.attributes.known_redirects**: Known redirect URIs or URLs associated with this entity.
- **entity.target.attributes.managed**: Indicates whether the entity is managed by an external system.
- **entity.target.attributes.mfa_enabled**: Indicates whether multi-factor authentication is enabled for this entity.

- **entity.target.attributes.oauth_consent_restrictionRestriction**: applied to OAuth consent for this entity.
- **entity.target.attributes.permissions**: Action-level permissions associated with this entity.
- **entity.target.attributes.storage_class**: Storage tier or class assigned to an object storage resource.
- **entity.target.behavior**: A set of ephemeral characteristics of the entity, derived from observed behaviors during a specific time period.
- **entity.target.display_name**: An optional field used when a pretty name is desired for entity-centric operations.
- **entity.target.display_name.text**: An optional field used when a pretty name is desired for entity-centric operations.
- **entity.target.id**: Unique identifier for the entity.
- **entity.target.last_seen_timestamp**: Indicates the date/time when this entity was last "seen."
- **entity.target.lifecycle.last_activity**: Timestamp of the most recent action performed by or attributed to this entity.
- **entity.target.metrics**: Field set for any fields containing numeric entity metrics.
- **entity.target.name**: The name of the entity.
- **entity.target.name.text**: The name of the entity.
- **entity.target.raw**: Original, unmodified fields from the source system.
- **entity.target.reference**: A URI, URL, or other direct reference to access or locate the entity.
- **entity.target.relationships.administers.entity.idIdentifiers**: of referenced entities.
- **entity.target.relationships.administers.host.idReferenced**: host ids.
- **entity.target.relationships.administers.host.nameReferenced**: host names.
- **entity.target.relationships.administers.service.idReferenced**: service ids.
- **entity.target.relationships.administers.service.nameReferenced**: service names.
- **entity.target.relationships.administers.user.domainReferenced**: user directory or AD/LDAP domain names.
- **entity.target.relationships.administers.user.emailReferenced**: user email addresses.
- **entity.target.relationships.administers.user.idReferenced**: user ids.
- **entity.target.relationships.administers.user.nameReferenced**: user short names or logins.
- **entity.target.relationships.depends_on.entity.idIdentifiers**: of referenced entities.
- **entity.target.relationships.depends_on.host.idReferenced**: host ids.
- **entity.target.relationships.depends_on.host.nameReferenced**: host names.
- **entity.target.relationships.depends_on.service.idReferenced**: service ids.
- **entity.target.relationships.depends_on.service.nameReferenced**: service names.
- **entity.target.relationships.depends_on.user.domainReferenced**: user directory or AD/LDAP domain names.
- **entity.target.relationships.depends_on.user.emailReferenced**: user email addresses.
- **entity.target.relationships.depends_on.user.idReferenced**: user ids.

- **entity.target.relationships.depends_on.user.nameReferenced**: user short names or logins.
- **entity.target.relationships.owns.entity.id**: Identifiers of referenced entities.
- **entity.target.relationships.owns.host.id**: Referenced host ids.
- **entity.target.relationships.owns.host.name**: Referenced host names.
- **entity.target.relationships.owns.service.id**: Referenced service ids.
- **entity.target.relationships.owns.service.nameReferenced**: service names.
- **entity.target.relationships.owns.user.domainReferenced**: user directory or AD/LDAP domain names.
- **entity.target.relationships.owns.user.email**: Referenced user email addresses.
- **entity.target.relationships.owns.user.id**: Referenced user ids.
- **entity.target.relationships.owns.user.name**: Referenced user short names or logins.
- **entity.target.relationships.supervises.entity.idIdentifiers**: of referenced entities.
- **entity.target.relationships.supervises.host.id**: Referenced host ids.
- **entity.target.relationships.supervises.host.nameReferenced**: host names.
- **entity.target.relationships.supervises.service.idReferenced**: service ids.
- **entity.target.relationships.supervises.service.nameReferenced**: service names.
- **entity.target.relationships.supervises.user.domainReferenced**: user directory or AD/LDAP domain names.
- **entity.target.relationships.supervises.user.emailReferenced**: user email addresses.
- **entity.target.relationships.supervises.user.idReferenced**: user ids.
- **entity.target.relationships.supervises.user.nameReferenced**: user short names or logins.
- **entity.target.source**: Source module or integration that provided the entity data.
- **entity.target.sub_type**: The specific type designation for the entity as defined by its provider or system.
- **entity.target.type**: Standardized high-level classification of the entity.
- **entity.type**: Standardized high-level classification of the entity.

error

- **error.code**: Error code describing the error.
- **error.id**: Unique identifier for the error.
- **error.message**: Error message.
- **error.stack_trace**: The stack trace of this error in plain text.
- **error.stack_trace.text**: The stack trace of this error in plain text.
- **error.type**: The type of the error, for example the class name of the exception.

event

- **event.action**: The action captured by the event.
- **event.agent_id_status**: Validation status of the event's agent.id field.
- **event.category**: Event category. The second categorization field in the hierarchy.

- **event.code**: Identification code for this event.
- **event.created**: Time when the event was first read by an agent or by your pipeline.
- **event.dataset**: Name of the dataset.
- **event.duration**: Duration of the event in nanoseconds.
- **event.end**: **event.end** contains the date when the event ended or when the activity was last observed.
- **event.hash**: Hash (perhaps logstash fingerprint) of raw field to be able to demonstrate log integrity.
- **event.id**: Unique ID to describe the event.
- **event.ingested**: Timestamp when an event arrived in the central data store.
- **event.kind**: The kind of the event. The highest categorization field in the hierarchy.
- **event.module**: Name of the module this data is coming from.
- **event.original**: Raw text message of entire event.
- **event.outcome**: The outcome of the event. The lowest level categorization field in the hierarchy.
- **event.provider**: Source of the event.
- **event.reason**: Reason why this event happened, according to the source
- **event.reference**: Event reference URL
- **event.risk_score**: Risk score or priority of the event (e.g. security solutions). Use your system's original value here.
- **event.risk_score_norm**: Normalized risk score or priority of the event (0-100).
- **event.sequence**: Sequence number of the event.
- **event.severity**: Numeric severity of the event.
- **event.start**: **event.start** contains the date when the event started or when the activity was first observed.
- **event.timezone**: Event time zone.
- **event.type**: Event type. The third categorization field in the hierarchy.
- **event.url**: Event investigation URL

faas

- **faas.coldstart**: Boolean value indicating a cold start of a function.
- **faas.execution**: The execution ID of the current function execution.
- **faas.id**: The unique identifier of a serverless function.
- **faas.name**: The name of a serverless function.
- **faas.trigger.request_id**: The ID of the trigger request , message, event, etc.
- **faas.trigger.type**: The trigger for the function execution.
- **faas.version**: The version of a serverless function.

file

- **file.accessed**: Last time the file was accessed.
- **file.attributes**: Array of file attributes.

- **file.code_signature.digest_algorithm**: Hashing algorithm used to sign the process.
- **file.code_signature.exists**: Boolean to capture if a signature is present.
- **file.code_signature.flags**: Code signing flags of the process
- **file.code_signature.signing_id**: The identifier used to sign the process.
- **file.code_signature.status**: Additional information about the certificate status.
- **file.code_signature.subject_name**: Subject name of the code signer
- **file.code_signature.team_id**: The team identifier used to sign the process.
- **file.code_signature.thumbprint_sha256**: SHA256 hash of the certificate.
- **file.code_signature.timestamp**: When the signature was generated and signed.
- **file.code_signature.trusted**: Stores the trust status of the certificate chain.
- **file.code_signature.valid**: Boolean to capture if the digital signature is verified against the binary content.
- **file.created**: File creation time.
- **file.ctime**: Last time the file attributes or metadata changed.
- **file.device**: Device that is the source of the file.
- **file.directory**: Directory where the file is located.
- **file.drive_letter**: Drive letter where the file is located.
- **file.elf.architecture**: Machine architecture of the ELF file.
- **file.elf.byte_order**: Byte sequence of ELF file.
- **file.elf.cpu_type**: CPU type of the ELF file.
- **file.elf.creation_date**: Build or compile date.
- **file.elf.exports**: List of exported element names and types.
- **file.elf.go_import_hash**: A hash of the Go language imports in an ELF file.
- **file.elf.go_imports**: List of imported Go language element names and types.
- **file.elf.go_imports_names_entropy**: Shannon entropy calculation from the list of Go imports.
- **file.elf.go_imports_names_var_entropy**: Variance for Shannon entropy calculation from the list of Go imports.
- **file.elf.go_stripped**: Whether the file is a stripped or obfuscated Go executable.
- **file.elf.header.abi_version**: Version of the ELF Application Binary Interface (ABI).
- **file.elf.header.class**: Header class of the ELF file.
- **file.elf.header.data**: Data table of the ELF header.
- **file.elf.header.entrypoint**: Header entrypoint of the ELF file.
- **file.elf.header.object_version**: "0x1" for original ELF files.
- **file.elf.header.os_abi**: Application Binary Interface (ABI) of the Linux OS.
- **file.elf.header.type**: Header type of the ELF file.
- **file.elf.header.version**: Version of the ELF header.
- **file.elf.import_hash**: A hash of the imports in an ELF file.
- **file.elf.imports**: List of imported element names and types.
- **file.elf.imports_names_entropy**: Shannon entropy calculation from the list of imported element names and types.
- **file.elf.imports_names_var_entropy**: Variance for Shannon entropy calculation from the list of imported element names and types.

- **file.elf.sections**: Section information of the ELF file.
- **file.elf.sections.chi2**: Chi-square probability distribution of the section.
- **file.elf.sections.entropy**: Shannon entropy calculation from the section.
- **file.elf.sections.flags**: ELF Section List flags.
- **file.elf.sections.name**: ELF Section List name.
- **file.elf.sections.physical_offset**: ELF Section List offset.
- **file.elf.sections.physical_size**: ELF Section List physical size.
- **file.elf.sections.type**: ELF Section List type.
- **file.elf.sections.var_entropy**: Variance for Shannon entropy calculation from the section.
- **file.elf.sections.virtual_address**: ELF Section List virtual address.
- **file.elf.sections.virtual_size**: ELF Section List virtual size.
- **file.elf.segments**: ELF object segment list.
- **file.elf.segments.sections**: ELF object segment sections.
- **file.elf.segments.type**: ELF object segment type.
- **file.elf.shared_libraries**: List of shared libraries used by this ELF object.
- **file.elf.telfhash**: telfhash hash for ELF file.
- **file.extension**: File extension, excluding the leading dot.
- **file.fork_name**: A fork is additional data associated with a filesystem object.
- **file.gid**: Primary group ID (GID) of the file.
- **file.group**: Primary group name of the file.
- **file.hash.cdhash**: The Code Directory (CD) hash of an executable.
- **file.hash.md5**: MD5 hash.
- **file.hash.sha1**: SHA1 hash.
- **file.hash.sha256**: SHA256 hash.
- **file.hash.sha384**: SHA384 hash.
- **file.hash.sha512**: SHA512 hash.
- **file.hash.ssdeep**: SSDEEP hash.
- **file.hash.tlsh**: TLSH hash.
- **file.inode**: Inode representing the file in the filesystem.
- **file.macho.go_import_hash**: A hash of the Go language imports in a Mach-O file.
- **file.macho.go_imports**: List of imported Go language element names and types.
- **file.macho.go_imports_names_entropy**: Shannon entropy calculation from the list of Go imports.
- **file.macho.go_imports_names_var_entropy**: Variance for Shannon entropy calculation from the list of Go imports.
- **file.macho.go_stripped**: Whether the file is a stripped or obfuscated Go executable.
- **file.macho.import_hash**: A hash of the imports in a Mach-O file.
- **file.macho.imports**: List of imported element names and types.
- **file.macho.imports_names_entropy**: Shannon entropy calculation from the list of imported element names and types.
- **file.macho.imports_names_var_entropy**: Variance for Shannon entropy calculation from the list of imported element names and types.

- **file.macho.sections:** Section information of the Mach-O file.
- **file.macho.sections.entropy:** Shannon entropy calculation from the section.
- **file.macho.sections.name:** Mach-O Section List name.
- **file.macho.sections.physical_size:** Mach-O Section List physical size.
- **file.macho.sections.var_entropy:** Variance for Shannon entropy calculation from the section.
- **file.macho.sections.virtual_size:** Mach-O Section List virtual size. This is always the same as **physical_size**.
- **file.macho.symhash:** A hash of the imports in a Mach-O file.
- **file.mime_type:** Media type of file, document, or arrangement of bytes.
- **file.mode:** Mode of the file in octal representation.
- **file.mtime:** Last time the file content was modified.
- **file.name:** Name of the file including the extension, without the directory.
- **file.origin_referrer_url:** The URL of the webpage that linked to the file.
- **file.origin_url:** The URL where the file is hosted.
- **file.owner:** File owner's username.
- **file.path:** Full path to the file, including the file name.
- **file.path.text:** Full path to the file, including the file name.
- **file.pe.architecture:** CPU architecture target for the file.
- **file.pe.company:** Internal company name of the file, provided at compile-time.
- **file.pe.description:** Internal description of the file, provided at compile-time.
- **file.pe.file_version:** Process name.
- **file.pe.go_import_hash:** A hash of the Go language imports in a PE file.
- **file.pe.go_imports:** List of imported Go language element names and types.
- **file.pe.go_imports_names_entropy:** Shannon entropy calculation from the list of Go imports.
- **file.pe.go_imports_names_var_entropy:** Variance for Shannon entropy calculation from the list of Go imports.
- **file.pe.go_stripped:** Whether the file is a stripped or obfuscated Go executable.
- **file.pe.imphash:** A hash of the imports in a PE file.
- **file.pe.import_hash:** A hash of the imports in a PE file.
- **file.pe.imports:** List of imported element names and types.
- **file.pe.imports_names_entropy:** Shannon entropy calculation from the list of imported element names and types.
- **file.pe.imports_names_var_entropy:** Variance for Shannon entropy calculation from the list of imported element names and types.
- **file.pe.original_file_name:** Internal name of the file, provided at compile-time.
- **file.pe.pehash:** A hash of the PE header and data from one or more PE sections.
- **file.pe.product:** Internal product name of the file, provided at compile-time.
- **file.pe.sections:** Section information of the PE file.
- **file.pe.sections.entropy:** Shannon entropy calculation from the section.
- **file.pe.sections.name:** PE Section List name.
- **file.pe.sections.physical_size:** PE Section List physical size.

- **file.pe.sections.var_entropy**: Variance for Shannon entropy calculation from the section.
- **file.pe.sections.virtual_size**: PE Section List virtual size. This is always the same as **physical_size**.
- **file.size**: File size in bytes.
- **file.target_path**: Target path for symlinks.
- **file.target_path.text**: Target path for symlinks.
- **file.type**: File type (file, dir, or symlink).
- **file.uid**: The user ID (UID) or security identifier (SID) of the file owner.
- **file.x509.alternative_names**: List of subject alternative names (SAN).
- **file.x509.issuer.common_name**: List of common name (CN) of issuing certificate authority.
- **file.x509.issuer.country**: List of country (C) codes
- **file.x509.issuer.distinguished_name**: Distinguished name (DN) of issuing certificate authority.
- **file.x509.issuer.locality**: List of locality names (L)
- **file.x509.issuer.organization**: List of organizations (O) of issuing certificate authority.
- **file.x509.issuer.organizational_unit**: List of organizational units (OU) of issuing certificate authority.
- **file.x509.issuer.state_or_province**: List of state or province names (ST, S, or P)
- **file.x509.not_after**: Time at which the certificate is no longer considered valid.
- **file.x509.not_before**: Time at which the certificate is first considered valid.
- **file.x509.public_key_algorithm**: Algorithm used to generate the public key.
- **file.x509.public_key_curve**: The curve used by the elliptic curve public key algorithm. This is algorithm specific.
- **file.x509.public_key_exponent**: Exponent used to derive the public key. This is algorithm specific.
- **file.x509.public_key_size**: The size of the public key space in bits.
- **file.x509.serial_number**: Unique serial number issued by the certificate authority.
- **file.x509.signature_algorithm**: Identifier for certificate signature algorithm.
- **file.x509.subject.common_name**: List of common names (CN) of subject.
- **file.x509.subject.country**: List of country (C) code
- **file.x509.subject.distinguished_name**: Distinguished name (DN) of the certificate subject entity.
- **file.x509.subject.locality**: List of locality names (L)
- **file.x509.subject.organization**: List of organizations (O) of subject.
- **file.x509.subject.organizational_unit**: List of organizational units (OU) of subject.
- **file.x509.subject.state_or_province**: List of state or province names (ST, S, or P)
- **file.x509.version_number**: Version of x509 format.

gen_ai

- **gen_ai.agent.description**: Free-form description of the GenAI agent provided by the application.
- **gen_ai.agent.id**: The unique identifier of the GenAI agent.
- **gen_ai.agent.name**: Human-readable name of the GenAI agent provided by the application.
- **gen_ai.input.messages**: The chat history provided to the model as an input.
- **gen_ai.operation.name**: The name of the operation being performed.
- **gen_ai.output.messages**: Messages returned by the model where each message represents a specific model response (choice, candidate).
- **gen_ai.output.type**: Represents the content type requested by the client.
- **gen_ai.provider.name**: The Generative AI provider as identified by the client or server instrumentation.
- **gen_ai.request.choice.count**: The target number of candidate completions to return.
- **gen_ai.request.encoding_formats**: The encoding formats requested in an embeddings operation, if specified.
- **gen_ai.request.frequency_penalty**: The frequency penalty setting for the GenAI request.
- **gen_ai.request.max_tokens**: The maximum number of tokens the model generates for a request.
- **gen_ai.request.model**: The name of the GenAI model a request is being made to.
- **gen_ai.request.presence_penalty**: The presence penalty setting for the GenAI request.
- **gen_ai.request.seed**: Requests with same seed value more likely to return same result.
- **gen_ai.request.stop_sequences**: List of sequences that the model will use to stop generating further tokens.
- **gen_ai.request.temperature**: The temperature setting for the GenAI request.
- **gen_ai.request.top_k**: The top_k sampling setting for the GenAI request.
- **gen_ai.request.top_p**: The top_p sampling setting for the GenAI request.
- **gen_ai.response.finish_reasons**: Array of reasons the model stopped generating tokens, corresponding to each generation received.
- **gen_ai.response.id**: The unique identifier for the completion.
- **gen_ai.response.model**: The name of the model that generated the response.
- **gen_ai.system_instructions**: The system message or instructions provided to the GenAI model separately from the chat history.
- **gen_ai.token.type**: The type of token being counted.
- **gen_ai.tool.call.arguments**: Parameters passed to the tool call.
- **gen_ai.tool.call.id**: The tool call identifier.
- **gen_ai.tool.call.result**: The result returned by the tool call (if any and if execution was successful).
- **gen_ai.tooldefinitions**: The list of source system tool definitions available to the GenAI agent or model.

- **gen_ai.tool.name**: Name of the tool utilized by the agent.
- **gen_ai.tool.type**: Type of the tool utilized by the agent
- **gen_ai.usage.input_tokens**: The number of tokens used in the GenAI input (prompt).
- **gen_ai.usage.output_tokens**: The number of tokens used in the GenAI response (completion).

group

- **group.domain**: Name of the directory the group is a member of.
- **group.id**: Unique identifier for the group on the system/platform.
- **group.name**: Name of the group.

host

- **host.architecture**: Operating system architecture.
- **host.boot.id**: Linux boot uuid taken from /proc/sys/kernel/random/boot_id
- **host.cpu.usage**: Percent CPU used, between 0 and 1.
- **host.disk.read.bytes**: The number of bytes read by all disks.
- **host.disk.write.bytes**: The number of bytes written on all disks.
- **host.domain**: Name of the directory the group is a member of.
- **host.entity.attributes.known_redirects**: Known redirect URIs or URLs associated with this entity.
- **host.entity.attributes.managed**: Indicates whether the entity is managed by an external system.
- **host.entity.attributes.mfa_enabled**: Indicates whether multi-factor authentication is enabled for this entity.
- **host.entity.attributes.oauth_consent_restrictionRestriction**: applied to OAuth consent for this entity.
- **host.entity.attributes.permissions**: Action-level permissions associated with this entity.
- **host.entity.attributes.storage_class**: Storage tier or class assigned to an object storage resource.
- **host.entity.behavior**: A set of ephemeral characteristics of the entity, derived from observed behaviors during a specific time period.
- **host.entity.display_name**: An optional field used when a pretty name is desired for entity-centric operations.
- **host.entity.display_name.text**: An optional field used when a pretty name is desired for entity-centric operations.
- **host.entity.id**: Unique identifier for the entity.
- **host.entity.last_seen_timestamp**: Indicates the date/time when this entity was last "seen."
- **host.entity.lifecycle.last_activity**: Timestamp of the most recent action performed by or attributed to this entity.
- **host.entity.metrics**: Field set for any fields containing numeric entity metrics.

- **host.entity.name**: The name of the entity.
- **host.entity.name.text**: The name of the entity.
- **host.entity.raw**: Original, unmodified fields from the source system.
- **host.entity.reference**: A URI, URL, or other direct reference to access or locate the entity.
- **host.entity.relationships.administers.entity.idIdentifiers**: of referenced entities.
- **host.entity.relationships.administers.host.id**: Referenced host ids.
- **host.entity.relationships.administers.host.nameReferenced**: host names.
- **host.entity.relationships.administers.service.idReferenced**: service ids.
- **host.entity.relationships.administers.service.nameReferenced**: service names.
- **host.entity.relationships.administers.user.domainReferenced**: user directory or AD/LDAP domain names.
- **host.entity.relationships.administers.user.emailReferenced**: user email addresses.
- **host.entity.relationships.administers.user.id**: Referenced user ids.
- **host.entity.relationships.administers.user.nameReferenced**: user short names or logins.
- **host.entity.relationships.depends_on.entity.idIdentifiers**: of referenced entities.
- **host.entity.relationships.depends_on.host.idReferenced**: host ids.
- **host.entity.relationships.depends_on.host.nameReferenced**: host names.
- **host.entity.relationships.depends_on.service.idReferenced**: service ids.
- **host.entity.relationships.depends_on.service.nameReferenced**: service names.
- **host.entity.relationships.depends_on.user.domainReferenced**: user directory or AD/LDAP domain names.
- **host.entity.relationships.depends_on.user.emailReferenced**: user email addresses.
- **host.entity.relationships.depends_on.user.idReferenced**: user ids.
- **host.entity.relationships.depends_on.user.nameReferenced**: user short names or logins.
- **host.entity.relationships.owns.entity.id**: Identifiers of referenced entities.
- **host.entity.relationships.owns.host.id**: Referenced host ids.
- **host.entity.relationships.owns.host.name**: Referenced host names.
- **host.entity.relationships.owns.service.id**: Referenced service ids.
- **host.entity.relationships.owns.service.name**: Referenced service names.
- **host.entity.relationships.owns.user.domain**: Referenced user directory or AD/LDAP domain names.
- **host.entity.relationships.owns.user.email**: Referenced user email addresses.
- **host.entity.relationships.owns.user.id**: Referenced user ids.
- **host.entity.relationships.owns.user.name**: Referenced user short names or logins.
- **host.entity.relationships.supervises.entity.id**: Identifiers of referenced entities.
- **host.entity.relationships.supervises.host.id**: Referenced host ids.
- **host.entity.relationships.supervises.host.nameReferenced**: host names.
- **host.entity.relationships.supervises.service.idReferenced**: service ids.
- **host.entity.relationships.supervises.service.nameReferenced**: service names.

- **host.entity.relationships.supervises.user.domainReferenced**: user directory or AD/LDAP domain names.
- **host.entity.relationships.supervises.user.emailReferenced**: user email addresses.
- **host.entity.relationships.supervises.user.id**: Referenced user ids.
- **host.entity.relationships.supervises.user.nameReferenced**: user short names or logins.
- **host.entity.source**: Source module or integration that provided the entity data.
- **host.entity.sub_type**: The specific type designation for the entity as defined by its provider or system.
- **host.entity.type**: Standardized high-level classification of the entity.
- **host.geo.city_name**: City name.
- **host.geo.continent_code**: Continent code.
- **host.geo.continent_name**: Name of the continent.
- **host.geo.country_iso_code**: Country ISO code.
- **host.geo.country_name**: Country name.
- **host.geo.location**: Longitude and latitude.
- **host.geo.name**: User-defined description of a location.
- **host.geo.postal_code**: Postal code.
- **host.geo.region_iso_code**: Region ISO code.
- **host.geo.region_name**: Region name.
- **host.geo.timezone**: Time zone.
- **host.hostname**: Hostname of the host.
- **host.id**: Unique host id.
- **host.ip**: Host ip addresses.
- **host.mac**: Host MAC addresses.
- **host.name**: Name of the host.
- **host.network.egress.bytes**: The number of bytes sent on all network interfaces.
- **host.network.egress.packets**: The number of packets sent on all network interfaces.
- **host.network.ingress.bytes**: The number of bytes received on all network interfaces.
- **host.network.ingress.packets**: The number of packets received on all network interfaces.
- **host.os.family**: OS family (such as redhat, debian, freebsd, windows).
- **host.os.full**: Operating system name, including the version or code name.
- **host.os.full.text**: Operating system name, including the version or code name.
- **host.os.kernel**: Operating system kernel version as a raw string.
- **host.os.name**: Operating system name, without the version.
- **host.os.name.text**: Operating system name, without the version.
- **host.os.platform**: Operating system platform (such centos, ubuntu, windows).
- **host.os.type**: Which commercial OS family (one of: linux, macos, unix, windows, ios or android).
- **host.os.version**: Operating system version as a raw string.
- **host.pid_ns_ino**: Pid namespace inode

- **host.risk.calculated_level**: A risk classification level calculated by an internal system as part of entity analytics and entity risk scoring.
- **host.risk.calculated_score**: A risk classification score calculated by an internal system as part of entity analytics and entity risk scoring.
- **host.risk.calculated_score_norm**: A normalized risk score calculated by an internal system.
- **host.risk.static_level**: A risk classification level obtained from outside the system, such as from some external Threat Intelligence Platform.
- **host.risk.static_score**: A risk classification score obtained from outside the system, such as from some external Threat Intelligence Platform.
- **host.risk.static_score_norm**: A normalized risk score calculated by an external system.
- **host.target.architecture**: Operating system architecture.
- **host.target.boot.id**: Linux boot uuid taken from /proc/sys/kernel/random/boot_id
- **host.target.cpu.usage**: Percent CPU used, between 0 and 1.
- **host.target.disk.read.bytes**: The number of bytes read by all disks.
- **host.target.disk.write.bytes**: The number of bytes written on all disks.
- **host.target.domain**: Name of the directory the group is a member of.
- **host.target.entity.attributes.known_redirects**: Known redirect URIs or URLs associated with this entity.
- **host.target.entity.attributes.managed**: Indicates whether the entity is managed by an external system.
- **host.target.entity.attributes.mfa_enabled**: Indicates whether multi-factor authentication is enabled for this entity.
- **host.target.entity.attributes.oauth_consent_restrictionRestriction**: applied to OAuth consent for this entity.
- **host.target.entity.attributes.permissions**: Action-level permissions associated with this entity.
- **host.target.entity.attributes.storage_class**: Storage tier or class assigned to an object storage resource.
- **host.target.entity.behavior**: A set of ephemeral characteristics of the entity, derived from observed behaviors during a specific time period.
- **host.target.entity.display_name**: An optional field used when a pretty name is desired for entity-centric operations.
- **host.target.entity.display_name.text**: An optional field used when a pretty name is desired for entity-centric operations.
- **host.target.entity.id**: Unique identifier for the entity.
- **host.target.entity.last_seen_timestamp**: Indicates the date/time when this entity was last "seen."
- **host.target.entity.lifecycle.last_activity**: Timestamp of the most recent action performed by or attributed to this entity.
- **host.target.entity.metrics**: Field set for any fields containing numeric entity metrics.
- **host.target.entity.name**: The name of the entity.

- **host.target.entity.name.text**: The name of the entity.
- **host.target.entity.raw**: Original, unmodified fields from the source system.
- **host.target.entity.reference**: A URI, URL, or other direct reference to access or locate the entity.
- **host.target.entity.relationships.administers.entity.idIdentifiers**: of referenced entities.
- **host.target.entity.relationships.administers.host.idReferenced**: host ids.
- **host.target.entity.relationships.administers.host.nameReferenced**: host names.
- **host.target.entity.relationships.administers.service.idReferenced**: service ids.
- **host.target.entity.relationships.administers.service.nameReferenced**: service names.
- **host.target.entity.relationships.administers.user.domainReferenced**: user directory or AD/LDAP domain names.
- **host.target.entity.relationships.administers.user.emailReferenced**: user email addresses.
- **host.target.entity.relationships.administers.user.idReferenced**: user ids.
- **host.target.entity.relationships.administers.user.nameReferenced**: user short names or logins.
- **host.target.entity.relationships.depends_on.entity.idIdentifiers**: of referenced entities.
- **host.target.entity.relationships.depends_on.host.idReferenced**: host ids.
- **host.target.entity.relationships.depends_on.host.nameReferenced**: host names.
- **host.target.entity.relationships.depends_on.service.idReferenced**: service ids.
- **host.target.entity.relationships.depends_on.service.nameReferenced**: service names.
- **host.target.entity.relationships.depends_on.user.domainReferenced**: user directory or AD/LDAP domain names.
- **host.target.entity.relationships.depends_on.user.emailReferenced**: user email addresses.
- **host.target.entity.relationships.depends_on.user.idReferenced**: user ids.
- **host.target.entity.relationships.depends_on.user.nameReferenced**: user short names or logins.
- **host.target.entity.relationships.owns.entity.idIdentifiers**: of referenced entities.
- **host.target.entity.relationships.owns.host.id**: Referenced host ids.
- **host.target.entity.relationships.owns.host.nameReferenced**: host names.
- **host.target.entity.relationships.owns.service.idReferenced**: service ids.
- **host.target.entity.relationships.owns.service.nameReferenced**: service names.
- **host.target.entity.relationships.owns.user.domainReferenced**: user directory or AD/LDAP domain names.
- **host.target.entity.relationships.owns.user.emailReferenced**: user email addresses.
- **host.target.entity.relationships.owns.user.id**: Referenced user ids.
- **host.target.entity.relationships.owns.user.nameReferenced**: user short names or logins.

- **host.target.entity.relationships.supervises.entity.idIdentifiers**: of referenced entities.
- **host.target.entity.relationships.supervises.host.idReferenced**: host ids.
- **host.target.entity.relationships.supervises.host.nameReferenced**: host names.
- **host.target.entity.relationships.supervises.service.idReferenced**: service ids.
- **host.target.entity.relationships.supervises.service.nameReferenced**: service names.
- **host.target.entity.relationships.supervises.user.domainReferenced**: user directory or AD/LDAP domain names.
- **host.target.entity.relationships.supervises.user.emailReferenced**: user email addresses.
- **host.target.entity.relationships.supervises.user.idReferenced**: user ids.
- **host.target.entity.relationships.supervises.user.nameReferenced**: user short names or logins.
- **host.target.entity.source**: Source module or integration that provided the entity data.
- **host.target.entity.sub_type**: The specific type designation for the entity as defined by its provider or system.
- **host.target.entity.type**: Standardized high-level classification of the entity.
- **host.target.geo.city_name**: City name.
- **host.target.geo.continent_code**: Continent code.
- **host.target.geo.continent_name**: Name of the continent.
- **host.target.geo.country_iso_code**: Country ISO code.
- **host.target.geo.country_name**: Country name.
- **host.target.geo.location**: Longitude and latitude.
- **host.target.geo.name**: User-defined description of a location.
- **host.target.geo.postal_code**: Postal code.
- **host.target.geo.region_iso_code**: Region ISO code.
- **host.target.geo.region_name**: Region name.
- **host.target.geo.timezone**: Time zone.
- **host.target.hostname**: Hostname of the host.
- **host.target.id**: Unique host id.
- **host.target.ip**: Host ip addresses.
- **host.target.mac**: Host MAC addresses.
- **host.target.name**: Name of the host.
- **host.target.network.egress.bytes**: The number of bytes sent on all network interfaces.
- **host.target.network.egress.packets**: The number of packets sent on all network interfaces.
- **host.target.network.ingress.bytes**: The number of bytes received on all network interfaces.
- **host.target.network.ingress.packets**: The number of packets received on all network interfaces.
- **host.target.os.family**: OS family (such as redhat, debian, freebsd, windows).
- **host.target.os.full**: Operating system name, including the version or code name.
- **host.target.os.full.text**: Operating system name, including the version or code name.

- **host.target.os.kernel**: Operating system kernel version as a raw string.
- **host.target.os.name**: Operating system name, without the version.
- **host.target.os.name.text**: Operating system name, without the version.
- **host.target.os.platform**: Operating system platform (such centos, ubuntu, windows).
- **host.target.os.type**: Which commercial OS family (one of: linux, macos, unix, windows, ios or android).
- **host.target.os.version**: Operating system version as a raw string.
- **host.target.pid_ns_ino**: Pid namespace inode
- **host.target.risk.calculated_level**: A risk classification level calculated by an internal system as part of entity analytics and entity risk scoring.
- **host.target.risk.calculated_score**: A risk classification score calculated by an internal system as part of entity analytics and entity risk scoring.
- **host.target.risk.calculated_score_norm**: A normalized risk score calculated by an internal system.
- **host.target.risk.static_level**: A risk classification level obtained from outside the system, such as from some external Threat Intelligence Platform.
- **host.target.risk.static_score**: A risk classification score obtained from outside the system, such as from some external Threat Intelligence Platform.
- **host.target.risk.static_score_norm**: A normalized risk score calculated by an external system.
- **host.target.type**: Type of host.
- **host.target.uptime**: Seconds the host has been up.
- **host.type**: Type of host.
- **host.uptime**: Seconds the host has been up.

http

- **http.request.body.bytes**: Size in bytes of the request body.
- **http.request.body.content**: The full HTTP request body.
- **http.request.body.content.text**: The full HTTP request body.
- **http.request.bytes**: Total size in bytes of the request (body and headers).
- **http.request.id**: HTTP request ID.
- **http.request.method**: HTTP request method.
- **http.request.mime_type**: Mime type of the body of the request.
- **http.request.referrer**: Referrer for this HTTP request.
- **http.response.body.bytes**: Size in bytes of the response body.
- **http.response.body.content**: The full HTTP response body.
- **http.response.body.content.text**: The full HTTP response body.
- **http.response.bytes**: Total size in bytes of the response (body and headers).
- **http.response.mime_type**: Mime type of the body of the response.
- **http.response.status_code**: HTTP response status code.
- **http.version**: HTTP version.

log

- **log.file.path**: Full path to the log file this event came from.
- **log.level**: Log level of the log event.
- **log.logger**: Name of the logger.
- **log.origin.file.line**: The line number of the file which originated the log event.
- **log.origin.file.name**: The code file which originated the log event.
- **log.origin.function**: The function which originated the log event.
- **log.syslog**: Syslog metadata
- **log.syslog.appname**: The device or application that originated the Syslog message.
- **log.syslog.facility.code**: Syslog numeric facility of the event.
- **log.syslog.facility.name**: Syslog text-based facility of the event.
- **log.syslog.hostname**: The host that originated the Syslog message.
- **log.syslog.msgid**: An identifier for the type of Syslog message.
- **log.syslog.priority**: Syslog priority of the event.
- **log.syslog.procid**: The process name or ID that originated the Syslog message.
- **log.syslog.severity.code**: Syslog numeric severity of the event.
- **log.syslog.severity.name**: Syslog text-based severity of the event.
- **log.syslog.structured_data**: Structured data expressed in RFC 5424 messages.
- **log.syslog.version**: Syslog protocol version.

network

- **network.application**: Application level protocol name.
- **network.bytes**: Total bytes transferred in both directions.
- **network.community_id**: A hash of source and destination IPs and ports.
- **network.direction**: Direction of the network traffic.
- **network.forwarded_ip**: Host IP address when the source IP address is the proxy.
- **network.iana_number**: IANA Protocol Number.
- **network.inner**: Inner VLAN tag information
- **network.inner.vlan.id**: VLAN ID as reported by the observer.
- **network.inner.vlan.name**: Optional VLAN name as reported by the observer.
- **network.name**: Name given by operators to sections of their network.
- **network.packets**: Total packets transferred in both directions.
- **network.protocol**: Application protocol name.
- **network.transport**: Protocol Name corresponding to the field **iana_number**.
- **network.type**: In the OSI Model this would be the Network Layer. ipv4, ipv6, ipsec, pim, etc
- **network.vlan.id**: VLAN ID as reported by the observer.
- **network.vlan.name**: Optional VLAN name as reported by the observer.

observer

- **observer.egress**: Object field for egress information
- **observer.egress.interface.alias**: Interface alias
- **observer.egress.interface.id**: Interface ID
- **observer.egress.interface.name**: Interface name
- **observer.egress.vlan.id**: VLAN ID as reported by the observer.
- **observer.egress.vlan.name**: Optional VLAN name as reported by the observer.
- **observer.egress.zone**: Observer Egress zone
- **observer.geo.city_name**: City name.
- **observer.geo.continent_code**: Continent code.
- **observer.geo.continent_name**: Name of the continent.
- **observer.geo.country_iso_code**: Country ISO code.
- **observer.geo.country_name**: Country name.
- **observer.geo.location**: Longitude and latitude.
- **observer.geo.name**: User-defined description of a location.
- **observer.geo.postal_code**: Postal code.
- **observer.geo.region_iso_code**: Region ISO code.
- **observer.geo.region_name**: Region name.
- **observer.geo.timezone**: Time zone.
- **observer.hostname**: Hostname of the observer.
- **observer.ingress**: Object field for ingress information
- **observer.ingress.interface.alias**: Interface alias
- **observer.ingress.interface.id**: Interface ID
- **observer.ingress.interface.name**: Interface name
- **observer.ingress.vlan.id**: VLAN ID as reported by the observer.
- **observer.ingress.vlan.name**: Optional VLAN name as reported by the observer.
- **observer.ingress.zone**: Observer ingress zone
- **observer.ip**: IP addresses of the observer.
- **observer.mac**: MAC addresses of the observer.
- **observer.name**: Custom name of the observer.
- **observer.os.family**: OS family (such as redhat, debian, freebsd, windows).
- **observer.os.full**: Operating system name, including the version or code name.
- **observer.os.full.text**: Operating system name, including the version or code name.
- **observer.os.kernel**: Operating system kernel version as a raw string.
- **observer.os.name**: Operating system name, without the version.
- **observer.os.name.text**: Operating system name, without the version.
- **observer.os.platform**: Operating system platform (such centos, ubuntu, windows).
- **observer.os.type**: Which commercial OS family (one of: linux, macos, unix, windows, ios or android).
- **observer.os.version**: Operating system version as a raw string.
- **observer.product**: The product name of the observer.

- **observer.serial_number**: Observer serial number.
- **observer.type**: The type of the observer the data is coming from.
- **observer.vendor**: Vendor name of the observer.
- **observer.version**: Observer version.

orchestrator

- **orchestrator.api_version**: API version being used to carry out the action
- **orchestrator.cluster.id**: Unique ID of the cluster.
- **orchestrator.cluster.name**: Name of the cluster.
- **orchestrator.cluster.url**: URL of the API used to manage the cluster.
- **orchestrator.cluster.version**: The version of the cluster.
- **orchestrator.entity.attributes.known_redirectsKnown**: redirect URIs or URLs associated with this entity.
- **orchestrator.entity.attributes.managed**: Indicates whether the entity is managed by an external system.
- **orchestrator.entity.attributes.mfa_enabled**: Indicates whether multi-factor authentication is enabled for this entity.
- **orchestrator.entity.attributes.oauth_consent_restrictionRestriction**: applied to OAuth consent for this entity.
- **orchestrator.entity.attributes.permissions**: Action-level permissions associated with this entity.
- **orchestrator.entity.attributes.storage_class**: Storage tier or class assigned to an object storage resource.
- **orchestrator.entity.behavior**: A set of ephemeral characteristics of the entity, derived from observed behaviors during a specific time period.
- **orchestrator.entity.display_name**: An optional field used when a pretty name is desired for entity-centric operations.
- **orchestrator.entity.display_name.text**: An optional field used when a pretty name is desired for entity-centric operations.
- **orchestrator.entity.id**: Unique identifier for the entity.
- **orchestrator.entity.last_seen_timestamp**: Indicates the date/time when this entity was last "seen."
- **orchestrator.entity.lifecycle.last_activity**: Timestamp of the most recent action performed by or attributed to this entity.
- **orchestrator.entity.metrics**: Field set for any fields containing numeric entity metrics.
- **orchestrator.entity.name**: The name of the entity.
- **orchestrator.entity.name.text**: The name of the entity.
- **orchestrator.entity.raw**: Original, unmodified fields from the source system.
- **orchestrator.entity.reference**: A URI, URL, or other direct reference to access or locate the entity.
- **orchestrator.entity.relationships.administers.entity.idIdentifiers**: of referenced entities.

- **orchestrator.entity.relationships.administers.host.idReferenced**: host ids.
- **orchestrator.entity.relationships.administers.host.nameReferenced**: host names.
- **orchestrator.entity.relationships.administers.service.idReferenced**: service ids.
- **orchestrator.entity.relationships.administers.service.nameReferenced**: service names.
- **orchestrator.entity.relationships.administers.user.domainReferenced**: user directory or AD/LDAP domain names.
- **orchestrator.entity.relationships.administers.user.emailReferenced**: user email addresses.
- **orchestrator.entity.relationships.administers.user.idReferenced**: user ids.
- **orchestrator.entity.relationships.administers.user.nameReferenced**: user short names or logins.
- **orchestrator.entity.relationships.depends_on.entity.idIdentifiers**: of referenced entities.
- **orchestrator.entity.relationships.depends_on.host.idReferenced**: host ids.
- **orchestrator.entity.relationships.depends_on.host.nameReferenced**: host names.
- **orchestrator.entity.relationships.depends_on.service.idReferenced**: service ids.
- **orchestrator.entity.relationships.depends_on.service.nameReferenced**: service names.
- **orchestrator.entity.relationships.depends_on.user.domainReferenced**: user directory or AD/LDAP domain names.
- **orchestrator.entity.relationships.depends_on.user.emailReferenced**: user email addresses.
- **orchestrator.entity.relationships.depends_on.user.idReferenced**: user ids.
- **orchestrator.entity.relationships.depends_on.user.nameReferenced**: user short names or logins.
- **orchestrator.entity.relationships.owns.entity.idIdentifiers**: of referenced entities.
- **orchestrator.entity.relationships.owns.host.idReferenced**: host ids.
- **orchestrator.entity.relationships.owns.host.nameReferenced**: host names.
- **orchestrator.entity.relationships.owns.service.idReferenced**: service ids.
- **orchestrator.entity.relationships.owns.service.nameReferenced**: service names.
- **orchestrator.entity.relationships.owns.user.domainReferenced**: user directory or AD/LDAP domain names.
- **orchestrator.entity.relationships.owns.user.emailReferenced**: user email addresses.
- **orchestrator.entity.relationships.owns.user.idReferenced**: user ids.
- **orchestrator.entity.relationships.owns.user.nameReferenced**: user short names or logins.
- **orchestrator.entity.relationships.supervises.entity.idIdentifiers**: of referenced entities.
- **orchestrator.entity.relationships.supervises.host.idReferenced**: host ids.
- **orchestrator.entity.relationships.supervises.host.nameReferenced**: host names.
- **orchestrator.entity.relationships.supervises.service.idReferenced**: service ids.

- **orchestrator.entity.relationships.supervises.service.nameReferenced**: service names.
- **orchestrator.entity.relationships.supervises.user.domainReferenced**: user directory or AD/LDAP domain names.
- **orchestrator.entity.relationships.supervises.user.emailReferenced**: user email addresses.
- **orchestrator.entity.relationships.supervises.user.idReferenced**: user ids.
- **orchestrator.entity.relationships.supervises.user.nameReferenced**: user short names or logins.
- **orchestrator.entity.source**: Source module or integration that provided the entity data.
- **orchestrator.entity.sub_type**: The specific type designation for the entity as defined by its provider or system.
- **orchestrator.entity.type**: Standardized high-level classification of the entity.
- **orchestrator.namespace**: Namespace in which the action is taking place.
- **orchestrator.organization**: Organization affected by the event (for multi-tenant orchestrator setups).
- **orchestrator.resource.annotation**: The list of annotations added to the resource.
- **orchestrator.resource.id**: Unique ID of the resource being acted upon.
- **orchestrator.resource.ip**: IP address assigned to the resource associated with the event being observed.
- **orchestrator.resource.label**: The list of labels added to the resource.
- **orchestrator.resource.name**: Name of the resource being acted upon.
- **orchestrator.resource.parent.type**: Type or kind of the parent resource associated with the event being observed.
- **orchestrator.resource.type**: Type of resource being acted upon.
- **orchestrator.type**: Orchestrator cluster type (e.g. kubernetes, nomad or cloudfoundry).

organization

- **organization.id**: Unique identifier for the organization.
- **organization.name**: Organization name.
- **organization.name.text**: Organization name.

package

- **package.architecture**: Package architecture.
- **package.build_version**: Build version information
- **package.checksum**: Checksum of the installed package for verification.
- **package.description**: Description of the package.
- **package.install_scope**: Indicating how the package was installed, e.g. user-local, global.
- **package.installed**: Time when package was installed.
- **package.license**: Package license

- **package.name**: Package name
- **package.path**: Path where the package is installed.
- **package.reference**: Package home page or reference URL
- **package.size**: Package size in bytes.
- **package.type**: Package type
- **package.version**: Package version

process

- **process.args**: Array of process arguments.
- **process.args_count**: Length of the process.args array.
- **process.code_signature.digest_algorithm**: Hashing algorithm used to sign the process.
- **process.code_signature.exists**: Boolean to capture if a signature is present.
- **process.code_signature.flags**: Code signing flags of the process
- **process.code_signature.signing_id**: The identifier used to sign the process.
- **process.code_signature.status**: Additional information about the certificate status.
- **process.code_signature.subject_name**: Subject name of the code signer
- **process.code_signature.team_id**: The team identifier used to sign the process.
- **process.code_signature.thumbprint_sha256SHA256**: hash of the certificate.
- **process.code_signature.timestamp**: When the signature was generated and signed.
- **process.code_signature.trusted**: Stores the trust status of the certificate chain.
- **process.code_signature.valid**: Boolean to capture if the digital signature is verified against the binary content.
- **process.command_line**: Full command line that started the process.
- **process.command_line.text**: Full command line that started the process.
- **process.elf.architecture**: Machine architecture of the ELF file.
- **process.elf.byte_order**: Byte sequence of ELF file.
- **process.elf.cpu_type**: CPU type of the ELF file.
- **process.elf.creation_date**: Build or compile date.
- **process.elf.exports**: List of exported element names and types.
- **process.elf.go_import_hash**: A hash of the Go language imports in an ELF file.
- **process.elf.go_imports**: List of imported Go language element names and types.
- **process.elf.go_imports_names_entropy**: Shannon entropy calculation from the list of Go imports.
- **process.elf.go_imports_names_var_entropyVariance**: for Shannon entropy calculation from the list of Go imports.
- **process.elf.go_stripped**: Whether the file is a stripped or obfuscated Go executable.
- **process.elf.header.abi_version**: Version of the ELF Application Binary Interface (ABI).
- **process.elf.header.class**: Header class of the ELF file.
- **process.elf.header.data**: Data table of the ELF header.
- **process.elf.header.entrypoint**: Header entrypoint of the ELF file.
- **process.elf.header.object_version**: "0x1" for original ELF files.

- **process.elf.header.os_abi**: Application Binary Interface (ABI) of the Linux OS.
- **process.elf.header.type**: Header type of the ELF file.
- **process.elf.header.version**: Version of the ELF header.
- **process.elf.import_hash**: A hash of the imports in an ELF file.
- **process.elf.imports**: List of imported element names and types.
- **process.elf.imports_names_entropy**: Shannon entropy calculation from the list of imported element names and types.
- **process.elf.imports_names_var_entropy**: Variance for Shannon entropy calculation from the list of imported element names and types.
- **process.elf.sections**: Section information of the ELF file.
- **process.elf.sections.chi2**: Chi-square probability distribution of the section.
- **process.elf.sections.entropy**: Shannon entropy calculation from the section.
- **process.elf.sections.flags**: ELF Section List flags.
- **process.elf.sections.name**: ELF Section List name.
- **process.elf.sections.physical_offset**: ELF Section List offset.
- **process.elf.sections.physical_size**: ELF Section List physical size.
- **process.elf.sections.type**: ELF Section List type.
- **process.elf.sections.var_entropy**: Variance for Shannon entropy calculation from the section.
- **process.elf.sections.virtual_address**: ELF Section List virtual address.
- **process.elf.sections.virtual_size**: ELF Section List virtual size.
- **process.elf.segments**: ELF object segment list.
- **process.elf.segments.sections**: ELF object segment sections.
- **process.elf.segments.type**: ELF object segment type.
- **process.elf.shared_libraries**: List of shared libraries used by this ELF object.
- **process.elf.telfhash**: telfhash hash for ELF file.
- **process.end**: The time the process ended.
- **process.entity_id**: Unique identifier for the process.
- **process.entry_leader.args**: Array of process arguments.
- **process.entry_leader.args_count**: Length of the process.args array.
- **process.entry_leader.attested_groups.nameName**: of the group.
- **process.entry_leader.attested_user.id**: Unique identifier of the user.
- **process.entry_leader.attested_user.name**: Short name or login of the user.
- **process.entry_leader.attested_user.name.textShort**: name or login of the user.
- **process.entry_leader.command_line**: Full command line that started the process.
- **process.entry_leader.command_line.text**: Full command line that started the process.
- **process.entry_leader.entity_id**: Unique identifier for the process.
- **process.entry_leader.entry_meta.source.ip**: IP address of the source.
- **process.entry_leader.entry_meta.type**: The entry type for the entry session leader.
- **process.entry_leader.executable**: Absolute path to the process executable.
- **process.entry_leader.executable.text**: Absolute path to the process executable.
- **process.entry_leader.group.id**: Unique identifier for the group on the system/platform.
- **process.entry_leader.group.name**: Name of the group.

- **process.entry_leader.interactive:** Whether the process is connected to an interactive shell.
- **process.entry_leader.name:** Process name.
- **process.entry_leader.name.text:** Process name.
- **process.entry_leader.parent.entity_id:** Unique identifier for the process.
- **process.entry_leader.parent.pid:** Process id.
- **process.entry_leader.parent.session_leader.entity_idUnique:** identifier for the process.
- **process.entry_leader.parent.session_leader.pidProcess:** id.
- **process.entry_leader.parent.session_leader.startThe:** time the process started.
- **process.entry_leader.parent.session_leader.vpidVirtual:** process id.
- **process.entry_leader.parent.start:** The time the process started.
- **process.entry_leader.parent.vpid:** Virtual process id.
- **process.entry_leader.pid:** Process id.
- **process.entry_leader.real_group.id:** Unique identifier for the group on the system/platform.
- **process.entry_leader.real_group.name:** Name of the group.
- **process.entry_leader.real_user.id:** Unique identifier of the user.
- **process.entry_leader.real_user.name:** Short name or login of the user.
- **process.entry_leader.real_user.name.text:** Short name or login of the user.
- **process.entry_leader.same_as_process:** This boolean is used to identify if a leader process is the same as the top level process.
- **process.entry_leader.saved_group.id:** Unique identifier for the group on the system/platform.
- **process.entry_leader.saved_group.name:** Name of the group.
- **process.entry_leader.saved_user.id:** Unique identifier of the user.
- **process.entry_leader.saved_user.name:** Short name or login of the user.
- **process.entry_leader.saved_user.name.textShort:** name or login of the user.
- **process.entry_leader.start:** The time the process started.
- **process.entry_leader.supplemental_groups.idUnique:** identifier for the group on the system/platform.
- **process.entry_leader.supplemental_groups.nameName:** of the group.
- **process.entry_leader.tty:** Information about the controlling TTY device.
- **process.entry_leader.tty.char_device.major:** The TTY character device's major number.
- **process.entry_leader.tty.char_device.minor:** The TTY character device's minor number.
- **process.entry_leader.user.id:** Unique identifier of the user.
- **process.entry_leader.user.name:** Short name or login of the user.
- **process.entry_leader.user.name.text:** Short name or login of the user.
- **process.entry_leader.vpid:** Virtual process id.
- **process.entry_leader.working_directory:** The working directory of the process.
- **process.entry_leader.working_directory.text:** The working directory of the process.

- **process.env_vars**: Array of environment variable bindings.
- **process.executable**: Absolute path to the process executable.
- **process.executable.text**: Absolute path to the process executable.
- **process.exit_code**: The exit code of the process.
- **process.group.id**: Unique identifier for the group on the system/platform.
- **process.group.name**: Name of the group.
- **process.group_leader.args**: Array of process arguments.
- **process.group_leader.args_count**: Length of the process.args array.
- **process.group_leader.command_line**: Full command line that started the process.
- **process.group_leader.command_line.text**: Full command line that started the process.
- **process.group_leader.entity_id**: Unique identifier for the process.
- **process.group_leader.executable**: Absolute path to the process executable.
- **process.group_leader.executable.text**: Absolute path to the process executable.
- **process.group_leader.group.id**: Unique identifier for the group on the system/platform.
- **process.group_leader.group.name**: Name of the group.
- **process.group_leader.interactive**: Whether the process is connected to an interactive shell.
- **process.group_leader.name**: Process name.
- **process.group_leader.name.text**: Process name.
- **process.group_leader.pid**: Process id.
- **process.group_leader.real_group.id**: Unique identifier for the group on the system/platform.
- **process.group_leader.real_group.name**: Name of the group.
- **process.group_leader.real_user.id**: Unique identifier of the user.
- **process.group_leader.real_user.name**: Short name or login of the user.
- **process.group_leader.real_user.name.text**: Short name or login of the user.
- **process.group_leader.same_as_process**: This boolean is used to identify if a leader process is the same as the top level process.
- **process.group_leader.saved_group.id**: Unique identifier for the group on the system/platform.
- **process.group_leader.saved_group.name**: Name of the group.
- **process.group_leader.saved_user.id**: Unique identifier of the user.
- **process.group_leader.saved_user.name**: Short name or login of the user.
- **process.group_leader.saved_user.name.textShort**: name or login of the user.
- **process.group_leader.start**: The time the process started.
- **process.group_leader.supplemental_groups.idUnique**: identifier for the group on the system/platform.
- **process.group_leader.supplemental_groups.nameName**: of the group.
- **process.group_leader.tty**: Information about the controlling TTY device.
- **process.group_leader.tty.char_device.majorThe**: TTY character device's major number.

- **process.group_leader.tty.char_device.minor**The: TTY character device's minor number.
- **process.group_leader.user.id**: Unique identifier of the user.
- **process.group_leader.user.name**: Short name or login of the user.
- **process.group_leader.user.name.text**: Short name or login of the user.
- **process.group_leader.vpid**: Virtual process id.
- **process.group_leader.working_directory**: The working directory of the process.
- **process.group_leader.working_directory.text**The: working directory of the process.
- **process.hash.cdhash**: The Code Directory (CD) hash of an executable.
- **process.hash.md5**: MD5 hash.
- **process.hash.sha1**: SHA1 hash.
- **process.hash.sha256**: SHA256 hash.
- **process.hash.sha384**: SHA384 hash.
- **process.hash.sha512**: SHA512 hash.
- **process.hash.ssdeep**: SSDEEP hash.
- **process.hash.tlsh**: TLSH hash.
- **process.interactive**: Whether the process is connected to an interactive shell.
- **process.io**: A chunk of input or output (IO) from a single process.
- **process.io.bytes_skipped**: An array of byte offsets and lengths denoting where IO data has been skipped.
- **process.io.bytes_skipped.length**: The length of bytes skipped.
- **process.io.bytes_skipped.offset**: The byte offset into this event's io.text (or io.bytes in the future) where length bytes were skipped.
- **process.io.max_bytes_per_process_exceeded**If: true, the process producing the output has exceeded the max_kilobytes_per_process configuration setting.
- **process.io.text**: A chunk of output or input sanitized to UTF-8.
- **process.io.total_bytes_captured**: The total number of bytes captured in this event.
- **process.io.total_bytes_skipped**: The total number of bytes that were not captured due to implementation restrictions such as buffer size limits.
- **process.io.type**: The type of object on which the IO action (read or write) was taken.
- **process.macho.go_import_hash**: A hash of the Go language imports in a Mach-O file.
- **process.macho.go_imports**: List of imported Go language element names and types.
- **process.macho.go_imports_names_entropy**Shannon: entropy calculation from the list of Go imports.
- **process.macho.go_imports_names_var_entropy**Variance: for Shannon entropy calculation from the list of Go imports.
- **process.macho.go_stripped**: Whether the file is a stripped or obfuscated Go executable.
- **process.macho.import_hash**: A hash of the imports in a Mach-O file.
- **process.macho.imports**: List of imported element names and types.
- **process.macho.imports_names_entropy**: Shannon entropy calculation from the list of imported element names and types.

- **process.macho.imports_names_var_entropyVariance**: for Shannon entropy calculation from the list of imported element names and types.
- **process.macho.sections**: Section information of the Mach-O file.
- **process.macho.sections.entropy**: Shannon entropy calculation from the section.
- **process.macho.sections.name**: Mach-O Section List name.
- **process.macho.sections.physical_size**: Mach-O Section List physical size.
- **process.macho.sections.var_entropy**: Variance for Shannon entropy calculation from the section.
- **process.macho.sections.virtual_size**: Mach-O Section List virtual size. This is always the same as **physical_size**.
- **process.macho.symhash**: A hash of the imports in a Mach-O file.
- **process.name**: Process name.
- **process.name.text**: Process name.
- **process.parent.args**: Array of process arguments.
- **process.parent.args_count**: Length of the process.args array.
- **process.parent.code_signature.digest_algorithmHashing**: algorithm used to sign the process.
- **process.parent.code_signature.exists**: Boolean to capture if a signature is present.
- **process.parent.code_signature.flags**: Code signing flags of the process
- **process.parent.code_signature.signing_id**: The identifier used to sign the process.
- **process.parent.code_signature.status**: Additional information about the certificate status.
- **process.parent.code_signature.subject_nameSubject**: name of the code signer
- **process.parent.code_signature.team_id**: The team identifier used to sign the process.
- **process.parent.code_signature.thumbprint_sha256SHA256**: hash of the certificate.
- **process.parent.code_signature.timestamp**: When the signature was generated and signed.
- **process.parent.code_signature.trusted**: Stores the trust status of the certificate chain.
- **process.parent.code_signature.valid**: Boolean to capture if the digital signature is verified against the binary content.
- **process.parent.command_line**: Full command line that started the process.
- **process.parent.command_line.text**: Full command line that started the process.
- **process.parent.elf.architecture**: Machine architecture of the ELF file.
- **process.parent.elf.byte_order**: Byte sequence of ELF file.
- **process.parent.elf.cpu_type**: CPU type of the ELF file.
- **process.parent.elf.creation_date**: Build or compile date.
- **process.parent.elf.exports**: List of exported element names and types.
- **process.parent.elf.go_import_hash**: A hash of the Go language imports in an ELF file.
- **process.parent.elf.go_imports**: List of imported Go language element names and types.
- **process.parent.elf.go_imports_names_entropyShannon**: entropy calculation from the list of Go imports.

- **process.parent.elf.go_imports_names_var_entropyVariance**: for Shannon entropy calculation from the list of Go imports.
- **process.parent.elf.go_stripped**: Whether the file is a stripped or obfuscated Go executable.
- **process.parent.elf.header.abi_version**: Version of the ELF Application Binary Interface (ABI).
- **process.parent.elf.header.class**: Header class of the ELF file.
- **process.parent.elf.header.data**: Data table of the ELF header.
- **process.parent.elf.header.entrypoint**: Header entrypoint of the ELF file.
- **process.parent.elf.header.object_version**: "0x1" for original ELF files.
- **process.parent.elf.header.os_abi**: Application Binary Interface (ABI) of the Linux OS.
- **process.parent.elf.header.type**: Header type of the ELF file.
- **process.parent.elf.header.version**: Version of the ELF header.
- **process.parent.elf.import_hash**: A hash of the imports in an ELF file.
- **process.parent.elf.imports**: List of imported element names and types.
- **process.parent.elf.imports_names_entropy**: Shannon entropy calculation from the list of imported element names and types.
- **process.parent.elf.imports_names_var_entropyVariance**: for Shannon entropy calculation from the list of imported element names and types.
- **process.parent.elf.sections**: Section information of the ELF file.
- **process.parent.elf.sections.chi2**: Chi-square probability distribution of the section.
- **process.parent.elf.sections.entropy**: Shannon entropy calculation from the section.
- **process.parent.elf.sections.flags**: ELF Section List flags.
- **process.parent.elf.sections.name**: ELF Section List name.
- **process.parent.elf.sections.physical_offset**: ELF Section List offset.
- **process.parent.elf.sections.physical_size**: ELF Section List physical size.
- **process.parent.elf.sections.type**: ELF Section List type.
- **process.parent.elf.sections.var_entropy**: Variance for Shannon entropy calculation from the section.
- **process.parent.elf.sections.virtual_address**: ELF Section List virtual address.
- **process.parent.elf.sections.virtual_size**: ELF Section List virtual size.
- **process.parent.elf.segments**: ELF object segment list.
- **process.parent.elf.segments.sections**: ELF object segment sections.
- **process.parent.elf.segments.type**: ELF object segment type.
- **process.parent.elf.shared_libraries**: List of shared libraries used by this ELF object.
- **process.parent.elf.telfhash**: telfhash hash for ELF file.
- **process.parent.end**: The time the process ended.
- **process.parent.entity_id**: Unique identifier for the process.
- **process.parent.executable**: Absolute path to the process executable.
- **process.parent.executable.text**: Absolute path to the process executable.
- **process.parent.exit_code**: The exit code of the process.
- **process.parent.group.id**: Unique identifier for the group on the system/platform.
- **process.parent.group.name**: Name of the group.

- **process.parent.group_leader.entity_id**: Unique identifier for the process.
- **process.parent.group_leader.pid**: Process id.
- **process.parent.group_leader.start**: The time the process started.
- **process.parent.group_leader.vpid**: Virtual process id.
- **process.parent.hash.cdhash**: The Code Directory (CD) hash of an executable.
- **process.parent.hash.md5**: MD5 hash.
- **process.parent.hash.sha1**: SHA1 hash.
- **process.parent.hash.sha256**: SHA256 hash.
- **process.parent.hash.sha384**: SHA384 hash.
- **process.parent.hash.sha512**: SHA512 hash.
- **process.parent.hash.ssdeep**: SSDEEP hash.
- **process.parent.hash.tlsh**: TLSH hash.
- **process.parent.interactive**: Whether the process is connected to an interactive shell.
- **process.parent.macho.go_import_hash**: A hash of the Go language imports in a Mach-O file.
- **process.parent.macho.go_imports**: List of imported Go language element names and types.
- **process.parent.macho.go_imports_names_entropyShannon**: entropy calculation from the list of Go imports.
- **process.parent.macho.go_imports_names_var_entropyVariance**: for Shannon entropy calculation from the list of Go imports.
- **process.parent.macho.go_stripped**: Whether the file is a stripped or obfuscated Go executable.
- **process.parent.macho.import_hash**: A hash of the imports in a Mach-O file.
- **process.parent.macho.imports**: List of imported element names and types.
- **process.parent.macho.imports_names_entropyShannon**: entropy calculation from the list of imported element names and types.
- **process.parent.macho.imports_names_var_entropyVariance**: for Shannon entropy calculation from the list of imported element names and types.
- **process.parent.macho.sections**: Section information of the Mach-O file.
- **process.parent.macho.sections.entropy**: Shannon entropy calculation from the section.
- **process.parent.macho.sections.name**: Mach-O Section List name.
- **process.parent.macho.sections.var_entropy**: Variance for Shannon entropy calculation from the section.
- **process.parent.macho.sections.virtual_size**: Mach-O Section List virtual size. This is always the same as **physical_size**.
- **process.parent.macho.symhash**: A hash of the imports in a Mach-O file.
- **process.parent.name**: Process name.
- **process.parent.name.text**: Process name.
- **process.parent.pe.architecture**: CPU architecture target for the file.
- **process.parent.pe.company**: Internal company name of the file, provided at compile-time.

- **process.parent.pe.description**: Internal description of the file, provided at compile-time.
- **process.parent.pe.file_version**: Process name.
- **process.parent.pe.go_import_hash**: A hash of the Go language imports in a PE file.
- **process.parent.pe.go_imports**: List of imported Go language element names and types.
- **process.parent.pe.go_imports_names_entropyShannon**: entropy calculation from the list of Go imports.
- **process.parent.pe.go_imports_names_var_entropyVariance**: for Shannon entropy calculation from the list of Go imports.
- **process.parent.pe.go_stripped**: Whether the file is a stripped or obfuscated Go executable.
- **process.parent.pe.imphash**: A hash of the imports in a PE file.
- **process.parent.pe.import_hash**: A hash of the imports in a PE file.
- **process.parent.pe.imports**: List of imported element names and types.
- **process.parent.pe.imports_names_entropy**: Shannon entropy calculation from the list of imported element names and types.
- **process.parent.pe.imports_names_var_entropyVariance**: for Shannon entropy calculation from the list of imported element names and types.
- **process.parent.pe.original_file_name**: Internal name of the file, provided at compile-time.
- **process.parent.pe.pehash**: A hash of the PE header and data from one or more PE sections.
- **process.parent.pe.product**: Internal product name of the file, provided at compile-time.
- **process.parent.pe.sections**: Section information of the PE file.
- **process.parent.pe.sections.entropy**: Shannon entropy calculation from the section.
- **process.parent.pe.sections.name**: PE Section List name.
- **process.parent.pe.sections.physical_size**: PE Section List physical size.
- **process.parent.pe.sections.var_entropy**: Variance for Shannon entropy calculation from the section.
- **process.parent.pe.sections.virtual_size**: PE Section List virtual size. This is always the same as **physical_size**.
- **process.parent.pid**: Process id.
- **process.parent.real_group.id**: Unique identifier for the group on the system/platform.
- **process.parent.real_group.name**: Name of the group.
- **process.parent.real_user.id**: Unique identifier of the user.
- **process.parent.real_user.name**: Short name or login of the user.
- **process.parent.real_user.name.text**: Short name or login of the user.
- **process.parent.saved_group.id**: Unique identifier for the group on the system/platform.
- **process.parent.saved_group.name**: Name of the group.
- **process.parent.saved_user.id**: Unique identifier of the user.
- **process.parent.saved_user.name**: Short name or login of the user.
- **process.parent.saved_user.name.text**: Short name or login of the user.

- **process.parent.start**: The time the process started.
- **process.parent.supplemental_groups.id**: Unique identifier for the group on the system/platform.
- **process.parent.supplemental_groups.name**: Name of the group.
- **process.parent.thread.capabilities.effective**: Array of capabilities used for permission checks.
- **process.parent.thread.capabilities.permitted**: Array of capabilities a thread could assume.
- **process.parent.thread.id**: Thread ID.
- **process.parent.thread.name**: Thread name.
- **process.parent.title**: Process title.
- **process.parent.title.text**: Process title.
- **process.parent.tty**: Information about the controlling TTY device.
- **process.parent.tty.char_device.major**: The TTY character device's major number.
- **process.parent.tty.char_device.minor**: The TTY character device's minor number.
- **process.parent.uptime**: Seconds the process has been up.
- **process.parent.user.id**: Unique identifier of the user.
- **process.parent.user.name**: Short name or login of the user.
- **process.parent.user.name.text**: Short name or login of the user.
- **process.parent.vpid**: Virtual process id.
- **process.parent.working_directory**: The working directory of the process.
- **process.parent.working_directory.text**: The working directory of the process.
- **process.pe.architecture**: CPU architecture target for the file.
- **process.pe.company**: Internal company name of the file, provided at compile-time.
- **process.pe.description**: Internal description of the file, provided at compile-time.
- **process.pe.file_version**: Process name.
- **process.pe.go_import_hash**: A hash of the Go language imports in a PE file.
- **process.pe.go_imports**: List of imported Go language element names and types.
- **process.pe.go_imports_names_entropy**: Shannon entropy calculation from the list of Go imports.
- **process.pe.go_imports_names_var_entropyVariance**: for Shannon entropy calculation from the list of Go imports.
- **process.pe.go_stripped**: Whether the file is a stripped or obfuscated Go executable.
- **process.pe.imphash**: A hash of the imports in a PE file.
- **process.pe.import_hash**: A hash of the imports in a PE file.
- **process.pe.imports**: List of imported element names and types.
- **process.pe.imports_names_entropy**: Shannon entropy calculation from the list of imported element names and types.
- **process.pe.imports_names_var_entropy**: Variance for Shannon entropy calculation from the list of imported element names and types.
- **process.pe.original_file_name**: Internal name of the file, provided at compile-time.
- **process.pe.pehash**: A hash of the PE header and data from one or more PE sections.
- **process.pe.product**: Internal product name of the file, provided at compile-time.

- **process.pe.sections**: Section information of the PE file.
- **process.pe.sections.entropy**: Shannon entropy calculation from the section.
- **process.pe.sections.name**: PE Section List name.
- **process.pe.sections.physical_size**: PE Section List physical size.
- **process.pe.sections.var_entropy**: Variance for Shannon entropy calculation from the section.
- **process.pe.sections.virtual_size**: PE Section List virtual size. This is always the same as **physical_size**.
- **process.pid**: Process id.
- **process.previous.args**: Array of process arguments.
- **process.previous.args_count**: Length of the process.args array.
- **process.previous.executable**: Absolute path to the process executable.
- **process.previous.executable.text**: Absolute path to the process executable.
- **process.real_group.id**: Unique identifier for the group on the system/platform.
- **process.real_group.name**: Name of the group.
- **process.real_user.id**: Unique identifier of the user.
- **process.real_user.name**: Short name or login of the user.
- **process.real_user.name.text**: Short name or login of the user.
- **process.saved_group.id**: Unique identifier for the group on the system/platform.
- **process.saved_group.name**: Name of the group.
- **process.saved_user.id**: Unique identifier of the user.
- **process.saved_user.name**: Short name or login of the user.
- **process.saved_user.name.text**: Short name or login of the user.
- **process.session_leader.args**: Array of process arguments.
- **process.session_leader.args_count**: Length of the process.args array.
- **process.session_leader.command_line**: Full command line that started the process.
- **process.session_leader.command_line.text**: Full command line that started the process.
- **process.session_leader.entity_id**: Unique identifier for the process.
- **process.session_leader.executable**: Absolute path to the process executable.
- **process.session_leader.executable.text**: Absolute path to the process executable.
- **process.session_leader.group.id**: Unique identifier for the group on the system/platform.
- **process.session_leader.group.name**: Name of the group.
- **process.session_leader.interactive**: Whether the process is connected to an interactive shell.
- **process.session_leader.name**: Process name.
- **process.session_leader.name.text**: Process name.
- **process.session_leader.parent.entity_id**: Unique identifier for the process.
- **process.session_leader.parent.pid**: Process id.
- **process.session_leader.parent.session_leader.entity_id**Unique: identifier for the process.
- **process.session_leader.parent.session_leader.pid**Process: id.

- **process.session_leader.parent.session_leader.startThe**: time the process started.
- **process.session_leader.parent.session_leader.vpidVirtual**: process id.
- **process.session_leader.parent.start**: The time the process started.
- **process.session_leader.parent.vpid**: Virtual process id.
- **process.session_leader.pid**: Process id.
- **process.session_leader.real_group.id**: Unique identifier for the group on the system/platform.
- **process.session_leader.real_group.name**: Name of the group.
- **process.session_leader.real_user.id**: Unique identifier of the user.
- **process.session_leader.real_user.name**: Short name or login of the user.
- **process.session_leader.real_user.name.textShort**: name or login of the user.
- **process.session_leader.same_as_process**: This boolean is used to identify if a leader process is the same as the top level process.
- **process.session_leader.saved_group.id**: Unique identifier for the group on the system/platform.
- **process.session_leader.saved_group.name**: Name of the group.
- **process.session_leader.saved_user.id**: Unique identifier of the user.
- **process.session_leader.saved_user.name**: Short name or login of the user.
- **process.session_leader.saved_user.name.textShort**: name or login of the user.
- **process.session_leader.start**: The time the process started.
- **process.session_leader.supplemental_groups.idUnique**: identifier for the group on the system/platform.
- **process.session_leader.supplemental_groups.nameName**: of the group.
- **process.session_leader.tty**: Information about the controlling TTY device.
- **process.session_leader.tty.char_device.majorThe**: TTY character device's major number.
- **process.session_leader.tty.char_device.minorThe**: TTY character device's minor number.
- **process.session_leader.user.id**: Unique identifier of the user.
- **process.session_leader.user.name**: Short name or login of the user.
- **process.session_leader.user.name.text**: Short name or login of the user.
- **process.session_leader.vpid**: Virtual process id.
- **process.session_leader.working_directory**: The working directory of the process.
- **process.session_leader.working_directory.textThe**: working directory of the process.
- **process.start**: The time the process started.
- **process.supplemental_groups.id**: Unique identifier for the group on the system/platform.
- **process.supplemental_groups.name**: Name of the group.
- **process.thread.capabilities.effective**: Array of capabilities used for permission checks.
- **process.thread.capabilities.permitted**: Array of capabilities a thread could assume.
- **process.thread.id**: Thread ID.
- **process.thread.name**: Thread name.
- **process.title**: Process title.

- **process.title.text**: Process title.
- **process.tty**: Information about the controlling TTY device.
- **process.tty.char_device.major**: The TTY character device's major number.
- **process.tty.char_device.minor**: The TTY character device's minor number.
- **process.tty.columns**: The number of character columns per line. e.g terminal width
- **process.tty.rows**: The number of character rows in the terminal. e.g terminal height
- **process.uptime**: Seconds the process has been up.
- **process.user.id**: Unique identifier of the user.
- **process.user.name**: Short name or login of the user.
- **process.user.name.text**: Short name or login of the user.
- **process.vpid**: Virtual process id.
- **process.working_directory**: The working directory of the process.
- **process.working_directory.text**: The working directory of the process.

registry

- **registry.data.bytes**: Original bytes written with base64 encoding.
- **registry.data.strings**: List of strings representing what was written to the registry.
- **registry.data.type**: Standard registry type for encoding contents
- **registry.hive**: Abbreviated name for the hive.
- **registry.key**: Hive-relative path of keys.
- **registry.path**: Full path, including hive, key and value
- **registry.value**: Name of the value written.

related

- **related.hash**: All the hashes seen on your event.
- **related.hosts**: All the host identifiers seen on your event.
- **related.ip**: All of the IPs seen on your event.
- **related.user**: All the user names or other user identifiers seen on the event.

rule

- **rule.author**: Rule author
- **rule.category**: Rule category
- **rule.description**: Rule description
- **rule.id**: Rule ID
- **rule.license**: Rule license
- **rule.name**: Rule name
- **rule.reference**: Rule reference URL
- **rule.ruleset**: Rule ruleset
- **rule.uuid**: Rule UUID
- **rule.version**: Rule version

server

- **server.address**: Server network address.
- **server.as.number**: Unique number allocated to the autonomous system.
- **server.as.organization.name**: Organization name.
- **server.as.organization.name.text**: Organization name.
- **server.bytes**: Bytes sent from the server to the client.
- **server.domain**: The domain name of the server.
- **server.geo.city_name**: City name.
- **server.geo.continent_code**: Continent code.
- **server.geo.continent_name**: Name of the continent.
- **server.geo.country_iso_code**: Country ISO code.
- **server.geo.country_name**: Country name.
- **server.geo.location**: Longitude and latitude.
- **server.geo.name**: User-defined description of a location.
- **server.geo.postal_code**: Postal code.
- **server.geo.region_iso_code**: Region ISO code.
- **server.geo.region_name**: Region name.
- **server.geo.timezone**: Time zone.
- **server.ip**: IP address of the server.
- **server.mac**: MAC address of the server.
- **server.nat.ip**: Server NAT ip
- **server.nat.port**: Server NAT port
- **server.packets**: Packets sent from the server to the client.
- **server.port**: Port of the server.
- **server.registered_domain**: The highest registered server domain, stripped of the subdomain.
- **server.subdomain**: The subdomain of the domain.
- **server.top_level_domain**: The effective top level domain (com, org, net, co.uk).
- **server.user.domain**: Name of the directory the user is a member of.
- **server.user.email**: User email address.
- **server.user.full_name**: User's full name, if available.
- **server.user.full_name.text**: User's full name, if available.
- **server.user.group.domain**: Name of the directory the group is a member of.
- **server.user.group.id**: Unique identifier for the group on the system/platform.
- **server.user.group.name**: Name of the group.
- **server.user.hash**: Unique user hash to correlate information for a user in anonymized form.
- **server.user.id**: Unique identifier of the user.
- **server.user.name**: Short name or login of the user.
- **server.user.name.text**: Short name or login of the user.
- **server.user.roles**: Array of user roles at the time of the event.

service

- **service.address**: Address of this service.
- **service.entity.attributes.known_redirects**: Known redirect URIs or URLs associated with this entity.
- **service.entity.attributes.managed**: Indicates whether the entity is managed by an external system.
- **service.entity.attributes.mfa_enabled**: Indicates whether multi-factor authentication is enabled for this entity.
- **service.entity.attributes.oauth_consent_restrictionRestriction**: applied to OAuth consent for this entity.
- **service.entity.attributes.permissions**: Action-level permissions associated with this entity.
- **service.entity.attributes.storage_class**: Storage tier or class assigned to an object storage resource.
- **service.entity.behavior**: A set of ephemeral characteristics of the entity, derived from observed behaviors during a specific time period.
- **service.entity.display_name**: An optional field used when a pretty name is desired for entity-centric operations.
- **service.entity.display_name.text**: An optional field used when a pretty name is desired for entity-centric operations.
- **service.entity.id**: Unique identifier for the entity.
- **service.entity.last_seen_timestamp**: Indicates the date/time when this entity was last "seen."
- **service.entity.lifecycle.last_activity**: Timestamp of the most recent action performed by or attributed to this entity.
- **service.entity.metrics**: Field set for any fields containing numeric entity metrics.
- **service.entity.name**: The name of the entity.
- **service.entity.name.text**: The name of the entity.
- **service.entity.raw**: Original, unmodified fields from the source system.
- **service.entity.reference**: A URI, URL, or other direct reference to access or locate the entity.
- **service.entity.relationships.administers.entity.idIdentifiers**: of referenced entities.
- **service.entity.relationships.administers.host.idReferenced**: host ids.
- **service.entity.relationships.administers.host.nameReferenced**: host names.
- **service.entity.relationships.administers.service.idReferenced**: service ids.
- **service.entity.relationships.administers.service.nameReferenced**: service names.
- **service.entity.relationships.administers.user.domainReferenced**: user directory or AD/LDAP domain names.
- **service.entity.relationships.administers.user.emailReferenced**: user email addresses.
- **service.entity.relationships.administers.user.idReferenced**: user ids.

- **service.entity.relationships.administers.user.nameReferenced**: user short names or logins.
- **service.entity.relationships.depends_on.entity.idIdentifiers**: of referenced entities.
- **service.entity.relationships.depends_on.host.idReferenced**: host ids.
- **service.entity.relationships.depends_on.host.nameReferenced**: host names.
- **service.entity.relationships.depends_on.service.idReferenced**: service ids.
- **service.entity.relationships.depends_on.service.nameReferenced**: service names.
- **service.entity.relationships.depends_on.user.domainReferenced**: user directory or AD/LDAP domain names.
- **service.entity.relationships.depends_on.user.emailReferenced**: user email addresses.
- **service.entity.relationships.depends_on.user.idReferenced**: user ids.
- **service.entity.relationships.depends_on.user.nameReferenced**: user short names or logins.
- **service.entity.relationships.owns.entity.id**: Identifiers of referenced entities.
- **service.entity.relationships.owns.host.id**: Referenced host ids.
- **service.entity.relationships.owns.host.name**: Referenced host names.
- **service.entity.relationships.owns.service.id**: Referenced service ids.
- **service.entity.relationships.owns.service.nameReferenced**: service names.
- **service.entity.relationships.owns.user.domainReferenced**: user directory or AD/LDAP domain names.
- **service.entity.relationships.owns.user.email**: Referenced user email addresses.
- **service.entity.relationships.owns.user.id**: Referenced user ids.
- **service.entity.relationships.owns.user.name**: Referenced user short names or logins.
- **service.entity.relationships.supervises.entity.idIdentifiers**: of referenced entities.
- **service.entity.relationships.supervises.host.idReferenced**: host ids.
- **service.entity.relationships.supervises.host.nameReferenced**: host names.
- **service.entity.relationships.supervises.service.idReferenced**: service ids.
- **service.entity.relationships.supervises.service.nameReferenced**: service names.
- **service.entity.relationships.supervises.user.domainReferenced**: user directory or AD/LDAP domain names.
- **service.entity.relationships.supervises.user.emailReferenced**: user email addresses.
- **service.entity.relationships.supervises.user.idReferenced**: user ids.
- **service.entity.relationships.supervises.user.nameReferenced**: user short names or logins.
- **service.entity.source**: Source module or integration that provided the entity data.
- **service.entity.sub_type**: The specific type designation for the entity as defined by its provider or system.
- **service.entity.type**: Standardized high-level classification of the entity.
- **service.environment**: Environment of the service.
- **service.ephemeral_id**: Ephemeral identifier of this service.
- **service.id**: Unique identifier of the running service.
- **service.name**: Name of the service.

- **service.node.name**: Name of the service node.
- **service.node.role**: Deprecated role (singular) of the service node.
- **service.node.roles**: Roles of the service node.
- **service.origin.address**: Address of this service.
- **service.origin.entity.attributes.known_redirectsKnown**: redirect URIs or URLs associated with this entity.
- **service.origin.entity.attributes.managed**: Indicates whether the entity is managed by an external system.
- **service.origin.entity.attributes.mfa_enabled**: Indicates whether multi-factor authentication is enabled for this entity.
- **service.origin.entity.attributes.oauth_consent_restrictionRestriction**: applied to OAuth consent for this entity.
- **service.origin.entity.attributes.permissions**: Action-level permissions associated with this entity.
- **service.origin.entity.attributes.storage_class**: Storage tier or class assigned to an object storage resource.
- **service.origin.entity.behavior**: A set of ephemeral characteristics of the entity, derived from observed behaviors during a specific time period.
- **service.origin.entity.display_name**: An optional field used when a pretty name is desired for entity-centric operations.
- **service.origin.entity.display_name.text**: An optional field used when a pretty name is desired for entity-centric operations.
- **service.origin.entity.id**: Unique identifier for the entity.
- **service.origin.entity.last_seen_timestamp**: Indicates the date/time when this entity was last "seen."
- **service.origin.entity.lifecycle.last_activity**: Timestamp of the most recent action performed by or attributed to this entity.
- **service.origin.entity.metrics**: Field set for any fields containing numeric entity metrics.
- **service.origin.entity.name**: The name of the entity.
- **service.origin.entity.name.text**: The name of the entity.
- **service.origin.entity.raw**: Original, unmodified fields from the source system.
- **service.origin.entity.reference**: A URI, URL, or other direct reference to access or locate the entity.
- **service.origin.entity.relationships.administers.entity.idIdentifiers**: of referenced entities.
- **service.origin.entity.relationships.administers.host.idReferenced**: host ids.
- **service.origin.entity.relationships.administers.host.nameReferenced**: host names.
- **service.origin.entity.relationships.administers.service.idReferenced**: service ids.
- **service.origin.entity.relationships.administers.service.nameReferenced**: service names.
- **service.origin.entity.relationships.administers.user.domainReferenced**: user directory or AD/LDAP domain names.

- **service.origin.entity.relationships.administers.user.emailReferenced**: user email addresses.
- **service.origin.entity.relationships.administers.user.idReferenced**: user ids.
- **service.origin.entity.relationships.administers.user.nameReferenced**: user short names or logins.
- **service.origin.entity.relationships.depends_on.entity.idIdentifiers**: of referenced entities.
- **service.origin.entity.relationships.depends_on.host.idReferenced**: host ids.
- **service.origin.entity.relationships.depends_on.host.nameReferenced**: host names.
- **service.origin.entity.relationships.depends_on.service.idReferenced**: service ids.
- **service.origin.entity.relationships.depends_on.service.nameReferenced**: service names.
- **service.origin.entity.relationships.depends_on.user.domainReferenced**: user directory or AD/LDAP domain names.
- **service.origin.entity.relationships.depends_on.user.emailReferenced**: user email addresses.
- **service.origin.entity.relationships.depends_on.user.idReferenced**: user ids.
- **service.origin.entity.relationships.depends_on.user.nameReferenced**: user short names or logins.
- **service.origin.entity.relationships.owns.entity.idIdentifiers**: of referenced entities.
- **service.origin.entity.relationships.owns.host.idReferenced**: host ids.
- **service.origin.entity.relationships.owns.host.nameReferenced**: host names.
- **service.origin.entity.relationships.owns.service.idReferenced**: service ids.
- **service.origin.entity.relationships.owns.service.nameReferenced**: service names.
- **service.origin.entity.relationships.owns.user.domainReferenced**: user directory or AD/LDAP domain names.
- **service.origin.entity.relationships.owns.user.emailReferenced**: user email addresses.
- **service.origin.entity.relationships.owns.user.idReferenced**: user ids.
- **service.origin.entity.relationships.owns.user.nameReferenced**: user short names or logins.
- **service.origin.entity.relationships.supervises.entity.idIdentifiers**: of referenced entities.
- **service.origin.entity.relationships.supervises.host.idReferenced**: host ids.
- **service.origin.entity.relationships.supervises.host.nameReferenced**: host names.
- **service.origin.entity.relationships.supervises.service.idReferenced**: service ids.
- **service.origin.entity.relationships.supervises.service.nameReferenced**: service names.
- **service.origin.entity.relationships.supervises.user.domainReferenced**: user directory or AD/LDAP domain names.
- **service.origin.entity.relationships.supervises.user.emailReferenced**: user email addresses.
- **service.origin.entity.relationships.supervises.user.idReferenced**: user ids.

- **service.origin.entity.relationships.supervises.user.nameReferenced:** user short names or logins.
- **service.origin.entity.source:** Source module or integration that provided the entity data.
- **service.origin.entity.sub_type:** The specific type designation for the entity as defined by its provider or system.
- **service.origin.entity.type:** Standardized high-level classification of the entity.
- **service.origin.environment:** Environment of the service.
- **service.origin.ephemeral_id:** Ephemeral identifier of this service.
- **service.origin.id:** Unique identifier of the running service.
- **service.origin.name:** Name of the service.
- **service.origin.node.name:** Name of the service node.
- **service.origin.node.role:** Deprecated role (singular) of the service node.
- **service.origin.node.roles:** Roles of the service node.
- **service.origin.state:** Current state of the service.
- **service.origin.type:** The type of the service.
- **service.origin.version:** Version of the service.
- **service.state:** Current state of the service.
- **service.target.address:** Address of this service.
- **service.target.entity.attributes.known_redirectsKnown:** redirect URIs or URLs associated with this entity.
- **service.target.entity.attributes.managed:** Indicates whether the entity is managed by an external system.
- **service.target.entity.attributes.mfa_enabled:** Indicates whether multi-factor authentication is enabled for this entity.
- **service.target.entity.attributes.oauth_consent_restrictionRestriction:** applied to OAuth consent for this entity.
- **service.target.entity.attributes.permissions:** Action-level permissions associated with this entity.
- **service.target.entity.attributes.storage_classStorage:** tier or class assigned to an object storage resource.
- **service.target.entity.behavior:** A set of ephemeral characteristics of the entity, derived from observed behaviors during a specific time period.
- **service.target.entity.display_name:** An optional field used when a pretty name is desired for entity-centric operations.
- **service.target.entity.display_name.text:** An optional field used when a pretty name is desired for entity-centric operations.
- **service.target.entity.id:** Unique identifier for the entity.
- **service.target.entity.last_seen_timestamp:** Indicates the date/time when this entity was last "seen."
- **service.target.entity.lifecycle.last_activity:** Timestamp of the most recent action performed by or attributed to this entity.
- **service.target.entity.metrics:** Field set for any fields containing numeric entity metrics.
- **service.target.entity.name:** The name of the entity.

- **service.target.entity.name.text**: The name of the entity.
- **service.target.entity.raw**: Original, unmodified fields from the source system.
- **service.target.entity.reference**: A URI, URL, or other direct reference to access or locate the entity.
- **service.target.entity.relationships.administers.entity.idIdentifiers**: of referenced entities.
- **service.target.entity.relationships.administers.host.idReferenced**: host ids.
- **service.target.entity.relationships.administers.host.nameReferenced**: host names.
- **service.target.entity.relationships.administers.service.idReferenced**: service ids.
- **service.target.entity.relationships.administers.service.nameReferenced**: service names.
- **service.target.entity.relationships.administers.user.domainReferenced**: user directory or AD/LDAP domain names.
- **service.target.entity.relationships.administers.user.emailReferenced**: user email addresses.
- **service.target.entity.relationships.administers.user.idReferenced**: user ids.
- **service.target.entity.relationships.administers.user.nameReferenced**: user short names or logins.
- **service.target.entity.relationships.depends_on.entity.idIdentifiers**: of referenced entities.
- **service.target.entity.relationships.depends_on.host.idReferenced**: host ids.
- **service.target.entity.relationships.depends_on.host.nameReferenced**: host names.
- **service.target.entity.relationships.depends_on.service.idReferenced**: service ids.
- **service.target.entity.relationships.depends_on.service.nameReferenced**: service names.
- **service.target.entity.relationships.depends_on.user.domainReferenced**: user directory or AD/LDAP domain names.
- **service.target.entity.relationships.depends_on.user.emailReferenced**: user email addresses.
- **service.target.entity.relationships.depends_on.user.idReferenced**: user ids.
- **service.target.entity.relationships.depends_on.user.nameReferenced**: user short names or logins.
- **service.target.entity.relationships.owns.entity.idIdentifiers**: of referenced entities.
- **service.target.entity.relationships.owns.host.idReferenced**: host ids.
- **service.target.entity.relationships.owns.host.nameReferenced**: host names.
- **service.target.entity.relationships.owns.service.idReferenced**: service ids.
- **service.target.entity.relationships.owns.service.nameReferenced**: service names.
- **service.target.entity.relationships.owns.user.domainReferenced**: user directory or AD/LDAP domain names.
- **service.target.entity.relationships.owns.user.emailReferenced**: user email addresses.
- **service.target.entity.relationships.owns.user.idReferenced**: user ids.

- **service.target.entity.relationships.owns.user.nameReferenced**: user short names or logins.
- **service.target.entity.relationships.supervises.entity.idIdentifiers**: of referenced entities.
- **service.target.entity.relationships.supervises.host.idReferenced**: host ids.
- **service.target.entity.relationships.supervises.host.nameReferenced**: host names.
- **service.target.entity.relationships.supervises.service.idReferenced**: service ids.
- **service.target.entity.relationships.supervises.service.nameReferenced**: service names.
- **service.target.entity.relationships.supervises.user.domainReferenced**: user directory or AD/LDAP domain names.
- **service.target.entity.relationships.supervises.user.emailReferenced**: user email addresses.
- **service.target.entity.relationships.supervises.user.idReferenced**: user ids.
- **service.target.entity.relationships.supervises.user.nameReferenced**: user short names or logins.
- **service.target.entity.source**: Source module or integration that provided the entity data.
- **service.target.entity.sub_type**: The specific type designation for the entity as defined by its provider or system.
- **service.target.entity.type**: Standardized high-level classification of the entity.
- **service.target.environment**: Environment of the service.
- **service.target.ephemeral_id**: Ephemeral identifier of this service.
- **service.target.id**: Unique identifier of the running service.
- **service.target.name**: Name of the service.
- **service.target.node.name**: Name of the service node.
- **service.target.node.role**: Deprecated role (singular) of the service node.
- **service.target.node.roles**: Roles of the service node.
- **service.target.state**: Current state of the service.
- **service.target.type**: The type of the service.
- **service.target.version**: Version of the service.
- **service.type**: The type of the service.
- **service.version**: Version of the service.

source

- **source.address**: Source network address.
- **source.as.number**: Unique number allocated to the autonomous system.
- **source.as.organization.name**: Organization name.
- **source.as.organization.name.text**: Organization name.
- **source.bytes**: Bytes sent from the source to the destination.
- **source.domain**: The domain name of the source.
- **source.geo.city_name**: City name.
- **source.geo.continent_code**: Continent code.

- **source.geo.continent_name**: Name of the continent.
- **source.geo.country_iso_code**: Country ISO code.
- **source.geo.country_name**: Country name.
- **source.geo.location**: Longitude and latitude.
- **source.geo.name**: User-defined description of a location.
- **source.geo.postal_code**: Postal code.
- **source.geo.region_iso_code**: Region ISO code.
- **source.geo.region_name**: Region name.
- **source.geo.timezone**: Time zone.
- **source.ip**: IP address of the source.
- **source.mac**: MAC address of the source.
- **source.nat.ip**: Source NAT ip
- **source.nat.port**: Source NAT port
- **source.packets**: Packets sent from the source to the destination.
- **source.port**: Port of the source.
- **source.registered_domain**: The highest registered source domain, stripped of the subdomain.
- **source.subdomain**: The subdomain of the domain.
- **source.top_level_domain**: The effective top level domain (com, org, net, co.uk).
- **source.user.domain**: Name of the directory the user is a member of.
- **source.user.email**: User email address.
- **source.user.full_name**: User's full name, if available.
- **source.user.full_name.text**: User's full name, if available.
- **source.user.group.domain**: Name of the directory the group is a member of.
- **source.user.group.id**: Unique identifier for the group on the system/platform.
- **source.user.group.name**: Name of the group.
- **source.user.hash**: Unique user hash to correlate information for a user in anonymized form.
- **source.user.id**: Unique identifier of the user.
- **source.user.name**: Short name or login of the user.
- **source.user.name.text**: Short name or login of the user.
- **source.user.roles**: Array of user roles at the time of the event.

span

- **span.id**: Unique identifier of the span within the scope of its trace.

threat

- **threat.enrichments**: List of objects containing indicators enriching the event.
- **threat.enrichments.indicator**: Object containing indicators enriching the event.
- **threat.enrichments.indicator.as.number**: Unique number allocated to the autonomous system.

- **threat.enrichments.indicator.as.organization.nameOrganization**: name.
- **threat.enrichments.indicator.as.organization.name.textOrganization**: name.
- **threat.enrichments.indicator.confidence**: Indicator confidence rating
- **threat.enrichments.indicator.description**: Indicator description
- **threat.enrichments.indicator.email.address**: Indicator email address
- **threat.enrichments.indicator.file.accessed**: Last time the file was accessed.
- **threat.enrichments.indicator.file.attributes**: Array of file attributes.
- **threat.enrichments.indicator.file.code_signature.digest_algorithmHashing**: algorithm used to sign the process.
- **threat.enrichments.indicator.file.code_signature.existsBoolean**: to capture if a signature is present.
- **threat.enrichments.indicator.file.code_signature.flagsCode**: signing flags of the process
- **threat.enrichments.indicator.file.code_signature.signing_idThe**: identifier used to sign the process.
- **threat.enrichments.indicator.file.code_signature.statusAdditional**: information about the certificate status.
- **threat.enrichments.indicator.file.code_signature.subject_nameSubject**: name of the code signer
- **threat.enrichments.indicator.file.code_signature.team_idThe**: team identifier used to sign the process.
- **threat.enrichments.indicator.file.code_signature.thumbprint_sha256SHA256**: hash of the certificate.
- **threat.enrichments.indicator.file.code_signature.timestampWhen**: the signature was generated and signed.
- **threat.enrichments.indicator.file.code_signature.trustedStores**: the trust status of the certificate chain.
- **threat.enrichments.indicator.file.code_signature.validBoolean**: to capture if the digital signature is verified against the binary content.
- **threat.enrichments.indicator.file.created**: File creation time.
- **threat.enrichments.indicator.file.ctime**: Last time the file attributes or metadata changed.
- **threat.enrichments.indicator.file.device**: Device that is the source of the file.
- **threat.enrichments.indicator.file.directory**: Directory where the file is located.
- **threat.enrichments.indicator.file.drive_letter**: Drive letter where the file is located.
- **threat.enrichments.indicator.file.elf.architectureMachine**: architecture of the ELF file.
- **threat.enrichments.indicator.file.elf.byte_orderByte**: sequence of ELF file.
- **threat.enrichments.indicator.file.elf.cpu_typeCPU**: type of the ELF file.
- **threat.enrichments.indicator.file.elf.creation_dateBuild**: or compile date.
- **threat.enrichments.indicator.file.elf.exports**: List of exported element names and types.
- **threat.enrichments.indicator.file.elf.go_import_hashA**: hash of the Go language imports in an ELF file.

- **threat.enrichments.indicator.file.elf.go_importsList**: of imported Go language element names and types.
- **threat.enrichments.indicator.file.elf.go_imports_names_entropyShannon**: entropy calculation from the list of Go imports.
- **threat.enrichments.indicator.file.elf.go_imports_names_var_entropyVariance**: for Shannon entropy calculation from the list of Go imports.
- **threat.enrichments.indicator.file.elf.go_strippedWhether**: the file is a stripped or obfuscated Go executable.
- **threat.enrichments.indicator.file.elf.header.abi_versionVersion**: of the ELF Application Binary Interface (ABI).
- **threat.enrichments.indicator.file.elf.header.classHeader**: class of the ELF file.
- **threat.enrichments.indicator.file.elf.header.dataData**: table of the ELF header.
- **threat.enrichments.indicator.file.elf.header.entrypointHeader**: entrypoint of the ELF file.
- **threat.enrichments.indicator.file.elf.header.os_abiApplication**: Binary Interface (ABI) of the Linux OS.
- **threat.enrichments.indicator.file.elf.header.typeHeader**: type of the ELF file.
- **threat.enrichments.indicator.file.elf.header.versionVersion**: of the ELF header.
- **threat.enrichments.indicator.file.elf.import_hashA**: hash of the imports in an ELF file.
- **threat.enrichments.indicator.file.elf.imports**: List of imported element names and types.
- **threat.enrichments.indicator.file.elf.imports_names_entropyShannon**: entropy calculation from the list of imported element names and types.
- **threat.enrichments.indicator.file.elf.imports_names_var_entropyVariance**: for Shannon entropy calculation from the list of imported element names and types.
- **threat.enrichments.indicator.file.elf.sections**: Section information of the ELF file.
- **threat.enrichments.indicator.file.elf.sections.entropyShannon**: entropy calculation from the section.
- **threat.enrichments.indicator.file.elf.sections.flagsELF**: Section List flags.
- **threat.enrichments.indicator.file.elf.sections.nameELF**: Section List name.
- **threat.enrichments.indicator.file.elf.sections.physical_offsetELF**: Section List offset.
- **threat.enrichments.indicator.file.elf.sections.physical_sizeELF**: Section List physical size.
- **threat.enrichments.indicator.file.elf.sections.typeELF**: Section List type.
- **threat.enrichments.indicator.file.elf.sections.var_entropyVariance**: for Shannon entropy calculation from the section.
- **threat.enrichments.indicator.file.elf.sections.virtual_addressELF**: Section List virtual address.
- **threat.enrichments.indicator.file.elf.sections.virtual_sizeELF**: Section List virtual size.
- **threat.enrichments.indicator.file.elf.segmentsELF**: object segment list.
- **threat.enrichments.indicator.file.elf.segments.sectionsELF**: object segment sections.

- **threat.enrichments.indicator.file.elf.segments.typeELF**: object segment type.
- **threat.enrichments.indicator.file.elf.shared_librariesList**: of shared libraries used by this ELF object.
- **threat.enrichments.indicator.file.elf.telfhash**: telfhash hash for ELF file.
- **threat.enrichments.indicator.file.extension**: File extension, excluding the leading dot.
- **threat.enrichments.indicator.file.fork_name**: A fork is additional data associated with a filesystem object.
- **threat.enrichments.indicator.file.gid**: Primary group ID (GID) of the file.
- **threat.enrichments.indicator.file.group**: Primary group name of the file.
- **threat.enrichments.indicator.file.hash.cdhashThe**: Code Directory (CD) hash of an executable.
- **threat.enrichments.indicator.file.hash.md5**: MD5 hash.
- **threat.enrichments.indicator.file.hash.sha1**: SHA1 hash.
- **threat.enrichments.indicator.file.hash.sha256SHA256**: hash.
- **threat.enrichments.indicator.file.hash.sha384SHA384**: hash.
- **threat.enrichments.indicator.file.hash.sha512SHA512**: hash.
- **threat.enrichments.indicator.file.hash.ssdeepSSDEEP**: hash.
- **threat.enrichments.indicator.file.hash.tlsh**: TLSH hash.
- **threat.enrichments.indicator.file.inode**: Inode representing the file in the filesystem.
- **threat.enrichments.indicator.file.mime_type**: Media type of file, document, or arrangement of bytes.
- **threat.enrichments.indicator.file.mode**: Mode of the file in octal representation.
- **threat.enrichments.indicator.file.mtime**: Last time the file content was modified.
- **threat.enrichments.indicator.file.name**: Name of the file including the extension, without the directory.
- **threat.enrichments.indicator.file.origin_referrer_urlThe**: URL of the webpage that linked to the file.
- **threat.enrichments.indicator.file.origin_url**: The URL where the file is hosted.
- **threat.enrichments.indicator.file.owner**: File owner's username.
- **threat.enrichments.indicator.file.path**: Full path to the file, including the file name.
- **threat.enrichments.indicator.file.path.text**: Full path to the file, including the file name.
- **threat.enrichments.indicator.file.pe.architectureCPU**: architecture target for the file.
- **threat.enrichments.indicator.file.pe.companyInternal**: company name of the file, provided at compile-time.
- **threat.enrichments.indicator.file.pe.descriptionInternal**: description of the file, provided at compile-time.
- **threat.enrichments.indicator.file.pe.file_versionProcess**: name.
- **threat.enrichments.indicator.file.pe.go_import_hashA**: hash of the Go language imports in a PE file.
- **threat.enrichments.indicator.file.pe.go_importsList**: of imported Go language element names and types.
- **threat.enrichments.indicator.file.pe.go_imports_names_entropyShannon**: entropy calculation from the list of Go imports.

- **threat.enrichments.indicator.file.pe.go_imports_names_var_entropyVariance**: for Shannon entropy calculation from the list of Go imports.
- **threat.enrichments.indicator.file.pe.go_strippedWhether**: the file is a stripped or obfuscated Go executable.
- **threat.enrichments.indicator.file.pe.imphash**: A hash of the imports in a PE file.
- **threat.enrichments.indicator.file.pe.import_hashA**: hash of the imports in a PE file.
- **threat.enrichments.indicator.file.pe.imports**: List of imported element names and types.
- **threat.enrichments.indicator.file.pe.imports_names_entropyShannon**: entropy calculation from the list of imported element names and types.
- **threat.enrichments.indicator.file.pe.imports_names_var_entropyVariance**: for Shannon entropy calculation from the list of imported element names and types.
- **threat.enrichments.indicator.file.pe.original_file_nameInternal**: name of the file, provided at compile-time.
- **threat.enrichments.indicator.file.pe.pehash**: A hash of the PE header and data from one or more PE sections.
- **threat.enrichments.indicator.file.pe.product**: Internal product name of the file, provided at compile-time.
- **threat.enrichments.indicator.file.pe.sections**: Section information of the PE file.
- **threat.enrichments.indicator.file.pe.sections_entropyShannon**: entropy calculation from the section.
- **threat.enrichments.indicator.file.pe.sections.namePE**: Section List name.
- **threat.enrichments.indicator.file.pe.sections.physical_sizePE**: Section List physical size.
- **threat.enrichments.indicator.file.pe.sections.var_entropyVariance**: for Shannon entropy calculation from the section.
- **threat.enrichments.indicator.file.pe.sections.virtual_sizePE**: Section List virtual size. This is always the same as **physical_size**.
- **threat.enrichments.indicator.file.size**: File size in bytes.
- **threat.enrichments.indicator.file.target_path**: Target path for symlinks.
- **threat.enrichments.indicator.file.target_path.textTarget**: path for symlinks.
- **threat.enrichments.indicator.file.type**: File type (file, dir, or symlink).
- **threat.enrichments.indicator.file.uid**: The user ID (UID) or security identifier (SID) of the file owner.
- **threat.enrichments.indicator.file.x509.alternative_namesList**: of subject alternative names (SAN).
- **threat.enrichments.indicator.file.x509.issuer.common_nameList**: of common name (CN) of issuing certificate authority.
- **threat.enrichments.indicator.file.x509.issuer.countryList**: of country (C) codes
- **threat.enrichments.indicator.file.x509.issuer.distinguished_nameDistinguished**: name (DN) of issuing certificate authority.
- **threat.enrichments.indicator.file.x509.issuer.localityList**: of locality names (L)

- **threat.enrichments.indicator.file.x509.issuer.organizationList**: of organizations (O) of issuing certificate authority.
- **threat.enrichments.indicator.file.x509.issuer.organizational_unitList**: of organizational units (OU) of issuing certificate authority.
- **threat.enrichments.indicator.file.x509.issuer.state_or_provinceList**: of state or province names (ST, S, or P)
- **threat.enrichments.indicator.file.x509.not_afterTime**: at which the certificate is no longer considered valid.
- **threat.enrichments.indicator.file.x509.not_beforeTime**: at which the certificate is first considered valid.
- **threat.enrichments.indicator.file.x509.public_key_algorithmAlgorithm**: used to generate the public key.
- **threat.enrichments.indicator.file.x509.public_key_curveThe**: curve used by the elliptic curve public key algorithm. This is algorithm specific.
- **threat.enrichments.indicator.file.x509.public_key_exponentExponent**: used to derive the public key. This is algorithm specific.
- **threat.enrichments.indicator.file.x509.public_key_sizeThe**: size of the public key space in bits.
- **threat.enrichments.indicator.file.x509.serial_numberUnique**: serial number issued by the certificate authority.
- **threat.enrichments.indicator.file.x509.signature_algorithmIdentifier**: for certificate signature algorithm.
- **threat.enrichments.indicator.file.x509.subject.common_nameList**: of common names (CN) of subject.
- **threat.enrichments.indicator.file.x509.subject.countryList**: of country (C) code
- **threat.enrichments.indicator.file.x509.subject.distinguished_nameDistinguished**: name (DN) of the certificate subject entity.
- **threat.enrichments.indicator.file.x509.subject.localityList**: of locality names (L)
- **threat.enrichments.indicator.file.x509.subject.organizationList**: of organizations (O) of subject.
- **threat.enrichments.indicator.file.x509.subject.organizational_unitList**: of organizational units (OU) of subject.
- **threat.enrichments.indicator.file.x509.subject.state_or_provinceList**: of state or province names (ST, S, or P)
- **threat.enrichments.indicator.file.x509.version_numberVersion**: of x509 format.
- **threat.enrichments.indicator.first_seen**: Date/time indicator was first reported.
- **threat.enrichments.indicator.geo.city_name**: City name.
- **threat.enrichments.indicator.geo.continent_codeContinent**: code.
- **threat.enrichments.indicator.geo.continent_nameName**: of the continent.
- **threat.enrichments.indicator.geo.country_iso_codeCountry**: ISO code.
- **threat.enrichments.indicator.geo.country_nameCountry**: name.
- **threat.enrichments.indicator.geo.location**: Longitude and latitude.
- **threat.enrichments.indicator.geo.name**: User-defined description of a location.

- **threat.enrichments.indicator.geo.postal_codePostal**: code.
- **threat.enrichments.indicator.geo.region_iso_codeRegion**: ISO code.
- **threat.enrichments.indicator.geo.region_nameRegion**: name.
- **threat.enrichments.indicator.geo.timezone**: Time zone.
- **threat.enrichments.indicator.ip**: Indicator IP address
- **threat.enrichments.indicator.last_seen**: Date/time indicator was last reported.
- **threat.enrichments.indicator.marking.tlp**: Indicator TLP marking
- **threat.enrichments.indicator.marking.tlp_versionIndicator**: TLP version
- **threat.enrichments.indicator.modified_at**: Date/time indicator was last updated.
- **threat.enrichments.indicator.name**: Indicator display name
- **threat.enrichments.indicator.port**: Indicator port
- **threat.enrichments.indicator.provider**: Indicator provider
- **threat.enrichments.indicator.reference**: Indicator reference URL
- **threat.enrichments.indicator.registry.data.bytesOriginal**: bytes written with base64 encoding.
- **threat.enrichments.indicator.registry.data.stringsList**: of strings representing what was written to the registry.
- **threat.enrichments.indicator.registry.data.typeStandard**: registry type for encoding contents
- **threat.enrichments.indicator.registry.hive**: Abbreviated name for the hive.
- **threat.enrichments.indicator.registry.key**: Hive-relative path of keys.
- **threat.enrichments.indicator.registry.path**: Full path, including hive, key and value
- **threat.enrichments.indicator.registry.value**: Name of the value written.
- **threat.enrichments.indicator.scanner_stats**: Scanner statistics
- **threat.enrichments.indicator.sightings**: Number of times indicator observed
- **threat.enrichments.indicator.type**: Type of indicator
- **threat.enrichments.indicator.url.domain**: Domain of the url.
- **threat.enrichments.indicator.url.extension**: File extension from the request url, excluding the leading dot.
- **threat.enrichments.indicator.url.fragment**: Portion of the url after the #.
- **threat.enrichments.indicator.url.full**: Full unparsed URL.
- **threat.enrichments.indicator.url.full.text**: Full unparsed URL.
- **threat.enrichments.indicator.url.original**: Unmodified original url as seen in the event source.
- **threat.enrichments.indicator.url.original.text**: Unmodified original url as seen in the event source.
- **threat.enrichments.indicator.url.password**: Password of the request.
- **threat.enrichments.indicator.url.path**: Path of the request, such as "/search".
- **threat.enrichments.indicator.url.port**: Port of the request, such as 443.
- **threat.enrichments.indicator.url.query**: Query string of the request.
- **threat.enrichments.indicator.url.registered_domainThe**: highest registered url domain, stripped of the subdomain.
- **threat.enrichments.indicator.url.scheme**: Scheme of the url.

- **threat.enrichments.indicator.url.subdomain**: The subdomain of the domain.
- **threat.enrichments.indicator.url.top_level_domain**The: effective top level domain (com, org, net, co.uk).
- **threat.enrichments.indicator.url.username**: Username of the request.
- **threat.enrichments.indicator.x509.alternative_namesList**: of subject alternative names (SAN).
- **threat.enrichments.indicator.x509.issuer.common_nameList**: of common name (CN) of issuing certificate authority.
- **threat.enrichments.indicator.x509.issuer.countryList**: of country (C) codes
- **threat.enrichments.indicator.x509.issuer.distinguished_nameDistinguished**: name (DN) of issuing certificate authority.
- **threat.enrichments.indicator.x509.issuer.localityList**: of locality names (L)
- **threat.enrichments.indicator.x509.issuer.organizationList**: of organizations (O) of issuing certificate authority.
- **threat.enrichments.indicator.x509.issuer.organizational_unitList**: of organizational units (OU) of issuing certificate authority.
- **threat.enrichments.indicator.x509.issuer.state_or_provinceList**: of state or province names (ST, S, or P)
- **threat.enrichments.indicator.x509.not_after**: Time at which the certificate is no longer considered valid.
- **threat.enrichments.indicator.x509.not_beforeTime**: at which the certificate is first considered valid.
- **threat.enrichments.indicator.x509.public_key_algorithmAlgorithm**: used to generate the public key.
- **threat.enrichments.indicator.x509.public_key_curveThe**: curve used by the elliptic curve public key algorithm. This is algorithm specific.
- **threat.enrichments.indicator.x509.public_key_exponentExponent**: used to derive the public key. This is algorithm specific.
- **threat.enrichments.indicator.x509.public_key_sizeThe**: size of the public key space in bits.
- **threat.enrichments.indicator.x509.serial_numberUnique**: serial number issued by the certificate authority.
- **threat.enrichments.indicator.x509.signature_algorithmIdentifier**: for certificate signature algorithm.
- **threat.enrichments.indicator.x509.subject.common_nameList**: of common names (CN) of subject.
- **threat.enrichments.indicator.x509.subject.countryList**: of country (C) code
- **threat.enrichments.indicator.x509.subject.distinguished_nameDistinguished**: name (DN) of the certificate subject entity.
- **threat.enrichments.indicator.x509.subject.localityList**: of locality names (L)
- **threat.enrichments.indicator.x509.subject.organizationList**: of organizations (O) of subject.

- **threat.enrichments.indicator.x509.subject.organizational_unitList**: of organizational units (OU) of subject.
- **threat.enrichments.indicator.x509.subject.state_or_provinceList**: of state or province names (ST, S, or P)
- **threat.enrichments.indicator.x509.version_numberVersion**: of x509 format.
- **threat.enrichments.matched.atomic**: Matched indicator value
- **threat.enrichments.matched.field**: Matched indicator field
- **threat.enrichments.matched.id**: Matched indicator identifier
- **threat.enrichments.matched.index**: Matched indicator index
- **threat.enrichments.matched.occurred**: Date of match
- **threat.enrichments.matched.type**: Type of indicator match
- **threat.feed.dashboard_id**: Feed dashboard ID.
- **threat.feed.description**: Description of the threat feed.
- **threat.feed.name**: Name of the threat feed.
- **threat.feed.reference**: Reference for the threat feed.
- **threat.framework**: Threat classification framework.
- **threat.group.alias**: Alias of the group.
- **threat.group.id**: ID of the group.
- **threat.group.name**: Name of the group.
- **threat.group.reference**: Reference URL of the group.
- **threat.indicator.as.number**: Unique number allocated to the autonomous system.
- **threat.indicator.as.organization.name**: Organization name.
- **threat.indicator.as.organization.name.text**: Organization name.
- **threat.indicator.confidence**: Indicator confidence rating
- **threat.indicator.description**: Indicator description
- **threat.indicator.email.address**: Indicator email address
- **threat.indicator.file.accessed**: Last time the file was accessed.
- **threat.indicator.file.attributes**: Array of file attributes.
- **threat.indicator.file.code_signature.digest_algorithmHashing**: algorithm used to sign the process.
- **threat.indicator.file.code_signature.exists**: Boolean to capture if a signature is present.
- **threat.indicator.file.code_signature.flags**: Code signing flags of the process
- **threat.indicator.file.code_signature.signing_idThe**: identifier used to sign the process.
- **threat.indicator.file.code_signature.status**: Additional information about the certificate status.
- **threat.indicator.file.code_signature.subject_nameSubject**: name of the code signer
- **threat.indicator.file.code_signature.team_id**: The team identifier used to sign the process.
- **threat.indicator.file.code_signature.thumbprint_sha256SHA256**: hash of the certificate.

- **threat.indicator.file.code_signature.timestampWhen**: the signature was generated and signed.
- **threat.indicator.file.code_signature.trusted**: Stores the trust status of the certificate chain.
- **threat.indicator.file.code_signature.valid**: Boolean to capture if the digital signature is verified against the binary content.
- **threat.indicator.file.created**: File creation time.
- **threat.indicator.file.ctime**: Last time the file attributes or metadata changed.
- **threat.indicator.file.device**: Device that is the source of the file.
- **threat.indicator.file.directory**: Directory where the file is located.
- **threat.indicator.file.drive_letter**: Drive letter where the file is located.
- **threat.indicator.file.elf.architecture**: Machine architecture of the ELF file.
- **threat.indicator.file.elf.byte_order**: Byte sequence of ELF file.
- **threat.indicator.file.elf.cpu_type**: CPU type of the ELF file.
- **threat.indicator.file.elf.creation_date**: Build or compile date.
- **threat.indicator.file.elf.exports**: List of exported element names and types.
- **threat.indicator.file.elf.go_import_hash**: A hash of the Go language imports in an ELF file.
- **threat.indicator.file.elf.go_imports**: List of imported Go language element names and types.
- **threat.indicator.file.elf.go_imports_names_entropyShannon**: entropy calculation from the list of Go imports.
- **threat.indicator.file.elf.go_imports_names_var_entropyVariance**: for Shannon entropy calculation from the list of Go imports.
- **threat.indicator.file.elf.go_stripped**: Whether the file is a stripped or obfuscated Go executable.
- **threat.indicator.file.elf.header.abi_version**: Version of the ELF Application Binary Interface (ABI).
- **threat.indicator.file.elf.header.class**: Header class of the ELF file.
- **threat.indicator.file.elf.header.data**: Data table of the ELF header.
- **threat.indicator.file.elf.header.entrypoint**: Header entrypoint of the ELF file.
- **threat.indicator.file.elf.header.os_abi**: Application Binary Interface (ABI) of the Linux OS.
- **threat.indicator.file.elf.header.type**: Header type of the ELF file.
- **threat.indicator.file.elf.header.version**: Version of the ELF header.
- **threat.indicator.file.elf.import_hash**: A hash of the imports in an ELF file.
- **threat.indicator.file.elf.imports**: List of imported element names and types.
- **threat.indicator.file.elf.imports_names_entropyShannon**: entropy calculation from the list of imported element names and types.
- **threat.indicator.file.elf.imports_names_var_entropyVariance**: for Shannon entropy calculation from the list of imported element names and types.
- **threat.indicator.file.elf.sections**: Section information of the ELF file.
- **threat.indicator.file.elf.sections.chi2**: Chi-square probability distribution of the section.

- **threat.indicator.file.elf.sections.entropy**: Shannon entropy calculation from the section.
- **threat.indicator.file.elf.sections.flags**: ELF Section List flags.
- **threat.indicator.file.elf.sections.name**: ELF Section List name.
- **threat.indicator.file.elf.sections.physical_offsetELF**: Section List offset.
- **threat.indicator.file.elf.sections.physical_sizeELF**: Section List physical size.
- **threat.indicator.file.elf.sections.type**: ELF Section List type.
- **threat.indicator.file.elf.sections.var_entropy**: Variance for Shannon entropy calculation from the section.
- **threat.indicator.file.elf.sections.virtual_addressELF**: Section List virtual address.
- **threat.indicator.file.elf.sections.virtual_size**: ELF Section List virtual size.
- **threat.indicator.file.elf.segments**: ELF object segment list.
- **threat.indicator.file.elf.segments.sections**: ELF object segment sections.
- **threat.indicator.file.elf.segments.type**: ELF object segment type.
- **threat.indicator.file.elf.shared_libraries**: List of shared libraries used by this ELF object.
- **threat.indicator.file.elf.telfhash**: telfhash hash for ELF file.
- **threat.indicator.file.extension**: File extension, excluding the leading dot.
- **threat.indicator.file.fork_name**: A fork is additional data associated with a filesystem object.
- **threat.indicator.file.gid**: Primary group ID (GID) of the file.
- **threat.indicator.file.group**: Primary group name of the file.
- **threat.indicator.file.hash.cdhash**: The Code Directory (CD) hash of an executable.
- **threat.indicator.file.hash.md5**: MD5 hash.
- **threat.indicator.file.hash.sha1**: SHA1 hash.
- **threat.indicator.file.hash.sha256**: SHA256 hash.
- **threat.indicator.file.hash.sha384**: SHA384 hash.
- **threat.indicator.file.hash.sha512**: SHA512 hash.
- **threat.indicator.file.hash.ssdeep**: SSDEEP hash.
- **threat.indicator.file.hash.tlsh**: TLSH hash.
- **threat.indicator.file.inode**: Inode representing the file in the filesystem.
- **threat.indicator.file.mime_type**: Media type of file, document, or arrangement of bytes.
- **threat.indicator.file.mode**: Mode of the file in octal representation.
- **threat.indicator.file.mtime**: Last time the file content was modified.
- **threat.indicator.file.name**: Name of the file including the extension, without the directory.
- **threat.indicator.file.origin_referrer_url**: The URL of the webpage that linked to the file.
- **threat.indicator.file.origin_url**: The URL where the file is hosted.
- **threat.indicator.file.owner**: File owner's username.
- **threat.indicator.file.path**: Full path to the file, including the file name.
- **threat.indicator.file.path.text**: Full path to the file, including the file name.
- **threat.indicator.file.pe.architecture**: CPU architecture target for the file.

- **threat.indicator.file.pe.company**: Internal company name of the file, provided at compile-time.
- **threat.indicator.file.pe.description**: Internal description of the file, provided at compile-time.
- **threat.indicator.file.pe.file_version**: Process name.
- **threat.indicator.file.pe.go_import_hash**: A hash of the Go language imports in a PE file.
- **threat.indicator.file.pe.go_imports**: List of imported Go language element names and types.
- **threat.indicator.file.pe.go_imports_names_entropyShannon**: entropy calculation from the list of Go imports.
- **threat.indicator.file.pe.go_imports_names_var_entropyVariance**: for Shannon entropy calculation from the list of Go imports.
- **threat.indicator.file.pe.go_stripped**: Whether the file is a stripped or obfuscated Go executable.
- **threat.indicator.file.pe.imphash**: A hash of the imports in a PE file.
- **threat.indicator.file.pe.import_hash**: A hash of the imports in a PE file.
- **threat.indicator.file.pe.imports**: List of imported element names and types.
- **threat.indicator.file.pe.imports_names_entropyShannon**: entropy calculation from the list of imported element names and types.
- **threat.indicator.file.pe.imports_names_var_entropyVariance**: for Shannon entropy calculation from the list of imported element names and types.
- **threat.indicator.file.pe.original_file_name**: Internal name of the file, provided at compile-time.
- **threat.indicator.file.pe.pehash**: A hash of the PE header and data from one or more PE sections.
- **threat.indicator.file.pe.product**: Internal product name of the file, provided at compile-time.
- **threat.indicator.file.pe.sections**: Section information of the PE file.
- **threat.indicator.file.pe.sections.entropy**: Shannon entropy calculation from the section.
- **threat.indicator.file.pe.sections.name**: PE Section List name.
- **threat.indicator.file.pe.sections.physical_sizePE**: Section List physical size.
- **threat.indicator.file.pe.sections.var_entropy**: Variance for Shannon entropy calculation from the section.
- **threat.indicator.file.pe.sections.virtual_size**: PE Section List virtual size. This is always the same as **physical_size**.
- **threat.indicator.file.size**: File size in bytes.
- **threat.indicator.file.target_path**: Target path for symlinks.
- **threat.indicator.file.target_path.text**: Target path for symlinks.
- **threat.indicator.file.type**: File type (file, dir, or symlink).
- **threat.indicator.file.uid**: The user ID (UID) or security identifier (SID) of the file owner.
- **threat.indicator.file.x509.alternative_names**: List of subject alternative names (SAN).

- **threat.indicator.file.x509.issuer.common_nameList**: of common name (CN) of issuing certificate authority.
- **threat.indicator.file.x509.issuer.country**: List of country (C) codes
- **threat.indicator.file.x509.issuer.distinguished_nameDistinguished**: name (DN) of issuing certificate authority.
- **threat.indicator.file.x509.issuer.locality**: List of locality names (L)
- **threat.indicator.file.x509.issuer.organization**: List of organizations (O) of issuing certificate authority.
- **threat.indicator.file.x509.issuer.organizational_unitList**: of organizational units (OU) of issuing certificate authority.
- **threat.indicator.file.x509.issuer.state_or_provinceList**: of state or province names (ST, S, or P)
- **threat.indicator.file.x509.not_after**: Time at which the certificate is no longer considered valid.
- **threat.indicator.file.x509.not_before**: Time at which the certificate is first considered valid.
- **threat.indicator.file.x509.public_key_algorithmAlgorithm**: used to generate the public key.
- **threat.indicator.file.x509.public_key_curve**: The curve used by the elliptic curve public key algorithm. This is algorithm specific.
- **threat.indicator.file.x509.public_key_exponentExponent**: used to derive the public key. This is algorithm specific.
- **threat.indicator.file.x509.public_key_size**: The size of the public key space in bits.
- **threat.indicator.file.x509.serial_number**: Unique serial number issued by the certificate authority.
- **threat.indicator.file.x509.signature_algorithmIdentifier**: for certificate signature algorithm.
- **threat.indicator.file.x509.subject.common_nameList**: of common names (CN) of subject.
- **threat.indicator.file.x509.subject.country**: List of country (C) code
- **threat.indicator.file.x509.subject.distinguished_nameDistinguished**: name (DN) of the certificate subject entity.
- **threat.indicator.file.x509.subject.locality**: List of locality names (L)
- **threat.indicator.file.x509.subject.organizationList**: of organizations (O) of subject.
- **threat.indicator.file.x509.subject.organizational_unitList**: of organizational units (OU) of subject.
- **threat.indicator.file.x509.subject.state_or_provinceList**: of state or province names (ST, S, or P)
- **threat.indicator.file.x509.version_number**: Version of x509 format.
- **threat.indicator.first_seen**: Date/time indicator was first reported.
- **threat.indicator.geo.city_name**: City name.
- **threat.indicator.geo.continent_code**: Continent code.
- **threat.indicator.geo.continent_name**: Name of the continent.

- **threat.indicator.geo.country_iso_code**: Country ISO code.
- **threat.indicator.geo.country_name**: Country name.
- **threat.indicator.geo.location**: Longitude and latitude.
- **threat.indicator.geo.name**: User-defined description of a location.
- **threat.indicator.geo.postal_code**: Postal code.
- **threat.indicator.geo.region_iso_code**: Region ISO code.
- **threat.indicator.geo.region_name**: Region name.
- **threat.indicator.geo.timezone**: Time zone.
- **threat.indicator.id**: ID of the indicator
- **threat.indicator.ip**: Indicator IP address
- **threat.indicator.last_seen**: Date/time indicator was last reported.
- **threat.indicator.marking.tlp**: Indicator TLP marking
- **threat.indicator.marking.tlp_version**: Indicator TLP version
- **threat.indicator.modified_at**: Date/time indicator was last updated.
- **threat.indicator.name**: Indicator display name
- **threat.indicator.port**: Indicator port
- **threat.indicator.provider**: Indicator provider
- **threat.indicator.reference**: Indicator reference URL
- **threat.indicator.registry.data.bytes**: Original bytes written with base64 encoding.
- **threat.indicator.registry.data.strings**: List of strings representing what was written to the registry.
- **threat.indicator.registry.data.type**: Standard registry type for encoding contents
- **threat.indicator.registry.hive**: Abbreviated name for the hive.
- **threat.indicator.registry.key**: Hive-relative path of keys.
- **threat.indicator.registry.path**: Full path, including hive, key and value
- **threat.indicator.registry.value**: Name of the value written.
- **threat.indicator.scanner_stats**: Scanner statistics
- **threat.indicator.sightings**: Number of times indicator observed
- **threat.indicator.type**: Type of indicator
- **threat.indicator.url.domain**: Domain of the url.
- **threat.indicator.url.extension**: File extension from the request url, excluding the leading dot.
- **threat.indicator.url.fragment**: Portion of the url after the #.
- **threat.indicator.url.full**: Full unparsed URL.
- **threat.indicator.url.full.text**: Full unparsed URL.
- **threat.indicator.url.original**: Unmodified original url as seen in the event source.
- **threat.indicator.url.original.text**: Unmodified original url as seen in the event source.
- **threat.indicator.url.password**: Password of the request.
- **threat.indicator.url.path**: Path of the request, such as "/search".
- **threat.indicator.url.port**: Port of the request, such as 443.
- **threat.indicator.url.query**: Query string of the request.
- **threat.indicator.url.registered_domain**: The highest registered url domain, stripped of the subdomain.

- **threat.indicator.url.scheme**: Scheme of the url.
- **threat.indicator.url.subdomain**: The subdomain of the domain.
- **threat.indicator.url.top_level_domain**: The effective top level domain (com, org, net, co.uk).
- **threat.indicator.url.username**: Username of the request.
- **threat.indicator.x509.alternative_names**: List of subject alternative names (SAN).
- **threat.indicator.x509.issuer.common_name**: List of common name (CN) of issuing certificate authority.
- **threat.indicator.x509.issuer.country**: List of country (C) codes
- **threat.indicator.x509.issuer.distinguished_nameDistinguished**: name (DN) of issuing certificate authority.
- **threat.indicator.x509.issuer.locality**: List of locality names (L)
- **threat.indicator.x509.issuer.organization**: List of organizations (O) of issuing certificate authority.
- **threat.indicator.x509.issuer.organizational_unitList**: of organizational units (OU) of issuing certificate authority.
- **threat.indicator.x509.issuer.state_or_provinceList**: of state or province names (ST, S, or P)
- **threat.indicator.x509.not_after**: Time at which the certificate is no longer considered valid.
- **threat.indicator.x509.not_before**: Time at which the certificate is first considered valid.
- **threat.indicator.x509.public_key_algorithm**: Algorithm used to generate the public key.
- **threat.indicator.x509.public_key_curve**: The curve used by the elliptic curve public key algorithm. This is algorithm specific.
- **threat.indicator.x509.public_key_exponent**: Exponent used to derive the public key. This is algorithm specific.
- **threat.indicator.x509.public_key_size**: The size of the public key space in bits.
- **threat.indicator.x509.serial_number**: Unique serial number issued by the certificate authority.
- **threat.indicator.x509.signature_algorithm**: Identifier for certificate signature algorithm.
- **threat.indicator.x509.subject.common_nameList**: of common names (CN) of subject.
- **threat.indicator.x509.subject.country**: List of country (C) code
- **threat.indicator.x509.subject.distinguished_nameDistinguished**: name (DN) of the certificate subject entity.
- **threat.indicator.x509.subject.locality**: List of locality names (L)
- **threat.indicator.x509.subject.organization**: List of organizations (O) of subject.
- **threat.indicator.x509.subject.organizational_unitList**: of organizational units (OU) of subject.
- **threat.indicator.x509.subject.state_or_provinceList**: of state or province names (ST, S, or P)
- **threat.indicator.x509.version_number**: Version of x509 format.
- **threat.software.alias**: Alias of the software

- **threat.software.id**: ID of the software
- **threat.software.name**: Name of the software.
- **threat.software.platforms**: Platforms of the software.
- **threat.software.reference**: Software reference URL.
- **threat.software.type**: Software type.
- **threat.tactic.id**: Threat tactic id.
- **threat.tactic.name**: Threat tactic.
- **threat.tactic.reference**: Threat tactic URL reference.
- **threat.technique.id**: Threat technique id.
- **threat.technique.name**: Threat technique name.
- **threat.technique.name.text**: Threat technique name.
- **threat.technique.reference**: Threat technique URL reference.
- **threat.technique.subtechnique.id**: Threat subtechnique id.
- **threat.technique.subtechnique.name**: Threat subtechnique name.
- **threat.technique.subtechnique.name.text**: Threat subtechnique name.
- **threat.technique.subtechnique.reference**: Threat subtechnique URL reference.

tls

- **tls.cipher**: String indicating the cipher used during the current connection.
- **tls.client.certificate**: PEM-encoded stand-alone certificate offered by the client.
- **tls.client.certificate_chain**: Array of PEM-encoded certificates that make up the certificate chain offered by the client.
- **tls.client.hash.md5**: Certificate fingerprint using the MD5 digest of DER-encoded version of certificate offered by the client.
- **tls.client.hash.sha1**: Certificate fingerprint using the SHA1 digest of DER-encoded version of certificate offered by the client.
- **tls.client.hash.sha256**: Certificate fingerprint using the SHA256 digest of DER-encoded version of certificate offered by the client.
- **tls.client.issuer**: Distinguished name of subject of the issuer of the x.509 certificate presented by the client.
- **tls.client.ja3**: A hash that identifies clients based on how they perform an SSL/TLS handshake.
- **tls.client.not_after**: Date/Time indicating when client certificate is no longer considered valid.
- **tls.client.not_before**: Date/Time indicating when client certificate is first considered valid.
- **tls.client.server_name**: Hostname the client is trying to connect to. Also called the SNI.
- **tls.client.subject**: Distinguished name of subject of the x.509 certificate presented by the client.
- **tls.client.supported_ciphers**: Array of ciphers offered by the client during the client hello.
- **tls.client.x509.alternative_names**: List of subject alternative names (SAN).

- **tls.client.x509.issuer.common_name**: List of common name (CN) of issuing certificate authority.
- **tls.client.x509.issuer.country**: List of country (C) codes
- **tls.client.x509.issuer.distinguished_name**: Distinguished name (DN) of issuing certificate authority.
- **tls.client.x509.issuer.locality**: List of locality names (L)
- **tls.client.x509.issuer.organization**: List of organizations (O) of issuing certificate authority.
- **tls.client.x509.issuer.organizational_unit**: List of organizational units (OU) of issuing certificate authority.
- **tls.client.x509.issuer.state_or_province**: List of state or province names (ST, S, or P)
- **tls.client.x509.not_after**: Time at which the certificate is no longer considered valid.
- **tls.client.x509.not_before**: Time at which the certificate is first considered valid.
- **tls.client.x509.public_key_algorithm**: Algorithm used to generate the public key.
- **tls.client.x509.public_key_curve**: The curve used by the elliptic curve public key algorithm. This is algorithm specific.
- **tls.client.x509.public_key_exponent**: Exponent used to derive the public key. This is algorithm specific.
- **tls.client.x509.public_key_size**: The size of the public key space in bits.
- **tls.client.x509.serial_number**: Unique serial number issued by the certificate authority.
- **tls.client.x509.signature_algorithm**: Identifier for certificate signature algorithm.
- **tls.client.x509.subject.common_name**: List of common names (CN) of subject.
- **tls.client.x509.subject.country**: List of country (C) code
- **tls.client.x509.subject.distinguished_name**: Distinguished name (DN) of the certificate subject entity.
- **tls.client.x509.subject.locality**: List of locality names (L)
- **tls.client.x509.subject.organization**: List of organizations (O) of subject.
- **tls.client.x509.subject.organizational_unit**: List of organizational units (OU) of subject.
- **tls.client.x509.subject.state_or_province**: List of state or province names (ST, S, or P)
- **tls.client.x509.version_number**: Version of x509 format.
- **tls.curve**: String indicating the curve used for the given cipher, when applicable.
- **tls.established**: Boolean flag indicating if the TLS negotiation was successful and transitioned to an encrypted tunnel.
- **tls.next_protocol**: String indicating the protocol being tunneled.
- **tls.resumed**: Boolean flag indicating if this TLS connection was resumed from an existing TLS negotiation.
- **tls.server.certificate**: PEM-encoded stand-alone certificate offered by the server.
- **tls.server.certificate_chain**: Array of PEM-encoded certificates that make up the certificate chain offered by the server.
- **tls.server.hash.md5**: Certificate fingerprint using the MD5 digest of DER-encoded version of certificate offered by the server.
- **tls.server.hash.sha1**: Certificate fingerprint using the SHA1 digest of DER-encoded version of certificate offered by the server.

- **tls.server.hash.sha256**: Certificate fingerprint using the SHA256 digest of DER-encoded version of certificate offered by the server.
- **tls.server.issuer**: Subject of the issuer of the x.509 certificate presented by the server.
- **tls.server.ja3s**: A hash that identifies servers based on how they perform an SSL/TLS handshake.
- **tls.server.not_after**: Timestamp indicating when server certificate is no longer considered valid.
- **tls.server.not_before**: Timestamp indicating when server certificate is first considered valid.
- **tls.server.subject**: Subject of the x.509 certificate presented by the server.
- **tls.server.x509.alternative_names**: List of subject alternative names (SAN).
- **tls.server.x509.issuer.common_name**: List of common name (CN) of issuing certificate authority.
- **tls.server.x509.issuer.country**: List of country (C) codes
- **tls.server.x509.issuer.distinguished_name**: Distinguished name (DN) of issuing certificate authority.
- **tls.server.x509.issuer.locality**: List of locality names (L)
- **tls.server.x509.issuer.organization**: List of organizations (O) of issuing certificate authority.
- **tls.server.x509.issuer.organizational_unit**: List of organizational units (OU) of issuing certificate authority.
- **tls.server.x509.issuer.state_or_province**: List of state or province names (ST, S, or P)
- **tls.server.x509.not_after**: Time at which the certificate is no longer considered valid.
- **tls.server.x509.not_before**: Time at which the certificate is first considered valid.
- **tls.server.x509.public_key_algorithm**: Algorithm used to generate the public key.
- **tls.server.x509.public_key_curve**: The curve used by the elliptic curve public key algorithm. This is algorithm specific.
- **tls.server.x509.public_key_exponent**: Exponent used to derive the public key. This is algorithm specific.
- **tls.server.x509.public_key_size**: The size of the public key space in bits.
- **tls.server.x509.serial_number**: Unique serial number issued by the certificate authority.
- **tls.server.x509.signature_algorithm**: Identifier for certificate signature algorithm.
- **tls.server.x509.subject.common_name**: List of common names (CN) of subject.
- **tls.server.x509.subject.country**: List of country (C) code
- **tls.server.x509.subject.distinguished_name**: Distinguished name (DN) of the certificate subject entity.
- **tls.server.x509.subject.locality**: List of locality names (L)
- **tls.server.x509.subject.organization**: List of organizations (O) of subject.
- **tls.server.x509.subject.organizational_unit**: List of organizational units (OU) of subject.
- **tls.server.x509.subject.state_or_province**: List of state or province names (ST, S, or P)
- **tls.server.x509.version_number**: Version of x509 format.

- **tls.version**: Numeric part of the version parsed from the original string.
- **tls.version_protocol**: Normalized lowercase protocol name parsed from original string.

trace

- **trace.id**: Unique identifier of the trace.

transaction

- **transaction.id**: Unique identifier of the transaction within the scope of its trace.

url

- **url.domain**: Domain of the url.
- **url.extension**: File extension from the request url, excluding the leading dot.
- **url.fragment**: Portion of the url after the #.
- **url.full**: Full unparsed URL.
- **url.full.text**: Full unparsed URL.
- **url.original**: Unmodified original url as seen in the event source.
- **url.original.text**: Unmodified original url as seen in the event source.
- **url.password**: Password of the request.
- **url.path**: Path of the request, such as "/search".
- **url.port**: Port of the request, such as 443.
- **url.query**: Query string of the request.
- **url.registered_domain**: The highest registered url domain, stripped of the subdomain.
- **url.scheme**: Scheme of the url.
- **url.subdomain**: The subdomain of the domain.
- **url.top_level_domain**: The effective top level domain (com, org, net, co.uk).
- **url.username**: Username of the request.

user

- **user.changes.domain**: Name of the directory the user is a member of.
- **user.changes.email**: User email address.
- **user.changes.entity.attributes.known_redirectsKnown**: redirect URIs or URLs associated with this entity.
- **user.changes.entity.attributes.managed**: Indicates whether the entity is managed by an external system.
- **user.changes.entity.attributes.mfa_enabled**: Indicates whether multi-factor authentication is enabled for this entity.
- **user.changes.entity.attributes.oauth_consent_restrictionRestriction**: applied to OAuth consent for this entity.

- **user.changes.entity.attributes.permissions:** Action-level permissions associated with this entity.
- **user.changes.entity.attributes.storage_classStorage:** tier or class assigned to an object storage resource.
- **user.changes.entity.behavior:** A set of ephemeral characteristics of the entity, derived from observed behaviors during a specific time period.
- **user.changes.entity.display_name:** An optional field used when a pretty name is desired for entity-centric operations.
- **user.changes.entity.display_name.text:** An optional field used when a pretty name is desired for entity-centric operations.
- **user.changes.entity.id:** Unique identifier for the entity.
- **user.changes.entity.last_seen_timestamp:** Indicates the date/time when this entity was last "seen."
- **user.changes.entity.lifecycle.last_activity:** Timestamp of the most recent action performed by or attributed to this entity.
- **user.changes.entity.metrics:** Field set for any fields containing numeric entity metrics.
- **user.changes.entity.name:** The name of the entity.
- **user.changes.entity.name.text:** The name of the entity.
- **user.changes.entity.raw:** Original, unmodified fields from the source system.
- **user.changes.entity.reference:** A URI, URL, or other direct reference to access or locate the entity.
- **user.changes.entity.relationships.administers.entity.idIdentifiers:** of referenced entities.
- **user.changes.entity.relationships.administers.host.idReferenced:** host ids.
- **user.changes.entity.relationships.administers.host.nameReferenced:** host names.
- **user.changes.entity.relationships.administers.service.idReferenced:** service ids.
- **user.changes.entity.relationships.administers.service.nameReferenced:** service names.
- **user.changes.entity.relationships.administers.user.domainReferenced:** user directory or AD/LDAP domain names.
- **user.changes.entity.relationships.administers.user.emailReferenced:** user email addresses.
- **user.changes.entity.relationships.administers.user.idReferenced:** user ids.
- **user.changes.entity.relationships.administers.user.nameReferenced:** user short names or logins.
- **user.changes.entity.relationships.depends_on.entity.idIdentifiers:** of referenced entities.
- **user.changes.entity.relationships.depends_on.host.idReferenced:** host ids.
- **user.changes.entity.relationships.depends_on.host.nameReferenced:** host names.
- **user.changes.entity.relationships.depends_on.service.idReferenced:** service ids.
- **user.changes.entity.relationships.depends_on.service.nameReferenced:** service names.

- **user.changes.entity.relationships.depends_on.user.domainReferenced:** user directory or AD/LDAP domain names.
- **user.changes.entity.relationships.depends_on.user.emailReferenced:** user email addresses.
- **user.changes.entity.relationships.depends_on.user.idReferenced:** user ids.
- **user.changes.entity.relationships.depends_on.user.nameReferenced:** user short names or logins.
- **user.changes.entity.relationships.owns.entity.idIdentifiers:** of referenced entities.
- **user.changes.entity.relationships.owns.host.idReferenced:** host ids.
- **user.changes.entity.relationships.owns.host.nameReferenced:** host names.
- **user.changes.entity.relationships.owns.service.idReferenced:** service ids.
- **user.changes.entity.relationships.owns.service.nameReferenced:** service names.
- **user.changes.entity.relationships.owns.user.domainReferenced:** user directory or AD/LDAP domain names.
- **user.changes.entity.relationships.owns.user.emailReferenced:** user email addresses.
- **user.changes.entity.relationships.owns.user.idReferenced:** user ids.
- **user.changes.entity.relationships.owns.user.nameReferenced:** user short names or logins.
- **user.changes.entity.relationships.supervises.entity.idIdentifiers:** of referenced entities.
- **user.changes.entity.relationships.supervises.host.idReferenced:** host ids.
- **user.changes.entity.relationships.supervises.host.nameReferenced:** host names.
- **user.changes.entity.relationships.supervises.service.idReferenced:** service ids.
- **user.changes.entity.relationships.supervises.service.nameReferenced:** service names.
- **user.changes.entity.relationships.supervises.user.domainReferenced:** user directory or AD/LDAP domain names.
- **user.changes.entity.relationships.supervises.user.emailReferenced:** user email addresses.
- **user.changes.entity.relationships.supervises.user.idReferenced:** user ids.
- **user.changes.entity.relationships.supervises.user.nameReferenced:** user short names or logins.
- **user.changes.entity.source:** Source module or integration that provided the entity data.
- **user.changes.entity.sub_type:** The specific type designation for the entity as defined by its provider or system.
- **user.changes.entity.type:** Standardized high-level classification of the entity.
- **user.changes.full_name:** User's full name, if available.
- **user.changes.full_name.text:** User's full name, if available.
- **user.changes.group.domain:** Name of the directory the group is a member of.
- **user.changes.group.id:** Unique identifier for the group on the system/platform.
- **user.changes.group.name:** Name of the group.

- **user.changes.hash**: Unique user hash to correlate information for a user in anonymized form.
- **user.changes.id**: Unique identifier of the user.
- **user.changes.name**: Short name or login of the user.
- **user.changes.name.text**: Short name or login of the user.
- **user.changes.risk.calculated_level**: A risk classification level calculated by an internal system as part of entity analytics and entity risk scoring.
- **user.changes.risk.calculated_score**: A risk classification score calculated by an internal system as part of entity analytics and entity risk scoring.
- **user.changes.risk.calculated_score_norm**: A normalized risk score calculated by an internal system.
- **user.changes.risk.static_level**: A risk classification level obtained from outside the system, such as from some external Threat Intelligence Platform.
- **user.changes.risk.static_score**: A risk classification score obtained from outside the system, such as from some external Threat Intelligence Platform.
- **user.changes.risk.static_score_norm**: A normalized risk score calculated by an external system.
- **user.changes.roles**: Array of user roles at the time of the event.
- **user.domain**: Name of the directory the user is a member of.
- **user.effective.domain**: Name of the directory the user is a member of.
- **user.effective.email**: User email address.
- **user.effective.entity.attributes.known_redirectsKnown**: redirect URIs or URLs associated with this entity.
- **user.effective.entity.attributes.managed**: Indicates whether the entity is managed by an external system.
- **user.effective.entity.attributes.mfa_enabled**: Indicates whether multi-factor authentication is enabled for this entity.
- **user.effective.entity.attributes.oauth_consent_restrictionRestriction**: applied to OAuth consent for this entity.
- **user.effective.entity.attributes.permissions**: Action-level permissions associated with this entity.
- **user.effective.entity.attributes.storage_classStorage**: tier or class assigned to an object storage resource.
- **user.effective.entity.behavior**: A set of ephemeral characteristics of the entity, derived from observed behaviors during a specific time period.
- **user.effective.entity.display_name**: An optional field used when a pretty name is desired for entity-centric operations.
- **user.effective.entity.display_name.text**: An optional field used when a pretty name is desired for entity-centric operations.
- **user.effective.entity.id**: Unique identifier for the entity.
- **user.effective.entity.last_seen_timestamp**: Indicates the date/time when this entity was last "seen."

- **user.effective.entity.lifecycle.last_activity**: Timestamp of the most recent action performed by or attributed to this entity.
- **user.effective.entity.metrics**: Field set for any fields containing numeric entity metrics.
- **user.effective.entity.name**: The name of the entity.
- **user.effective.entity.name.text**: The name of the entity.
- **user.effective.entity.raw**: Original, unmodified fields from the source system.
- **user.effective.entity.reference**: A URI, URL, or other direct reference to access or locate the entity.
- **user.effective.entity.relationships.administers.entity.idIdentifiers**: of referenced entities.
- **user.effective.entity.relationships.administers.host.idReferenced**: host ids.
- **user.effective.entity.relationships.administers.host.nameReferenced**: host names.
- **user.effective.entity.relationships.administers.service.idReferenced**: service ids.
- **user.effective.entity.relationships.administers.service.nameReferenced**: service names.
- **user.effective.entity.relationships.administers.user.domainReferenced**: user directory or AD/LDAP domain names.
- **user.effective.entity.relationships.administers.user.emailReferenced**: user email addresses.
- **user.effective.entity.relationships.administers.user.idReferenced**: user ids.
- **user.effective.entity.relationships.administers.user.nameReferenced**: user short names or logins.
- **user.effective.entity.relationships.depends_on.entity.idIdentifiers**: of referenced entities.
- **user.effective.entity.relationships.depends_on.host.idReferenced**: host ids.
- **user.effective.entity.relationships.depends_on.host.nameReferenced**: host names.
- **user.effective.entity.relationships.depends_on.service.idReferenced**: service ids.
- **user.effective.entity.relationships.depends_on.service.nameReferenced**: service names.
- **user.effective.entity.relationships.depends_on.user.domainReferenced**: user directory or AD/LDAP domain names.
- **user.effective.entity.relationships.depends_on.user.emailReferenced**: user email addresses.
- **user.effective.entity.relationships.depends_on.user.idReferenced**: user ids.
- **user.effective.entity.relationships.depends_on.user.nameReferenced**: user short names or logins.
- **user.effective.entity.relationships.owns.entity.idIdentifiers**: of referenced entities.
- **user.effective.entity.relationships.owns.host.idReferenced**: host ids.
- **user.effective.entity.relationships.owns.host.nameReferenced**: host names.
- **user.effective.entity.relationships.owns.service.idReferenced**: service ids.
- **user.effective.entity.relationships.owns.service.nameReferenced**: service names.
- **user.effective.entity.relationships.owns.user.domainReferenced**: user directory or AD/LDAP domain names.

- **user.effective.entity.relationships.owns.user.emailReferenced**: user email addresses.
- **user.effective.entity.relationships.owns.user.idReferenced**: user ids.
- **user.effective.entity.relationships.owns.user.nameReferenced**: user short names or logins.
- **user.effective.entity.relationships.supervises.entity.idIdentifiers**: of referenced entities.
- **user.effective.entity.relationships.supervises.host.idReferenced**: host ids.
- **user.effective.entity.relationships.supervises.host.nameReferenced**: host names.
- **user.effective.entity.relationships.supervises.service.idReferenced**: service ids.
- **user.effective.entity.relationships.supervises.service.nameReferenced**: service names.
- **user.effective.entity.relationships.supervises.user.domainReferenced**: user directory or AD/LDAP domain names.
- **user.effective.entity.relationships.supervises.user.emailReferenced**: user email addresses.
- **user.effective.entity.relationships.supervises.user.idReferenced**: user ids.
- **user.effective.entity.relationships.supervises.user.nameReferenced**: user short names or logins.
- **user.effective.entity.source**: Source module or integration that provided the entity data.
- **user.effective.entity.sub_type**: The specific type designation for the entity as defined by its provider or system.
- **user.effective.entity.type**: Standardized high-level classification of the entity.
- **user.effective.full_name**: User's full name, if available.
- **user.effective.full_name.text**: User's full name, if available.
- **user.effective.group.domain**: Name of the directory the group is a member of.
- **user.effective.group.id**: Unique identifier for the group on the system/platform.
- **user.effective.group.name**: Name of the group.
- **user.effective.hash**: Unique user hash to correlate information for a user in anonymized form.
- **user.effective.id**: Unique identifier of the user.
- **user.effective.name**: Short name or login of the user.
- **user.effective.name.text**: Short name or login of the user.
- **user.effective.risk.calculated_level**: A risk classification level calculated by an internal system as part of entity analytics and entity risk scoring.
- **user.effective.risk.calculated_score**: A risk classification score calculated by an internal system as part of entity analytics and entity risk scoring.
- **user.effective.risk.calculated_score_norm**: A normalized risk score calculated by an internal system.
- **user.effective.risk.static_level**: A risk classification level obtained from outside the system, such as from some external Threat Intelligence Platform.
- **user.effective.risk.static_score**: A risk classification score obtained from outside the system, such as from some external Threat Intelligence Platform.

- **user.effective.risk.static_score_norm**: A normalized risk score calculated by an external system.
- **user.effective.roles**: Array of user roles at the time of the event.
- **user.email**: User email address.
- **user.entity.attributes.known_redirects**: Known redirect URIs or URLs associated with this entity.
- **user.entity.attributes.managed**: Indicates whether the entity is managed by an external system.
- **user.entity.attributes.mfa_enabled**: Indicates whether multi-factor authentication is enabled for this entity.
- **user.entity.attributes.oauth_consent_restrictionRestriction**: applied to OAuth consent for this entity.
- **user.entity.attributes.permissions**: Action-level permissions associated with this entity.
- **user.entity.attributes.storage_class**: Storage tier or class assigned to an object storage resource.
- **user.entity.behavior**: A set of ephemeral characteristics of the entity, derived from observed behaviors during a specific time period.
- **user.entity.display_name**: An optional field used when a pretty name is desired for entity-centric operations.
- **user.entity.display_name.text**: An optional field used when a pretty name is desired for entity-centric operations.
- **user.entity.id**: Unique identifier for the entity.
- **user.entity.last_seen_timestamp**: Indicates the date/time when this entity was last "seen."
- **user.entity.lifecycle.last_activity**: Timestamp of the most recent action performed by or attributed to this entity.
- **user.entity.metrics**: Field set for any fields containing numeric entity metrics.
- **user.entity.name**: The name of the entity.
- **user.entity.name.text**: The name of the entity.
- **user.entity.raw**: Original, unmodified fields from the source system.
- **user.entity.reference**: A URI, URL, or other direct reference to access or locate the entity.
- **user.entity.relationships.administers.entity.idIdentifiers**: of referenced entities.
- **user.entity.relationships.administers.host.id**: Referenced host ids.
- **user.entity.relationships.administers.host.nameReferenced**: host names.
- **user.entity.relationships.administers.service.idReferenced**: service ids.
- **user.entity.relationships.administers.service.nameReferenced**: service names.
- **user.entity.relationships.administers.user.domainReferenced**: user directory or AD/LDAP domain names.
- **user.entity.relationships.administers.user.emailReferenced**: user email addresses.
- **user.entity.relationships.administers.user.id**: Referenced user ids.
- **user.entity.relationships.administers.user.nameReferenced**: user short names or logins.

- **user.entity.relationships.depends_on.entity.idIdentifiers**: of referenced entities.
- **user.entity.relationships.depends_on.host.idReferenced**: host ids.
- **user.entity.relationships.depends_on.host.nameReferenced**: host names.
- **user.entity.relationships.depends_on.service.idReferenced**: service ids.
- **user.entity.relationships.depends_on.service.nameReferenced**: service names.
- **user.entity.relationships.depends_on.user.domainReferenced**: user directory or AD/LDAP domain names.
- **user.entity.relationships.depends_on.user.emailReferenced**: user email addresses.
- **user.entity.relationships.depends_on.user.idReferenced**: user ids.
- **user.entity.relationships.depends_on.user.nameReferenced**: user short names or logins.
- **user.entity.relationships.owns.entity.id**: Identifiers of referenced entities.
- **user.entity.relationships.owns.host.id**: Referenced host ids.
- **user.entity.relationships.owns.host.name**: Referenced host names.
- **user.entity.relationships.owns.service.id**: Referenced service ids.
- **user.entity.relationships.owns.service.name**: Referenced service names.
- **user.entity.relationships.owns.user.domain**: Referenced user directory or AD/LDAP domain names.
- **user.entity.relationships.owns.user.email**: Referenced user email addresses.
- **user.entity.relationships.owns.user.id**: Referenced user ids.
- **user.entity.relationships.owns.user.name**: Referenced user short names or logins.
- **user.entity.relationships.supervises.entity.id**: Identifiers of referenced entities.
- **user.entity.relationships.supervises.host.id**: Referenced host ids.
- **user.entity.relationships.supervises.host.nameReferenced**: host names.
- **user.entity.relationships.supervises.service.idReferenced**: service ids.
- **user.entity.relationships.supervises.service.nameReferenced**: service names.
- **user.entity.relationships.supervises.user.domainReferenced**: user directory or AD/LDAP domain names.
- **user.entity.relationships.supervises.user.emailReferenced**: user email addresses.
- **user.entity.relationships.supervises.user.id**: Referenced user ids.
- **user.entity.relationships.supervises.user.nameReferenced**: user short names or logins.
- **user.entity.source**: Source module or integration that provided the entity data.
- **user.entity.sub_type**: The specific type designation for the entity as defined by its provider or system.
- **user.entity.type**: Standardized high-level classification of the entity.
- **user.full_name**: User's full name, if available.
- **user.full_name.text**: User's full name, if available.
- **user.group.domain**: Name of the directory the group is a member of.
- **user.group.id**: Unique identifier for the group on the system/platform.
- **user.group.name**: Name of the group.
- **user.hash**: Unique user hash to correlate information for a user in anonymized form.
- **user.id**: Unique identifier of the user.

- **user.name:** Short name or login of the user.
- **user.name.text:** Short name or login of the user.
- **user.risk.calculated_level:** A risk classification level calculated by an internal system as part of entity analytics and entity risk scoring.
- **user.risk.calculated_score:** A risk classification score calculated by an internal system as part of entity analytics and entity risk scoring.
- **user.risk.calculated_score_norm:** A normalized risk score calculated by an internal system.
- **user.risk.static_level:** A risk classification level obtained from outside the system, such as from some external Threat Intelligence Platform.
- **user.risk.static_score:** A risk classification score obtained from outside the system, such as from some external Threat Intelligence Platform.
- **user.risk.static_score_norm:** A normalized risk score calculated by an external system.
- **user.roles:** Array of user roles at the time of the event.
- **user.target.domain:** Name of the directory the user is a member of.
- **user.target.email:** User email address.
- **user.target.entity.attributes.known_redirects:** Known redirect URIs or URLs associated with this entity.
- **user.target.entity.attributes.managed:** Indicates whether the entity is managed by an external system.
- **user.target.entity.attributes.mfa_enabled:** Indicates whether multi-factor authentication is enabled for this entity.
- **user.target.entity.attributes.oauth_consent_restrictionRestriction:** applied to OAuth consent for this entity.
- **user.target.entity.attributes.permissions:** Action-level permissions associated with this entity.
- **user.target.entity.attributes.storage_class:** Storage tier or class assigned to an object storage resource.
- **user.target.entity.behavior:** A set of ephemeral characteristics of the entity, derived from observed behaviors during a specific time period.
- **user.target.entity.display_name:** An optional field used when a pretty name is desired for entity-centric operations.
- **user.target.entity.display_name.text:** An optional field used when a pretty name is desired for entity-centric operations.
- **user.target.entity.id:** Unique identifier for the entity.
- **user.target.entity.last_seen_timestamp:** Indicates the date/time when this entity was last "seen."
- **user.target.entity.lifecycle.last_activity:** Timestamp of the most recent action performed by or attributed to this entity.
- **user.target.entity.metrics:** Field set for any fields containing numeric entity metrics.
- **user.target.entity.name:** The name of the entity.
- **user.target.entity.name.text:** The name of the entity.
- **user.target.entity.raw:** Original, unmodified fields from the source system.

- **user.target.entity.reference**: A URI, URL, or other direct reference to access or locate the entity.
- **user.target.entity.relationships.administers.entity.idIdentifiers**: of referenced entities.
- **user.target.entity.relationships.administers.host.idReferenced**: host ids.
- **user.target.entity.relationships.administers.host.nameReferenced**: host names.
- **user.target.entity.relationships.administers.service.idReferenced**: service ids.
- **user.target.entity.relationships.administers.service.nameReferenced**: service names.
- **user.target.entity.relationships.administers.user.domainReferenced**: user directory or AD/LDAP domain names.
- **user.target.entity.relationships.administers.user.emailReferenced**: user email addresses.
- **user.target.entity.relationships.administers.user.idReferenced**: user ids.
- **user.target.entity.relationships.administers.user.nameReferenced**: user short names or logins.
- **user.target.entity.relationships.depends_on.entity.idIdentifiers**: of referenced entities.
- **user.target.entity.relationships.depends_on.host.idReferenced**: host ids.
- **user.target.entity.relationships.depends_on.host.nameReferenced**: host names.
- **user.target.entity.relationships.depends_on.service.idReferenced**: service ids.
- **user.target.entity.relationships.depends_on.service.nameReferenced**: service names.
- **user.target.entity.relationships.depends_on.user.domainReferenced**: user directory or AD/LDAP domain names.
- **user.target.entity.relationships.depends_on.user.emailReferenced**: user email addresses.
- **user.target.entity.relationships.depends_on.user.idReferenced**: user ids.
- **user.target.entity.relationships.depends_on.user.nameReferenced**: user short names or logins.
- **user.target.entity.relationships.owns.entity.idIdentifiers**: of referenced entities.
- **user.target.entity.relationships.owns.host.id**: Referenced host ids.
- **user.target.entity.relationships.owns.host.nameReferenced**: host names.
- **user.target.entity.relationships.owns.service.idReferenced**: service ids.
- **user.target.entity.relationships.owns.service.nameReferenced**: service names.
- **user.target.entity.relationships.owns.user.domainReferenced**: user directory or AD/LDAP domain names.
- **user.target.entity.relationships.owns.user.emailReferenced**: user email addresses.
- **user.target.entity.relationships.owns.user.id**: Referenced user ids.
- **user.target.entity.relationships.owns.user.nameReferenced**: user short names or logins.
- **user.target.entity.relationships.supervises.entity.idIdentifiers**: of referenced entities.
- **user.target.entity.relationships.supervises.host.idReferenced**: host ids.

- **user.target.entity.relationships.supervises.host.nameReferenced**: host names.
- **user.target.entity.relationships.supervises.service.idReferenced**: service ids.
- **user.target.entity.relationships.supervises.service.nameReferenced**: service names.
- **user.target.entity.relationships.supervises.user.domainReferenced**: user directory or AD/LDAP domain names.
- **user.target.entity.relationships.supervises.user.emailReferenced**: user email addresses.
- **user.target.entity.relationships.supervises.user.idReferenced**: user ids.
- **user.target.entity.relationships.supervises.user.nameReferenced**: user short names or logins.
- **user.target.entity.source**: Source module or integration that provided the entity data.
- **user.target.entity.sub_type**: The specific type designation for the entity as defined by its provider or system.
- **user.target.entity.type**: Standardized high-level classification of the entity.
- **user.target.full_name**: User's full name, if available.
- **user.target.full_name.text**: User's full name, if available.
- **user.target.group.domain**: Name of the directory the group is a member of.
- **user.target.group.id**: Unique identifier for the group on the system/platform.
- **user.target.group.name**: Name of the group.
- **user.target.hash**: Unique user hash to correlate information for a user in anonymized form.
- **user.target.id**: Unique identifier of the user.
- **user.target.name**: Short name or login of the user.
- **user.target.name.text**: Short name or login of the user.
- **user.target.risk.calculated_level**: A risk classification level calculated by an internal system as part of entity analytics and entity risk scoring.
- **user.target.risk.calculated_score**: A risk classification score calculated by an internal system as part of entity analytics and entity risk scoring.
- **user.target.risk.calculated_score_norm**: A normalized risk score calculated by an internal system.
- **user.target.risk.static_level**: A risk classification level obtained from outside the system, such as from some external Threat Intelligence Platform.
- **user.target.risk.static_score**: A risk classification score obtained from outside the system, such as from some external Threat Intelligence Platform.
- **user.target.risk.static_score_norm**: A normalized risk score calculated by an external system.
- **user.target.roles**: Array of user roles at the time of the event.

user_agent

- **user_agent.device.name**: Name of the device.
- **user_agent.name**: Name of the user agent.

- **user_agent.original**: Unparsed user_agent string.
- **user_agent.original.text**: Unparsed user_agent string.
- **user_agent.os.family**: OS family (such as redhat, debian, freebsd, windows).
- **user_agent.os.full**: Operating system name, including the version or code name.
- **user_agent.os.full.text**: Operating system name, including the version or code name.
- **user_agent.os.kernel**: Operating system kernel version as a raw string.
- **user_agent.os.name**: Operating system name, without the version.
- **user_agent.os.name.text**: Operating system name, without the version.
- **user_agent.os.platform**: Operating system platform (such centos, ubuntu, windows).
- **user_agent.os.type**: Which commercial OS family (one of: linux, macos, unix, windows, ios or android).
- **user_agent.os.version**: Operating system version as a raw string.
- **user_agent.version**: Version of the user agent.

volume

- **volume.bus_type**: Bus type of the device.
- **volume.default_access**: Bus type of the device.
- **volume.device_name**: Device name of the volume.
- **volume.device_type**: Volume device type.
- **volume.dos_name**: DOS name of the device.
- **volume.file_system_type**: Volume device file system type.
- **volume.mount_name**: Mount name of the volume.
- **volume.nt_name**: NT name of the device.
- **volume.product_id**: ProductID of the device.
- **volume.product_name**: Produce name of the volume.
- **volume.removable**: Indicates if the volume is removable.
- **volume.serial_number**: Serial number of the device.
- **volume.size**: Size of the volume device in bytes.
- **volume.vendor_id**: VendorID of the device.
- **volume.vendor_name**: Vendor name of the device.
- **volume.writable**: Indicates if the volume is writable.

vulnerability

- **vulnerability.category**: Category of a vulnerability.
- **vulnerability.classification**: Classification of the vulnerability.
- **vulnerability.description**: Description of the vulnerability.
- **vulnerability.description.text**: Description of the vulnerability.
- **vulnerability.enumeration**: Identifier of the vulnerability.
- **vulnerability.id**: ID of the vulnerability.
- **vulnerability.reference**: Reference of the vulnerability.
- **vulnerability.report_id**: Scan identification number.

- **vulnerability.scanner.vendor**: Name of the scanner vendor.
- **vulnerability.score.base**: Vulnerability Base score.
- **vulnerability.score.environmental**: Vulnerability Environmental score.
- **vulnerability.score.temporal**: Vulnerability Temporal score.
- **vulnerability.score.version**: CVSS version.
- **vulnerability.severity**: Severity of the vulnerability.
- **vulnerability.status**: Lifecycle state of a vulnerability finding.

Rules to Understand And Link Fields:

Kibana Query Language (KQL) Reference for Query Generation

Overview

Kibana Query Language (KQL) is a text-based query language used for filtering Elasticsearch data.

Important Notes

- KQL only filters data.
 - KQL does not perform aggregation, transformation, or sorting.
 - KQL is different from Lucene Query Language.
 - Boolean operators (**AND**, **OR**, **NOT**) are case-insensitive, but examples should follow standard KQL formatting.
-

Basic Syntax

Field Exists

Return documents where a field contains any indexed value.

Syntax

field.name: *

Example

http.request.method: *

Exact Value Matching

Search for documents where a field matches a specific value.

Syntax

field.name: value

Example

http.request.method: GET

Examples

host.name: LKO-109

destination.ip: 192.168.0.12

event.category: network

Search Across All Fields

If no field is specified, KQL searches all fields.

Example

Hello

Text Field Searches

For text fields, Elasticsearch analyzes the text before searching.

Example

http.request.body.content: null pointer

Matches:

null pointer
pointer null

Exact Phrase Match

Use quotation marks when word order matters.

http.request.body.content: "null pointer"

Special Characters and Escaping

Quoted Value

http.request.referrer: "https://example-url"

Escaped Value

http.request.referrer: https\\://example-url

Characters That Must Be Escaped

\ () : < > " *

Range Queries

Less Than

http.response.bytes < 10000

Greater Than

http.response.bytes > 10000

Less Than or Equal

http.response.bytes <= 20000

Greater Than or Equal

`http.response.bytes >= 10000`

Range Example

`http.response.bytes > 10000 and http.response.bytes <= 20000`

Date Range Example

`@timestamp < now-2w`

Returns documents older than two weeks.

Wildcard Searches

Use `*` to match zero or more characters.

Example

`http.response.status_code: 4*`

Matches:

400

401

403

404

Query Multiple Fields

`datastream.*: logs`

Negation

Exclude matching documents using `NOT`.

Example

NOT http.request.method: GET

Boolean Operators

OR

Match either condition.

http.request.method: GET OR http.response.status_code: 400

AND

Match both conditions.

http.request.method: GET AND http.response.status_code: 400

Parentheses for Precedence

(http.request.method: GET AND http.response.status_code: 200)

OR

(http.request.method: POST AND http.response.status_code: 400)

Multiple Values for the Same Field

http.request.method: (GET OR POST OR DELETE)

Common Security Operations Center (SOC) Examples

Search by Destination IP

destination.ip: "192.168.0.12"

Search by Host Name

host.name: "LKO-109"

Search by User

user.name: "jsmith"

Search by Process

process.name: "powershell.exe"

Search by File Hash

file.hash.sha256: "HASH_VALUE"

Search by Source and Destination IP

source.ip: "10.10.10.5" AND destination.ip: "192.168.0.12"

Search by Destination IP and Host Name

destination.ip: "192.168.0.12" AND host.name: "LKO-109"

Query Generation Rules

When generating KQL queries:

1. Use the format:

field.name: value

2. Use quotation marks around values containing special characters, spaces, hostnames, IP addresses, or URLs.

3. Use:

AND

OR

NOT

for boolean operations.

4. Use parentheses to control precedence.

5. Use * for wildcard searches.

6. Use range operators:

<

<=

>

>=

7. Escape special characters when not using quotes.

8. Do not generate SQL syntax.

9. Do not generate Lucene syntax.

10. Output only valid Kibana Query Language (KQL).