Control-Flow Instructions

- The first two instructions use a different addressing mode called pc-relative addressing at the resolution of 12 bit.

- **Branch on equal** sets the `pc` to `pc + imm` if the content of `$rs1` matches `$rs2`.

- **Jump and link** is used for procedure calls and stores the return address (address of next instruction) in `$rd`.

- **Jump and link register** is similar to `jal`, except that it uses register relative addressing in order to jump a little further.

`beq`	`$rs1`	`$rs2`	`imm`
`jal`	`$rd`	`imm`	
`jalr`	`$rd`	`$rs1`	`imm`



Link Register

```
uint64_t increment(uint64_t inc) {
   return inc + 1;
}

uint64_t main() {
   uint64_t a;

   a = 0
   a = increment(a);

   return a;
}
```

The next **instruction** that is linked is the assignment into a!

Control-Flow Instructions

`beq`	`$rs1`	`$rs2`	`imm`
`jal`	`$rd`	`imm`	
`jalr`	`$rd`	`$rs1`	`imm`

- The first two instructions use a different addressing mode called pc-relative addressing at the resolution of 12 bit.

- **Branch on equal** sets the `pc` to `pc + imm` if the content of `$rs1` matches `$rs2`.

- **Jump and link** is used for procedure calls and stores the return address (address of next instruction) in `$rd`.

- **Jump and link register** is similar to `jal`, except that it uses register relative addressing in order to jump a little further.