

# openPASS / World\_OSI

Setup guide

February 24, 2020

# Contents

1	Do	Pocument History	2
2		ntroduction	
_			
3 Prerequisites			2
4	Dependency installation guide		3
	4.1	MinGW	3
	4.2	CMake	3
	4.3	Protobuf	3
	4.4	Open Simulation Interface	
	4.5	boost	
	4.6	Google Test and Google Mock	5
	4.7	Modelon FMI Library	6
5	Co	Compiling openPASS	
6		imulation	
7	Re	References	8



# 1 Document History

Version	Description of the changes	Author	Date
0.9	First tracked version	Reinhard Biegel	25.11.2019
1.0	Extension of the Compile Core chapter	Arun Das	12.12.2019
1.1	Added list of third party libraries, Link to OSI Repo	Arun Das	14.01.2020
1.2	Added FMI Library to dependency list and dependency installation guide	Reinhard Biegel	24.02.2020

## 2 Introduction

The World\_OSI provides an implementation of the WorldInterface using Open Simulation Interface (OSI) as a "backend storage" [1]. OSI already provides data structures for representing various objects in traffic simulation environments. As these objects are specified rather sensor centric, the OSI source currently needs some additions to satisfy the needs of the World\_OSI module (see OSI WorldInterface Pull Request [2]).

To allow unit-testing of the implementation, an additional layer has been introduced on top of OSI, whose classes represent the objects needed in the simulator's world (WorldData). The OSI objects are instantiated there. An architectural diagram showing WorldData and its interactions is currently not available.

Another benefit of the additional WorldData layer is keeping the area of contact to the data backend small, to allow easy adaption if OSI switches from protobuf to another storage technology (open discussion).

The current use of protobuf provides easy serialization and deserialization of all stored data out-of-the-box.

# 3 Prerequisites

You'll find the openPASS sources in Eclipse Gerrit [10]. Please note to check out the **intech** branch, where the OSI changes will be located for now. Of course, associated changes on Gerrit are also an option. For the OSI world demonstration an additional project file <code>OpenPASS\_OSI\_UseCase.pro</code> has been added, which can be opened in QtCreator IDE, or directly be built using <code>qmake</code> on the command line.

It is recommended to use a **short path for the source code checkout**, due to limitations in the MinGW/Windows setup. If you ever come across compilation errors regarding files not being found, you might have run into problems with path length restrictions.

Before being able to compile and run the World\_OSI, make sure to have all dependencies installed.

World\_OSI has been developed on Linux x86\_64 using Qt 5.12.3, gcc 7.1.0, 7.3.0 and 8.1.0. On Windows systems a MinGW environment with the same compiler versions has been used. There are no known issues regarding different gcc versions.

To summarize, openPASS with World\_OSI has these dependencies:

- MinGW gcc environment (Windows, testet gcc versions are 7.1.0, 7.3.0 and 8.1.0, 64-bit)



- Qt 5.12.3 (incl. QtCreator IDE and qmake build system)
- Open Simulation Interface (OSI)
- Google Protobuf 3.6.1
- Cmake 3.9.4
- boost library 1.63
  - o algorithm
  - o math
  - geometry
- Google Test / Google Mock 1.8.1
- Modelon FMILibrary 2.0.3 (if using Algorithm\_FmuWrapper)

**NOTE:** Please stick to the paths as given by this tutorial and the source code – unless you're an expert. Only if the default paths are used, compatibility with the GUI can be guaranteed.

# 4 Dependency installation guide

The World\_OSI module introduces additional third-party dependency on the OSI library, and as a consequence on Google protobuffers. Furthermore, the boost (geometry) library is required to compile and run World\_OSI [6]. Other dependencies have to be set up for the build environment itself.

#### 4.1 MinGW

An installation for 64-bit MinGW environments is provided at [9]. You can download a generic installer binary, which will let you select different Versions of MinGW. Latest tested setup is  $x86\_64-8.1.0-posix-seh-rt_v6-rev0$ .

## 4.2 CMake

For compilation of protobuf and OSI, the CMake build system is required. Please download and install a binary distribution of CMake [5]. Version 3.9.4 has been used during testing. Please feel free to try a more recent version, but note that issues with newer versions have already been reported.

#### 4.3 Protobuf

If not already installed on the system, the protobuf library and headers have to be built prior to being able to compile OSI. Protobuf sources are located at [4]. This guide will give some instructions to compile version 3.6.1, but any other version should be compatible (including 2.x).

As most users seem to work on Windows environments, the following instructions will target these systems.

- Download protobuf-cpp-3.6.1.zip and extract the archive. We will use C:\OpenPASS\thirdParty\sources as target directory.
- 2. Open a command line with MinGW environment at the extraction directory
- 3. Create the build directory
  - > cd cmake



- > mkdir build
  > cd build
- 4. Run CMake (tests are disabled here due to some compiler warnings being treated as errors, may vary with compiler version)

```
> cmake -G "MinGW Makefiles" -DCMAKE_BUILD_TYPE=Release
-DCMAKE_INSTALL_PREFIX=C:/OpenPASS/thirdParty
-Dprotobuf_BUILD_SHARED_LIBS=ON
-Dprotobuf_BUILD_TESTS=OFF ..
```

5. Compilation

```
> mingw32-make -j3
```

6. Installation

```
> mingw32-make install
```

- 7. Final steps
  - a. Copy the MinGW runtime libraries from the MinGW installation directory to the thirdParty/bin directory (libgcc\_s\_seh-1.dll, libwinpthread-1.dll and libstdc++6.dll). This allows running the protobuf compiler (protoc.exe) outside of a full MinGW environment.
  - b. Copy the libprotobuf.dll from bin to lib subfolder

## 4.4 Open Simulation Interface

The OSI project is hosted on Github. Please check out the source of the mentioned **pull request at [2].** A direct link to the repository can be found at [3] (Make sure to get the world-interface branch). We will use C:\OpenPASS\thirdParty\sources as target directory. Compile OSI using the following commands executed from the source directory.

1. Create build directory

```
> mkdir build
> cd build
```

2. Run CMake. As I could not make CMake find protobuf in the custom installation directory, we specify the paths manually here.

```
> cmake -G "MinGW Makefiles" -DCMAKE_BUILD_TYPE=Release
-DCMAKE_INSTALL_PREFIX=C:/OpenPASS/thirdParty
-DProtobuf_INCLUDE_DIR=C:/OpenPASS/thirdParty/include
-DProtobuf_PROTOC_EXECUTABLE=C:/OpenPASS/thirdParty/bin/protoc.exe
-DProtobuf_LIBRARIES=C:/OpenPASS/thirdParty/lib ..
```

3. Adding linker flags for protobuf

```
Edit the file C:\OpenPASS\thirdParty\sources\open-simulation-interface\build\CMakeFiles\open_simulation_interface.dir\linklibs.rsp
```

Add "-LC:/OpenPASS/thirdParty/lib -lprotobuf" to the end of the line. *If anybody knows how to avoid this step, please drop a note.* 

4. Compilation



```
> mingw32-make -j3
```

5. Installation

```
> mingw32-make install
```

- 6. Final steps
  - a. Include path fix: rename thirdParty/include/osi3 to osi
  - b. Copy libopen simulation interface.dll from lib/osi3 subfolder to lib

The OSI class documentation is part of the source code and can be compiled using Doxygen. Instructions are located in the OSI Readme.md. A Pre-compiled version is located here: <a href="https://opensimulationinterface.github.io/open-simulation-interface/index.html">https://opensimulationinterface.github.io/open-simulation-interface/index.html</a>. Note that this version of the documentation doesn't include the extensions from the OSI WorldInterface pull request.

#### 4.5 boost

Boost consists of multiple libraries, many of them being header-only <a>[6]</a>. At the moment, World\_OSI only makes use of the algorithm, math and geometry header-only-libraries.

- 1. Download and extract boost from [7]. Boost version 1.63 was used during development of World\_OSI. Newer versions should be compatible, but have not been tested yet.
- 2. Extract downloaded archive to a temporary directory
- 3. Copy the boost subfolder to your thirdParty/include directory

## 4.6 Google Test and Google Mock

For unit-testing, World\_OSI and other modules make use of the gtest/gmock framework. Installation requires <code>cmake</code>, just like <code>protobuf</code>, which was mentioned above.

- Download a release from [8].
   Version 1.8.1 has been used during development.
- 2. Extract the archive to a temporary directory
- 3. Open a MinGW shell at the extraction directory
- 4. Create the build directory

```
> mkdir build
> cd build
```

5. Run CMake

```
> cmake -G "MinGW Makefiles"
-DCMAKE INSTALL PREFIX=C:/OpenPASS/thirdParty ...
```



#### 6. Compilation

```
> mingw32-make
```

#### 7. Installation

```
> mingw32-make install
```

## 4.7 Modelon FMI Library

If the component Algorithm\_FmuWrapper is to be used, the FMI Library is an additional dependency for compiling and running openPASS. FMI Library uses the CMake build system and requires minor patching:

- 1. Download release 2.0.3 from [11]
- 2. Extract archive to a temporary director
- 3. Open a MinGW shell at the extraction directory
- 4. Apply the patch below

(Algorithm\_FmuWrapper uses code from FMU Compliance Checker [12], which has dependencies on some additional symbols in FMI Library)

```
diff --git a/src/Util/include/JM/jm_portability.h
b/src/Util/include/JM/jm_portability.h
index 82e472a..a9acc3f 100644
--- a/src/Util/include/JM/jm_portability.h
+++ b/src/Util/include/JM/jm_portability.h
@@ -65,6 +65,7 @@ jm_status_enu_t jm_portability_get_current_working_directory(char*
buffer, size_
    jm_status_enu_t jm_portability_set_current_working_directory(const char* cwd);

/** \brief Get system-wide temporary directory */
+FMILIB_EXPORT
    const char* jm_get_system_temp_dir();

/**
@@ -118,6 +119,7 @@ jm_status_enu_t jm_mkdir(jm_callbacks* cb, const char* dir);
/**
\brief Remove directory and all it contents.
*/
+FMILIB_EXPORT
jm_status_enu_t jm_rmdir(jm_callbacks* cb, const char* dir);
/**
```

#### 5. Create the build directory

```
> mkdir build
> cd build
```

### 6. Run CMake

```
> cmake -G "MinGW Makefiles"
-DFMILIB_INSTALL_PREFIX=C:/OpenPASS/thirdParty
-DFMILIB_BUILD_TYPE=Release
-DFMILIB_BUILD_STATIC_LIB=OFF
-DFMILIB_BUILD_SHARED_LIB=ON ..
```



#### 7. Compilation

> mingw32-make

#### 8. Installation

> mingw32-make install

9. Move the FMI Library headers (located in C:\OpenPASS\thirdParty\include) into a new subfolder C:\OpenPASS\thirdParty\include\FMILibrary. The files/folders to be moved are: FMI, FMI1, FMI2, JM, fmilib.h and fmilib config.h.

# 5 Compiling openPASS

The variables EXTRA\_LIB\_PATH and EXTRA\_INCLUDE\_PATH are set to C:/OpenPASS/thirdParty/lib and C:/OpenPASS/thirdParty/include by default. Please adapt the paths in the OpenPass\_Source\_Code/defaults.pri in case you are using different locations. It is also possible to pass these variables on the qmake command line, which will then override the default values.

**NOTE:** On windows, path length limitations apply during building which often causes the build to fail. To overcome this problem, it is recommended to copy the folder <code>OpenPass\_Source\_Code</code> directly to your drive <code>C:</code> and rename it in order to have a short name (e.g. <code>OP)</code>. Same applies to the build directory, which can be changed under <code>Projects</code>  $\rightarrow$  <code>Build Settings</code>  $\rightarrow$  <code>Build directory</code> after opening the project file.

Build the  $OpenPASS\_OSI\_UseCase.pro$  project to build the simulation core with all components and the graphical user interface.

## 6 Simulation

The proposed demo scenario can be simulated using the configuration files from OpenPass\_Source\_Code/openPASS\_Resource/OpenPass\_OSI\_UseCase.

**NOTE:** Remember to copy the required third party libraries (see table below) to the directory, where the OpenPassSlave.exe is located. Dependency locations during runtime are (mostly) independent from compile-time locations. Alternatively, you can add a directory containing these libraries to the PATH environment variable.

Required third party libraries	Location to get the libraries from
libprotobuf.dll libopen_simulation_interface.dll libfmilib_shared.dll (optional)	C:\OpenPASS\thirdParty\lib
Qt5Xml.dll Qt5Core.dl	<pre>Qt install directory (e.g. C:\Qt\Qt5.12.2\Tools\QtCreator\bin )</pre>
libwinpthread-1.dll libstdc++-6.dll libgcc_s_seh-1.dll	MinGW install directoy (e.g. C:\Qt\mingw- w64\x86_64-8.1.0-posix-seh-rt_v6- rev0\mingw64\bin )



# 7 References

[1]	https://github.com/OpenSimulationInterface/open-simulation-interface
[2]	https://github.com/OpenSimulationInterface/open-simulation-interface/pull/244
[3]	https://github.com/ReinhardBiegelIntech/open-simulation-interface/tree/world-interface
[4]	https://github.com/protocolbuffers/protobuf/releases
[5]	https://cmake.org/files/v3.9/
[6]	https://www.boost.org/
[7]	https://sourceforge.net/projects/boost/files/boost/
[8]	https://github.com/google/googletest
[9]	https://sourceforge.net/projects/mingw-w64/
[10]	https://git.eclipse.org/r/#/admin/projects/simopenpass/simopenpass
[11]	https://github.com/modelon-community/fmi-library
[12]	https://github.com/modelica-tools/FMUComplianceChecker