

The IMP Programming Language

Christiano Braga
cbraga@ic.uff.br

Instituto de Computação
Universidade Federal Fluminense



Abstract. IMP is a simple imperative programming language created to illustrate the use of the Basic Programming Languages Constructs library ([BPLC](#)). It is implemented in the [Maude](#) language.

1 IMP syntax

$\langle \text{program} \rangle ::= \text{'module' } \langle \text{ident} \rangle \langle \text{clauses} \rangle \text{'end'}$

$\langle \text{clauses} \rangle ::= \langle \text{var} \rangle^? \langle \text{const} \rangle^? \langle \text{init} \rangle^? \langle \text{proc} \rangle^+$

$\langle \text{var} \rangle ::= \text{'var' } \langle \text{ident} \rangle^+$

$\langle \text{const} \rangle ::= \text{'const' } \langle \text{ident} \rangle^+$

$\langle \text{init} \rangle ::= \text{'init' } \langle \text{ini} \rangle^+$

$\langle \text{ini} \rangle ::= \langle \text{ident} \rangle \text{'=' } \langle \text{exp} \rangle$

$\langle \text{proc} \rangle ::= \text{'proc' } \langle \text{ident} \rangle \text{'(' } \langle \text{ident} \rangle^* \text{' ')} \langle \text{block} \rangle$

$\langle \text{block} \rangle ::= \text{'{' } \langle \text{cmd} \rangle^+ \text{'}'}$

$\langle \text{cmd} \rangle ::= \langle \text{ident} \rangle \text{' := ' } \langle \text{exp} \rangle$
| $\langle \text{if} \rangle$ | $\langle \text{while} \rangle$ | $\langle \text{print} \rangle$ | $\langle \text{exit} \rangle$
| $\langle \text{call} \rangle$ | $\langle \text{seq} \rangle$ | $\langle \text{choice} \rangle$

$\langle \text{if} \rangle ::= \text{'if' } \langle \text{boolexp} \rangle \langle \text{cmd} \rangle \text{'else' } \langle \text{cmd} \rangle$
| $\text{'if' } \langle \text{boolexp} \rangle \langle \text{cmd} \rangle \text{'else' } \langle \text{block} \rangle$
| $\text{'if' } \langle \text{boolexp} \rangle \langle \text{block} \rangle \text{'else' } \langle \text{cmd} \rangle$
| $\text{'if' } \langle \text{boolexp} \rangle \langle \text{block} \rangle \text{'else' } \langle \text{block} \rangle$

$\langle \text{while} \rangle ::= \text{'while' } \langle \text{boolexp} \rangle \langle \text{block} \rangle$

$\langle \text{print} \rangle ::= \text{'print' '(' } \langle \text{exp} \rangle \text{')'}$

$\langle \text{exit} \rangle ::= \text{'exit' '(' } \langle \text{exp} \rangle \text{')'}$

```

⟨call⟩ := ⟨ident⟩ '(' ⟨exp⟩ '*' ')'
⟨seq⟩ := ⟨cmd⟩ ';' ⟨cmd⟩
⟨choice⟩ := ⟨cmd⟩ '|' ⟨cmd⟩
⟨exp⟩ := ⟨ident⟩
      | ⟨ident⟩ ⟨arithop⟩ ⟨ident⟩
      | ⟨boolexp⟩
⟨arithop⟩ := '+' | '-' | '*' | '|' | '/'
⟨boolexp⟩ := ⟨ident⟩ ⟨boolop⟩ ⟨ident⟩
⟨boolop⟩ := '~' | '=' | '<' | '<=' | '>' | '>='

```

2 IMP semantics

2.1 Genralized SMC Machines & BPLC

2.2 GSMC Rules for IMP

3 Maude implementation

3.1 A Maude primer

3.2 Parser

Module TOKEN specifies what Tokens, TokenLists and NeTokenList are. They are constructed with operators token, bubble and neTokenList, where attribute Exclude specify which terms are not to be constructed by the given constructor.

```

⟨token-module⟩≡
  fmod TOKEN is
    pr QID-LIST .
    sorts Token Bubble TokenList NeTokenList .
    subsort Token < TokenList .

    op _,_ : TokenList TokenList -> TokenList [assoc prec 5] .

    op token : Qid -> Token
      [special
        (id-hook Bubble          (1 1)
         op-hook qidSymbol      (<Qids> : ~> Qid)
         id-hook Exclude        ( true false nop print ))] .

    op bubble : QidList -> Bubble
      [special
        (id-hook Bubble          (1 -1)
         op-hook qidListSymbol  (__ : QidList QidList ~> QidList)

```

```

        op-hook qidSymbol      (<Qids> : ~> Qid)
        id-hook Exclude       ( | if then else end { }
                               while ; := = nop )) ] .

op neTokenList : QidList -> NeTokenList
[special
  (id-hook Bubble            (1 -1)
   op-hook qidListSymbol    (__ : QidList QidList ~> QidList)
   op-hook qidSymbol        (<Qids> : ~> Qid)
   id-hook Exclude          ( . ))] .
endfm

```

Module IMP-GRAMMAR implements the grammar of Section 1 in Maude. Each sort implements a non-terminal of the grammar in Section 1 whereas constants, tokens, as described in module TOKEN, or operators implement terminals. For instance, the following rule in the grammar of Section 1

$\langle proc \rangle := 'proc' \langle ident \rangle '(' \langle ident \rangle^* ')' \langle block \rangle$

is implemented in Module IMP-GRAMMAR by the operation declarations

```
1 op proc\_\_ : Token BlockCommandDecl -> ProcDecl [prec 50] .
2 op proc\_ '(' \_ ')' \_ : Token TokenList BlockCommandDecl -> ProcDecl [prec 50] .
```

together with the declarations for sorts ProcDecl and BlockCommandDecl.

```
 $\langle imp\text{-}grammar\text{-}module \rangle \equiv$ 
fmod IMP-GRAMMAR is
  pr TOKEN .
  pr RAT .
  inc PREDICATE-DECL .
  inc COMMAND-DECL .
  sorts VariablesDecl ConstantsDecl OperationsDecl ProcDeclList
         ProcDecl FormalsDecl BlockCommandDecl ExpressionDecl
         InitDecl InitDeclList InitDecls ClausesDecl
         ModuleDecl Expression .

  subsort InitDecl < InitDeclList .
  subsort VariablesDecl ConstantsDecl ProcDeclList
         InitDecls < ClausesDecl .
  subsort BlockCommandDecl < CommandDecl .
  subsort ProcDecl < ProcDeclList .
  subsort PredicateDecl < ExpressionDecl .

  *** Boolean expressions
  op _==_ : Token Token -> PredicateDecl [prec 30] .
  op _==_ : Token ExpressionDecl -> PredicateDecl [prec 30] .
  op _==_ : ExpressionDecl Token -> PredicateDecl [prec 30] .
  op _==_ : ExpressionDecl ExpressionDecl -> PredicateDecl
         [prec 30] .
  op _/\_ : PredicateDecl PredicateDecl -> PredicateDecl
         [assoc comm prec 35] .
  op ~ : PredicateDecl -> PredicateDecl .

  *** Arithmetic expressions
  op _+_ : Token Token -> ExpressionDecl [gather(e E) prec 15] .
  op _+_ : Token ExpressionDecl -> ExpressionDecl [gather(e E) prec 15] .
  op _+_ : ExpressionDecl Token -> ExpressionDecl [gather(e E) prec 15] .
  op _+_ : ExpressionDecl ExpressionDecl -> ExpressionDecl
         [gather(e E) prec 15] .
```

```

op _- : Token Token -> ExpressionDecl [gather(e E) prec 15] .
op _- : Token ExpressionDecl -> ExpressionDecl [gather(e E) prec 15] .
op _- : ExpressionDecl Token -> ExpressionDecl [gather(e E) prec 15] .
op _- : ExpressionDecl ExpressionDecl -> ExpressionDecl
    [gather(e E) prec 15] .

op *_ : Token Token -> ExpressionDecl [gather(e E) prec 10] .
op *_ : Token ExpressionDecl -> ExpressionDecl [gather(e E) prec 10] .
op *_ : ExpressionDecl Token -> ExpressionDecl [gather(e E) prec 10] .
op *_ : ExpressionDecl ExpressionDecl -> ExpressionDecl
    [gather(e E) prec 10] .

op _/ : Token Token -> ExpressionDecl [prec 20] .
op _/ : Token ExpressionDecl -> ExpressionDecl [prec 20] .
op _/ : ExpressionDecl Token -> ExpressionDecl [prec 20] .
op _/ : ExpressionDecl ExpressionDecl -> ExpressionDecl [prec 20] .

*** Commands
op _:= : Token Token -> CommandDecl [prec 40] .
op _:= : Token ExpressionDecl -> CommandDecl [prec 40] .

op _() : Token -> CommandDecl .
op _(_) : Token Bubble -> CommandDecl .
op print : Token -> CommandDecl .
op print : ExpressionDecl -> CommandDecl .
op _;_ : CommandDecl CommandDecl -> CommandDecl [assoc prec 50] .
op _|_ : CommandDecl CommandDecl -> CommandDecl [assoc prec 50] .
op while_do_ : PredicateDecl BlockCommandDecl -> CommandDecl [prec 40] .
op { _ } : CommandDecl -> BlockCommandDecl [prec 35] .
op if__else_ : PredicateDecl CommandDecl CommandDecl -> CommandDecl
    [prec 40] .

*** Declarations
op module__end : Token ClausesDecl -> ModuleDecl [prec 80] .
op __ : ClausesDecl ClausesDecl -> ClausesDecl [assoc comm prec 70] .
op var_ : TokenList -> VariablesDecl [prec 60] .
op const_ : TokenList -> ConstantsDecl [prec 60] .
op init_ : InitDecl -> InitDecls [prec 60] .
op init_ : InitDeclList -> InitDecls [prec 60] .
op _=_ : Token Token -> InitDecl [prec 40] .
op _=_ : Token ExpressionDecl -> InitDecl [prec 40] .
op _,_ : InitDeclList InitDeclList -> InitDeclList [assoc prec 50] .
op proc__ : Token BlockCommandDecl -> ProcDecl [prec 50] .
op proc_'(_)'_ : Token TokenList BlockCommandDecl -> ProcDecl
    [prec 50] .

```

```
  op __ : ProcDeclList ProcDeclList -> ProcDeclList  [assoc comm prec 60] .  
endfm
```

3.3 Compiling to BPLC

```
<compiler-to-bplc>≡
  load ../../../../maude/bplc.maude

mod COMPILE-IMP-TO-BPLC is
  inc PREDICATE-DECL .
  inc COMMAND-DECL .
  pr BPLC .
  pr META-LEVEL .

  *** Compiling IMP expressions to BPLC Exp.

  op compileId : Qid -> Id .
  eq compileId(I:Qid) = idn(downTerm(I:Qid, 'Qid)) .

  op compileId : Term -> Id .
  eq compileId('token[I:Qid]) =
    if (metaParse(upModule('RAT, false),
      downTerm(I:Qid, 'Qid), 'Rat) :: ResultPair)
      then rat(downTerm(getTerm(metaParse(upModule('RAT, false),
        downTerm(I:Qid, 'Qid), 'Rat)), 1/2))
    else
      if (metaParse(upModule('BOOL, false),
        downTerm(I:Qid, 'Qid), 'Bool) :: ResultPair)
        then boo(downTerm(getTerm(metaParse(upModule('BOOL, false),
          downTerm(I:Qid, 'Qid), 'Bool)), true))
        else idn(downTerm(I:Qid, 'Qid))
      fi
    fi .

  op compileExp : Term -> Exp .
  ceq compileExp(I:Qid) = compileId(I:Qid)
  if not(I:Qid :: Constant) .
  eq compileExp('token[I:Qid]) = compileId('token[I:Qid]) .
  eq compileExp('+_ [T1:Term, T2:Term]) =
    add(compileExp(T1:Term), compileExp(T2:Term)) .
  eq compileExp('_-_ [T1:Term, T2:Term]) =
    sub(compileExp(T1:Term), compileExp(T2:Term)) .
  eq compileExp('*_ [T1:Term, T2:Term]) =
    mul(compileExp(T1:Term), compileExp(T2:Term)) .
  eq compileExp('/_ [T1:Term, T2:Term]) =
    div(compileExp(T1:Term), compileExp(T2:Term)) .
  eq compileExp('true.PredicateDecl) = boo(true) .
  eq compileExp('false.PredicateDecl) = boo(false) .
  eq compileExp('~[T:Term]) = neg(compileExp(T:Term)) .
```

```

eq compileExp('_/\_[T1:Term,T2:Term]) =
    and(compileExp(T1:Term), compileExp(T2:Term)) .
eq compileExp('_\/_[T1:Term,T2:Term]) =
    or(compileExp(T1:Term), compileExp(T2:Term)) .
eq compileExp('==_[T1:Term,T2:Term]) =
    eq(compileExp(T1:Term), compileExp(T2:Term)) .
eq compileExp('>_[T1:Term,T2:Term]) =
    gt(compileExp(T1:Term), compileExp(T2:Term)) .
eq compileExp('>=_[T1:Term,T2:Term]) =
    ge(compileExp(T1:Term), compileExp(T2:Term)) .
eq compileExp('<_[T1:Term,T2:Term]) =
    lt(compileExp(T1:Term), compileExp(T2:Term)) .
eq compileExp('<=_[T1:Term,T2:Term]) =
    le(compileExp(T1:Term), compileExp(T2:Term)) .

*** Compiling IMP commands to BPLC Cmd.

op compileCmd : Term -> Cmd .
eq compileCmd('nop.CommandDecl) = nop .
eq compileCmd(':=_[I:Qid], T:Term]) =
    assign(compileId('token[I:Qid]), compileExp(T:Term)) .
eq compileCmd('{'_'}[T:Term]) = blk(compileCmd(T:Term)) .
eq compileCmd(';_[T1:Term, T2:Term]) =
    seq(compileCmd(T1:Term), compileCmd(T2:Term)) .
eq compileCmd('|_[T1:Term, T2:Term]) =
    choice(compileCmd(T1:Term), compileCmd(T2:Term)) .
eq compileCmd('if__else_[T1:Term, T2:Term, T3:Term]) =
    if(compileExp(T1:Term), compileCmd(T2:Term),
        compileCmd(T3:Term)) .
eq compileCmd('while_do_[T1:Term, T2:Term]) =
    loop(compileExp(T1:Term), compileCmd(T2:Term)) .
eq compileCmd('print[T:Term]) = print(compileId(T:Term)) .

*** Compiling IMP commands to BPLC Cmd:
*** Procedure calls deserve more attention...

eq compileCmd('_(('[I:Qid])) =
    cal(compileId('token[I:Qid])) .
eq compileCmd('_(('[I:Qid], 'bubble[Q:Qid])) =
    cal(compileId('token[I:Qid]), compileActuals(Q:Qid)) .
eq compileCmd('_(('[I:Qid],
    'bubble['__[TL:TermList]])) =
    cal(compileId('token[I:Qid]), compileActuals(TL:TermList)) .

op compileActuals : TermList -> Actuals .

```



```

eq compileActuals(Q:Qid) = compileId('token[Q:Qid]) .
eq compileActuals((TL1:TermList, "','.Qid , TL2:TermList)) =
  act(makeExp(TL1:TermList) , compileActuals(TL2:TermList)) .
eq compileActuals(TL:TermList) = makeExp(TL:TermList) [owise] .

op makeExp : TermList -> Exp .
eq makeExp(Q:Qid) = compileId(Q:Qid) .
ceq makeExp(TL:TermList) =
  compileExp(
    getTerm(
      metaParse(upModule('IMP-GRAMMAR, false),
        makeExprDeclQidList(TL:TermList), 'ExpressionDecl)))
  if (metaParse(upModule('IMP-GRAMMAR, false),
    makeExprDeclQidList(TL:TermList), 'ExpressionDecl) ::
    ResultPair) .

op makeExprDeclQidList : TermList -> QidList .
eq makeExprDeclQidList((empty).TermList) = (nil).QidList .
ceq makeExprDeclQidList(Q:Qid) = downTerm(Q:Qid, 'error)
  if downTerm(Q:Qid, 'error) /= 'error .
eq makeExprDeclQidList((Q:Qid , TL:TermList)) =
  makeExprDeclQidList(Q:Qid) makeExprDeclQidList(TL:TermList) .

*** Compiling IMP declarations to BPLC Dec.

*** Compiling variables. The initialization clause is
*** necessary to properly declare variables according to BPLC
*** ref construct.

op compileVar : Term Term -> Dec .
op $compileVar : Term Term -> Dec .
eq compileVar('var_[TL1:TermList], 'init_[TL2:TermList]) =
  $compileVar(TL1:TermList, TL2:TermList) .
eq $compileVar('token[I:Qid], '_=[ 'token[I:Qid], T:Term]) =
  ref(compileId('token[I:Qid]), compileExp(T:Term)) .
eq $compileVar('token[I:Qid],
  ('_',[ '_=[ 'token[I:Qid], T:Term], TL:TermList])) =
  ref(compileId('token[I:Qid]), compileExp(T:Term)) .
ceq $compileVar('token[I1:Qid],
  ('_',[ '_=[ 'token[I2:Qid], T:Term], TL:TermList])) =
  $compileVar('token[I1:Qid], TL:TermList)
  if I1:Qid /= I2:Qid .
eq $compileVar('_',[ '_=[ 'token[I:Qid], IS:TermList],
  '_=[ 'token[I:Qid], T:Term]) =
  ref(compileId('token[I:Qid]), compileExp(T:Term)) .

```

```

eq $compileVar(''_[_'token[I:Qid], IS:TermList],
               ''[_[TL:TermList]]) =
  dec($compileVar('token[I:Qid], ''[_[TL:TermList]]),
      $compileVar(IS:TermList, ''[_[TL:TermList]])) .

*** Compiling constants.
op compileConst : Term Term -> Dec .
op $compileConst : Term Term -> Dec .
eq compileConst('const_[T1:Term], 'init_[T2:Term]) =
  $compileConst(T1:Term, T2:Term) .
eq $compileConst('token[I:Qid],
                 ''[_'token[I:Qid], T:Term]) =
  cns(compileId('token[I:Qid]), compileExp(T:Term)) .
eq $compileConst('token[I:Qid],
                 (''_[_'[_'token[I:Qid], T:Term], TL:TermList])) =
  cns(compileId('token[I:Qid]), compileExp(T:Term)) .
ceq $compileConst('token[I1:Qid],
                  (''_[_'[_'token[I2:Qid], T:Term], TL:TermList])) =
  $compileConst('token[I1:Qid], TL:TermList)
if I1:Qid /= I2:Qid .
eq $compileConst(''_[_'token[I:Qid], IS:TermList],
                 ''[_'token[I:Qid], T:Term]) =
  cns(compileId('token[I:Qid]), compileExp(T:Term)) .
eq $compileConst(''_[_'token[I:Qid], IS:TermList], ''[_[TL:TermList]]) =
  dec($compileConst('token[I:Qid], ''[_[TL:TermList]]),
      $compileConst(IS:TermList, ''[_[TL:TermList]])) .

*** Compiling procedure declarations.
op compileProc : TermList -> Dec .
op compileToFormals : TermList -> Formals .
eq compileProc('__[TL1:TermList, TL2:TermList]) =
  dec(compileProc(TL1:TermList), compileProc(TL2:TermList)) .
eq compileProc('proc__[token[0:Qid], TL:TermList, T:Term]) =
  prc(compileId('token[0:Qid]), compileCmd(T:Term)) .
eq compileProc('proc_'(_')_'token[0:Qid], TL:TermList, T:Term]) =
  prc(compileId('token[0:Qid]),
      compileToFormals(TL:TermList), compileCmd(T:Term)) .
eq compileToFormals('token[0:Qid]) = par(compileId('token[0:Qid])) .
eq compileToFormals(''_[_[TL1:TermList, TL2:TermList]]) =
  for(compileToFormals(TL1:TermList), compileToFormals(TL2:TermList)) .

*** Compiling modules.
op compileMod : Term -> Dec .
eq compileMod('module__end['token[I:Qid],
               ''[_'var_[T1:Term],

```

```

        '__['const_[T2:Term],
        '__['init_[T3:Term],
            T:Term]]])) =
    dec(compileVar('var_[T1:Term], 'init_[T3:Term]),
        dec(compileConst('const_[T2:Term], 'init_[T3:Term]),
            compileProc(T:Term))) .
eq compileMod('module__end['token[I:Qid],
    '__['var_[T1:Term],
    '__['init_[T3:Term],
        T:Term]])) =
    dec(compileVar('var_[T1:Term], 'init_[T3:Term]),
        compileProc(T:Term)) .
eq compileMod('module__end['token[I:Qid],
    '__['var_[T1:Term],
    '__['const_[T2:Term],
    '__['init_[T3:Term],
        '__[TL:TermList]]]])) =
    dec(compileVar('var_[T1:Term], 'init_[T3:Term]),
        dec(compileConst('const_[T2:Term], 'init_[T3:Term]),
            compileProc('__[TL:TermList])))) .
eq compileMod('module__end['token[I:Qid],
    '__['var_[T1:Term],
    '__['init_[T3:Term],
        '__[TL:TermList]]]])) =
    dec(compileVar('var_[T1:Term], 'init_[T3:Term]),
        compileProc('__[TL:TermList])) .
endm

```

3.4 Pretty-printing IMP programs, their execution and model checking results

```

<imp-pretty-printing>≡
mod IMP-PRETTY-PRINTING is
  pr BPLC-MODEL-CHECKER .
  pr INT .

  *** Some auxiliary constants and functions.
  ops level incr : -> Nat .
  eq level = 3 .
  eq incr = 3 .

  op printSpaces : Nat -> QidList .
  eq printSpaces(0) = (nil).QidList .
  eq printSpaces(N:Nat) = '\s printSpaces(sd(N:Nat, 1)) .

  op printTermList : TermList -> QidList .
  eq printTermList(empty) = (nil).QidList .
  eq printTermList((Q:Qid,TL:TermList)) =
    downTerm(Q:Qid,'Qid) printTermList(TL:TermList) .

  op printTokens : Term -> QidList .
  eq printTokens(Q:Qid) = Q:Qid .
  eq printTokens('token[Q:Qid]) = downTerm(Q:Qid, 'Qid) .
  eq printTokens('_',[T1:Term, T2:Term]) =
    printTokens(T1:Term) printToken('_',) '\s printTokens(T2:Term) .

  *** Pretty-printing IMP Expressions
  op printExp : Term -> QidList .
  eq printExp('true.PredicateDecl) = 'true .
  eq printExp('false.PredicateDecl) = 'false .
  eq printExp('bubble['_[TL:TermList]]) = printTermList(TL:TermList) .
  eq printExp('token[Q:Qid]) = downTerm(Q:Qid, 'Qid) .
  eq printExp('==_[T1:Term, T2:Term]) =
    printExp(T1:Term) printToken('==) printExp(T2:Term) .
  eq printExp('\/_[T1:Term, T2:Term]) =
    printExp(T1:Term) printToken('\/) printExp(T2:Term) .
  eq printExp('_/\_[T1:Term, T2:Term]) =
    printExp(T1:Term) printToken('_\/) printExp(T2:Term) .
  eq printExp('~[T:Term]) =
    printToken('~) printExp(T:Term) .
  eq printExp('<_[T1:Term, T2:Term]) =
    printExp(T1:Term) printToken('<) printExp(T2:Term) .
  eq printExp('<=_[T1:Term, T2:Term]) =
    printExp(T1:Term) printToken('<=) printExp(T2:Term) .
  eq printExp('>_[T1:Term, T2:Term]) =

```

```

    printExp(T1:Term) printToken('>') printExp(T2:Term) .
eq printExp('>=_[T1:Term, T2:Term]') =
    printExp(T1:Term) printToken('>=') printExp(T2:Term) .
eq printExp('>+_[T1:Term, T2:Term]') =
    printExp(T1:Term) printToken('>+') printExp(T2:Term) .
eq printExp('>*_ [T1:Term, T2:Term]') =
    printExp(T1:Term) printToken('>*') printExp(T2:Term) .
eq printExp('>_-[T1:Term, T2:Term]') =
    printExp(T1:Term) printToken('>-') printExp(T2:Term) .
eq printExp('>/_[T1:Term, T2:Term]') =
    printExp(T1:Term) printToken('>/') printExp(T2:Term) .
eq printExp(T:Term) =
    metaPrettyPrint(upModule('IMP-GRAMMAR, false), T:Term) [owise] .

*** Pretty-printing IMP Commands
op printCmd : Term Nat -> QidList .
eq printCmd('nop.CommandDecl, N:Nat) = 'nop .
eq printCmd('print[T:Term], N:Nat) =
    printToken('print') printToken('(') printExp(T:Term) printToken('') .
eq printCmd('<_<(')[T1:Term, T2:Term], N:Nat) =
    printExp(T1:Term) printToken('<(') printExp(T2:Term) printToken('<') .
eq printCmd('<_|_[T1:Term, '<_<[T2:TermList]], N:Nat) =
    printSpaces(N:Nat)
    printCmd(T1:Term, N:Nat) printToken('<|') '\n
    printSpaces(N:Nat) printToken('<(')
    printCmd('<_<[T2:TermList], N:Nat) printToken('<') .
ceq printCmd('<_|_[T:TermList, F:Qid[TL:TermList]], N:Nat) =
    printSpaces(N:Nat) printCmd(T:TermList, N:Nat) printToken('<|')
    printCmd(F:Qid[TL:TermList], N:Nat)
if F:Qid != '<_< .
ceq printCmd('<_<[F1:Qid[TL1:TermList], F2:Qid[TL2:TermList]], N:Nat) =
    printCmd(F1:Qid[TL1:TermList], N:Nat) '\s printToken('<;')
    printCmd(F2:Qid[TL2:TermList], N:Nat)
if F1:Qid != '<_< and F2:Qid != '<_< .
ceq printCmd('<_<[F1:Qid[TL1:TermList], F2:Qid[TL2:TermList]], N:Nat) =
    printSpaces(N:Nat)
    printCmd(F1:Qid[TL1:TermList], N:Nat) '\s printToken('<;') '\n
    printSpaces(N:Nat)
    printCmd(F1:Qid[TL1:TermList], N:Nat)
if F1:Qid == '<_< or F2:Qid == '<_< .
eq printCmd('<_<=[T1:Term, T2:Term], N:Nat) =
    printExp(T1:Term) printToken('<:=') printExp(T2:Term) .
eq printCmd('<while_do_[T1:Term, T2:Term], N:Nat) =
    printToken('<while') ' printToken('<(') printExp(T1:Term) printToken('<') '
    printToken('<do')

```

```

    printCmd(T2:Term, N:Nat) .
eq printCmd('if__else_[T1:Term, T2:Term, T3:Term], N:Nat) =
    printToken('if) ' printToken('(') printExp(T1:Term) printToken(')') '
    printCmd(T2:Term, N:Nat)
    '\s printToken('else) printCmd(T3:Term, N:Nat) .
eq printCmd('{_}[C:Constant], N:Nat) =
    '\s printToken('{)
    printCmd(C:Constant, 0)
    printToken('}') .
eq printCmd('{_}[_][TL:TermList]], N:Nat) =
    '\s printToken('{) '\n
    printSpaces(N:Nat + incr)
    printCmd('_[_][TL:TermList], N:Nat + incr) '\n
    printSpaces(N:Nat) printToken('}') .
eq printCmd('{_}[_|_][TL:TermList]], N:Nat) =
    '\s printToken('{) '\n
    printCmd('_|_][TL:TermList], N:Nat + incr) '\n
    printSpaces(N:Nat) printToken('}') .
ceq printCmd('{_}[F:Qid[TL:TermList]], N:Nat) =
    '\s printToken('{) '\n
    printSpaces(N:Nat + incr)
    printCmd(F:Qid[TL:TermList], N:Nat + incr) '\n
    printSpaces(N:Nat) printToken('}')
if F:Qid /== '[_]_ /\ F:Qid /== '[_]_ .

eq printCmd(T:Term, N:Nat) =
    printSpaces(N:Nat)
    metaPrettyPrint(upModule('IMP-GRAMMAR, false), T:Term) [owise] .

*** Pretty-printing IMP Declarations
op printModule : Term -> QidList .
eq printModule('module__end[T1:Term, T2:Term]) =
    printToken('module) printTokens(T1:Term)
    printClauses(T2:Term)
    '\n printToken('end) .

op printClauses : Term -> QidList .
eq printClauses('proc__[T1:Term, T2:Term]) =
    '\n printSpaces(level)
    printToken('proc) printTokens(T1:Term)
    printCmd(T2:Term, level) .
eq printClauses('__[proc__[T1:Term, T2:Term], T3:Term]) =
    '\n printSpaces(level) printToken('proc) printTokens(T1:Term)
    printCmd(T2:Term, level)
    printClauses(T3:Term) .

```

```

eq printClauses('proc_'[_']_[T1:Term, T2:Term, T3:Term]) =
  '\n printSpaces(level)
  printToken('proc') printTokens(T1:Term)
  printToken(''(') printTokens(T2:Term) printToken('')
  printCmd(T3:Term, level) .
eq printClauses('__[']_'proc_'[_']_[T1:Term, T2:Term, T3:Term], T4:Term)) =
  '\n printSpaces(level) printToken('proc')
  printTokens(T1:Term) printToken(''(') printTokens(T2:Term) printToken('')
  printCmd(T3:Term, level)
  printClauses(T4:Term) .
eq printClauses('__[']_'init_'[T1:Term], T2:Term)) =
  '\n printSpaces(level) printToken('init')
  printInit(T1:Term) printClauses(T2:Term) .
eq printClauses('__[']_'const_'[T1:Term], T2:Term)) =
  '\n printSpaces(level) printToken('const')
  printTokens(T1:Term) printClauses(T2:Term) .
eq printClauses('__[']_'var_'[T1:Term], T2:Term)) =
  '\n printSpaces(level) printToken('var')
  printTokens(T1:Term) printClauses(T2:Term) .

op printInit : Term -> QidList .
eq printInit('=_'[T1:Term, T2:Term]) =
  printTokens(T1:Term) printToken('=') printExp(T2:Term) .
eq printInit('=_','[T1:Term, T2:Term]) =
  printInit(T1:Term) printToken(',') '\s printInit(T2:Term) .

*** Pretty-printing parse error
op printQidList : QidList -> QidList .
eq printQidList(nil) = (nil).QidList .
eq printQidList(Q:Qid QL:QidList) = printToken(Q:Qid) printQidList(QL:QidList) .

op printToken : Qid -> Qid .
eq printToken(Q:Qid) = '\b '\! Q:Qid '\o .

op printInputWithError : QidList Nat -> QidList .
op $printInputWithError : QidList Int QidList -> QidList .
eq printInputWithError(QL:QidList, N:Nat) =
  $printInputWithError(QL:QidList, N:Nat, (nil).QidList) .
eq $printInputWithError(nil, I:Int, QL:QidList) = QL:QidList .
eq $printInputWithError(QL:QidList, 0, (nil).QidList) = (nil).QidList .
ceq $printInputWithError(QL1:QidList, 0, (QL2:QidList Q:Qid)) =
  QL2:QidList '\r '\u '>> Q:Qid '<< 'HERE '\o
  printQidList(QL1:QidList)
if QL2:QidList /= nil .
eq $printInputWithError(Q:Qid QL1:QidList, I:Int, QL2:QidList) =

```

```

    $printInputWithError(QL1:QidList, (I:Int + (- 1)), QL2:QidList
      printToken(Q:Qid)) .

op printParseError : QidList ResultPair? -> Qid .
eq printParseError('module Q:Qid QL:QidList , noParse(N:Nat)) =
  'IMP: 'Error 'at 'position
  metaPrettyPrint(upModule('NAT, false), upTerm(N:Nat))
    'while 'parsing 'Module Q:Qid ': '\n
    printInputWithError(('module Q:Qid QL:QidList), N:Nat) .
eq printParseError(QL:QidList, ambiguity(T1:ResultPair, T2:ResultPair)) =
  'IMP: '\r 'Ambiguous 'parse '\o '\n
  metaPrettyPrint(upModule('IMP-GRAMMAR, false), getTerm(T1:ResultPair)) '\n
  '\r 'vs. '\o '\n
  metaPrettyPrint(upModule('IMP-GRAMMAR, false), getTerm(T2:ResultPair)) .

*** Pretty-print exec and mc output
op printState : Env Store -> QidList .
eq printState(noEnv, S:Store) = (nil).QidList .
eq printState((I:Id |-> bind(L:Loc)) , ((L:Loc |-> store(R:Rat)), S:Store)) =
  printId(I:Id) '= metaPrettyPrint(upModule('RAT, false), upTerm(R:Rat)) .
ceq printState(((I:Id |-> bind(L:Loc)), E:Env) ,
  ((L:Loc |-> store(R:Rat)), S:Store)) =
  printId(I:Id) '=
  metaPrettyPrint(upModule('RAT, false), upTerm(R:Rat))
  printState(E:Env , (L:Loc |-> store(R:Rat), S:Store))
if E:Env /= noEnv .
eq printState((I:Id |-> bind(L:Loc)), (L:Loc |-> store(B:Bool), S:Store)) =
  printId(I:Id) '= metaPrettyPrint(upModule('BOOL, false), upTerm(B:Bool)) .
ceq printState(((I:Id |-> bind(L:Loc)), E:Env) ,
  ((L:Loc |-> store(B:Bool)), S:Store)) =
  printId(I:Id) '= metaPrettyPrint(upModule('RAT, false), upTerm(B:Bool)) ' ',
  printState(E:Env , (L:Loc |-> store(B:Bool), S:Store))
if E:Env /= noEnv .
eq printState(((I:Id |-> B:Bindable), E:Env) , S:Store) =
  printState(E:Env , S:Store) [owise] .

op printId : Id -> Qid .
eq printId(idn(Q:Qid)) = (Q:Qid).Qid .

op printCnt : ControlStack ValueStack -> QidList .
eq printCnt((LOOP C:ControlStack),
  (V:Value val(loop(E:Exp, K:Cmd)) VS:ValueStack)) =
  printToken('while) printToken('(') printExp(E:Exp) printToken(')') '... .
eq printCnt((choice(K1:Cmd, K2:Cmd) C:ControlStack), VS:ValueStack) =
  printCmd(K1:Cmd) printToken('|') printCmd(K2:Cmd) .

```



```

eq printCnt(C:ControlStack, VS:ValueStack) =
  '\n 'Constrol 'stack:
  metaPrettyPrint(upModule('BPLC+META-LEVEL, false),
    upTerm(C:ControlStack))
  '\n 'Value 'stack:
  metaPrettyPrint(upModule('BPLC+META-LEVEL, false),
    upTerm(VS:ValueStack)) .

op printExp : Exp -> QidList .
eq printExp(rat(R:Rat)) = '\g metaPrettyPrint(upModule('RAT, false),
  upTerm(R:Rat)) '\o .
eq printExp(boo(B:Bool)) = '\g metaPrettyPrint(upModule('B00L, false),
  upTerm(B:Bool)) '\o .
eq printExp(neg(E:Exp)) = printToken('~') printExp(E:Exp) .
eq printExp(and(E1:Exp, E2:Exp)) =
  printExp(E1:Exp) printToken('/') printExp(E2:Exp) .
eq printExp(eq(E1:Exp, E2:Exp)) =
  printExp(E1:Exp) printToken('==') printExp(E2:Exp) .
eq printExp(idn(Q:Qid)) = printTokens(Q:Qid) .
eq printExp(E:Exp) = metaPrettyPrint(upModule('BPLC, false), upTerm(E:Exp)) .

op printCmd : Cmd -> QidList .
eq printCmd(seq(C1:Cmd, C2:Cmd)) =
  printCmd(C1:Cmd) printToken(';') printCmd(C2:Cmd) .
eq printCmd(assign(I:Id, E:Exp)) =
  printExp(I:Id) printToken(':=') printExp(E:Exp) .
eq printCmd(if(E:Exp, C1:Cmd, C2:Cmd)) =
  printToken('if') printExp(E:Exp) '... .
eq printCmd(choice(C1:Cmd, C2:Cmd)) = printCmd(C1:Cmd)
  printToken('|') printCmd(C2:Cmd) .
eq printCmd(C:Cmd) = metaPrettyPrint(upModule('BPLC, false), upTerm(C:Cmd)) .

op printConf : Conf -> QidList .
eq printConf(< env : E:Env , sto : S:Store , exc : X:Exc ,
  cnt : C:ControlStack, val : V:ValueStack, ...:Set{SemComp} > ) =
  if X:Exc == CNT
  then printCnt(C:ControlStack, V:ValueStack) '[' printState(E:Env, S:Store) '['
  else 'IMP: 'Internal 'error 'while 'printing 'configuration.
  fi .

op printValueStack : ValueStack -> QidList .
eq printValueStack(evs) = '\b 'No 'output. '\o .
eq printValueStack(val(R:Rat) evs) =
  metaPrettyPrint(upModule('RAT, false), upTerm(R:Rat)) .
eq printValueStack(val(B:Bool) evs) =

```

```

    metaPrettyPrint(upModule('BOOL, false), upTerm(B:Bool)) .
eq printValueStack(V:Value VS:ValueStack) =
    printValueStack(V:Value) printValueStack(VS:ValueStack) .

op printOut : Conf -> QidList .
eq printOut(< out : O:ValueStack , ...:Set{SemComp} > ) =
    printValueStack(O:ValueStack) .

op printExec : Term ~> QidList .
ceq printExec(T:Term) = printOut(downTerm(T:Term, < noSemComp >))
if downTerm(T:Term, < noSemComp >) /= < noSemComp > .

op printTraceStep : TraceStep -> QidList .
eq printTraceStep({T:Term, Y:Type, R:Rule}) =
    printConf(downTerm(T:Term, < noSemComp >)) .

op printTrace : Trace Nat -> QidList .
eq printTrace(nil, N:Nat) = (nil).QidList .
eq printTrace(TS:TraceStep, N:Nat) =
    '\b 'State
    metaPrettyPrint(upModule('NAT, false),
        upTerm(N:Nat)) ': '\o '\n
    printTraceStep(TS:TraceStep) .
ceq printTrace(TS:TraceStep T:Trace, N:Nat) =
    '\b 'State
    metaPrettyPrint(upModule('NAT, false),
        upTerm(N:Nat)) ': '\o '\n
    printTraceStep(TS:TraceStep) '\n printTrace(T:Trace, (N:Nat + 1))
if T:Trace /= nil .

op printTransitionList : TransitionList -> QidList .
eq printTransitionList(nil) = (nil).QidList .
eq printTransitionList({C:Conf, R:RuleName}) = printConf(C:Conf) .
ceq printTransitionList({C:Conf, R:RuleName} TL:TransitionList) =
    printConf(C:Conf) '\b '-> '\o printTransitionList(TL:TransitionList)
if TL:TransitionList /= nil .

op printModelCheckResult : ModelCheckResult QidList -> QidList .
eq printModelCheckResult(B:Bool, QL:QidList) =
    'IMP: '\b 'Model 'check 'result 'to 'command
    '\c QL:QidList '\o '\b ': '\o '\n
    metaPrettyPrint(upModule('BOOL, false), upTerm(B:Bool)) .

eq printModelCheckResult(
    counterexample(TL1:TransitionList, TL2:TransitionList), QL:QidList) =

```

```

      'IMP: '\b 'Model 'check 'counter 'example 'to 'command
      '\c QL:QidList '\o '\b ': '\o '\n
      '\b 'Path 'from 'the 'initial 'state: '\o
      '\n printTransitionList(TL1:TransitionList)
      '\n '\b 'Loop: '\o
      '\n printTransitionList(TL2:TransitionList) .
endm

```

3.5 IMP command line interface

<imp-interface>≡

```
mod IMP-INTERFACE is
  pr LOOP-MODE * (sort State to LoopState).
  pr COMPILE-IMP-TO-BPLC .
  pr IMP-PRETTY-PRINTING .

  sorts Dec? MetaIMPModule Command IMPState .
  subsort Term < MetaIMPModule .
  subsort Dec < Dec? .
  subsort IMPState < LoopState .

  op noDec : -> Dec? .
  op noModule : -> MetaIMPModule .
  op idle : -> Command .
  op <_> : MetaIMPModule Dec? QidList -> IMPState .
  op init : -> System .
  op init'IMP'no'banner : -> System .
  op banner : -> QidList .

  eq banner = '\g 'IMP 'Prototype '\o '
              '( '\y '\! 'March '2018 '\o '' ) .
  eq init = [nil, < noModule ; noDec ; nil >, banner] .
  eq init'IMP'no'banner = [nil, < noModule ; noDec ; nil >, nil] .

  vars QIL QIL' QIL'' QIL1 QIL2 : QidList .

  rl [version] : ['version, L:LoopState, QIL] =>
    [nil, L:LoopState, banner] .

  *** Loading a module.
  crl [in] : ['module Q:Qid QIL,
              < M:MetaIMPModule ; D:Dec? ; QIL' >, QIL''] =>
    if (T:ResultPair? :: ResultPair)
    then [nil, < getTerm(T:ResultPair?) ;
              compileMod(getTerm(T:ResultPair?)) ;
              'IMP: '\b 'Module Q:Qid 'loaded. '\o >, QIL'']
    else [nil, < noModule ; noDec ; nil >,
          printParseError('module Q:Qid QIL, T:ResultPair?')]
    fi
  if T:ResultPair? :=
    metaParse(upModule('IMP-GRAMMAR, false),
              'module Q:Qid QIL, 'ModuleDecl) .

  *** Viewing a module.
```

```

crl [view] : ['view , < M:MetaIMPModule ; D:Dec ; QIL' >, QIL'] =>
    [nil, < M:MetaIMPModule ; D:Dec ; QIL' >,
      printModule(M:MetaIMPModule)]
if M:MetaIMPModule /= noModule .

*** Executing a command.
crl [exec-unbounded] : [('exec QIL),
    < M:MetaIMPModule ; D:Dec ; QIL' >, QIL'] =>
if P:ResultPair? :: ResultPair
then [nil, < M:MetaIMPModule ; D:Dec ; QIL' > ,
    if compileCmd(getTerm(P:ResultPair?)) :: Cmd
    then
        'IMP: '\b 'Execution 'result 'for '\c QIL '\o '\b ': '\o
        printExec(getTerm(metaRewrite(upModule('BPLC+META-LEVEL, false),
            'run[upTerm(compileCmd(getTerm(P:ResultPair?))),
                upTerm(D:Dec)], unbounded)))
        else 'IMP: '\r 'Internal 'Error 'while 'compiling '\s QIL
    fi ]
else [nil, < M:MetaIMPModule ; D:Dec ; QIL' >,
    'IMP: '\r 'Error 'while 'processing 'command '\o 'exec '\s QIL ]
fi
if P:ResultPair? :=
    metaParse(upModule('IMP-GRAMMAR, false), QIL, 'CommandDecl) .

*** Model check command
crl [mc] : [('mc QIL1 '|= QIL2),
    < 'module__end[T1:Term, T2:Term] ; D:Dec ; QIL' >, QIL'] =>
if ((P1:ResultPair? :: ResultPair) and (P2:ResultPair? :: ResultPair))
then [nil, < 'module__end[T1:Term, T2:Term] ; D:Dec ; QIL' >,
    if compileCmd(getTerm(P1:ResultPair?)) :: Cmd
    then
        printModelCheckResult(downTerm(
            getTerm(metaReduce(
                makeMCMModule(printTokens(T1:Term), D:Dec),
                '_','_|=?'[upTerm(D:Dec),
                upTerm(compileCmd(getTerm(P1:ResultPair?))),
                getTerm(P2:ResultPair?)])),true), QIL1 '\s '|= '\s QIL2)
        else 'IMP: '\r 'Internal 'Error 'while
            'processing 'command '\o 'mc QIL1 '|= QIL2
    fi ]
else [nil, < 'module__end[T1:Term, T2:Term] ; D:Dec ; QIL' >,
    'IMP: '\r 'Error 'while 'processing 'command '\o
    'mc QIL1 '|= QIL2]
fi
if P1:ResultPair? :=

```

```

        metaParse(upModule('IMP-GRAMMAR, false), QIL1, 'CommandDecl) /\
P2:ResultPair? :=
        metaParse(makeMCMModule(printTokens(T1:Term), D:Dec), QIL2, 'Formula) .

*** Output
crl [out] : [nil, < M:MetaIMPModule ; D:Dec? ; QIL' > , QIL''] =>
            [nil, < M:MetaIMPModule ; D:Dec? ; nil > , QIL']
if QIL' /= nil .

*** Command error
crl [com-error] : [Q:Qid QIL, < M:MetaIMPModule ; D:Dec ; QIL' > , QIL''] =>
            [nil, < M:MetaIMPModule ; D:Dec ; QIL' > ,
              'IMP: '\r 'Error 'no 'such 'command '\o Q:Qid QIL]
if (Q:Qid /= 'module) /\ (Q:Qid /= 'view) /\
   (Q:Qid /= 'exec) /\ (Q:Qid /= 'mc) .
endm

loop init .

```