

28/09

→ `docker stop containername`

↳ Running la isuka container a idle a maathum

→ `docker rm containername`

↳ Remove container.

* Running Container should be force removed or stopped before removal.

→ `docker rm -f containername`

↳ To forcefully remove.

→ `docker run -d --name sjc-devops imagename`
↳ daemon → background process.

↳ Launches a container & starts it.

↳ Opens in foreground. & not in background.

↳ `Ctrl+C` kidutha shut down aagum. Stop.

→ `docker exec -it sjc-devops /bin/bash`

↓
To open

↓
interactive terminal

↓
terminal oda path

(like windows naa
cund)

→ exit

↳ Comes out of the container.

→ apt update

↳ Everytime u open something in linux, update it

→ cd /htdocs.

↳ Apache o/a root directory



Contains source code which can be configured.

→ ip config.

↳ To find IP address.

→ docker run -d --name test -p 8082:80 httpd.

↓ host port

Port forwarding

* To search pannapo https use panna-koodathu because https requires SSL certificate.

→ Create panna container & port change panna nundiyathu

→ vi index.html.

↳ Will not open because the container is lightweight and does not contain text editor.

→ apt install vim

* CG NAT IP → IPs translate & give.

→ docker commit containername imagename:tag.

↳ To create snapshot (backup) of container.

↳ Stores in docker only

//_

→ `docker run -d --name demo -p 8080:80`

Snapshot: 1.0

↳ To create ~~new~~ container of customized image
→ `docker save snapshot:1.0 > demobackup.tar`

↳ To convert a backup image as a file.
↳ Stores to local system.
↳ Not able to load.

→ `docker save -o sjcbackup.tar snapshot:1.0`

→ `docker load -i sjcbackup.tar`
↳ To load backed up image.

Dockerfile :-

↳ Used to automatically build images.

Syntax :-

↳ Compulsorily caps

INSTRUCTION arguments

→ Dockerfile is a text document that contains all the commands a user could call on the command line to assemble an image.

Instructions :-

FROM :-

↳ Create a new build stage from base image

Eg:- `FROM ubuntu:latest`

RUN:-

- ↳ Execute build commands.
- ↳ Manual a parathra inga kudupom.

Eg:- RUN apt update

COPY:-

Eg:- COPY index.html /var/www/html
Source Destination.

→ Copy files & directories.

EXPOSE:-

- ↳ describe which ports your application is listening on.
- ↳ Set default port

Eg:- EXPOSE 80/tcp

WORKDIR

- ↳ Change working directory.
- ↳ Can set default path.

ENV:-

- ↳ Set Environment variables like user name

CMD:-

- ↳ Specify default commands
- ↳ Can Overwrite.

ENTRYPOINT :-

- ↳ Specify default executable.
- ↳ Cannot Overwrite.

→ `docker build -t customimg:latest .`

Diagram illustrating the command components:

- `-t` points to `tag.` → `Creates image`
- `customimg:latest` points to `where?` (Docker file)
- `.` points to `Current directory`

→ `mv (dockerfile.txt) dockerfile`

↳ Renames.

Docker Networks :-

* Bridge :-

- If network not mentioned, default is bridge.
- Eg:- `docker run ubuntu`.
- Communication b/w all containers.

~~* None :-~~

* None :-

- No Communication.
- Best for developing stage.