

# Polishing plots for communication

## Solution for yesterday's problem


```
housing_reshaped <- housing_raw %>%  
  gather(key = "time", value = "hpi",  
    -Geography, -`New housing price indexes`) %>%  
  spread(`New housing price indexes`, hpi)
```

```
housing_bc <- housing_reshaped %>%  
  mutate(date = lubridate::parse_date_time(time, order = "my")) %>%  
  filter(Geography %in% c("Canada", "British Columbia (12)")) %>%  
  rename(total = `Total (house and land)`,  
    geography = Geography)
```

To export the data:

```
write_csv(housing_bc, "housing.csv")
```


```
housing_bc %>%  
  ggplot(aes(date, total)) +  
  geom_line(aes(color = geography))
```



# Your Turn 1

**Discuss with your  
neighbours:**

What would you want  
to change before  
publishing this plot?




**Assigning the result  
of the plot to a  
variable**

```
basic_plot <- housing %>%  
  filter(geography %in% c("Canada", "British Columbia (12)")) %>%  
  ggplot(housing, mapping = aes(x = date, y = total)) +  
    geom_line(aes(color = geography))  
basic_plot
```

**Asking for the  
variable, displays  
the plot**



Add a title, maybe a subtitle










# Labels

```
diamonds_plot <- ggplot(data = diamonds) +  
  geom_bar(mapping = aes(x = cut, fill = clarity))
```



# + labs()

Our original plot

```
diamonds_plot +  
  labs(title = "Diamonds data",  
        subtitle = "Most diamonds are Ideal cut",  
        caption = "Data from ggplot2::diamonds",  
        x = "Diamond Cut",  
        fill = "Clarity"  
  )
```


title, subtitle, caption

Labels for other scales



# Diamonds data

Most diamonds are Ideal cut




Data from ggplot2::diamonds


## Stats

An alternative way to build a layer

A stat builds new variables to plot (e.g., count, prop).



Visualize a stat by changing the default stat of a geom function, `geom_bar(stat="count")` or by using a stat function, `stat_count(geom="bar")`, which calls a default geom to make a layer (equivalent to a geom function). Use `..name..` syntax to map stat variables to aesthetics.



```
c + stat_bin(binwidth = 1, origin = 10)
x, y | ..count.., ..density..
c + stat_count(width = 1) x, y, | ..count.., ..prop..
c + stat_density(adjust = 1, kernel = "gaussian")
x, y, | ..count.., ..density.., ..scaled..

e + stat_bin_2d(bins = 30, drop = T)
x, y, fill | ..count.., ..density..
e + stat_bin_hex(bins=30) x, y, fill | ..count.., ..density..
e + stat_density_2d(contour = TRUE, n = 100)
x, y, color, size | ..level..
e + stat_ellipse(level = 0.95, segments = 51, type = "t")

l + stat_contour(aes(z = z)) x, y, z, order | ..level..
l + stat_summary_hex(aes(z = z), bins = 30, fun = max)
x, y, z, fill | ..value..
l + stat_summary_2d(aes(z = z), bins = 30, fun = mean)
x, y, z, fill | ..value..

f + stat_boxplot(coef = 1.5) x, y | ..lower.., ..middle.., ..upper.., ..width.., ..ymin.., ..ymax..
f + stat_ydensity(kernel = "gaussian", scale = "area") x, y | ..density.., ..scaled.., ..count.., ..n.., ..violinwidth.., ..width..


e + stat_ecdf(n = 40) x, y | ..x.., ..y..
e + stat_quantile(quantiles = c(0.1, 0.9), formula = y ~ x, method = "rq") x, y | ..quantile..
e + stat_smooth(method = "lm", formula = y ~ x, se = T, level = 0.95) x, y | ..se.., ..x.., ..y.., ..ymin.., ..ymax..

ggplot() + stat_function(aes(x = 3:3), n = 99, fun = dnorm, args = list(sd=0.5)) x | ..x.., ..y..
e + stat_identity(na.rm = TRUE)

ggplot() + stat_qq(aes(sample=1:100), dist = qt, dparam=list(dF=5)) sample, x, y | ..sample.., ..theoretical..
e + stat_sum() x, y, size | ..n.., ..prop..
e + stat_summary(fun.data = "mean_cl_boot")
h + stat_summary_bin(fun.y = "mean", geom = "bar")
e + stat_unique()
```

## Scales

Scales map data values to the visual values of an aesthetic. To change a mapping, add a new scale.



### GENERAL PURPOSE SCALES

Use with most aesthetics

```
scale_<_>.continuous() - map cont' values to visual ones
scale_<_>.discrete() - map discrete values to visual ones
scale_<_>.identity() - use data values as visual ones
scale_<_>.manual(values = c()) - map discrete values to manually chosen visual ones
scale_<_>.date(date_labels = "%m/%d"), date_breaks = "2 weeks" - treat data values as dates.
scale_<_>.datetime() - treat data x values as date times. Use same arguments as scale_<_>.date(). See ?strptime for label formats.
```

### X & Y LOCATION SCALES

Use with x or y aesthetics (x shown here)

```
scale_x_log10() - Plot x on log10 scale
scale_x_reverse() - Reverse direction of x axis
scale_x_sqrt() - Plot x on square root scale
```

### COLOR AND FILL SCALES (DISCRETE)

```
n <- d + geom_bar(aes(fill = fl))
n + scale_fill_brewer(palette = "Blues")
For palette choices:
RColorBrewer::display.brewer.all()
n + scale_fill_grey(start = 0.2, end = 0.8, na.value = "red")
```

### COLOR AND FILL SCALES (CONTINUOUS)

```
o <- c + geom_dotplot(aes(fill = ..x..))
o + scale_fill_distiller(palette = "Blues")
o + scale_fill_gradient(low="red", high="yellow")
o + scale_fill_gradient2(low="red", high="blue", mid = "white", midpoint = 25)
o + scale_fill_gradientn(colours=topo.colors(5))
Also: rainbow(), heat.colors(), terrain.colors(), cm.colors(), RColorBrewer::brewer.pal()
```

### SHAPE AND SIZE SCALES

```
p <- e + geom_point(aes(shape = fl, size = cyl))
p + scale_shape() + scale_size()
p + scale_shape_manual(values = c(3:7))
c 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25
□ ○ △ × ◇ ▼ ▽ ◆ ⊕ ⊗ ⊙ ⊛ ⊜ ⊝ ⊞ ⊠ ⊡ ⊢ ⊣ ⊤ ⊥ ⊦ ⊧ ⊨ ⊩ ⊪ ⊫ ⊬ ⊭ ⊮ ⊯ ⊰ ⊱ ⊲ ⊳ ⊴ ⊵ ⊶ ⊷ ⊸ ⊹ ⊺ ⊻ ⊼ ⊽ ⊾ ⊿ ⊺ ⊻ ⊼ ⊽ ⊾ ⊿
p + scale_radius(range = c(1,6))
p + scale_size_area(max_size = 5)
```

## Coordinate Systems

```
r <- d + geom_bar()
r + coord_cartesian(xlim = c(0, 5))
xlim, ylim
The default cartesian coordinate system
r + coord_fixed(ratio = 1/2)
ratio, xlim, ylim
Creates an coordinates with fixed aspect ratio between x and y units
r + coord_flip()
xlim, ylim
Flips the Cartesian coordinates
r + coord_polar(theta = "x", direction = 1)
theta, start, direction
Polar coordinates
r + coord_trans(ytrans = "sqrt")
xtrans, ytrans, xlim, ylim
Transformed cartesian coordinates. Subtrans and ytrans to the name of a window function.
r + coord_quickmap()
r + coord_map(projection = "ortho", orientation=c(41, -74, 0))projection, brenztation, xlim, ylim
Map projections from the mapproj package (mercator, azimutal, etc.)
```

## Position Adjustments

Position adjustments determine how to arrange geoms that would otherwise occupy the same space.

```
s <- ggplot(mpg, aes(fl, fill = drv))
s + geom_bar(position = "dodge")
Arrange elements side by side
s + geom_bar(position = "fill")
Stack elements on top of one another, normalize height.
e + geom_point()
Add random noise element to avoid
e + geom_label()
Nudge labels away
s + geom_bar(position = "stack")
Stack elements
```

Each position adjustment manual width and height

s + geom\_bar(position = "stack")

## Themes

```
r + theme_bw()
White background with grid lines
r + theme_gray()
Grey background (default theme)
r + theme_dark()
dark for contrast
```

## Faceting

Facets divide a plot into subplots based on the values of one or more discrete variables.

```
t <- ggplot(mpg, aes(cty, hwy)) + geom_point()

t + facet_grid(. ~ fl)
facet into columns based on fl
t + facet_grid(year ~ .)
facet into rows based on year
t + facet_grid(year ~ fl)
facet into both rows and columns
t + facet_wrap(~ fl)
wrap facets into a rectangular layout
```

Set scales to let axis limits vary across facets

```
t + facet_grid(drv ~ fl, scales = "free")
x and y axis limits adjust to individual facets
"free_x" - x axis limits adjust
"free_y" - y axis limits adjust
```

Set labeller to adjust facet labels

```
t + facet_grid(. ~ fl, labeller = label_both)
fl:c fl:d fl:e fl:p fl:r
t + facet_grid(fl ~ ., labeller = label_bquote(alpha ^ .(fl)))
αc αd αe αp αr
t + facet_grid(. ~ fl, labeller = label_parsed)
c d e p r
```

## Labels

```
t + labs(x = "New x axis label", y = "New y axis label", title = "Add a title above the plot")
```

**t + labs( x = "New x axis label", y = "New y axis label", title = "Add a title above the plot", subtitle = "Add a subtitle below title", caption = "Add a caption below plot", <AES> = "New <AES> legend title")**

Use scale functions to update legend labels

**t + annotate(geom = "text", x = 8, y = 9, label = "A")**

geom to place

manual values for geom's aesthetics



Add a title, maybe a subtitle

Nicer axis labels

total

date


Data credit

Remove heading

geography

British Columbia (12)

Canada





# Your Turn 2

Edit the code to add appropriate labelling to the house price plot.

```
basic_plot +  
  labs(title = "New Housing Price Index, Canada and B.C.",  
        subtitle = "Total (house and land)",  
        x = "",  
        y = "NHPI (December 2016 = 100)",  
        color = "",  
        caption = "Source: Statistics Canada CANSIM table  
327-0056"  
  )
```


# Themes



# Themes

Visual appearance of non-data elements


```
diamonds_plot +  
  theme_bw()
```




## Stats

An alternative way to build a layer

A stat builds new variables to plot (e.g., count, prop).



Visualize a stat by changing the default stat of a geom function, `geom_bar(stat="count")` or by using a stat function, `stat_count(geom="bar")`, which calls a default geom to make a layer (equivalent to a geom function). Use `..name..` syntax to map stat variables to aesthetics.



```
c + stat_bin(binwidth = 1, origin = 10)
x, y | ..count.., ..ncount.., ..density.., ..ndensity..

c + stat_count(width = 1) x, y | ..count.., ..prop..

c + stat_density(adjust = 1, kernel = "gaussian")
x, y | ..count.., ..density.., ..scaled..

e + stat_bin_2d(bins = 30, drop = T)
x, y, fill | ..count.., ..density..

e + stat_bin_hex(bins=30) x, y, fill | ..count.., ..density..

e + stat_density_2d(contour = TRUE, n = 100)
x, y, color, size | ..level..

e + stat_ellipse(level = 0.95, segments = 51, type = "t")

l + stat_contour(aes(z = z)) x, y, z, order | ..level..

l + stat_summary_hex(aes(z = z), bins = 30, fun = max)
x, y, z, fill | ..value..

l + stat_summary_2d(aes(z = z), bins = 30, fun = mean)
x, y, z, fill | ..value..

f + stat_boxplot(coef = 1.5) x, y | ..lower..,
  ..middle.., ..upper.., ..width.., ..ymin.., ..ymax..

f + stat_ydensity(kernel = "gaussian", scale = "area") x, y |
  ..density.., ..scaled.., ..count.., ..n.., ..violinwidth.., ..width..

e + stat_ecdf(n = 40) x, y | ..x.., ..y..

e + stat_quantile(quantiles = c(0.1, 0.9), formula = y ~
  log(x), method = "rq") x, y | ..quantile..

e + stat_smooth(method = "lm", formula = y ~ x, se=T,
  level=0.55) x, y | ..se.., ..x.., ..ymin.., ..ymax..

ggplot() + stat_function(aes(x = 3:3), n = 99, fun =
  dnorm, args = list(sd=0.5)) x | ..x.., ..y..

e + stat_identity(na.rm = TRUE)

ggplot() + stat_qq(aes(sample=1:100), dist = qt,
  dparam=list(df=5)) sample, x, y | ..sample.., ..theoretical..

e + stat_sum() x, y, size | ..n.., ..prop..


e + stat_summary(fun.data = "mean_cl_boot")

h + stat_summary_bin(fun.y = "mean", geom = "bar")

e + stat_unique()
```

## Scales

**Scales** map data values to the visual values of an aesthetic. To change a mapping, add a new scale.



### GENERAL PURPOSE SCALES

Use with most aesthetics

**scale\_\*\_continuous()** - map cont' values to visual ones  
**scale\_\*\_discrete()** - map discrete values to visual ones  
**scale\_\*\_identity()** - use data values as visual ones  
**scale\_\*\_manual(values = c())** - map discrete values to manually chosen visual ones  
**scale\_\*\_date(date\_labels = "%m/%d")**, **date\_breaks = "2 weeks"** - treat data values as dates.  
**scale\_\*\_datetime()** - treat data x values as date times. Use same arguments as **scale\_x\_date()**. See `?strptime` for label formats.

### X & Y LOCATION SCALES

Use with x or y aesthetics (x shown here)

**scale\_x\_log10()** - Plot x on log10 scale  
**scale\_x\_reverse()** - Reverse direction of x axis  
**scale\_x\_sqrt()** - Plot x on square root scale

### COLOR AND FILL SCALES (DISCRETE)

**n <- d + geom\_bar(aes(fill = fl))**  
**n + scale\_fill\_brewer(palette = "Blues")**  
For palette choices:  
`RColorBrewer::display.brewer.all()`  
**n + scale\_fill\_grey(start = 0.2, end = 0.8, na.value = "red")**

### COLOR AND FILL SCALES (CONTINUOUS)

**o <- c + geom\_dotplot(aes(fill = ..x..))**  
**o + scale\_fill\_distiller(palette = "Blues")**  
**o + scale\_fill\_gradient(low="red", high="yellow")**  
**o + scale\_fill\_gradient2(low="red", high="blue", mid = "white", midpoint = 25)**  
**o + scale\_fill\_gradientn(colours=topo.colors(6))**  
Also: `rainbow()`, `heat.colors()`, `terrain.colors()`, `cm.colors()`, `RColorBrewer::brewer.pal()`

### SHAPE AND SIZE SCALES

**p <- e + geom\_point(aes(shape = fl, size = cyl))**  
**p + scale\_shape() + scale\_size()**  
**p + scale\_shape\_manual(values = c(3:7))**  
`c(1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25)`  
`c(1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25)`  
**p + scale\_radius(range = c(1,6))**  
**p + scale\_size\_area(max\_size = 6)**

## Coordinate Systems

```
r <- d + geom_bar()

r + coord_cartesian(xlim = c(0, 5))
xlim, ylim
The default cartesian coordinate system

r + coord_fixed(ratio = 1/2)
ratio, xlim, ylim
Carries an coordinates with fixed aspect ratio between x and y units

r + coord_flip()
xlim, ylim
Flipped Cartesian coordinates

r + coord_polar(theta = "x", direction=1)
theta, stat, direction
Polar coordinates

r + coord_trans(ytrans = "sqrt")
xtrans, ytrans, xlim, ylim
Transformed Cartesian coordinates. Set xtrans and ytrans to the name of a window function.

r + coord_quickmap()
r + coord_map(projection = "ortho",
  orientation=c(11, -75, 0))projection, brenztation,
xlim, ylim
Map projections from the mapproj package
(mercator (default), azecularae, ...)
```

## Faceting

Facets divide a plot into subplots based on the values of one or more discrete variables.

```
t <- ggplot(mpg, aes(cty, hwy)) + geom_point()

t + facet_grid(~ fl)
facet into columns based on fl

t + facet_grid(year ~ .)
facet into rows based on year

t + facet_grid(year ~ fl)
facet into both rows and columns

t + facet_wrap(~ fl)
wrap facets into a rectangular layout

Set scales to let axis limits vary across facets

t + facet_grid(drv ~ fl, scales = "free")
x and y axis limits adjust to individual facets
"free_x" - x axis limits adjust
"free_y" - y axis limits adjust
```



## Position Adjustment

Position adjustments determine how to a that would otherwise occupy the same space.

```
s <- ggplot(mpg, aes(fl, fill = drv))

s + geom_bar(position = "dodge")
Arrange elements side by side

s + geom_bar(position = "fill")
Stack elements on top of one and normalize height

e + geom_point(position = "jitter")
Add random noise to X and Y position element to avoid overplotting

e + geom_label(position = "nudge")
Nudge labels away from points

s + geom_bar(position = "stack")
Stack elements on top of one and
```

Each position adjustment can be recast as manual width and height arguments  
**s + geom\_bar(position = position\_dodge)**


## Themes

```
r + theme_bw()
White background with grid lines


r + theme_gray()
Grey background (default theme)

r + theme_dark()
dark for contrast
```


# Themes




**r + theme\_bw()**  
White background with grid lines




**r + theme\_gray()**  
Grey background (default theme)



**r + theme\_dark()**  
dark for contrast



**r + theme\_classic()**




**r + theme\_light()**

**r + theme\_linedraw()**

**r + theme\_minimal()**

Minimal themes



**r + theme\_void()**

Empty theme



RStudio® is a trademark of RStudio, Inc. • CC BY RStudio • Info@rstudio.com • 944-448-1212 • rstudio




# Your Turn 3

Add a theme to `basic_plot`. Try a few and pick one you like.




```
basic_plot + theme_classic()
```




```
# install.packages("ggthemes")  
library(ggthemes)  
basic_plot +  
  theme_excel()
```

## Even more themes



```
# install.packages("ggthemes")  
library(ggthemes)  
basic_plot +  
  theme_ws()
```




# Scales



# Scales

Customize color scales, other mappings

```
diamonds_plot +  
  scale_fill_brewer()
```



# Scale functions

diamonds\_plot +

**scale\_fill\_brewer()**

All start  
with  
scale\_

Aesthetic  
the scale  
applies to


A specific  
kind of  
scale

Other  
arguments  
to the scale



# Scales

**Scales** map data values to the visual values of an aesthetic. To change a mapping, add a new scale.



## GENERAL PURPOSE SCALES

Use with most aesthetics

**scale\_\*\_continuous()** - map cont' values to visual ones

**scale\_\*\_discrete()** - map discrete values to visual ones

**scale\_\*\_identity()** - use data values as visual ones

**scale\_\*\_manual(values = c())** - map discrete values to manually chosen visual ones

**scale\_\*\_date(date\_labels = "%m/%d"), date\_breaks = "2 weeks")** - treat data values as dates.

**scale\_\*\_datetime()** - treat data x values as date times.

Use same arguments as scale\_x\_date(). See ?strptime for label formats.

## X & Y LOCATION SCALES

Use with x or y aesthetics (x shown here)

**scale\_x\_log10()** - Plot x on log10 scale

**scale\_x\_reverse()** - Reverse direction of x axis

**scale\_x\_sqrt()** - Plot x on square root scale

**Stats** An alternative way to build a layer

A stat builds new variables to plot (e.g., count, prop).

data → stat → geom → coordinate → plot

Visualize a stat by changing the default stat of a geom function, **geom\_bar(stat="count")** or by using a stat function, **stat\_count(geom="bar")**, which calls a default geom to make a layer (equivalent to a geom function). Use **..name..** syntax to map stat variables to aesthetics.

**geom to use** **stat function** **geom mappings**

**i + stat\_density2d(aes(fill = ..level..), geom = "polygon")**

**variable created by stat**

**Scales** Scales map data values to the visual values of an aesthetic. To change a mapping, add a new scale.

**(n <- d + geom\_bar(aes(fill = fl)))**

**scale\_** **aesthetic to adjust** **prepackaged scale to use** **scale-specific arguments**

**n + scale\_fill\_manual(values = c("skyblue", "royalblue", "blue", "navy"), limits = c("d", "e", "p", "r"), breaks = c("d", "e", "p", "r"), name = "fuel", labels = c("D", "E", "P", "R"))**

**range of values to include in mapping** **title to use in legend/axis** **labels to use in legend/axis** **breaks to use in legend/axis**

**GENERAL PURPOSE SCALES**

Use with most aesthetics

**scale\_\*\_continuous()** - map cont' values to visual ones

**scale\_\*\_discrete()** - map discrete values to visual ones

**scale\_\*\_identity()** - use data values as visual ones

**scale\_\*\_manual(values = c())** - map discrete values to manually chosen visual ones

**scale\_\*\_date(date\_labels = "%m/%d"), date\_breaks = "2 weeks")** - treat data values as dates.

**scale\_\*\_datetime()** - treat data x values as date times. Use same arguments as scale\_x\_date(). See ?strptime for label formats.

**X & Y LOCATION SCALES**

Use with x or y aesthetics (x shown here)

**scale\_x\_log10()** - Plot x on log10 scale

**scale\_x\_reverse()** - Reverse direction of x axis

**scale\_x\_sqrt()** - Plot x on square root scale

**COLOR AND FILL SCALES (DISCRETE)**

**n <- d + geom\_bar(aes(fill = fl))**

**n + scale\_fill\_brewer(palette = "Blues")**

For palette choices: **RColorBrewer::display.brewer.all()**

**n + scale\_fill\_grey(start = 0.2, end = 0.8, na.value = "red")**

**COLOR AND FILL SCALES (CONTINUOUS)**

**o <- c + geom\_dotplot(aes(fill = ..x..))**

**o + scale\_fill\_distiller(palette = "Blues")**

**o + scale\_fill\_gradient(low="red", high="yellow")**

**o + scale\_fill\_gradient2(low="red", high="blue", mid = "white", midpoint = 25)**

**o + scale\_fill\_gradientn(colours=topo.colors(6))**

Also: **rainbow()**, **heat.colors()**, **terrain.colors()**, **cm.colors()**, **RColorBrewer::brewer.pal()**

**SHAPE AND SIZE SCALES**

**p <- e + geom\_point(aes(shape = fl, size = cyl))**

**p + scale\_shape() + scale\_size()**

**p + scale\_shape\_manual(values = c(3:7))**

**p + scale\_size\_manual(values = c(3:7))**

**p + scale\_radius(range = c(1,6))**

**p + scale\_size\_area(max\_size = 6)**

**Themes**

**r + theme\_minimal()** Minimal theme

**r + theme\_void()** Empty theme

**r + theme\_dark()** dark for contrast

**r + theme\_linedraw()** Grey background (default theme)

**Zooming**

Without clipping (preferred)

**t + coord\_cartesian(xlim = c(0, 100), ylim = c(10, 20))**

With clipping (removes unseen data points)

**t + xlim(0, 100) + ylim(10, 20)**

**t + scale\_x\_continuous(limits = c(0, 100)) + scale\_y\_continuous(limits = c(0, 100))**

**R Studio**

RStudio® is a trademark of RStudio, Inc. • CC BY RStudio • Info@rstudio.com • 344-448-1212 • rstudio.com • Learn more at <http://ggplot2.tidyverse.org> • ggplot2 2.1.0 • Updated: 2016-11

## COLOR AND FILL SCALES (DISCRETE)

**n <- d + geom\_bar(aes(fill = fl))**

**n + scale\_fill\_brewer(palette = "Blues")**

For palette choices: **RColorBrewer::display.brewer.all()**

**n + scale\_fill\_grey(start = 0.2, end = 0.8, na.value = "red")**

## COLOR AND FILL SCALES (CONTINUOUS)

**o <- c + geom\_dotplot(aes(fill = ..x..))**

**o + scale\_fill\_distiller(palette = "Blues")**

**o + scale\_fill\_gradient(low="red", high="yellow")**

**o + scale\_fill\_gradient2(low="red", high="blue", mid = "white", midpoint = 25)**

**o + scale\_fill\_gradientn(colours=topo.colors(6))**

Also: **rainbow()**, **heat.colors()**, **terrain.colors()**, **cm.colors()**, **RColorBrewer::brewer.pal()**

## SHAPE AND SIZE SCALES

**p <- e + geom\_point(aes(shape = fl, size = cyl))**

**p + scale\_shape() + scale\_size()**

**p + scale\_shape\_manual(values = c(3:7))**

**0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25**

**p + scale\_radius(range = c(1,6))**


**p + scale\_size\_area(max\_size = 6)**




# Your Turn 4

Add a brewer scale to the basic\_plot.

```
basic_plot + scale_color_brewer()
```




```
basic_plot +  
  scale_color_brewer(palette = "Blues")
```





To see available brewer palettes


```
RColorBrewer::display.brewer.all()
```



# Your Turn 5

Choose a better color palette for the brewer scale.

```
basic_plot + scale_color_brewer(palette = "Set1")
```






# scale\_color\_manual()

An way to completely control mapping

```
basic_plot +  
  scale_color_manual(  
    values = c("Canada" = "#fdb913", "British Columbia (12)" = "#234075")  
  )
```

# scale\_color\_manual()

An way to completely control mapping




basic  
scale  
)

75")


Putting it together



diamonds\_plot




```
diamonds_plot +  
  labs(title = "Diamonds data",  
        subtitle = "Most diamonds are Ideal cut",  
        caption = "Data from ggplot2::diamonds",  
        x = "Diamond Cut",  
        fill = "Clarity")  
)
```



```


diamonds_plot +
  labs(title = "Diamonds data",
        subtitle = "Most diamonds are Ideal cut",
        caption = "Data from ggplot2::diamonds",
        x = "Diamond Cut",
        fill = "Clarity")
) +
theme_bw()

```





```
diamonds_plot +  
  labs(title = "Diamonds data",  
        subtitle = "Most diamonds are Ideal cut",  
        caption = "Data from ggplot2::diamonds",  
        x = "Diamond Cut",  
        fill = "Clarity")  
  ) +  
  theme_bw() +  
  scale_fill_brewer()
```



# Your Turn 6

Put the labels, theme and scale changes together for `basic_plot`.


What is left to change?

```
basic_plot +  
  labs(title = "New Housing Price Index, Canada and B.C.",  
        subtitle = "Total (house and land)",  
        x = "",  
        y = "NHPI (December 2016 = 100)",  
        color = "",  
        caption = "Source: Statistics Canada CANSIM table 327-0056") +  
  theme_classic() +  
  scale_color_brewer(palette = "Set1")
```




# New Housing Price Index, Canada and B.C.

Total (house and land)



Source: Statistics Canada CANSIM table 327-0056

```
last_plot() +  
  scale_x_datetime(date_labels = "%b-%y") +  
  theme(legend.position = c(0.75, 0.2))
```



Needs to  
be made at  
the data  
level

# Summary

Everything visual on the plot is customizable

**Labels** - easiest thing to change to increase readability

**Themes** - change all non-data visual elements

**Scales** - control mappings and the legends that go with them