



Alvium 1800 U

Alvium 1800 U-511
Monochrome, Closed
Housing, C-Mount, 90°

Alvium 1800 U-511 innovative USB camera with Sony IMX547 global shutter sensor provides industrial performance for cost effective embedded and machine vision applications.

Configuration: 15937

General

Model:	Alvium 1800 U-511
Product code:	15937
Product series:	Alvium 1800 U
Status:	Available

Sensor

Sensor type:	Area scan
Chroma:	Monochrome
Spectrum:	Visible
Spectral range:	300 nm to 1100 nm
Resolution:	2,464 × 2,064 (5.10 MP)
Sensor model:	Sony IMX547
Sensor architecture (material):	CMOS
Shutter type(s):	Global Shutter
Sensor size:	9 mm ø (Type 1/1.8)
Pixel size:	2.74 µm × 2.74 µm

Pixel formats

Sensor bit depth:	12-bit
Monochrome pixel formats:	Mono8, Mono10, Mono10p, Mono12, Mono12p

Imaging performance

Quantum efficiency @ 529 nm:	68 %
------------------------------	------

Timing and gain

Max. frame rate:	79 fps
------------------	--------

I/Os and power

Non-isolated lines:	4 programmable GPIOs
Power supply:	Power over USB 3.1 Gen 1 External power 5.0 V
Power consumption:	USB power: 3.2 W (typical) Ext. power: 3.4 W (typical)

Operating conditions

Operating temperature (housing):	-20 °C to 65 °C
----------------------------------	-----------------

Mechanical properties

Housing:	Closed Housing
Body dimensions (L x W x H in mm):	38 × 32 × 29 mm
Lens mount(s):	C-Mount
Camera angle:	90°
Weight:	70 g

On-board memory and FPGA

Image buffer (RAM):	256 KByte
Non-volatile memory (Flash):	1024 KByte

Interfaces

Digital interface:	usb3.0
Vision standard:	USB3 Vision

Quantum Efficiency



