

# Case-Control with Gestational Age Matching

*Christof Seiler*

21 November 2019

## Contents

1	Goal . . . . .	2
2	Prerequisites . . . . .	2
3	Import Data . . . . .	2
4	Quality Control . . . . .	7
5	Preprocessing. . . . .	8
6	Data Exploration . . . . .	9
7	Differential Expression Analyses . . . . .	11
	Session Info . . . . .	15

### 1 Goal

---

1. Load and normalize data using `oligo`
2. Differential analysis using `limma`

### 2 Prerequisites

---

Install necessary packages from bioconductor repository. Run this code only once to install packages.

```
pkgs_needed = c("oligo", "limma", "hta20transcriptcluster.db", "pd.hta.2.0",
                "affycoretools", "genefilter", "MatchIt", "optmatch", "ggfortify",
                "magrittr", "statmod", "readr", "dplyr", "readxl", "stringr",
                "tibble", "ggrepel")
letsinstall = setdiff(pkgs_needed, installed.packages())
if (length(letsinstall) > 0) {
  source("http://bioconductor.org/biocLite.R")
  biocLite(letsinstall)
}
```

Load packages.

```
library("oligo")
library("limma")
library("hta20transcriptcluster.db")
library("affycoretools")
library("genefilter")
library("MatchIt")
library("ggfortify")
library("magrittr")
library("statmod")
library("readr")
library("dplyr")
library("readxl")
library("stringr")
library("tibble")
library("ggrepel")
```

### 3 Import Data


---

Read sample tables. Merge with sample information table.

```
sample_table = read_csv("sample_table_from_word.csv")
## Parsed with column specification:
## cols(
##   ptidno = col_double(),
##   visitcode = col_double(),
##   gestage_delivery = col_double(),
##   gestage_pbmc_collected = col_double(),
##   ptb_case = col_character(),
```

## Case-Control with Gestational Age Matching

```
##   ptb_casenum = col_double(),
##   ptb_controlnum = col_double()
## )
new_matched = read_excel("MSS Case-Control Matches (Masked)_new_matched.xlsx")
sample_table %<>% dplyr::left_join(new_matched, by = "ptidno",
                                   suffix = c("", "2"))
ggplot(sample_table, aes(as.factor(ptb_casenum), gestage_pbmc_collected,
                           color = ptb_case)) +
  geom_jitter(position=position_dodge(width = 0.5), size = 2) +
  xlab("matched pair id")
```



```
sample_table %<>% dplyr::select(ptidno,
                                ptb_case,
                                gestage_pbmc_collected,
                                gestage_delivery,
                                sample_id = SampleID)
```

Find CEL files in current folder.

```
file_names_cel = list.files("./", pattern = "CEL")
params$treatment
## [1] "unstim"
if(params$treatment == "stim") {
  file_names_cel = file_names_cel[str_detect(
    string = file_names_cel,
    pattern = "Bayless_H1N1|\\+\\-\\(HTA)"]
} else {
  file_names_cel = file_names_cel[str_detect(
    string = file_names_cel,
    pattern = "Bayless_US|\\-\\-\\(HTA|\\-\\-\\(HTA|\\-\\-\\(HTA)"]
}
tb_file_name = lapply(sample_table$sample_id, function(id) {
  pattern = paste0("[ _]", id)
  name = file_names_cel[which(str_detect(file_names_cel, pattern))]
  if(length(name)==0) name = NA
  tibble(sample_id = id, file_name = name)
}) %>% bind_rows()
```

## Case-Control with Gestational Age Matching

```
sample_table %<>% dplyr::left_join(tb_file_name, by = "sample_id")
sample_table %<>% na.omit
table(sample_table$ptb_case)
##
##      case control
##      20      38
```

Match samples.

```
set.seed(0xdada2)
sample_table$group = sample_table$ptb_case == "case"
mout = matchit(group ~ gestage_pbmc_collected,
               data = sample_table,
               method = "optimal",
               ratio = 1)
## Warning in optmatch::fullmatch(d, min.controls = ratio, max.controls = ratio, : Without 'data' argument t
##      to be the same as your original data.
summary(mout)
##
## Call:
## matchit(formula = group ~ gestage_pbmc_collected, data = sample_table,
##      method = "optimal", ratio = 1)
##
## Summary of balance for all data:
##
##               Means Treated Means Control SD Control Mean Diff
## distance                0.3752         0.3288    0.1148    0.0464
## gestage_pbmc_collected    21.4100        23.6605    5.2473   -2.2505
##
##               eQQ Med eQQ Mean eQQ Max
## distance                0.0586    0.0525  0.1042
## gestage_pbmc_collected  1.8000    2.2350  7.4000
##
##
## Summary of balance for matched data:
##
##               Means Treated Means Control SD Control Mean Diff
## distance                0.3752         0.3753    0.0887   -1e-04
## gestage_pbmc_collected    21.4100        21.4100    3.6864    0e+00
##
##               eQQ Med eQQ Mean eQQ Max
## distance                0.0041    0.0055  0.017
## gestage_pbmc_collected  0.2000    0.2300  0.700
##
##
## Percent Balance Improvement:
##
##               Mean Diff. eQQ Med eQQ Mean eQQ Max
## distance                99.7989 93.0472  89.6035 83.7009
## gestage_pbmc_collected 100.0000 88.8889  89.7092 90.5405
##
##
## Sample sizes:
##
##               Control Treated
## All                38      20
## Matched            20      20
## Unmatched          18       0
## Discarded           0       0
```

## Case-Control with Gestational Age Matching


```

sample_table$pair = NA
A = rownames(mout$match.matrix) %>% as.integer
B = mout$match.matrix %>% as.integer
for(i in 1:nrow(mout$match.matrix)) {
  sample_table$pair[A[i]] = i
  sample_table$pair[B[i]] = i
}
sample_table %>% dplyr::select(-group)
sample_table %>% na.omit
sample_table %>%
  dplyr::select(sample_id,ptidno,pair,ptb_case,gestage_pbmc_collected,
                gestage_delivery) %>%
  arrange(pair,ptb_case) %>%
  print(n = Inf)
## # A tibble: 40 x 6
##   sample_id ptidno pair ptb_case gestage_pbmc_collected gestage_delivery
##   <chr>      <dbl> <int> <chr>          <dbl>          <dbl>
## 1 1.2      14104760     1 case           15.7           21.3
## 2 2.2      14104580     1 control        15.6           37.4
## 3 2.1      14101980     2 case           15.3           33.6
## 4 2.3      14105160     2 control        15           39.3
## 5 3.3      14225030     3 case           18.7           33.4
## 6 3.2      14223910     3 control        18.6           38
## 7 4.2      14100420     4 case           18.3           33
## 8 3.1      14105820     4 control        18           38
## 9 5.3      14222170     5 case           19.3           30.9
## 10 6.3     14223900     5 control        19.3           39
## 11 6.1     14220060     6 case           19.4           29.6
## 12 8.1     14104890     6 control        19.4           41
## 13 7.2     14100460     7 case           18           32.9
## 14 4.3     14102700     7 control        17.9           40
## 15 8.3     14224240     8 case           19.9           23
## 16 5.2     14103060     8 control        19.9           42.3
## 17 9.2     14102840     9 case           18.9           24.1
## 18 9.1     14102770     9 control        19           38.3
## 19 10.1    14223520    10 case           21.6           27.9
## 20 11.1    14104710    10 control        21.4           39.9
## 21 11.2    14102560    11 case           21.3           31.9
## 22 10.3    14224520    11 control        21           37.6
## 23 12.1    14220350    12 case           22           27.3
## 24 13.1    14100770    12 control        22.3           39.1
## 25 13.2    14224670    13 case           21.6           26.7
## 26 13.3    14100390    13 control        22.6           37.3
## 27 14.3    14222790    14 case           23.9           31
## 28 14.2    14105140    14 control        23.7           43
## 29 16.1    14102780    15 case           24           33.7
## 30 17.3    14100120    15 control        24.6           39.6
## 31 17.2    14105630    16 case           23.9           31.3
## 32 14.1    14100400    16 control        23.4           39.6
## 33 18.3    14222340    17 case           25.4           27.6
## 34 18.1    14104350    17 control        25.7           38.4

```

## Case-Control with Gestational Age Matching

```
## 35 19.1      14103660      18 case      26.1      29.1
## 36 19.3      14102370      18 control    26.1      41
## 37 20.2      14100230      19 case      26.3      26.7
## 38 19.2      14225270      19 control    26.3      39
## 39 21.3      14106020      20 case      28.6      31.7
## 40 21.2      14220100      20 control    28.4      39
write_csv(sample_table, path = paste0("sample_table_matched_", params$treatment, ".csv"))
ggplot(sample_table, aes(as.factor(pair), gestage_pbmc_collected,
                        color = ptb_case)) +
  geom_jitter(position=position_dodge(width = 0.5), size = 2) +
  xlab("matched pair id")
```



Then load Affymetrix CEL files. At this stage, Bioconductor will automatically download the necessary annotation packages and install them for us.

```
pd = as(as.data.frame(sample_table), "AnnotatedDataFrame")
rawData = read.celfiles(sample_table$file_name,
                        phenoData = pd,
                        sampleNames = sample_table$sample_id)

## Loading required package: pd.hta.2.0
## Loading required package: RSQLite
## Loading required package: DBI
## Platform design info loaded.
## Reading in : Nicholas Bayless_US 1.2_(HTA-2_0).CEL
## Reading in : Nicholas Bayless_US 2.1_(HTA-2_0).CEL
## Reading in : Nicholas Bayless_US 2.3_(HTA-2_0).CEL
## Reading in : Nicholas Bayless_US 2.2_(HTA-2_0).CEL
## Reading in : Nicholas Bayless_US 3.3_(HTA-2_0).CEL
## Reading in : Nicholas Bayless_US 3.2_(HTA-2_0).CEL
## Reading in : Nicholas Bayless_US 3.1_(HTA-2_0).CEL
## Reading in : Nicholas Bayless_US 4.2_(HTA-2_0).CEL
## Reading in : Nicholas Bayless_US 4.3_(HTA-2_0).CEL
## Reading in : Nicholas Bayless_US 5.3_(HTA-2_0).CEL
## Reading in : Nicholas Bayless_US 5.2_(HTA-2_0).CEL
## Reading in : Nicholas Bayless_US 6.1_(HTA-2_0).CEL
## Reading in : Nicholas Bayless_US 6.3_(HTA-2_0).CEL
## Reading in : Nicholas Bayless_7.2 _-(HTA-2_0).CEL
```

## Case-Control with Gestational Age Matching


```
## Reading in : Nicholas Bayless_8.3 -(HTA-2_0).CEL
## Reading in : Nicholas Bayless_8.1 -(HTA-2_0).CEL
## Reading in : Nicholas Bayless_9.2 -(HTA-2_0).CEL
## Reading in : Nicholas Bayless_9.1 -(HTA-2_0).CEL
## Reading in : Nicholas Bayless_10.1 -(HTA-2_0).CEL
## Reading in : Nicholas Bayless_10.3 -(HTA-2_0).CEL
## Reading in : Nicholas Bayless_11.2 -(HTA-2_0).CEL
## Reading in : Nicholas Bayless_11.1 -(HTA-2_0).CEL
## Reading in : Nicholas Bayless_12.1 -(HTA-2_0).CEL
## Reading in : Nicholas Bayless_US 13.2 (HTA-2_0).CEL
## Reading in : Nicholas Bayless_US 13.1 (HTA-2_0).CEL
## Reading in : Nicholas Bayless_US 13.3 (HTA-2_0).CEL
## Reading in : Nicholas Bayless_US 14.3 (HTA-2_0).CEL
## Reading in : Nicholas Bayless_US 14.2 (HTA-2_0).CEL
## Reading in : Nicholas Bayless_US 14.1 (HTA-2_0).CEL
## Reading in : Nicholas Bayless_US 16.1 (HTA-2_0).CEL
## Reading in : Nicholas Bayless_US 17.2 (HTA-2_0).CEL
## Reading in : Nicholas Bayless_US 17.3 (HTA-2_0).CEL
## Reading in : Nicholas Bayless_US 18.3 (HTA-2_0).CEL
## Reading in : Nicholas Bayless_US 18.1 (HTA-2_0).CEL
## Reading in : Nicholas Bayless_US 19.1 (HTA-2_0).CEL
## Reading in : Nicholas Bayless_US 19.3 (HTA-2_0).CEL
## Reading in : Nicholas Bayless_US 19.2 (HTA-2_0).CEL
## Reading in : Nicholas Bayless_US 20.2 (HTA-2_0).CEL
## Reading in : Nicholas Bayless_US 21.3 (HTA-2_0).CEL
## Reading in : Nicholas Bayless_US 21.2 (HTA-2_0).CEL
## Warning in read.celfiles(sample_table$file_name, phenoData = pd, sampleNames
## = sample_table$sample_id): 'channel' automatically added to varMetadata in
## phenoData.
rawData
## HTAFeatureSet (storageMode: lockedEnvironment)
## assayData: 6892960 features, 40 samples
## element names: exprs
## protocolData
## rowNames: 1 2 ... 40 (40 total)
## varLabels: exprs dates
## varMetadata: labelDescription channel
## phenoData
## rowNames: 1 2 ... 40 (40 total)
## varLabels: ptidno ptb_case ... pair (7 total)
## varMetadata: labelDescription channel
## featureData: none
## experimentData: use 'experimentData(object)'
## Annotation: pd.hta.2.0
```

## 4 Quality Control

MA plots on the first three samples.

## Case-Control with Gestational Age Matching

```
MAplot(rawData[, 1:3], pairs=TRUE)
```



## 5 Preprocessing

Background subtraction, normalization and summarization using median-polish.

```
eset = rma(rawData)
## Background correcting
## Normalizing
## Calculating Expression
```

Get rid of background probes and annotate using functions in `affycoretools` package.

```
dbGetQuery(db(pd.hta.2.0), "select * from type_dict;")
##   type                                     type_id
## 1     1                                           main
## 2     2               Antigenomic background control
## 3     3               control->affx->bac_spike
## 4     4               control->affx->polya_spike
## 5     5 ERCC (External RNA Controls Consortium) step control
## 6     6           Exonic normalization control (Positive Control)
## 7     7       Intronic normalization control (Negative Control)
## 8     8                                           Positive Control
table(getMainProbes("pd.hta.2.0")$type)
##
##      1      2      3      4      5      6      7
## 67516   23     4     4   155   698   646
eset = getMainProbes(eset)
```

Filter probes that we cannot map to symbols.

```
e2s = toTable(hta20transcriptclusterSYMBOL)
prob_ids = rownames(exprs(eset))
keep_ids = which(prob_ids %in% e2s$probe_id)
eset = ExpressionSet(assayData = exprs(eset)[keep_ids,],
                    phenoData = phenoData(eset),
                    experimentData = experimentData(eset),
                    annotation = annotation(eset))
```



## Case-Control with Gestational Age Matching

Save to file.

```
class(eset)
## [1] "ExpressionSet"
## attr(,"package")
## [1] "Biobase"
show(eset)
## ExpressionSet (storageMode: lockedEnvironment)
## assayData: 29503 features, 40 samples
## element names: exprs
## protocolData: none
## phenoData
## sampleNames: 1 2 ... 40 (40 total)
## varLabels: ptidno ptb_case ... pair (7 total)
## varMetadata: labelDescription channel
## featureData: none
## experimentData: use 'experimentData(object)'
## Annotation: pd.hta.2.0
exprs(eset)[1:10, 1:2]
##           1          2
## TC01000003.hg.1  2.124867  2.271436
## TC01000007.hg.1 11.059400 10.764831
## TC01000010.hg.1  3.202259  2.941917
## TC01000018.hg.1  6.939298  7.623561
## TC01000019.hg.1  5.839381  5.748863
## TC01000020.hg.1  5.660097  5.819165
## TC01000021.hg.1  5.654589  5.693005
## TC01000022.hg.1  5.674174  5.616228
## TC01000023.hg.1  6.026052  6.319220
## TC01000024.hg.1  5.800042  5.859162
save(eset, file = "eset.Rdata")
```

Write processed expressions to file for GEO upload.


```
geo_exprs_rma = exprs(eset)
condition = ifelse(pData(eset)$ptb_case == "control",
  yes = "Term", no = "Preterm")
sample_name = paste0(pData(eset)$sample_id, "_",
  condition, "_",
  ifelse(params$treatment == "stim",
    yes = "H1N1", "Mock"))
colnames(geo_exprs_rma) = sample_name
geo_exprs_rma %<>% as_tibble(rownames = "ID_REF")
write_csv(geo_exprs_rma, path = paste0("case_control_rma_", params$treatment, ".csv"))
```

## 6 Data Exploration


PCA plot of normalized expressions.

```
res_pca = prcomp(t(exprs(eset)), scale. = FALSE)
screeplot(res_pca)
```


## Case-Control with Gestational Age Matching



```
sample_table_annotated = eset@phenoData@data
sample_table_annotated$pair %<>% as.factor
asp_ratio = res_pca$sdev[2]^2/res_pca$sdev[1]^2
autoplot(res_pca,
  data = sample_table_annotated,
  shape = "ptb_case",
  colour = "gestage_pbmc_collected",
  size = 3,
  asp = asp_ratio)
```




```
autoplot(res_pca,
  data = sample_table_annotated,
  shape = "ptb_case",
  colour = "gestage_delivery",
  size = 3,
  asp = asp_ratio)
```



```
rownames(sample_table_annotated) = paste0(sample_table_annotated$pair,
  "_",
  sample_table_annotated$sample_id)
autoplot(res_pca,
```

## Case-Control with Gestational Age Matching

```
data = sample_table_annotated,
shape = FALSE,
colour = "pair",
label = TRUE,
asp = asp_ratio)
```



## 7 Differential Expression Analyses

Use `limma` for linear models to assess difference in expression. Paired analysis as described in Section 9.4.1 on page 42 in the [limma vignette](#).

Automatic independent filtering as described in [DESeq2 doc](#):

1. Filter genes based on mean expression
2. Fit linear model
3. Compute moderated *t*-tests
4. Count number of rejections at FDR of 10%

Pick the threshold that maximizes the number of discoveries.

```
mean_expr = rowMeans(exprs(eset))
thres_candidates = seq(min(mean_expr), quantile(mean_expr, probs = 0.95), 1)
fit_list = lapply(thres_candidates, function(thres) {
  cat("Automatic independent filtering: thres = ", thres, "\n")
  # threshold
  eset_thres = ExpressionSet(assayData = exprs(eset)[mean_expr >= thres,],
                             phenoData = phenoData(eset),
                             experimentData = experimentData(eset),
                             annotation = annotation(eset))


  # fit model
  targets = eset@phenoData@data
  pair = factor(targets$pair)
  treat = factor(targets$ptb_case, levels = c("control", "case"))
  design = model.matrix(~ pair + treat)
```

## Case-Control with Gestational Age Matching

```
fit = lmFit(eset_thres, design)
eBayes(fit)
})
## Automatic independent filtering: thres = 1.415861
## Automatic independent filtering: thres = 2.415861
## Automatic independent filtering: thres = 3.415861
## Automatic independent filtering: thres = 4.415861
## Automatic independent filtering: thres = 5.415861
## Automatic independent filtering: thres = 6.415861
num_sig = sapply(fit_list, function(fit) {
  gene_table = topTable(fit, coef = "treatcase", adjust = "BH",
                        number = nrow(fit))
  gene_table %<>% dplyr::filter(adj.P.Val < 0.1)
  nrow(gene_table)
})
num_sig
## [1] 0 0 0 0 0 0
fit = fit_list[[which.max(num_sig)]]
```

The `topTable` command provides us a way of ranking genes for further evaluation. In the case below, we adjust for multiple testing by FDR.

```
gene_table = topTable(fit, coef = "treatcase", adjust = "BH",
                      number = nrow(fit))
hist(gene_table$P.Value, breaks = 20)
```




```
sum(gene_table$adj.P.Val < 0.1)
## [1] 0
```

Volcano plots for quality control.

```
volcanoplot(fit, coef = "treatcase", highlight = 10)
```

### Case-Control with Gestational Age Matching



Map between manufacturer identifiers and gene symbols.

```
map_gene_symbol = function(gene_table) {
  prob_id = rownames(gene_table)
  symbol = apply(prob_id, function(prob_id) {
    matching_symbol = e2s$symbol[prob_id==e2s$probe_id]
    if(length(matching_symbol)==0) matching_symbol = "No_Symbol_Found"
    matching_symbol
  }) %>% unlist
  gene_table = cbind(gene_table, symbol=symbol, stringsAsFactors=FALSE)
  gene_table
}

gene_table = map_gene_symbol(gene_table)
print(head(gene_table, n = 10))
```

##		logFC	AveExpr	t	P.Value	adj.P.Val
##	TC04001942.hg.1	0.3964871	3.316441	4.736341	9.335941e-05	0.5114967
##	TC06002060.hg.1	0.2001396	2.642368	4.506959	1.646325e-04	0.5114967
##	TC11000211.hg.1	0.2261746	5.190697	4.475880	1.777978e-04	0.5114967
##	TC06003369.hg.1	0.6938335	6.947984	4.356977	2.386576e-04	0.5114967
##	TC06002625.hg.1	0.2560004	3.762744	4.326441	2.573996e-04	0.5114967
##	TC07002768.hg.1	0.3270357	5.441849	4.302524	2.730997e-04	0.5114967
##	TC06001226.hg.1	0.7722665	6.874004	4.255594	3.067389e-04	0.5114967
##	TC06003141.hg.1	-0.5904733	4.303887	-4.246605	3.136386e-04	0.5114967
##	TC07000793.hg.1	-0.4470670	6.128909	-4.235625	3.222778e-04	0.5114967
##	TC04001652.hg.1	0.3054274	4.363445	4.212081	3.416088e-04	0.5114967
##		B	symbol			
##	TC04001942.hg.1	-0.2228733	SEPSECS-AS1			
##	TC06002060.hg.1	-0.5255553	FAM184A			
##	TC11000211.hg.1	-0.5670429	SPON1			
##	TC06003369.hg.1	-0.7267408	TUBB2B			
##	TC06002625.hg.1	-0.7679904	ALDH5A1			
##	TC07002768.hg.1	-0.8003627	ZNF890P			
##	TC06001226.hg.1	-0.8640440	TUBB2A			
##	TC06003141.hg.1	-0.8762644	TIAM2			
##	TC07000793.hg.1	-0.8912032	TSPAN33			
##	TC04001652.hg.1	-0.9232694	LOC729870			

Write to text file.


```
file_name_processed = paste0("case_control_", params$treatment, ".csv")
file_name_processed
## [1] "case_control_unstim.csv"
```

## Case-Control with Gestational Age Matching

```
write_csv(gene_table, path = file_name_processed)
```

Add gene names to standard volcano plot.

```
logfc_thres = 1 # logFC threshold
pvalue_thres = 3.5 # -log10 of unadjusted p-value
gene_table %<>% mutate(
  show = ifelse(abs(logFC) > logfc_thres | pvalue_thres < -log10(P.Value),
    "yes", "no")
)
ggplot(gene_table, aes(logFC, -log10(P.Value), color = show)) +
  geom_point() +
  geom_vline(xintercept = c(-logfc_thres, logfc_thres), linetype = 2) +
  geom_hline(yintercept = pvalue_thres, linetype = 2) +
  geom_text_repel(
    data = dplyr::filter(gene_table, show == "yes"),
    aes(label = symbol),
    size = 5,
    box.padding = unit(0.35, "lines"),
    point.padding = unit(0.3, "lines")
  ) +
  xlab("log2 fold change") +
  ylab("-log10(p-value)") +
  theme(legend.position = "none") +
  scale_colour_manual(values = c("gray", "black")) +
  ggtitle(ifelse(params$treatment == "unstim",
    "Unstimulated Samples",
    "Stimulated Samples"))
```



## Case-Control with Gestational Age Matching

```
ggsave(filename = paste0("log2_fc_", params$treatment, ".png"))  
## Saving 6 x 6 in image
```

## Session Info

```
sessionInfo()  
## R version 3.5.1 (2018-07-02)  
## Platform: x86_64-apple-darwin15.6.0 (64-bit)  
## Running under: macOS 10.15.1  
##  
## Matrix products: default  
## BLAS: /Library/Frameworks/R.framework/Versions/3.5/Resources/lib/libRblas.0.dylib  
## LAPACK: /Library/Frameworks/R.framework/Versions/3.5/Resources/lib/libRlapack.dylib  
##  
## locale:  
## [1] en_US.UTF-8/en_US.UTF-8/en_US.UTF-8/C/en_US.UTF-8/en_US.UTF-8  
##  
## attached base packages:  
## [1] stats4      parallel    stats      graphics  grDevices  utils      datasets  
## [8] methods     base  
##  
## other attached packages:  
## [1] pd.hta.2.0.3.12.2          DBI_1.0.0  
## [3] RSQLite_2.1.1             ggrepel_0.8.1  
## [5] tibble_2.1.3              stringr_1.4.0  
## [7] readxl_1.3.1              dplyr_0.8.3  
## [9] readr_1.3.1               statmod_1.4.32  
## [11] magrittr_1.5              ggfortify_0.4.7  
## [13] ggplot2_3.2.1             MatchIt_3.0.2  
## [15] genefilter_1.64.0         affycoretools_1.54.0  
## [17] hta20transcriptcluster.db_8.7.0 org.Hs.eg.db_3.7.0  
## [19] AnnotationDbi_1.44.0      limma_3.38.3  
## [21] oligo_1.46.0              Biostrings_2.50.2  
## [23] XVector_0.22.0            IRanges_2.16.0  
## [25] S4Vectors_0.20.1         Biobase_2.42.0  
## [27] oligoClasses_1.44.0      BiocGenerics_0.28.0  
## [29] BiocStyle_2.10.0  
##  
## loaded via a namespace (and not attached):  
## [1] utf8_1.1.4                R.utils_2.8.0  
## [3] tidyselect_0.2.5          htmlwidgets_1.3  
## [5] grid_3.5.1               BiocParallel_1.16.6  
## [7] munsell_0.5.0            codetools_0.2-16  
## [9] preprocessCore_1.44.0     withr_2.1.2  
## [11] colorspace_1.4-1         Category_2.48.1  
## [13] OrganismDbi_1.24.0       knitr_1.22  
## [15] rstudioapi_0.10          labeling_0.3  
## [17] GenomeInfoDbData_1.2.0   hwriter_1.3.2
```

## Case-Control with Gestational Age Matching

```
## [19] bit64_0.9-7          vctrs_0.2.0
## [21] xfun_0.6             biovizBase_1.30.1
## [23] affxparser_1.54.0    R6_2.4.1
## [25] GenomeInfoDb_1.18.2  optmatch_0.9-11
## [27] locfit_1.5-9.1       AnnotationFilter_1.6.0
## [29] bitops_1.0-6         reshape_0.8.8
## [31] DelayedArray_0.8.0   assertthat_0.2.1
## [33] scales_1.0.0         nnet_7.3-12
## [35] gtable_0.3.0         affy_1.60.0
## [37] ggbio_1.30.0         svd_0.5
## [39] ensemblDb_2.6.8      rlang_0.4.1
## [41] zeallot_0.1.0        splines_3.5.1
## [43] rtracklayer_1.42.2   lazyeval_0.2.2
## [45] acepack_1.4.1        dichromat_2.0-0
## [47] checkmate_1.9.4      BiocManager_1.30.4
## [49] yaml_2.2.0           reshape2_1.4.3
## [51] abind_1.4-5          GenomicFeatures_1.34.8
## [53] backports_1.1.5      Hmisc_4.2-0
## [55] RBGL_1.58.2          tools_3.5.1
## [57] bookdown_0.9         affyio_1.52.0
## [59] gplots_3.0.1.1       ff_2.2-14
## [61] RColorBrewer_1.1-2   Rcpp_1.0.3
## [63] plyr_1.8.4           base64enc_0.1-3
## [65] progress_1.2.2       zlibbioc_1.28.0
## [67] purrr_0.3.3          RCurl_1.95-4.12
## [69] prettyunits_1.0.2    rpart_4.1-15
## [71] SummarizedExperiment_1.12.0 cluster_2.0.9
## [73] data.table_1.12.6    SparseM_1.77
## [75] ProtGenerics_1.14.0  matrixStats_0.55.0
## [77] hms_0.5.2            evaluate_0.13
## [79] xtable_1.8-4         XML_3.98-1.19
## [81] gcrma_2.54.0         gridExtra_2.3
## [83] RITools_0.1-17       compiler_3.5.1
## [85] biomaRt_2.38.0       KernSmooth_2.23-15
## [87] crayon_1.3.4         ReportingTools_2.22.1
## [89] R.oo_1.22.0          htmltools_0.3.6
## [91] GOstats_2.48.0       Formula_1.2-3
## [93] tidyr_1.0.0          geneplotter_1.60.0
## [95] MASS_7.3-51.4        Matrix_1.2-17
## [97] cli_1.1.0            R.methodsS3_1.7.1
## [99] gdata_2.18.0         GenomicRanges_1.34.0
## [101] pkgconfig_2.0.3      GenomicAlignments_1.18.1
## [103] foreign_0.8-71       foreach_1.4.4
## [105] annotate_1.60.1      AnnotationForge_1.24.0
## [107] VariantAnnotation_1.28.13 digest_0.6.22
## [109] graph_1.60.0         rmarkdown_1.12
## [111] cellranger_1.1.0     htmlTable_1.13.2
## [113] edgeR_3.24.3         GSEABase_1.44.0
## [115] curl_4.2             Rsamtools_1.34.1
## [117] gtools_3.8.1         lifecycle_0.1.0
## [119] PFAM.db_3.7.0        BSgenome_1.50.0
```



## Case-Control with Gestational Age Matching

```
## [121] fansi_0.4.0          pillar_1.4.2
## [123] lattice_0.20-38      GGally_1.4.0
## [125] httr_1.4.0           survival_2.44-1.1
## [127] G0.db_3.7.0          glue_1.3.1
## [129] iterators_1.0.10     bit_1.1-14
## [131] Rgraphviz_2.26.0     stringi_1.4.3
## [133] blob_1.1.1           DESeq2_1.22.2
## [135] latticeExtra_0.6-28  caTools_1.17.1.2
## [137] memoise_1.1.0
```