# IEC60730BSERN

# IEC60730B Example release notes

Rev. 2 — 12/2021 Release Notes

by: NXP Semiconductors

### 1 Introduction

These release notes describe important release information for the IEC60730B safety example application released with IEC60730B library v4.2.

All information about IEC60730B are at www.nxp.com/iec60730.

#### 

Revision history.....3

Contents

5

### 2 What is new

The example released with the IEC60730B library version v4\_2 contains example projects for the following boards:

Table 1. Device with available example projects

Development board	Version of library	Example projects available in MCUXspresso SDK
evkmimxrt1170	4.2	SDK 2.11
evkmimxrt1160	4.2	SDK 2.11
frdmke17z	4.2	SDK 2.11
lpcxpresso54s018m	4.2	SDK 2.11
evkmimxrt1060	4.1	SDK 2.10
evkbmimxrt1060	4.1	SDK 2.10
frdmk22f	4.1	SDK 2.10
lpcxpresso51u68	4.1	SDK 2.10
lpcxpresso845max	4.1	SDK 2.9
lpcxpresso824max	4.1	SDK 2.9
frdmkv11z	4.1	SDK 2.9
frdmke15z	4.1	SDK 2.9
frdmk32l2a4s	4.1	SDK 2.9
evkmimx8mm	4.1	SDK 2.9
evkmimxrt1020	4.1	SDK 2.9
evkmimxrt1024	4.1	SDK 2.9
evkbimxrt1050	4.1	SDK 2.9
frdmkv31f	4.1	SDK 2.9

Table continues on the next page...



Table 1. Device with available example projects (continued)

Development board	Version of library	Example projects available in MCUXspresso SDK	
lpcxpresso55s69	4.1	SDK 2.9	
lpcxpresso55s28	4.1	SDK 2.9	
evkmimx8mn	4.1	SDK 2.9	
frdmkl26z	4.1	For example please contact an NXP representative	
frdmke02z40m	4.1	For example please contact an NXP representative	
twrke18f	4.1	For example please contact an NXP representative	
twrkv58f220m	4.1	For example please contact an NXP representative	
twrkv46f150m	4.1	For example please contact an NXP representative	
frdmk32l2b3	4.1	For example please contact an NXP representative	

## 3 Development tools

The safety IEC60730B example application were tested with the following development tools:

- IAR Embedded Workbench IDE version 9.10.2
- Arm<sup>®</sup>-MDK Keil<sup>®</sup> μVision<sup>®</sup> version 5.34
- MCUxpresso IDE version 11.5.0

FreeMASTER tool version 3.0 was used for application monitoring.

## 4 Known issues or important changes

This chapter contains the description of known issues or non-stantdard behavior of the released example.

#### LPCXpresso54S018M

The LPCXpresso54S018M application examples are not provided for the Keil and MCUXpresso IDEs.

#### MIMX8M Mini and Nano

The MIMX8M Mini and Nano application examples are not provided for the Keil and MCUXpresso IDEs.

#### LPCxpresso80x - MCUXpresso IDE

The FreeMASTER monitoring is turned off due to small memory size of the MCU.

#### FRDM-KL26 uVision Keil support

The current version of the SDK does not support KL26 with the ArmV6 compiler.

Release Notes 2/4

#### FRDM-KW36/38 uVision Keil support

Example for KW36/38 in uVision Keil not suported.

#### FRDM-KE02z uVision support

The MKE02Z application example is not provided for the Keil IDE.

#### TWR-KV58F220M - uVision support

In the uVision Keil, turn off the flash test due to a problem with the download of the edited binary file by the debugger.

## 5 Revision history

Table 2. Revision table

Revision	SDK	Description
Rev 0	2.9.0	Intial release
Rev 1	2.10.0	Change devices supported in SDK rel. 2.10.
Rev 2	2.11.0	Change devices supported in SDK rel. 2.11.

How To Reach Us

Home Page:

nxp.com

Web Support:

nxp.com/support

Information in this document is provided solely to enable system and software implementers to use NXP products. There are no express or implied copyright licenses granted hereunder to design or fabricate any integrated circuits based on the information in this document. NXP reserves the right to make changes without further notice to any products herein.

NXP makes no warranty, representation, or guarantee regarding the suitability of its products for any particular purpose, nor does NXP assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters that may be provided in NXP data sheets and/or specifications can and do vary in different applications, and actual performance may vary over time. All operating parameters, including "typicals," must be validated for each customer application by customer's technical experts. NXP does not convey any license under its patent rights nor the rights of others. NXP sells products pursuant to standard terms and conditions of sale, which can be found at the following address: nxp.com/SalesTermsandConditions.

While NXP has implemented advanced security features, all products may be subject to unidentified vulnerabilities. Customers are responsible for the design and operation of their applications and products to reduce the effect of these vulnerabilities on customer's applications and products, and NXP accepts no liability for any vulnerability that is discovered. Customers should implement appropriate design and operating safeguards to minimize the risks associated with their applications and products.

NXP, the NXP logo, NXP SECURE CONNECTIONS FOR A SMARTER WORLD, COOLFLUX, EMBRACE, GREENCHIP, HITAG, ICODE, JCOP, LIFE VIBES, MIFARE, MIFARE CLASSIC. MIFARE DESFire, MIFARE PLUS, MIFARE FLEX, MANTIS, MIFARE ULTRALIGHT, MIFARE4MOBILE, MIGLO, NTAG, ROADLINK, SMARTLX, SMARTMX, STARPLUG, TOPFET, TRENCHMOS, UCODE, Freescale, the Freescale logo, AltiVec, CodeWarrior, ColdFire, ColdFire+, the Energy Efficient Solutions logo, Kinetis, Layerscape, MagniV, mobileGT, PEG, PowerQUICC, Processor Expert, QorlQ, QorlQ Qonverge, SafeAssure, the SafeAssure logo, StarCore, Symphony, VortiQa, Vybrid, Airfast, BeeKit, BeeStack, CoreNet, Flexis, MXC, Platformin a Package, QUICC Engine, Tower, TurboLink, EdgeScale, EdgeLock, eIQ, and Immersive3D are trademarks of NXP B.V. All other product or service names are the property of their respective owners. AMBA, Arm, Arm7, Arm7TDMI, Arm9, Arm11, Artisan, big.LITTLE, Cordio, CoreLink, CoreSight, Cortex, DesignStart, DynamlQ, Jazelle, Keil, Mali, Mbed, Mbed Enabled, NEON, POP, RealView, SecurCore, Socrates, Thumb, TrustZone, ULINK, ULINK2, ULINK-ME, ULINK-PLUS, ULINKpro, µVision, Versatile are trademarks or registered trademarks of Arm Limited (or its subsidiaries) in the US and/or elsewhere. The related technology may be protected by any or all of patents, copyrights, designs and trade secrets. All rights reserved. Oracle and Java are registered trademarks of Oracle and/or its affiliates. The Power Architecture and Power.org word marks and the Power and Power.org logos and related marks are trademarks and service marks licensed by Power.org.

© NXP B.V. 2021.

All rights reserved.

For more information, please visit: http://www.nxp.com
For sales office addresses, please send an email to: salesaddresses@nxp.com

Date of release: 12/2021 Document identifier: IEC60730BSERN

