## CHRISTOPH.METADATA

| | | |
|---|---|---|
| F | PRODUCTION_RULE_ID | NUMBER |
| F | METADATA_AIM | NUMBER |
| F | METADATA_MIN | NUMBER |
| F | METADATA_MAX | NUMBER |

- 🔑 FK_AIM (METADATA_AIM)
- 🔑 FK_MAX (METADATA_MAX)
- 🔑 FK_MIN (METADATA_MIN)
- 🔑 FK_PRODUCTION_RULE (PRODUCTION_RULE_ID)

## CHRISTOPH.PRODUCTION_RULE

| | | | |
|---|---|---|---|
| P | * | PRODUCTION_RULE_ID | NUMBER |
| F | | PRODUCTION_RULE_GROUP_ID | NUMBER |
| | | PRODUCTION_RULE_NAME | VARCHAR2 (50 BYTE) |

- 🔑 PK_PRODUCTION_RULE_ID (PRODUCTION_RULE_ID)
- 🔑 FK_PRODUCTION_RULE_GROUP (PRODUCTION_RULE_GROUP_ID)
- ◆ PK_PRODUCTION_RULE_ID (PRODUCTION_RULE_ID)

## CHRISTOPH.PARAMETER

| | | | |
|---|---|---|---|
| P | * | PARAMETER_ID | NUMBER |
| | | PARAMETER_NAME | VARCHAR2 (50 BYTE) |
| | | DEFAULT_VALUE | NUMBER |
| | | UPPER_LIMIT | NUMBER |
| | | LOWER_LIMIT | NUMBER |
| | | MEASUREMENT_TIME | VARCHAR2 (50 BYTE) |
| | | UNIT | VARCHAR2 (50 BYTE) |
| | | ORIGIN | VARCHAR2 (50 BYTE) |
| | | ENTRY_TYPE | VARCHAR2 (50 BYTE) |
| | | IS_TEXT | NUMBER (1) |
| | | IS_ACTIVE | NUMBER (1) |
| | | SUB_AREA | VARCHAR2 (50 BYTE) |
| | | PROCESS_PARAMETER | NUMBER (1) |
| | | QUALITY_PARAMETER | NUMBER (1) |

- 🔑 PK_PARAMETER (PARAMETER_ID)
- ◆ PK_PARAMETER (PARAMETER_ID)

## CHRISTOPH.MOLD

| | | | |
|---|---|---|---|
| P | * | ID | NUMBER |
| | * | VOLUME | NUMBER |
| | * | AGE | NUMBER |
| F | * | FORMAT | NUMBER |

- 🔑 PK_MOLD (ID)
- 🔑 FK_FORMAT (FORMAT)
- ◆ PK_MOLD (ID)

## CHRISTOPH.DISTRIBUTOR

| | | | |
|---|---|---|---|
| P | * | ID | NUMBER |
| | * | VOLUME | NUMBER |
| | * | AGE | NUMBER |

- 🔑 PK_DISTRIBUTOR (ID)
- ◆ PK_DISTRIBUTOR (ID)

## CHRISTOPH.PAN

| | | | |
|---|---|---|---|
| P | * | ID | NUMBER |
| | | VOLUME | NUMBER |
| | | AGE | NUMBER |

- 🔑 PK_PAN (ID)
- ◆ PK_PAN (ID)

## CHRISTOPH.FORMAT

| | | | |
|---|---|---|---|
| P | * | ID | NUMBER |
| | * | HEIGHT | NUMBER |
| | * | WIDTH | NUMBER |
| | * | LENGTH | NUMBER |

- 🔑 PK_FORMAT (ID)
- ◆ PK_FORMAT (ID)

## CHRISTOPH.PARAMETER_VALUE

| | | | |
|---|---|---|---|
| PF | * | PARAMETER_ID | NUMBER |
| | | TEXT | VARCHAR2 (50 BYTE) |
| | | DIGIT | NUMBER |

- 🔑 PK_PARAMETER_VALUE (PARAMETER_ID)
- 🔑 FK_PARAMETER_VALUE (PARAMETER_ID)
- ◆ PK_PARAMETER_VALUE (PARAMETER_ID)