

An Investigation of a Notion of „Variable Forgetting“ that Minimizes Truth Values

Bachelor's Thesis

in partial fulfillment of the requirements for
the degree of Bachelor of Science (B.Sc.)
in Computer Science

submitted by
Christoph Kaplan

First examiner: Prof. Dr. Matthias Thimm
Artificial Intelligence Group

Advisor: Kai Sauerwald
Artificial Intelligence Group

Statement

Ich erkläre, dass ich die Bachelorarbeit selbstständig und ohne unzulässige Inanspruchnahme Dritter verfasst habe. Ich habe dabei nur die angegebenen Quellen und Hilfsmittel verwendet und die aus diesen wörtlich oder sinngemäß entnommenen Stellen als solche kenntlich gemacht. Die Versicherung selbstständiger Arbeit gilt auch für enthaltene Zeichnungen, Skizzen oder graphische Darstellungen. Die Bachelorarbeit wurde bisher in gleicher oder ähnlicher Form weder derselben noch einer anderen Prüfungsbehörde vorgelegt und auch nicht veröffentlicht. Mit der Abgabe der elektronischen Fassung der endgültigen Version der Bachelorarbeit nehme ich zur Kenntnis, dass diese mit Hilfe eines Plagiatserkennungsdienstes auf enthaltene Plagiate geprüft werden kann und ausschließlich für Prüfungszwecke gespeichert wird.

	Yes	No
I agree to have this thesis published in the library.	☐	☐
I agree to have this thesis published on the webpage of the artificial intelligence group.	☐	☐
The thesis text is available under a Creative Commons License (CC BY-SA 4.0).	☐	☐
The source code is available under a GNU General Public License (GPLv3).	☐	☐
The collected data is available under a Creative Commons License (CC BY-SA 4.0).	☐	☐

..... (Place, Date)	 (Signature)
------------------------	----------------------

Abstract

Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet. Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua.

Contents

1	Motivation	1
2	SyntacticAnalysis	2
2.1	Behavior of Truth Values in Abstract Syntax Trees	3
3	SemanticInvestigation	4

1 Motivation

Propositional logic deals, among other things, with the satisfiability of sentences or the inference of sentences from a set of premises. A knowledge base may contain many different statements in various respects. To assert or entail sentences about specific phenomena or interest, it would be advantageous to work only with relevant knowledge to reduce computational complexity. In other words, non-relevant or irrelevant information in relation to the current interest could be "forgotten". Furthermore, knowledge bases change over time, and old knowledge might need to be contracted. To this end, an operation exists for eliminating variables within a proposition. As stated in [LR94] or [LLM03], we define variable forgetting inductively as follows:

Definition 1 (Skeptical Variable Forgetting) *Let F be a formula, p an atomic variable and S as Set of Variables. The skeptical forgetting of p in F $SkepForget(F, p)$, respectively, the skeptical forgetting of S in F $SkepForget(F, S)$, is given inductively by:*

- $SkepForget(F, \emptyset) = F$
- $SkepForget(F, \{p\}) = F[p/\top] \wedge F[p/\perp]$
- $SkepForget(F, p) = SkepForget(F, \{p\})$
- $SkepForget(F, S \cup \{p\}) = SkepForget(SkepForget(F, \{p\}), S)$

For some formulas F , this operation of variable elimination can lead to a notable reductive or drastic results. We start by considering an example where *Forget* behaves quite appropriate. Let a sentence F_1 be $a \wedge b$ and we choose to forget about b :

$$\begin{aligned} Forget(a \wedge b, b) &= F_1[b/\top] \vee F_1[b/\perp] \\ &\equiv ((a \wedge \top) \vee (a \wedge \perp)) \\ &\equiv (a \vee \perp) \\ &\equiv a \end{aligned}$$

We can see, as shown above, that $Forget(F_1, b)$ is equivalent to a which seems to be the intuitive result when thinking of forgetting about b in F_1 . Next, we consider forgetting of b in the formula $F_2 = a \vee b$

$$\begin{aligned} Forget(a \vee b, b) &= F_2[b/\top] \vee F_2[b/\perp] \\ &\equiv ((a \vee \top) \vee (a \vee \perp)) \\ &\equiv (\top \vee a) \\ &\equiv \top \end{aligned}$$

We observe that $Forget(F_2, b)$ is *tautological*, which can be seen as a rather drastic result when we choose to forget b only. A variation of a forget operation could be defined as follows:

Definition 2 (Skeptical Variable Forgetting) Let F be a formula, p an atomic variable and S as Set of Variables. The skeptical forgetting of p in F $SkepForget(F, p)$, respectively, the skeptical forgetting of S in F $SkepForget(F, S)$, is given inductively by:

- $SkepForget(F, \emptyset) = F$
- $SkepForget(F, \{p\}) = F[p/\top] \wedge F[p/\perp]$
- $SkepForget(F, p) = SkepForget(F, \{p\})$
- $SkepForget(F, S \cup \{p\}) = SkepForget(SkepForget(F, \{p\}), S)$

The idea is to use conjunction instead of disjunction. The consequences for our previous examples are the following:

$$\begin{aligned} SkepForget(a \wedge b, b) &= F_1[b/\top] \wedge F_1[b/\perp] \\ &\equiv ((a \wedge \top) \wedge (a \wedge \perp)) \\ &\equiv (a \wedge \perp) \\ &\equiv a \end{aligned}$$

$$\begin{aligned} SkepForget(a \vee b, b) &= F_2[b/\top] \wedge F_2[b/\perp] \\ &\equiv ((a \vee \top) \wedge (a \vee \perp)) \\ &\equiv (\top \wedge a) \\ &\equiv \top \end{aligned}$$

We observe that our alternative operation, at least in these examples, doesn't necessarily entail less drastic results. We obtain a contradiction in the first case and in the second case, our equivalent to a . It suggests a duality between the two operations.

2 SyntacticAnalysis

what are good examples to start of with the semantical analysis ? When does deeper nesting affect the result of the semantical analysis ? $F_1 = a$

$$F_2 = a \wedge b$$

$$F_3 = (x \vee y) \wedge (w \vee z)$$

$$\begin{aligned}
Forget(a, a) &= F_1[a/\top] \vee F_1[a/\perp] \\
&\equiv (\top \vee \perp) \\
&\equiv \top \\
Forget(a \wedge b, a) &= F_2[a/\top] \vee F_2[a/\perp] \\
&\equiv ((\top \wedge b) \vee (\perp \wedge b)) \\
&\equiv (b \vee \perp) \\
&\equiv b \\
Forget((x \vee y) \wedge (w \vee z), x) &= F_3[x/\top] \vee F_3[x/\perp] \\
&\equiv (((\top \vee y) \wedge (w \vee z)) \vee ((\perp \vee y) \wedge (w \vee z))) \\
&\equiv ((\top \wedge (w \vee z)) \vee (y \wedge (w \vee z))) \\
&\equiv ((w \vee z) \vee (y \wedge (w \vee z))) \\
&\equiv (w \vee z)
\end{aligned}$$

2.1 Behavior of Truth Values in Abstract Syntax Trees

The behavior of truth values presents notably insights when considering their interactions with logical connectives. We know that $\top \wedge \perp \equiv \perp$ and $\top \vee \perp \equiv \top$. To investigate the behaviour abstract syntax trees are a great way to visualize sentences.




Figure 1: caption

In these examples we can observe the propagation of truth values, in this case $\top$. Starting from the leafes $@ \top$ effectively "absorbs" all siblings in conjunction with $\vee$ and stops propagating at $\wedge$.




Figure 2: caption

Dual to that, $\perp$ "annihilates" all siblings when paired with a logical $\wedge$ and halts at $\vee$. This dynamic interaction implies that truth values possess the capability to selectively "eliminate" variables and entire propositions.

3 SemanticInvestigation

A	B	C	$((A \vee B) \wedge C)$	$((\top \vee B) \wedge C) \vee ((\perp \vee B) \wedge C) \equiv C$
0	1	1	1	1
0	1	0	0	0
0	0	1	0	1
0	0	0	0	0
1	1	1	1	1
1	1	0	0	0
1	0	1	1	1
1	0	0	0	0

Figure 3: Forget $((A \vee B) \wedge C, A)$

A	B	C	$((A \vee B) \wedge C)$	$((\top \vee B) \wedge C) \wedge ((\perp \vee B) \wedge C) \equiv (B \wedge C)$
0	1	1	1	1
0	1	0	0	0
0	0	1	0	0
0	0	0	0	0
1	1	1	1	1
1	1	0	0	0
1	0	1	1	0
1	0	0	0	0

Figure 4: SkipForget $((A \vee B) \wedge C, A)$

A	B	C	$((A \wedge B) \vee C)$	$((\top \wedge B) \vee C) \vee ((\perp \wedge B) \vee C) \equiv (B \vee C)$
0	1	1	1	1
0	1	0	0	1
0	0	1	1	1
0	0	0	0	0
1	1	1	1	1
1	1	0	1	1
1	0	1	1	1
1	0	0	0	0

Figure 5: Forget $((A \wedge B) \vee C, A)$

A	B	C	$((A \wedge B) \vee C)$	$((\top \wedge B) \vee C) \wedge ((\perp \wedge B) \vee C) \equiv C$
0	1	1	1	1
0	1	0	0	0
0	0	1	1	1
0	0	0	0	0
1	1	1	1	1
1	1	0	1	0
1	0	1	1	1
1	0	0	0	0

Figure 6: SkipForget $((A \wedge B) \vee C, A)$

A	B	C	$((A \vee B) \wedge C)$	$((A \vee B) \wedge \top) \vee ((A \vee B) \wedge \perp) \equiv (A \vee B)$
1	1	0	0	1
1	0	0	0	1
0	1	0	0	1
0	0	0	0	0
1	1	1	1	1
1	0	1	1	1
0	1	1	1	1
0	0	1	0	0

Figure 7: $\text{Forget}((A \vee B) \wedge C, C)$

A	B	C	$((A \vee B) \wedge C)$	$((A \vee B) \wedge \top) \wedge ((A \vee B) \wedge \perp) \equiv \perp$
1	1	0	0	0
1	0	0	0	0
0	1	0	0	0
0	0	0	0	0
1	1	1	1	0
1	0	1	1	0
0	1	1	1	0
0	0	1	0	0

Figure 8: $\text{SkepForget}((A \vee B) \wedge C, C)$

A	B	C	$((A \wedge B) \vee C)$	$((A \wedge B) \vee \top) \vee ((A \wedge B) \vee \perp) \equiv \top$
1	1	0	1	1
1	0	0	0	1
0	1	0	0	1
0	0	0	0	1
1	1	1	1	1
1	0	1	1	1
0	1	1	1	1
0	0	1	1	1

Figure 9: $\text{Forget}((A \wedge B) \vee C, C)$

A	B	C	$((A \wedge B) \vee C)$	$((A \wedge B) \vee \top) \wedge ((A \wedge B) \vee \perp) \equiv (A \wedge B)$
1	1	0	1	1
1	0	0	0	0
0	1	0	0	0
0	0	0	0	0
1	1	1	1	1
1	0	1	1	0
0	1	1	1	0
0	0	1	1	0

Figure 10: $\text{SkepForget}((A \wedge B) \vee C, C)$

$$\text{Mod}(\text{Forget}(F, x)) = \text{Mod}(F) \cup \{\text{Switch}(w, x) \mid w \models F\}$$

$$\text{Mod}(\text{SkepForget}(F, x)) = \text{Mod}(F) \cap \{\text{Switch}(w, x) \mid w \models F\}$$

References

- [LLM03] Jérôme Lang, Paolo Liberatore, and Pierre Marquis. Propositional independence-formula-variable independence and forgetting. *Journal of Artificial Intelligence Research*, 18:391–443, 2003.
- [LR94] Fangzhen Lin and Ray Reiter. Forget it. In *Working Notes of AAAI Fall Symposium on Relevance*, pages 154–159, 1994.