


[Re] A circuit model of auditory cortexParvathy Neelakandan¹ and Christoph Metzner^{1,2, }¹Neural Information Processing Group, Institute of Software Engineering and Theoretical Computer Science, Technische Universität Berlin, Berlin, Germany – ²Biocomputation Group, Centre for Computer Science and Informatics Research, University of Hertfordshire, Hatfield, United KingdomEdited by
(Editor)Received
–Published
–DOI
–**Introduction**

bla

Methods

In this replication, we focus on the rate models proposed in the original article. The firing rate model was an extensions of the traditional Wilson-Cowan model¹ and represented an iso-frequency unit of the auditory cortex. This iso-frequency unit consisted of one excitatory and two inhibitory populations. Building on this unit a more complex three-unit rate models was developed, to investigate stimulus-specific adaptation, forward suppression, tunig-curve adaptation and feedforward functional connectivity.

Iso-Frequency Unit Model The iso-frequency unit model was based on the Wilson-Cowan model¹ but was modified to include two different types of inihbitory interneurons. The two inhibitory population are meant to represent parvalbumin-psoitve (PV) and somatostatin (SST) cells. The single unit model is given by

$$\tau_u \frac{du(t)}{dt} = -u(t) + f(w_{ee}u(t) - w_{ep}p(t) - w_{es}s(t) + qg(t)i(t)), \quad (1)$$

$$\tau_p \frac{dp(t)}{dt} = -p(t) + f(w_{pe}u(t) - w_{pp}p(t) - w_{ps}s(t) + I_{Opt,PV}(t) + qg(t)i(t)), \quad (2)$$

$$\tau_s \frac{ds(t)}{dt} = -s(t) + f(w_{se}u(t) - w_{sp}p(t) - w_{ss}s(t) + I_{Opt,SST}(t)), \quad (3)$$

with $u(t)$, $p(t)$, and $s(t)$ being the normalized firing rates (in $[0, 1]$) of the pyramidal cell population, the PV population and the SST population, respectively. Furthermore, w_{xy} represents the strengths of connections from population y to population x . The two terms $I_{Opt,PV}$ and $I_{Opt,SST}$ describe the input current to cells due to optogenetic stimulation of the PV population and SST population, respectively. τ_i , $i \in u, p, s$ defines the time constants for the respective populaitons. The function f is realised as a threshold linear function given by

$$f(x) = \begin{cases} 0 & \text{if } x \leq 0 \\ rx & \text{if } 0 < x \leq 1/r \\ 1 & \text{if } x > 1/r, \end{cases}$$

Copyright © 2020 P. Neelakandan and C. Metzner, released under a Creative Commons Attribution 4.0 International license.
Correspondence should be addressed to Christoph Metzner (cmetzner@ni.tu-berlin.de)
The authors have declared that no competing interests exists.
Code is available at <https://github.com/ChristophMetzner/Park-Geffen-Replication>.

Table 1. Overview of the model parameters

a	b	c
1	2	3

(4)

which coarsely approximates a sigmoid function. Furthermore, the function f is thresholded by simply subtracting a constant u_i from the input x (i.e. $f(x - u_i)$) which varied for the different populations. Lastly, afferent auditory input is fed into the unit is given by $qg(t)i(t)$, which is subdivided into the 'raw' input $i(t)$ and a slow modulation $g(t)$ mimicking synaptic depression at thalamic synapses. The input function $i(t)$ is simply an instantaneous rise with amplitude q and an exponential decay with a time constant of τ_q . The synaptic depression $g(t)$ is governed by the following equation

$$\frac{dg(t)}{dt} = \frac{g_0 - g(t)}{\tau_{d1}} - \frac{g(t)i(t)}{\tau_{d2}}. \quad (5)$$

The parameter values can be found in Table 1

Three-Unit Model Building on the single unit a three-unit model was implemented, with each single unit representing a different input frequency, thus creating a simple tonotopic layout that allowed to explore more complex auditory inputs. Intra-unit connectivity was as described before for the single-unit model. Inter-unit connectivity was restricted to immediate neighbours and included the following connection types: Exc to exc, exc to PV and SST to exc. Together, the activity of the three populations of each unit was governed by

$$\tau_u \frac{du_i(t)}{dt} = -u_i(t) + f(w_{ee}u_i(t) - (w_{ep} - a(1 - D_i(t)))p_i(t) - w_{es}s_i(t) + J_{1,i}(t)), \quad (6)$$

$$\tau_p \frac{dp_i(t)}{dt} = -p_i(t) + f(w_{pe}u_i(t) - w_{pp}p_i(t) - w_{ps}s_i(t) + I_{Opt,PV}(t) + J_{2,i}(t)), \quad (7)$$

$$\tau_s \frac{ds_i(t)}{dt} = -s_i(t) + f(w_{se}u_i(t) - w_{sp}p_i(t) - w_{ss}s_i(t) + I_{Opt,SST}(t) + J_{3,i}(t)), \quad (8)$$

with

$$J_{1,i}(t) = \begin{cases} -F_i(t)s_2(t) + qI_i(t) + w_{ee}^*u_2(t) & \text{if } i = 1, 3 \\ -F_s(t)(s_1(t) + s_3(t)) + qI_2(t) + \frac{w_{ee}^*(u_1(t) + u_3(t))}{2} & \text{if } i = 2 \end{cases} \quad (9)$$

and

$$J_{2,i}(t) = \begin{cases} qI_i(t) + w_{pe}^*u_2(t) & \text{if } i = 1, 3 \\ qI_2(t) + \frac{w_{pe}^*(u_1(t) + u_3(t))}{2} & \text{if } i = 2 \end{cases} \quad (10)$$

and

$$J_{3,i}(t) = \begin{cases} qI_i(t) + w_{se}^*u_2(t) & \text{if } i = 1, 3 \\ qI_2(t) + \frac{w_{se}^*(u_1(t) + u_3(t))}{2} & \text{if } i = 2. \end{cases} \quad (11)$$




Figure 1. ReFig1




Figure 2. ReFig2

Here, $I_i(t)$ is described by

$$I_k(t) = g_k(t)i_k(t) + g_2(t)i_2(t)\alpha \quad \text{for } k = 1, 3 \quad (12)$$

and

$$I_2(t) = (g_1(t)i_1(t) + g_3(t)i_3(t))\alpha + g_2(t)i_2(t). \quad (13)$$

Reproduction of experiments

Reimplementation

The iso-frequency unit model and the three-unit model were both implemented in Python and integrated into the neurolib framework².

Discussion

bla




Figure 3. ReFig3

References

1. H. R. Wilson and J. D. Cowan. "Excitatory and inhibitory interactions in localized populations of model neurons." In: **Biophysical journal** 12.1 (1972), pp. 1–24.
2. C. Cakan, C. Metzner, and N. Jajcay. **neurolib: A Python simulation framework for easy whole-brain neural mass modeling**. 2019.




Figure 4. ReFig4




Figure 5. ReFig6




Figure 6. ReFig8




Figure 7. ReFig9