


CS3110 Formal Language and Automata

Tingting Chen
Computer Science
Cal Poly Pomona



Example PDA

- PDA M , $L(M) = \{a^n b^n : n \geq 0\}$




Execution Example: Time 0

Input





Stack

current
state




Execution Example: Time 1

Input





Stack




Execution Example: Time 2

Input





Stack




Execution Example: Time 3

Input





Stack




Execution Example: Time 4

Input





Stack




Execution Example: Time 5

Input





Stack




Execution Example: Time 6

Input





Stack




Execution Example: Time 7

Input





Stack




Execution Example: Time 8

Input



Stack



PDA – Accepting a string



- A string is accepted if there is a computation such that
 - All the input is consumed
 - And the last state is an accepting state
 - At the end of computation, we do not care about the stack contents. The stack can be empty at the last state.

PDA – Rejecting a string

- A string is rejected if there is no computation such that
 - All the input is consumed
 - And the last state is an accepting state
 - At the end of computation, we do not care about the stack contents.


Rejection Example: Time 0

Input





Stack

current
state




Rejection Example: Time 1

Input





Stack

current
state




Rejection Example: Time 2

Input





Stack

current
state




Rejection Example: Time 3

Input





Stack

current
state



Rejection Example: Time 4


Input




Stack

Reject

current
state



PDA -- Example




Guess the middle of string

$$L(M) = \{vv^R : v \in \{a,b\}^*\}$$

How the PDA executes, with input string abbb?







Exercise: $L(M)=?$



$$L(M) = \{w \in \{a,b\}^* : \text{every prefix } v, n_a(v) \geq n_b(v)\}$$

Push Strings

Example




Exercise: $L(M)=?$

$a, \$ \rightarrow 0\$$ $b, \$ \rightarrow 1\$$

$a, 0 \rightarrow 00$ $b, 1 \rightarrow 11$

$a, 1 \rightarrow \lambda$ $b, 0 \rightarrow \lambda$



Pushdown Automaton: Formal Definition

A nondeterministic pushdown automaton (NPDA) is a 7-tuple

Q is a finite set of states

Σ is the input alphabet (a finite set)

Γ is the stack alphabet (a finite set)

$\delta : Q \times (\Sigma \cup \{\lambda\}) \times \Gamma \rightarrow (\text{finite subsets of } Q \times \Gamma^*)$

is the transition function

$q_0 \in Q$ is the start state

$z \in \Gamma$ is the initial stack symbol

$F \subseteq Q$ is the set of accepting states