

# Package ‘MatchingFrontier’

August 13, 2014

**Version** 0.1

**Date** 2014-08-08

**Type** Package

**Title** R Package for Calculating the Balance-Sample Size Frontier

**Author** Gary King, Christopher Lucas, and Richard Nielsen

**Maintainer** Christopher Lucas <clucas@fas.harvard.edu>

**Description** Implements methods from King, Lucas, and Nielsen

**Imports** igraph

**LazyData** true

**License** GPL-3

## R topics documented:

estimateEffects . . . . .	2
generateDataset . . . . .	2
lalonge . . . . .	3
makeFrontier . . . . .	4
plotEstimates . . . . .	5
plotFrontier . . . . .	6
<b>Index</b>	<b>7</b>

---

estimateEffects	<i>Estimate Effects on the Frontier</i>
-----------------	---

---

### Description

estimateEffects() is used to estimate the effect of the treatment along the entire frontier.

### Usage

```
estimateEffects(frontier.object, formula)
```

### Arguments

frontier.object	An object generated by makeFrontier().
formula	An object of class formula (or one that can be coerced to that class). This will be passed to lm().

### Examples

```
## Not run:
data(lalonde)
match.on <- colnames(lalonde)[!(colnames(lalonde) %in% c('re78', 'treat'))]
my.frontier <- makeFrontier(dataset = lalonde,
                           treatment = 'treat',
                           outcome = 're78',
                           match.on = match.on)
my.estimates <- estimateEffects(my.frontier, 're78 ~ treat')

## End(Not run)
```

---

generateDataset	<i>Generate a data set that is on the balance - sample size frontier.</i>
-----------------	---

---

### Description

generateDataset() allows the user to export a data set that sits on the frontier.

### Usage

```
generateDataset(frontier.object, number.to.prune)
```

**Arguments**`frontier.object`An object generated by `makeFrontier()`.`number.to.prune`The number of observations that are to be pruned. If the user selects an undefined point, `generateDataset` returns a dataset from the nearest defined point on the frontier.**Examples**

```
## Not run:
data(lalonge)
match.on <- colnames(lalonge)[!(colnames(lalonge) %in% c('re78', 'treat'))]
my.frontier <- makeFrontier(dataset = lalonge,
                           treatment = 'treat',
                           outcome = 're78',
                           match.on = match.on)
my.dataset <- generateDataset(my.frontier, 1000)

## End(Not run)
```

lalonge

*Modified Lalonde dataset***Description**

This is a modified version of the Lalonde experimental dataset used for explanatory purposes only.

**Usage**

```
data(lalonge)
```

**Format**

A data frame with 16437 observations on the following 11 variables.

`treat` treatment variable indicator

`age` age

`education` years of education

`black` race indicator variable

`married` marital status indicator variable

`nodegree` indicator variable for not possessing a degree

`re74` real earnings in 1974

`re75` real earnings in 1975

`re78` real earnings in 1978 (post-treatment outcome)

`hispanic` ethnic indicator variable



---

plotEstimates	<i>Plot estimates along the frontier.</i>
---------------	---

---

## Description

plotEstimates() plots estimates along the frontier.

## Usage

```
plotEstimates(frontier.object, estimates.object, xlab = "Number of Observations Pruned", ylab = "Estimate")
```

## Arguments

frontier.object	An object generated by makeFrontier()
estimates.object	An object generated by estimateEffects()
xlab	The label for the x-axis. Defaults to 'Number of Observations Pruned'.
ylab	The label for the y-axis. Defaults to 'Estimate'.
main	The main label. Defaults to 'Effects Plot'.
...	Additional arguments to be passed to plot.

## Details

plotEstimates() wraps plot and uses ... to pass additional arguments to the base plot() function, like color, axis range, etc.

## Examples

```
## Not run:
data(lalonde)
match.on <- colnames(lalonde)[!(colnames(lalonde) %in% c('re78', 'treat'))]
my.frontier <- makeFrontier(dataset = lalonde,
                           treatment = 'treat',
                           outcome = 're78',
                           match.on = match.on)
my.estimates <- estimateEffects(my.frontier, 're78 ~ treat')
plotEstimates(my.frontier, my.estimates)

## End(Not run)
```

---

plotFrontier	<i>Plot the balance - sample size frontier.</i>
--------------	---

---

### Description

plotFrontier() plots the balance - sample size frontier.

### Usage

```
plotFrontier(frontier.object, xlab = "Number of Observations Pruned", ylab = "AMD", main = "Frontier P
```

### Arguments

frontier.object	An object generated by makeFrontier()
xlab	The label for the x-axis. Defaults to 'Number of Observations Pruned'.
ylab	The label for the y-axis. Defaults to 'Estimate'.
main	The main label. Defaults to 'Effects Plot'.
...	Additional arguments to be passed to plot.

### Details

plotEstimates() wraps plot and uses ... to pass additional arguments to the base plot() function, like color, axis range, etc.

### Examples

```
## Not run:
data(lalonde)
match.on <- colnames(lalonde)[!(colnames(lalonde) %in% c('re78', 'treat'))]
my.frontier <- makeFrontier(dataset = lalonde,
                           treatment = 'treat',
                           outcome = 're78',
                           match.on = match.on)
my.estimates <- estimateEffects(my.frontier, 're78 ~ treat')
plotFrontier(my.frontier)

## End(Not run)
```

# Index

`estimateEffects`, [2](#)

`generateDataset`, [2](#)

`lalonge`, [3](#)

`makeFrontier`, [4](#)

`plotEstimates`, [5](#)

`plotFrontier`, [6](#)