

# Dell | Cloudera Solution Crowbar Administration Users Guide v.2.2

A Dell Users Guide for Apache Hadoop Deployment

Revision 1.0



## Table of Contents

<b>Table of Contents .....</b>	<b>2</b>
<b>Figures .....</b>	<b>3</b>
<b>Tables .....</b>	<b>4</b>
<b>Trademarks.....</b>	<b>4</b>
<b>Notes, Cautions, and Warnings .....</b>	<b>4</b>
<b>Abbreviations.....</b>	<b>5</b>
<b>Overview .....</b>	<b>5</b>
<b>Introduction.....</b>	<b>5</b>
<b>Document Scope .....</b>	<b>6</b>
Opscode Chef Server.....	6
Dell Specific Options .....	6
<b>Dell   Cloudera Solution .....</b>	<b>7</b>
Network Setup .....	7
Managing Growth.....	7
<i>Rack.....</i>	<i>7</i>
<i>Pod.....</i>	<i>7</i>
<i>Cluster.....</i>	<i>7</i>
Default Networks.....	8
<i>Layout .....</i>	<i>8</i>
<i>IP Addressing .....</i>	<i>9</i>
<i>Rack Awareness.....</i>	<i>9</i>
Hadoop Basics .....	10
Apache Hadoop Component Deployment .....	10
<b>Crowbar User Interface .....</b>	<b>11</b>
<b>Cloudera Manager Overview .....</b>	<b>12</b>
Functionality Outline.....	12
<b>Barclamps .....</b>	<b>13</b>
Cloudera Manager Barclamp .....	14
<i>Cloudera Manager Installation Overview .....</i>	<i>14</i>
<i>Cloudera Manager Node Inventory Page.....</i>	<i>14</i>
<i>Cloudera Manager Administration Console.....</i>	<i>15</i>
Login Screen.....	16
License Key Upload Screen.....	16
License Key Restart Screen .....	18
License Key Confirmation Screen.....	19
Node Search Screen .....	20
Node Search Results Screen.....	21
Select Repository Screen .....	22
Repository Configuration Screen .....	23
SSH Credentials Screen .....	25
Package Install Screen .....	26

- Host Inspector Screen .....27
- Service Selection Screen .....28
- Inspect Role Assignments Screen # 1.....29
- Inspect Role Assignments Screen # 2 .....30
- Monitoring Database Setup Screen.....31
- Review Configuration Changes Screen.....32
- Cluster Services Initialization Screen .....33
- Configuration Completion Screen .....34
- Service Display Screen.....35
- Pig Barclamp .....36
- Sqoop Barclamp .....37
- Support.....37**
  - Dell Support.....37
  - Cloudera Support.....37
- Appendix A: Dell | Hadoop Solution Components .....38**
- Appendix B: References.....38**
- To Learn More.....38**

Figures

- FIGURE 1: NODE INVENTORY SCREEN .....15
- FIGURE 2: LOGIN SCREEN.....16
- FIGURE 3: LICENSE KEY UPLOAD SCREEN .....17
- FIGURE 4: LICENSE KEY RESTART SCREEN.....18
- FIGURE 5: LICENSE KEY CONFIRMATION SCREEN .....19
- FIGURE 6: CLOUDERA CLUSTER NODE SEARCH SCREEN.....20
- FIGURE 7: NODE SEARCH RESULTS SCREEN .....21
- FIGURE 8: SELECT REPOSITORY SCREEN .....22
- FIGURE 9: REPOSITORY CONFIGURATION SCREEN .....24
- FIGURE 10: SSH CREDENTIALS SCREEN.....25
- FIGURE 11: PACKAGE INSTALL SCREEN.....26
- FIGURE 12: HOST INSPECTOR SCREEN.....27
- FIGURE 13: SERVICE SELECTION SCREEN .....28
- FIGURE 14: INSPECT ROLE ASSIGNMENTS SCREEN # 1.....29
- FIGURE 15: INSPECT ROLE ASSIGNMENTS SCREEN #2.....30
- FIGURE 16: MONITORING DATABASE SETUP SCREEN.....31
- FIGURE 17: REVIEW CONFIGURATION CHANGES SCREEN.....32
- FIGURE 18: CLUSTER SERVICES INITIALIZATION SCREEN.....33
- FIGURE 19: CONFIGURATION COMPLETION SCREEN .....34
- FIGURE 20: SERVICE DISPLAY SCREEN.....35

## Tables

TABLE 1: DEFAULT NETWORKS .....	8
TABLE 2: MASTER/SECONDARY (ADMIN) NAME NODES NETWORK CONNECTIONS .....	8
TABLE 3: EDGE NODES NETWORK CONNECTIONS.....	8
TABLE 4: DATA NODES NETWORK CONNECTIONS.....	9
TABLE 5: IP ADDRESSING SCHEMA .....	9
TABLE 6: POD 1 IP EXAMPLE ADDRESSING LAYOUT .....	9
TABLE 7: POD 2 IP EXAMPLE ADDRESSING LAYOUT .....	10
TABLE 8: SUPPORTED APACHE HADOOP COMPONENTS .....	11
TABLE 9: USER INTERFACE SERVICE URLS .....	12
TABLE 10: DIFFERENCES BETWEEN CLOUDERA MANAGER FREE EDITION AND CLOUDERA MANAGER .....	13
TABLE 11: BARCLAMP DESCRIPTIONS .....	13
TABLE 12: BARCLAMP PARAMETERS .....	14
TABLE 13: OPERATING SYSTEM PARAMETERS .....	14
TABLE 14: HADOOP HIGH AVAILABILITY PARAMETERS (SHARED STORAGE USING NFS) .....	14
TABLE 15: PIG BARCLAMP PARAMETERS.....	36
TABLE 17: SQOOP BARCLAMP PARAMETERS .....	37

## Trademarks

THIS PAPER IS FOR INFORMATIONAL PURPOSES ONLY, AND MAY CONTAIN TYPOGRAPHICAL ERRORS AND TECHNICAL INACCURACIES. THE CONTENT IS PROVIDED AS IS, WITHOUT EXPRESS OR IMPLIED WARRANTIES OF ANY KIND.

Reproduction of these materials is allowed under the Apache 2 license.

Information in this document is subject to change without notice.

© 2013 Dell Inc. All rights reserved.

Dell, the DELL logo, and the DELL badge, PowerConnect, and PowerEdge are trademarks of Dell Inc. Cloudera, CDH, and Cloudera Enterprise are trademarks of Cloudera and its affiliates in the US and other countries. Intel and Xeon are registered trademarks of Intel Corporation in the U.S. and other countries. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Dell Inc. disclaims any proprietary interest in trademarks and trade names other than its own.

Other trademarks used in this text: Nagios®, Opscode Chef™, OpenStack™, Canonical Ubuntu™, and VMware™, Dell Precision™, OptiPlex™, Latitude™, PowerEdge™, PowerVault™, PowerConnect™, OpenManage™, EqualLogic™, KACE™, FlexAddress™ and Vostro™ are trademarks of Dell Inc. Intel®, Pentium®, Xeon®, Core™ and Celeron® are registered trademarks of Intel Corporation in the U.S. and other countries. AMD® is a registered trademark and AMD Opteron™, AMD Phenom™, and AMD Sempron™ are trademarks of Advanced Micro Devices, Inc. Microsoft®, Windows®, Windows Server®, MS-DOS® and Windows Vista® are either trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Red Hat Enterprise Linux® and Enterprise Linux® are registered trademarks of Red Hat, Inc. in the United States and/or other countries. Novell® is a registered trademark and SUSE™ is a trademark of Novell Inc. in the United States and other countries. Oracle® is a registered trademark of Oracle Corporation and/or its affiliates. Citrix®, Xen®, XenServer® and XenMotion® are either registered trademarks or trademarks of Citrix Systems, Inc. in the United States and/or other countries. VMware®, Virtual SMP®, vMotion®, vCenter®, and vSphere® are registered trademarks or trademarks of VMware, Inc. in the United States or other countries.

Other trademarks and trade names may be used in this publication to refer to either the entities claiming the marks and names or their products. Dell Inc. disclaims any proprietary interest in trademarks and trade names other than its own.

March 2013

## Notes, Cautions, and Warnings



**Note:** A NOTE indicates important information that helps you make better use of your computer.



**CAUTION:** A CAUTION indicates potential damage to hardware or loss of data if instructions are not followed.



**WARNING:** A WARNING indicates a potential for property damage, personal injury, or death.

## Abbreviations

---

Abbreviation	Definition
BMC	Baseboard Management Controller.
DBMS	Database management system.
EDW	Enterprise data warehouse.
EoR	End-of-row switch/router.
HDFS	Hadoop Distributed File System.
IPMI	Intelligent Platform Management Interface.
LAG	Link aggregation group.
LOM	Local Area Network on Motherboard.
NIC	Network interface card.
ToR	Top-of-rack switch/router.

## Overview

---


Hadoop is an Apache project being built and used by a global community of contributors, written in the Java programming language. Yahoo! has been the largest contributor to the project, and uses Hadoop extensively across its businesses. Other contributors and users include Facebook, LinkedIn, eHarmony, and eBay. Cloudera has created a quality controlled distribution of Hadoop and offers commercial management software, support, and consulting services.

Dell developed a solution for Hadoop that includes optimized hardware, software, and services to streamline deployment and improve the customer experience.

## Introduction

---

This document provides instructions you to use when deploying Cloudera Manager and Apache Hadoop Ecosystem components with Crowbar. This guide is for use with the Crowbar Users Guide, and is *not* a stand-alone document. It specifically covers Cloudera Manager, Apache Hadoop and the deployment steps from a Crowbar prospective. Please refer to the *Crowbar User Guide* for assistance with installing common Crowbar components and configuring the target systems.

 **Note:** Concepts beyond the scope of this guide are introduced as needed in notes and references to other documentation.

The Dell | Cloudera Solution is based on the Cloudera CDH Enterprise distribution of Hadoop. Dell's solution includes:

- Dell Reference architecture (RA) and best practices documentation.
- Optimized hardware and network infrastructure.
- Cloudera CDH software (CDH Community-provided for customer-deployed solutions).
- Cloudera Manager free edition with the ability to upgrade to enterprise level via Cloudera issued license key.
- Cloudera Manager provided Hadoop infrastructure management tools.
- Dell Crowbar software framework.

This solution provides Dell a foundation to offer additional solutions as the Hadoop environment evolves and expands.

### Document Scope

---

The focus of this guide is the use of Crowbar, *not* Apache Hadoop or Cloudera Manager. While Crowbar includes substantial components to assist in the deployment of Apache Hadoop and Cloudera Manager, its operational aspects are completely independent. For more detailed information, please refer to the following links:

#### Cloudera Manager 4.5 Free Edition Documentation

- <https://ccp.cloudera.com/display/DOC/Documentation#Documentation-ClouderaManager4.5FreeEditionDocumentation>

#### Cloudera Manager 4.5 Enterprise Edition Documentation


- <https://ccp.cloudera.com/display/DOC/Documentation#Documentation-ClouderaManager4.5EnterpriseEditionDocumentation>

#### CDH4 Documentation

- <https://ccp.cloudera.com/display/DOC/Documentation#Documentation-CDH4Documentation>

#### Apache Hadoop Documentation

- <http://hadoop.apache.org/>

 This guide provides this additional information about Cloudera as notes flagged with the Cloudera logo. For detailed operational support for Hadoop, we suggest visiting the Cloudera documentation web site at <http://www.cloudera.com>.

### Opscode Chef Server

Crowbar makes extensive use of Opscode Chef Server, <http://opscode.com>. To explain Crowbar actions, you should understand the underlying Chef implementation. This guide provides this additional Chef information as notes flagged with the Opscode logo.



To use Crowbar, it is not necessary to log into the Chef Server; consequently, use of the Chef UI is not covered in this guide. Supplemental information about Chef is included.

### Dell Specific Options

The Dell EULA version of Crowbar provides additional functionality and color pallets than the open source version. When divergences are relevant, they are identified.



To perform some configuration options and provide some integration, we use libraries that cannot be distributed using open source.

Crowbar is not limited to managing Dell servers and components. Due to driver requirements, some barclamps, for example: BIOS and RAID must be targeted to specific hardware; however, those barclamps are not required for system configuration.

### Dell | Cloudera Solution

---

#### Network Setup

The network configuration assumes a flat L2 wiring. All network connections should be accessible at that layer. Where isolation between different logical networks is required, VLANs are used.

#### Managing Growth

The system architecture is organized into three components, for sizing as the Hadoop environment grows. From smallest to largest, they are:

- Rack
- Pod
- Cluster

Each has specific characteristics and sizing considerations. You can scale the environment by adding additional capacity as needed, without the need to replace any existing components.

##### Rack

A rack is the smallest component in a Hadoop environment, and consists of all of the power, network cabling, and two Ethernet switches required to support up to 20 data nodes. These nodes should utilize their own power connectivity and data center space – separate from other racks – and be treated as a fault zone.

##### Pod

A pod is a single set of stacked Ethernet switches. For the Dell | Cloudera Reference Architecture, both the maximum and minimum are six. A pod consists of the administration and operation infrastructure to support three racks.

##### Cluster

A cluster is a set of greater than one pod, up to a maximum of 12 pods. A cluster is a set of Hadoop nodes that share the same Network Node and management tools for operating the Hadoop environment.


 **Note:** Please see the *Dell | Cloudera Solution - Reference Architecture Guide* for more detailed information.

## Default Networks

The default networks are presented in the following table.

**Table 1: Default Networks**

Usage	Description	Default reserved vLAN tag	Tagged
<b>Management vLAN</b>	Used for administrative functions such as Crowbar node installation, TFTP booting, DHCP assignments,, system logs, backups, and other monitoring. There is only one vLAN set up for this function and it is spanned across the entire network.	100	Not tagged
<b>BMC vLAN</b>	Used for connecting to the BMC of each node.	100	Not tagged
<b>Production vLAN</b>	Used by the Hadoop system to handle traffic between all nodes for HDFS operations, MapReduce jobs, and other Hadoop traffic.	200	802.1q Tagged
<b>Edge vLANs</b>	Used for connections to devices external to the Hadoop cluster; these include externally visible services such as load balancers and web servers. Use one or many of these networks, dependent on the need to segregate traffic among groups of servers	300	802.1q Tagged

 **Note:** The admin and BMC networks are expected to be in the same L2 network.

### Layout

Due to the nature of Crowbar's network layout, addresses are assigned to a whole network based upon interface, Network Type (Production, Management, and External) and teaming type.

**Table 2: Master/Secondary (Admin) Name Nodes Network Connections**

Interface	Network Type	Teaming Type
<b>BMC</b>	Management LAN	Single
<b>LOM1</b>	Production LAN	Teamed
<b>LOM2</b>	Production LAN	Teamed
<b>Eth1</b>	Production LAN	Teamed
<b>Eth2</b>	Management LAN	Single

**Table 3: Edge Nodes Network Connections**

Interface	Network Type	Teaming Type
<b>BMC</b>	Management LAN	Single
<b>LOM1</b>	Production LAN	Teamed 1
<b>LOM2</b>	Production LAN	Teamed 1
<b>Eth1</b>	Edge LAN	Teamed 2
<b>Eth2</b>	Edge LAN	Teamed 2



Table 4: Data Nodes Network Connections

Interface	Network Type	Teaming Type
BMC	Management LAN	Single
LOM1	Production LAN	Teamed 1
LOM2	Production LAN	Teamed 1

### IP Addressing

The IP address can be assigned in this fashion, using large subnets to support many machines on the production network. The management network is a Class C network with 254 IP addresses. The Production network is what is known as a /23 with 512 IP addresses. In each network, the first 10 IP addresses are reserved for switches, routers, and firewalls.


 **Note:** Each network's ".1" address is reserved for the network gateway.

Table 5: IP Addressing Schema

LAN	Network	Subnet	Gateway	Reserved
Management LAN	172.16.0.0	255.255.255.0	172.16.0.1	0.1 – 0.10
Production LAN	172.16.2.0	255.255.254.0	172.16.2.1	2.1-2.20
Name Nodes	DHCP Allocated			
Data Nodes	DHCP Allocated			
External LAN	TBD by Customer			

### Rack Awareness

With the network set up using Top of Rack (ToR) switches, Rack Awareness can be programmed using the Chef information about which switch the LOM1 is plugged into. A simple script has been added to the Hadoop configuration to pull the information out of Chef, and then use it for Rack Awareness.

Table 6: Pod 1 IP Example Addressing Layout

**Network: 172.16.0.0** Netmask: 255.255.252.0

**Multicast: 172.16.0.0** Broadcast 172.16.3.255

Pod	Rack Number	Network	Server Type	IP Range	Subnet Mask	Gateway
1	1	Production	Data Node	172.16.0.1-42	255.255.252.0	172.16.0.1
1	2	Production	Data Node	172.16.1. 1-42	255.255.252.0	172.16.0.1
1	3	Production	Data Node	172.16.2. 1-42	255.255.252.0	172.16.0.1
1		Production	Master Name Node	172.16.3.1-19	255.255.252.0	172.16.0.1
1		Production	Secondary Name Node	172.16.3.20-30	255.255.252.0	172.16.0.1
1		Production	Edge Node	172.16.3.41-50	255.255.252.0	172.16.0.1
1	1	BMC	Data Node	172.16.0.200-242	255.255.252.0	172.16.0.1
1	2	BMC	Data Node	172.16.1.200-242	255.255.252.0	172.16.0.1
1	3	BMC	Data Node	172.16.2.200.242	255.255.252.0	172.16.0.1
1		BMC	Master Name Node	172.16.3.201-219	255.255.252.0	172.16.0.1
1		BMC	Secondary Name Node	172.16.3.220-230	255.255.252.0	172.16.0.1
1		BMC	Edge Node	172.16.3.231-250	255.255.252.0	172.16.0.1

Table 7: Pod 2 IP Example Addressing Layout

<b>Network: 172.16.0.0</b>	Netmask: 255.255.252.0
<b>Multicast: 172.16.0.0</b>	Broadcast: 172.16.3.255

Pod	Rack Number	Network	Server Type	IP Range	Subnet Mask	Gateway
2	1	Production	Data Node	172.16.4.1-42	255.255.252.0	172.16.4.1
2	2	Production	Data Node	172.16.5. 1-42	255.255.252.0	172.16.4.1
2	3	Production	Data Node	172.16.6. 1-42	255.255.252.0	172.16.4.1
2		Production	Master Name Node	172.16.7.1-19	255.255.252.0	172.16.4.1
2		Production	Secondary Name Node	172.16.7.20-30	255.255.252.0	172.16.4.1
2		Production	Edge Node	172.16.7.41-50	255.255.252.0	172.16.4.1
2	1	BMC	Data Node	172.16.4.200-242	255.255.252.0	172.16.4.1
2	2	BMC	Data Node	172.16.5.200-242	255.255.252.0	172.16.4.1
2	3	BMC	Data Node	172.16.6.200-242	255.255.252.0	172.16.4.1
2		BMC	Master Name Node	172.16.7.201-219	255.255.252.0	172.16.4.1
2		BMC	Secondary Name Node	172.16.7.220-230	255.255.252.0	172.16.4.1
2		BMC	Edge Node	172.16.7.231-250	255.255.252.0	172.16.4.1
2		External	Edge Node	TBD by Customer	TBD	TBD

## Hadoop Basics

The Hadoop software library is a framework that allows for the distributed processing of large data sets across clusters of computers using a simple programmatic driven processing model. Hadoop is designed to scale up from a minimum of three servers to thousands of machines, each offering local computation and storage.


Rather than rely on hardware to deliver high-availability, the Hadoop library itself is designed to detect and handle failures at the application layer, so delivering a highly-available service on a cluster of computers, each of which may be prone to failures.

Hadoop is ideal for organizations with a growing need to store and process massive application datasets. It enables applications to work with thousands of nodes and petabytes of data.

- **Hadoop Core:** The common libraries and utilities that provide the basic Hadoop runtime environment. A set of components and interfaces which implement a distributed filesystem and provide general I/O access for the Hadoop framework (serialization, Java RPC and persistent data storage).
- **Hadoop Distributed File System (HDFS):** A distributed file system that provides redundant, high-throughput access to application data.
- **MapReduce:** A software framework for distributed processing of large data sets on compute clusters.

## Apache Hadoop Component Deployment

For Hadoop (Cloudera Manager) and Eco-System components (Sqoop and Pig), employ Crowbar tools to construct a starting proposal and then edit any parameters to fit the specific needs of your environment. Once the proposal is ready, apply the proposal to deploy each system components.

 **Note:** The Base Hadoop system (HDFS and Map Reduce), Zookeeper, HBase, Oozie, Hive, and Hue are deployed using the Cloudera Manager administration console. Crowbar also provided some supplemental Hadoop Ecosystem Barclamps (Sqoop and Pig) and you must install the base Hadoop system (HDFS and Map Reduce) using Cloudera Manager before deploying any of these add-ons.


**Table 8: Supported Apache Hadoop Components**

Component	Deployment Method	Description
<b>Hadoop Core (HDFS/Map Reduce)</b>	Cloudera Manager	Common libraries and utilities that provides the basic Hadoop runtime environment (HDFS/map reduce), a set of components and interfaces which implements a distributed filesystem and provides general i/o access for the Hadoop framework (serialization, Java RPC and persistent data storage).
<b>HUE</b>	Cloudera Manager	HUE (Hadoop User Experience) is a user interface framework and SDK platform for visual Hadoop applications. It delivers a suite of web base UI applications which can be used to access and modify the Hadoop Distributed File System (HDFS) and Map Reduce job queue. HUE provides UI application portals for HDFS file browsing, Map/Reduce job control, user account administration and web based on-line help.
<b>HBase</b>	Cloudera Manager	HBase is an open-source, non-relational, distributed database modeled after Google's BigTable and is written in Java. It is developed as part of Apache Software Foundation's Apache Hadoop project and runs on top of HDFS (Hadoop Distributed Filesystem), providing BigTable-like capabilities for Hadoop. That is, it provides a fault-tolerant way of storing large quantities of sparse data. HBase features compression, in-memory operation, and Bloom filters on a per-column basis as outlined in the original BigTable paper. Tables in HBase can serve as the input and output for MapReduce jobs run in Hadoop, and may be accessed through the Java API but also through REST, Avro or Thrift gateway APIs. HBase is not a direct replacement for a classic SQL Database, although recently its performance has improved, and it is now serving several data-driven websites, including Facebook's Messaging Platform.
<b>ZooKeeper</b>	Cloudera Manager	High-performance coordination service for distributed applications. ZooKeeper provides primitives such as distributed locks which can be used for building large scale distributed processing applications.
<b>Oozie</b>	Cloudera Manager	Oozie is an open-source workflow/coordination service to manage data processing jobs for Apache Hadoop™. It is an extensible, scalable and data-aware service to orchestrate dependencies between jobs running on Hadoop (including HDFS, Pig and MapReduce).
<b>Hive</b>	Cloudera Manager	Data warehouse infrastructure that provides SQL based data summarization and ad-hoc querying.
<b>Pig</b>	Crowbar Barclamp	Platform for analyzing large data sets that consists of a high-level language for expressing data algorithms.
<b>Sqoop</b>	Crowbar Barclamp	SQL based command-line tool to assist with HDFS data import/export (SQL-to-Hadoop).

For more information about Hadoop, please visit <http://hadoop.apache.org/>.


## Crowbar User Interface

Crowbar is delivered as a Web application available on the admin node using HTTP on port 3000. By default, you can access it using <http://192.168.124.10:3000>. Additionally, the default installation contains an implementation of Hadoop specific components (see table below).

 **Note:** Dell supports running Crowbar on the following browsers: Firefox 3.6, Firefox 11, Google Chrome, Internet Explorer 8, and Internet Explorer 9. HTML5 compatibility and a minimum screen resolution of 1024x768 are recommended.

**Table 9: User Interface Service URLs**

User Interface Service	Default Location	Port	Example URL
<b>Crowbar</b>	Crowbar Admin Node	3000	http://<crowbar_admin_node>:3000
<b>Cloudera Manager</b>	Hadoop Edge Node	7180	http://<cloudera_manager_server_node>:7180
<b>Hadoop Name Node</b>	Hadoop Name Node	50070	http://<master_name_node>:50070
<b>Hadoop Secondary Name Node</b>	Hadoop Secondary Name Node	50090	http://<secondary_name_node>:50090
<b>Hadoop Data Node</b>	Hadoop Data Node	50075	http://<data_node>: 50075
<b>Hadoop Job Tracker Web</b>	Hadoop Job Tracker Node	50030	http://<job_tracker_node>: 50030
<b>Hadoop Task Tracker Web</b>	Task Tracker Node	50060	http://<task_tracker_node>:50060

 **Note:** The crowbar admin node IP address (192.168.124.10) is the default address. Replace it with the address assigned to the Crowbar Admin node. Nagios, Ganglia and Chef can be accessed directly from a web browser or via selecting one of the links on the Crowbar Dashboard.

---

## Cloudera Manager Overview

Cloudera Manager deploys and centrally operates a complete Hadoop stack. The application automates the installation process, reducing deployment time from weeks to minutes, gives you a cluster-wide, real time view of the services running and the status of their hosts, provides a single, central place to enact configuration changes across your cluster; and incorporates a full range of reporting and diagnostic tools to help you optimize cluster performance and utilization. Cloudera Manager provides full lifecycle management for Hadoop deployments.

### Functionality Outline

- Installs the complete Hadoop stack in minutes via a wizard-based interface.
- Gives you complete, end-to-end visibility and control over your Hadoop cluster from a single interface.
- Lets you set server roles and configure services across the cluster.
- Lets you gracefully start, stop and restart of services as needed.
- Shows information pertaining to hosts in your cluster including status, resident memory, virtual memory and roles.

Table 10: Differences between Cloudera Manager Free Edition and Cloudera Manager

Feature	Cloudera Manager Free Edition	Cloudera Manager
Max number of hosts supported	50	Unlimited
Automated installer	✓	✓
Host Monitoring	✓	✓
Secure communication between server and agents (TLS)	✓	✓
Service and Configuration Management	✓	✓
Manage HDFS, MapReduce, HBase, Hue, Oozie, and Zookeeper	✓	✓
Configuration audit trails	✓	✓
Workflows to start, stop, restart, add, delete, and decommission role instances	✓	✓
Configuration versioning and history	⚠	✓
Support for Kerberos	⚠	✓
Service Monitoring	⚠	✓
Status and health summary	⚠	✓
Proactive health tests	⚠	✓
Log Search and Management	⚠	✓
Events Management	⚠	✓
Alerts	⚠	✓
Activity Monitoring	⚠	✓
Operational Reports	⚠	✓
Global Time Control for historical diagnosis	⚠	✓
Support integration	⚠	✓

## Barclamps

 **Note:** Best practice is to reboot a node whenever a barclamp proposal is applied or updated.

Table 11: Barclamp Descriptions

Barclamp	Description
<b>Cloudera Manager</b>	Provides end-to-end management for apache Hadoop with the ability to deploy and centrally operate a complete Hadoop stack gives you a cluster wide, real time view of nodes and services running and provides a single central place to enact configuration changes across your cluster. Cloudera Manager incorporates a full range of reporting and diagnostic tools to help you optimize cluster performance and utilization.
<b>Hive</b>	Data warehouse infrastructure that provides SQL based data summarization and ad hoc querying.
<b>Pig</b>	Platform for analyzing large data sets that consists of a high-level language for expressing data algorithms.
<b>Sqoop</b>	SQL based command-line tool to assist with HDFS data import/export (SQL-to-Hadoop).
<b>ZooKeeper</b>	High-performance coordination service for distributed applications. ZooKeeper provides primitives such as distributed locks which can be used for building large scale distributed processing applications.

## Cloudera Manager Barclamp

The Cloudera Manager Barclamp performs all the low level operating system configuration setup for the Hadoop cluster and installs the Cloudera Manager server setup in order to prepare for Hadoop cluster deployment.

**Table 12: Barclamp Parameters**

Name	Description	Required	Default
<b>Log Debug Messages</b>	Enable log debug messages (/var/log/chef/client.log).	true	false

**Table 13: Operating System Parameters**

Name	Description	Required	Default
<b>File System Type</b>	File system type (ext3/ext4).	true	ext4
<b>Map/Reduce File Handles</b>	Maximum number of Map/Reduce open file handles.	true	32768
<b>HDFS File Handles</b>	Maximum number of HDFS open file handles.	true	32768
<b>HBASE File Handles</b>	Maximum number of HBASE open file handles.	true	32768

**Table 14: Hadoop High Availability Parameters (Shared storage using NFS)**

Name	Description	Required	Default
<b>Shared Edits Directory</b>	Specifies the HA shared edits directory.	true	/dfs/ha
<b>Shared Edits Export Options</b>	Specifies the HA shared edits export options.	true	rw,async,no_root_squash,no_subtree_check
<b>Shared Edits Mount Options</b>	Specifies the HA shared edits mount options.	true	rsz=65536,wsz=65536,intr,soft,bg

## Cloudera Manager Installation Overview

After the Cloudera Manager Barclamp has been deployed from Crowbar, you must run the Cloudera Manager configuration wizard in order to fully deploy the Hadoop cluster. This operation will perform the following tasks:

- Using SSH, discover the cluster hosts you specify via IP address ranges or hostnames.
- Install the Cloudera Manager Agent and CDH4 (including Hue) on the cluster data nodes.
- Configures the package repositories for Cloudera Manager, CDH4 and the Oracle JDK.
- Allow you to select and configure optional Hadoop eco-system components.
- Determine mapping of services to host.
- Suggest a Hadoop configuration and automatically starts the Hadoop services.

You can choose to abort the Cloudera Manager Agent and CDH installation process; the Cloudera Manager wizard will automatically revert and completely rollback the installation process for any uninstalled components. Installed components are not uninstalled during an abort.

## Cloudera Manager Node Inventory Page

Once the Cloudera barclamp has been deployed, from the Edit Proposal page, there is a link below the Proposal Attributes section called "Cloudera Manager Nodes." Clicking on this link will display a page titled "Cloudera Node Inventory." This screen is pictured in the figure below. You may print this page as it will be very useful during the Cloudera Manager installation to ensure the correct nodes are selected for their intended Cloudera Manager roles.

Figure 1: Node Inventory Screen

The screenshot shows the Crowbar Node Inventory screen. At the top, there's a navigation bar with links: Nodes, Network, Barclamps, Utilities, EULA, and Help. Below the navigation bar, the title "Node Inventory" is displayed with an "Export to CSV" button. The screen is divided into several sections, each containing a table of node information.

Cloudera Manager Server Node				
IP Address	Name	CPU	RAM	Drives
192.168.124.82	d00-0c-29-e5-d0-09.dale.org	Intel(R) Core(TM) i7-2960XM CPU @ 2.70GHz	2.94 GB	2

Name Nodes				
IP Address	Name	CPU	RAM	Drives
192.168.124.81	d00-0c-29-55-ac-c6.dale.org	Intel(R) Core(TM) i7-2960XM CPU @ 2.70GHz	2.94 GB	2
192.168.124.82	d00-0c-29-e5-d0-09.dale.org	Intel(R) Core(TM) i7-2960XM CPU @ 2.70GHz	2.94 GB	2

Data Nodes				
IP Address	Name	CPU	RAM	Drives
192.168.124.85	d00-0c-29-10-dd-37.dale.org	Intel(R) Core(TM) i7-2960XM CPU @ 2.70GHz	2.94 GB	2
192.168.124.84	d00-0c-29-dc-23-e5.dale.org	Intel(R) Core(TM) i7-2960XM CPU @ 2.70GHz	2.94 GB	2
192.168.124.86	d00-0c-29-f0-e6-1a.dale.org	Intel(R) Core(TM) i7-2960XM CPU @ 2.70GHz	2.94 GB	2

Edge Nodes				
IP Address	Name	CPU	RAM	Drives
192.168.124.83	d00-0c-29-84-db-0d.dale.org	Intel(R) Core(TM) i7-2960XM CPU @ 2.70GHz	2.94 GB	2

High Availability Journaling Nodes				
IP Address	Name	CPU	RAM	Drives
192.168.124.87	d00-0c-29-0b-6e-e0.dale.org	Intel(R) Core(TM) i7-2960XM CPU @ 2.70GHz	2.94 GB	2

High Availability Filer Nodes				
IP Address	Name	CPU	RAM	Drives
192.168.124.87	d00-0c-29-0b-6e-e0.dale.org	Intel(R) Core(TM) i7-2960XM CPU @ 2.70GHz	2.94 GB	2

At the bottom of the screen, it says "Provided by CloudEdge Solutions team - Version hadoop-2.2.cloudera-build.2443.redhat-6.2".

**Note:** You may also export this data to a comma separated value file by selecting the "Export to CSV" button at the top of the page.

## Cloudera Manager Administration Console

**Note:** Dell has tested running the Cloudera Manager Administration console on the following browsers: Firefox 3.6, Firefox 11, Google Chrome, Internet Explorer 8, and Internet Explorer 9.

To start the Cloudera Manager Administration Console:

- In a web browser, type the following URL: `http(s):// IP_ADDRESS: PORT_NUMBER`.
  - IP\_ADDRESS is the name or IP address of the host machine where the Cloudera Manager Web Server is installed.
  - PORT\_NUMBER is the default port number (7180).
  - Crowbar Installation defaults are Crowbar Admin Node on port 7180 (<http://192.168.124.10:7180>).
- Log into the Cloudera Manager Admin Console. The default login credentials are:


- Username: admin
- Password: admin
- You can also access the Cloudera Manager Administration Console from the Crowbar User Interface using the link located on the crowbar admin node view page (Cloudera Manager).

**Note:** For security, you should change the password for the default admin user account as soon as possible. This option from the Cloudera Manager application, under the Administration->Password tab.

### Login Screen

- Enter the user login name and password (default=admin, admin).
- If you want to save the password, enable the **Remember me on this computer** checkbox.
- Click the **Login** button to proceed.

Figure 2: Login Screen




### License Key Upload Screen

1. If you have obtained a Cloudera Manager License key and you wish to upgrade to the Cloudera Manager Enterprise Edition, you can enter the license key.
  - a. Click the **Browse** button and select the license key file.
  - b. Click the **Upload License and Upgrade to the Full Version** button to apply the license key.
  - c. Click the **Continue** Button to proceed after the license key has been applied.
2. If you wish to use the Cloudera Manager Free Edition, click the **Just Install the Latest Free Edition** button to proceed.



**Note:** Applying the license key is an optional step and you can always enter the license key later on in the process by clicking on the **welcome->admin** link in the Cloudera Manager user interface. This menu option is located at the top right side of the display.


Figure 3: License Key Upload Screen



### License Key Restart Screen

- Once the license key has been uploaded, the Cloudera Manager application will ask you to restart the Cloudera Manager server in order for it to take effect. You need to open an SSH console on the node which has the Cloudera Manager (*clouderamanager-server*) role applied to it (login=root/crowbar) and execute the following commands:
  - `cd /etc/init.d`
  - `sudo service cloudera-scm-server restart`
- Once the Cloudera manager server has been restarted, you need to log back into the Cloudera Manager user Interface to proceed.

Figure 4: License Key Restart Screen




### License Key Confirmation Screen

If you have entered the Cloudera Manager License key, you will see this additional screen.

- Click the **Continue** Button to proceed.

Figure 5: License Key Confirmation Screen



### Node Search Screen

1. Enter the IP range or hostname search pattern for all Hadoop cluster nodes. Cloudera Manager will search the cluster using this pattern and will consider any node with a Cloudera Manager agent process running on it as a valid Hadoop node candidate. For example;
  - 192.168.124.[80-90] will attempt to discover all the nodes between 192.168.124.80 and 192.168.124.90
  - 192.168.124.8[1-3] will attempt to discover 192.168.124.81, 192.168.124.82, and 192.168.124.83
  - For additional information on Cloudera Manager search patterns, see the **search for hostnames and/or IP addresses using patterns** link on the Cloudera Manager user interface.
2. Optionally, enter the host's **SSH Port**. The default port is 22.
3. Click the **Search** button to proceed.


Figure 6: Cloudera Cluster Node Search Screen

The screenshot shows the Cloudera Manager web interface for specifying hosts. The browser tabs include 'Crowbar: index', '192.168.124.10:3000/dell\_c', and 'Specify hosts for your CDH'. The address bar shows '192.168.124.84:7180/cmf/express-wizard/hosts'. The page has a dark header with 'cloudera MANAGER' and navigation links like 'Support', 'Help', and 'admin'. The main content area is titled 'Specify hosts for your CDH cluster installation.' Below this is a light blue hint box: 'Hint: Search for hostnames and/or IP addresses using [patterns](#).' A large text input field contains the pattern '192.168.124.[80-90]'. To the right of this field is an 'SSH Port' label, a text input field with the value '22', and a blue 'Search' button. At the bottom of the form, there are two buttons: a 'Back' button and a blue 'Continue' button.

## Node Search Results Screen

1. Verify that all your Hadoop nodes have been discovered.
2. Make any cluster configuration adjustments by selecting or deselecting any checkboxes.
3. Click the **Continue** button to proceed.

Figure 7: Node Search Results Screen




### Select Repository Screen

- Select **Use Packages** as the installation method.

 **Note:** The Dell | Cloudera Solution includes built-in software repositories, accessible via Packages instead of the default Cloudera "parcels". This enables you to install the software without Internet access.


Figure 8: Select Repository Screen



The Select Repository screen expands to display configuration choices.

### Repository Configuration Screen

1. Select **CDH4** for installation.
2. Select **Custom Repository** for CDH.
  - Enter this URL - <http://192.168.124.10:8091/redhat-6.2/crowbar-extra/clouderamanager>
3. Select **None** for Impala installation.
  - Or, to install Impala, select **Custom Repository** for Impala.
  - Enter this URL - <http://192.168.124.10:8091/redhat-6.2/crowbar-extra/clouderamanager>
4. Select **Custom Repository** for Cloudera Manager.
  - Enter this URL - <http://192.168.124.10:8091/redhat-6.2/crowbar-extra/clouderamanager>
5. Leave the GPG Key URL field empty.
6. Click the **Continue** button to proceed.


 **Note:** RPM based packages are served from the crowbar admin node. By default, the IP address is 192.168.124.10 on port 8091 (http:// 192.168.124.10:8091). If you configure the crowbar admin node to be on another IP address, you will have to make the appropriate adjustments to the URLs listed above.

 **Note:** Impala is a Cloudera beta product; as such, Dell does not provide support for Impala. You can find Cloudera's Impala documentation at <https://ccp.cloudera.com/display/IMPALA10BETADOC/Cloudera+Impala+1.0+Beta+Documentation>.

Cloudera Impala™ enables you to perform fast SQL queries upon HDFS or HBase-stored Apache Hadoop data. It uses the same ODBC driver, SQL (Hive SQL) syntax, storage infrastructure, and user interface as Apache Hive. Impala is not a replacement for MapReduce-based batch processing frameworks.

You must point the *Custom Repository for Impala* to Cloudera's corresponding repository in order to download Impala. See [Repository Configuration Screen](#) above. Cloudera Manager must be installed and operational upon a node with Internet access in order for Impala to function. Cloudera currently supports Impala running on Red Hat Enterprise Linux (RHEL)/CentOS 6.2 (64-bit) platforms only.

Figure 9: Repository Configuration Screen



Cluster Installation - Cloudera

192.168.124.83:7180/cm/express-wizard/wizard

☒ Use Packages ⓘ  
☐ Use Parcels (Recommended) ⓘ

**Select the version of CDH**

☒ CDH4  
☐ CDH3

**Select the specific release of CDH you want to install on your hosts.**

☐ Latest Release of CDH4  
☐ CDH 4.2.0  
☐ CDH 4.1.3  
☐ CDH 4.1.2  
☐ CDH 4.1.1  
☐ CDH 4.1.0  
☐ CDH 4.0.1  
☐ CDH 4.0.0  
☒ Custom Repository

Example for SLES, Redhat or other RPM based distributions:  
`http://archive.cloudera.com/cdh4/redhat/5/x86_64/cdh/4/`

Example for Ubuntu or other Debian based distributions:  
`deb http://archive.cloudera.com/cdh4/ubuntu/lucid/amd64/cdh/ lucid-cdh4 contrib`

**Select the specific release of Impala you want to install on your hosts.**

☐ Latest Release of Impala  
☒ Custom Repository  
☐ None

**Note:** Impala is supported only on CDH 4.2 or later deployments.

**Select the specific release of the Cloudera Manager Agent you want to install on your hosts.**

☐ Matched release for this Cloudera Manager server  
☒ Custom Repository

Back 1 2 3 4 5 Continue

Crowbar nodes.htm Show all downloads...



### SSH Credentials Screen

1. Select **Login to all hosts as root**.
2. Select **All hosts accept same password**.
3. Enter the SSH login password for the cluster (default=crowbar).
4. Accept the default settings for the **SSH port** and **number of simultaneous installations**.
5. Click the **Continue** button to proceed.

Figure 10: SSH Credentials Screen

The screenshot shows the Cloudera Manager web interface for the 'Cluster Installation' wizard. The browser address bar shows the URL '192.168.124.84:7180/cmf/express-wizard/wizard#step=hostCredentialsStep'. The page title is 'cloudera MANAGER'. The main heading is 'Cluster Installation'. Below it, the instruction 'Provide SSH login credentials.' is displayed. A text block explains that root access is required for installing Cloudera packages and that the installer will connect via SSH, logging in as root or another user. The 'Login to all hosts as:' section has two radio buttons: 'root' (selected) and 'Another User:'. The 'Authentication Method:' section has two radio buttons: 'All hosts accept same password' (selected) and 'All hosts accept same private key'. There are two password input fields labeled 'Enter Password:' and 'Confirm Password:', both containing six dots. The 'SSH Port:' is set to '22'. The 'Number of simultaneous installations:' is set to '10', with a note below it stating '(Running a large number of installations at once can consume large amounts of network bandwidth and other system resources)'. At the bottom, there is a 'Back' button, a progress indicator with five steps (step 2 is highlighted), and a 'Continue' button.

Cluster Installation

Provide SSH login credentials.

Root access to your hosts is required to install the Cloudera packages. This installer will connect to your hosts via SSH and log in either directly as root or as another user with password-less sudo privileges to become root.

Login to all hosts as: ☒ root ☐ Another User:

You may connect via password or public-key authentication for the user selected above.

Authentication Method: ☒ All hosts accept same password ☐ All hosts accept same private key

Enter Password:

Confirm Password:

SSH Port:

Number of simultaneous installations:   
(Running a large number of installations at once can consume large amounts of network bandwidth and other system resources)


Back 1 2 3 4 5 Continue

Package Install Screen

You will see bar graphs next to each node and the name of the package it is installing.

- 1. Wait for the installation process to complete.
- 2. Click the **Continue** button to proceed.

Figure 11: Package Install Screen




## Host Inspector Screen

The Cloudera Manager Host Inspector runs during this part of the installation process in order to validate the proper cluster configuration for the Hadoop installation.


1. Wait for this process to complete.
2. Click the **Run Again** button if you want to run the Host Inspector again.
3. Click the **Continue** button to proceed.

Figure 12: Host Inspector Screen



## Service Selection Screen


1. Select the services that you want to install.
  - **Core Hadoop** – includes HDFS, MapReduce, Oozie, Hive, and Hue
  - **Core with Real-Time Delivery** – Includes HDFS, MapReduce, ZooKeeper, HBase, Oozie, Hive, and Hue
  - **Core with Real-Time Query (Beta)** – Includes HDFS, MapReduce, Impala, Oozie, Hive, and Hue
  - **All Services** – Includes HDFS, MapReduce, ZooKeeper, HBase, Impala, Oozie, Hive, and Hue
  - **Custom Services** – Select only the services that you want
  - **Cloudera Navigator** – A separately-licensed suite of management services

 **Note:** If you select anything other than *All Services*, you can optionally add additional services in the future.

2. If you select *Cloudera Navigator*, first ensure that you have purchased the required licenses. Cloudera Navigator is a separately-licensed feature. Please contact your Dell representative for more information.
3. Click the **Inspect Role Assignments** button to configure the Hadoop cluster services.

**Important:** *Do not* select *Continue*, as this will give you the default role assignments, which may not be acceptable to you.

Figure 13: Service Selection Screen



## Inspect Role Assignments Screen # 1

1. Select the Cloudera Manager role assignments for Hadoop cluster deployment.

Recommended settings for the Dell Reference Architecture:

- **CM DataNode** – Crowbar nodes which contains the *clouderamanager-datanode* role.
- **CM NameNode** – 1<sup>st</sup> Crowbar node which contains the *clouderamanager-namenode* role.
- **CM SecondaryNameNode** – 2<sup>nd</sup> Crowbar node which contains the *clouderamanager-namenode* role.
- **CM TaskTracker roles** – Crowbar nodes which contains the *clouderamanager-datanode* role.
- **CM JobTracker role** – Crowbar node which contains the *clouderamanager-namenode* role.
- **Cloudera Management Service roles** – Crowbar node which contains the *clouderamanager-server* role.

2. Please refer to Figure 15: Inspect Role Assignments Screen #2, before clicking the **Continue** button.



 **Note:** The Cloudera Node Inventory page you printed from within the Cloudera Manager barclamp page in Crowbar is very useful for this step to ensure the roles selected in Cloudera Manager are assigned to nodes which have been provisioned (RAID, BIOS, etc.) specifically for that purpose.

Figure 14: Inspect Role Assignments Screen # 1



**Inspect role assignments**

You can customize the role assignments for your new cluster here, but note that if assignments are made incorrectly, such as assigning too many roles to a single host, this can significantly impact the performance of your services. Cloudera does not recommend altering assignments unless you have specific requirements, such as having pre-selected a specific host for a specific role.

The host list presented here is prefiltered to remove hosts which are not valid candidates; these include hosts that are: unhealthy, members of other clusters, and/or which have an incompatible version of CDH installed on them.

	HDFS			MapReduce			Hive		
	DataNode <a href="#">All</a>   <a href="#">None</a>	NameNode	SecondaryNameNode	HttpFS <a href="#">All</a>   <a href="#">None</a>	TaskTracker <a href="#">All</a>   <a href="#">None</a>	JobTracker	Gateway <a href="#">All</a>   <a href="#">None</a>	Hive Metastore Server <a href="#">All</a>   <a href="#">None</a>	Hive Serve <a href="#">All</a>   <a href="#">None</a>
d00-0c-29-0b-6e-e0.dale.org	<input type="checkbox"/>	<input type="radio"/>	<input type="radio"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="radio"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
d00-0c-29-10-dd-37.dale.org	<input checked="" type="checkbox"/>	<input type="radio"/>	<input type="radio"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="radio"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
d00-0c-29-55-ac-c6.dale.org	<input type="checkbox"/>	<input checked="" type="radio"/>	<input type="radio"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="radio"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
d00-0c-29-84-db-0d.dale.org	<input type="checkbox"/>	<input type="radio"/>	<input type="radio"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="radio"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
d00-0c-29-dc-23-e5.dale.org	<input checked="" type="checkbox"/>	<input type="radio"/>	<input checked="" type="radio"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="radio"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
d00-0c-29-e5-d0-09.dale.org	<input type="checkbox"/>	<input type="radio"/>	<input type="radio"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="radio"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
d00-0c-29-f0-e6-1a.dale.org	<input checked="" type="checkbox"/>	<input type="radio"/>	<input type="radio"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="radio"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>


[Back](#) [Continue](#)

Inspect Role Assignments Screen # 2

If you entered the Cloudera Manager License key, you will see this additional screen.

- 1. Select the role assignments for Hadoop add-ons services and monitoring services (Activity Monitor, Service Monitor, Reports Manager, etc.). Dell suggests that you assign these roles to the Cloudera Manager Server Node.
- 2. Click the **Continue** button to proceed.

Figure 15: Inspect Role Assignments Screen #2



## Monitoring Database Setup Screen

If you entered the Cloudera Manager License key, you will see this additional screen.

1. Select **Use Embedded Database**.
2. You can leave the rest of the settings at default values unless you want to change them.
3. Click the **Test Connection** button to make sure you can connect to all the databases (required).
4. Click the **Continue** button to proceed.

Figure 16: Monitoring Database Setup Screen

**Database Setup**

On this page you configure and test database connections. If using custom databases, create the databases first according to the [Installing and Configuring an External Database](#) section of the [Installation Guide](#) .

When using the Embedded Database, passwords are auto generated. Please copy them down.

☒ Use Embedded Database  
☐ Use Custom Databases

---

**Hive**

Currently assigned to run on d00-0c-29-e5-d0-09.dale.org:7432

Database Host Name:	Database Type:	Database Name :	Username:	Password:
d00-0c-29-e5-d0-09.dale.org:7432	PostgreSQL	hive	hive	oxg6E9XSBL

**Service Monitor**

Currently assigned to run on d00-0c-29-e5-d0-09.dale.org:7432

Database Host Name:	Database Type:	Database Name :	Username:	Password:
d00-0c-29-e5-d0-09.dale.org:7432	PostgreSQL	smon	smon	TGhoZYzz5F

**Activity Monitor**

Currently assigned to run on d00-0c-29-e5-d0-09.dale.org:7432

Database Host Name:	Database Type:	Database Name :	Username:	Password:
d00-0c-29-e5-d0-09.dale.org:7432	PostgreSQL			

Back Test Connection Continue

## Review Configuration Changes Screen

If you entered the Cloudera Manager License key, you will see this additional screen.

1. If not set by default, set the Alert Publisher mail server hostname for alerts (*localhost*).
2. If not set by default, set the Alert Publisher mail server message recipients for alerts (*root@localhost*).
3. Click the **Continue** button to proceed.

Figure 17: Review Configuration Changes Screen

cloudera MANAGER

Review configuration changes

Set the following configuration values for your new role(s). Required values are marked with \*.

Group	Parameter	Recommended Value	Description
<b>Service hbase1</b>			
Service-Wide	HDFS Root Directory* hbase.rootdir	/hbase default value	The HDFS directory shared by HBase RegionServers.
<b>Service hdfs1</b>			
DataNode (Base) <a href="#">Show Members</a>	DataNode Data Directory* dfs.datanode.data.dir	<input type="text" value="/data/1/dfs/dn"/> <a href="#">Reset to empty default value</a>	Comma-delimited list of directories on the local file system where the DataNode stores HDFS block data. Typical values are /data/N/dfs/dn for N = 1, 2, 3... These directories should be mounted using the noatime option and the disks should be configured using JBOD. RAID is not recommended.
DataNode (Base) <a href="#">Show Members</a>	DataNode Failed Volumes Tolerated dfs.datanode.failed.volumes.tolerated	0 default value	The number of volumes that are allowed to fail before a DataNode stops offering service. By default, any volume failure will cause a DataNode to shutdown.
DataNode (1) <a href="#">Show Members</a>	DataNode Data Directory* dfs.datanode.data.dir	<input type="text" value="/data/1/dfs/dn"/> <a href="#">Reset to empty default value</a>	Comma-delimited list of directories on the local file system where the DataNode stores HDFS block data. Typical values are /data/N/dfs/dn for N = 1, 2, 3... These directories should be mounted using the noatime option and the


[Back](#) [Continue](#)



## Cluster Services Initialization Screen

1. Wait for the Hadoop cluster installation process to complete.
2. Click the **Continue** button to proceed.

Figure 18: Cluster Services Initialization Screen




### Configuration Completion Screen

If the Hadoop configuration steps complete successfully, you will see the final Cloudera Manager confirmation screen.

- Click the **Continue** button to start using Cloudera Manager.

**Figure 19: Configuration Completion Screen**




Service Display Screen

This is the normal startup screen after Cloudera Manager has completed the installation steps.

- Please refer to the *Cloudera Manager Users Guide* for additional information on operating Cloudera Manager.

Figure 20: Service Display Screen



## Pig Barclamp

Apache Pig is a platform for analyzing large data sets that consists of a high-level language for expressing data analysis programs, coupled with infrastructure for **evaluating** these programs. The salient property of Pig programs is that their structure is amenable to substantial parallelization, which in turns enables them to handle very large data sets.

Pig's infrastructure layer consists of a compiler that produces sequences of MapReduce programs, for which large-scale parallel implementations already exist (e.g., the Hadoop subproject). Pig's language layer currently consists of a textual language called Pig Latin, which has the following key properties:

- **Ease of programming:** It is trivial to achieve parallel execution of simple, "embarrassingly parallel" data analysis tasks. Complex tasks comprised of multiple interrelated data transformations are explicitly encoded as data flow sequences, making them easy to write, understand, and maintain.
- **Optimization opportunities:** The way in which tasks are encoded permits the system to optimize their execution automatically, allowing the user to focus on semantics rather than efficiency.
- **Extensibility:** Users can create their own functions to do special-purpose processing.

**Table 15: Pig Barclamp Parameters**

Name	Description	Required	Default
java_home	JAVA_HOME environment variable.	true	/usr/java/jdk1.6.0_31/jre
log4jconf	log4jconf log4j configuration file.	true	./conf/log4j.properties
brief	brief logging - no timestamps.	true	false
cluster	Clustername, name of the hadoop jobtracker. If no port is defined port 50020 will be used.	false	
debug_level	Debug level, INFO is default.	true	INFO
file	A file that contains pig script.	false	
jar	Load jarfile, colon separated.	false	
verbose	Verbose print all log messages to screen (default to print only INFO and above to screen).	true	false
exectype	Exectype local or mapreduce - mapreduce is default.	true	mapreduce
ssh_gateway	HOD gateway property.	false	
hod_expect_root	HOD expect root property.	false	
hod_expect_uselatest	HOD use latest root property.	false	
hod_command	HOD command root property.	false	
hod_config_dir	HOD config directory property.	false	
hod_param	HOD param property.	false	
pig_spill_size_threshold	Do not spill temp files smaller than this size (bytes).	true	5000000
pig_spill_gc_activation_size	EXPERIMENT: Activate garbage collection when spilling a file bigger than this size (bytes). This should help reduce the number of files being spilled.	true	40000000
log_file	Log file location.	false	

## Sqoop Barclamp

Sqoop is an SQL-based command-line tool to assist with HDFS data import/export (SQL-to-Hadoop). Sqoop is a tool designed to transfer data between Hadoop and relational databases. You can use Sqoop to import data from a relational database management system (RDBMS) such as MySQL or Oracle into the Hadoop Distributed File System (HDFS), transform the data in Hadoop MapReduce, and then export the data back into an RDBMS.

Sqoop automates most of this process by relying on the database to describe the schema for the data to be imported. Sqoop uses MapReduce to import and export the data, which provides parallel operation as well as fault tolerance.

**Table 16: Sqoop Barclamp Parameters**

Name	Description	Required	Default
<b>sqoop_connection_factories</b>	A comma-delimited list of ManagerFactory implementations which are consulted, in order, to instantiate ConnManager instances used to drive connections to databases.	false	
<b>sqoop_tool_plugins</b>	A comma-delimited list of ToolPlugin implementations which are consulted, in order, to register SqoopTool instances which allow third-party tools to be used.	false	
<b>sqoop_metastore_client_enable_autoconnect</b>	If true, Sqoop will connect to a local metastore for job management when no other metastore arguments are provided.	true	false
<b>sqoop_metastore_client_autoconnect_url</b>	The connect string to use when connecting to a job-management metastore. If unspecified, uses ~/.sqoop/. You can specify a different path here.	false	
<b>sqoop_metastore_client_autoconnect_username</b>	The username to bind to the metastore.	false	
<b>sqoop_metastore_client_autoconnect_password</b>	The password to bind to the metastore.	false	
<b>sqoop_metastore_client_record_password</b>	If true, allow saved passwords in the metastore.	false	
<b>sqoop_metastore_server_location</b>	Path to the shared metastore database files. If this is not set, it will be placed in ~/.sqoop/.	false	
<b>sqoop_metastore_server_port</b>	Port that this metastore should listen on.	false	

## Support

### Dell Support

To obtain Dell hardware and software support:

- Open a request at Dell's support portal: <http://support.dell.com>
- See a list of Dell Technical Support [call centers](#) near you

### Cloudera Support

To obtain support for Hadoop:

- Open a request at Cloudera's support portal: <http://www.cloudera.com/hadoop-support/>

## Appendix A: Dell | Hadoop Solution Components

---

- **Hadoop:** <http://en.wikipedia.org/wiki/Hadoop>.
- **Hadoop Distributed File System (HDFS):** A distributed file system that provides high-throughput access to application data ([http://en.wikipedia.org/wiki/Hadoop\\_Distributed\\_FileSystem#Hadoop\\_Distributed\\_File\\_System](http://en.wikipedia.org/wiki/Hadoop_Distributed_FileSystem#Hadoop_Distributed_File_System)).
- **MapReduce:** A software framework for distributed processing of large data sets on compute clusters (<http://en.wikipedia.org/wiki/MapReduce>).
- **HBase:** A scalable, distributed database that supports structured data storage for large tables.
- **Hive:** A data warehouse infrastructure that provides data summarization and ad-hoc querying.
- **ZooKeeper:** A high-performance coordination service for distributed applications.
- **Pig:** A platform for analyzing large data sets that consists of high-level language for expressing data analysis programs, coupled with infrastructure for evaluating these programs.
- **Sqoop:** A tool designed to import data from relational databases into Hadoop. Sqoop uses JDBC to connect to a database.
- **Oozie:** An open-source workflow engine and coordination service to manage data processing jobs within Hadoop.
- **Hue:** A browser based interface for interacting with Hadoop clusters.
- **Crowbar:** A Dell-provided, supported, and maintained toolset for system deployment and configuration automation. Crowbar supports the bare-metal bring-up of new hardware and configuration management of existing hardware.

## Appendix B: References

---

- Cloudera: <http://www.cloudera.com>
- Nagios: <http://www.nagios.org>
- Ganglia: <http://ganglia.sourceforge.net>

### To Learn More

For more information on the Dell | Cloudera Solution, visit:

[www.Dell.com/Hadoop](http://www.Dell.com/Hadoop)

©2013 Dell Inc. All rights reserved. Trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Specifications are correct at date of publication but are subject to availability or change without notice at any time. Dell and its affiliates cannot be responsible for errors or omissions in typography or photography. Dell's Terms and Conditions of Sales and Service apply and are available on request. Dell service offerings do not affect consumer's statutory rights.

Dell, the DELL logo, and the DELL badge, PowerConnect, and PowerVault are trademarks of Dell Inc.

**Printed in USA**