

NAMOSIM: a Robot Motion Planner for Navigation Among Movable Obstacles

David Brown^{1,4}, Jacques Saraydaryan^{1,3,4}, Benoit Renault^{1,2,4}, and Olivier Simonin^{1,2,4}

1 Inria, CHROMA Team 2 INSA Lyon 3 CPE Lyon 4 CITI Laboratory

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#)
- [Repository](#)
- [Archive](#)

Editor: [Open Journals](#)

Reviewers:

- [@openjournals](#)

Submitted: 01 January 1970

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).




Figure 1: A NAMOSIM scenario with one robot and two obstacles is visualized in RViz. The robot's plan is shown by the blue lines. The darker shade of blue indicates the part of the path involving an obstacle transfer. The empty rectangles indicate the planned obstacle placements. The social costmap is seen in the rainbow background.

Summary

NAMOSIM is a mobile robot motion planner designed for the problem of **Navigation Among Movable Obstacles (NAMO)**. The planner simulates robots navigating in 2D polygonal environments where certain obstacles can be grasped and relocated to enable robots to reach their goals. NAMOSIM thus extends the classic navigation problem with a layer of interactivity, posing interesting research questions while remaining well-defined and amenable to various algorithmic approaches. NAMOSIM is intended for researchers and developers working on robot navigation in dynamic environments, particularly where physical interaction is necessary.

NAMOSIM supports the development of custom NAMO algorithms using a modular agent-based architecture. It includes a baseline agent that implements Stilman's NAMO algorithm (Stilman & Kuffner, 2005) and also incorporates a communication-free coordination strategy for multi-robot scenarios (Renault et al., 2024). A variety of other agent behaviors are implemented, and new agents utilizing alternative approaches can be created and integrated

19 into the planner by implementing the **Agent** base class. NAMOSIM thus supports reproducible
20 research in single and multi-robot NAMO algorithms.

21 NAMOSIM is packaged as a ROS2 package for easy integration into robotics projects and can
22 also be used as a standalone Python module. It utilizes ROS2 messages for visualization of
23 environments, plans, and execution via RViz and includes several prebuilt scenarios for testing
24 and benchmarking. Scenarios are stored as SVG files, allowing the convenient creation of
25 custom scenarios using a free SVG editor such as Inkscape.

26 Statement of Need

27 Many interesting applications in autonomous mobile robotics involve some kind of physical
28 interaction with the environment as well as social coordination with other agents. However,
29 global navigation planners typically assume static, non-interactive environments, leaving higher-
30 level behaviors to other parts of the software stack and thus complicating their implementation
31 to some degree. Ideally, motion planners should be able to reason about physical and social
32 interactions, continuously update their internal state in response to incoming data, and adapt
33 to changing conditions. NAMOSIM takes a first step towards addressing this challenging
34 problem by offering a simulation environment explicitly designed to study NAMO problems,
35 which involve not only path planning but also reasoning about which obstacles to move,
36 where to move them, and how to combine standard navigation with obstacle manipulation.
37 Additionally, NAMOSIM supports multi-robot environments, facilitating reproducible research
38 in social navigation.

39 Major Features

40 NAMOSIM provides a robust set of features to support research and development in Navigation
41 Among Movable Obstacles (NAMO):

- 42 ■ **Modular Agent-Based Architecture:** The simulator is built around a flexible Agent inter-
43 face, allowing users to implement and test custom NAMO planning algorithms. A baseline
44 NAMO algorithm implementation is available for immediate use and benchmarking.
- 45 ■ **Support for Multiple Robot Models:** NAMOSIM supports both holonomic and differential-
46 drive robot models, enabling realistic simulation of various robotic platforms.
- 47 ■ **ROS2 Integration:** NAMOSIM forms a ROS2 package, enabling seamless integration
48 into simulated and physical robotics projects and visualization via RViz.
- 49 ■ **2D Environment Simulation:** The simulator provides a customizable 2D environment
50 where users can define static and movable obstacles, supporting complex scenarios for
51 testing multi-robot coordination strategies and NAMO algorithms.
- 52 ■ **Prebuilt Scenarios and Tests:** NAMOSIM includes several custom scenario files for
53 benchmarking and testing specific situations.
- 54 ■ **Multi-Robot Coordination:** The simulator supports multi-robot scenarios, and our
55 baseline agent implements a communication-free coordination strategy (Renault et al.,
56 2024).

57 These features make NAMOSIM a versatile tool for prototyping, evaluating, and deploying
58 NAMO algorithms in diverse robotic applications.

59 Customizable Scenarios

60 NAMOSIM environments, or **scenarios**, are stored in SVG format and can be edited using any
61 SVG editor, such as Inkscape. The scenario SVG file contains the following key elements:

- 62 ■ The geometry of the static map
- 63 ■ The polygons and orientations of all robots and movable obstacles

- 64 ■ Configuration settings that define the behavior of the environment and robots
- 65 The static map can also be included as an image layer within the SVG to conveniently
- 66 incorporate ROS grid-map images generated by standard mapping tools.

67 Architecture




Figure 2: NAMOSIM High-Level Architecture

68 At a high level, NAMOSIM executes a SENSE-THINK-ACT loop that performs the following
69 functions at each iteration:

- 70 1. **SENSE**: Each agent senses the environment and updates its internal representation.
- 71 2. **THINK**: Each agent computes a new plan or updates its current plan.
- 72 3. **ACT**: Each agent selects a single discrete action to execute.

73 The loop is expected to execute at a regular frequency, with the assumption that all agent
74 functions run sequentially in a synchronized manner.

75 Stilman's NAMO Algorithm

76 NAMOSIM includes a baseline implementation of Stilman's 2005 NAMO algorithm (Stilman
77 & Kuffner, 2005). The key idea of this algorithm is to move obstacles to merge disjoint
78 components of the robot's free configuration space. The map is divided into a set of disjoint
79 **connected components**, where each grid cell in a given component is reachable from all other
80 cells in the same component. It can be proven that components are separated by movable
81 obstacles or are otherwise unreachable. The algorithm functions by moving obstacles to join
82 components until the robot's current component includes the goal cell.

83 The algorithm works by recursively performing the following two stages:

- 84 1. **SELECT_OBSTACLE_AND_COMPONENT**: The first stage performs a simplified
85 A* grid search, allowing the agent to pass through movable obstacles. It returns the ID
86 of the first movable obstacle encountered on the optimal path to the goal and the ID of
87 the component encountered after passing through the obstacle.
- 88 2. **OBSTACLE_MANIPULATION_SEARCH**: The second stage finds a **transit path**
89 from the robot's current position to a grasp pose near the obstacle. Then, it finds a
90 **transfer path** by performing an obstacle manipulation search to join the robot's current
91 component to the component selected in stage 1. If this stage fails, the obstacle and
92 component pair are added to an avoid-list, and the algorithm returns to stage 1.

Each iteration of the algorithm continues with a copy of the environment where the robot and obstacle start from the poses resulting from the previous obstacle manipulation search. See also (Renault, 2023) for more details.

Collision Detection

Custom agents are free to implement their own collision detection routines; however, the baseline agent detects collisions using a simple binary-occupancy grid during transit paths (when not carrying an obstacle), assuming a circular robot footprint. When transporting a movable obstacle, the robot footprint is non-circular, and collision detection is based on the **convex swept volume** resulting from the area swept by the combined robot-obstacle footprint due to the action motion. Although computationally expensive, this ensures all possible collisions are detected, regardless of the shape of the robot or obstacle.

Social Costmap

A novel contribution in the baseline implementation is the option to use a social costmap during the obstacle manipulation search to guide obstacle placement decisions. This allows robots to place obstacles in areas less likely to block the free passage of other agents, including humans, reducing the likelihood that obstacles will need to be moved again. The key heuristic of the social costmap is to **avoid narrow corridors and central areas**, assigning higher costs to narrow corridors and the centers of open spaces. This helps robots avoid placing obstacles in front of doorways or in the center of rooms. The social costmap is explained in greater detail in (Renault et al., 2020; Renault, 2023).

Conflict Avoidance and Deadlock Resolution

NAMOSIM's baseline agent can avoid conflicts and resolve deadlocks with other agents. Conflict avoidance works by looking ahead along the agent's current plan for a fixed number of steps, called the **conflict horizon**. Within this horizon, the agent simulates each planned action and checks for potential conflicts. For example, the agent may have planned to move an obstacle that is no longer at the expected location, or another robot may be crossing the planned path within the conflict horizon, raising the potential for a collision.

The baseline agent avoids conflicts by either pausing or replanning around them. A **deadlock** is detected when the same conflict configuration is repeatedly encountered, even after replanning. To resolve deadlocks, the agent follows an evasion strategy which is optionally based on the local social costmap (Renault et al., 2024).

Acknowledgements

This research was supported by the Inria NAMOEX initiative.

References

- Renault, B. (2023). *Navigation among movable obstacles (NAMO) extended to social and multi-robot constraints* (PhD Thesis No. 2023ISAL0105, INSA Lyon). <https://hal.science/tel-04418723>
- Renault, B., Saraydaryan, J., Brown, D., & Simonin, O. (2024). Multi-robot navigation among movable obstacles: Implicit coordination to deal with conflicts and deadlocks. *IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 1–7. <https://hal.science/hal-04705395>

- 134 Renault, B., Saraydaryan, J., & Simonin, O. (2020). Modeling a social placement cost to
135 extend navigation among movable obstacles (NAMO) algorithms. *IEEE/RSJ International*
136 *Conference on Intelligent Robots and Systems (IROS)*, 11345–11351. [https://doi.org/10.](https://doi.org/10.1109/IROS45743.2020.9340892)
137 [1109/IROS45743.2020.9340892](https://doi.org/10.1109/IROS45743.2020.9340892)
- 138 Stilman, M., & Kuffner, J. J. (2005). Navigation among movable obstacles: Real-time
139 reasoning in complex environments. *International Journal of Humanoid Robotics*, 2(4),
140 479–503. <https://doi.org/10.1142/S0219843605000545>

DRAFT