Script Documentation

The document is a documentation for how scripts in The Guild 3 are set up and how functions work. It does not cover how-to's for modding computer games!

Official Website: https://theguildgame.com/

Official Discord: https://discord.gg/theguild

Structure of Scripts
- Example: PaintYourHome
- Hot Reload

Action Template Variable Details
- General
- UI
- ActionGUIData
- Illegal Actions/Guarding
- Sound
- Costs
- Target Selection
- DesiredProfiles
  - Evaluation Validity
- Results
  - ActivityResult
  - AI

Script Functions
- FunctionAffectServiceNeeds
- FunctionAffectNeeds
- FunctionApplyResults
- FunctionChangeCharacterState
- FunctionCreateLiaisonWithTarget
- FunctionCreateRomanceWithTarget
- FunctionDenyTradeProposal
- FunctionFocusActor
- FunctionFocusConversation
- FunctionRemoveForward
- FunctionAddForward
- FunctionGenerateEvidence
- FunctionGiveBirth
- FunctionGiveExperience
- FunctionGiveMoney
- FunctionKidnapTarget

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

FunctionKill
FunctionLookAt
FunctionMarryTarget
FunctionOpenUI
FunctionPickRandom
FunctionPlayRandomReaction
FunctionRegainConsciousness
FunctionRemoveEffect
FunctionRemoveTagsFromTradeMarkets
FunctionRemoveUnconsciousness
FunctionRestore
FunctionSelectActor
FunctionSendMessage
FunctionShowDeathUI
FunctionShowDynastyTradeRequest
FunctionShowSovereignResult
FunctionShowVoteResults
FunctionStartScene
FunctionTagEventTradeMarket
FunctionTrackObjectiveProgress
FunctionTransferEvidence
FunctionTransferItems
FunctionTransferMoney
FunctionTransferPrestige
FunctionTriggerAction
FunctionUpdateRelationship
FunctionForceBuildingClosure
FunctionUpdateGroupRelationship
FunctionAddUiNotice
FunctionRemoveUiNotice
FunctionEndAction
FunctionChainHostage
FunctionAddObjective
FunctionRemoveObjective
FunctionStopScriptEvent
FunctionShowBookOfPrisoners
FunctionReleaseFromJail
FunctionTransferMoneyToOfficeHolder
FunctionUnlockNobilityTitle

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

Structure of Scripts

You have 4 ways to make an action available in the game:
1. Include the action in the file GameplayDefault.oc under "Nobility" if the action should be unlocked by a title (use nobility title 0 if the action should be available from gamestart on).
2. Include the action in the file G3SkillsDefault.oc if it should be unlocked by a skill.
3. If the action should be unlocked by an artifact, then you have to unlock the action in the artifact item (see for example the item "Antidote" and the action "UseAntidote".
4. If the action should be available for everyone, then write the line "IsUnlockedAction = -1;" in the ActionGUIData of the action. The ActionsGUIData still checks if actors are allowed to use it.

The order of functions and properties is not relevant, with few exceptions:
- the order within filters (profiles) is relevant, because they are checked from top to bottom
- the order of functions with a Result is relevant, because they are executed from bottom to top

The example below shows a simple action that targets a building:

Example: PaintYourHome

```
"PaintYourHome" = G3ActionTemplate                    // internal name of the action
{
  GUIPresent = true;                                  // the action is displayed in the action bar
  UICategory = "Family";                              // category of the action in the action bar
  OrderIndex = 25;                                    // the position of the action in the action bar category

  ActionClassName = "SimpleExecutionAction";          // the class of the action
```

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

```
GUIData = array
{
  ActionGUIData                                   // begin of the filter for the actor
  {
    IsCharacter = 1;                              // actor must be a character
    IsFamilyMember = 1;                           // actor must be a member of a family/dynasty
    BelongsToOwnFamily = 1;                       // actor must belong to the player family
    IsAdult = 1;                                  // actor must be an adult
  }
};
UsableBy = array{ "$gui.item.UsableByAdultFamilyMembers" };        // usable by information shown in the tooltip

ActionActor = "Character";                        // the actor must be a character
TargetActor = "Building";                         // the target must be a building

SourceScoreFormula = "1.5 + Source.Intelligence";  // the formula for the actor
TargetScoreFormula = "Target.BuildingSecurity";    // the formula for the target

IconName = "PaintingTheHome";                     // the icon for the action; if left out the game will use an icon with the internal action name
ActionName = "PaintYourHome";                     // must be identical to the internal name
DisplayName = "$PaintYourHome";                   // display name of the action
Description = "$PaintYourHomeDesc";               // description of the action
Instruction = "$selectionPrompt.SelectResidence";  // instruction shown when player clicks the action

Duration = 0.0083;                                // duration, 1.0 = 24 hours
Cooldown = 0.05;                                  // cooldown, 1.0 = 24 hours
BaseRewardXP = 25;                                // XP reward if action is successful
CanFail = true;                                   // action can fail, so SourceScoreFormula and TargetScoreFormula are used
CriticalFactor = 0.9;                             // percentage chance of a critical success or critical failure (1 - CriticalFactor)

ShowSelectionPrompt = "UseTargetProfile";                  // show list of possible targets
```

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

```
SelectionPromptCallToAction = "$selectionPrompt.SelectResidence";          // text for list of possible targets
SelectionPromptNoTargetMessage = "$selectionPrompt.NoResidence";          // text when there is no valid target
HideSelectionPromptCancelButton = true;                                   // hide cancel button

TargetTags = array{"HasBeenPainted"};                        // array of tags to check in the DesiredProfiles
DesiredProfiles = array                                      // begin of the filter for the target
{
  TargetProfileBuilding                                      // first target profile for a building
  {
    MatchTargetTags = -3;                                    // none of the specified Tags must be active on the target building
    IncludedTypes = array{"CountryHouse", "PoorHouse", "CityHouse", "Mansion"};       // the building must be CountryHouse, PoorHouse, CityHouse or Mansion
    CloseToActor = 2;                                        // target should be close to the actor (relevant if actor is AI)
    Burning = -3;                                            // target must not burn
    FamilyProfile = TargetProfileFamily                      // profile of the building owner
    {
      MyFamily = 3;                                          // family of the actor
    };

    // Make sure the AutoSelect profile comes first, so it will be checked first!
    IsCurrentBuilding = 3;                                   // if the character is inside a building that matches, then…
    AutoSelect = true;                                       // … auto select this building
  },

  TargetProfileBuilding                                      // second target profile for a building
  {
    MatchTargetTags = -3;                                    // none of the specified Tags must be active on the target building
    IncludedTypes = array{"CountryHouse", "PoorHouse", "CityHouse", "Mansion"};       // the building must be CountryHouse, PoorHouse, CityHouse or Mansion
    CloseToActor = 2;                                        // target should be close to the actor (relevant if actor is AI)
    Burning = -3;                                            // target must not burn
    FamilyProfile = TargetProfileFamily                      // profile of the building owner
    {
```

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

```
        MyFamily = 3;                                   // family of the actor
      };
    };
  };

  TargetSnapPoint = TargetSnapPoint                     // aim for a snap point at the target building where the actor performs the action
  {
    Required = true;                                    // the snap point is required
    ShouldReserve = true;                               // the snap point should be reserved
    ShouldOccupy = true;                                // the snap point will be occupied

    Profiles = array                                    // filter for the snap point
    {
      TargetProfileSnapPoint{ Context = "Artefact"; },  // context of the snap point
    };
    Animations = array                                  // the animation the actor should play on the snap point
    {
      TargetSnapPointAnimation{ Animation = "ManipulateMiddle"; },      // name of the animation
    };
  };

  EnterBuilding = "TryEnter";                           // source should try to enter a building - note stepping on the outside area of a building means entering

  CriticalSuccessResult = array                         // result if CRITICAL SUCCESS
  {
    DisplayEffect                                       // adds a state information in the character or building panel bottom left
    {
      ApplyTo = "Target";                               // applied to the target
      Tags = array{"HasBeenPainted"};                   // adds a Tag to the target and combines the Tag with the DisplayEffect (important when the Tag is removed)
      DisplayGroup = "buffed";                          // the display group of the effect
      DisplayName = "$BuildingPaintedBuff";             // the name of the effect
```

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

```
    Duration = 1800.0;                          // IMPORTANT: this duration uses “ticks” (specified in GameplayDefault.oc with NormalYearTime
  },
  ModifierEffect                                // adds a modifier effect to the target
  {
    ApplyTo = "Target";                         // applied to the target
    Tags = array{"HasBeenPainted"};             // adds a Tag to the target and combines the Tag with the ModifierEffect (important when the Tag is removed)
    ActorValue = "Health";                      // affects the ActorValue “Health” of the target
    Mod = 50.0;                                 // the ActorValue is modified by 50
    Duration = 1800;                            // IMPORTANT: this duration uses “ticks” (specified in GameplayDefault.oc with NormalYearTime
    Recover = true;                             // the modification of the actor value is removed when the duration is up
  },
  FunctionTriggerAction                         // triggers an action
  {
    ApplyTo = "Source";                         // applied to the source
    Actions = array{"Exit"};                    // array of names of (randomly) the triggered actions (Exit let the character leave the current building)
  },
  FunctionTrackObjectiveProgress
  {
    ObjectiveTypename = "IncreaseSecurity";     // changes/satisfies the desire “IncreaseSecurity” of an AI dynasty
    Amount = 15;                                // by 15 points
  },
};

SuccessResult = array                           // result if SUCCESS
{
  DisplayEffect                                 // adds a state information in the character or building panel bottom left
  {
    ApplyTo = "Target";                         // applied to the target
    Tags = array{"HasBeenPainted"};             // adds a Tag to the target and combines the Tag with the DisplayEffect (important when the Tag is removed)
    DisplayGroup = "buffed";                    // the display group of the effect
    DisplayName = "$BuildingPaintedBuff";       // the name of the effect
```

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

```
    Duration = 1200.0;                          // IMPORTANT: this duration uses “ticks” (specified in GameplayDefault.oc with NormalYearTime
  },
  ModifierEffect                                // adds a modifier effect to the target
  {
    ApplyTo = "Target";                         // applied to the target
    Tags = array{"HasBeenPainted"};             // adds a Tag to the target and combines the Tag with the ModifierEffect (important when the Tag is removed)
    ActorValue = "Health";                      // affects the ActorValue “Health” of the target
    Mod = 25.0;                                 // the ActorValue is modified by 25
    Duration = 1200;                            // IMPORTANT: this duration uses “ticks” (specified in GameplayDefault.oc with NormalYearTime
    Recover = true;                             // the modification of the actor value is removed when the duration is up
  },
  FunctionTriggerAction                         // triggers an action
  {
    ApplyTo = "Source";                         // applied to the source
    Actions = array{"Exit"};                    // array of names of (randomly) the triggered actions (Exit let the character leave the current building)
  },
  FunctionTrackObjectiveProgress
  {
    ObjectiveTypename = "IncreaseSecurity";     // changes/satisfies the desire “IncreaseSecurity” of an AI dynasty
    Amount = 10;                                // by 10 points
  },
};

FailureResult = array                           // result if FAILURE
{
  DisplayEffect                                 // adds a state information in the character or building panel bottom left
  {
    ApplyTo = "Target";                         // applied to the target
    Tags = array{"HasBeenPainted"};             // adds a Tag to the target and combines the Tag with the DisplayEffect (important when the Tag is removed)
    DisplayGroup = "buffed";                    // the display group of the effect
    DisplayName = "$BuildingPaintedDebuff";     // the name of the effect
```

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

```
    Duration = 1200.0;                          // IMPORTANT: this duration uses “ticks” (specified in GameplayDefault.oc with NormalYearTime
  },
  ModifierEffect                                // adds a modifier effect to the target
  {
    ApplyTo = "Target";                         // applied to the target
    Tags = array{"HasBeenPainted"};             // adds a Tag to the target and combines the Tag with the ModifierEffect (important when the Tag is removed)
    ActorValue = "Health";                      // affects the ActorValue “Health” of the target
    Mod = -10.0;                                // the ActorValue is modified by -10
    Duration = 1200;                            // IMPORTANT: this duration uses “ticks” (specified in GameplayDefault.oc with NormalYearTime
    Recover = true;                             // the modification of the actor value is removed when the duration is up
  },
  FunctionTriggerAction                         // triggers an action
  {
    ApplyTo = "Source";                         // applied to the source
    Actions = array{"Exit"};                    // array of names of (randomly) the triggered actions (Exit let the character leave the current building)
  },
};

CriticalFailureResult = array                   // result if CRITICAL FAILURE
{
  DisplayEffect                                 // adds a state information in the character or building panel bottom left
  {
    ApplyTo = "Target";                         // applied to the target
    Tags = array{"HasBeenPainted"};             // adds a Tag to the target and combines the Tag with the DisplayEffect (important when the Tag is removed)
    DisplayGroup = "buffed";                    // the display group of the effect
    DisplayName = "$BuildingPaintedDebuff";     // the name of the effect
    Duration = 1800.0;                          // IMPORTANT: this duration uses “ticks” (specified in GameplayDefault.oc with NormalYearTime
  },
  ModifierEffect                                // adds a modifier effect to the target
  {
    ApplyTo = "Target";                         // applied to the target
```

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

```
      Tags = array{"HasBeenPainted"};          // adds a Tag to the target and combines the Tag with the ModifierEffect (important when the Tag is removed)
      ActorValue = "Health";                   // affects the ActorValue “Health” of the target
      Mod = -30.0;                             // the ActorValue is modified by -30
      Duration = 1800;                         // IMPORTANT: this duration uses “ticks” (specified in GameplayDefault.oc with NormalYearTime
      Recover = true;                          // the modification of the actor value is removed when the duration is up
    },
    FunctionTriggerAction                      // triggers an action
    {
      ApplyTo = "Source";                      // applied to the source
      Actions = array{"Exit"};                 // array of names of (randomly) the triggered actions (Exit let the character leave the current building)
    },
  };
};
```

Hot Reload

When running The Guild 3, all action scripts will be reloaded into the game once you have saved a file. However, this does not work for most other properties you may change, like settings in GameplayDefault.oc!

Action Template Variable Details

This is a complete list of all the variables that can be set. Variables that are required for an action to work are marked as **bold and red**.

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

General

Name	Type	Description	Default Value
ActionName	String	Internal name the code is referencing to, needs to be the same as the map entry string	
ActionActor	String	Type of the actor that executes the action, can either be ● "Character" if a Character should execute the action ● "Building" if a building should execute the action (ex. RepairBuilding) ● "Family" in special cases with special implementations like "BuyBusiness"	
TargetActor	String	Type of target the action expects, can be ● "Character" ● "Building" ● "Coordinate" - a certain spot on a street ● "Family" ● "AutomationParameters" - if the action itself has an implementation to pick a target (example: Tend to customers in healing businesses) ● Empty - If no TargetActor is set the Actor that executes the action will also be the target (Ex. DrinkHerbTea)	
SourceScoreForumla	String	Formula to calculate the dice roll value for the source of the action. The chance for success of the action is: Random(TargetScoreFormula, SourceScoreFormula) <= SourceScoreFormula Every attribute, state or tag and mathematical formulas can be used here. Examples: “Source.AttackPower + 1” It is also possible to include expressions for the target as well, e.g. “Source.AttackPower - Target.DefensePower”	
TargetScoreFormula	String	Formula to calculate the dice roll value for the target of the action. Same as SourceScoreFormula but with “Target.” in front of the expression. Examples: “Target.DefensePower + 1”	

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

Name	Type	Description	Default Value
Duration	float	Fraction of an ingame year for how long the action is supposed to take needs to be >= 0	0.0f
Cooldown	float	Fraction of an ingame year for how long the cooldown of the action should be. Needs to be >= 0	0.0f
EnterBuilding	String	Enter Building behavior for if the target is either a building or a character inside a building, can be ● "No" - don't enter ● "TryEnter" - enter building if you are allowed by the enter building rules to enter the building ● "ForceEnter" - always enter the building	No
RequiredBuildings	Array<String>	List of buildings where the action will be shown as assignable action in the building's production menu	
CanPerformShackled	bool	If true, the character will be able to perform the action even when they are shackled, example: in jail or kidnapped	false
CanBeCancelled	bool	If the action can be cancelled once started	true
AskConfirmationOnCancel	bool	If player needs to confirm when they want to cancel an active action	true
CanFail	bool	If true only SourceScoreForumla is rolled to decide if it will be a normal or critical success, but the action cannot fail	true
OnlyExecute	bool	If set true the character won't move to the target but immediately start executing the action	false
ShowCombatText	bool	If set true combat texts with the outcome will show over the source/target's heads	true
SourceRun	bool	If set true, the character will run towards the target, if set false the character will walk there	true
DistanceFromTarget	float	Character will try to get at least this close to the target of an action, if it is already closer, the action will start immediately	0.0f
DistanceFromTargetMin	float	If character is closer than this to their target they will move away from the target until they are at least DistanceFromTargetMin away from the target	0.0f

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

Name	Type	Description	Default Value
RestartAfterUnconsciousness	bool	if a action should be restarted if the character got knocked unconscious while executing the action	false
ResumeProgress	bool	If an action should resume where it left off after being interrupted by another character or if it should start at 0	false
InteractionPriority	int	priority for actions that start/interrupt interactions. Actions with higher priority can interrupt interactions with lower priority. (A bigger value means higher priority. See constants MAX_INTERACTION_PRIORITY and MIN_INTERACTION_PRIORITY)	0

UI

Name	Type	Description	Default Value
DisplayName	String	Localization Key for the name of the action that should be shown to the player	
Description	String	Localization key for the description in the action tooltip shown to the player	
IconName	String	The name of the icon for the action	
Instruction	String	Localization key for the call to action that is shown to the player if they hover over an invalid target	
GUIData	Array<ActionGUIData>	Set of rules for which actors the action is available/shown in the actionbar. **For details about the variety of options and how they work, see ActionGUIData**	

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

Name	Type	Description	Default Value
UICategory	String	Category in which the action should be sorted in to, can be · "Urgent" · "Business" · "Fighting" · "Rogue" · "Covert" · "Family" · "Diplomacy" · "SecretSociety" · "Building" · "Artifact" ● Empty - action will be directly in the action bar, left to the first UI category, try to avoid this	
OrderIndex	Int	Order of actions within the same category, actions are ordered from highest to lowest number	max Int
GUIPresent	bool	If the action should be shown in the action bar at all, set true for actions that should only be executed by AI/Neutral citizens	true
ShowSelectionPrompt	bool	If set true player will see a list of preselected "good" targets for the action	false
CanPickFromWorld	bool	If set true the selection prompt will have a "Pick from world" button so the player can choose to pick their own target	true
HideSelectionPromptCancelButton	bool	If set true, the selection prompt list won't have a "cancel" button	false
SelectionPromptCallToAction	String	Localization key for the message shown as call to action in the selection prompt list	
SelectionPromptNoTargetMessage	String	Localization key for the message shown if no valid targets are found for a selection prompt list	

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

Name	Type	Description	Default Value
ConfirmExecution	bool	If set true, the player will need to confirm if they really want to execute the action, even if it doesn't cost anything	false
CharacterState	Array<String>	If set, action will only be shown if the character is in a certain state, for example "Indoor". Array of multiple states, if any of these is met, the action will be shown for characters that fulfill the ActionGuiData rules	
SuppressBuildingEnterBehavior	bool	If set to true the default behavior, that a building UI would open if a character that you have selected enters the building is disabled	false

ActionGUIData

In General ActionGuiData settings have three states:

- -1 = "Don't care" = system won't check for this condition
- 0 = "Must not have" = action will not be available for an actor that satisfies this condition
- 1 = "Must have" = action will be available for an actor that satisfies this condition

Multiple ActionGUIData within the GUIData array of the action template are connected with an logical OR, so if at least one ActionGUIData in the GUIData array is fulfilled the actor will have the action available

Name	Description	Default Value
IsAnythingSelected	checks if any building or character is currently selected	-1

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

IsCharacter IsCharacterSelected	checks if the selected actor is a character	-1
SelectionPlayer	Checks if the selected actor is the leader of the local player family	-1
SelectionOtherFamily	Checks if the selected actor belongs to a family that is not the player's family	-1
SelectionSecretSociety	Checks if the selected actor belongs to a family that is part of a guild	-1
CharacterNearSeller	Checks if the selected character is close to a market or resource provider	-1
CharacterMemberSociety	Checks if the selected character is part of a family that is part of a guild	-1
ContainHostage	Checks if the selected character has at least 1 kidnapped character in it's inventory	-1
FamilyMemberOfOwnSociety	Checks if the selected actor belongs to a family that is part of the same guild as the player's family	-1
CharacterInBuilding	Checks if the selected character is inside any building	-1
CharacterInOwnBuilding	Checks if the selected character is inside a building belonging to the player family	-1
CharacterSleeping	Checks if the selected character is sleeping	-1

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

CharacterUnconscious	Checks if the selected character is unconscious	0
CharacterNearControlledBuilding	Checks if the selected character is close to a player owned building	-1
CharacterNearChurch	Checks if the selected character is close to a church	-1
CharacterIsHome	Checks if the selected character is in his home building	-1
CharacterHasHome	Checks if the selected character has a home building	-1
CharacterIsInHouse	Checks if the selected character is in a residential building	-1
CharacterIsInOneOfHisHouse	Checks if the selected character is in an owned residential building	-1
CharacterIsInForeignHouse	Checks if the selected character is in a residential building that does not belong to his family	-1
CharacterIsInCityBuilding	Checks if the selected character is in city building (public building)	-1
CharacterIsInBusiness	Checks if the selected character is in a business	-1
CharacterIsInOwnBusiness	Checks if the selected character is in an owned business	-1

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

CharacterIsInForeignBusiness	Checks if the selected character is in business that does not belong to his family	-1
CharacterIsInLiaison	Checks if the selected character has an active liaison	-1
CharacterHasASpouse	Checks if the selected character has a spouse	-1
CharacterIsNotInsideBuildingType	Checks if the selected character is not inside a building of a certain target **Exception! Does not take a int value but a string with the building type as variable**	""
SceneAvailable	Checks if the selected character is inside an interior scene	-1
IsWorldScenePlaying	Checks if the selected character is part of an interaction scene	-1
SceneTrialAvailable	Checks if the selected character is part of a trial scene	-1
IsBuilding	Checks if the selected actor is a building	-1
IsBuildingOrInsideBuilding	Checks if the selected actor is a building or a character inside a building	-1
SelectionBusiness	Checks if the selected building is a business	-1
SelectionWarehouse	Checks if the selected building is a warehouse	-1

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

InsideBuildingWithInteriorScene	Check if the selected character is inside a building that offers an interior scene	-1
IsOnBuildingInside	Check if the character is inside a building (doesn't matter if the building has an interior or not)	-1
IsOnBuildingExterior	Check if the character is on the exterior of a building	-1
HasInterior	Check if the selected building has an interior assigned (i.e. the building's template has a valid InteriorName).	-1
IsActiveInterior	Check if the selected building's interior is currently active.	-1
IsInActiveInterior	Check if the selected character is in the currently active interior. Will return true if the character is outside, and no interior is active.	-1
IsMainBuilding	Checks if the selected building is the main building of the local player's family	-1
CharacterHasPoliticalOffice	Checks if the selected character is holding an office position	-1
IsDisposableChildOfLeader	Checks if the selected character is an "unimportant" member of the family. Meaning ● not the leader, ● not the heir, ● not married, ● not holding any office, ● or not applying for any office	-1
BuildingIsDamaged	checks if the selected building is damaged	-1

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

BuildingIsOnFire	checks if the selected building is on fire	-1
FeudWithFamily	Checks if the selected actor's family is in feud with the selector family	-1
AllianceWithFamily	Checks if the selected actor's family is in an alliance with selector family	-1
CanHireHenchmen	Checks if the family of the selected actor has reached their Max Henchmen limit	-1
FamilyHasASecretSociety	Checks if the family of the selected actor is part of a guild	-1
RessourceProducerOrCityBuilding	Checks if a selected building is a Resource Producer or a City building	-1
FamilyMainHouse	Checks if the selected building is the main residence of the dynasty leader	-1
CharacterPrisoner	Checks if a selected character is in jail	-1
HasProfession	Checks if a selected character has a specific profession **Exception! Does not take a int value but a string with the building type as variable**	""
DoesNotHaveProfession	Checks if a selected character does not have a specific profession **Exception! Does not take a int value but a string with the building type as variable**	""
HasFamily	Checks if a selected Actor belongs to a dynasty	-1

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

MinLevel	Checks if a selected character has at least the set level **Exception! Takes INT value, but the int value checks the level against the set value**	-1
BelongsToOwnFamily	Checks if the selected actor belongs to the same dynasty as the player	-1
IsAtEmployer	Checks if the selected character is inside a building and if that building is the building they are employed in	-1
IsControlledByHuman	Checks if the selected actor belongs to a player	-1
IsLeader	Checks if the selected character is the leader of a dynasty	-1
IsHeir	Checks if the selected character is the appointed heir of a dynasty	-1
IsSpouseOfLeader	Checks if the selected character is the spouse of the dynasty leader	-1
IsFamilyMember	Checks if the selected character is a family member of the dynasty they belong to	-1
IsEmployee	Checks if the selected character is an employee	-1
IsTrueBloodline	Checks if the selected character is part of the true bloodline of the family they belong to (aka a descendant or adopted orphan of that family)	-1
MinAge	Checks if the character's age is equal or higher the set age **Exception! Takes INT value, but the int value checks the character age against the set value**	-1

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

IsToddler	Checks if the selected character is below the age at which they start to become controllable	-1
IsChild	Checks if the selected character is above the toddler age but below the grown up age	-1
IsAdult	Checks if the selected character is an adult	-1
UncontrollablyDrunk	Checks if the selected character has the tag that they are uncontrollably drunk	0
IsUnlockedAction	Checks if the selected actor has the action the GUIData checks for unlocked	1
IsIncapacitated	Checks if the selected character is in a state where they are incapacitated	0
IsCharacterOutsideMap	Checks if the selected character is in a state where they are outside of the map	0
Filter	Accepts arbitrary expressions like ResultDefintions do. **Expressions must be entered as a string**. E.g.: Filter = "IsHenchman && ExistsScriptEventWithTag.WarEvent";	""

Illegal Actions/Guarding

Name	Type	Description	Default Value

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

IsImmediatelyKnownByTarget	bool	if set true the victim will always detect the action if • character is not unconscious • building has hat least 1 character guarding it	false
IsAggression	bool	if an action is a physical aggression. Henchmen or lansquenets might interfere with these actions even if they are legal	false
Roaming	bool	If a character goes on patrol when starting a guarding action or if they stay at the assigned spot	false
DetectionRadius	float	Radius around a character executing a guarding action in which the character can detect crimes/aggressive actions	0.0f
GuardingDetectionRules	DetectionRules	Set of rules for characters inside the detction radius to check if a guard should react to them or not	

Sound

Name	Type	Description	Default Value
ConfirmationSoundId	int	id of the sound that should play when the action is assigned to	0 (no sound)

Costs

Name	Type	Description	Default Value
Price	int	Price of the action	0

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

CurrencyType	String	What kind of currency is used to pay for the action, only relevant if Price > 0 ● "Money" ● "Prestige" (influence)	"Money"

Target Selection

Name	Type	Description	Default Value
TargetTags	Array<String>	Array of string values about Tags on a potential target that are relevant for the evaluation of the TargetProfile option "MatchTargetTags"	
DesiredProfiles	Array<DesiredTargetProfiles>	Settings to define if a target is valid or not. Has also range to help AI choose good targets without making them invalid. **For details see DesiredProfiles**	
ThirdPartyActor	String	Define if you want to execute an action where the action results should include two different targets where one will be considered as the "Source" of the target. Good for actions that should change the relationship between 2 families. Can be ● "Family" ● "Character" ● "Building"	
ThirdPartyProfiles	Array<DesiredTargetProfiles>	Same as "DesiredProfiles" but for the ThirdPartyActor	

DesiredProfiles

This is a list of the currently declared properties for selected target validity, that can be used in the .oc scripts. Compatible ones can be combined.

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

TP stands for **TargetProfile,** therefore the full names of the profiles are TargetProfileBuilding, TargetProfileCharacter, TargetProfileFamily, TargetProfileNeighborhood, and TargetProfilePosition.

Property	Type	TPBuilding	TPCharacter	TPFamily	TPNeighborhood	TPPosition	Details
ActiveResidence	boolean	X					
Adult	boolean		X				Character is adult
Boat	boolean		X				Character is a boat
Burning	boolean	X					
Business	boolean	X					
Buyable	boolean	X					
CityBuilding	boolean	X					Building is a city building
CloseToActor	boolean	X	X				
CrimeAware	boolean				X		
DeprecatedBuilding	boolean	X					Building HP are <= 34% of MaxHP
DirectUpperOffice	boolean		X				

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

Property	Type	TPBuilding	TPCharacter	TPFamily	TPNeighborhood	TPPosition	Details
DynastyMember	boolean	X	X				Target Character/Building is of a the same dynasty as the Source Character
Employee	boolean		X				Character is an employee
FightingProwess	boolean		X				
GoodRelationWithMe	boolean			X	X		
Guarded	boolean	X					
Healthy	boolean		X				
Heretic	boolean			X			
HigherOfficeLevel	boolean		X				
Infected	boolean		X		X		
Inhabitated	boolean				X		
Leader	boolean		X				Character is leader of a dynasty
MemberOfSecretSociety	boolean			X			

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

Property	Type	TPBuilding	TPCharacter	TPFamily	TPNeighborhood	TPPosition	Details
NPCGuard	boolean		X				Character is a city guard
NPC	boolean		X				Character does not belong to a family and is not a guard
OfficeHolder	boolean		X				
Open	boolean	X					
OppositeGender	boolean		X				Target Character is of a different gender than Source Character
OtherCity	boolean			X	X		
OutideCityWall	boolean				X		
Poisoned	boolean		X		X		
PoliticalImportance	boolean			X	X		
OnStreet	boolean					X	Target is on a Street
QuarterCity	boolean				X		Neighborhood is of Type City

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

Property	Type	TPBuilding	TPCharacter	TPFamily	TPNeighborhood	TPPosition	Details
QuarterSurrounding	boolean				X		Neighborhood is of Type Surroundings
QuarterVillage	boolean				X		Neighborhood is of Type Village
RessourceProducer	boolean	X					Building is a resource producer
Rich	boolean			X	X		
SocialHigher	boolean			X			
WellGuarded	boolean				X		
MatchTargetTags	boolean	X	X				If true Target has at least on of the tags declared in the TargetTags property. If false Target has none of the tags declared in the TargetTags property

Evaluation Validity

Target profiles are listed in a long array of profiles:

```
DesiredProfiles = array {
  TargetProfileCharacter {
    // First kind of characters accepted
  },
  TargetProfileCharacter {
    // Next kind of characters accepted
  },
```

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

```
  TargetProfileCharacter {
    // Another kind of characters accepted
  },
};
```

At least one of the profiles has to be valid for the target to be considered valid.
As special case, if no profiles are listed, ALL targets are accepted (rather than rejecting all targets).
The validity of an action is evaluated at many different places:

- When picking a target from the game world.
- When a selection list is constructed for picking from a list.
- When automatic target finding is processed, for example through business automation or for the AI players.
- When the action starts.
- During action processing, when certain movement milestones are reached, or the destination is reached.
- When the relationship status (feud/alliance) of a family changes.

The evaluation of these profiles can be affected by setting certain properties on the profiles themselves, selectively enabling and disabling them:

Property	Default Value	Evaluation point	Description
EvaluateByDefault	true	All that have no separate setting provided	By default, this is true, and all other evaluation points are on 'use default', which results in profiles getting evaluated everywhere.
EvaluateWhileInProgress	<no value>	• Any time the action source performs movement validation • When the action source reaches its target • When the relationship status (feud/alliance) of a family changes	This can be used to selectively enable or disable a profile after the action has started.

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

As an example, this is how you can simply disable validation once the action has started:

```
DesiredProfiles = array {
  TargetProfileCharacter {
    // Our profile, which will simply be skipped after the action has started.
    // Since that leaves no profiles, the target will be accepted by default once the action has started successfully.

    EvaluateWhileInProgress = false;
  },
};
```

And here's an example of how to provide a separate profile exclusively for active (running) actions:

```
DesiredProfiles = array {
  TargetProfileCharacter {
    // This profile will be checked at all times, EXCEPT after the action has started.

    EvaluateWhileInProgress = false;
  },
  TargetProfileCharacter {
    // This profile will be checked ONLY when the action is progressing, since EvaluateByDefault is false.

    EvaluateByDefault = false;
    EvaluateWhileInProgress = true;
  },
};
```

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

Results

ActivityResult

Name	Type	Description	Default Value
CriticalFactor	float	Factor that decides at what threshold a dice roll is a critical success/failure • Should be between 0.0f and 1.0f • If dice roll is above CriticalFactor * MaxSourceRoll the roll was a critical success • If the dice roll is below CriticalFactor * -MaxTargetRoll the roll was a critical failure • 1.0f means there are no critical results • 0.0f means there are only critical results	0.8f
BaseRewardXP	float	XP that is rewarded for successful execution of the action, if the action fails only a fraction of the XP will rewarded	0.0f
BaseRewardPrestige	float	Prestige rewarded on successful execution of the action	0.0f
CriticalSuccessResult	ActivityResult	These results get applied when the action finishes with a critical success.	
SuccessResult	ActivityResult	These results get applied when the action finishes with a simple success.	
FailureResult	ActivityResult	These results get applied when the action finishes with a simple failure.	
CriticalFailureResult	ActivityResult	These results get applied when the action finishes with a critical failure.	
DetectedResult	ActivityResult	These results get applied when the action finishes and the source actor was detected by a guard or the victim.	
OnStartResult	ActivityResult	These results get applied when the action starts.	

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

Name	Type	Description	Default Value
OnCancelResult	ActivityResult	These results get applied when the action gets canceled/interrupted (e.g. by a user or by a scene or interaction).	
OnFailResult	ActivityResult	These results get applied when the action fails due to technical reasons (e.g. target is unreachable. NOT when the action finishes but the dice roll determines that the outcome was a failure.).	
OnEndResult	ActivityResult	These results get applied when the action ends for any reason (canceled / failed / finished).	
OnDestinationReachedResult	ActivityResult	These results get applied when a SimpleExecutionAction has reached the target and the interaction starts. It does NOT get applied in actions with custom logic, such as TalkToNeighborhoodAction.	

AI

Name	Type	Description	Default Value

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

AIValues	AIProblemValues	Indicator for the AI on how strongly an action helps to solve it's current problems.
		
		AIValues = AIProblemValues
		
		{
		
		Values = array{Money, Family, RelationWithOtherFamilies, RelationToPublic, Security, Politics};
		
		};
		
		The single values like "Money" are int values, a positive value means it helps solve the problem, a negative value means it makes the problem worse	

ObjectiveWeights	Map<HString, float>	A map of an AI Objective name and a float value. For every AI objective listed in the map, the float value is a weight for how likely the AI will pick this action to solve the objective. Needs to be set for every action that is deemed to help solve one of the possible AI objectives or Map campaigns	

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

MoralAlignment	MoralAlignment	Indicator for how the action affects the morality of the whole dynasty. This is how AI dynasties and the city judges the behavior of a dynasty and also has an impact to what Guilds a dynasty gets invited in to in the late game
		
		There are 3 different Moral Alignment pairs
		
		● Honest/Shady
		● Philantropic/Egoistic
		● Diplomatic/Aggressive
		
		Example:
		
		MoralAlignment = MoralAlignment
		
		{
		
		Values = array{0.090, -0.050, 0.010};
		
		};
		
		This action will increase Honesty by 0.09, increase Egoism by 0.05 and increase Diplomacy by 0.01	

ReturnAndDropAllOnAutomation	bool	If a character should clear their inventory before and after executing an action when it was assigned	

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

		through a building. Set true for all business actions that require inventory space of the character	
IsAIObjective	bool	set false if you don't want AI to be able to execute this action, for example actions that only open a UI element, like the dynasty trade UI	true
IsEssential	bool	If set true, AI has weaker rules for if it is allowed to spent money on it than for non essential actions. Used for everything that helps AI Progress their businesses	false

Animation

Name	Type	Description	Default Value
CustomAnimationPool	Array<CustomAnimationInfo>	Array of animations that can play during the execution of the action. One of the defined will be picked randomly	

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

CustomReceiverAnimationPool	Array<CustomAnimationInfo>	Array of animations that the target of an action can play. Will pick the same index that was picked for CustomAnimationPool to play.	
ArtefactAnimPool	Array<CustomAnimationInfo>	If set, special animation for a defined prop, like throwing a bomb. If none is set but a Prop is defined, the prop will be snapped to the hand of the action source and follow the animation	
ArtefactPropName	String	Name of the prop that can be used during the animation played during action execution	
DestinationPointOfInterestType	String	If set at the target a Point of Interest for neutral citizen NPC will be set that they can go to and cheer at. The defined type will define what kind of animations they will play. POI will be removed when the action finishes. Types:	

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

Special settings

Name	Type	Description	Default Value
ArtefactName	String	Name of the item that will get consumed by executing the action	
MainTemplateName	String	For GoDoReturnAction type actions, set the name of the action after which the character should return home	
NeedSkillToPerform	bool	Used for actions that will award you a building, like build building, buy building, conquer building. Will check if you have the right skill to operate the business if set true	false
ServiceType	String	For Healthcare Services, defines if it is healing, curing diseases, or curing poison can be set to ● "HealService" ● "PoisonService" ● "DiseaseService"	

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

Script Functions

There are two parameters that are inherently available to all functions:

- **ApplyTo = "Target" | "Self" | "Source" | "Context";**
  - This specifies who the function is applied to.
  - Default is Target, and will apply the function to the target of the action or result.
  - Self is the same as Source, and will apply the function to the source of the action or result.
  - Context is context dependent, and can be a family, a third party character, etc...
- **Filter = "<Filter expression>";**
  - This controls if the function gets applied at all.
  - Default is empty, which means no filter, and the function is always applied.
  - If the filter expression returns 0.0 (false), then the function is skipped, otherwise it gets applied.
  - Please see the generic filter page to check how filters work: Filter

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

Function name	Important Properties	Description	Example
FunctionAffectServiceNeeds	**ApplyTo**: if empty will affect all social castes in all neighborhoods **ServiceNeeds**: list of needs that will be affected by this function	Adjust the service needs for the ApplyTo's social caste in its neighborhood	*FunctionAffectServiceNeeds* *{* *ApplyTo = "Self";* *ServiceNeeds = map* *{* *"HealNeed" = 1;* *};* *};*

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

Function name	Important Properties	Description	Example
FunctionAffectNeeds	**ApplyTo**: if empty will affect all social castes in all neighborhoods **ProductType**: need's index (see description) **Amount**: quantity that will be added to the required need **ShouldUseCurrentNeighborhood**: When true, uses the current neighborhood of the actor (where he is standing). Otherwise uses the associated neighborhood of the actor (home neighborhood for NPCs, family neighborhood for characters with a family). Default value is 'false'.	Adjust needs for the **ApplyTo**'s social caste in its neighborhood RawMaterial = 1, Food = 2, WeaponArmor = 3, Clothing = 4, Trinkets = 5, Luxury = 6, Tinctures = 7, Components = 8, Transportation = 9, Livestock = 10,	*FunctionAffectNeeds* *{* *ApplyTo = "Target";* *ProductType = 7;* *Amount = -0.1;* *};*

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

Function name	Important Properties	Description	Example
FunctionApplyResults	**ResultObjectIds**: list of results to apply	Apply each **ResultObjectId** (media\base\guild3\ResultObjectsDefault.oc) to **ApplyTo**	*FunctionApplyResults* *{* *ApplyTo = "Source";* *ResultObjectIds = array{"CharacterKidnapped", "HeirHumiliation"};* *};*

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

FunctionChangeCharacterState	**State**: Which state to switch to. If left empty (default), will switch the character back to a reasonable default state - InDoor if in a building, or Outdoor if not. **Please note that the potential for screwing something up is SIGNIFICANT with this function!**	List of states in game (note that many of them are legacy and don't do anything reasonable): • Outdoor • InDoor • Unconscious • GetUp • Banished • PreCombatAttacker • PreCombatDefender • Combat • PostCombatWinner • PostCombatLoser • PreCrimePerpetrator • InCart • JailJailer • JailPrisoner • PreDuelDefender • PostDuelWinner • InMedievalWoodenSewer • OutsideMap • AssassinationVictim • Executed • Exiled	*FunctionChangeCharacterState {* *ApplyTo = "Source";* *State = "JailPrisoner";* *},*

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

Function name	Important Properties	Description	Example
FunctionCreateLiaisonWithTarget		Start a liaison with the target	*FunctionCreateLiaisonWithTarget {};*
FunctionCreateRomanceWithTarget		Start romance with the target	*FunctionCreateRomanceWithTarget {};*
FunctionDenyTradeProposal		Deny trade proposal (trade proposal must be the context of the function)	*FunctionDenyTradeProposal {};*
FunctionFocusActor		move the camera to **ApplyTo**'s character	*FunctionFocusActor* *{* *ApplyTo = "Source";* *};*
FunctionFocusConversation		Show the context's dialogue	*FunctionFocusConversation{};*

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

Function name	Important Properties	Description	Example
FunctionRemoveForward	**Relation**: (Self, Family, Owner, Guild, Neighborhood, MainBuilding) **ResultObjectId**: (media\base\guild3\ResultObjectsDefault.oc) **RemovePermanentOnEnd**: true/false **RemoveTemporaryOnEnd**: true/false	Remove **ResultObjectId** from **ApplyTo** based on **Relation** (e.g. 'Family' removes it from the family)	*FunctionRemoveForward* *{* *ApplyTo = "Target";* *Relation = "Self";* *ResultObjectId = "OverseeWorkersCritFailure";* *};*
FunctionAddForward	**Relation**: (Self, Family, Owner, Guild, Neighborhood, MainBuilding) **ResultObjectId**: (media\base\guild3\ResultObjectsDefault.oc)	**NOTE: currently not used so no way to know if works properly** Add **ResultObjectId** to **ApplyTo** based on **Relation** (e.g. 'Family' adds it from the family)	*FunctionAddForward* *{* *ApplyTo = "Target";* *Relation = "Self";* *ResultObjectId = "OverseeWorkersCritFailure";* *};*

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

Function name	Important Properties	Description	Example
FunctionGenerateEvidence	**Giver**: perpetrator of the crime **Receiver**: victim **Crimes**: list of crimes to pick from **Amount**: number of evidences to generate (default: 1)	Create **Amount** evidences, **RANDOMLY** selecting among **Crimes**. **Giver** will be the perpetrator while **Receiver** will be the victim. You can name crimes more than once in **Crimes** - the function will then generate evidence for the same crime more than once. **Amount** specifies how many evidences you want. If you set it to 0 (or negative), it will attempt to create evidence for all crimes in the list of crimes.	*FunctionGenerateEvidence* *{* *Giver = "Target";* *Receiver = "Source";* *Crimes = array{"BreakBone", "AttackCharacter", "PickPocket"};* *};*
FunctionGiveBirth	**IsBastard**: true/false	Give birth to a child. If **IsBastard** is true, no other parent is necessary and the child will get a debuff If **IsBastard** is false, the target of the action will be the other parent	*FunctionGiveBirth* *{* *ApplyTo = "Self";* *IsBastard = true;* *};*

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

Function name	Important Properties	Description	Example
FunctionGiveExperience	Amount, IsDiceDependant	Adds given amount of XP to context actor. If **IsDiceDependant** is set to true the amount is multiplied by the positive score. If Actor is a character XP is added directly. If Actor is a Building, XP is added to its owning family leader.	*FunctionGiveExperience* *{* *ApplyTo = "Target";* *Amount = 15;* *};*
FunctionGiveMoney	Amount, IsDiceDependant	Adds given amount of gold to context actor. If **IsDiceDependant** is set to true the amount is multiplied by the positive score.	*FunctionGiveMoney* *{* *ApplyTo = "Self";* *Amount = 250;* *IsDiceDependant = true;* *};*
FunctionKidnapTarget		Kidnapper is the source while the victim is the target	*FunctionKidnapTarget {};*
FunctionKill		Kill **ApplyTo**'s character	*FunctionKill* *{* *ApplyTo = "Source";* *};*

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

Function name	Important Properties	Description	Example
FunctionLookAt	• **`ApplyTo`** - Who is being rotated. • **`Target`** - Who the target of look at is, i.e. who will ApplyTo face.	This will rotate ApplyTo so they face Target. By default, ApplyTo is Target, and Target is set to be Source. That means that if you have e.g. an action that has a character as a target, and you use FunctionLookAt without any further parameters, it will cause the target of the action to look at whoever is performing the action. Similarly, if you use it in a dialogue, then by default it will rotate whoever is being talked to so they face whoever started the dialogue. You can easily switch this around by specifying ApplyTo = "Source" and Target = "Target". If you want both parties to look at each other, use two FunctionLookAt.	*// This will make them face us:* *FunctionLookAt {* *},* *// And this will make us face them:* *FunctionLookAt {* *ApplyTo = "Self";* *Target = "Target";* *},*
FunctionMarryTarget		Marry source with target	*FunctionMarryTarget {};*
FunctionOpenUI	**UIName**: name of the UI to open **ShowOnTop**: true/false **PlaySound**: true/false	Open UIName	*FunctionOpenUI* *{* *UIName = "newQuestsWindow";* *ShowOnTop = true;* *PlaySound = true;* *};*

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

Function name	Important Properties	Description	Example
FunctionPickRandom	**ResultObjectIds**: list of results to randomly select from	Randomly apply a **ResultObjectId**	*FunctionPickRandom* *{* *ResultObjectIds = array{* *"PoisonWellSpreadCold",* *"PoisonWellSpreadLeprosy",* *"PoisonWellSpreadPlague"* *};*
FunctionPlayRandomReaction	**Animations**: list of animation to randomly pick from **VoiceOvers**: list of voice overs to randomly pick from	**ApplyTo** will play random animation and voice over	*FunctionPlayRandomReaction* *{* *ApplyTo = "Target";* *Animations = array { "AcceptPresent", "accept1" };* *VoiceOvers = array {};* *};*
FunctionRegainConsciousness	GetUp: true/false	**NOTE: currently not used so no way to know if works properly** **ApplyTo**'s character regain consciousness and will play the get up animation if GetUp is set to true	*FunctionRegainConsciousness* *{* *GetUp = true;* *};*

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

Function name	Important Properties	Description	Example
FunctionRemoveEffect	MatchAny: true/false Tags: list of effects' tags	Remove **MatchAny** effects with specified **Tags** from ApplyTo. If **MatchAny** is set to **true**, remove every effect that has any of the **Tags**. If **MatchAny** is set to **false**, remove only effects that have all the **Tags**.	*FunctionRemoveEffect* *{* *ApplyTo = "Self";* *MatchAny = true;* *Tags = array {"Poison", "Poisoned"};* *};*
FunctionRemoveTagsFromTradeMarkets	Tags: List of tags to remove	Remove the specified list of tags from all trade markets.	*FunctionRemoveTagsFromTradeMarkets* *{* *Tags = array {"WarEventTarget"};* *};*
FunctionRemoveUnconsciousness		Remove unconsciousness from **ApplyTo**	*FunctionRemoveUnconsciousness* *{* *ApplyTo = "Target";* *};*

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

Function name	Important Properties	Description	Example
FunctionRestore	**ActorValue**: name of the actor value to restore **Value**: float value that indicates the amount of restoration (must be positive)	**NOTE: currently not used so no way to know if works properly** Restore **ActorValue** of **Value** to **ApplyTo**	*FunctionRestore* *{* *ApplyTo = "Target";* *ActorValue = "Health";* *Value = 10.0;* *};*
FunctionSelectActor	**PlaySound**: true/false	Select ApplyTo's character. Play the selection sound if PlaySound is set to true;	*FunctionSelectActor* *{* *PlaySound = false;* *};*

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

Function name	Important Properties	Description	Example
FunctionSendMessage	**Description**: contend of the message **Broadcast:** false (default) to send the message to the target of the function. true to send the message to all players EXCEPT the target of the function.	Send a notification to ApplyTo. Messages' descriptions can be found in: \media\base\guild3\Messages\MessagesContainer.oc	*FunctionSendMessage* *{* *ApplyTo = "Target";* *Description = "CharacterOutlawed";* *};*
FunctionShowDeathUI	**Title**: header of the UI **Body**: content of the UI	Show death UI with Title and Body	*FunctionShowDeathUI* *{* *Title = "$message.FamilyMemberDied.Header";* *Body = "$message.FamilyMemberDied";* *};*
FunctionShowDynastyTradeRequest		Show dynastic trade UI. Note that the context of this function must be a valid trade.	*FunctionShowDynastyTradeRequest {};*
FunctionShowSovereignResult		Show the results of the latest sovereign's election.	*FunctionShowSovereignResult {};*

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

Function name	Important Properties	Description	Example
FunctionShowVoteResults		Show the results of a political power vote. Note: the proposal must be set as the context of the function	*FunctionShowVoteResults {};*

FunctionStartScene	**Scene:** Class name of the scene to start. AdoptionScene, WeddingScene, etc...
	
	Participants: List of participants to inherit from the calling action. This assigns them to their scene slots (which depend on the scene).
	
	InteractionPriority: A value for the interaction priority for this scene. The default is maximum priority (4294967295), but any number between [0, 4294967295] is valid.
	
	FillFailureCombatText: Loca key of a combat text to show if a required scene participant could not be found. If empty, will not show a combat text for this.
	
	StartFailureCombatText: Loca key of a combat text to show if the scene itself couldn't start (for any reason). If empty, will not show a combat text for this.
		Starts the specified scene. You can't just start any scene, the scene has to be specially written to support this. At the time of writing only the AdoptionScene is meant to be started this way, but more are to come.
		
		Participants is a map that assigns an actor reference inherited from the surrounding result or action to a named slot in the scene. Which names are available and have to be filled depends on the action and the scene. An optional bool specifies if the position is required or optional (default is true, the position is required).
		
		InteractionPriority is important for deciding if another scene can steal characters from this scene. Only scenes with HIGHER interaction priorities can steal characters. When in doubt, leave the default, which is maximum priority - no one can steal.
		
		FillFailureCombatText - will show the given combat text if a required scene participant can't be found.
		
		StartFailureCombatText - will show if the scene itself fails to start.
			FunctionStartScene {
			
			Scene = "AdoptionScene";
			
			Participants = map { "Adopter" = ("Source", true), // One entry per position - this will assign the source of the surrounding action to the slot "Adopter" in the scene, and make him required
			
			};
			
			InteractionPriority = 123123; // Just an example. Actual adoption scene uses the default value.
			
			FillFailureCombatText = "$adoption.AdopterBusy"; // Which combat text to show if Adopter is unavailable.
			
			StartFailureCombatText = "$adoption.ChurchNotAvailable"; // Which combat text to show if the scene itself fails, e.g. because the church's priest is busy.
			
			};

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

Function name	Important Properties	Description	Example
FunctionTagEventTradeMarket	Tags: Array of tags to apply to the chosen trade market	Tag a random trade market with the list of tags specified to choose it as an event target	*FunctionTagEventTradeMarket* *{* *Tags = array {"WarEventTarget"};* *};*
FunctionTrackObjectiveProgress	**Amount**: quantity to be added to the current progress **ObjectiveTypename**: objective to track	Increase the **ObjectiveTypename**'s progress by **Amount**	*FunctionTrackObjectiveProgress* *{* *Amount = 12;* *ObjectiveTypename = "IncreaseSecurity";* *};*

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

Function name	Important Properties	Description	Example
FunctionTransferEvidence	Receiver: "Source"/"Target" Giver: "Source"/"Target" IsDiceDependent: true/false CreateEvidenceOfCurrentAction: true/false	Transfer an evidence from Source to Giver. If **CreateEvidenceOfCurrentAction** is set to true and the context's action is illegal, an evidence will be created. if **CreateEvidenceOfCurrentAction** is set to false, a random evidence will be given to Receiver to Giver Note: evidences are not transferred are only copied from source to target.	*FunctionTransferEvidence* *{* *Receiver = "Source";* *Giver = "Target";* *IsDiceDependent = true;* *CreateEvidenceOfCurrentAction = false;* *};*

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

Function name	Important Properties	Description	Example
FunctionTransferItems	Receiver: "Source"/"Target" Giver: "Source"/"Target" MinAmount: min amount to transfer MaxAmount: max amount to transfer SpecificItems: list of items you want to transfer	Transfer a random amount [**MinAmount**, **MaxAmount**] of items from **Giver** to **Receiver**. If **Giver** is not defined, items are generated for the **Receiver**. If Receiver is not defined If **SpecificItems** are defined the items to be transferred will be randomly selected from that list otherwise random items will be taken from **Giver**.	*FunctionTransferItems* *{* *Receiver = "Source";* *Giver = "Target";* *MinAmount = 2;* *MaxAmount = 8;* *SpecificItems = array{"Amber", "Brocade", "Ivory"};* *};*

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

FunctionTransferMoney	**Giver**: "Source"/"Target" **Receiver**: "Source"/"Target" **MaxTransferred**: cap for amount transferred **Amount**: base quantity to transfer, can be a formula too **PercentageOfWealthTaken**: additional percentage of money taken from Giver **IsDiceDependant**: true/false **BudgetPost**: Explicit budget post to use. If empty, will attempt to use the budget post of the context action. If FunctionTransferMoney gets executed from a ResultObject (and not directly from an action), then BudgetPost *must* be explicitly defined. Automatically reading it from the action only works when the FunctionTransferMoney is executed directly from an action. **BudgetPot**: The budget pot to use. Will default to 'Force', forcing transfer of funds. If set to 'FromAction', will use the same budget pot as the context action (if any).	**TransferAmount (Amount + (Giver's MoneyWealth * PercentageOfWealthTaken))** from **Giver** to **Receiver**. If **IsDiceDependant** is true **TransferAmount** is adjusted by positive action score (only if context is an action) The **TransferAmount** transferred will be capped at **MaxTransferred**. If **Giver** is not defined, **Amount** will be given to **Receiver**. If **Receiver** is not defined, **TransferAmount** will be removed from **Giver** directly. **MoneyWealth**: • **NPC**: Wealth defined by NpcWealthMoney (GamePlayDefault.oc) * FractionMoneyCitizen (GamePlayDefault.oc) • **Neutral Building**: MarketValue • **Employee**: FamilyMoney * FractionFamMoneyEmployee(GamePlayDefault.oc) / (Family member + Employee count) • **FamilyMember**: FamilyMoney * FractionFamMoneyMember(GamePlayDefault.oc) / Family member • **FamilyBuilding**: FamilyMoney * FractionFamMoneyBuilding(GamePlayDefault.oc) / Family building count	*FunctionTransferMoney* *{* *Giver = "Target";* *Receiver = "Source";* *MaxTransferred = 1500;* *Amount = 300;* *PercentageOfWealthTaken = 0.15;* *IsDiceDependant = true;* *};* *FunctionTransferMoney* *{* *Giver = "Target";* *Receiver = "Source";* *MaxTransferred = 1500;* *Amount = "750-(100*Source.Luck)";* *PercentageOfWealthTaken = 0.15;* *IsDiceDependant = true;* *};*

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

FunctionTransferPrestige	**Giver**: "Source"/"Target" **Receiver**: "Source"/"Target" **MaxTransferred**: cap for amount transferred **Amount**: base quantity to transfer, can be a formula too **PercentageOfWealthTaken**: additional percentage of money taken from Giver **IsDiceDependant**: true/false	**TransferAmount (Amount + (Giver's PrestigeWealth * PercentageOfWealthTaken))** from **Giver** to **Receiver**. If **IsDiceDependant** is true **TransferAmount** is adjusted by positive action score (only if context is an action) The **TransferAmount** transferred will be capped at **MaxTransferred**. If **Giver** is not defined, **Amount** will be given to **Receiver** directly. If **Receiver** is not defined, **TransferAmount** will be removed from **Giver** directly. Note: **PrestigeGainMult** is taken into consideration **PrestigeWealth**: • **NPC**: Wealth defined by NpcWealthPrestige(GamePlayDefault.oc) * FractionPrestigeCitizen(GamePlayDefault.oc) • **Neutral Building**: 2500 • **Employee**: FamilyPrestige * FractionFamPrestigeEmployee(GamePlayDefault.oc) / (Family member + Employee count) • **FamilyMember**: FamilyPrestige * FractionFamPrestigeMember(GamePlayDefault.oc) / Family member count • **FamilyBuilding**: FamilyMoney * FractionFamPrestigeBuilding(GamePlayDefault.oc) / Family building count	*FunctionTransferPrestige* *{* *Giver = "Target";* *Receiver = "Source";* *Amount = 5;* *MaxTransferred = 1500;* *Amount = 300;* *PercentageOfWealthTaken = 0.15;* *IsDiceDependant = true;* *};* *FunctionTransferPrestige* *{* *Giver = "Target";* *Receiver = "Source";* *Amount = "750-(100*Source.Luck)";* *MaxTransferred = 1500;* *Amount = 300;* *PercentageOfWealthTaken = 0.15;* *IsDiceDependant = true;* *};*

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

FunctionTriggerAction	**Actions**: List of action names, which this function will trigger. Random selection takes place. **CheckSourceProfile**: Check if the action can actually be executed by the actor (bool, default true). **MakeFree**: Make the triggered action free of costs (bool, default false). **ReuseSnappoint**: Reuse the current snap point if it fits the triggered action's target profile, otherwise the actions will need to search for one (bool, default true). **ResumeInterruptedAction**: The triggered action will resume a possibly interrupted action after it has finished (bool, default false). **ActionTarget**: Specifies how the target for the action gets selected. Valid values are: ● **"" (default**): Selects automatically from the context. ● **"Target"**: Selects the context target. ● **"Source"**: Selects the context source. ● **"Context"**: Selects the context actor (aka thirdParty) of the triggering action. ● **"FromTargetProfile"**: Selects a random target based on the target profile.		

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

	ThirdPartyTarget: Specifies what should happen to the third party target if a new target search happens. Valid values are: ● **"" (default)**: Reuses the third party target from the source action even if a new target search happens. ● **"FromThirdPartyProfile"**: Searches a new ThridPartyTarget using the ThirdPartyProfile		

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

FunctionTriggerAction	**ApplyTo**: "Source" ("Self" also works) or "Target" **Actions**: array{"...", "...", ...} of actions to randomly select from **CheckSourceProfile**: true/false **MakeFree**: true/false **ActionTarget**: "" / "Target" / "Source" / "Context" / "FromTargetProfile" / "Target.Workplace" / "Source.Workplace" / "Context.Workplace" **ThirdPartyTarget**: "" / "FromThirdPartyProfile"	**ApplyTo** starts a random action selected from **Actions.** If **CheckSourceProfile** is true (default), will check the action GUI data to see if the source can actually execute the action. If false, will force execute the action even if the source usually can't. If **MakeFree** is false (default) the action will cost its usual price. If the source has insufficient funds, it will fail to start. If true, the action will be free of cost. **ActionTarget**: Specifies how the target for the action gets selected. Valid values are: • "": default, selects automatically from the context. When **ApplyTo** is "Source", it will pick the target of the triggering action. Otherwise it will pick the source. • "Target": selects the context target • "Source": selects the context source • "Context": selects the context actor (aka thirdParty) of the triggering action. For this to work, the FunctionTriggerAction must be executed directly from an action. If it gets executed from a ResultObject for example, it will not work. • "FromTargetProfile": selects a random target based on the target profile of the action • "Target.Workplace": selects the workplace of the target (where the character is employeed). Requires the target to be a character - otherwise it fails and returns null	*FunctionTriggerAction* *{* *ApplyTo = "Source";* *Actions = array{"Drunk"};* *ActionTarget = "FromTargetProfile";* *};*

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

		• "Source.Workplace": selects the workplace of the source • "Context.Workplace": selects the workplace of the context actor (aka thirdParty) **ThirdPartyTarget**: Specifies how the third party target for the triggered action gets determined. Options: • "": default, copies the third party target from the triggering action over to the triggered action. • "FromThirdPartyProfile": Will discard the current third party target when triggering the follow up action, and instead search for a fresh third party target using that action's ThirdPartyProfile.	

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

FunctionUpdateRelationship	AffectTarget AffectTargetFamily AffectTargetAllies AffectTargetEnemies AffectTargetSocietyMembers AffectTargetAlliedSocietyMembers AffectTargetEnemySocietyMembers AffectCurrentNeighborhoodToTarget AffectSource AffectSourceFamily AffectSourceAllies AffectSourceEnemies AffectSourceSocietyMembers AffectSourceAlliedSocietyMembers AffectSourceEnemySocietyMembers AffectCurrentNeighborhoodToSource AffectLiaison	Change relationships' values	*FunctionUpdateRelationship* *{* *AffectTarget = -8;* *AffectTargetFamily = 0;* *AffectTargetAllies = 5;* *AffectTargetEnemies = 2;* *AffectTargetSocietyMembers = 0;* *AffectTargetAlliedSocietyMembers = 0;* *AffectTargetEnemySocietyMembers = 6;* *AffectCurrentNeighborhoodToTarget = -15;* *AffectSource = 0;* *AffectSourceFamily = 0;* *AffectSourceAllies = 0;* *AffectSourceEnemies = 0;* *AffectSourceSocietyMembers = 0;* *AffectSourceAlliedSocietyMembers = 0;* *AffectSourceEnemySocietyMembers = 0;* *AffectCurrentNeighborhoodToSource = 0;* *AffectLiaison = 0;* *},*

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

Function name	Important Properties	Description	Example
FunctionForceBuildingClosure	**Duration**: played game years	forcefully closes targeted building for specified time	*FunctionForceBuildingClosure* *{* *ApplyTo = "Target";* *Duration = 0.25f;* *},*

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

Function name	Important Properties	Description	Example
FunctionUpdateGroupRelationship	**FirstContext:** Source, Target or Context **FirstGroup:** Family/Guild/Religion/Specific Religion/Specific Guild **FirstSet:** Self, Other, All **FirstNeutrals:** true/false **SecondContext:** Source, Target or Context **SecondGroup:** Family/Guild/Religion/Specific Religion/Specific Guild **SecondSet:** Self, Other, All **SecondNeutrals:** true/false **ChangeFormula:** formula to define the relationship change	Searches for families A and B. Adjusts relationships between every family of group A and B. Detailed documentation is can be found on linked sub page.	*FunctionUpdateGroupRelationship* *{* *FirstContext = "Source";* *FirstGroup = "Guild";* *FirstSet = "All";* *FirstNeutrals = true;* *SecondContext = "Target";* *SecondGroup = "Religion";* *SecondSet = "Other";* *SecondNeutrals = false;* *ChangeFormula = "1*SocialLevel";* *},*

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

Function name	Important Properties	Description	Example
FunctionAddUiNotice	• ApplyTo - Used to pick out the player. "All" will broadcast the notice to all players. • NoticeId - The ID of the notice badge (valid IDs at the time of writing: "notice.quests", "notice.chat", "notice.calendar") • Reason - The reason for the notice, a loca key	Adds a reason to the specified Notice badge. The badge will automatically show itself on the screen as long as it has at least one reason to be displayed. Based on the ApplyTo property, the correct family and thereby player will be identified and the notice on their client will be updated. All the reasons are displayed in the tooltip of the notice badge, but they do **NOT** support any placeholders so the texts should be simple. More info here: https://jc.sproing.at/confluence/display/LORDS/Notice+badges	*FunctionAddUiNotice* *{* *ApplyTo = "Target";* *NoticeId = "notice.calendar";* *Reason = "$notice.calendar.newEntry";* *}*
FunctionRemoveUiNotice	• ApplyTo - Used to pick out the player. "All" will broadcast to all players. • NoticeId - The ID of the notice badge • Reason - The reason for the notice, a loca key	Removes one of the reasons from the specified Notice badge. The badge will hide if all reasons are removed. Based on the ApplyTo property, the correct family and thereby player will be identified and the notice on their client will be updated. More info here: https://jc.sproing.at/confluence/display/LORDS/Notice+badges	*FunctionRemoveUiNotice* *{* *ApplyTo = "Self";* *NoticeId = "notice.calendar";* *Reason = "$notice.calendar.newEntry";* *}*

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

Function name	Important Properties	Description	Example

FunctionEndAction	• ApplyTo - Which of the participating actors should have his action ended. You can use this to end the action of your target, if you want.
	• Type - How the action should be ended. Options are:
	  ○ Fail (default) - Will fail the action, refunding costs and so on, just as if an internal condition failed.
	  ○ Cancel - Will cancel the action, as if the owner of the target interrupted it intentionally.
	  ○ Finish - Will immediately finish the action, as if it had run to its end.
		This can be used to prematurely end an action, by either failing, canceling or finishing it. Doing this can in theory lead to strange results, especially when doing it to the target, which might be in a more or less random state.
		This function can't be used to change the outcome of an action. So e.g. you can't put it into the OnFinishResult to change the outcome to a failure, as end processing can't be nested.
			FunctionEndAction
			{
			ApplyTo = "Self";
			Type = "Cancel";
			}

FunctionChainHostage	The function has no parameters. In the context it gets executed, it expects 'source' to be a character and 'target' to be a building.	Transfers all kidnapped characters from the source characters inventory to the target buildings storage.	*FunctionChainHostage{}*

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

Function name	Important Properties	Description	Example

FunctionAddObjective	• ApplyTo - Which of the participating actors should have his action ended. You can use this to end the action of your target, if you want.
	• Objective - Defines the objective to be added.
		Adds a quest objective to the target family/families. The objectives will appear in the quest UI. Objectives can have a duration, but do not need to have one.	*FunctionAddObjective*
			{
			ApplyTo = "All"; // apply to all families
			Objective = G3ObjectiveBase
			{
			ID = "WarObjective";
			ObjectiveName = "$objective.war.name";
			ObjectiveDescription = "$objective.war.desc";
			Duration = 0.5;
			};
			}

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

Function name	Important Properties	Description	Example

FunctionRemoveObjective	• ApplyTo - Which of the participating actors should have his action ended. You can use this to end the action of your target, if you want.
	• ObjectiveID - Defines the ID of objective(s) to be removed.
		Removes quest objective(s) from the target familiy/families. Matches the objective based on the ID.	*FunctionRemoveObjective*
			{
			ApplyTo = "All"; // apply to all families
			ObjectiveID = "WarObjective";
			}

FunctionStopScriptEvent	• Tags - Defines tags that need to be matched by the target ScriptEvent. • MatchAny - When true, a single tag of the ScriptEvent must match the tags of the FunctionStopScriptEvent - otherwise all must match. Default is 'false'. • ApplyEndResults - Indicates if the 'OnEndResult' of the ScriptEvent should get executed. Default is 'true'.	Prematurely ends ScriptEvents from the RandomEventsManager that match the required tags.	*FunctionStopScriptEvent* *{* *Tags = array{ "War" };* *}*

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

Function name	Important Properties	Description	Example

FunctionShowBookOfPrisoners	• ApplyTo - The character who is used as the 'source' for the book of prisoners. This can matter in mode "BribeRelease" where the price of actions can depend on the character who performs the bribe. (See below)
	• Mode - Valid values are "" (default), "BribeRelease"
	  ○ "": only displays the prisoners in the current building
	  ○ "BribeRelease": shows buttons for paying to release prisonsers that belong to the own family
		Opens the Book of Prisoners UI	*FunctionShowBookOfPrisoners*
			{
			ApplyTo = "Source";
			Mode = "BribeRelease";
			}

FunctionReleaseFromJail	• ApplyTo - The character will be released	(Prematurely) releases a character from jail.	*FunctionReleaseFromJail* *{* *ApplyTo = "Context";* *}*

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

Function name	Important Properties	Description	Example
FunctionTransferMoneyToOfficeHolder	• FractionOfActionCost - The fraction of the cost that was paid to start the action. This amount will be transferred. • Office - The name of the office. The politician who holds this office will be recipient of the currency. The office is selected in the current city of the action. • Message - The message that will be sent to the politician. The message can mention the transferred amount via the "%reward%" parameter. Additionally, all usual parameters of FunctionTransferMessage are also available.	Special single use function that transfers part of the action cost to an office holder and sends a notification that lists the transferred amount. This function is used for when releasing a prisoner with a bribe. It is unlikely to be re-usable for other purposes.	*FunctionTransferMoneyToOfficeHolder* *{* *FractionOfActionCost = 0.2;* *Office = "ArsenalMaster";* *Message = "BribeReleasedPrisoner";* *}*

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

FunctionUnlockNobilityTitle	• **`Title`** - Either a value from 1 to 15, which corresponds to one of our 15 nobility titles, or 0. 0 is the default and means "Unlock next higher title".
	• **PriceMultiplier** - Float (default = 1.0). Makes it possible to apply a discount to the price.
	• **`ShowUi`** - Bool (default = true). If true, then the unlocker will get a prompt that asks if they are sure they want to unlock (with a Confirm and Cancel button), or a warning box that informs them that they can't afford the unlock. If false, all UI is suppressed and the title is either unlocked right away, or nothing happens (if they can't afford it).
		This function unlocks the specified nobility title on ApplyTo's dynasty (if they have a dynasty).
		If you specify 0 as title (the default), the function attempts to unlock the next higher title. I.e. if the target's dynasty has title 4 (Resident), then it attempts to unlock 5 (Citizen). If the dynasty is already at the maximum level, nothing happens.
		If you specify an explicit title, then it will try and unlock ALL titles UP TO AND INCLUDING the specified title at once. If e.g. the target's dynasty is at title 4, and you specify 10 (Lord), then it will attempt to unlock 5, 6, 7, 8, 9 and 10 all at once. If the target cannot afford that, then nothing will happen.
		Available titles are:
		1. Serf
		2. Commoner
		3. Yeoman
		4. Resident
		5. Citizen
		6. FreeCitizen
		7. Patrician
		8. Nobleman
		9. Squire
		10. Lord
		11. Baron
		12. Count
			FunctionUnlockNobilityTitle {
			Title = 0; // Next available
			PriceMultiplier = 1.0f; // Make sure they have to pay the full price
			ShowUi = true; // Show any confirmation/warning windows necessary.
			};

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

		13. Marquis 14. Duke 15. Archduke The function also takes care of popping up the nobility title window - it will only show the highest nobility title unlocked, however.	

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved

© 2022-2023 THQ Nordic AB, Sweden. Developed by Purple Lamp, Austria & GolemLabs, Canada. Published by THQ Nordic GmbH, Austria. The Guild & Die Gilde are registered trademarks of THQ Nordic AB, Sweden. All other brands, product names and logos are trademarks or registered trademarks of their respective owners. All rights reserved